

---

**rdflib**

***Release 7.0.0***

**unknown**

**Aug 01, 2023**



## CONTENTS

<b>1</b>	<b>Getting started</b>	<b>3</b>
<b>2</b>	<b>In depth</b>	<b>29</b>
<b>3</b>	<b>Reference</b>	<b>49</b>
<b>4</b>	<b>Versioning</b>	<b>623</b>
<b>5</b>	<b>For developers</b>	<b>625</b>
<b>6</b>	<b>Source Code</b>	<b>643</b>
<b>7</b>	<b>Further help &amp; Contact</b>	<b>645</b>
	<b>Bibliography</b>	<b>647</b>
	<b>Python Module Index</b>	<b>649</b>
	<b>Index</b>	<b>651</b>



RDFLib is a pure Python package for working with [RDF](#). It contains:

- **Parsers & Serializers**
  - for RDF/XML, N3, NTriples, N-Quads, Turtle, TriX, JSON-LD, HexTuples, RDFa and Microdata
- **Store implementations**
  - memory stores
  - persistent, on-disk stores, using databases such as BerkeleyDB
  - remote SPARQL endpoints
- **Graph interface**
  - to a single graph
  - or to multiple Named Graphs within a dataset
- **SPARQL 1.1 implementation**
  - both Queries and Updates are supported

**Caution:** RDFLib is designed to access arbitrary network and file resources, in some cases these are directly requested resources, in other cases they are indirectly referenced resources.

If you are using RDFLib to process untrusted documents or queries you should take measures to restrict file and network access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.



## GETTING STARTED

If you have never used RDFLib, the following will help get you started:

### 1.1 Getting started with RDFLib

#### 1.1.1 Installation

RDFLib is open source and is maintained in a [GitHub](#) repository. RDFLib releases, current and previous, are listed on [PyPi](#)

The best way to install RDFLib is to use `pip` (sudo as required):

```
$ pip install rdflib
```

If you want the latest code to run, clone the main branch of the GitHub repo and use that or you can `pip install` directly from GitHub:

```
$ pip install git+https://github.com/RDFLib/rdflib.git@main#egg=rdflib
```

#### 1.1.2 Support

Usage support is available via questions tagged with `[rdflib]` on [StackOverflow](#) and development support, notifications and detailed discussion through the `rdflib-dev` group (mailing list):

<http://groups.google.com/group/rdflib-dev>

If you notice an bug or want to request an enhancement, please do so via our Issue Tracker in Github:

<http://github.com/RDFLib/rdflib/issues>

#### 1.1.3 How it all works

*The package uses various Python idioms that offer an appropriate way to introduce RDF to a Python programmer who hasn't worked with RDF before.*

The primary interface that RDFLib exposes for working with RDF is a [Graph](#).

RDFLib graphs are un-sorted containers; they have ordinary Python set operations (e.g. `add()` to add a triple) plus methods that search triples and return them in arbitrary order.

RDFLib graphs also redefine certain built-in Python methods in order to behave in a predictable way. They do this by [emulating container types](#) and are best thought of as a set of 3-item tuples (“triples”, in RDF-speak):

```
[
    (subject0, predicate0, object0),
    (subject1, predicate1, object1),
    ...
    (subjectN, predicateN, objectN)
]
```

### 1.1.4 A tiny example

```
from rdflib import Graph

# Create a Graph
g = Graph()

# Parse in an RDF file hosted on the Internet
g.parse("http://www.w3.org/People/Berners-Lee/card")

# Loop through each triple in the graph (subj, pred, obj)
for subj, pred, obj in g:
    # Check if there is at least one triple in the Graph
    if (subj, pred, obj) not in g:
        raise Exception("It better be!")

# Print the number of "triples" in the Graph
print(f"Graph g has {len(g)} statements.")
# Prints: Graph g has 86 statements.

# Print out the entire Graph in the RDF Turtle format
print(g.serialize(format="turtle"))
```

Here a *Graph* is created and then an RDF file online, Tim Berners-Lee's social network details, is parsed into that graph. The `print()` statement uses the `len()` function to count the number of triples in the graph.

### 1.1.5 A more extensive example

```
from rdflib import Graph, Literal, RDF, URIRef
# rdflib knows about quite a few popular namespaces, like W3C ontologies, schema.org etc.
from rdflib.namespace import FOAF, XSD

# Create a Graph
g = Graph()

# Create an RDF URI node to use as the subject for multiple triples
donna = URIRef("http://example.org/donna")

# Add triples using store's add() method.
g.add((donna, RDF.type, FOAF.Person))
g.add((donna, FOAF.nick, Literal("donna", lang="en")))
g.add((donna, FOAF.name, Literal("Donna Fales")))
g.add((donna, FOAF.mbox, URIRef("mailto:donna@example.org")))
```

(continues on next page)



(continued from previous page)

```

# Add another person
ed = URIRef("http://example.org/edward")

# Add triples using store's add() method.
g.add((ed, RDF.type, FOAF.Person))
g.add((ed, FOAF.nick, Literal("ed", datatype=XSD.string)))
g.add((ed, FOAF.name, Literal("Edward Scissorhands")))
g.add((ed, FOAF.mbox, Literal("e.scissorhands@example.org", datatype=XSD.anyURI)))

# Iterate over triples in store and print them out.
print("--- printing raw triples ---")
for s, p, o in g:
    print((s, p, o))

# For each foaf:Person in the store, print out their mbox property's value.
print("--- printing mboxses ---")
for person in g.subjects(RDF.type, FOAF.Person):
    for mbox in g.objects(person, FOAF.mbox):
        print(mbox)

# Bind the FOAF namespace to a prefix for more readable output
g.bind("foaf", FOAF)

# print all the data in the Notation3 format
print("--- printing mboxses ---")
print(g.serialize(format='n3'))

```

### 1.1.6 A SPARQL query example

```

from rdflib import Graph

# Create a Graph, parse in Internet data
g = Graph().parse("http://www.w3.org/People/Berners-Lee/card")

# Query the data in g using SPARQL
# This query returns the 'name' of all ``foaf:Person`` instances
q = """
    PREFIX foaf: <http://xmlns.com/foaf/0.1/>

    SELECT ?name
    WHERE {
        ?p rdf:type foaf:Person .

        ?p foaf:name ?name .
    }
    """

# Apply the query to the graph and iterate through results
for r in g.query(q):

```

(continues on next page)

(continued from previous page)

```
print(r["name"])
# prints: Timothy Berners-Lee
```

## 1.1.7 More examples

There are many more *examples* in the `examples` folder in the source distribution.

## 1.2 Loading and saving RDF

### 1.2.1 Reading RDF files

RDF data can be represented using various syntaxes (`turtle`, `rd/xml`, `n3`, `n-triples`, `trix`, `JSON-LD`, etc.). The simplest format is `ntriples`, which is a triple-per-line format.

Create the file `demo.nt` in the current directory with these two lines in it:

```
<http://example.com/drewp> <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://
→xmlns.com/foaf/0.1/Person> .
<http://example.com/drewp> <http://example.com/says> "Hello World" .
```

On line 1 this file says “drewp is a FOAF Person”. On line 2 it says “drep says “Hello World””.

RDFLib can guess what format the file is by the file ending (“`.nt`” is commonly used for `n-triples`) so you can just use `parse()` to read in the file. If the file had a non-standard RDF file ending, you could set the keyword-parameter `format` to specify either an Internet Media Type or the format name (a *list of available parsers* is available).

In an interactive python interpreter, try this:

```
from rdflib import Graph

g = Graph()
g.parse("demo.nt")

print(len(g))
# prints: 2

import pprint
for stmt in g:
    pprint.pprint(stmt)
# prints:
# (rdflib.term.URIRef('http://example.com/drewp'),
#  rdflib.term.URIRef('http://example.com/says'),
#  rdflib.term.Literal('Hello World'))
# (rdflib.term.URIRef('http://example.com/drewp'),
#  rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#type'),
#  rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Person'))
```

The final lines show how RDFLib represents the two statements in the file: the statements themselves are just length-3 tuples (“triples”) and the subjects, predicates, and objects of the triples are all `rdflib` types.

## 1.2.2 Reading remote RDF

Reading graphs from the Internet is easy:

```
from rdflib import Graph

g = Graph()
g.parse("http://www.w3.org/People/Berners-Lee/card")
print(len(g))
# prints: 86
```

`rdflib.Graph.parse()` can process local files, remote data via a URL, as in this example, or RDF data in a string (using the `data` parameter).

## 1.2.3 Saving RDF

To store a graph in a file, use the `rdflib.Graph.serialize()` function:

```
from rdflib import Graph

g = Graph()
g.parse("http://www.w3.org/People/Berners-Lee/card")
g.serialize(destination="tbl.ttl")
```

This parses data from <http://www.w3.org/People/Berners-Lee/card> and stores it in a file `tbl.ttl` in this directory using the turtle format, which is the default RDF serialization (as of rdflib 6.0.0).

To read the same data and to save it as an RDF/XML format string in the variable `v`, do this:

```
from rdflib import Graph

g = Graph()
g.parse("http://www.w3.org/People/Berners-Lee/card")
v = g.serialize(format="xml")
```

The following table lists the RDF formats you can serialize data to with rdflib, out of the box, and the `format=KEYWORD` keyword used to reference them within `serialize()`:

RDF mat	For-	Keyword	Notes
Turtle		turtle, ttl or turtle2	turtle2 is just turtle with more spacing & linebreaks
RDF/XML		xml or pretty-xml	Was the default format, rdflib < 6.0.0
JSON-LD		json-ld	There are further options for compact syntax and other JSON-LD variants
N-Triples		ntriples, nt or nt11	nt11 is exactly like nt, only utf8 encoded
Notation-3		n3	N3 is a superset of Turtle that also caters for rules and a few other things
Trig		trig	Turtle-like format for RDF triples + context (RDF quads) and thus multiple graphs
Trix		trix	RDF/XML-like format for RDF quads
N-Quads		nquads	N-Triples-like format for RDF quads

## 1.2.4 Working with multi-graphs

To read and query multi-graphs, that is RDF data that is context-aware, you need to use rdflib's *rdflib.ConjunctiveGraph* or *rdflib.Dataset* class. These are extensions to *rdflib.Graph* that know all about quads (triples + graph IDs).

If you had this multi-graph data file (in the `trig` format, using new-style PREFIX statement (not the older `@prefix`):

```
PREFIX eg: <http://example.com/person/>
PREFIX foaf: <http://xmlns.com/foaf/0.1/>

eg:graph-1 {
    eg:drewp a foaf:Person .
    eg:drewp eg:says "Hello World" .
}

eg:graph-2 {
    eg:nick a foaf:Person .
    eg:nick eg:says "Hi World" .
}
```

You could parse the file and query it like this:

```
from rdflib import Dataset
from rdflib.namespace import RDF

g = Dataset()
g.parse("demo.trig")

for s, p, o, g in g.quads((None, RDF.type, None, None)):
    print(s, g)
```

This will print out:

```
http://example.com/person/drewp http://example.com/person/graph-1
http://example.com/person/nick http://example.com/person/graph-2
```

## 1.3 Creating RDF triples

### 1.3.1 Creating Nodes

RDF data is a graph where the nodes are URI references, Blank Nodes or Literals. In RDFS, these node types are represented by the classes *URIRef*, *BNode*, and *Literal*. URIRefs and BNodes can both be thought of as resources, such as a person, a company, a website, etc.

- A *BNode* is a node where the exact URI is not known - usually a node with identity only in relation to other nodes.
- A *URIRef* is a node where the exact URI is known. In addition to representing some subjects and predicates in RDF graphs, URIRefs are always used to represent properties/predicates
- *Literals* represent object values, such as a name, a date, a number, etc. The most common literal values are XML data types, e.g. string, int... but custom types can be declared too

Nodes can be created by the constructors of the node classes:

```

from rdflib import URIRef, BNode, Literal

bob = URIRef("http://example.org/people/Bob")
linda = BNode() # a GUID is generated

name = Literal("Bob") # passing a string
age = Literal(24) # passing a python int
height = Literal(76.5) # passing a python float

```

Literals can be created from Python objects, this creates data-typed literals. For the details on the mapping see *Literals*.

For creating many URIRefs in the same namespace, i.e. URIs with the same prefix, RDFLib has the `rdflib.namespace.Namespace` class

```

from rdflib import Namespace

n = Namespace("http://example.org/people/")

n.bob # == rdflib.term.URIRef("http://example.org/people/bob")
n.eve # == rdflib.term.URIRef("http://example.org/people/eve")

```

This is very useful for schemas where all properties and classes have the same URI prefix. RDFLib defines Namespaces for some common RDF/OWL schemas, including most W3C ones:

```

from rdflib.namespace import CSVW, DC, DCAT, DCTERMS, DOAP, FOAF, ODRL2, ORG, OWL, \
    PROF, PROV, RDF, RDFS, SDO, SH, SKOS, SOSA, SSN, TIME, \
    VOID, XMLNS, XSD

RDF.type
# == rdflib.term.URIRef("http://www.w3.org/1999/02/22-rdf-syntax-ns#type")

FOAF.knows
# == rdflib.term.URIRef("http://xmlns.com/foaf/0.1/knows")

PROF.isProfileOf
# == rdflib.term.URIRef("http://www.w3.org/ns/dx/prof/isProfileOf")

SOSA.Sensor
# == rdflib.term.URIRef("http://www.w3.org/ns/sosa/Sensor")

```

### 1.3.2 Adding Triples to a graph

We already saw in *Loading and saving RDF*, how triples can be added from files and online locations with the `parse()` function.

Triples can also be added within Python code directly, using the `add()` function:

Graph.`add(triple)`

Add a triple with self as context

#### Parameters

- `self` (`TypeVar(_GraphT, bound= Graph)`) –

- **triple** (Tuple[Node, Node, Node]) –

**Return type**`TypeVar(_GraphT, bound= Graph)`

`add()` takes a 3-tuple (a “triple”) of RDFLib nodes. Using the nodes and namespaces we defined previously:

```
from rdflib import Graph, URIRef, Literal, BNode
from rdflib.namespace import FOAF, RDF

g = Graph()
g.bind("foaf", FOAF)

bob = URIRef("http://example.org/people/Bob")
linda = BNode() # a GUID is generated

name = Literal("Bob")
age = Literal(24)

g.add((bob, RDF.type, FOAF.Person))
g.add((bob, FOAF.name, name))
g.add((bob, FOAF.age, age))
g.add((bob, FOAF.knows, linda))
g.add((linda, RDF.type, FOAF.Person))
g.add((linda, FOAF.name, Literal("Linda")))

print(g.serialize())
```

outputs:

```
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .

<http://example.org/people/Bob> a foaf:Person ;
    foaf:age 24 ;
    foaf:knows [ a foaf:Person ;
        foaf:name "Linda" ] ;
    foaf:name "Bob" .
```

For some properties, only one value per resource makes sense (i.e they are *functional properties*, or have a max-cardinality of 1). The `set()` method is useful for this:

```
from rdflib import Graph, URIRef, Literal
from rdflib.namespace import FOAF

g = Graph()
bob = URIRef("http://example.org/people/Bob")

g.add((bob, FOAF.age, Literal(42)))
print(f"Bob is {g.value(bob, FOAF.age)}")
# prints: Bob is 42

g.set((bob, FOAF.age, Literal(43))) # replaces 42 set above
print(f"Bob is now {g.value(bob, FOAF.age)}")
# prints: Bob is now 43
```

`rdflib.graph.Graph.value()` is the matching query method. It will return a single value for a property, optionally raising an exception if there are more.

You can also add triples by combining entire graphs, see *Set Operations on RDFLib Graphs*.

### 1.3.3 Removing Triples

Similarly, triples can be removed by a call to `remove()`:

`Graph.remove(triple)`

Remove a triple from the graph

If the triple does not provide a context attribute, removes the triple from all contexts.

#### Parameters

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **triple** (`Tuple[Optional[Node], Optional[Node], Optional[Node]]`) –

#### Return type

`TypeVar(_GraphT, bound= Graph)`

When removing, it is possible to leave parts of the triple unspecified (i.e. passing `None`), this will remove all matching triples:

```
g.remove((bob, None, None)) # remove all triples about bob
```

### 1.3.4 An example

LiveJournal produces FOAF data for their users, but they seem to use `foaf:member_name` for a person's full name but `foaf:member_name` isn't in FOAF's namespace and perhaps they should have used `foaf:name`

To retrieve some LiveJournal data, add a `foaf:name` for every `foaf:member_name` and then remove the `foaf:member_name` values to ensure the data actually aligns with other FOAF data, we could do this:

```
from rdflib import Graph
from rdflib.namespace import FOAF

g = Graph()
# get the data
g.parse("http://danbri.livejournal.com/data/foaf")

# for every foaf:member_name, add foaf:name and remove foaf:member_name
for s, p, o in g.triples((None, FOAF['member_name'], None)):
    g.add((s, FOAF['name'], o))
    g.remove((s, FOAF['member_name'], o))
```

**Note:** Since rdflib 5.0.0, using `foaf:member_name` is somewhat prevented in RDFlib since FOAF is declared as a `ClosedNamespace()` class instance that has a closed set of members and `foaf:member_name` isn't one of them! If LiveJournal had used RDFlib 5.0.0, an error would have been raised for `foaf:member_name` when the triple was created.

### 1.3.5 Creating Containers & Collections

There are two convenience classes for RDF Containers & Collections which you can use instead of declaring each triple of a Containers or a Collections individually:

- `Container()` (also Bag, Seq & Alt) and
- `Collection()`

See their documentation for how.

## 1.4 Navigating Graphs

An RDF Graph is a set of RDF triples, and we try to mirror exactly this in RDFLib. The Python `Graph()` tries to emulate a container type.

### 1.4.1 Graphs as Iterators

RDFLib graphs override `__iter__()` in order to support iteration over the contained triples:

```
for s, p, o in someGraph:
    if not (s, p, o) in someGraph:
        raise Exception("Iterator / Container Protocols are Broken!!")
```

This loop iterates through all the subjects(s), predicates (p) & objects (o) in `someGraph`.

### 1.4.2 Contains check

Graphs implement `__contains__()`, so you can check if a triple is in a graph with a `triple in graph` syntax:

```
from rdflib import URIRef
from rdflib.namespace import RDF

bob = URIRef("http://example.org/people/bob")
if (bob, RDF.type, FOAF.Person) in graph:
    print("This graph knows that Bob is a person!")
```

Note that this triple does not have to be completely bound:

```
if (bob, None, None) in graph:
    print("This graph contains triples about Bob!")
```



### 1.4.3 Set Operations on RDFLib Graphs

Graphs override several python's operators: `__iadd__()`, `__isub__()`, etc. This supports addition, subtraction and other set-operations on Graphs:

operation	effect
<code>G1 + G2</code>	return new graph with union (triples on both)
<code>G1 += G2</code>	in place union / addition
<code>G1 - G2</code>	return new graph with difference (triples in G1, not in G2)
<code>G1 -= G2</code>	in place difference / subtraction
<code>G1 &amp; G2</code>	intersection (triples in both graphs)
<code>G1 ^ G2</code>	xor (triples in either G1 or G2, but not in both)

**Warning:** Set-operations on graphs assume Blank Nodes are shared between graphs. This may or may not be what you want. See [Merging graphs](#) for details.

### 1.4.4 Basic Triple Matching

Instead of iterating through all triples, RDFLib graphs support basic triple pattern matching with a `triples()` function. This function is a generator of triples that match a pattern given by arguments, i.e. arguments restrict the triples that are returned. Terms that are `None` are treated as a wildcard. For example:

```
g.parse("some_foaf.ttl")
# find all subjects (s) of type (rdf:type) person (foaf:Person)
for s, p, o in g.triples((None, RDF.type, FOAF.Person)):
    print(f"{s} is a person")

# find all subjects of any type
for s, p, o in g.triples((None, RDF.type, None)):
    print(f"{s} is a {o}")

# create a graph
bobgraph = Graph()
# add all triples with subject 'bob'
bobgraph += g.triples((bob, None, None))
```

If you are not interested in whole triples, you can get only the bits you want with the methods `objects()`, `subjects()`, `predicates()`, `predicate_objects()`, etc. Each take parameters for the components of the triple to constraint:

```
for person in g.subjects(RDF.type, FOAF.Person):
    print("{} is a person".format(person))
```

Finally, for some properties, only one value per resource makes sense (i.e they are *functional properties*, or have a max-cardinality of 1). The `value()` method is useful for this, as it returns just a single node, not a generator:

```
# get any name of bob
name = g.value(bob, FOAF.name)
# get the one person that knows bob and raise an exception if more are found
person = g.value(predicate=FOAF.knows, object=bob, any=False)
```

### 1.4.5 Graph methods for accessing triples

Here is a list of all convenience methods for querying Graphs:

Graph.**triples**(*triple*)

Generator over the triple store

Returns triples that match the given triple pattern. If triple pattern does not provide a context, all contexts will be searched.

**Parameters**

**triple** (Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]]) –

**Return type**

Generator[Union[Tuple[Node, Node, Node], Tuple[Node, Path, Node]], None, None]

Graph.**value**(*subject=None, predicate=rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#value'), object=None, default=None, any=True*)

Get a value for a pair of two criteria

Exactly one of subject, predicate, object must be None. Useful if one knows that there may only be one value.

It is one of those situations that occur a lot, hence this ‘macro’ like utility

Parameters: subject, predicate, object – exactly one must be None default – value to be returned if no values found any – if True, return any value in the case there is more than one, else, raise UniquenessError

**Parameters**

- **subject** (Optional[Node]) –
- **predicate** (Optional[Node]) –
- **object** (Optional[Node]) –
- **default** (Optional[Node]) –
- **any** (bool) –

**Return type**

Optional[Node]

Graph.**subjects**(*predicate=None, object=None, unique=False*)

A generator of (optionally unique) subjects with the given predicate and object

**Parameters**

- **predicate** (Union[None, Path, Node]) –
- **object** (Optional[Node]) –
- **unique** (bool) –

**Return type**

Generator[Node, None, None]

Graph.**objects**(*subject=None, predicate=None, unique=False*)

A generator of (optionally unique) objects with the given subject and predicate

**Parameters**

- **subject** (Optional[Node]) –
- **predicate** (Union[None, Path, Node]) –
- **unique** (bool) –

**Return type**`Generator[Node, None, None]``Graph.predicates(subject=None, object=None, unique=False)`

A generator of (optionally unique) predicates with the given subject and object

**Parameters**

- **subject** (`Optional[Node]`) –
- **object** (`Optional[Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Node, None, None]``Graph.subject_objects(predicate=None, unique=False)`

A generator of (optionally unique) (subject, object) tuples for the given predicate

**Parameters**

- **predicate** (`Union[None, Path, Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Tuple[Node, Node], None, None]``Graph.subject_predicates(object=None, unique=False)`

A generator of (optionally unique) (subject, predicate) tuples for the given object

**Parameters**

- **object** (`Optional[Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Tuple[Node, Node], None, None]``Graph.predicate_objects(subject=None, unique=False)`

A generator of (optionally unique) (predicate, object) tuples for the given subject

**Parameters**

- **subject** (`Optional[Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Tuple[Node, Node], None, None]`

## 1.5 Querying with SPARQL

### 1.5.1 Run a Query

The RDFLib comes with an implementation of the [SPARQL 1.1 Query](#) and [SPARQL 1.1 Update](#) query languages.

Queries can be evaluated against a graph with the `rdflib.graph.Graph.query()` method, and updates with `rdflib.graph.Graph.update()`.

The query method returns a `rdflib.query.Result` instance. For SELECT queries, iterating over this returns `rdflib.query.ResultRow` instances, each containing a set of variable bindings. For CONSTRUCT/DESCRIBE queries, iterating over the result object gives the triples. For ASK queries, iterating will yield the single boolean answer, or evaluating the result object in a boolean-context (i.e. `bool(result)`)

For example...

```
import rdflib
g = rdflib.Graph()
g.parse("http://danbri.org/foaf.rdf#")

knows_query = """
SELECT DISTINCT ?aname ?bname
WHERE {
    ?a foaf:knows ?b .
    ?a foaf:name ?aname .
    ?b foaf:name ?bname .
}"""

qres = g.query(knows_query)
for row in qres:
    print(f"{row.aname} knows {row.bname}")
```

The results are tuples of values in the same order as your SELECT arguments. Alternatively, the values can be accessed by variable name, either as attributes, or as items, e.g. `row.b` and `row["b"]` are equivalent. The above, given the appropriate data, would print something like:

```
Timothy Berners-Lee knows Edd Dumbill
Timothy Berners-Lee knows Jennifer Golbeck
Timothy Berners-Lee knows Nicholas Gibbins
...
```

As an alternative to using SPARQLs PREFIX, namespace bindings can be passed in with the `initNs` kwarg, see [Namespaces and Bindings](#).

Variables can also be pre-bound, using the `initBindings` kwarg which can pass in a dict of initial bindings. This is particularly useful for prepared queries, as described below.

## 1.5.2 Update Queries

Update queries are performed just like reading queries but using the `rdflib.graph.Graph.update()` method. An example:

```
from rdflib import Graph

# Create a Graph, add in some test data
g = Graph()
g.parse(
    data="""
        <x:> a <c:> .
        <y:> a <c:> .
    """,
    format="turtle"
)
```

(continues on next page)

(continued from previous page)

```

# Select all the things (s) that are of type (rdf:type) c:
qres = g.query("""SELECT ?s WHERE { ?s a <c:> }""")

for row in qres:
    print(f"{row.s}")
# prints:
# x:
# y:

# Add in a new triple using SPARQL UPDATE
g.update("""INSERT DATA { <z:> a <c:> }""")

# Select all the things (s) that are of type (rdf:type) c:
qres = g.query("""SELECT ?s WHERE { ?s a <c:> }""")

print("After update:")
for row in qres:
    print(f"{row.s}")
# prints:
# x:
# y:
# z:

# Change type of <y:> from <c:> to <d:>
g.update("""
    DELETE { <y:> a <c:> }
    INSERT { <y:> a <d:> }
    WHERE { <y:> a <c:> }
""")

print("After second update:")
qres = g.query("""SELECT ?s ?o WHERE { ?s a ?o }""")
for row in qres:
    print(f"{row.s} a {row.o}")
# prints:
# x: a c:
# z: a c:
# y: a d:

```

### 1.5.3 Querying a Remote Service

The SERVICE keyword of SPARQL 1.1 can send a query to a remote SPARQL endpoint.

```

import rdflib

g = rdflib.Graph()
qres = g.query(
    """
    SELECT ?s
    WHERE {
        SERVICE <https://dbpedia.org/sparql> {

```

(continues on next page)

(continued from previous page)

```

        ?s a ?o .
    }
}
LIMIT 3
"""
)

for row in qres:
    print(row.s)

```

This example sends a query to [DBpedia's SPARQL endpoint service](#) so that it can run the query and then send back the result:

```

<http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://www.openlinksw.com/schemas/
↳ virtcxml#FacetCategoryPattern>
<http://www.w3.org/2001/XMLSchema#anyURI> <http://www.w3.org/2000/01/rdf-schema#Datatype>
<http://www.w3.org/2001/XMLSchema#anyURI> <http://www.w3.org/2000/01/rdf-schema#Datatype>

```

### 1.5.4 Prepared Queries

RDFLib lets you *prepare* queries before execution, this saves re-parsing and translating the query into SPARQL Algebra each time.

The method `rdflib.plugins.sparql.prepareQuery()` takes a query as a string and will return a `rdflib.plugins.sparql.sparql.Query` object. This can then be passed to the `rdflib.graph.Graph.query()` method.

The `initBindings` kwarg can be used to pass in a dict of initial bindings:

```

q = prepareQuery(
    "SELECT ?s WHERE { ?person foaf:knows ?s .}",
    initNs = { "foaf": FOAF }
)

g = rdflib.Graph()
g.parse("foaf.rdf")

tim = rdflib.URIRef("http://www.w3.org/People/Berners-Lee/card#i")

for row in g.query(q, initBindings={'person': tim}):
    print(row)

```

### 1.5.5 Custom Evaluation Functions

For experts, it is possible to override how bits of SPARQL algebra are evaluated. By using the `setuptools` entry-point `rdf.plugins.sparqlevel`, or simply adding to an entry to `rdflib.plugins.sparql.CUSTOM_EVALS`, a custom function can be registered. The function will be called for each algebra component and may raise `NotImplementedError` to indicate that this part should be handled by the default implementation.

See `examples/custom_eval.py`

## 1.6 Utilities & convenience functions

For RDF programming, RDFLib and Python may not be the fastest tools, but we try hard to make them the easiest and most convenient to use and thus the *fastest* overall!

This is a collection of hints and pointers for hassle-free RDF coding.

### 1.6.1 Functional properties

Use `value()` and `set()` to work with *functional property* instances, i.e. properties than can only occur once for a resource.

```
from rdflib import Graph, URIRef, Literal, BNode
from rdflib.namespace import FOAF, RDF

g = Graph()
g.bind("foaf", FOAF)

# Add demo data
bob = URIRef("http://example.org/people/Bob")
g.add((bob, RDF.type, FOAF.Person))
g.add((bob, FOAF.name, Literal("Bob")))
g.add((bob, FOAF.age, Literal(38)))

# To get a single value, use 'value'
print(g.value(bob, FOAF.age))
# prints: 38

# To change a single of value, use 'set'
g.set((bob, FOAF.age, Literal(39)))
print(g.value(bob, FOAF.age))
# prints: 39
```

### 1.6.2 Slicing graphs

Python allows slicing arrays with a slice object, a triple of start, stop and step-size:

```
for i in range(20)[2:9:3]:
    print(i)
# prints:
# 2, 5, 8
```

RDFLib graphs override `__getitem__` and we pervert the slice triple to be a RDF triple instead. This lets slice syntax be a shortcut for `triples()`, `subject_predicates()`, `__contains__()`, and other Graph query-methods:

```
from rdflib import Graph, URIRef, Literal, BNode
from rdflib.namespace import FOAF, RDF

g = Graph()
g.bind("foaf", FOAF)
```

(continues on next page)

(continued from previous page)

```
# Add demo data
bob = URIRef("http://example.org/people/Bob")
bill = URIRef("http://example.org/people/Bill")
g.add((bob, RDF.type, FOAF.Person))
g.add((bob, FOAF.name, Literal("Bob")))
g.add((bob, FOAF.age, Literal(38)))
g.add((bob, FOAF.knows, bill))

print(g[:])
# same as
print(iter(g))

print(g[bob])
# same as
print(g.predicate_objects(bob))

print(g[bob: FOAF.knows])
# same as
print(g.objects(bob, FOAF.knows))

print(g[bob: FOAF.knows: bill])
# same as
print((bob, FOAF.knows, bill) in g)

print(g[:FOAF.knows])
# same as
print(g.subject_objects(FOAF.knows))
```

See [examples.slice](#) for a complete example.

---

**Note:** Slicing is convenient for run-once scripts for playing around in the Python REPL, however since slicing returns tuples of varying length depending on which parts of the slice are bound, you should be careful using it in more complicated programs. If you pass in variables, and they are `None` or `False`, you may suddenly get a generator of different length tuples back than you expect.

---

### 1.6.3 SPARQL Paths

SPARQL property paths are possible using overridden operators on URIRefs. See [examples.foafpaths](#) and [rdflib.paths](#).



### 1.6.4 Serializing a single term to N3

For simple output, or simple serialisation, you often want a nice readable representation of a term. All terms (URIRef, Literal etc.) have a `n3` method, which will return a suitable N3 format:

```
from rdflib import Graph, URIRef, Literal
from rdflib.namespace import FOAF

# A URIRef
person = URIRef("http://xmlns.com/foaf/0.1/Person")
print(person.n3())
# prints: <http://xmlns.com/foaf/0.1/Person>

# Simplifying the output with a namespace prefix:
g = Graph()
g.bind("foaf", FOAF)

print(person.n3(g.namespace_manager))
# prints foaf:Person

# A typed literal
l = Literal(2)
print(l.n3())
# prints "2"^^<http://www.w3.org/2001/XMLSchema#integer>

# Simplifying the output with a namespace prefix
# XSD is built in, so no need to bind() it!
l.n3(g.namespace_manager)
# prints: "2"^^xsd:integer
```

### 1.6.5 Parsing data from a string

You can parse data from a string with the `data` param:

```
from rdflib import Graph

g = Graph().parse(data="<a:> <p:> <p:>.")
for r in g.triples((None, None, None)):
    print(r)
# prints: (rdflib.term.URIRef('a:'), rdflib.term.URIRef('p:'), rdflib.term.URIRef('p:'))
```

### 1.6.6 Command Line tools

RDFLib includes a handful of commandline tools, see [rdflib.tools](#).

## 1.7 examples Package

These examples all live in `./examples` in the source-distribution of RDFLib.

### 1.7.1 conjunctive\_graphs Module

An RDFLib `ConjunctiveGraph` is an (unnamed) aggregation of all the `Named Graphs` within a `Store`. The `get_context()` method can be used to get a particular named graph for use, such as to add triples to, or the default graph can be used.

This example shows how to create `Named Graphs` and work with the conjunction (union) of all the graphs.

### 1.7.2 custom\_datatype Module

RDFLib can map between RDF data-typed literals and Python objects.

Mapping for integers, floats, `dateTimes`, etc. are already added, but you can also add your own.

This example shows how `rdflib.term.bind()` lets you register new mappings between literal datatypes and Python objects

### 1.7.3 custom\_eval Module

This example shows how a custom evaluation function can be added to handle certain SPARQL Algebra elements.

A custom function is added that adds `rdfs:subClassOf` “inference” when asking for `rdf:type` triples.

Here the custom eval function is added manually, normally you would use `setuptools` and `entry_points` to do it: i.e. in your `setup.py`:

```
entry_points = {
    'rdf.plugins.sparqleval': [
        'myfunc = mypackage:MyFunction',
    ],
}
```

`examples.custom_eval.customEval(ctx, part)`

Rewrite triple patterns to get super-classes

### 1.7.4 foafpaths Module

SPARQL 1.1 defines path operators for combining/repeating predicates in triple-patterns.

We overload some Python operators on `URIRefs` to allow creating path operators directly in Python.

Operator	Path
<code>p1 / p2</code>	Path sequence
<code>p1   p2</code>	Path alternative
<code>p1 * '*'</code>	chain of 0 or more p's
<code>p1 * '+'</code>	chain of 1 or more p's
<code>p1 * '?'</code>	0 or 1 p
<code>~p1</code>	p1 inverted, i.e. (s p1 o) <=> (o ~p1 s)
<code>-p1</code>	NOT p1, i.e. any property but p1

These can then be used in property position for `s,p,o` triple queries for any graph method.

See the docs for [rdflib.paths](#) for the details.

This example shows how to get the name of friends (i.e values two steps away x knows y, y name z) with a single query.

### 1.7.5 prepared\_query Module

SPARQL Queries be prepared (i.e parsed and translated to SPARQL algebra) by the [rdflib.plugins.sparql.prepareQuery\(\)](#) method.

`initNs` can be used instead of PREFIX values.

When executing, variables can be bound with the `initBindings` keyword parameter.

### 1.7.6 resource\_example Module

RDFLib has a [Resource](#) class, for a resource-centric API. The [Graph](#) class also has a `resource` function that can be used to create resources and manipulate them by quickly adding or querying for triples where this resource is the subject.

This example shows `g.resource()` in action.

### 1.7.7 berkeleydb\_example Module

BerkeleyDB in use as a persistent Graph store.

Example 1: simple actions

- creating a ConjunctiveGraph using the BerkeleyDB Store
- adding triples to it
- counting them
- closing the store, emptying the graph
- re-opening the store using the same DB files
- getting the same count of triples as before

Example 2: larger data

- loads multiple graphs downloaded from GitHub into a BerkeleyDB-baked graph stored in the folder `gsq_vocabs`.
- does not delete the DB at the end so you can see it on disk

`examples.berkeleydb_example.example_1()`

Creates a ConjunctiveGraph and performs some BerkeleyDB tasks with it

`examples.berkeleydb_example.example_2()`

Loads a number of SKOS vocabularies from GitHub into a BerkeleyDB-backed graph stored in the local folder 'gsq\_vocabs'

**Should print out the number of triples after each load, e.g.:**

177 248 289 379 421 628 764 813 965 1381 9666 9719 ...

### 1.7.8 slice Module

RDFLib Graphs (and Resources) can be “sliced” with [] syntax

This is a short-hand for iterating over triples.

Combined with SPARQL paths (see `foafpaths.py`) - quite complex queries can be realised.

See `rdflib.graph.Graph.__getitem__()` for details

### 1.7.9 smushing Module

A FOAF smushing example.

Filter a graph by normalizing all `foaf:Persons` into URIs based on their `mbox_sha1sum`.

Suppose I get two [FOAF](#) documents each talking about the same person (according to `mbox_sha1sum`) but they each used a `rdflib.term.BNode` for the subject. For this demo I’ve combined those two documents into one file:

This filters a graph by changing every subject with a `foaf:mbox_sha1sum` into a new subject whose URI is based on the `sha1sum`. This new graph might be easier to do some operations on.

An advantage of this approach over other methods for collapsing BNodes is that I can incrementally process new FOAF documents as they come in without having to access my ever-growing archive. Even if another `65b983bb397fb71849da910996741752ace8369b` document comes in next year, I would still give it the same stable subject URI that merges with my existing data.

### 1.7.10 sparql\_query\_example Module

SPARQL Query using `rdflib.graph.Graph.query()`

The method returns a `Result`, iterating over this yields `ResultRow` objects

The variable bindings can be accessed as attributes of the row objects For variable names that are not valid python identifiers, dict access (i.e. with `row[var]` / `__getitem__`) is also possible.

`vars` contains the variables

### 1.7.11 sparql\_update\_example Module

SPARQL Update statements can be applied with `rdflib.graph.Graph.update()`

### 1.7.12 sparqlstore\_example Module

Simple examples showing how to use the SPARQLStore

### 1.7.13 swap\_primer Module

This is a simple primer using some of the example stuff in the Primer on N3:

<http://www.w3.org/2000/10/swap/Primer>

### 1.7.14 transitive Module

An example illustrating how to use the `transitive_subjects()` and `transitive_objects()` graph methods

#### Formal definition

The `transitive_objects()` method finds all nodes such that there is a path from subject to one of those nodes using only the predicate property in the triples. The `transitive_subjects()` method is similar; it finds all nodes such that there is a path from the node to the object using only the predicate property.

#### Informal description, with an example

In brief, `transitive_objects()` walks forward in a graph using a particular property, and `transitive_subjects()` walks backward. A good example uses a property `ex:parent`, the semantics of which are biological parentage. The `transitive_objects()` method would get all the ancestors of a particular person (all nodes such that there is a parent path between the person and the object). The `transitive_subjects()` method would get all the descendants of a particular person (all nodes such that there is a parent path between the node and the person). So, say that your URI is `ex:person`.

This example would get all of your (known) ancestors, and then get all the (known) descendants of your maternal grandmother.

**Warning:** The `transitive_objects()` method has the start node as the *first* argument, but the `transitive_subjects()` method has the start node as the *second* argument.

#### User-defined transitive closures

The method `transitiveClosure()` returns transitive closures of user-defined functions.

### 1.7.15 secure\_with\_audit Module

This example demonstrates how to use [Python audit hooks](#) to block access to files and URLs.

It installs an audit hook with `sys.addaudithook` that blocks access to files and URLs that end with `blocked.jsonld`.

The code in the example then verifies that the audit hook is blocking access to URLs and files as expected.

`examples.secure_with_audit.audit_hook(name, args)`

An audit hook that blocks access when an attempt is made to open a file or URL that ends with `blocked.jsonld`.

Details of the audit events can be seen in the [audit events table](#).

#### Parameters

- **name** (`str`) – The name of the audit event.
- **args** (`Tuple[Any, ...]`) – The arguments of the audit event.

#### Return type

`None`

#### Returns

`None` if the audit hook does not block access.

#### Raises

[PermissionError](#) – If the file or URL being accessed ends with `blocked.jsonld`.

`examples.secure_with_audit.main()`

The main code of the example.

The important steps are: `rtype: None`

- Install a custom audit hook that blocks some URLs and files.
- Attempt to parse a JSON-LD document that will result in a blocked URL being accessed.
- Verify that the audit hook blocked access to the URL.
- Attempt to parse a JSON-LD document that will result in a blocked file being accessed.
- Verify that the audit hook blocked access to the file.

### 1.7.16 secure\_with\_urlopen Module

This example demonstrates how to use a custom global URL opener installed with `urllib.request.install_opener` to block access to URLs.

`class examples.secure_with_urlopen.SecuredHTTPHandler(debuglevel=0)`

Bases: `HTTPHandler`

A HTTP handler that blocks access to URLs that end with “blocked.jsonld”.

`__module__ = 'examples.secure_with_urlopen'`

`http_open(req)`

Block access to URLs that end with “blocked.jsonld”.

#### Parameters

**req** (`Request`) – The request to open.

#### Return type

`HTTPResponse`

**Returns**

The response.

**Raises**

**PermissionError** – If the URL ends with “blocked.jsonld”.

`examples.secure_with_urlopen.main()`

The main code of the example.

The important steps are: :rtype: **None**

- Install a custom global URL opener that blocks some URLs.
- Attempt to parse a JSON-LD document that will result in a blocked URL being accessed.
- Verify that the URL opener blocked access to the URL.





If you are familiar with RDF and are looking for details on how RDFLib handles it, these are for you:

## 2.1 RDF terms in rdflib

Terms are the kinds of objects that can appear in a RDFLib's graph's triples. Those that are part of core RDF concepts are: `IRIs`, `Blank Node` and `Literal`, the latter consisting of a literal value and either a `datatype` or an [RFC 3066](#) language tag.

---

**Note:** RDFLib's class for representing IRIs/URIs is called “`URIRef`” because, at the time it was implemented, that was what the then current RDF specification called URIs/IRIs. We preserve that class name but refer to the RDF object as “`IRI`”.

---

### 2.1.1 Class hierarchy

All terms in RDFLib are sub-classes of the `rdflib.term.Identifier` class. A class diagram of the various terms is:

Fig. 1: Term Class Hierarchy

Nodes are a subset of the Terms that underlying stores actually persist.

The set of such Terms depends on whether or not the store is formula-aware. Stores that aren't formula-aware only persist those terms core to the RDF Model but those that are formula-aware also persist the N3 extensions. However, utility terms that only serve the purpose of matching nodes by term-patterns will probably only be terms and not nodes.

### 2.1.2 Python Classes

The three main RDF objects - *IRI*, *Blank Node* and *Literal* are represented in RDFLib by these three main Python classes:

## URIRef

An IRI (Internationalized Resource Identifier) is represented within RDFLib using the `URIRef` class. From [the RDF 1.1 specification's IRI section](#):

Here is the `URIRef` class' auto-built documentation:

```
class rdflib.term.URIRef(value: str, base: str | None = None)
```

RDF 1.1's IRI Section <https://www.w3.org/TR/rdf11-concepts/#section-IRIs>

---

**Note:** Documentation on RDF outside of RDFLib uses the term IRI or URI whereas this class is called `URIRef`. This is because it was made when the first version of the RDF specification was current, and it used the term *URIRef*, see [RDF 1.0 URIRef](#)

---

An IRI (Internationalized Resource Identifier) within an RDF graph is a Unicode string that conforms to the syntax defined in RFC 3987.

IRIs in the RDF abstract syntax **MUST** be absolute, and **MAY** contain a fragment identifier.

IRIs are a generalization of URIs [RFC3986] that permits a wider range of Unicode characters.

```
>>> from rdflib import URIRef
>>> uri = URIRef()
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: __new__() missing 1 required positional argument: 'value'
>>> uri = URIRef('')
>>> uri
rdflib.term.URIRef('')
>>> uri = URIRef('http://example.com')
>>> uri
rdflib.term.URIRef('http://example.com')
>>> uri.n3()
'<http://example.com>'
```

## BNodes

In RDF, a blank node (also called `BNode`) is a node in an RDF graph representing a resource for which an IRI or literal is not given. The resource represented by a blank node is also called an anonymous resource. According to the RDF standard, a blank node can only be used as subject or object in a triple, although in some syntaxes like Notation 3 it is acceptable to use a blank node as a predicate. If a blank node has a node ID (not all blank nodes are labelled in all RDF serializations), it is limited in scope to a particular serialization of the RDF graph, i.e. the node `p1` in one graph does not represent the same node as a node named `p1` in any other graph – [wikipedia](#)

Here is the `BNode` class' auto-built documentation:

```
class rdflib.term.BNode(value: str | None = None, _sn_gen: ~typing.Callable[[], str] = <function
    _serial_number_generator._generator>, _prefix: str = 'N')
```

RDF 1.1's Blank Nodes Section: <https://www.w3.org/TR/rdf11-concepts/#section-blank-nodes>

Blank Nodes are local identifiers for unnamed nodes in RDF graphs that are used in some concrete RDF syntaxes or RDF store implementations. They are always locally scoped to the file or RDF store, and are not persistent or portable identifiers for blank nodes. The identifiers for Blank Nodes are not part of the RDF abstract syntax, but are entirely dependent on particular concrete syntax or implementation (such as Turtle, JSON-LD).

—

RDFLib's `BNode` class makes unique IDs for all the Blank Nodes in a Graph but you should *never* expect, or reply on, BNodes' IDs to match across graphs, or even for multiple copies of the same graph, if they are regenerated from some non-RDFLib source, such as loading from RDF data.

```
>>> from rdflib import BNode
>>> bn = BNode()
>>> bn
rdflib.term.BNode('AFwALAKU0')
>>> bn.n3()
'_:AFwALAKU0'
```

## Literals

Literals are attribute values in RDF, for instance, a person's name, the date of birth, height, etc. and are stored using simple data types, e.g. *string*, *double*, *dateTime* etc. This usually looks something like this:

```
name = Literal("Nicholas") # the name 'Nicholas', as a string
age = Literal(39, datatype=XSD.integer) # the number 39, as an integer
```

A slightly special case is a *langString* which is a *string* with a language tag, e.g.:

```
name = Literal("Nicholas", lang="en") # the name 'Nicholas', as an English string
imie = Literal("Mikołaj", lang="pl") # the Polish version of the name 'Nicholas'
```

Special literal types indicated by use of a custom IRI for a literal's *datatype* value, for example the GeoSPARQL RDF standard invents a custom datatype, `geoJSONLiteral` to indicate GeoJSON geometry serializations like this:

```
GEO = Namespace("http://www.opengis.net/ont/geosparql#")

geojson_geometry = Literal(
    '{"type": "Point", "coordinates": [-83.38, 33.95]}' ,
    datatype=GEO.geoJSONLiteral
```

Here is the `Literal` class' auto-built documentation, followed by notes on `Literal` from the [RDF 1.1 specification](#) 'Literals' section.

```
class rdflib.term.Literal(lexical_or_value: Any, lang: str | None = None, datatype: str | None = None,
                        normalize: bool | None = None)
```

RDF 1.1's Literals Section: <http://www.w3.org/TR/rdf-concepts/#section-Graph-Literal>

Literals are used for values such as strings, numbers, and dates.

A literal in an RDF graph consists of two or three elements:

- a lexical form, being a Unicode string, which SHOULD be in Normal Form C
- a datatype IRI, being an IRI identifying a datatype that determines how the lexical form maps to a literal value, and
- if and only if the datatype IRI is <http://www.w3.org/1999/02/22-rdf-syntax-ns#langString>, a non-empty language tag. The language tag MUST be well-formed according to section 2.2.9 of [Tags for identifying languages](#).

A literal is a language-tagged string if the third element is present. Lexical representations of language tags MAY be converted to lower case. The value space of language tags is always in lower case.

For valid XSD datatypes, the lexical form is optionally normalized at construction time. Default behaviour is set by `rdflib.NORMALIZE_LITERALS` and can be overridden by the `normalize` parameter to `__new__`

Equality and hashing of Literals are done based on the lexical form, i.e.:

```
>>> from rdflib.namespace import XSD
```

```
>>> Literal('01') != Literal('1') # clear - strings differ
True
```

but with data-type they get normalized:

```
>>> Literal('01', datatype=XSD.integer) != Literal('1', datatype=XSD.integer)
False
```

unless disabled:

```
>>> Literal('01', datatype=XSD.integer, normalize=False) != Literal('1',
↳datatype=XSD.integer)
True
```

Value based comparison is possible:

```
>>> Literal('01', datatype=XSD.integer).eq(Literal('1', datatype=XSD.float))
True
```

The `eq` method also provides limited support for basic python types:

```
>>> Literal(1).eq(1) # fine - int compatible with xsd:integer
True
>>> Literal('a').eq('b') # fine - str compatible with plain-lit
False
>>> Literal('a', datatype=XSD.string).eq('a') # fine - str compatible with
↳xsd:string
True
>>> Literal('a').eq(1) # not fine, int incompatible with plain-lit
NotImplemented
```

Greater-than/less-than ordering comparisons are also done in value space, when compatible datatypes are used. Incompatible datatypes are ordered by DT, or by lang-tag. For other nodes the ordering is `None < BNode < URIRef < Literal`

Any comparison with non-rdflib Node are “NotImplemented” In PY3 this is an error.

```
>>> from rdflib import Literal, XSD
>>> lit2006 = Literal('2006-01-01',datatype=XSD.date)
>>> lit2006.toPython()
datetime.date(2006, 1, 1)
>>> lit2006 < Literal('2007-01-01',datatype=XSD.date)
True
>>> Literal(datetime.utcnow()).datatype
```

(continues on next page)

(continued from previous page)

```

rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dateTime')
>>> Literal(1) > Literal(2) # by value
False
>>> Literal(1) > Literal(2.0) # by value
False
>>> Literal('1') > Literal(1) # by DT
True
>>> Literal('1') < Literal('1') # by lexical form
False
>>> Literal('a', lang='en') > Literal('a', lang='fr') # by lang-tag
False
>>> Literal(1) > URIRef('foo') # by node-type
True

```

The `>` `<` operators will eat this `NotImplemented` and throw a `TypeError` (py3k):

```

>>> Literal(1).__gt__(2.0)
NotImplemented

```

A literal in an RDF graph contains one or two named components.

All literals have a lexical form being a Unicode string, which SHOULD be in Normal Form C.

Plain literals have a lexical form and optionally a language tag as defined by [RFC 3066](#), normalized to lowercase. An exception will be raised if illegal language-tags are passed to `rdflib.term.Literal.__new__()`.

Typed literals have a lexical form and a datatype URI being an RDF URI reference.

---

**Note:** When using the language tag, care must be taken not to confuse language with locale. The language tag relates only to human language text. Presentational issues should be addressed in end-user applications.

---



---


**Note:** The case normalization of language tags is part of the description of the abstract syntax, and consequently the abstract behaviour of RDF applications. It does not constrain an RDF implementation to actually normalize the case. Crucially, the result of comparing two language tags should not be sensitive to the case of the original input. – [RDF Concepts and Abstract Syntax](#)

---

## Common XSD datatypes

Most simple literals such as *string* or *integer* have XML Schema (XSD) datatypes defined for them, see the figure below. Additionally, these XSD datatypes are listed in the `XSD Namespace class` that ships with `RDFLib`, so many Python code editors will prompt you with autocomplete for them when using it.

Remember, you don't *have* to use XSD datatypes and can always make up your own, as GeoSPARQL does, as described above.



## Python conversions

RDFLib Literals essentially behave like unicode characters with an XML Schema datatype or language attribute.

The class provides a mechanism to both convert Python literals (and their built-ins such as time/date/datetime) into equivalent RDF Literals and (conversely) convert Literals to their Python equivalent. This mapping to and from Python literals is done as follows:

XML Datatype	Python type
None	None <sup>1</sup>
xsd:time	time <sup>2</sup>
xsd:date	date
xsd:dateTime	datetime
xsd:string	None
xsd:normalizedString	None
xsd:token	None
xsd:language	None
xsd:boolean	boolean
xsd:decimal	Decimal
xsd:integer	long
xsd:nonPositiveInteger	int
xsd:long	long
xsd:nonNegativeInteger	int
xsd:negativeInteger	int
xsd:int	long
xsd:unsignedLong	long
xsd:positiveInteger	int
xsd:short	int
xsd:unsignedInt	long
xsd:byte	int
xsd:unsignedShort	int
xsd:unsignedByte	int
xsd:float	float
xsd:double	float
xsd:base64Binary	base64
xsd:anyURI	None
rdf:XMLLiteral	xml.dom.minidom.Document <sup>3</sup>
rdf:HTML	xml.dom.minidom.DocumentFragment

An appropriate data-type and lexical representation can be found using:

`rdflib.term._castPythonToLiteral(obj, datatype)`

Casts a tuple of a python type and a special datatype URI to a tuple of the lexical value and a datatype URI (or None)

### Parameters

- **obj** (*Any*) –
- **datatype** (*Optional[str]*) –

<sup>1</sup> plain literals map directly to value space

<sup>2</sup> Date, time and datetime literals are mapped to Python instances using the *isodate* package).

<sup>3</sup> this is a bit dirty - by accident the *html5lib* parser produces *DocumentFragments*, and the *xml* parser *Documents*, letting us use this to decide what datatype when round-tripping.

**Return type**

`Tuple[Any, Optional[str]]`

and the other direction with

`rdflib.term._castLexicalToPython(lexical, datatype)`

Map a lexical form to the value-space for the given datatype :rtype: `Any` :returns: a python object for the value or None

**Parameters**

- **lexical** (`Union[str, bytes]`) –
- **datatype** (`Optional[URIRef]`) –

All this happens automatically when creating `Literal` objects by passing Python objects to the constructor, and you never have to do this manually.

You can add custom data-types with `rdflib.term.bind()`, see also [examples.custom\\_datatype](#)

## 2.2 Namespaces and Bindings

RDFLib provides several short-cuts to working with many URIs in the same namespace.

The `rdflib.namespace` defines the `rdflib.namespace.Namespace` class which lets you easily create URIs in a namespace:

```
from rdflib import Namespace

EX = Namespace("http://example.org/")
EX.Person # a Python attribute for EX. This example is equivalent to rdflib.term.
↳ URIRef("http://example.org/Person")

# use dict notation for things that are not valid Python identifiers, e.g.:
n['first%20name'] # as rdflib.term.URIRef("http://example.org/first%20name")
```

These two styles of namespace creation - object attribute and dict - are equivalent and are made available just to allow for valid RDF namespaces and URIs that are not valid Python identifiers. This isn't just for syntactic things like spaces, as per the example of `first%20name` above, but also for Python reserved words like `class` or `while`, so for the URI `http://example.org/class`, create it with `EX['class']`, not `EX.class`.

### 2.2.1 Common Namespaces

The `namespace` module defines many common namespaces such as RDF, RDFS, OWL, FOAF, SKOS, PROF, etc. The list of the namespaces provided grows with user contributions to RDFLib.

These Namespaces, and any others that users define, can also be associated with prefixes using the `rdflib.namespace.NamespaceManager`, e.g. using `foaf` for `http://xmlns.com/foaf/0.1/`.

Each RDFLib graph has a `namespace_manager` that keeps a list of namespace to prefix mappings. The namespace manager is populated when reading in RDF, and these prefixes are used when serialising RDF, or when parsing SPARQL queries. Prefixes can be bound with the `rdflib.graph.Graph.bind()` method:

```
from rdflib import Graph, Namespace
from rdflib.namespace import FOAF
```

(continues on next page)



(continued from previous page)

```
EX = Namespace("http://example.org/")

g = Graph()
g.bind("foaf", FOAF) # bind an RDFLib-provided namespace to a prefix
g.bind("ex", EX)     # bind a user-declared namespace to a prefix
```

The `rdflib.graph.Graph.bind()` method is actually supplied by the `rdflib.namespace.NamespaceManager` class - see next.

## 2.2.2 NamespaceManager

Each RDFLib graph comes with a `rdflib.namespace.NamespaceManager` instance in the `namespace_manager` field; you can use the `bind()` method of this instance to bind a prefix to a namespace URI, as above, however note that the `NamespaceManager` automatically performs some bindings according to a selected strategy.

Namespace binding strategies are indicated with the `bind_namespaces` input parameter to `NamespaceManager` instances and may be set via `Graph` also:

```
from rdflib import Graph
from rdflib.namespace import NamespaceManager

g = Graph(bind_namespaces="rdflib") # bind via Graph

g2 = Graph()
nm = NamespaceManager(g2, bind_namespaces="rdflib") # bind via NamespaceManager
```

Valid strategies are:

- **core:**
  - binds several core RDF prefixes only
  - owl, rdf, rdfs, xsd, xml from the `NAMESPACE_PREFIXES_CORE` object
  - this is default
- **rdflib:**
  - binds all the namespaces shipped with RDFLib as `DefinedNamespace` instances
  - all the core namespaces and all the following: brick, csvw, dc, dcat
  - dcmitype, dcterms, dcam, doap, foaf, geo, odrl, org, prof, prov, qb, sdo
  - sh, skos, sosa, ssn, time, vann, void
  - see the `NAMESPACE_PREFIXES_RDFLIB` object in `rdflib.namespace` for up-to-date list
- **none:**
  - binds no namespaces to prefixes
  - note this is NOT default behaviour
- **cc:**
  - using prefix bindings from prefix.cc which is a online prefixes database
  - not implemented yet - this is aspirational

## Re-binding

Note that regardless of the strategy employed, prefixes for namespaces can be overwritten with users preferred prefixes, for example:

```
from rdflib import Graph
from rdflib.namespace import GEO # imports GeoSPARQL's namespace

g = Graph(bind_namespaces="rdflib") # binds GeoSPARQL's namespace to prefix 'geo'

g.bind('geosp', GEO, override=True)
```

`NamespaceManager` also has a method to normalize a given url:

```
from rdflib.namespace import NamespaceManager

nm = NamespaceManager(Graph())
nm.normalizeUri(t)
```

For simple output, or simple serialisation, you often want a nice readable representation of a term. All `RDFLib` terms have a `.n3()` method, which will return a suitable N3 format and into which you can supply a `NamespaceManager` instance to provide prefixes, i.e. `.n3(namespace_manager=some_nm)`:

```
>>> from rdflib import Graph, URIRef, Literal, BNode
>>> from rdflib.namespace import FOAF, NamespaceManager

>>> person = URIRef("http://xmlns.com/foaf/0.1/Person")
>>> person.n3()
'<http://xmlns.com/foaf/0.1/Person>'

>>> g = Graph()
>>> g.bind("foaf", FOAF)

>>> person.n3(g.namespace_manager)
'foaf:Person'

>>> l = Literal(2)
>>> l.n3()
'"2"^^<http://www.w3.org/2001/XMLSchema#integer>'

>>> l.n3(NamespaceManager(Graph(), bind_namespaces="core"))
'"2"^^xsd:integer'
```

The namespace manager also has a useful method `compute_qname` `g.namespace_manager.compute_qname(x)` (or just `g.compute_qname(x)`) which takes a URI and decomposes it into the parts:

```
self.assertEqual(g.compute_qname(URIRef("http://foo/bar#baz")),
                 ("ns2", URIRef("http://foo/bar#"), "baz"))
```

### 2.2.3 Namespaces in SPARQL Queries

The `initNs` argument supplied to `query()` is a dictionary of namespaces to be expanded in the query string. If you pass no `initNs` argument, the namespaces registered with the graphs `namespace_manager` are used:

```
from rdflib.namespace import FOAF
graph.query('SELECT * WHERE { ?p a foaf:Person }', initNs={'foaf': FOAF})
```

In order to use an empty prefix (e.g. `?a :knows ?b`), use a `PREFIX` directive with no prefix in the SPARQL query to set a default namespace:

```
PREFIX : <http://xmlns.com/foaf/0.1/>
```

## 2.3 Persistence

RDFLib provides an *abstracted Store API* for persistence of RDF and Notation 3. The *Graph* class works with instances of this API (as the first argument to its constructor) for triple-based management of an RDF store including: garbage collection, transaction management, update, pattern matching, removal, length, and database management (`open()` / `close()` / `destroy()`).

Additional persistence mechanisms can be supported by implementing this API for a different store.

### 2.3.1 Stores currently shipped with core RDFLib

- *Memory* - not persistent!
- *BerkeleyDB* - on disk persistence via Python's *berkeleydb* package
- *SPARQLStore* - a read-only wrapper around a remote SPARQL Query endpoint
- *SPARQLUpdateStore* - a read-write wrapper around a remote SPARQL query/update endpoint pair

### 2.3.2 Usage

In most cases, passing the name of the store to the *Graph* constructor is enough:

```
from rdflib import Graph

graph = Graph(store='BerkeleyDB')
```

Most stores offering on-disk persistence will need to be opened before reading or writing. When persisting a triplestore, rather than a *ConjunctiveGraph* quadstore, you need to specify an identifier with which you can open the graph:

```
graph = Graph('BerkeleyDB', identifier='mygraph')

# first time create the store:
graph.open('/home/user/data/myRDFLibStore', create=True)

# work with the graph:
data = """
    PREFIX : <https://example.org/>
```

(continues on next page)

(continued from previous page)

```
    :a :b :c .
    :d :e :f .
    :d :g :h .
    """"
graph.parse(data=data, format="ttl")

# when done!
graph.close()
```

When done, `close()` must be called to free the resources associated with the store.

### 2.3.3 Additional store plugins

More store implementations are available in RDFLib extension projects:

- `rdflib-sqlalchemy` – a store which supports a wide-variety of RDBMS backends,
- `rdflib-leveldb` – a store on top of Google’s [LevelDB](#) key-value store.
- `rdflib-kyotocabinet` – a store on top of the [Kyoto Cabinet](#) key-value store.

### 2.3.4 Example

- `examples.berkeleydb_example` contains an example for using a BerkeleyDB store.
- `examples.sparqlstore_example` contains an example for using a SPARQLStore.

## 2.4 Merging graphs

Graphs share blank nodes only if they are derived from graphs described by documents or other structures (such as an RDF dataset) that explicitly provide for the sharing of blank nodes between different RDF graphs. Simply downloading a web document does not mean that the blank nodes in a resulting RDF graph are the same as the blank nodes coming from other downloads of the same document or from the same RDF source.

RDF applications which manipulate concrete syntaxes for RDF which use blank node identifiers should take care to keep track of the identity of the blank nodes they identify. Blank node identifiers often have a local scope, so when RDF from different sources is combined, identifiers may have to be changed in order to avoid accidental conflation of distinct blank nodes.

For example, two documents may both use the blank node identifier “\_:x” to identify a blank node, but unless these documents are in a shared identifier scope or are derived from a common source, the occurrences of “\_:x” in one document will identify a different blank node than the one in the graph described by the other document. When graphs are formed by combining RDF from multiple sources, it may be necessary to standardize apart the blank node identifiers by replacing them by others which do not occur in the other document(s).

*(copied directly from <https://www.w3.org/TR/rdf11-mt/#shared-blank-nodes-unions-and-merges>)*

In RDFLib, blank nodes are given unique IDs when parsing, so graph merging can be done by simply reading several files into the same graph:

```
from rdflib import Graph
```

```
graph = Graph()
```

```
graph.parse(input1)
```

```
graph.parse(input2)
```

graph now contains the merged graph of input1 and input2.

**Note:** However, the set-theoretic graph operations in RDFLib are assumed to be performed in sub-graphs of some larger data-base (for instance, in the context of a *ConjunctiveGraph*) and assume shared blank node IDs, and therefore do NOT do *correct* merging, i.e.:

```
from rdflib import Graph
```

```
g1 = Graph()
```

```
g1.parse(input1)
```

```
g2 = Graph()
```

```
g2.parse(input2)
```

```
graph = g1 + g2
```

May cause unwanted collisions of blank-nodes in graph.

## 2.5 Upgrading from version 6 to 7

### 2.5.1 Python version

RDFLib 7 requires Python 3.8.1 or later.

### 2.5.2 New behaviour for publicID in parse methods.

Before version 7, the publicID argument to the *rdflib.graph.ConjunctiveGraph.parse()* and *rdflib.graph.Dataset.parse()* methods was used as the name for the default graph, and triples from the default graph in a source were loaded into the graph named publicID.

In version 7, the publicID argument is only used as the base URI for relative URI resolution as defined in [IETF RFC 3986](#).

To accommodate this change, ensure that use of the publicID argument is consistent with the new behaviour.

If you want to load triples from a format that does not support named graphs into a named graph, use the following code:

```
from rdflib import ConjunctiveGraph
```

```
cg = ConjunctiveGraph()
```

```
cg.get_context("example:graph_name").parse("http://example.com/source.ttl", format=  
→ "turtle")
```

If you want to move triples from the default graph into a named graph, use the following code:

```
from rdflib import ConjunctiveGraph

cg = ConjunctiveGraph()
cg.parse("http://example.com/source.trig", format="trig")
destination_graph = cg.get_context("example:graph_name")
for triple in cg.default_context.triples((None, None, None)):
    destination_graph.add(triple)
    cg.default_context.remove(triple)
```

## 2.6 Upgrading 5.0.0 to 6.0.0

6.0.0 fully adopts Python 3 practices and drops Python 2 support so it is neater, faster and generally more modern than 5.0.0. It also tidies up the Graph API (removing duplicate functions) so it does include a few breaking changes. Additionally, there is a long list of PRs merged into 6.0.0 adding a number of small fixes and features which are listed below.

RDFLib version 5.0.0 was released in 2020, 3 years after the previous version (4.2.2) and is fundamentally 5.0.0 compatible with. If you need very long-term backwards-compatibility or Python 2 support, you need 5.0.0.

### 2.6.1 Major Changes

The most notable changes in RDFLib 6.0.0 are:

#### Python 3.7+

- The oldest version of python you can use to run RDFLib is now 3.7.
- This is a big jump from RDFLib 5.0.0 that worked on python 2.7 and 3.5.
- This change is to allow the library maintainers to adopt more modern development tools, newer language features, and avoid the need to support EOL versions of python in the future

#### JSON-LD integration and JSON-LD 1.1

- The json-ld serializer/parser plugin was by far the most commonly used RDFLib addon.
- Last year we brought it under the RDFLib org in Github
- Now for 6.0.0 release the JSON-LD serializer and parser are integrated into RDFLib core
- This includes the experimental support for the JSON-LD v1.1 spec
- You no longer need to install the json-ld dependency separately.

## 2.6.2 All Changes

This list has been assembled from Pull Request and commit information.

### General Bugs Fixed:

- Pr 451 redux [PR #978](#)

### Enhanced Features:

- Register additional serializer plugins for SPARQL mime types. [PR #987](#)

### SPARQL Fixes:

- Total order patch patch [PR #862](#)

### Code Quality and Cleanups:

- a slightly opinionated autopep8 run [PR #870](#)

### Testing:

- 3.7 for travis [PR #864](#)

### Documentation Fixes:

- Fix a doc string in the query module [PR #976](#)

### Integrate JSON-LD into RDFLib:

[PR #1354](#)

## 2.7 Upgrading 4.2.2 to 5.0.0

RDFLib version 5.0.0 appeared over 3 years after the previous release, 4.2.2 and contains a large number of both enhancements and bug fixes. Fundamentally though, 5.0.0 is compatible with 4.2.2.

### 2.7.1 Major Changes

#### Literal Ordering

Literal total ordering [PR #793](#) is implemented. That means all literals can now be compared to be greater than or less than any other literal. This is required for implementing some specific SPARQL features, but it is counter-intuitive to those who are expecting a `TypeError` when certain normally-incompatible types are compared. For example, comparing a `Literal(int(1), datatype=xsd:integer)` to `Literal(datetime.date(10,01,2020), datatype=xsd:date)` using a `>` or `<` operator in rdflib 4.2.2 and earlier, would normally throw a `TypeError`, however

in rdflib 5.0.0 this operation now returns a True or False according to the Literal Total Ordering according the rules outlined in [PR #793](#)

## Removed RDF Parsers

The RDFa and Microdata format RDF parsers were removed from rdflib. There are still other python libraries available to implement these parsers.

## 2.7.2 All Changes

This list has been assembled from Pull Request and commit information.

### General Bugs Fixed:

- Pr 451 redux [PR #978](#)
- NTriples fails to parse URIs with only a scheme [ISSUE #920](#) [PR #974](#)
- cannot clone it on windows - Remove colons from test result files. Fix #901. [ISSUE #901](#) [PR #971](#)
- Add requirement for requests to setup.py [PR #969](#)
- fixed URIRef including native unicode characters [PR #961](#)
- DCTERMS.format not working [ISSUE #932](#)
- infixowl.manchesterSyntax do not encode strings [PR #906](#)
- Fix blank node label to not contain ‘\_:’ during parsing [PR #886](#)
- rename new SPARQLWrapper to SPARQLConnector [PR #872](#)
- Fix #859. Unquote and Uriquote Literal Datatype. [PR #860](#)
- Parsing nquads [ISSUE #786](#)
- ntriples spec allows for upper-cased lang tag, fixes #782 [PR #784](#)
- Error parsing N-Triple file using RDFLib [ISSUE #782](#)
- Adds escaped single quote to literal parser [PR #736](#)
- N3 parse error on single quote within single quotes [ISSUE #732](#)
- Fixed #725 [PR #730](#)
- test for issue #725: canonicalization collapses BNodes [PR #726](#)
- RGDA1 graph canonicalization sometimes still collapses distinct BNodes [ISSUE #725](#)
- Accept header should use a q parameter [PR #720](#)
- Added test for Issue #682 and fixed. [PR #718](#)
- Incompatibility with Python3: unicr [ISSUE #687](#)
- namespace.py include colon in ALLOWED\_NAME\_CHARS [PR #663](#)
- namespace.py fix compute\_qname missing namespaces [PR #649](#)
- RDFa parsing Error! \_\_init\_\_() got an unexpected keyword argument ‘encoding’ [ISSUE #639](#)
- Bugfix: term.Literal.\_\_add\_\_ [PR #451](#)



- fixup of #443 [PR #445](#)
- Microdata to rdf second edition bak [PR #444](#)

### Enhanced Features:

- Register additional serializer plugins for SPARQL mime types. [PR #987](#)
- Pr 388 redux [PR #979](#)
- Allows RDF terms introduced by JSON-LD 1.1 [PR #970](#)
- make SPARQLConnector work with DBpedia [PR #941](#)
- ClosedNamespace returns right exception for way of access [PR #866](#)
- Not adding all namespaces for n3 serializer [PR #832](#)
- Adds basic support of xsd:duration [PR #808](#)
- Add possibility to set authority and basepath to skolemize graph [PR #807](#)
- Change notation3 list realization to non-recursive function. [PR #805](#)
- Suppress warning for not using custom encoding. [PR #800](#)
- Add support to parsing large xml inputs [ISSUE #749](#) [PR #750](#)
- improve hash efficiency by directly using str/unicode hash [PR #746](#)
- Added the csvw prefix to the RDFa initial context. [PR #594](#)
- syncing changes from pyMicrodata [PR #587](#)
- Microdata parser: updated the parser to the latest version of the microdata->rdf note (published in December 2014) [PR #443](#)
- Literal.toPython() support for xsd:hexBinary [PR #388](#)

### SPARQL Fixes:

- Total order patch patch [PR #862](#)
- use <= instead of deprecated << [PR #861](#)
- Fix #847 [PR #856](#)
- RDF Literal “1”^^xsd:boolean should \_not\_ coerce to True [ISSUE #847](#)
- Makes NOW() return an UTC date [PR #844](#)
- NOW() SPARQL should return an xsd:dateTime with a timezone [ISSUE #843](#)
- fix property paths bug: issue #715 [PR #822](#) [ISSUE #715](#)
- MulPath: correct behaviour of n3() [PR #820](#)
- Literal total ordering [PR #793](#)
- Remove SPARQLWrapper dependency [PR #744](#)
- made UNION faster by not preventing duplicates [PR #741](#)
- added a hook to add custom functions to SPARQL [PR #723](#)
- Issue714 [PR #717](#)

- Use <= instead of deprecated << in SPARQL parser [PR #417](#)
- Custom FILTER function for SPARQL engine [ISSUE #274](#)

### Code Quality and Cleanups:

- a slightly opinionated autopep8 run [PR #870](#)
- remove rdfa and microdata parsers from core RDFLib [PR #828](#)
- ClosedNamespace KeyError -> AttributeError [PR #827](#)
- typo in rdflib/plugins/sparql/update.py [ISSUE #760](#)
- Fix logging in interactive mode [PR #731](#)
- make namespace module flake8-compliant, change exceptions in that mod... [PR #711](#)
- delete ez\_setup.py? [ISSUE #669](#)
- code duplication issue between rdflib and pymicrodata [ISSUE #582](#)
- Transition from 2to3 to use of six.py to be merged in 5.0.0-dev [PR #519](#)
- sparqlstore drop deprecated methods and args [PR #516](#)
- python3 code seems shockingly inefficient [ISSUE #440](#)
- removed md5\_term\_hash, fixes #240 [PR #439](#) [ISSUE #240](#)

### Testing:

- 3.7 for travis [PR #864](#)
- Added trig unit tests to highlight some current parsing/serializing issues [PR #431](#)

### Documentation Fixes:

- Fix a doc string in the query module [PR #976](#)
- setup.py: Make the license field use an SPDX identifier [PR #789](#)
- Update README.md [PR #764](#)
- Update namespaces\_and\_bindings.rst [PR #757](#)
- DOC: README.md: rdflib-jsonld, https uris [PR #712](#)
- make doctest support py2/py3 [ISSUE #707](#)
- pip install rdflib (as per README.md) gets OSError on Mint 18.1 [ISSUE #704](#) [PR #717](#)
- Use <= instead of deprecated << in SPARQL parser [PR #417](#)
- Custom FILTER function for SPARQL engine [ISSUE #274](#)

## 2.8 Security Considerations

RDFLib is designed to access arbitrary network and file resources, in some cases these are directly requested resources, in other cases they are indirectly referenced resources.

An example of where indirect resources are accessed is JSON-LD processing, where network or file resources referenced by `@context` values will be loaded and processed.

RDFLib also supports SPARQL, which has federated query capabilities that allow queries to query arbitrary remote endpoints.

If you are using RDFLib to process untrusted documents or queries, you should take measures to restrict file and network access.

Some measures that can be taken to restrict file and network access are:

- *Operating System Security Measures.*
- *Python Runtime Audit Hooks.*
- *Custom URL Openers.*

Of these, operating system security measures are recommended. The other measures work, but they are not as effective as operating system security measures, and even if they are used, they should be used in conjunction with operating system security measures.

### 2.8.1 Operating System Security Measures

Most operating systems provide functionality that can be used to restrict network and file access of a process.

Some examples of these include:

- **Open Container Initiative (OCI) Containers** (aka Docker containers).

Most OCI runtimes provide mechanisms to restrict network and file access of containers. For example, using Docker, you can limit your container to only being able to access files explicitly mapped into the container and only access the network through a firewall. For more information, refer to the documentation of the tool you use to manage your OCI containers:

- **Kubernetes**
- **Docker**
- **Podman**

- **firejail** can be used to sandbox a process on Linux and restrict its network and file access.
- File and network access restrictions.

Most operating systems provide a way to restrict operating system users to only being able to access files and network resources that are explicitly allowed. Applications that process untrusted input could be run as a user with these restrictions in place.

Many other measures are available, however, listing them is outside the scope of this document.

Of the listed measures, OCI containers are recommended. In most cases, OCI containers are constrained by default and can't access the loopback interface and can only access files that are explicitly mapped into the container.

## 2.8.2 Python Runtime Audit Hooks

From Python 3.8 onwards, Python provides a mechanism to install runtime audit hooks that can be used to limit access to files and network resources.

The runtime audit hook system is described in more detail in [PEP 578 – Python Runtime Audit Hooks](#).

Runtime audit hooks can be installed using the `sys.addaudithook` function, and will then get called when audit events occur. The audit events raised by the Python runtime and standard library are described in Python’s [audit events table](#).

RDFLib uses `urllib.request.urlopen` for HTTP, HTTPS and other network access, and this function raises a `urllib.Request` audit event. For file access, RDFLib uses `open`, which raises an `open` audit event.

Users of RDFLib can install audit hooks that react to these audit events and raise an exception when an attempt is made to access files or network resources that are not explicitly allowed.

RDFLib’s test suite includes tests which verify that audit hooks can block access to network and file resources.

RDFLib also includes an example that shows how runtime audit hooks can be used to restrict network and file access in [secure\\_with\\_audit](#).

## 2.8.3 Custom URL Openers

RDFLib uses the `urllib.request.urlopen` for HTTP, HTTPS and other network access. This function will use a `urllib.request.OpenerDirector` installed with `urllib.request.install_opener` to open the URLs.

Users of RDFLib can install a custom URL opener that raises an exception when an attempt is made to access network resources that are not explicitly allowed.

RDFLib’s test suite includes tests which verify that custom URL openers can be used to block access to network resources.

RDFLib also includes an example that shows how a custom opener can be used to restrict network access in [secure\\_with\\_urlopen](#).

## REFERENCE

The nitty-gritty details of everything.

API reference:

### 3.1 rdflib

#### 3.1.1 rdflib package

##### Subpackages

##### rdflib.extras package

##### Submodules

##### rdflib.extras.cmdlineutils module

`rdflib.extras.cmdlineutils.main(target, _help=<function _help>, options="", stdin=True)`

A main function for tools that read RDF from files given on commandline or from STDIN (if stdin parameter is true)

##### rdflib.extras.describer module

A Descriptor is a stateful utility for creating RDF statements in a semi-declarative manner. It has methods for creating literal values, rel and rev resource relations (somewhat resembling RDFa).

The *Descriptor.rel* and *Descriptor.rev* methods return a context manager which sets the current about to the referenced resource for the context scope (for use with the `with` statement).

Full example in the `to_rdf` method below:

```
>>> import datetime
>>> from rdflib.graph import Graph
>>> from rdflib.namespace import Namespace, RDFS, FOAF
>>>
>>> ORG_URI = "http://example.org/"
>>>
>>> CV = Namespace("http://purl.org/captsolo/resume-rdf/0.2/cv#")
>>>
```

(continues on next page)

(continued from previous page)

```

>>> class Person:
...     def __init__(self):
...         self.first_name = u"Some"
...         self.last_name = u"Body"
...         self.username = "some1"
...         self.presentation = u"Just a Python & RDF hacker."
...         self.image = "/images/persons/" + self.username + ".jpg"
...         self.site = "http://example.net/"
...         self.start_date = datetime.date(2009, 9, 4)
...     def get_full_name(self):
...         return u" ".join([self.first_name, self.last_name])
...     def get_absolute_url(self):
...         return "/persons/" + self.username
...     def get_thumbnail_url(self):
...         return self.image.replace('.jpg', '-thumb.jpg')
...
...     def to_rdf(self):
...         graph = Graph()
...         graph.bind('foaf', FOAF)
...         graph.bind('cv', CV)
...         lang = 'en'
...         d = Describer(graph, base=ORG_URI)
...         d.about(self.get_absolute_url()+'#person')
...         d.rdftype(FOAF.Person)
...         d.value(FOAF.name, self.get_full_name())
...         d.value(FOAF.givenName, self.first_name)
...         d.value(FOAF.familyName, self.last_name)
...         d.rel(FOAF.homepage, self.site)
...         d.value(RDFS.comment, self.presentation, lang=lang)
...         with d.rel(FOAF.depiction, self.image):
...             d.rdftype(FOAF.Image)
...             d.rel(FOAF.thumbnail, self.get_thumbnail_url())
...         with d.rev(CV.aboutPerson):
...             d.rdftype(CV.CV)
...             with d.rel(CV.hasWorkHistory):
...                 d.value(CV.startDate, self.start_date)
...                 d.rel(CV.employedIn, ORG_URI+"#company")
...         return graph
...
>>> person_graph = Person().to_rdf()
>>> expected = Graph().parse(data='''<?xml version="1.0" encoding="utf-8"?>
... <rdf:RDF
...   xmlns:foaf="http://xmlns.com/foaf/0.1/"
...   xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
...   xmlns:cv="http://purl.org/captsolo/resume-rdf/0.2/cv#"
...   xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#">
...   <foaf:Person rdf:about="http://example.org/persons/some1#person">
...     <foaf:name>Some Body</foaf:name>
...     <foaf:givenName>Some</foaf:givenName>
...     <foaf:familyName>Body</foaf:familyName>
...     <foaf:depiction>
...       <foaf:Image

```

(continues on next page)

(continued from previous page)

```

...     rdf:about=
...         "http://example.org/images/persons/some1.jpg">
...     <foaf:thumbnail
...     rdf:resource=
...         "http://example.org/images/persons/some1-thumb.jpg"/>
...     </foaf:Image>
... </foaf:depiction>
... <rdfs:comment xml:lang="en">
...     Just a Python & RDF hacker.
... </rdfs:comment>
... <foaf:homepage rdf:resource="http://example.net"/>
... </foaf:Person>
... <cv:CV>
...     <cv:aboutPerson
...         rdf:resource="http://example.org/persons/some1#person">
...     </cv:aboutPerson>
...     <cv:hasWorkHistory>
...         <rdf:Description>
...             <cv:startDate
...                 rdf:datatype="http://www.w3.org/2001/XMLSchema#date"
...                 >2009-09-04</cv:startDate>
...             <cv:employedIn rdf:resource="http://example.org/#company"/>
...         </rdf:Description>
...     </cv:hasWorkHistory>
... </cv:CV>
... </rdf:RDF>
... ''' , format="xml")
>>>
>>> from rdflib.compare import isomorphic
>>> isomorphic(person_graph, expected)
True

```

```
class rdflib.extras.describer.Describer(graph=None, about=None, base=None)
```

Bases: `object`

```
__dict__ = mappingproxy({'__module__': 'rdflib.extras.describer', '__init__':
<function Describer.__init__>, 'about': <function Describer.about>, 'value':
<function Describer.value>, 'rel': <function Describer.rel>, 'rev': <function
Describer.rev>, 'rdftype': <function Describer.rdftype>, '_current': <function
Describer._current>, '_subject_stack': <function Describer._subject_stack>,
'__dict__': <attribute '__dict__' of 'Describer' objects>, '__weakref__':
<attribute '__weakref__' of 'Describer' objects>, '__doc__': None,
'__annotations__': {}})
```

```
__init__(graph=None, about=None, base=None)
```

```
__module__ = 'rdflib.extras.describer'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
about(subject, **kws)
```

Sets the current subject. Will convert the given object into an URIRef if it's not an Identifier.

Usage:

```
>>> d = Describer()
>>> d._current()
rdflib.term.BNode(...)
>>> d.about("http://example.org/")
>>> d._current()
rdflib.term.URIRef(u'http://example.org/')
```

**rdftype(*t*)**

Shorthand for setting rdf:type of the current subject.

Usage:

```
>>> from rdflib import URIRef
>>> from rdflib.namespace import RDF, RDFS
>>> d = Describer(about="http://example.org/")
>>> d.rdftype(RDFS.Resource)
>>> (URIRef('http://example.org/'),
...   RDF.type, RDFS.Resource) in d.graph
True
```

**rel(*p*, *o*=None, \*\**kws*)**

Set an object for the given property. Will convert the given object into an URIRef if it's not an Identifier. If none is given, a new BNode is used.

Returns a context manager for use in a with block, within which the given object is used as current subject.

Usage:

```
>>> from rdflib import URIRef
>>> from rdflib.namespace import RDF, RDFS
>>> d = Describer(about="/", base="http://example.org/")
>>> _ctxt = d.rel(RDFS.seeAlso, "/about")
>>> d.graph.value(URIRef('http://example.org/'), RDFS.seeAlso)
rdflib.term.URIRef(u'http://example.org/about')

>>> with d.rel(RDFS.seeAlso, "/more"):
...     d.value(RDFS.label, "More")
>>> (URIRef('http://example.org/'), RDFS.seeAlso,
...   URIRef('http://example.org/more')) in d.graph
True
>>> d.graph.value(URIRef('http://example.org/more'), RDFS.label)
rdflib.term.Literal(u'More')
```

**rev(*p*, *s*=None, \*\**kws*)**

Same as rel, but uses current subject as *object* of the relation. The given resource is still used as subject in the returned context manager.

Usage:

```
>>> from rdflib import URIRef
>>> from rdflib.namespace import RDF, RDFS
>>> d = Describer(about="http://example.org/")
>>> with d.rev(RDFS.seeAlso, "http://example.net/"):
...     d.value(RDFS.label, "Net")
>>> (URIRef('http://example.net/'), RDFS.seeAlso,
```

(continues on next page)



(continued from previous page)

```

...         URIRef('http://example.org/')) in d.graph
True
>>> d.graph.value(URIRef('http://example.net/'), RDFS.label)
rdflib.term.Literal(u'Net')

```

**value**(*p*, *v*, *\*\*kws*)

Set a literal value for the given property. Will cast the value to an `Literal` if a plain literal is given.

Usage:

```

>>> from rdflib import URIRef
>>> from rdflib.namespace import RDF, RDFS
>>> d = Descriptor(about="http://example.org/")
>>> d.value(RDFS.label, "Example")
>>> d.graph.value(URIRef('http://example.org/'), RDFS.label)
rdflib.term.Literal(u'Example')

```

`rdflib.extras.describer.cast_identifier`(*ref*, *\*\*kws*)

`rdflib.extras.describer.cast_value`(*v*, *\*\*kws*)

### `rdflib.extras.external_graph_libs` module

`rdflib.extras.external_graph_libs.rdflib_to_graphtool`(*graph*, *v\_prop\_names*=['term'],  
*e\_prop\_names*=['term'],  
*transform\_s*=<function <lambda>>,  
*transform\_p*=<function <lambda>>,  
*transform\_o*=<function <lambda>>)

Converts the given graph into a `graph_tool.Graph()`.

The subjects and objects are the later vertices of the Graph. The predicates become edges.

#### Parameters

- *graph*: a `rdflib.Graph`.
- *v\_prop\_names*: a list of names for the vertex properties. The default is set to ['term'] (see *transform\_s*, *transform\_o* below).
- *e\_prop\_names*: a list of names for the edge properties.
- *transform\_s*: callable with *s*, *p*, *o* input. Should return a dictionary containing a value for each name in *v\_prop\_names*. By default is set to {'term': *s*} which in combination with *v\_prop\_names* = ['term'] adds *s* as 'term' property to the generated vertex for *s*.
- *transform\_p*: similar to *transform\_s*, but wrt. *e\_prop\_names*. By default returns {'term': *p*} which adds *p* as a property to the generated edge between the vertex for *s* and the vertex for *o*.
- *transform\_o*: similar to *transform\_s*.

Returns: `graph_tool.Graph()`

```

>>> from rdflib import Graph, URIRef, Literal
>>> g = Graph()
>>> a, b, l = URIRef('a'), URIRef('b'), Literal('l')

```

(continues on next page)

(continued from previous page)

```

>>> p, q = URIRef('p'), URIRef('q')
>>> edges = [(a, p, b), (a, q, b), (b, p, a), (b, p, l)]
>>> for t in edges:
...     g.add(t)
...
>>> mdg = rdflib_to_graphtool(g)
>>> len(list(mdg.edges()))
4
>>> from graph_tool import util as gt_util
>>> vpterm = mdg.vertex_properties['term']
>>> va = gt_util.find_vertex(mdg, vpterm, a)[0]
>>> vb = gt_util.find_vertex(mdg, vpterm, b)[0]
>>> vl = gt_util.find_vertex(mdg, vpterm, l)[0]
>>> (va, vb) in [(e.source(), e.target()) for e in list(mdg.edges())]
True
>>> epterm = mdg.edge_properties['term']
>>> len(list(gt_util.find_edge(mdg, epterm, p))) == 3
True
>>> len(list(gt_util.find_edge(mdg, epterm, q))) == 1
True

```

```

>>> mdg = rdflib_to_graphtool(
...     g,
...     e_prop_names=[str('name')],
...     transform_p=lambda s, p, o: {str('name'): unicode(p)})
>>> epterm = mdg.edge_properties['name']
>>> len(list(gt_util.find_edge(mdg, epterm, unicode(p)))) == 3
True
>>> len(list(gt_util.find_edge(mdg, epterm, unicode(q)))) == 1
True

```

### Parameters

- **graph** (*Graph*) –
- **v\_prop\_names** (*List[str]*) –
- **e\_prop\_names** (*List[str]*) –

`rdflib.extras.external_graph_libs.rdflib_to_networkx_digraph(graph, calc_weights=True, edge_attrs=<function <lambda>>, **kws)`

Converts the given graph into a `networkx.DiGraph`.

As an `rdflib.Graph()` can contain multiple edges between nodes, by default adds the a ‘triples’ attribute to the single `DiGraph` edge with a list of all triples between `s` and `o`. Also by default calculates the edge weight as the length of triples.

### Parameters

- **graph**: a `rdflib.Graph`.
- **calc\_weights**: If true calculate multi-graph edge-count as edge ‘weight’

- **edge\_attrs:** Callable to construct later edge attributes. It receives 3 variables (s, p, o) and should construct a dictionary that is passed to networkx's `add_edge(s, o, **attrs)` function.

By default this will include setting the 'triples' attribute here, which is treated specially by us to be merged. Other attributes of multi-edges will only contain the attributes of the first edge. If you don't want the 'triples' attribute for tracking, set this to `lambda s, p, o: {}`.

Returns: `networkx.DiGraph`

```
>>> from rdflib import Graph, URIRef, Literal
>>> g = Graph()
>>> a, b, l = URIRef('a'), URIRef('b'), Literal('1')
>>> p, q = URIRef('p'), URIRef('q')
>>> edges = [(a, p, b), (a, q, b), (b, p, a), (b, p, l)]
>>> for t in edges:
...     g.add(t)
...
>>> dg = rdflib_to_networkx_digraph(g)
>>> dg[a][b]['weight']
2
>>> sorted(dg[a][b]['triples']) == [(a, p, b), (a, q, b)]
True
>>> len(dg.edges())
3
>>> dg.size()
3
>>> dg.size(weight='weight')
4.0
```

```
>>> dg = rdflib_to_networkx_graph(g, False, edge_attrs=lambda s,p,o:{})
>>> 'weight' in dg[a][b]
False
>>> 'triples' in dg[a][b]
False
```

### Parameters

- **graph** (*Graph*) –
- **calc\_weights** (*bool*) –

`rdflib.extras.external_graph_libs.rdflib_to_networkx_graph`(*graph*, *calc\_weights*=*True*, *edge\_attrs*=<function <lambda>>, *\*\*kws*)

Converts the given graph into a `networkx.Graph`.

As an `rdflib.Graph()` can contain multiple directed edges between nodes, by default adds the a 'triples' attribute to the single `DiGraph` edge with a list of triples between *s* and *o* in graph. Also by default calculates the edge weight as the `len(triples)`.

### Parameters

- **graph**: a `rdflib.Graph`.
- **calc\_weights**: If true calculate multi-graph edge-count as edge 'weight'

- **edge\_attrs:** Callable to construct later edge\_attributes. It receives 3 variables (s, p, o) and should construct a dictionary that is passed to networkx's `add_edge(s, o, **attrs)` function.

By default this will include setting the 'triples' attribute here, which is treated specially by us to be merged. Other attributes of multi-edges will only contain the attributes of the first edge. If you don't want the 'triples' attribute for tracking, set this to `lambda s, p, o: {}`.

**Returns:**

`networkx.Graph`

```
>>> from rdflib import Graph, URIRef, Literal
>>> g = Graph()
>>> a, b, l = URIRef('a'), URIRef('b'), Literal('l')
>>> p, q = URIRef('p'), URIRef('q')
>>> edges = [(a, p, b), (a, q, b), (b, p, a), (b, p, l)]
>>> for t in edges:
...     g.add(t)
...
>>> ug = rdflib_to_networkx_graph(g)
>>> ug[a][b]['weight']
3
>>> sorted(ug[a][b]['triples']) == [(a, p, b), (a, q, b), (b, p, a)]
True
>>> len(ug.edges())
2
>>> ug.size()
2
>>> ug.size(weight='weight')
4.0
```

```
>>> ug = rdflib_to_networkx_graph(g, False, edge_attrs=lambda s,p,o:{})
>>> 'weight' in ug[a][b]
False
>>> 'triples' in ug[a][b]
False
```

**Parameters**

- **graph** (*Graph*) –
- **calc\_weights** (*bool*) –

`rdflib.extras.external_graph_libs.rdflib_to_networkx_multidigraph`(*graph*, *edge\_attrs*=<function <lambda>>, *\*\*kws*)

Converts the given graph into a `networkx.MultiDiGraph`.

The subjects and objects are the later nodes of the `MultiDiGraph`. The predicates are used as edge keys (to identify multi-edges).

**Parameters**

- **graph**: a `rdflib.Graph`.

- **edge\_attrs:** Callable to construct later edge\_attributes. It receives 3 variables (s, p, o) and should construct a dictionary that is passed to networkx's `add_edge(s, o, **attrs)` function.

By default this will include setting the MultiDiGraph key=p here. If you don't want to be able to re-identify the edge later on, you can set this to `lambda s, p, o: {}`. In this case MultiDiGraph's default (increasing ints) will be used.

**Returns:**

`networkx.MultiDiGraph`

```
>>> from rdflib import Graph, URIRef, Literal
>>> g = Graph()
>>> a, b, l = URIRef('a'), URIRef('b'), Literal('l')
>>> p, q = URIRef('p'), URIRef('q')
>>> edges = [(a, p, b), (a, q, b), (b, p, a), (b, p, l)]
>>> for t in edges:
...     g.add(t)
...
>>> mdg = rdflib_to_networkx_multidigraph(g)
>>> len(mdg.edges())
4
>>> mdg.has_edge(a, b)
True
>>> mdg.has_edge(a, b, key=p)
True
>>> mdg.has_edge(a, b, key=q)
True
>>> mdg.has_edge(a, b, key=0)
True
```

```
>>> mdg = rdflib_to_networkx_multidigraph(g, edge_attrs=lambda s,p,o: {})
>>> mdg.has_edge(a, b, key=0)
True
>>> mdg.has_edge(a, b, key=1)
True
```

**Parameters**

**graph** (*Graph*) –

**rdflib.extras.infixowl module**

RDFLib Python binding for OWL Abstract Syntax

**OWL Constructor DL Syntax Manchester OWL Syntax Example**

intersectionOf C D C AND D Human AND Male unionOf C D C OR D Man OR Woman complementOf  $\neg$  C NOT C NOT Male oneOf {a} {b}... {a b ...} {England Italy Spain} someValuesFrom R C R SOME C hasColleague SOME Professor allValuesFrom R C R ONLY C hasColleague ONLY Professor minCardinality N R R MIN 3 hasColleague MIN 3 maxCardinality N R R MAX 3 hasColleague MAX 3 cardinality = N R R EXACTLY 3 hasColleague EXACTLY 3 hasValue R {a} R VALUE a hasColleague VALUE Matthew

see: <http://www.w3.org/TR/owl-semantics/syntax.html>  
[http://owl-workshop.man.ac.uk/acceptedLong/submission\\_9.pdf](http://owl-workshop.man.ac.uk/acceptedLong/submission_9.pdf)

**3.2.3 Axioms for complete classes without using owl:equivalentClass**

Named class description of type 2 (with owl:oneOf) or type 4-6 (with owl:intersectionOf, owl:unionOf or owl:complementOf)

Uses Manchester Syntax for `__repr__`

```
>>> exNs = Namespace("http://example.com/")
>>> g = Graph()
>>> g.bind("ex", exNs, override=False)
```

Now we have an empty graph, we can construct OWL classes in it using the Python classes defined in this module

```
>>> a = Class(exNs.Opera, graph=g)
```

Now we can assert rdfs:subClassOf and owl:equivalentClass relationships (in the underlying graph) with other classes using the 'subClassOf' and 'equivalentClass' descriptors which can be set to a list of objects for the corresponding predicates.

```
>>> a.subClassOf = [exNs.MusicalWork]
```

We can then access the rdfs:subClassOf relationships

```
>>> print(list(a.subClassOf))
[Class: ex:MusicalWork ]
```

This can also be used against already populated graphs:

```
>>> owlGraph = Graph().parse(str(OWL))
>>> list(Class(OWL.Class, graph=owlGraph).subClassOf)
[Class: rdfs:Class ]
```

Operators are also available. For instance we can add ex:Opera to the extension of the ex:CreativeWork class via the '+=' operator

```
>>> a
Class: ex:Opera SubClassOf: ex:MusicalWork
>>> b = Class(exNs.CreativeWork, graph=g)
>>> b += a
>>> print(sorted(a.subClassOf, key=lambda c:c.identifier))
[Class: ex:CreativeWork , Class: ex:MusicalWork ]
```

And we can then remove it from the extension as well

```
>>> b -= a
>>> a
Class: ex:Opera SubClassOf: ex:MusicalWork
```

Boolean class constructions can also be created with Python operators. For example, The `|` operator can be used to construct a class consisting of a `owl:unionOf` the operands:

```
>>> c = a | b | Class(exNs.Work, graph=g)
>>> c
( ex:Opera OR ex:CreativeWork OR ex:Work )
```

Boolean class expressions can also be operated as lists (using python list operators)

```
>>> del c[c.index(Class(exNs.Work, graph=g))]
>>> c
( ex:Opera OR ex:CreativeWork )
```

The `&` operator can be used to construct class intersection:

```
>>> woman = Class(exNs.Female, graph=g) & Class(exNs.Human, graph=g)
>>> woman.identifier = exNs.Woman
>>> woman
( ex:Female AND ex:Human )
>>> len(woman)
2
```

Enumerated classes can also be manipulated

```
>>> contList = [Class(exNs.Africa, graph=g), Class(exNs.NorthAmerica, graph=g)]
>>> EnumeratedClass(members=contList, graph=g)
{ ex:Africa ex:NorthAmerica }
```

`owl:Restrictions` can also be instantiated:

```
>>> Restriction(exNs.hasParent, graph=g, allValuesFrom=exNs.Human)
( ex:hasParent ONLY ex:Human )
```

Restrictions can also be created using Manchester OWL syntax in ‘colloquial’ Python `>>> exNs.hasParent @ some @ Class(exNs.Physician, graph=g) ( ex:hasParent SOME ex:Physician )`

```
>>> Property(exNs.hasParent, graph=g) @ max @ Literal(1)
( ex:hasParent MAX 1 )
```

```
>>> print(g.serialize(format='pretty-xml'))
```

```
rdflib.extras.infixowl.AllClasses(graph)
```

```
rdflib.extras.infixowl.AllDifferent(members)
```

TODO: implement this function

```
DisjointClasses(' description description { description } ')
```

```
rdflib.extras.infixowl.AllProperties(graph)
```

```
class rdflib.extras.infixowl.AnnotatableTerms(identifier, graph=None, nameAnnotation=None,
                                              nameIsLabel=False)
```

Bases: *Individual*

Terms in an OWL ontology with rdfs:label and rdfs:comment

## Interface with ATTEMPTO (<http://attempto.ifi.uzh.ch/site>)

### Verbalisation of OWL entity IRIS

#### How are OWL entity IRIs verbalized?

The OWL verbalizer maps OWL entity IRIs to ACE content words such that

- OWL individuals map to ACE proper names (PN)
- OWL classes map to ACE common nouns (CN)
- OWL properties map to ACE transitive verbs (TV)

There are 6 morphological categories that determine the surface form of an IRI:

- singular form of a proper name (e.g. John)
- singular form of a common noun (e.g. man)
- plural form of a common noun (e.g. men)
- singular form of a transitive verb (e.g. mans)
- plural form of a transitive verb (e.g. man)
- past participle form a transitive verb (e.g. manned)

The user has full control over the eventual surface forms of the IRIs but has to choose them in terms of the above categories. Furthermore,

- the surface forms must be legal ACE content words (e.g. they should not contain punctuation symbols);
- the mapping of IRIs to surface forms must be bidirectional within the same word class, in order to be able to (if needed) parse the verbalization back into OWL in a semantics preserving way.

### Using the lexicon

It is possible to specify the mapping of IRIs to surface forms using the following annotation properties:

```
http://attempto.ifi.uzh.ch/ace_lexicon#PN_sg
http://attempto.ifi.uzh.ch/ace_lexicon#CN_sg
http://attempto.ifi.uzh.ch/ace_lexicon#CN_pl
http://attempto.ifi.uzh.ch/ace_lexicon#TV_sg
http://attempto.ifi.uzh.ch/ace_lexicon#TV_pl
http://attempto.ifi.uzh.ch/ace_lexicon#TV_vbg
```

For example, the following axioms state that if the IRI “#man” is used as a plural common noun, then the wordform men must be used by the verbalizer. If, however, it is used as a singular transitive verb, then mans must be used.

```
<AnnotationAssertion>
  <AnnotationProperty IRI="http://attempto.ifi.uzh.ch/ace_lexicon#CN_pl"/>
  <IRI>#man</IRI>
  <Literal datatypeIRI="&xsd:string">men</Literal>
</AnnotationAssertion>
```

(continues on next page)



(continued from previous page)

```
<AnnotationAssertion>
  <AnnotationProperty IRI="http://attempto.ifi.uzh.ch/ace_lexicon#TV_sg"/>
  <IRI>#man</IRI>
  <Literal datatypeIRI="&xsd:string">mans</Literal>
</AnnotationAssertion>
```

```
__init__(identifier, graph=None, nameAnnotation=None, nameIsLabel=False)
```

```
__module__ = 'rdflib.extras.infixowl'
```

```
property comment
```

```
handleAnnotation(val)
```

```
property label
```

```
property seeAlso
```

```
setupACEAnnotations()
```

```
class rdflib.extras.infixowl.BooleanClass(identifier=None, opera-
                                         tor=rdflib.term.URIRef('http://www.w3.org/2002/07/owl#intersectionOf'),
                                         members=None, graph=None)
```

Bases: *OWLRDFListProxy, Class*

See: <http://www.w3.org/TR/owl-ref/#Boolean>

owl:complementOf is an attribute of Class, however

```
__init__(identifier=None, operator=rdflib.term.URIRef('http://www.w3.org/2002/07/owl#intersectionOf'),
         members=None, graph=None)
```

```
__module__ = 'rdflib.extras.infixowl'
```

```
__or__(other)
```

Adds other to the list and returns self

```
__repr__()
```

Returns the Manchester Syntax equivalent for this class

```
changeOperator(newOperator)
```

Converts a unionOf / intersectionOf class expression into one that instead uses the given operator

```
>>> testGraph = Graph()
>>> Individual.factoryGraph = testGraph
>>> EX = Namespace("http://example.com/")
>>> testGraph.bind("ex", EX, override=False)
>>> fire = Class(EX.Fire)
>>> water = Class(EX.Water)
>>> testClass = BooleanClass(members=[fire,water])
>>> testClass
( ex:Fire AND ex:Water )
>>> testClass.changeOperator(OWL.unionOf)
>>> testClass
( ex:Fire OR ex:Water )
>>> try:
```

(continues on next page)

(continued from previous page)

```
...     testClass.changeOperator(OWL.unionOf)
... except Exception as e:
...     print(e)
The new operator is already being used!
```

**copy()**

Create a copy of this class

**getIntersections** = <rdflib.extras.infixowl.Callable object>

**getUnions** = <rdflib.extras.infixowl.Callable object>

**isPrimitive()**

**serialize**(graph)

**class** rdflib.extras.infixowl.Callable(anycallable)

Bases: *object*

**\_\_call\_\_**(\*args, \*\*kwargs)

Call self as a function.

```
__dict__ = mappingproxy({'__module__': 'rdflib.extras.infixowl', '__init__':
<function Callable.__init__>, '__call__': <function Callable.__call__>, '__dict__':
<attribute '__dict__' of 'Callable' objects>, '__weakref__': <attribute
'__weakref__' of 'Callable' objects>, '__doc__': None, '__annotations__': {}})
```

**\_\_init\_\_**(anycallable)

**\_\_module\_\_** = 'rdflib.extras.infixowl'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

rdflib.extras.infixowl.**CastClass**(c, graph=None)

```
class rdflib.extras.infixowl.Class(identifier=None, subClassOf=None, equivalentClass=None,
disjointWith=None, complementOf=None, graph=None,
skipOWLClassMembership=False, comment=None,
nounAnnotations=None, nameAnnotation=None, nameIsLabel=False)
```

Bases: *AnnotatableTerms*

‘General form’ for classes:

The Manchester Syntax (supported in Protege) is used as the basis for the form of this class

See: [http://owl-workshop.man.ac.uk/acceptedLong/submission\\_9.pdf](http://owl-workshop.man.ac.uk/acceptedLong/submission_9.pdf):

[Annotation] ‘Class:’ classID {Annotation ( (‘SubClassOf:’ ClassExpression) | (‘EquivalentTo’ ClassExpression) | (‘DisjointWith’ ClassExpression)) }

Appropriate excerpts from OWL Reference:

“.. **Subclass axioms provide us with partial definitions: they represent**

necessary but not sufficient conditions for establishing class membership of an individual.”

“.. A class axiom may contain (multiple) owl:equivalentClass statements”

“..A class axiom may also contain (multiple) owl:disjointWith statements..”

**“..An owl:complementOf property links a class to precisely one class description.”**

**\_\_and\_\_(other)**

Construct an anonymous class description consisting of the intersection of this class and ‘other’ and return it

Chaining 3 intersections

```
>>> exNs = Namespace("http://example.com/")
>>> g = Graph()
>>> g.bind("ex", exNs, override=False)
>>> female = Class(exNs.Female, graph=g)
>>> human = Class(exNs.Human, graph=g)
>>> youngPerson = Class(exNs.YoungPerson, graph=g)
>>> youngWoman = female & human & youngPerson
>>> youngWoman
ex:YoungPerson THAT ( ex:Female AND ex:Human )
>>> isinstance(youngWoman, BooleanClass)
True
>>> isinstance(youngWoman.identifier, BNode)
True
```

**\_\_eq\_\_(other)**

Return self==value.

**\_\_hash\_\_()**

```
>>> b = Class(OWL.Restriction)
>>> c = Class(OWL.Restriction)
>>> len(set([b,c]))
1
```

**\_\_iadd\_\_(other)**

**\_\_init\_\_**(*identifier=None, subClassOf=None, equivalentClass=None, disjointWith=None, complementOf=None, graph=None, skipOWLClassMembership=False, comment=None, nounAnnotations=None, nameAnnotation=None, nameIsLabel=False*)

**\_\_invert\_\_()**

Shorthand for Manchester syntax’s not operator

**\_\_isub\_\_(other)**

**\_\_module\_\_** = 'rdflib.extras.infixowl'

**\_\_or\_\_(other)**

Construct an anonymous class description consisting of the union of this class and ‘other’ and return it

**\_\_repr\_\_**(*full=False, normalization=True*)

Returns the Manchester Syntax equivalent for this class

**property annotation**

**property complementOf**

**property disjointWith**

**property equivalentClass**

**property extent**

**property extentQuery**

**isPrimitive()**

**property parents**

computed attributes that returns a generator over taxonomic ‘parents’ by disjunction, conjunction, and subsumption

```
>>> from rdflib.util import first
>>> exNs = Namespace('http://example.com/')
>>> g = Graph()
>>> g.bind("ex", exNs, override=False)
>>> Individual.factoryGraph = g
>>> brother = Class(exNs.Brother)
>>> sister = Class(exNs.Sister)
>>> sibling = brother | sister
>>> sibling.identifier = exNs.Sibling
>>> sibling
( ex:Brother OR ex:Sister )
>>> first(brother.parents)
Class: ex:Sibling EquivalentTo: ( ex:Brother OR ex:Sister )
>>> parent = Class(exNs.Parent)
>>> male = Class(exNs.Male)
>>> father = parent & male
>>> father.identifier = exNs.Father
>>> list(father.parents)
[Class: ex:Parent , Class: ex:Male ]
```

**serialize(graph)**

**setupNounAnnotations(noun\_annotations)**

**property subClassOf**

**subSumpteeIds()**

**class** rdflib.extras.infixowl.**ClassNamespaceFactory**(value: *str* | *bytes*)

Bases: *Namespace*

**\_\_getattr\_\_**(name)

**\_\_getitem\_\_**(key, default=None)

Return self[key].

**\_\_module\_\_** = 'rdflib.extras.infixowl'

**term**(name)

rdflib.extras.infixowl.**CommonNSBindings**(graph, additionalNS=None)

Takes a graph and binds the common namespaces (rdf,rdfs, & owl)

rdflib.extras.infixowl.**ComponentTerms**(cls)

Takes a Class instance and returns a generator over the classes that are involved in its definition, ignoring unnamed classes

`rdflib.extras.infixowl.DeepClassClear(class_to_prune)`

Recursively clear the given class, continuing where any related class is an anonymous class

```
>>> EX = Namespace("http://example.com/")
>>> g = Graph()
>>> g.bind("ex", EX, override=False)
>>> Individual.factoryGraph = g
>>> classB = Class(EX.B)
>>> classC = Class(EX.C)
>>> classD = Class(EX.D)
>>> classE = Class(EX.E)
>>> classF = Class(EX.F)
>>> anonClass = EX.someProp @ some @ classD
>>> classF += anonClass
>>> list(anonClass.subClassOf)
[Class: ex:F ]
>>> classA = classE | classF | anonClass
>>> classB += classA
>>> classA.equivalentClass = [Class()]
>>> classB.subClassOf = [EX.someProp @ some @ classC]
>>> classA
( ex:E OR ex:F OR ( ex:someProp SOME ex:D ) )
>>> DeepClassClear(classA)
>>> classA
( )
>>> list(anonClass.subClassOf)
[]
>>> classB
Class: ex:B SubClassOf: ( ex:someProp SOME ex:C )
```

```
>>> otherClass = classD | anonClass
>>> otherClass
( ex:D OR ( ex:someProp SOME ex:D ) )
>>> DeepClassClear(otherClass)
>>> otherClass
( )
>>> otherClass.delete()
>>> list(g.triples((otherClass.identifier, None, None)))
[]
```

**class** `rdflib.extras.infixowl.EnumeratedClass(identifier=None, members=None, graph=None)`

Bases: `OWLRDFListProxy`, `Class`

Class for owl:oneOf forms:

OWL Abstract Syntax is used

**axiom** ::= 'EnumeratedClass'  
           classID ['Deprecated'] { annotation } { individualID } ')'

```
>>> exNs = Namespace("http://example.com/")
>>> g = Graph()
>>> g.bind("ex", exNs, override=False)
>>> Individual.factoryGraph = g
```

(continues on next page)

(continued from previous page)

```

>>> ogbujibros = EnumeratedClass(exNs.ogbujicBros,
...                               members=[exNs.chime,
...                                       exNs.uche,
...                                       exNs.ejike])
>>> ogbujibros
{ ex:chime ex:uche ex:ejike }
>>> col = Collection(g, first(
...     g.objects(predicate=OWL.oneOf, subject=ogbujibros.identifier)))
>>> sorted([g.qname(item) for item in col])
['ex:chime', 'ex:ejike', 'ex:uche']
>>> print(g.serialize(format='n3'))
@prefix ex: <http://example.com/> .
@prefix owl: <http://www.w3.org/2002/07/owl#> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .

ex:ogbujicBros a owl:Class;
    owl:oneOf ( ex:chime ex:uche ex:ejike ) .

```

```
__init__(identifier=None, members=None, graph=None)
```

```
__module__ = 'rdflib.extras.infixowl'
```

```
__repr__()
```

Returns the Manchester Syntax equivalent for this class

```
isPrimitive()
```

```
serialize(graph)
```

```
rdflib.extras.infixowl.GetIdentifiedClasses(graph)
```

```
class rdflib.extras.infixowl.Individual(identifier=None, graph=None)
```

Bases: `object`

A typed individual, the base class of the InfixOWL classes.

```

__dict__ = mappingproxy({'__module__': 'rdflib.extras.infixowl', '__doc__': '\n A
typed individual, the base class of the InfixOWL classes.\n\n ', 'factoryGraph':
<Graph identifier=Ncfefd84db1c94590b1f79b1ef95eb7ea (<class 'rdflib.graph.Graph'>)>,
'serialize': <function Individual.serialize>, '__init__': <function
Individual.__init__>, 'clearInDegree': <function Individual.clearInDegree>,
'clearOutDegree': <function Individual.clearOutDegree>, 'delete': <function
Individual.delete>, 'replace': <function Individual.replace>, '_get_type':
<function Individual._get_type>, '_set_type': <function Individual._set_type>,
'_delete_type': <function TermDeletionHelper.__call__.<locals>._remover>, 'type':
<property object>, '_get_identifier': <function Individual._get_identifier>,
'_set_identifier': <function Individual._set_identifier>, 'identifier': <property
object>, '_get_sameAs': <function Individual._get_sameAs>, '_set_sameAs':
<function Individual._set_sameAs>, '_delete_sameAs': <function
TermDeletionHelper.__call__.<locals>._remover>, 'sameAs': <property object>,
'__dict__': <attribute '__dict__' of 'Individual' objects>, '__weakref__':
<attribute '__weakref__' of 'Individual' objects>, '__annotations__': {}})

```

**\_\_init\_\_**(*identifier=None, graph=None*)

**\_\_module\_\_** = 'rdflib.extras.infixowl'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**clearInDegree**()

Remove references to this individual as an object in the backing store.

**clearOutDegree**()

Remove all statements to this individual as a subject in the backing store. Note that this only removes the statements themselves, not the blank node closure so there is a chance that this will cause orphaned blank nodes to remain in the graph.

**delete**()

Delete the individual from the graph, clearing the in and out degrees.

**factoryGraph** = <Graph identifier=Ncfebd84db1c94590b1f79b1ef95eb7ea (<class 'rdflib.graph.Graph'>>>

**property identifier**

**replace**(*other*)

Replace the individual in the graph with the given other, causing all triples that refer to it to be changed and then delete the individual.

```
>>> g = Graph()
>>> b = Individual(OWL.Restriction, g)
>>> b.type = RDFS.Resource
>>> len(list(b.type))
1
>>> del b.type
>>> len(list(b.type))
0
```

**property sameAs**

**serialize**(*graph*)

**property type**

**class** rdflib.extras.infixowl.**Infix**(*function*)

Bases: `object`

**\_\_call\_\_**(*value1, value2*)

Call self as a function.

```
__dict__ = mappingproxy({'__module__': 'rdflib.extras.infixowl', '__init__':
<function Infix.__init__>, '__rlshift__': <function Infix.__rlshift__>,
'__rshift__': <function Infix.__rshift__>, '__rmatmul__': <function
Infix.__rmatmul__>, '__matmul__': <function Infix.__matmul__>, '__call__':
<function Infix.__call__>, '__dict__': <attribute '__dict__' of 'Infix' objects>,
'__weakref__': <attribute '__weakref__' of 'Infix' objects>, '__doc__': None,
'__annotations__': {}})
```

**\_\_init\_\_**(*function*)

```
__matmul__(other)

__module__ = 'rdflib.extras.infixowl'

__rlshift__(other)

__rmatmul__(other)

__rshift__(other)

__weakref__
    list of weak references to the object (if defined)
exception rdflib.extras.infixowl.MalformedClass
    Bases: ValueError
    Deprecated since version TODO-NEXT-VERSION: This class will be removed in version 7.0.0.
    __module__ = 'rdflib.extras.infixowl'
    __weakref__
        list of weak references to the object (if defined)
exception rdflib.extras.infixowl.MalformedClassError(msg)
    Bases: MalformedClass
    __init__(msg)
    __module__ = 'rdflib.extras.infixowl'
    __repr__()
        Return repr(self).
class rdflib.extras.infixowl.OWLRDFListProxy(rdf_list, members=None, graph=None)
    Bases: object
    __contains__(item)
    __delitem__(key)
    __dict__ = mappingproxy({'__module__': 'rdflib.extras.infixowl', '__init__':
    <function OWLRDFListProxy.__init__>, '__eq__': <function OWLRDFListProxy.__eq__>,
    '__len__': <function OWLRDFListProxy.__len__>, 'index': <function
    OWLRDFListProxy.index>, '__getitem__': <function OWLRDFListProxy.__getitem__>,
    '__setitem__': <function OWLRDFListProxy.__setitem__>, '__delitem__': <function
    OWLRDFListProxy.__delitem__>, 'clear': <function OWLRDFListProxy.clear>,
    '__iter__': <function OWLRDFListProxy.__iter__>, '__contains__': <function
    OWLRDFListProxy.__contains__>, 'append': <function OWLRDFListProxy.append>,
    '__iadd__': <function OWLRDFListProxy.__iadd__>, '__dict__': <attribute '__dict__'
    of 'OWLRDFListProxy' objects>, '__weakref__': <attribute '__weakref__' of
    'OWLRDFListProxy' objects>, '__doc__': None, '__hash__': None, '__annotations__':
    {}})
    __eq__(other)
        Equivalence of boolean class constructors is determined by equivalence of its members
    __getitem__(key)
```



```

__hash__ = None

__iadd__(other)

__init__(rdf_list, members=None, graph=None)

__iter__()

__len__()

__module__ = 'rdflib.extras.infixowl'

__setitem__(key, value)

__weakref__
    list of weak references to the object (if defined)

append(item)

clear()

index(item)

class rdflib.extras.infixowl.Ontology(identifier=None, imports=None, comment=None, graph=None)
    Bases: AnnotatableTerms
    The owl ontology metadata

    __init__(identifier=None, imports=None, comment=None, graph=None)

    __module__ = 'rdflib.extras.infixowl'

    property imports

    setVersion(version)

class rdflib.extras.infixowl.Property(identifier=None, graph=None, base-
    Type=rdflib.term.URIRef('http://www.w3.org/2002/07/owl#ObjectProperty'),
    subPropertyOf=None, domain=None, range=None,
    inverseOf=None, otherType=None, equivalentProperty=None,
    comment=None, verbAnnotations=None, nameAnnotation=None,
    nameIsLabel=False)

    Bases: AnnotatableTerms

    axiom ::= 'DatatypeProperty(' datavaluedPropertyID ['Deprecated']
        { annotation } { 'super(' datavaluedPropertyID ')' } ['Functional'] { 'domain(' description ')' } { 'range('
        dataRange ')' } ')' | 'ObjectProperty(' individualvaluedPropertyID ['Deprecated'] { annotation } { 'super('
        individualvaluedPropertyID ')' } [ 'inverseOf(' individualvaluedPropertyID ')' ] [ 'Symmetric' ] [ 'Func-
        tional' | 'InverseFunctional' | 'Functional' 'InverseFunctional' | 'Transitive' ] { 'domain(' description ')' }
        { 'range(' description ')' } ')'

    __init__(identifier=None, graph=None,
        baseType=rdflib.term.URIRef('http://www.w3.org/2002/07/owl#ObjectProperty'),
        subPropertyOf=None, domain=None, range=None, inverseOf=None, otherType=None,
        equivalentProperty=None, comment=None, verbAnnotations=None, nameAnnotation=None,
        nameIsLabel=False)

    __module__ = 'rdflib.extras.infixowl'

```

**\_\_repr\_\_()**

Return repr(self).

**property domain**

**property extent**

**property inverseOf**

**property range**

**replace(*other*)**

Replace the individual in the graph with the given other, causing all triples that refer to it to be changed and then delete the individual.

```
>>> g = Graph()
>>> b = Individual(OWL.Restriction, g)
>>> b.type = RDFS.Resource
>>> len(list(b.type))
1
>>> del b.type
>>> len(list(b.type))
0
```

**serialize(*graph*)**

**setupVerbAnnotations(*verb\_annotations*)**

OWL properties map to ACE transitive verbs (TV)

There are 6 morphological categories that determine the surface form of an IRI:

singular form of a transitive verb (e.g. mans) plural form of a transitive verb (e.g. man) past  
participle form a transitive verb (e.g. manned)

[http://attempto.ifi.uzh.ch/ace\\_lexicon#TV\\_sg](http://attempto.ifi.uzh.ch/ace_lexicon#TV_sg)      [http://attempto.ifi.uzh.ch/ace\\_lexicon#TV\\_pl](http://attempto.ifi.uzh.ch/ace_lexicon#TV_pl)  
[http://attempto.ifi.uzh.ch/ace\\_lexicon#TV\\_vbg](http://attempto.ifi.uzh.ch/ace_lexicon#TV_vbg)

**property subPropertyOf**

**class** `rdflib.extras.infixowl.Restriction`(*onProperty*, *graph=None*, *allValuesFrom=None*,  
*someValuesFrom=None*, *value=None*, *cardinality=None*,  
*maxCardinality=None*, *minCardinality=None*,  
*identifier=None*)

Bases: `Class`

```
restriction ::= 'restriction(' datavaluedPropertyID dataRestrictionComponent { dataRestrictionComponent } ')'
| 'restriction(' individualvaluedPropertyID individualRestrictionComponent { individualRestrictionComponent } ')'
```

**\_\_eq\_\_(*other*)**

Equivalence of restrictions is determined by equivalence of the property in question and the restriction 'range'

**\_\_hash\_\_()**

```
>>> b = Class(OWL.Restriction)
>>> c = Class(OWL.Restriction)
>>> len(set([b,c]))
1
```

```

__init__(onProperty, graph=None, allValuesFrom=None, someValuesFrom=None, value=None,
         cardinality=None, maxCardinality=None, minCardinality=None, identifier=None)

__module__ = 'rdflib.extras.infixowl'

__repr__()
    Returns the Manchester Syntax equivalent for this restriction

property allValuesFrom

property cardinality

property hasValue

isPrimitive()

property maxCardinality

property minCardinality

property onProperty

restrictionKind()

restrictionKinds =
[rdflib.term.URIRef('http://www.w3.org/2002/07/owl#allValuesFrom'),
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#someValuesFrom'),
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#hasValue'),
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#cardinality'),
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#maxCardinality'),
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#minCardinality')]

serialize(graph)

```

```

>>> g1 = Graph()
>>> g2 = Graph()
>>> EX = Namespace("http://example.com/")
>>> g1.bind("ex", EX, override=False)
>>> g2.bind("ex", EX, override=False)
>>> Individual.factoryGraph = g1
>>> prop = Property(EX.someProp, baseType=OWL.DatatypeProperty)
>>> restr1 = (Property(
...     EX.someProp,
...     baseType=OWL.DatatypeProperty)) @ some @ (Class(EX.Foo))
>>> restr1
( ex:someProp SOME ex:Foo )
>>> restr1.serialize(g2)
>>> Individual.factoryGraph = g2
>>> list(Property(
...     EX.someProp, baseType=None).type
... )
[rdflib.term.URIRef(
    'http://www.w3.org/2002/07/owl#DatatypeProperty')]

```

```

property someValuesFrom

```

```
rdflib.extras.infixowl.classOrIdentifier(thing)
```

```
rdflib.extras.infixowl.classOrTerm(thing)
```

```
rdflib.extras.infixowl.generateQName(graph, uri)
```

```
rdflib.extras.infixowl.manchesterSyntax(thing, store, boolean=None, transientList=False)
```

Core serialization thing is a Class and is processed as a subject store is an RDFLib Graph to be queried about thing

```
rdflib.extras.infixowl.propertyOrIdentifier(thing)
```

## Module contents

### rdflib.namespace package

## Module contents

### Namespace Utilities

RDFLib provides mechanisms for managing Namespaces.

In particular, there is a *Namespace* class that takes as its argument the base URI of the namespace.

```
>>> from rdflib.namespace import Namespace
>>> RDFS = Namespace("http://www.w3.org/1999/02/22-rdf-syntax-ns#")
```

Fully qualified URIs in the namespace can be constructed either by attribute or by dictionary access on Namespace instances:

```
>>> RDFS.seeAlso
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#seeAlso')
>>> RDFS['seeAlso']
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#seeAlso')
```

### Automatic handling of unknown predicates

As a programming convenience, a namespace binding is automatically created when *rdflib.term.URIRef* predicates are added to the graph.

### Importable namespaces

The following namespaces are available by directly importing from rdflib:

- BRICK
- CSVW
- DC
- DCAT
- DCMITYPE

- DCTERMS
- DCAM
- DOAP
- FOAF
- ODRL2
- ORG
- OWL
- PROF
- PROV
- QB
- RDF
- RDFS
- SDO
- SH
- SKOS
- SOSA
- SSN
- TIME
- VANN
- VOID
- WGS
- XSD

```
>>> from rdflib.namespace import RDFS
>>> RDFS.seeAlso
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#seeAlso')
```

**class** rdflib.namespace.BRICK

Bases: *DefinedNamespace*

Brick Ontology classes, properties and entity properties. See <https://brickschema.org/> for more information.

Generated from: <https://github.com/BrickSchema/Brick/releases/download/nightly/Brick.ttl> Date: 2021-09-22T14:32:56

AED: *URIRef* = rdflib.term.URIRef('https://brickschema.org/schema/Brick#AED')

AHU: *URIRef* = rdflib.term.URIRef('https://brickschema.org/schema/Brick#AHU')

Ablutions\_Room: *URIRef* =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Ablutions\_Room')

Absorption\_Chiller: *URIRef* =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Absorption\_Chiller')

```
Acceleration_Time_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Acceleration_Time_Setpoint')

Access_Control_Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Access_Control_Equipment')

Access_Reader: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Access_Reader')

Active_Chilled_Beam: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Active_Chilled_Beam')

Active_Power_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Active_Power_Sensor')

Adjust_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Adjust_Sensor')

Air: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air')

Air_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Alarm')

Air_Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Air_Differential_Pressure_Sensor')

Air_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Air_Differential_Pressure_Setpoint')

Air_Diffuser: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Diffuser')

Air_Enthalpy_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Enthalpy_Sensor')

Air_Flow_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Air_Flow_Deadband_Setpoint')

Air_Flow_Demand_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Flow_Demand_Setpoint')

Air_Flow_Loss_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Flow_Loss_Alarm')

Air_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Flow_Sensor')

Air_Flow_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Flow_Setpoint')

Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Flow_Setpoint_Limit')

Air_Grains_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Grains_Sensor')
```

```
Air_Handler_Unit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Handler_Unit')  
  
Air_Handling_Unit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Handling_Unit')  
  
Air_Humidity_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Humidity_Setpoint')  
  
Air_Loop: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Loop')  
  
Air_Plenum: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Plenum')  
  
Air_Quality_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Quality_Sensor')  
  
Air_Static_Pressure_Step_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Air_Static_Pressure_Step_Parameter')  
  
Air_System: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_System')  
  
Air_Temperature_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Temperature_Alarm')  
  
Air_Temperature_Integral_Time_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Air_Temperature_Integral_Time_Parameter')  
  
Air_Temperature_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Temperature_Sensor')  
  
Air_Temperature_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Air_Temperature_Setpoint')  
  
Air_Temperature_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Air_Temperature_Setpoint_Limit')  
  
Air_Temperature_Step_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Air_Temperature_Step_Parameter')  
  
Air_Wet_Bulb_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Air_Wet_Bulb_Temperature_Sensor')  
  
Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Alarm')  
  
Alarm_Delay_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Alarm_Delay_Parameter')  
  
Angle_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Angle_Sensor')  
  
Auditorium: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Auditorium')
```

Automated\_External\_Defibrillator: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Automated_External_Defibrillator')`

Automatic\_Mode\_Command: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Automatic_Mode_Command')`

Availability\_Status: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Availability_Status')`

Average\_Cooling\_Demand\_Sensor: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Average_Cooling_Demand_Sensor')`

Average\_Discharge\_Air\_Flow\_Sensor: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Average_Discharge_Air_Flow_Sensor')`

Average\_Exhaust\_Air\_Static\_Pressure\_Sensor: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Average_Exhaust_Air_Static_Pressure_Sensor')`

Average\_Heating\_Demand\_Sensor: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Average_Heating_Demand_Sensor')`

Average\_Supply\_Air\_Flow\_Sensor: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Average_Supply_Air_Flow_Sensor')`

Average\_Zone\_Air\_Temperature\_Sensor: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Average_Zone_Air_Temperature_Sensor')`

Baseboard\_Radiator: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Baseboard_Radiator')`

Basement: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Basement')`

Battery: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Battery')`

Battery\_Energy\_Storage\_System: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Battery_Energy_Storage_System')`

Battery\_Room: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Battery_Room')`

Battery\_Voltage\_Sensor: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Battery_Voltage_Sensor')`

Bench\_Space: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bench_Space')`

Blowdown\_Water: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Blowdown_Water')`

Boiler: `URIRef` = `rdflib.term.URIRef('https://brickschema.org/schema/Brick#Boiler')`

Booster\_Fan: `URIRef` =  
`rdflib.term.URIRef('https://brickschema.org/schema/Brick#Booster_Fan')`



```
Box_Mode_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Box_Mode_Command')

Break_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Break_Room')

Breaker_Panel: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Breaker_Panel')

Breakroom: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Breakroom')

Broadcast_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Broadcast_Room')

Building: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Building')

Building_Air: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Building_Air')

Building_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Building_Air_Humidity_Setpoint')

Building_Air_Static_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Building_Air_Static_Pressure_Sensor')

Building_Air_Static_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Building_Air_Static_Pressure_Setpoint')

Building_Chilled_Water_Meter: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Building_Chilled_Water_Meter')

Building_Electrical_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Building_Electrical_Meter')

Building_Gas_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Building_Gas_Meter')

Building_Hot_Water_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Building_Hot_Water_Meter')

Building_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Building_Meter')

Building_Water_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Building_Water_Meter')

Bus_Riser: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bus_Riser')

Bypass_Air: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bypass_Air')

Bypass_Air_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bypass_Air_Flow_Sensor')
```

```
Bypass_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Bypass_Air_Humidity_Setpoint')

Bypass_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bypass_Command')

Bypass_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bypass_Valve')

Bypass_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bypass_Water')

Bypass_Water_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Bypass_Water_Flow_Sensor')

Bypass_Water_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Bypass_Water_Flow_Setpoint')

CAV: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#CAV')

CO: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO')

CO2: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO2')

CO2_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO2_Alarm')

CO2_Differential_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO2_Differential_Sensor')

CO2_Level_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO2_Level_Sensor')

CO2_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO2_Sensor')

CO2_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO2_Setpoint')

CO_Differential_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO_Differential_Sensor')

CO_Level_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO_Level_Sensor')

CO_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#CO_Sensor')

CRAC: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#CRAC')

Cafeteria: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cafeteria')

Camera: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Camera')

Capacity_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Capacity_Sensor')
```

```
Ceiling_Fan: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Ceiling_Fan')

Centrifugal_Chiller: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Centrifugal_Chiller')

Change_Filter_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Change_Filter_Alarm')

Chilled_Beam: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Beam')

Chilled_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water')

Chilled_Water_Coil: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water_Coil')

Chilled_Water_Differential_Pressure_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Differential_Pressure_Deadband_Setpoint')

Chilled_Water_Differential_Pressure_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Differential_Pressure_Integral_Time_Parameter')

Chilled_Water_Differential_Pressure_Load_Shed_Reset_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Differential_Pressure_Load_Shed_Reset_Status')

Chilled_Water_Differential_Pressure_Load_Shed_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Differential_Pressure_Load_Shed_Setpoint')

Chilled_Water_Differential_Pressure_Load_Shed_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Differential_Pressure_Load_Shed_Status')

Chilled_Water_Differential_Pressure_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Differential_Pressure_Proportional_Band_Parameter')

Chilled_Water_Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Differential_Pressure_Sensor')

Chilled_Water_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Differential_Pressure_Setpoint')

Chilled_Water_Differential_Pressure_Step_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Differential_Pressure_Step_Parameter')

Chilled_Water_Differential_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
/brickschema.org/schema/Brick#Chilled_Water_Differential_Temperature_Sensor')
```

```

Chilled_Water_Discharge_Flow_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Discharge_Flow_Sensor')

Chilled_Water_Discharge_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Discharge_Flow_Setpoint')

Chilled_Water_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water_Flow_Sensor')

Chilled_Water_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Chilled_Water_Flow_Setpoint')

Chilled_Water_Loop: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water_Loop')

Chilled_Water_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water_Meter')

Chilled_Water_Pump: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water_Pump')

Chilled_Water_Pump_Differential_Pressure_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Chilled_Water_Pump_Differential_Pressure_Deadband_Setpoint')

Chilled_Water_Return_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Chilled_Water_Return_Flow_Sensor')

Chilled_Water_Return_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Return_Temperature_Sensor')

Chilled_Water_Static_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Static_Pressure_Setpoint')

Chilled_Water_Supply_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Chilled_Water_Supply_Flow_Sensor')

Chilled_Water_Supply_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Supply_Flow_Setpoint')

Chilled_Water_Supply_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Supply_Temperature_Sensor')

Chilled_Water_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water_System')

Chilled_Water_System_Enable_Command: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_System_Enable_Command')

Chilled_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Chilled_Water_Temperature_Sensor')

Chilled_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Chilled_Water_Temperature_Setpoint')

```

```

Chilled_Water_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chilled_Water_Valve')

Chiller: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Chiller')

Class: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Class')

Close_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Close_Limit')

Coil: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Coil')

Cold_Box: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cold_Box')

Coldest_Zone_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Coldest_Zone_Air_Temperature_Sensor')

Collection: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Collection')

Collection_Basin_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Collection_Basin_Water')

Collection_Basin_Water_Heater: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Collection_Basin_Water_Heater')

Collection_Basin_Water_Level_Alarm: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Collection_Basin_Water_Level_Alarm')

Collection_Basin_Water_Level_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Collection_Basin_Water_Level_Sensor')

Collection_Basin_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Collection_Basin_Water_Temperature_Sensor')

Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Command')

Common_Space: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Common_Space')

Communication_Loss_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Communication_Loss_Alarm')

Compressor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Compressor')

Computer_Room_Air_Conditioning: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Computer_Room_Air_Conditioning')

Concession: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Concession')

Condensate_Leak_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Condensate_Leak_Alarm')

```

```

Condenser: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Condenser')

Condenser_Heat_Exchanger: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Condenser_Heat_Exchanger')

Condenser_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Condenser_Water')

Condenser_Water_Bypass_Valve: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Condenser_Water_Bypass_Valve')

Condenser_Water_Isolation_Valve: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Condenser_Water_Isolation_Valve')

Condenser_Water_Pump: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Condenser_Water_Pump')

Condenser_Water_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Condenser_Water_System')

Condenser_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Condenser_Water_Temperature_Sensor')

Condenser_Water_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Condenser_Water_Valve')

Condensing_Natural_Gas_Boiler: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Condensing_Natural_Gas_Boiler')

Conductivity_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Conductivity_Sensor')

Conference_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Conference_Room')

Constant_Air_Volume_Box: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Constant_Air_Volume_Box')

Contact_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Contact_Sensor')

Control_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Control_Room')

Cooling_Coil: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Coil')

Cooling_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Command')

Cooling_Demand_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Demand_Sensor')

Cooling_Demand_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Demand_Setpoint')

```

```

Cooling_Discharge_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Cooling_Discharge_Air_Flow_Setpoint')

Cooling_Discharge_Air_Temperature_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Cooling_Discharge_Air_Temperature_Deadband_Setpoint')

Cooling_Discharge_Air_Temperature_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Cooling_Discharge_Air_Temperature_Integral_Time_Parameter')

Cooling_Discharge_Air_Temperature_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Cooling_Discharge_Air_Temperature_Proportional_Band_Parameter')

Cooling_Start_Stop_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Start_Stop_Status')

Cooling_Supply_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Cooling_Supply_Air_Flow_Setpoint')

Cooling_Supply_Air_Temperature_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Cooling_Supply_Air_Temperature_Deadband_Setpoint')

Cooling_Supply_Air_Temperature_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Cooling_Supply_Air_Temperature_Integral_Time_Parameter')

Cooling_Supply_Air_Temperature_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Cooling_Supply_Air_Temperature_Proportional_Band_Parameter')

Cooling_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Cooling_Temperature_Setpoint')

Cooling_Tower: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Tower')

Cooling_Tower_Fan: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Tower_Fan')

Cooling_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cooling_Valve')

Copy_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Copy_Room')

Core_Temperature_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Core_Temperature_Sensor')

Core_Temperature_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Core_Temperature_Setpoint')

Cubicle: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cubicle')

```



```
Current_Imbalance_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Current_Imbalance_Sensor')  
  
Current_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Current_Limit')  
  
Current_Output_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Current_Output_Sensor')  
  
Current_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Current_Sensor')  
  
Curtailment_Override_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Curtailment_Override_Command')  
  
Cycle_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Cycle_Alarm')  
  
DC_Bus_Voltage_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#DC_Bus_Voltage_Sensor')  
  
DOAS: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#DOAS')  
  
Damper: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Damper')  
  
Damper_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Damper_Command')  
  
Damper_Position_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Damper_Position_Command')  
  
Damper_Position_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Damper_Position_Sensor')  
  
Damper_Position_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Damper_Position_Setpoint')  
  
Deadband_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Deadband_Setpoint')  
  
Deceleration_Time_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Deceleration_Time_Setpoint')  
  
Dedicated_Outdoor_Air_System_Unit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Dedicated_Outdoor_Air_System_Unit')  
  
Dehumidification_Start_Stop_Status: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Dehumidification_Start_Stop_Status')  
  
Deionised_Water_Conductivity_Sensor: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Deionised_Water_Conductivity_Sensor')  
  
Deionised_Water_Level_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Deionised_Water_Level_Sensor')  
  
Deionized_Water: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Deionized_Water')
```



```
Deionized_Water_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Deionized_Water_Alarm')  
  
Delay_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Delay_Parameter')  
  
Demand_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Demand_Sensor')  
  
Demand_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Demand_Setpoint')  
  
Derivative_Gain_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Derivative_Gain_Parameter')  
  
Derivative_Time_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Derivative_Time_Parameter')  
  
Detention_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Detention_Room')  
  
Dew_Point_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Dew_Point_Setpoint')  
  
Dewpoint_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Dewpoint_Sensor')  
  
Differential_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Air_Temperature_Setpoint')  
  
Differential_Pressure_Bypass_Valve: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Pressure_Bypass_Valve')  
  
Differential_Pressure_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Pressure_Deadband_Setpoint')  
  
Differential_Pressure_Integral_Time_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Pressure_Integral_Time_Parameter')  
  
Differential_Pressure_Load_Shed_Status: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Pressure_Load_Shed_Status')  
  
Differential_Pressure_Proportional_Band: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Pressure_Proportional_Band')  
  
Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Differential_Pressure_Sensor')  
  
Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Differential_Pressure_Setpoint')  
  
Differential_Pressure_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Pressure_Setpoint_Limit')  
  
Differential_Pressure_Step_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Differential_Pressure_Step_Parameter')
```

```
Differential_Speed_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Differential_Speed_Sensor')  
  
Differential_Speed_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Differential_Speed_Setpoint')  
  
Differential_Supply_Return_Water_Temperature_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Differential_Supply_Return_Water_Temperature_Sensor')  
  
Dimmer: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Dimmer')  
  
Direct_Expansion_Cooling_Coil: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Direct_Expansion_Cooling_Coil')  
  
Direct_Expansion_Heating_Coil: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Direct_Expansion_Heating_Coil')  
  
Direction_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Direction_Command')  
  
Direction_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Direction_Sensor')  
  
Direction_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Direction_Status')  
  
Disable_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Disable_Command')  
  
Disable_Differential_Enthalpy_Command: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Disable_Differential_Enthalpy_Command')  
  
Disable_Differential_Temperature_Command: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Disable_Differential_Temperature_Command')  
  
Disable_Fixed_Enthalpy_Command: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Disable_Fixed_Enthalpy_Command')  
  
Disable_Fixed_Temperature_Command: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Disable_Fixed_Temperature_Command')  
  
Disable_Hot_Water_System_Outside_Air_Temperature_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Disable_Hot_Water_System_Outside_Air_Temperature_Setpoint')  
  
Disable_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Disable_Status')  
  
Discharge_Air: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air')  
  
Discharge_Air_Dewpoint_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Discharge_Air_Dewpoint_Sensor')  
  
Discharge_Air_Duct_Pressure_Status: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Discharge_Air_Duct_Pressure_Status')
```

```
Discharge_Air_Flow_Demand_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Flow_Demand_Setpoint')

Discharge_Air_Flow_High_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Flow_High_Reset_Setpoint')

Discharge_Air_Flow_Low_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Flow_Low_Reset_Setpoint')

Discharge_Air_Flow_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Flow_Reset_Setpoint')

Discharge_Air_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Flow_Sensor')

Discharge_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Flow_Setpoint')

Discharge_Air_Humidity_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Humidity_Sensor')

Discharge_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Humidity_Setpoint')

Discharge_Air_Smoke_Detection_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Smoke_Detection_Alarm')

Discharge_Air_Static_Pressure_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Static_Pressure_Deadband_Setpoint')

Discharge_Air_Static_Pressure_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Static_Pressure_Integral_Time_Parameter')

Discharge_Air_Static_Pressure_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Static_Pressure_Proportional_Band_Parameter')

Discharge_Air_Static_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Static_Pressure_Sensor')

Discharge_Air_Static_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Static_Pressure_Setpoint')

Discharge_Air_Static_Pressure_Step_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Static_Pressure_Step_Parameter')

Discharge_Air_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Alarm')

Discharge_Air_Temperature_Cooling_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Cooling_Setpoint')

Discharge_Air_Temperature_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Deadband_Setpoint')
```

```
Discharge_Air_Temperature_Heating_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Heating_Setpoint')

Discharge_Air_Temperature_High_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_High_Reset_Setpoint')

Discharge_Air_Temperature_Low_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Low_Reset_Setpoint')

Discharge_Air_Temperature_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Proportional_Band_Parameter')

Discharge_Air_Temperature_Reset_Differential_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Reset_Differential_Setpoint')

Discharge_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Sensor')

Discharge_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Setpoint')

Discharge_Air_Temperature_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Setpoint_Limit')

Discharge_Air_Temperature_Step_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Temperature_Step_Parameter')

Discharge_Air_Velocity_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Air_Velocity_Pressure_Sensor')

Discharge_Chilled_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Chilled_Water')

Discharge_Fan: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Fan')

Discharge_Hot_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Hot_Water')

Discharge_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Water')

Discharge_Water_Differential_Pressure_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Water_Differential_Pressure_Deadband_Setpoint')

Discharge_Water_Differential_Pressure_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Water_Differential_Pressure_Integral_Time_Parameter')

Discharge_Water_Differential_Pressure_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Discharge_Water_Differential_Pressure_Proportional_Band_Parameter')
```

```
Discharge_Water_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Discharge_Water_Flow_Sensor')

Discharge_Water_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Discharge_Water_Flow_Setpoint')

Discharge_Water_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Discharge_Water_Temperature_Alarm')

Discharge_Water_Temperature_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Discharge_Water_Temperature_Proportional_Band_Parameter')

Discharge_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Discharge_Water_Temperature_Sensor')

Discharge_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Discharge_Water_Temperature_Setpoint')

Disconnect_Switch: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Disconnect_Switch')

Displacement_Flow_Air_Diffuser: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Displacement_Flow_Air_Diffuser')

Distribution_Frame: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Distribution_Frame')

Domestic_Hot_Water_Supply_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Domestic_Hot_Water_Supply_Temperature_Sensor')

Domestic_Hot_Water_Supply_Temperature_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Domestic_Hot_Water_Supply_Temperature_Setpoint')

Domestic_Hot_Water_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Domestic_Hot_Water_System')

Domestic_Hot_Water_System_Enable_Command: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Domestic_Hot_Water_System_Enable_Command')

Domestic_Hot_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Domestic_Hot_Water_Temperature_Setpoint')

Domestic_Hot_Water_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Domestic_Hot_Water_Valve')

Domestic_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Domestic_Water')

Domestic_Water_Loop: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Domestic_Water_Loop')

Drench_Hose: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Drench_Hose')
```

```
Drive_Ready_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Drive_Ready_Status')  
  
Duration_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Duration_Sensor')  
  
ESS_Panel: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#ESS_Panel')  
  
EconCycle_Start_Stop_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#EconCycle_Start_Stop_Status')  
  
Economizer: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Economizer')  
  
Economizer_Damper: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Economizer_Damper')  
  
Effective_Air_Temperature_Cooling_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Air_Temperature_Cooling_Setpoint')  
  
Effective_Air_Temperature_Heating_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Air_Temperature_Heating_Setpoint')  
  
Effective_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Air_Temperature_Setpoint')  
  
Effective_Discharge_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Discharge_Air_Temperature_Setpoint')  
  
Effective_Return_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Return_Air_Temperature_Setpoint')  
  
Effective_Room_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Room_Air_Temperature_Setpoint')  
  
Effective_Supply_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Supply_Air_Temperature_Setpoint')  
  
Effective_Zone_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Effective_Zone_Air_Temperature_Setpoint')  
  
Electric_Baseboard_Radiator: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Electric_Baseboard_Radiator')  
  
Electric_Boiler: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Electric_Boiler')  
  
Electric_Radiator: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Electric_Radiator')  
  
Electrical_Equipment: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Electrical_Equipment')  
  
Electrical_Meter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Electrical_Meter')
```



```
Electrical_Power_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Electrical_Power_Sensor')  
  
Electrical_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Electrical_Room')  
  
Electrical_System: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Electrical_System')  
  
Elevator: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Elevator')  
  
Elevator_Shaft: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Elevator_Shaft')  
  
Elevator_Space: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Elevator_Space')  
  
Embedded_Surface_System_Panel: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Embedded_Surface_System_Panel')  
  
Embedded_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Embedded_Temperature_Sensor')  
  
Embedded_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Embedded_Temperature_Setpoint')  
  
Emergency_Air_Flow_System: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Emergency_Air_Flow_System')  
  
Emergency_Air_Flow_System_Status: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Emergency_Air_Flow_System_Status')  
  
Emergency_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Emergency_Alarm')  
  
Emergency_Generator_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Emergency_Generator_Alarm')  
  
Emergency_Generator_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Emergency_Generator_Status')  
  
Emergency_Phone: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Emergency_Phone')  
  
Emergency_Power_Off_System: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Emergency_Power_Off_System')  
  
Emergency_Power_Off_System_Activated_By_High_Temperature_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Emergency_Power_Off_System_Activated_By_High_Temperature_Status')  
  
Emergency_Power_Off_System_Activated_By_Leak_Detection_System_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Emergency_Power_Off_System_Activated_By_Leak_Detection_System_Status')
```

```
Emergency_Power_Off_System_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Emergency_Power_Off_System_Status')

Emergency_Push_Button_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Emergency_Push_Button_Status')

Emergency_Wash_Station: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Emergency_Wash_Station')

Employee_Entrance_Lobby: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Employee_Entrance_Lobby')

Enable_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enable_Command')

Enable_Differential_Enthalpy_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enable_Differential_Enthalpy_Command')

Enable_Differential_Temperature_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enable_Differential_Temperature_Command')

Enable_Fixed_Enthalpy_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enable_Fixed_Enthalpy_Command')

Enable_Fixed_Temperature_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enable_Fixed_Temperature_Command')

Enable_Hot_Water_System_Outside_Air_Temperature_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enable_Hot_Water_System_Outside_Air_Temperature_Setpoint')

Enable_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enable_Status')

Enclosed_Office: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enclosed_Office')

Energy_Generation_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Energy_Generation_System')

Energy_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Energy_Sensor')

Energy_Storage: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Energy_Storage')

Energy_Storage_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Energy_Storage_System')

Energy_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Energy_System')

Energy_Usage_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Energy_Usage_Sensor')
```



```
Energy_Zone: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Energy_Zone')

Entering_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Entering_Water')

Entering_Water_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Entering_Water_Flow_Sensor')

Entering_Water_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Entering_Water_Flow_Setpoint')

Entering_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Entering_Water_Temperature_Sensor')

Entering_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Entering_Water_Temperature_Setpoint')

Enthalpy_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enthalpy_Sensor')

Enthalpy_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Enthalpy_Setpoint')

Entrance: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Entrance')

Environment_Box: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Environment_Box')

Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Equipment')

Equipment_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Equipment_Room')

Evaporative_Heat_Exchanger: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Evaporative_Heat_Exchanger')

Even_Month_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Even_Month_Status')

Exercise_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exercise_Room')

Exhaust_Air: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air')

Exhaust_Air_Dewpoint_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Exhaust_Air_Dewpoint_Sensor')

Exhaust_Air_Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Exhaust_Air_Differential_Pressure_Sensor')

Exhaust_Air_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Exhaust_Air_Differential_Pressure_Setpoint')
```

```
Exhaust_Air_Flow_Integral_Time_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Flow_Integral_Time_Parameter')

Exhaust_Air_Flow_Proportional_Band_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Flow_Proportional_Band_Parameter')

Exhaust_Air_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Flow_Sensor')

Exhaust_Air_Flow_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Flow_Setpoint')

Exhaust_Air_Humidity_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Humidity_Sensor')

Exhaust_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Humidity_Setpoint')

Exhaust_Air_Stack_Flow_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Stack_Flow_Deadband_Setpoint')

Exhaust_Air_Stack_Flow_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Stack_Flow_Integral_Time_Parameter')

Exhaust_Air_Stack_Flow_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Stack_Flow_Proportional_Band_Parameter')

Exhaust_Air_Stack_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Stack_Flow_Sensor')

Exhaust_Air_Stack_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Stack_Flow_Setpoint')

Exhaust_Air_Static_Pressure_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Static_Pressure_Proportional_Band_Parameter')

Exhaust_Air_Static_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Static_Pressure_Sensor')

Exhaust_Air_Static_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Static_Pressure_Setpoint')

Exhaust_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Temperature_Sensor')

Exhaust_Air_Velocity_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Air_Velocity_Pressure_Sensor')

Exhaust_Damper: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Damper')

Exhaust_Fan: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Exhaust_Fan')
```

```
Exhaust_Fan_Disable_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Exhaust_Fan_Disable_Command')

Exhaust_Fan_Enable_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Exhaust_Fan_Enable_Command')

Eye_Wash_Station: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Eye_Wash_Station')

FCU: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#FCU')

Failure_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Failure_Alarm')

Fan: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fan')

Fan_Coil_Unit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fan_Coil_Unit')

Fan_On_Off_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fan_On_Off_Status')

Fan_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fan_Status')

Fan_VFD: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fan_VFD')

Fault_Reset_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fault_Reset_Command')

Fault_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fault_Status')

Field_Of_Play: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Field_Of_Play')

Filter: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Filter')

Filter_Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Filter_Differential_Pressure_Sensor')

Filter_Reset_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Filter_Reset_Command')

Filter_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Filter_Status')

Final_Filter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Final_Filter')

Fire_Control_Panel: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fire_Control_Panel')

Fire_Safety_Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fire_Safety_Equipment')
```

```
Fire_Safety_System: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fire_Safety_System')  
  
Fire_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fire_Sensor')  
  
Fire_Zone: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fire_Zone')  
  
First_Aid_Kit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#First_Aid_Kit')  
  
First_Aid_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#First_Aid_Room')  
  
Floor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Floor')  
  
Flow_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Flow_Sensor')  
  
Flow_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Flow_Setpoint')  
  
Fluid: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fluid')  
  
Food_Service_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Food_Service_Room')  
  
Formaldehyde_Level_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Formaldehyde_Level_Sensor')  
  
Freeze_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Freeze_Status')  
  
Freezer: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Freezer')  
  
Frequency_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Frequency_Command')  
  
Frequency_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Frequency_Sensor')  
  
Fresh_Air_Fan: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fresh_Air_Fan')  
  
Fresh_Air_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fresh_Air_Setpoint_Limit')  
  
Frost: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Frost')  
  
Frost_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Frost_Sensor')  
  
Fuel_Oil: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fuel_Oil')
```

```
Fume_Hood: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fume_Hood')

Fume_Hood_Air_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Fume_Hood_Air_Flow_Sensor')

Furniture: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Furniture')

Gain_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gain_Parameter')

Gas: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gas')

Gas_Distribution: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gas_Distribution')

Gas_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gas_Meter')

Gas_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gas_Sensor')

Gas_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gas_System')

Gas_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gas_Valve')

Gasoline: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gasoline')

Gatehouse: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Gatehouse')

Generator_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Generator_Room')

Glycol: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Glycol')

HVAC_Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#HVAC_Equipment')

HVAC_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#HVAC_System')

HVAC_Zone: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#HVAC_Zone')

HX: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#HX')

Hail: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hail')

Hail_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hail_Sensor')
```

```
Hallway: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hallway')  
  
Hazardous_Materials_Storage: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Hazardous_Materials_Storage')  
  
Heat_Exchanger: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heat_Exchanger')  
  
Heat_Exchanger_Supply_Water_Temperature_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Heat_Exchanger_Supply_Water_Temperature_Sensor')  
  
Heat_Exchanger_System_Enable_Status: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Heat_Exchanger_System_Enable_Status')  
  
Heat_Recovery_Hot_Water_System: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Heat_Recovery_Hot_Water_System')  
  
Heat_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heat_Sensor')  
  
Heat_Wheel: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heat_Wheel')  
  
Heat_Wheel_VFD: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heat_Wheel_VFD')  
  
Heating_Coil: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heating_Coil')  
  
Heating_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heating_Command')  
  
Heating_Demand_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heating_Demand_Sensor')  
  
Heating_Demand_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heating_Demand_Setpoint')  
  
Heating_Discharge_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Heating_Discharge_Air_Flow_Setpoint')  
  
Heating_Discharge_Air_Temperature_Deadband_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Heating_Discharge_Air_Temperature_Deadband_Setpoint')  
  
Heating_Discharge_Air_Temperature_Integral_Time_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Heating_Discharge_Air_Temperature_Integral_Time_Parameter')  
  
Heating_Discharge_Air_Temperature_Proportional_Band_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Heating_Discharge_Air_Temperature_Proportional_Band_Parameter')
```

```
Heating_Start_Stop_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heating_Start_Stop_Status')  
  
Heating_Supply_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Heating_Supply_Air_Flow_Setpoint')  
  
Heating_Supply_Air_Temperature_Deadband_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Heating_Supply_Air_Temperature_Deadband_Setpoint')  
  
Heating_Supply_Air_Temperature_Integral_Time_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Heating_Supply_Air_Temperature_Integral_Time_Parameter')  
  
Heating_Supply_Air_Temperature_Proportional_Band_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Heating_Supply_Air_Temperature_Proportional_Band_Parameter')  
  
Heating_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Heating_Temperature_Setpoint')  
  
Heating_Thermal_Power_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Heating_Thermal_Power_Sensor')  
  
Heating_Valve: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Heating_Valve')  
  
Heating_Ventilation_Air_Conditioning_System: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Heating_Ventilation_Air_Conditioning_System')  
  
High_CO2_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#High_CO2_Alarm')  
  
High_Discharge_Air_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#High_Discharge_Air_Temperature_Alarm')  
  
High_Head_Pressure_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#High_Head_Pressure_Alarm')  
  
High_Humidity_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#High_Humidity_Alarm')  
  
High_Humidity_Alarm_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#High_Humidity_Alarm_Parameter')  
  
High_Outside_Air_Lockout_Temperature_Differential_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#High_Outside_Air_Lockout_Temperature_Differential_Parameter')  
  
High_Return_Air_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#High_Return_Air_Temperature_Alarm')  
  
High_Static_Pressure_Cutout_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#High_Static_Pressure_Cutout_Setpoint_Limit')
```



```

High_Temperature_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#High_Temperature_Alarm')

High_Temperature_Alarm_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#High_Temperature_Alarm_Parameter')

High_Temperature_Hot_Water_Return_Temperature_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#High_Temperature_Hot_Water_Return_Temperature_Sensor')

High_Temperature_Hot_Water_Supply_Temperature_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#High_Temperature_Hot_Water_Supply_Temperature_Sensor')

Hold_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hold_Status')

Hospitality_Box: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hospitality_Box')

Hot_Box: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Box')

Hot_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water')

Hot_Water_Baseboard_Radiator: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Hot_Water_Baseboard_Radiator')

Hot_Water_Coil: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Coil')

Hot_Water_Differential_Pressure_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Hot_Water_Differential_Pressure_Deadband_Setpoint')

Hot_Water_Differential_Pressure_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Hot_Water_Differential_Pressure_Integral_Time_Parameter')

Hot_Water_Differential_Pressure_Load_Shed_Reset_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Hot_Water_Differential_Pressure_Load_Shed_Reset_Status')

Hot_Water_Differential_Pressure_Load_Shed_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Hot_Water_Differential_Pressure_Load_Shed_Status')

Hot_Water_Differential_Pressure_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Hot_Water_Differential_Pressure_Proportional_Band_Parameter')

Hot_Water_Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Hot_Water_Differential_Pressure_Sensor')

```



```
Hot_Water_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Differential_Pressure_Setpoint')

Hot_Water_Differential_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Differential_Temperature_Sensor')

Hot_Water_Discharge_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Discharge_Flow_Sensor')

Hot_Water_Discharge_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Discharge_Flow_Setpoint')

Hot_Water_Discharge_Temperature_Load_Shed_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Discharge_Temperature_Load_Shed_Status')

Hot_Water_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Flow_Sensor')

Hot_Water_Flow_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Flow_Setpoint')

Hot_Water_Loop: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Loop')

Hot_Water_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Meter')

Hot_Water_Pump: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Pump')

Hot_Water_Radiator: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Radiator')

Hot_Water_Return_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Return_Flow_Sensor')

Hot_Water_Return_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Return_Temperature_Sensor')

Hot_Water_Static_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Static_Pressure_Setpoint')

Hot_Water_Supply_Flow_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Supply_Flow_Sensor')

Hot_Water_Supply_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Supply_Flow_Setpoint')

Hot_Water_Supply_Temperature_High_Reset_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Supply_Temperature_High_Reset_Setpoint')

Hot_Water_Supply_Temperature_Load_Shed_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Supply_Temperature_Load_Shed_Status')
```

```
Hot_Water_Supply_Temperature_Low_Reset_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Hot_Water_Supply_Temperature_Low_Reset_Setpoint')  
  
Hot_Water_Supply_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Hot_Water_Supply_Temperature_Sensor')  
  
Hot_Water_System: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_System')  
  
Hot_Water_System_Enable_Command: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Hot_Water_System_Enable_Command')  
  
Hot_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Hot_Water_Temperature_Setpoint')  
  
Hot_Water_Usage_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Usage_Sensor')  
  
Hot_Water_Valve: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Hot_Water_Valve')  
  
Humidification_Start_Stop_Status: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Humidification_Start_Stop_Status')  
  
Humidifier: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Humidifier')  
  
Humidifier_Fault_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Humidifier_Fault_Status')  
  
Humidify_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Humidify_Command')  
  
Humidity_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Humidity_Alarm')  
  
Humidity_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Humidity_Parameter')  
  
Humidity_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Humidity_Sensor')  
  
Humidity_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Humidity_Setpoint')  
  
Humidity_Tolerance_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Humidity_Tolerance_Parameter')  
  
IDF: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#IDF')  
  
Ice: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Ice')  
  
Ice_Tank_Leaving_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Ice_Tank_Leaving_Water_Temperature_Sensor')
```

```

Illuminance_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Illuminance_Sensor')

Imbalance_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Imbalance_Sensor')

Induction_Unit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Induction_Unit')

Information_Area: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Information_Area')

Inside_Face_Surface_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Inside_Face_Surface_Temperature_Sensor')

Inside_Face_Surface_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Inside_Face_Surface_Temperature_Setpoint')

Intake_Air_Filter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Intake_Air_Filter')

Intake_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Intake_Air_Temperature_Sensor')

Integral_Gain_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Integral_Gain_Parameter')

Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Integral_Time_Parameter')

Intercom_Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Intercom_Equipment')

Interface: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Interface')

Intrusion_Detection_Equipment: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Intrusion_Detection_Equipment')

Inverter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Inverter')

Isolation_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Isolation_Valve')

Janitor_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Janitor_Room')

Jet_Nozzle_Air_Diffuser: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Jet_Nozzle_Air_Diffuser')

Laboratory: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Laboratory')

Laminar_Flow_Air_Diffuser: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Laminar_Flow_Air_Diffuser')
```

```

Last_Fault_Code_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Last_Fault_Code_Status')

Lead_Lag_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lead_Lag_Command')

Lead_Lag_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lead_Lag_Status')

Lead_On_Off_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lead_On_Off_Command')

Leak_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Leak_Alarm')

Leaving_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Leaving_Water')

Leaving_Water_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Leaving_Water_Flow_Sensor')

Leaving_Water_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Leaving_Water_Flow_Setpoint')

Leaving_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Leaving_Water_Temperature_Sensor')

Leaving_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Leaving_Water_Temperature_Setpoint')

Library: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Library')

Lighting: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lighting')

Lighting_Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lighting_Equipment')

Lighting_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lighting_System')

Lighting_Zone: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lighting_Zone')

Limit: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Limit')

Liquid: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Liquid')

Liquid_CO2: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Liquid_CO2')

Liquid_Detection_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Liquid_Detection_Alarm')

Load_Current_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Load_Current_Sensor')

```

```
Load_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Load_Parameter')  
  
Load_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Load_Setpoint')  
  
Load_Shed_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Load_Shed_Command')  
  
Load_Shed_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Load_Shed_Differential_Pressure_Setpoint')  
  
Load_Shed_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Load_Shed_Setpoint')  
  
Load_Shed_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Load_Shed_Status')  
  
Loading_Dock: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Loading_Dock')  
  
Lobby: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lobby')  
  
Locally_On_Off_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Locally_On_Off_Status')  
  
Location: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Location')  
  
Lockout_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lockout_Status')  
  
Lockout_Temperature_Differential_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Lockout_Temperature_Differential_Parameter')  
  
Loop: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Loop')  
  
Lounge: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lounge')  
  
Louver: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Louver')  
  
Low_Freeze_Protect_Temperature_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Low_Freeze_Protect_Temperature_Parameter')  
  
Low_Humidity_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Low_Humidity_Alarm')  
  
Low_Humidity_Alarm_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Low_Humidity_Alarm_Parameter')  
  
Low_Outside_Air_Lockout_Temperature_Differential_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Low_Outside_Air_Lockout_Temperature_Differential_Parameter')  
  
Low_Outside_Air_Temperature_Enable_Differential_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Low_Outside_Air_Temperature_Enable_Differential_Sensor')
```

```
Low_Outside_Air_Temperature_Enable_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Low_Outside_Air_Temperature_Enable_Setpoint')

Low_Return_Air_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Low_Return_Air_Temperature_Alarm')

Low_Suction_Pressure_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Low_Suction_Pressure_Alarm')

Low_Temperature_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Low_Temperature_Alarm')

Low_Temperature_Alarm_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Low_Temperature_Alarm_Parameter')

Lowest_Exhaust_Air_Static_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Lowest_Exhaust_Air_Static_Pressure_Sensor')

Luminaire: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Luminaire')

Luminaire_Driver: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Luminaire_Driver')

Luminance_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Luminance_Alarm')

Luminance_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Luminance_Command')

Luminance_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Luminance_Sensor')

Luminance_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Luminance_Setpoint')

MAU: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#MAU')

MDF: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#MDF')

Mail_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mail_Room')

Maintenance_Mode_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Maintenance_Mode_Command')

Maintenance_Required_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Maintenance_Required_Alarm')

Majlis: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Majlis')

Makeup_Air_Unit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Makeup_Air_Unit')

Makeup_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Makeup_Water')
```

```
Makeup_Water_Valve: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Makeup_Water_Valve')  
  
Manual_Auto_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Manual_Auto_Status')  
  
Massage_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Massage_Room')  
  
Max_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Max_Air_Flow_Setpoint_Limit')  
  
Max_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Max_Air_Temperature_Setpoint')  
  
Max_Chilled_Water_Differential_Pressure_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Max_Chilled_Water_Differential_Pressure_Setpoint_Limit')  
  
Max_Cooling_Discharge_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Max_Cooling_Discharge_Air_Flow_Setpoint_Limit')  
  
Max_Cooling_Supply_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Max_Cooling_Supply_Air_Flow_Setpoint_Limit')  
  
Max_Discharge_Air_Static_Pressure_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Max_Discharge_Air_Static_Pressure_Setpoint_Limit')  
  
Max_Discharge_Air_Temperature_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Max_Discharge_Air_Temperature_Setpoint_Limit')  
  
Max_Frequency_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Max_Frequency_Command')  
  
Max_Heating_Discharge_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Max_Heating_Discharge_Air_Flow_Setpoint_Limit')  
  
Max_Heating_Supply_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Max_Heating_Supply_Air_Flow_Setpoint_Limit')  
  
Max_Hot_Water_Differential_Pressure_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Max_Hot_Water_Differential_Pressure_Setpoint_Limit')  
  
Max_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Max_Limit')  
  
Max_Load_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Max_Load_Setpoint')  
  
Max_Occupied_Cooling_Discharge_Air_Flow_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Max_Occupied_Cooling_Discharge_Air_Flow_Setpoint_Limit')
```



```

Max_Occupied_Cooling_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Max_Occupied_Cooling_Supply_Air_Flow_Setpoint_Limit')

Max_Occupied_Heating_Discharge_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Max_Occupied_Heating_Discharge_Air_Flow_Setpoint_Limit')

Max_Occupied_Heating_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Max_Occupied_Heating_Supply_Air_Flow_Setpoint_Limit')

Max_Position_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Max_Position_Setpoint_Limit')

Max_Speed_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Max_Speed_Setpoint_Limit')

Max_Static_Pressure_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Max_Static_Pressure_Setpoint_Limit')

Max_Supply_Air_Static_Pressure_Setpoint_Limit: URIRef = rdflib.term.URIRef('https:/
/brickschema.org/schema/Brick#Max_Supply_Air_Static_Pressure_Setpoint_Limit')

Max_Temperature_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Max_Temperature_Setpoint_Limit')

Max_Unoccupied_Cooling_Discharge_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Max_Unoccupied_Cooling_Discharge_Air_Flow_Setpoint_Limit')

Max_Unoccupied_Cooling_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Max_Unoccupied_Cooling_Supply_Air_Flow_Setpoint_Limit')

Max_Unoccupied_Heating_Discharge_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Max_Unoccupied_Heating_Discharge_Air_Flow_Setpoint_Limit')

Max_Unoccupied_Heating_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Max_Unoccupied_Heating_Supply_Air_Flow_Setpoint_Limit')

Max_Water_Level_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Max_Water_Level_Alarm')

Max_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Max_Water_Temperature_Setpoint')

Measurable: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Measurable')

Mechanical_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mechanical_Room')

```



```
Media_Hot_Desk: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Media_Hot_Desk')

Media_Production_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Media_Production_Room')

Media_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Media_Room')

Medical_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Medical_Room')

Medium_Temperature_Hot_Water_Differential_Pressure_Load_Shed_Reset_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Differential_Pressure_Load_Shed_Reset_Status')

Medium_Temperature_Hot_Water_Differential_Pressure_Load_Shed_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Differential_Pressure_Load_Shed_Setpoint')

Medium_Temperature_Hot_Water_Differential_Pressure_Load_Shed_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Differential_Pressure_Load_Shed_Status')

Medium_Temperature_Hot_Water_Differential_Pressure_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Differential_Pressure_Sensor')

Medium_Temperature_Hot_Water_Differential_Pressure_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Differential_Pressure_Setpoint')

Medium_Temperature_Hot_Water_Discharge_Temperature_High_Reset_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Discharge_Temperature_High_Reset_Setpoint')

Medium_Temperature_Hot_Water_Discharge_Temperature_Low_Reset_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Discharge_Temperature_Low_Reset_Setpoint')

Medium_Temperature_Hot_Water_Return_Temperature_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Return_Temperature_Sensor')

Medium_Temperature_Hot_Water_Supply_Temperature_High_Reset_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Supply_Temperature_High_Reset_Setpoint')

Medium_Temperature_Hot_Water_Supply_Temperature_Load_Shed_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Supply_Temperature_Load_Shed_Setpoint')

Medium_Temperature_Hot_Water_Supply_Temperature_Load_Shed_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Medium_Temperature_Hot_Water_Supply_Temperature_Load_Shed_Status')
```

```
Medium_Temperature_Hot_Water_Supply_Temperature_Low_Reset_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Medium_Temperature_Hot_Water_Supply_Temperature_Low_Reset_Setpoint')  
  
Medium_Temperature_Hot_Water_Supply_Temperature_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Medium_Temperature_Hot_Water_Supply_Temperature_Sensor')  
  
Meter: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Meter')  
  
Methane_Level_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Methane_Level_Sensor')  
  
Min_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Min_Air_Flow_Setpoint_Limit')  
  
Min_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Min_Air_Temperature_Setpoint')  
  
Min_Chilled_Water_Differential_Pressure_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Min_Chilled_Water_Differential_Pressure_Setpoint_Limit')  
  
Min_Cooling_Discharge_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Min_Cooling_Discharge_Air_Flow_Setpoint_Limit')  
  
Min_Cooling_Supply_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Min_Cooling_Supply_Air_Flow_Setpoint_Limit')  
  
Min_Discharge_Air_Static_Pressure_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Min_Discharge_Air_Static_Pressure_Setpoint_Limit')  
  
Min_Discharge_Air_Temperature_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Min_Discharge_Air_Temperature_Setpoint_Limit')  
  
Min_Fresh_Air_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Min_Fresh_Air_Setpoint_Limit')  
  
Min_Heating_Discharge_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Min_Heating_Discharge_Air_Flow_Setpoint_Limit')  
  
Min_Heating_Supply_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Min_Heating_Supply_Air_Flow_Setpoint_Limit')  
  
Min_Hot_Water_Differential_Pressure_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Min_Hot_Water_Differential_Pressure_Setpoint_Limit')  
  
Min_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Min_Limit')  
  
Min_Occupied_Cooling_Discharge_Air_Flow_Setpoint_Limit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Min_Occupied_Cooling_Discharge_Air_Flow_Setpoint_Limit')
```

```

Min_Occupied_Cooling_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Min_Occupied_Cooling_Supply_Air_Flow_Setpoint_Limit')

Min_Occupied_Heating_Discharge_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Min_Occupied_Heating_Discharge_Air_Flow_Setpoint_Limit')

Min_Occupied_Heating_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Min_Occupied_Heating_Supply_Air_Flow_Setpoint_Limit')

Min_Outside_Air_Flow_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Min_Outside_Air_Flow_Setpoint_Limit')

Min_Position_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Min_Position_Setpoint_Limit')

Min_Speed_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Min_Speed_Setpoint_Limit')

Min_Static_Pressure_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Min_Static_Pressure_Setpoint_Limit')

Min_Supply_Air_Static_Pressure_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://
/brickschema.org/schema/Brick#Min_Supply_Air_Static_Pressure_Setpoint_Limit')

Min_Temperature_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Min_Temperature_Setpoint_Limit')

Min_Unoccupied_Cooling_Discharge_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Min_Unoccupied_Cooling_Discharge_Air_Flow_Setpoint_Limit')

Min_Unoccupied_Cooling_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Min_Unoccupied_Cooling_Supply_Air_Flow_Setpoint_Limit')

Min_Unoccupied_Heating_Discharge_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Min_Unoccupied_Heating_Discharge_Air_Flow_Setpoint_Limit')

Min_Unoccupied_Heating_Supply_Air_Flow_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Min_Unoccupied_Heating_Supply_Air_Flow_Setpoint_Limit')

Min_Water_Level_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Min_Water_Level_Alarm')

Min_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Min_Water_Temperature_Setpoint')

Mixed_Air: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mixed_Air')

```

```
Mixed_Air_Filter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mixed_Air_Filter')  
  
Mixed_Air_Flow_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mixed_Air_Flow_Sensor')  
  
Mixed_Air_Humidity_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mixed_Air_Humidity_Sensor')  
  
Mixed_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Mixed_Air_Humidity_Setpoint')  
  
Mixed_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Mixed_Air_Temperature_Sensor')  
  
Mixed_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Mixed_Air_Temperature_Setpoint')  
  
Mixed_Damper: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mixed_Damper')  
  
Mode_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mode_Command')  
  
Mode_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Mode_Status')  
  
Motion_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motion_Sensor')  
  
Motor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motor')  
  
Motor_Control_Center: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motor_Control_Center')  
  
Motor_Current_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motor_Current_Sensor')  
  
Motor_Direction_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motor_Direction_Status')  
  
Motor_On_Off_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motor_On_Off_Status')  
  
Motor_Speed_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motor_Speed_Sensor')  
  
Motor_Torque_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Motor_Torque_Sensor')  
  
NO2_Level_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#NO2_Level_Sensor')  
  
NVR: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#NVR')  
  
Natural_Gas: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Natural_Gas')
```

```

Natural_Gas_Boiler: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Natural_Gas_Boiler')

Network_Video_Recorder: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Network_Video_Recorder')

No_Water_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#No_Water_Alarm')

Noncondensing_Natural_Gas_Boiler: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Noncondensing_Natural_Gas_Boiler')

Occupancy_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Occupancy_Command')

Occupancy_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Occupancy_Sensor')

Occupancy_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Occupancy_Status')

Occupied_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Air_Temperature_Setpoint')

Occupied_Cooling_Discharge_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Cooling_Discharge_Air_Flow_Setpoint')

Occupied_Cooling_Supply_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Cooling_Supply_Air_Flow_Setpoint')

Occupied_Cooling_Temperature_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Occupied_Cooling_Temperature_Deadband_Setpoint')

Occupied_Discharge_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Discharge_Air_Flow_Setpoint')

Occupied_Discharge_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Discharge_Air_Temperature_Setpoint')

Occupied_Heating_Discharge_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Heating_Discharge_Air_Flow_Setpoint')

Occupied_Heating_Supply_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Heating_Supply_Air_Flow_Setpoint')

Occupied_Heating_Temperature_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Occupied_Heating_Temperature_Deadband_Setpoint')

Occupied_Mode_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Occupied_Mode_Status')

Occupied_Return_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Return_Air_Temperature_Setpoint')

```

```

Occupied_Room_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Room_Air_Temperature_Setpoint')

Occupied_Supply_Air_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Supply_Air_Flow_Setpoint')

Occupied_Supply_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Supply_Air_Temperature_Setpoint')

Occupied_Zone_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Occupied_Zone_Air_Temperature_Setpoint')

Off_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Off_Command')

Off_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Off_Status')

Office: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Office')

Office_Kitchen: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Office_Kitchen')

Oil: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Oil')

On_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#On_Command')

On_Off_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#On_Off_Command')

On_Off_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#On_Off_Status')

On_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#On_Status')

On_Timer_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#On_Timer_Sensor')

Open_Close_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Open_Close_Status')

Open_Heating_Valve_Outside_Air_Temperature_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Open_Heating_Valve_Outside_Air_Temperature_Setpoint')

Open_Office: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Open_Office')

Operating_Mode_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Operating_Mode_Status')

Outdoor_Area: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outdoor_Area')

```



```
Output_Frequency_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Output_Frequency_Sensor')  
  
Output_Voltage_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Output_Voltage_Sensor')  
  
Outside: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside')  
  
Outside_Air: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air')  
  
Outside_Air_CO2_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_CO2_Sensor')  
  
Outside_Air_CO_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_CO_Sensor')  
  
Outside_Air_Dewpoint_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Outside_Air_Dewpoint_Sensor')  
  
Outside_Air_Enthalpy_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Outside_Air_Enthalpy_Sensor')  
  
Outside_Air_Flow_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_Flow_Sensor')  
  
Outside_Air_Flow_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_Flow_Setpoint')  
  
Outside_Air_Grains_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_Grains_Sensor')  
  
Outside_Air_Humidity_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Outside_Air_Humidity_Sensor')  
  
Outside_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Outside_Air_Humidity_Setpoint')  
  
Outside_Air_Lockout_Temperature_Differential_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Outside_Air_Lockout_Temperature_Differential_Parameter')  
  
Outside_Air_Lockout_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Outside_Air_Lockout_Temperature_Setpoint')  
  
Outside_Air_Temperature_Enable_Differential_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Outside_Air_Temperature_Enable_Differential_Sensor')  
  
Outside_Air_Temperature_High_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Outside_Air_Temperature_High_Reset_Setpoint')  
  
Outside_Air_Temperature_Low_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Outside_Air_Temperature_Low_Reset_Setpoint')
```

```

Outside_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_Temperature_Sensor')

Outside_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_Temperature_Setpoint')

Outside_Air_Wet_Bulb_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Air_Wet_Bulb_Temperature_Sensor')

Outside_Damper: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Damper')

Outside_Face_Surface_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Face_Surface_Temperature_Sensor')

Outside_Face_Surface_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Face_Surface_Temperature_Setpoint')

Outside_Illuminance_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Outside_Illuminance_Sensor')

Overload_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Overload_Alarm')

Overridden_Off_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Overridden_Off_Status')

Overridden_On_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Overridden_On_Status')

Overridden_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Overridden_Status')

Override_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Override_Command')

Ozone_Level_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Ozone_Level_Sensor')

PAU: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#PAU')

PID_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PID_Parameter')

PIR_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PIR_Sensor')

PM10_Level_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PM10_Level_Sensor')

PM10_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PM10_Sensor')

PM1_Level_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PM1_Level_Sensor')

```



```
PM1_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PM1_Sensor')

PVT_Panel: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PVT_Panel')

PV_Array: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PV_Array')

PV_Current_Output_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PV_Current_Output_Sensor')

PV_Generation_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PV_Generation_System')

PV_Panel: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PV_Panel')

Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Parameter')

Parking_Level: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Parking_Level')

Parking_Space: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Parking_Space')

Parking_Structure: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Parking_Structure')

Particulate_Matter_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Particulate_Matter_Sensor')

Passive_Chilled_Beam: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Passive_Chilled_Beam')

Peak_Power_Demand_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Peak_Power_Demand_Sensor')

Photovoltaic_Array: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Photovoltaic_Array')

Photovoltaic_Current_Output_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Photovoltaic_Current_Output_Sensor')

Piezoelectric_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Piezoelectric_Sensor')

PlugStrip: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#PlugStrip')

Plumbing_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Plumbing_Room')

Point: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Point')
```

```

Portfolio: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Portfolio')

Position_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Position_Command')

Position_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Position_Limit')

Position_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Position_Sensor')

Potable_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Potable_Water')

Power_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Power_Alarm')

Power_Loss_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Power_Loss_Alarm')

Power_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Power_Sensor')

Prayer_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Prayer_Room')

Pre_Filter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pre_Filter')

Pre_Filter_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pre_Filter_Status')

Preheat_Demand_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Preheat_Demand_Setpoint')

Preheat_Discharge_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Preheat_Discharge_Air_Temperature_Sensor')

Preheat_Hot_Water_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Preheat_Hot_Water_System')

Preheat_Hot_Water_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Preheat_Hot_Water_Valve')

Preheat_Supply_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Preheat_Supply_Air_Temperature_Sensor')

Pressure_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pressure_Alarm')

Pressure_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pressure_Sensor')

Pressure_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pressure_Setpoint')

```

```
Pressure_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pressure_Status')  
  
Private_Office: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Private_Office')  
  
Proportional_Band_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Proportional_Band_Parameter')  
  
Proportional_Gain_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Proportional_Gain_Parameter')  
  
Pump: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pump')  
  
Pump_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pump_Command')  
  
Pump_On_Off_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pump_On_Off_Status')  
  
Pump_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pump_Room')  
  
Pump_VFD: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Pump_VFD')  
  
Quantity: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Quantity')  
  
RC_Panel: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#RC_Panel')  
  
RTU: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#RTU')  
  
RVAV: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#RVAV')  
  
Radiant_Ceiling_Panel: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Radiant_Ceiling_Panel')  
  
Radiant_Panel: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Radiant_Panel')  
  
Radiant_Panel_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Radiant_Panel_Temperature_Sensor')  
  
Radiant_Panel_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Radiant_Panel_Temperature_Setpoint')  
  
Radiation_Hot_Water_System: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Radiation_Hot_Water_System')  
  
Radiator: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Radiator')  
  
Radioactivity_Concentration_Sensor: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Radioactivity_Concentration_Sensor')
```

```
Radon_Concentration_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Radon_Concentration_Sensor')

Rain_Duration_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Rain_Duration_Sensor')

Rain_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Rain_Sensor')

Rated_Speed_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Rated_Speed_Setpoint')

Reactive_Power_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Reactive_Power_Sensor')

Reception: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Reception')

Region: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Region')

Reheat_Hot_Water_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Reheat_Hot_Water_System')

Reheat_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Reheat_Valve')

Relative_Humidity_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Relative_Humidity_Sensor')

Relief_Damper: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Relief_Damper')

Relief_Fan: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Relief_Fan')

Remotely_On_Off_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Remotely_On_Off_Status')

Reset_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Reset_Command')

Reset_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Reset_Setpoint')

Rest_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Rest_Room')

Restroom: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Restroom')

Retail_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Retail_Room')

Return_Air: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air')
```

```

Return_Air_CO2_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air_CO2_Sensor')

Return_Air_CO2_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air_CO2_Setpoint')

Return_Air_CO_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air_CO_Sensor')

Return_Air_Dewpoint_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Return_Air_Dewpoint_Sensor')

Return_Air_Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Return_Air_Differential_Pressure_Sensor')

Return_Air_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Return_Air_Differential_Pressure_Setpoint')

Return_Air_Enthalpy_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Return_Air_Enthalpy_Sensor')

Return_Air_Filter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air_Filter')

Return_Air_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air_Flow_Sensor')

Return_Air_Grains_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air_Grains_Sensor')

Return_Air_Humidity_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Return_Air_Humidity_Sensor')

Return_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Return_Air_Humidity_Setpoint')

Return_Air_Plenum: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Air_Plenum')

Return_Air_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Return_Air_Temperature_Alarm')

Return_Air_Temperature_High_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Return_Air_Temperature_High_Reset_Setpoint')

Return_Air_Temperature_Low_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Return_Air_Temperature_Low_Reset_Setpoint')

Return_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Return_Air_Temperature_Sensor')

Return_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Return_Air_Temperature_Setpoint')

Return_Chilled_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Return_Chilled_Water_Temperature_Setpoint')

```

```
Return_Condenser_Water: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Condenser_Water')  
  
Return_Condenser_Water_Flow_Sensor: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Return_Condenser_Water_Flow_Sensor')  
  
Return_Condenser_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Return_Condenser_Water_Temperature_Sensor')  
  
Return_Condenser_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Return_Condenser_Water_Temperature_Setpoint')  
  
Return_Damper: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Damper')  
  
Return_Fan: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Fan')  
  
Return_Heating_Valve: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Heating_Valve')  
  
Return_Hot_Water: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Hot_Water')  
  
Return_Hot_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Return_Hot_Water_Temperature_Setpoint')  
  
Return_Water: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Water')  
  
Return_Water_Flow_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Return_Water_Flow_Sensor')  
  
Return_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Return_Water_Temperature_Sensor')  
  
Return_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Return_Water_Temperature_Setpoint')  
  
Riser: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Riser')  
  
Rooftop: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Rooftop')  
  
Rooftop_Unit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Rooftop_Unit')  
  
Room: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Room')  
  
Room_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Room_Air_Temperature_Setpoint')  
  
Run_Enable_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Run_Enable_Command')  
  
Run_Request_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Run_Request_Status')
```

```
Run_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Run_Status')

Run_Time_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Run_Time_Sensor')

Safety_Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Safety_Equipment')

Safety_Shower: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Safety_Shower')

Safety_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Safety_System')

Sash_Position_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Sash_Position_Sensor')

Schedule_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Schedule_Temperature_Setpoint')

Security_Equipment: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Security_Equipment')

Security_Service_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Security_Service_Room')

Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Sensor')

Server_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Server_Room')

Service_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Service_Room')

Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Setpoint')

Shading_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Shading_System')

Shared_Office: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Shared_Office')

Short_Cycle_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Short_Cycle_Alarm')

Shower: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Shower')

Site: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Site')

Smoke_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Smoke_Alarm')

Smoke_Detection_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Smoke_Detection_Alarm')
```



```
Solar_Azimuth_Angle_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Solar_Azimuth_Angle_Sensor')

Solar_Radiance_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Solar_Radiance_Sensor')

Solar_Thermal_Collector: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Solar_Thermal_Collector')

Solar_Zenith_Angle_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Solar_Zenith_Angle_Sensor')

Solid: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Solid')

Space: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Space')

Space_Heater: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Space_Heater')

Speed_Reset_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Speed_Reset_Command')

Speed_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Speed_Sensor')

Speed_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Speed_Setpoint')

Speed_Setpoint_Limit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Speed_Setpoint_Limit')

Speed_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Speed_Status')

Sports_Service_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Sports_Service_Room')

Stage_Enable_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Stage_Enable_Command')

Stage_Riser: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Stage_Riser')

Stages_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Stages_Status')

Staircase: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Staircase')

Standby_CRAC: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Standby_CRAC')

Standby_Fan: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Standby_Fan')

Standby_Glycool_Unit_On_Off_Status: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Standby_Glycool_Unit_On_Off_Status')
```



```

Standby_Load_Shed_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Standby_Load_Shed_Command')

Standby_Unit_On_Off_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Standby_Unit_On_Off_Status')

Start_Stop_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Start_Stop_Command')

Start_Stop_Status: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Start_Stop_Status')

Static_Pressure_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Static_Pressure_Deadband_Setpoint')

Static_Pressure_Integral_Time_Parameter: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Static_Pressure_Integral_Time_Parameter')

Static_Pressure_Proportional_Band_Parameter: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Static_Pressure_Proportional_Band_Parameter')

Static_Pressure_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Static_Pressure_Sensor')

Static_Pressure_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Static_Pressure_Setpoint')

Static_Pressure_Setpoint_Limit: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Static_Pressure_Setpoint_Limit')

Static_Pressure_Step_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Static_Pressure_Step_Parameter')

Status: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Status')

Steam: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam')

Steam_Baseboard_Radiator: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam_Baseboard_Radiator')

Steam_Distribution: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam_Distribution')

Steam_On_Off_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam_On_Off_Command')

Steam_Radiator: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam_Radiator')

Steam_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam_System')

Steam_Usage_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam_Usage_Sensor')

Steam_Valve: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Steam_Valve')

```

```
Step_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Step_Parameter')  
  
Storage_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Storage_Room')  
  
Storey: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Storey')  
  
Studio: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Studio')  
  
Substance: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Substance')  
  
Supply_Air: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Air')  
  
Supply_Air_Differential_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Supply_Air_Differential_Pressure_Sensor')  
  
Supply_Air_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Supply_Air_Differential_Pressure_Setpoint')  
  
Supply_Air_Duct_Pressure_Status: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Supply_Air_Duct_Pressure_Status')  
  
Supply_Air_Flow_Demand_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Supply_Air_Flow_Demand_Setpoint')  
  
Supply_Air_Flow_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Air_Flow_Sensor')  
  
Supply_Air_Flow_Setpoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Air_Flow_Setpoint')  
  
Supply_Air_Humidity_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Supply_Air_Humidity_Sensor')  
  
Supply_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Supply_Air_Humidity_Setpoint')  
  
Supply_Air_Integral_Gain_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Supply_Air_Integral_Gain_Parameter')  
  
Supply_Air_Plenum: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Air_Plenum')  
  
Supply_Air_Proportional_Gain_Parameter: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Supply_Air_Proportional_Gain_Parameter')  
  
Supply_Air_Static_Pressure_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Supply_Air_Static_Pressure_Deadband_Setpoint')  
  
Supply_Air_Static_Pressure_Integral_Time_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/  
Brick#Supply_Air_Static_Pressure_Integral_Time_Parameter')
```

```

Supply_Air_Static_Pressure_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Supply_Air_Static_Pressure_Proportional_Band_Parameter')

Supply_Air_Static_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Air_Static_Pressure_Sensor')

Supply_Air_Static_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Air_Static_Pressure_Setpoint')

Supply_Air_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Supply_Air_Temperature_Alarm')

Supply_Air_Temperature_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Air_Temperature_Deadband_Setpoint')

Supply_Air_Temperature_High_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Air_Temperature_High_Reset_Setpoint')

Supply_Air_Temperature_Low_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Air_Temperature_Low_Reset_Setpoint')

Supply_Air_Temperature_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Supply_Air_Temperature_Proportional_Band_Parameter')

Supply_Air_Temperature_Reset_Differential_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Supply_Air_Temperature_Reset_Differential_Setpoint')

Supply_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Supply_Air_Temperature_Sensor')

Supply_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Supply_Air_Temperature_Setpoint')

Supply_Air_Temperature_Step_Parameter: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Air_Temperature_Step_Parameter')

Supply_Air_Velocity_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Air_Velocity_Pressure_Sensor')

Supply_Chilled_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Chilled_Water')

Supply_Chilled_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Chilled_Water_Temperature_Setpoint')

Supply_Condenser_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Condenser_Water')

Supply_Condenser_Water_Flow_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Condenser_Water_Flow_Sensor')

Supply_Condenser_Water_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Supply_Condenser_Water_Temperature_Sensor')

```

```
Supply_Condenser_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Condenser_Water_Temperature_Setpoint')

Supply_Fan: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Fan')

Supply_Hot_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Hot_Water')

Supply_Hot_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Hot_Water_Temperature_Setpoint')

Supply_Water: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water')

Supply_Water_Differential_Pressure_Deadband_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Differential_Pressure_Deadband_Setpoint')

Supply_Water_Differential_Pressure_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Differential_Pressure_Integral_Time_Parameter')

Supply_Water_Differential_Pressure_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Differential_Pressure_Proportional_Band_Parameter')

Supply_Water_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Flow_Sensor')

Supply_Water_Flow_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Flow_Setpoint')

Supply_Water_Temperature_Alarm: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Temperature_Alarm')

Supply_Water_Temperature_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Temperature_Deadband_Setpoint')

Supply_Water_Temperature_Integral_Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Temperature_Integral_Time_Parameter')

Supply_Water_Temperature_Proportional_Band_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Temperature_Proportional_Band_Parameter')

Supply_Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Supply_Water_Temperature_Setpoint')

Surveillance_Camera: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Surveillance_Camera')

Switch: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Switch')
```

```
Switch_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Switch_Room')  
  
Switchgear: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Switchgear')  
  
System: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#System')  
  
System_Enable_Command: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#System_Enable_Command')  
  
System_Shutdown_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#System_Shutdown_Status')  
  
System_Status: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#System_Status')  
  
TABS_Panel: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#TABS_Panel')  
  
TETRA_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#TETRA_Room')  
  
TVOC_Level_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#TVOC_Level_Sensor')  
  
TVOC_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#TVOC_Sensor')  
  
Team_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Team_Room')  
  
Telecom_Room: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Telecom_Room')  
  
Temperature_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Temperature_Alarm')  
  
Temperature_Deadband_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Temperature_Deadband_Setpoint')  
  
Temperature_Differential_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Temperature_Differential_Reset_Setpoint')  
  
Temperature_High_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Temperature_High_Reset_Setpoint')  
  
Temperature_Low_Reset_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Temperature_Low_Reset_Setpoint')  
  
Temperature_Parameter: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Temperature_Parameter')  
  
Temperature_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Temperature_Sensor')
```

```

Temperature_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Temperature_Setpoint')

Temperature_Step_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Temperature_Step_Parameter')

Temperature_Tolerance_Parameter: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Temperature_Tolerance_Parameter')

Temporary_Occupancy_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Temporary_Occupancy_Status')

Terminal_Unit: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Terminal_Unit')

Thermal_Power_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Thermal_Power_Meter')

Thermal_Power_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Thermal_Power_Sensor')

Thermally_Activated_Building_System_Panel: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Thermally_Activated_Building_System_Panel')

Thermostat: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Thermostat')

Ticketing_Booth: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Ticketing_Booth')

Time_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Time_Parameter')

Time_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Time_Setpoint')

Tolerance_Parameter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Tolerance_Parameter')

Torque_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Torque_Sensor')

Touchpanel: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Touchpanel')

Trace_Heat_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Trace_Heat_Sensor')

Transformer: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Transformer')

Transformer_Room: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Transformer_Room')

Tunnel: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Tunnel')

```

```

Underfloor_Air_Plenum: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Underfloor_Air_Plenum')

Underfloor_Air_Plenum_Static_Pressure_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Underfloor_Air_Plenum_Static_Pressure_Sensor')

Underfloor_Air_Plenum_Static_Pressure_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Underfloor_Air_Plenum_Static_Pressure_Setpoint')

Underfloor_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Underfloor_Air_Temperature_Sensor')

Unit_Failure_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Unit_Failure_Alarm')

Unoccupied_Air_Temperature_Cooling_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Air_Temperature_Cooling_Setpoint')

Unoccupied_Air_Temperature_Heating_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Air_Temperature_Heating_Setpoint')

Unoccupied_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Air_Temperature_Setpoint')

Unoccupied_Cooling_Discharge_Air_Flow_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/
Brick#Unoccupied_Cooling_Discharge_Air_Flow_Setpoint')

Unoccupied_Discharge_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Discharge_Air_Temperature_Setpoint')

Unoccupied_Load_Shed_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Unoccupied_Load_Shed_Command')

Unoccupied_Return_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Return_Air_Temperature_Setpoint')

Unoccupied_Room_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Room_Air_Temperature_Setpoint')

Unoccupied_Supply_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Supply_Air_Temperature_Setpoint')

Unoccupied_Zone_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Unoccupied_Zone_Air_Temperature_Setpoint')

Usage_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Usage_Sensor')

VAV: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#VAV')

VFD: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#VFD')

VFD_Enable_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#VFD_Enable_Command')

```



```
Valve: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Valve')

Valve_Command: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Valve_Command')

Valve_Position_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Valve_Position_Sensor')

Variable_Air_Volume_Box: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Variable_Air_Volume_Box')

Variable_Air_Volume_Box_With_Reheat: URIRef = rdflib.term.URIRef('https://
brickschema.org/schema/Brick#Variable_Air_Volume_Box_With_Reheat')

Variable_Frequency_Drive: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Variable_Frequency_Drive')

Velocity_Pressure_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Velocity_Pressure_Sensor')

Velocity_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Velocity_Pressure_Setpoint')

Vent_Operating_Mode_Status: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Vent_Operating_Mode_Status')

Ventilation_Air_Flow_Ratio_Limit: URIRef = rdflib.term.URIRef('https://brickschema.
org/schema/Brick#Ventilation_Air_Flow_Ratio_Limit')

Ventilation_Air_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Ventilation_Air_System')

Vertical_Space: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Vertical_Space')

Video_Intercom: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Video_Intercom')

Video_Surveillance_Equipment: URIRef = rdflib.term.URIRef('https://brickschema.org/
schema/Brick#Video_Surveillance_Equipment')

Visitor_Lobby: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Visitor_Lobby')

Voltage_Imbalance_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Voltage_Imbalance_Sensor')

Voltage_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Voltage_Sensor')

Wardrobe: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Wardrobe')

Warm_Cool_Adjust_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Warm_Cool_Adjust_Sensor')
```



```
Warmest_Zone_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Warmest_Zone_Air_Temperature_Sensor')

Waste_Storage: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Waste_Storage')

Water: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water')

Water_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Alarm')

Water_Differential_Pressure_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Differential_Pressure_Setpoint')

Water_Differential_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Differential_Temperature_Sensor')

Water_Differential_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Differential_Temperature_Setpoint')

Water_Distribution: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Distribution')

Water_Flow_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Flow_Sensor')

Water_Flow_Setpoint: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Flow_Setpoint')

Water_Heater: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Heater')

Water_Level_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Level_Alarm')

Water_Level_Sensor: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Level_Sensor')

Water_Loop: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Loop')

Water_Loss_Alarm: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Loss_Alarm')

Water_Meter: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Meter')

Water_Pump: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Pump')

Water_System: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_System')

Water_Tank: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Tank')
```

```
Water_Temperature_Alarm: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Temperature_Alarm')  
  
Water_Temperature_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Temperature_Sensor')  
  
Water_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Water_Temperature_Setpoint')  
  
Water_Usage_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Usage_Sensor')  
  
Water_Valve: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Water_Valve')  
  
Weather_Station: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Weather_Station')  
  
Wind_Direction_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Wind_Direction_Sensor')  
  
Wind_Speed_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Wind_Speed_Sensor')  
  
Wing: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Wing')  
  
Workshop: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Workshop')  
  
Zone: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Zone')  
  
Zone_Air: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Zone_Air')  
  
Zone_Air_Cooling_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Zone_Air_Cooling_Temperature_Setpoint')  
  
Zone_Air_Dewpoint_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Zone_Air_Dewpoint_Sensor')  
  
Zone_Air_Heating_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#Zone_Air_Heating_Temperature_Setpoint')  
  
Zone_Air_Humidity_Sensor: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#Zone_Air_Humidity_Sensor')  
  
Zone_Air_Humidity_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Zone_Air_Humidity_Setpoint')  
  
Zone_Air_Temperature_Sensor: URIRef = rdflib.term.URIRef('https://brickschema.org/  
schema/Brick#Zone_Air_Temperature_Sensor')  
  
Zone_Air_Temperature_Setpoint: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Zone_Air_Temperature_Setpoint')  
  
Zone_Standby_Load_Shed_Command: URIRef = rdflib.term.URIRef('https://brickschema.  
org/schema/Brick#Zone_Standby_Load_Shed_Command')
```

```
Zone_Unoccupied_Load_Shed_Command: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#Zone_Unoccupied_Load_Shed_Command')

aggregate: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#aggregate')

area: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#area')

azimuth: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#azimuth')

buildingPrimaryFunction: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#buildingPrimaryFunction')

buildingThermalTransmittance: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#buildingThermalTransmittance')

conversionEfficiency: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#conversionEfficiency')

coolingCapacity: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#coolingCapacity')

coordinates: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#coordinates')

currentFlowType: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#currentFlowType')

electricalPhaseCount: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#electricalPhaseCount')

electricalPhases: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#electricalPhases')

feeds: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#feeds')

feedsAir: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#feedsAir')

grossArea: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#grossArea')

hasAddress: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasAddress')

hasAssociatedTag: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasAssociatedTag')

hasInputSubstance: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasInputSubstance')

hasLocation: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasLocation')

hasOutputSubstance: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasOutputSubstance')
```

```
hasPart: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasPart')  
  
hasPoint: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasPoint')  
  
hasQUDTReference: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasQUDTReference')  
  
hasTag: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasTag')  
  
hasTimeseriesId: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasTimeseriesId')  
  
hasUnit: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#hasUnit')  
  
isAssociatedWith: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isAssociatedWith')  
  
isFedBy: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isFedBy')  
  
isLocationOf: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isLocationOf')  
  
isMeasuredBy: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isMeasuredBy')  
  
isPartOf: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isPartOf')  
  
isPointOf: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isPointOf')  
  
isRegulatedBy: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isRegulatedBy')  
  
isTagOf: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#isTagOf')  
  
latitude: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#latitude')  
  
longitude: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#longitude')  
  
measuredModuleConversionEfficiency: URIRef = rdflib.term.URIRef('https://  
brickschema.org/schema/Brick#measuredModuleConversionEfficiency')  
  
measuredPowerOutput: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#measuredPowerOutput')  
  
measures: URIRef =  
rdflib.term.URIRef('https://brickschema.org/schema/Brick#measures')
```

```

netArea: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#netArea')

operationalStage: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#operationalStage')

operationalStageCount: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#operationalStageCount')

panelArea: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#panelArea')

powerComplexity: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#powerComplexity')

powerFlow: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#powerFlow')

ratedModuleConversionEfficiency: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#ratedModuleConversionEfficiency')

ratedPowerOutput: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#ratedPowerOutput')

regulates: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#regulates')

storedAt: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#storedAt')

temperatureCoefficientofPmax: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#temperatureCoefficientofPmax')

thermalTransmittance: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#thermalTransmittance')

tilt: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#tilt')

timeseries: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#timeseries')

value: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#value')

volume: URIRef = rdflib.term.URIRef('https://brickschema.org/schema/Brick#volume')

yearBuilt: URIRef =
rdflib.term.URIRef('https://brickschema.org/schema/Brick#yearBuilt')

```

**class** rdflib.namespace.CSVW

Bases: *DefinedNamespace*

CSVW Namespace Vocabulary Terms

This document describes the RDFS vocabulary description used in the Metadata Vocabulary for Tabular Data [[tabular-metadata]] along with the default JSON-LD Context.

Generated from: <http://www.w3.org/ns/csvw> Date: 2020-05-26 14:19:58.184766

```
Cell: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Cell')
Column: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Column')
Datatype: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Datatype')
Dialect: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Dialect')
Direction: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Direction')
ForeignKey: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#ForeignKey')
JSON: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#JSON')
NumericFormat: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#NumericFormat')
Row: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Row')
Schema: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Schema')
Table: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#Table')
TableGroup: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#TableGroup')
TableReference: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#TableReference')
Transformation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#Transformation')
aboutUrl: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#aboutUrl')
auto: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#auto')
base: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#base')
column: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#column')
columnReference: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#columnReference')
commentPrefix: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#commentPrefix')
csvEncodedTabularData: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#csvEncodedTabularData')
datatype: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#datatype')
decimalChar: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#decimalChar')
default: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#default')
delimiter: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#delimiter')
describes: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#describes')
dialect: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#dialect')
```

```

doubleQuote: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#doubleQuote')
encoding: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#encoding')
foreignKey: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#foreignKey')
format: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#format')
groupChar: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#groupChar')
header: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#header')
headerRowCount: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#headerRowCount')
inherit: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#inherit')
lang: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#lang')
length: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#length')
lineTerminators: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#lineTerminators')
ltr: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#ltr')
maxExclusive: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#maxExclusive')
maxInclusive: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#maxInclusive')
maxLength: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#maxLength')
minExclusive: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#minExclusive')
minInclusive: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#minInclusive')
minLength: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#minLength')
name: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#name')
note: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#note')
null: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#null')
ordered: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#ordered')
pattern: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#pattern')
primaryKey: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#primaryKey')
propertyUrl: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#propertyUrl')
quoteChar: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#quoteChar')
reference: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#reference')
referencedRow: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#referencedRow')
required: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#required')

```



```
resource: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#resource')
row: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#row')
rowTitle: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#rowTitle')
rownum: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#rownum')
rtl: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#rtl')
schemaReference: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#schemaReference')
scriptFormat: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#scriptFormat')
separator: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#separator')
skipBlankRows: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#skipBlankRows')
skipColumns: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#skipColumns')
skipInitialSpace: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#skipInitialSpace')
skipRows: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#skipRows')
source: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#source')
suppressOutput: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#suppressOutput')
table: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#table')
tableDirection: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#tableDirection')
tableSchema: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#tableSchema')
tabularMetadata: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#tabularMetadata')
targetFormat: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#targetFormat')
textDirection: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#textDirection')
title: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#title')
transformations: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/csvw#transformations')
trim: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#trim')
uriTemplate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#uriTemplate')
url: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#url')
valueUrl: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#valueUrl')
```



```
virtual: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/csvw#virtual')
```

```
class rdflib.namespace.ClosedNamespace(uri: str, terms: List[str])
```

Bases: *Namespace*

A namespace with a closed list of members

Trying to create terms not listed is an error

```
__annotations__ = {'_ClosedNamespace__uris': typing.Dict[str, rdflib.term.URIRef]}
```

```
__contains__(ref)
```

Allows to check if a URI is within (starts with) this Namespace.

```
>>> from rdflib import URIRef
>>> namespace = Namespace('http://example.org/')
>>> uri = URIRef('http://example.org/foo')
>>> uri in namespace
True
>>> person_class = namespace['Person']
>>> person_class in namespace
True
>>> obj = URIRef('http://not.example.org/bar')
>>> obj in namespace
False
```

**Parameters**

**ref** (*str*) –

**Return type**

*bool*

```
__dir__()
```

Default dir() implementation.

**Return type**

*List[str]*

```
__getattr__(name)
```

**Parameters**

**name** (*str*) –

**Return type**

*URIRef*

```
__getitem__(key)
```

Return self[key].

**Parameters**

**key** (*str*) –

**Return type**

*URIRef*

```
__module__ = 'rdflib.namespace'
```

```
static __new__(cls, uri, terms)
```

Parameters

- **uri** (`str`) –
- **terms** (`List[str]`) –

```
__repr__()
```

Return repr(self).

Return type

`str`

```
term(name)
```

Parameters

**name** (`str`) –

Return type

`URIRef`

```
property uri: str
```

```
class rdflib.namespace.DC
```

Bases: `DefinedNamespace`

Dublin Core Metadata Element Set, Version 1.1

Generated from: [https://www.dublincore.org/specifications/dublin-core/dcmi-terms/dublin\\_core\\_elements.ttl](https://www.dublincore.org/specifications/dublin-core/dcmi-terms/dublin_core_elements.ttl)

Date: 2020-05-26 14:19:58.671906

**contributor:** `URIRef` =

`rdflib.term.URIRef('http://purl.org/dc/elements/1.1/contributor')`

**coverage:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/coverage')`

**creator:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/creator')`

**date:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/date')`

**description:** `URIRef` =

`rdflib.term.URIRef('http://purl.org/dc/elements/1.1/description')`

**format:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/format')`

**identifier:** `URIRef` =

`rdflib.term.URIRef('http://purl.org/dc/elements/1.1/identifier')`

**language:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/language')`

**publisher:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/publisher')`

**relation:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/relation')`

**rights:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/rights')`

**source:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/source')`

**subject:** `URIRef` = `rdflib.term.URIRef('http://purl.org/dc/elements/1.1/subject')`

```

title: URIRef = rdflib.term.URIRef('http://purl.org/dc/elements/1.1/title')

type: URIRef = rdflib.term.URIRef('http://purl.org/dc/elements/1.1/type')

class rdflib.namespace.DCAM
    Bases: DefinedNamespace

    Metadata terms for vocabulary description

    Generated from: https://www.dublincore.org/specifications/dublin-core/dcmi-terms/dublin\_core\_abstract\_model.ttl Date: 2020-05-26 14:20:00.970966

    VocabularyEncodingScheme: URIRef =
rdflib.term.URIRef('http://purl.org/dc/dcam/VocabularyEncodingScheme')

    domainIncludes: URIRef =
rdflib.term.URIRef('http://purl.org/dc/dcam/domainIncludes')

    memberOf: URIRef = rdflib.term.URIRef('http://purl.org/dc/dcam/memberOf')

    rangeIncludes: URIRef = rdflib.term.URIRef('http://purl.org/dc/dcam/rangeIncludes')

class rdflib.namespace.DCAT
    Bases: DefinedNamespace

    The data catalog vocabulary

    DCAT is an RDF vocabulary designed to facilitate interoperability between data catalogs published on the Web.
    By using DCAT to describe datasets in data catalogs, publishers increase discoverability and enable applications
    easily to consume metadata from multiple catalogs. It further enables decentralized publishing of catalogs and
    facilitates federated dataset search across sites. Aggregated DCAT metadata can serve as a manifest file to fa-
    cilitate digital preservation. DCAT is defined at http://www.w3.org/TR/vocab-dcat/. Any variance between that
    normative document and this schema is an error in this schema.

    Generated from: https://www.w3.org/ns/dcat2.ttl Date: 2020-05-26 14:19:59.985854

    Catalog: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#Catalog')

    CatalogRecord: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#CatalogRecord')

    DataService: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#DataService')

    Dataset: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#Dataset')

    Distribution: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#Distribution')

    Relationship: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#Relationship')

    Resource: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#Resource')

    Role: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#Role')

    accessService: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#accessService')

    accessURL: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#accessURL')

    bbox: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#bbox')

```

```
byteSize: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#byteSize')
catalog: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#catalog')
centroid: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#centroid')
compressFormat: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#compressFormat')
contactPoint: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#contactPoint')
dataset: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#dataset')
distribution: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#distribution')
downloadURL: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#downloadURL')
endDate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#endDate')
endpointDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#endpointDescription')
endpointURL: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#endpointURL')
hadRole: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#hadRole')
keyword: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#keyword')
landingPage: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#landingPage')
mediaType: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#mediaType')
packageFormat: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#packageFormat')
qualifiedRelation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#qualifiedRelation')
record: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#record')
servesDataset: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#servesDataset')
service: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#service')
spatialResolutionInMeters: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#spatialResolutionInMeters')
startDate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#startDate')
temporalResolution: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#temporalResolution')
theme: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dcat#theme')
themeTaxonomy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dcat#themeTaxonomy')
```

**class rdflib.namespace.DCMITYPE**Bases: *DefinedNamespace*

DCMI Type Vocabulary

Generated from: [https://www.dublincore.org/specifications/dublin-core/dcmi-terms/dublin\\_core\\_type.ttl](https://www.dublincore.org/specifications/dublin-core/dcmi-terms/dublin_core_type.ttl) Date: 2020-05-26 14:19:59.084150Collection: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Collection')Dataset: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Dataset')Event: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Event')Image: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Image')InteractiveResource: *URIRef* =  
rdflib.term.URIRef('http://purl.org/dc/dcmitype/InteractiveResource')MovingImage: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/MovingImage')PhysicalObject: *URIRef* =  
rdflib.term.URIRef('http://purl.org/dc/dcmitype/PhysicalObject')Service: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Service')Software: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Software')Sound: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Sound')StillImage: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/StillImage')Text: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/dcmitype/Text')**class rdflib.namespace.DCTERMS**Bases: *DefinedNamespace*

DCMI Metadata Terms - other

Generated from: [https://www.dublincore.org/specifications/dublin-core/dcmi-terms/dublin\\_core\\_terms.ttl](https://www.dublincore.org/specifications/dublin-core/dcmi-terms/dublin_core_terms.ttl)  
Date: 2020-05-26 14:20:00.590514Agent: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/Agent')AgentClass: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/AgentClass')BibliographicResource: *URIRef* =  
rdflib.term.URIRef('http://purl.org/dc/terms/BibliographicResource')Box: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/Box')DCMIType: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/DCMIType')DDC: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/DDC')FileFormat: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/FileFormat')Frequency: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/Frequency')IMT: *URIRef* = rdflib.term.URIRef('http://purl.org/dc/terms/IMT')

```
IS03166: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/IS03166')
Jurisdiction: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/Jurisdiction')
LCC: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/LCC')
LCSH: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/LCSH')
LicenseDocument: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/LicenseDocument')
LinguisticSystem: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/LinguisticSystem')
Location: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/Location')
LocationPeriodOrJurisdiction: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/LocationPeriodOrJurisdiction')
MESH: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/MESH')
MediaType: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/MediaType')
MediaTypeOrExtent: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/MediaTypeOrExtent')
MethodOfAccrual: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/MethodOfAccrual')
MethodOfInstruction: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/MethodOfInstruction')
NLM: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/NLM')
Period: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/Period')
PeriodOfTime: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/PeriodOfTime')
PhysicalMedium: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/PhysicalMedium')
PhysicalResource: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/PhysicalResource')
Point: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/Point')
Policy: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/Policy')
ProvenanceStatement: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/ProvenanceStatement')
RFC1766: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/RFC1766')
RFC3066: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/RFC3066')
RFC4646: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/RFC4646')
RFC5646: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/RFC5646')
```

```
RightsStatement: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/RightsStatement')  
  
SizeOrDuration: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/SizeOrDuration')  
  
Standard: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/Standard')  
  
TGN: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/TGN')  
  
UDC: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/UDC')  
  
URI: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/URI')  
  
W3CDTF: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/W3CDTF')  
  
abstract: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/abstract')  
  
accessRights: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/accessRights')  
  
accrualMethod: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/accrualMethod')  
  
accrualPeriodicity: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/accrualPeriodicity')  
  
accrualPolicy: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/accrualPolicy')  
  
alternative: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/alternative')  
  
audience: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/audience')  
  
available: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/available')  
  
bibliographicCitation: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/bibliographicCitation')  
  
conformsTo: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/conformsTo')  
  
contributor: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/contributor')  
  
coverage: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/coverage')  
  
created: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/created')  
  
creator: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/creator')  
  
date: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/date')  
  
dateAccepted: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/dateAccepted')  
  
dateCopyrighted: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/dateCopyrighted')  
  
dateSubmitted: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/dateSubmitted')  
  
description: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/description')
```

```
educationLevel: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/educationLevel')  
  
extent: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/extent')  
  
format: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/format')  
  
hasFormat: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/hasFormat')  
  
hasPart: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/hasPart')  
  
hasVersion: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/hasVersion')  
  
identifier: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/identifier')  
  
instructionalMethod: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/instructionalMethod')  
  
isFormatOf: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/isFormatOf')  
  
isPartOf: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/isPartOf')  
  
isReferencedBy: URIRef =  
rdflib.term.URIRef('http://purl.org/dc/terms/isReferencedBy')  
  
isReplacedBy: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/isReplacedBy')  
  
isRequiredBy: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/isRequiredBy')  
  
isVersionOf: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/isVersionOf')  
  
issued: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/issued')  
  
language: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/language')  
  
license: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/license')  
  
mediator: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/mediator')  
  
medium: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/medium')  
  
modified: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/modified')  
  
provenance: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/provenance')  
  
publisher: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/publisher')  
  
references: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/references')  
  
relation: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/relation')  
  
replaces: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/replaces')  
  
requires: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/requires')  
  
rights: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/rights')  
  
rightsHolder: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/rightsHolder')  
  
source: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/source')
```



```

spatial: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/spatial')
subject: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/subject')
tableOfContents: URIRef =
rdflib.term.URIRef('http://purl.org/dc/terms/tableOfContents')
temporal: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/temporal')
title: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/title')
type: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/type')
valid: URIRef = rdflib.term.URIRef('http://purl.org/dc/terms/valid')

class rdflib.namespace.DOAP
    Bases: DefinedNamespace
    Description of a Project (DOAP) vocabulary
    The Description of a Project (DOAP) vocabulary, described using W3C RDF Schema and the Web Ontology
    Language.
    Generated from: http://usefulinc.com/ns/doap Date: 2020-05-26 14:20:01.307972
    ArchRepository: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#ArchRepository')
    BKRepository: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#BKRepository')
    BazaarBranch: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#BazaarBranch')
    CVSRepository: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#CVSRepository')
    DarcsRepository: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#DarcsRepository')
    GitBranch: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#GitBranch')
    GitRepository: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#GitRepository')
    HgRepository: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#HgRepository')
    Project: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#Project')
    Repository: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#Repository')
    SVNRepository: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#SVNRepository')
    Specification: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#Specification')
    Version: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#Version')

```

```
audience: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#audience')
blog: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#blog')
browse: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#browse')
category: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#category')
created: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#created')
description: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#description')
developer: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#developer')
documenter: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#documenter')
helper: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#helper')
homepage: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#homepage')
implements: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#implements')
language: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#language')
license: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#license')
location: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#location')
maintainer: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#maintainer')
module: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#module')
name: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#name')
os: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#os')
platform: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#platform')
release: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#release')
repository: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#repository')
repositoryOf: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#repositoryOf')
revision: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#revision')
screenshots: URIRef =
rdflib.term.URIRef('http://usefulinc.com/ns/doap#screenshots')
shortdesc: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#shortdesc')
tester: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#tester')
translator: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#translator')
vendor: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#vendor')
wiki: URIRef = rdflib.term.URIRef('http://usefulinc.com/ns/doap#wiki')
```

**class** rdflib.namespace.**DefinedNamespace**Bases: `object`

A Namespace with an enumerated list of members. Warnings are emitted if unknown members are referenced if `_warn` is True

**class** rdflib.namespace.**FOAF**Bases: `DefinedNamespace`

Friend of a Friend (FOAF) vocabulary

The Friend of a Friend (FOAF) RDF vocabulary, described using W3C RDF Schema and the Web Ontology Language.

Generated from: <http://xmlns.com/foaf/spec/index.rdf> Date: 2020-05-26 14:20:01.597998

**Agent:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Agent')`

**Document:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Document')`

**Group:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Group')`

**Image:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Image')`

**LabelProperty:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/LabelProperty')`

**OnlineAccount:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/OnlineAccount')`

**OnlineChatAccount:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/OnlineChatAccount')`

**OnlineEcommerceAccount:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/OnlineEcommerceAccount')`

**OnlineGamingAccount:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/OnlineGamingAccount')`

**Organization:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Organization')`

**Person:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Person')`

**PersonalProfileDocument:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/PersonalProfileDocument')`

**Project:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/Project')`

**account:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/account')`

**accountName:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/accountName')`

**accountServiceHomepage:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/accountServiceHomepage')`

**age:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/age')`

**aimChatID:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/aimChatID')`

**based\_near:** `URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/based_near')`

```
birthday: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/birthday')
currentProject: URIRef =
rdflib.term.URIRef('http://xmlns.com/foaf/0.1/currentProject')
depiction: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/depiction')
depicts: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/depicts')
dnaChecksum: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/dnaChecksum')
familyName: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/familyName')
family_name: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/family_name')
firstName: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/firstName')
focus: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/focus')
fundedBy: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/fundedBy')
geekcode: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/geekcode')
gender: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/gender')
givenName: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/givenName')
givenname: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/givenname')
holdsAccount: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/holdsAccount')
homepage: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/homepage')
icqChatID: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/icqChatID')
img: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/img')
interest: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/interest')
isPrimaryTopicOf: URIRef =
rdflib.term.URIRef('http://xmlns.com/foaf/0.1/isPrimaryTopicOf')
jabberID: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/jabberID')
knows: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/knows')
lastName: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/lastName')
logo: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/logo')
made: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/made')
maker: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/maker')
mbox: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/mbox')
mbox_sha1sum: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/mbox_sha1sum')
member: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/member')
```

```
membershipClass: URIRef =  
rdflib.term.URIRef('http://xmlns.com/foaf/0.1/membershipClass')  
  
msnChatID: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/msnChatID')  
  
myersBriggs: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/myersBriggs')  
  
name: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/name')  
  
nick: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/nick')  
  
openid: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/openid')  
  
page: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/page')  
  
pastProject: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/pastProject')  
  
phone: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/phone')  
  
plan: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/plan')  
  
primaryTopic: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/primaryTopic')  
  
publications: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/publications')  
  
schoolHomepage: URIRef =  
rdflib.term.URIRef('http://xmlns.com/foaf/0.1/schoolHomepage')  
  
sha1: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/sha1')  
  
skypeID: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/skypeID')  
  
status: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/status')  
  
surname: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/surname')  
  
theme: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/theme')  
  
thumbnail: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/thumbnail')  
  
tipjar: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/tipjar')  
  
title: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/title')  
  
topic: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/topic')  
  
topic_interest: URIRef =  
rdflib.term.URIRef('http://xmlns.com/foaf/0.1/topic_interest')  
  
weblog: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/weblog')  
  
workInfoHomepage: URIRef =  
rdflib.term.URIRef('http://xmlns.com/foaf/0.1/workInfoHomepage')  
  
workplaceHomepage: URIRef =  
rdflib.term.URIRef('http://xmlns.com/foaf/0.1/workplaceHomepage')  
  
yahooChatID: URIRef = rdflib.term.URIRef('http://xmlns.com/foaf/0.1/yahooChatID')
```

class rdflib.namespace.GEO

Bases: *DefinedNamespace*

An RDF/OWL vocabulary for representing spatial information

Generated from: [http://schemas.opengis.net/geosparql/1.0/geosparql\\_vocab\\_all.rdf](http://schemas.opengis.net/geosparql/1.0/geosparql_vocab_all.rdf) Date: 2021-12-27 17:38:15.101187

```
<http://www.opengis.net/ont/geosparql> dc:creator "Open Geospatial Consortium"^^
↳xsd:string
dc:date "2012-04-30"^^xsd:date
dc:source <http://www.opengis.net/doc/IS/geosparql/1.0>
      "OGC GeoSPARQL - A Geographic Query Language for RDF Data OGC 11-052r5"^^
↳xsd:string
rdfs:seeAlso <http://www.opengis.net/def/function/ogc-geosparql/1.0>
      <http://www.opengis.net/def/rule/ogc-geosparql/1.0>
      <http://www.opengis.net/doc/IS/geosparql/1.0>
owl:imports dc:
      <http://www.opengis.net/ont/gml>
      <http://www.opengis.net/ont/sf>
      <http://www.w3.org/2004/02/skos/core>
owl:versionInfo "OGC GeoSPARQL 1.0"^^xsd:string
```

Feature: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#Feature')

Geometry: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#Geometry')

SpatialObject: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#SpatialObject')

asGML: *URIRef* = rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#asGML')

asWKT: *URIRef* = rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#asWKT')

coordinateDimension: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#coordinateDimension')

defaultGeometry: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#defaultGeometry')

dimension: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#dimension')

ehContains: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehContains')

ehCoveredBy: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehCoveredBy')

ehCovers: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehCovers')

ehDisjoint: *URIRef* =

rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehDisjoint')

```
ehEquals: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehEquals')

ehInside: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehInside')

ehMeet: URIRef = rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehMeet')

ehOverlap: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#ehOverlap')

gmlLiteral: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#gmlLiteral')

hasGeometry: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#hasGeometry')

hasSerialization: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#hasSerialization')

isEmpty: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#isEmpty')

isSimple: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#isSimple')

rcc8dc: URIRef = rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8dc')

rcc8ec: URIRef = rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8ec')

rcc8eq: URIRef = rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8eq')

rcc8ntpp: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8ntpp')

rcc8ntppi: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8ntppi')

rcc8po: URIRef = rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8po')

rcc8tpp: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8tpp')

rcc8tppi: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#rcc8tppi')

sfContains: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfContains')

sfCrosses: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfCrosses')

sfDisjoint: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfDisjoint')

sfEquals: URIRef =
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfEquals')
```

```
sfIntersects: URIRef =  
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfIntersects')  
  
sfOverlaps: URIRef =  
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfOverlaps')  
  
sfTouches: URIRef =  
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfTouches')  
  
sfWithin: URIRef =  
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#sfWithin')  
  
spatialDimension: URIRef =  
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#spatialDimension')  
  
wktLiteral: URIRef =  
rdflib.term.URIRef('http://www.opengis.net/ont/geosparql#wktLiteral')
```

```
class rdflib.namespace.Namespace(value: str | bytes)
```

Bases: *str*

Utility class for quickly generating URIRefs with a common prefix

```
>>> from rdflib.namespace import Namespace  
>>> n = Namespace("http://example.org/")  
>>> n.Person # as attribute  
rdflib.term.URIRef('http://example.org/Person')  
>>> n['first-name'] # as item - for things that are not valid python identifiers  
rdflib.term.URIRef('http://example.org/first-name')  
>>> n.Person in n  
True  
>>> n2 = Namespace("http://example2.org/")  
>>> n.Person in n2  
False
```

```
__annotations__ = {}
```

```
__contains__(ref)
```

Allows to check if a URI is within (starts with) this Namespace.

```
>>> from rdflib import URIRef  
>>> namespace = Namespace('http://example.org/')  
>>> uri = URIRef('http://example.org/foo')  
>>> uri in namespace  
True  
>>> person_class = namespace['Person']  
>>> person_class in namespace  
True  
>>> obj = URIRef('http://not.example.org/bar')  
>>> obj in namespace  
False
```

**Parameters**

**ref** (*str*) –



**Return type**`bool`

```
__dict__ = mappingproxy({'__module__': 'rdflib.namespace', '__doc__': '\n Utility
class for quickly generating URIRefs with a common prefix\n\n >>> from
rdflib.namespace import Namespace\n >>> n = Namespace("http://example.org/")\n >>>
n.Person # as attribute\n rdflib.term.URIRef(\'http://example.org/Person\')\n >>>
n[\'first-name\'] # as item - for things that are not valid python identifiers\n
rdflib.term.URIRef(\'http://example.org/first-name\')\n >>> n.Person in n\n True\n
>>> n2 = Namespace("http://example2.org/")\n >>> n.Person in n2\n False\n ',
'__new__': <staticmethod object>, 'title': <property object>, 'term': <function
Namespace.term>, '__getitem__': <function Namespace.__getitem__>, '__getattr__':
<function Namespace.__getattr__>, '__repr__': <function Namespace.__repr__>,
'__contains__': <function Namespace.__contains__>, '__dict__': <attribute
'__dict__' of 'Namespace' objects>, '__weakref__': <attribute '__weakref__' of
'Namespace' objects>, '__annotations__': {}})
```

`__getattr__(name)`**Parameters**`name (str) –`**Return type**`URIRef``__getitem__(key)`

Return self[key].

**Parameters**`key (str) –`**Return type**`URIRef``__module__ = 'rdflib.namespace'``static __new__(cls, value)`**Parameters**`value (Union[str, bytes]) –`**Return type**`Namespace``__repr__()`

Return repr(self).

**Return type**`str``__weakref__`

list of weak references to the object (if defined)

`term(name)`**Parameters**`name (str) –`**Return type**`URIRef`

**property title:** *URIRef*

Return a version of the string where each word is titlecased.

More specifically, words start with uppercased characters and all remaining cased characters have lower case.

**class** rdflib.namespace.NamespaceManager(*graph*, *bind\_namespaces*='rdflib')

Bases: *object*

Class for managing prefix => namespace mappings

This class requires an RDFlib Graph as an input parameter and may optionally have the parameter *bind\_namespaces* set. This second parameter selects a strategy which is one of the following:

- **core:**
  - binds several core RDF prefixes only
  - owl, rdf, rdfs, xsd, xml from the NAMESPACE\_PREFIXES\_CORE object
- **rdflib:**
  - binds all the namespaces shipped with RDFLib as DefinedNamespace instances
  - all the core namespaces and all the following: brick, csvw, dc, dcat
  - dcmitype, dcterms, dcam, doap, foaf, geo, odrl, org, prof, prov, qb, schema
  - sh, skos, sosa, ssn, time, vann, void
  - see the NAMESPACE\_PREFIXES\_RDFLIB object for the up-to-date list
  - this is default
- **none:**
  - binds no namespaces to prefixes
  - note this is NOT default behaviour
- **cc:**
  - using prefix bindings from prefix.cc which is a online prefixes database
  - not implemented yet - this is aspirational

**Attention:** The namespaces bound for specific values of *bind\_namespaces* constitute part of RDFLib's public interface, so changes to them should only be additive within the same minor version. Removing values, or removing namespaces that are bound by default, constitutes a breaking change.

See the Sample usage

```
>>> import rdflib
>>> from rdflib import Graph
>>> from rdflib.namespace import Namespace, NamespaceManager
>>> EX = Namespace('http://example.com/')
>>> namespace_manager = NamespaceManager(Graph())
>>> namespace_manager.bind('ex', EX, override=False)
>>> g = Graph()
>>> g.namespace_manager = namespace_manager
>>> all_ns = [n for n in g.namespace_manager.namespaces()]
```

(continues on next page)

(continued from previous page)

```
>>> assert ('ex', rdflib.term.URIRef('http://example.com/')) in all_ns
>>>
```

**Parameters**

- **graph** (*Graph*) –
- **bind\_namespaces** (*Literal*['core', 'rdflib', 'none']) –

**\_\_contains\_\_(ref)****Parameters****ref** (*str*) –**Return type***bool*

```
__dict__ = mappingproxy({'__module__': 'rdflib.namespace', '__doc__': "Class for
managing prefix => namespace mappings\n\n This class requires an RDFlib Graph as an
input parameter and may optionally have\n the parameter bind_namespaces set. This
second parameter selects a strategy which\n is one of the following:\n\n * core:\n *
binds several core RDF prefixes only\n * owl, rdf, rdfs, xsd, xml from the
NAMESPACE_PREFIXES_CORE object\n * rdflib:\n * binds all the namespaces shipped with
RDFLib as DefinedNamespace instances\n * all the core namespaces and all the
following: brick, csvw, dc, dcat\n * dcmitype, dcterms, dcam, doap, foaf, geo,
odrl, org, prof, prov, qb, schema\n * sh, skos, sosa, ssn, time, vann, void\n * see
the NAMESPACE_PREFIXES_RDFLIB object for the up-to-date list\n * this is default\n *
none:\n * binds no namespaces to prefixes\n * note this is NOT default behaviour\n *
cc:\n * using prefix bindings from prefix.cc which is a online prefixes database\n *
not implemented yet - this is aspirational\n\n .. attention::\n\n The namespaces
bound for specific values of ``bind_namespaces``\n constitute part of RDFLib's
public interface, so changes to them should\n only be additive within the same minor
version. Removing values, or\n removing namespaces that are bound by default,
constitutes a breaking\n change.\n\n See the\n Sample usage\n\n .. code-block::
pycon\n\n >>> import rdflib\n >>> from rdflib import Graph\n >>> from
rdflib.namespace import Namespace, NamespaceManager\n >>> EX =
Namespace('http://example.com/')\n >>> namespace_manager =
NamespaceManager(Graph())\n >>> namespace_manager.bind('ex', EX, override=False)\n
>>> g = Graph()\n >>> g.namespace_manager = namespace_manager\n >>> all_ns = [n for
n in g.namespace_manager.namespaces()]\n >>> assert ('ex',
rdflib.term.URIRef('http://example.com/')) in all_ns\n >>>\n ", '__init__':
<function NamespaceManager.__init__>, '__contains__': <function
NamespaceManager.__contains__>, 'reset': <function NamespaceManager.reset>,
'store': <property object>, 'qname': <function NamespaceManager.qname>, 'curie':
<function NamespaceManager.curie>, 'qname_strict': <function
NamespaceManager.qname_strict>, 'normalizeUri': <function
NamespaceManager.normalizeUri>, 'compute_qname': <function
NamespaceManager.compute_qname>, 'compute_qname_strict': <function
NamespaceManager.compute_qname_strict>, 'expand_curie': <function
NamespaceManager.expand_curie>, '_store_bind': <function
NamespaceManager._store_bind>, 'bind': <function NamespaceManager.bind>,
'namespaces': <function NamespaceManager.namespaces>, 'absolutize': <function
NamespaceManager.absolutize>, '__dict__': <attribute '__dict__' of
'NamespaceManager' objects>, '__weakref__': <attribute '__weakref__' of
'NamespaceManager' objects>, '__annotations__': {'__cache': 'Dict[str, Tuple[str,
URIRef, str]]', '__cache_strict': 'Dict[str, Tuple[str, URIRef, str]]', '__strie':
'Dict[str, Any]', '__trie': 'Dict[str, Any]'}})
```

```
__init__(graph, bind_namespaces='rdflib')
```

#### Parameters

- `graph` (*Graph*) –
- `bind_namespaces` (*Literal*['core', 'rdflib', 'none']) –

```
__module__ = 'rdflib.namespace'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
absolutize(uri, defrag=1)
```

#### Parameters

- **uri** (*str*) –
- **defrag** (*int*) –

**Return type***URIRef***bind**(*prefix*, *namespace*, *override=True*, *replace=False*)

Bind a given namespace to the prefix

If override, rebind, even if the given namespace is already bound to another prefix.

If replace, replace any existing prefix with the new namespace

**Parameters**

- **prefix** (*Optional[str]*) –
- **namespace** (*Any*) –
- **override** (*bool*) –
- **replace** (*bool*) –

**Return type***None***compute\_qname**(*uri*, *generate=True*)**Parameters**

- **uri** (*str*) –
- **generate** (*bool*) –

**Return type***Tuple[str, URIRef, str]***compute\_qname\_strict**(*uri*, *generate=True*)**Parameters**

- **uri** (*str*) –
- **generate** (*bool*) –

**Return type***Tuple[str, str, str]***curie**(*uri*, *generate=True*)

From a URI, generate a valid CURIE.

Result is guaranteed to contain a colon separating the prefix from the name, even if the prefix is an empty string.

**Warning:** When *generate* is *True* (which is the default) and there is no matching namespace for the URI in the namespace manager then a new namespace will be added with prefix *ns{index}*.

Thus, when *generate* is *True*, this function is not a pure function because of this side-effect.

This default behaviour is chosen so that this function operates similarly to *NamespaceManager.qname*.

**Parameters**

- **uri** (*str*) – URI to generate CURIE for.

- **generate** (*bool*) – Whether to add a prefix for the namespace if one doesn’t already exist.  
Default: *True*.

**Return type***str***Returns**

CURIE for the URI.

**Raises****KeyError** – If generate is *False* and the namespace doesn’t already have a prefix.**expand\_curie**(*curie*)

Expand a CURIE of the form &lt;prefix:element&gt;, e.g. “rdf:type” into its full expression:

```
>>> import rdflib
>>> g = rdflib.Graph()
>>> g.namespace_manager.expand_curie("rdf:type")
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#type')
```

Raises exception if a namespace is not bound to the prefix.

**Parameters****curie** (*str*) –**Return type***URIRef***namespaces**()**Return type***Iterable*[*Tuple*[*str*, *URIRef*]]**normalizeUri**(*rdfTerm*)Takes an RDF Term and ‘normalizes’ it into a QName (using the registered prefix) or (unlike `compute_qname`) the Notation 3 form for URIs: <...URI...>**Parameters****rdfTerm** (*str*) –**Return type***str***qname**(*uri*)**Parameters****uri** (*str*) –**Return type***str***qname\_strict**(*uri*)**Parameters****uri** (*str*) –**Return type***str*

`reset()`

**Return type**

`None`

**property store:** `Store`

**class** `rdflib.namespace.ODRL2`

Bases: `DefinedNamespace`

ODRL Version 2.2

The ODRL Vocabulary and Expression defines a set of concepts and terms (the vocabulary) and encoding mechanism (the expression) for permissions and obligations statements describing digital content usage based on the ODRL Information Model.

Generated from: <https://www.w3.org/ns/odrl/2/ODRL2.ttl> Date: 2020-05-26 14:20:02.352356

**Action:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Action')`

**Agreement:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Agreement')`

**All:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/All')`

**All2ndConnections:** `URIRef` =  
`rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/All2ndConnections')`

**AllConnections:** `URIRef` =  
`rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/AllConnections')`

**AllGroups:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/AllGroups')`

**Assertion:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Assertion')`

**Asset:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Asset')`

**AssetCollection:** `URIRef` =  
`rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/AssetCollection')`

**AssetScope:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/AssetScope')`

**ConflictTerm:** `URIRef` =  
`rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/ConflictTerm')`

**Constraint:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Constraint')`

**Duty:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Duty')`

**Group:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Group')`

**Individual:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Individual')`

**LeftOperand:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/LeftOperand')`

**LogicalConstraint:** `URIRef` =  
`rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/LogicalConstraint')`

**Offer:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Offer')`

**Operator:** `URIRef` = `rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Operator')`

```
Party: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Party')

PartyCollection: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/PartyCollection')

PartyScope: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/PartyScope')

Permission: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Permission')

Policy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Policy')

Privacy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Privacy')

Prohibition: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Prohibition')

Request: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Request')

RightOperand: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/RightOperand')

Rule: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Rule')

Set: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Set')

Ticket: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/Ticket')

UndefinedTerm: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/UndefinedTerm')

absolutePosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/absolutePosition')

absoluteSize: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/absoluteSize')

absoluteSpatialPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/absoluteSpatialPosition')

absoluteTemporalPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/absoluteTemporalPosition')

acceptTracking: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/acceptTracking')

action: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/action')

adHocShare: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/adHocShare')

aggregate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/aggregate')

andSequence: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/andSequence')

annotate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/annotate')

anonymize: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/anonymize')

append: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/append')

appendTo: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/appendTo')
```



```
archive: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/archive')
assignee: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/assignee')
assigneeOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/assigneeOf')
assigner: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/assigner')
assignerOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/assignerOf')
attachPolicy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/attachPolicy')
attachSource: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/attachSource')
attribute: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/attribute')
attributedParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/attributedParty')
attributingParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/attributingParty')
commercialize: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/commercialize')
compensate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/compensate')
compensatedParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/compensatedParty')
compensatingParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/compensatingParty')
concurrentUse: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/concurrentUse')
conflict: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/conflict')
consentedParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/consentedParty')
consentingParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/consentingParty')
consequence: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/consequence')
constraint: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/constraint')
contractedParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/contractedParty')
contractingParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/contractingParty')
copy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/copy')
```

```
core: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/core')
count: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/count')
dataType: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/dataType')
dateTime: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/dateTime')
delayPeriod: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/delayPeriod')
delete: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/delete')
deliveryChannel: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/deliveryChannel')
derive: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/derive')
device: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/device')
digitize: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/digitize')
display: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/display')
distribute: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/distribute')
duty: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/duty')
elapsedTime: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/elapsedTime')
ensureExclusivity: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/ensureExclusivity')
eq: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/eq')
event: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/event')
execute: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/execute')
export: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/export')
extract: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/extract')
extractChar: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/extractChar')
extractPage: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/extractPage')
extractWord: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/extractWord')
failure: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/failure')
fileFormat: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/fileFormat')
function: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/function')
give: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/give')
grantUse: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/grantUse')
gt: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/gt')
```

```

gteq: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/gteq')
hasPart: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/hasPart')
hasPolicy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/hasPolicy')
ignore: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/ignore')
implies: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/implies')
include: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/include')
includedIn: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/includedIn')
index: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/index')
industry: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/industry')
inform: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/inform')
informedParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/informedParty')
informingParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/informingParty')
inheritAllowed: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/inheritAllowed')
inheritFrom: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/inheritFrom')
inheritRelation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/inheritRelation')
install: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/install')
invalid: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/invalid')
isA: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/isA')
isAllOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/isAllOf')
isAnyOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/isAnyOf')
isNoneOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/isNoneOf')
isPartOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/isPartOf')
language: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/language')
lease: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/lease')
leftOperand: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/leftOperand')
lend: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/lend')
license: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/license')
lt: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/lt')

```

```
lteq: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/lteq')
media: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/media')
meteredTime: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/meteredTime')
modify: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/modify')
move: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/move')
neq: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/neq')
nextPolicy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/nextPolicy')
obligation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/obligation')
obtainConsent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/obtainConsent')
operand: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/operand')
operator: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/operator')
output: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/output')
partOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/partOf')
pay: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/pay')
payAmount: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/payAmount')
payeeParty: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/payeeParty')
percentage: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/percentage')
perm: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/perm')
permission: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/permission')
play: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/play')
policyUsage: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/policyUsage')
present: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/present')
preview: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/preview')
print: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/print')
product: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/product')
profile: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/profile')
prohibit: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/prohibit')
prohibition: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/prohibition')
proximity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/proximity')
purpose: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/purpose')
```

```
read: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/read')

recipient: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/recipient')

refinement: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/refinement')

relation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/relation')

relativePosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/relativePosition')

relativeSize: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/relativeSize')

relativeSpatialPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/relativeSpatialPosition')

relativeTemporalPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/relativeTemporalPosition')

remedy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/remedy')

reproduce: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/reproduce')

resolution: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/resolution')

reviewPolicy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/reviewPolicy')

rightOperand: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/rightOperand')

rightOperandReference: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/rightOperandReference')

scope: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/scope')

secondaryUse: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/secondaryUse')

sell: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/sell')

share: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/share')

shareAlike: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/shareAlike')

source: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/source')

spatial: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/spatial')

spatialCoordinates: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/spatialCoordinates')

status: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/status')

stream: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/stream')

support: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/support')
```

```
synchronize: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/synchronize')
system: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/system')
systemDevice: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/systemDevice')
target: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/target')
textToSpeech: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/textToSpeech')
timeInterval: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/timeInterval')
timedCount: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/timedCount')
trackedParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/trackedParty')
trackingParty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/trackingParty')
transfer: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/transfer')
transform: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/transform')
translate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/translate')
uid: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/uid')
undefined: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/undefined')
uninstall: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/uninstall')
unit: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/unit')
unitOfCount: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/unitOfCount')
use: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/use')
version: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/version')
virtualLocation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/virtualLocation')
watermark: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/watermark')
write: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/write')
writeTo: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/writeTo')
xone: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/odrl/2/xone')
```

class rdflib.namespace.ORG

Bases: *DefinedNamespace*

Core organization ontology

Vocabulary for describing organizational structures, specializable to a broad variety of types of organization.

Generated from: <http://www.w3.org/ns/org#> Date: 2020-05-26 14:20:02.908408

```
ChangeEvent: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#ChangeEvent')

FormalOrganization: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#FormalOrganization')

Head: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#Head')

Membership: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#Membership')

Organization: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#Organization')

OrganizationalCollaboration: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#OrganizationalCollaboration')

OrganizationalUnit: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#OrganizationalUnit')

Post: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#Post')

Role: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#Role')

Site: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#Site')

basedAt: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#basedAt')

changedBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#changedBy')

classification: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#classification')

hasMember: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#hasMember')

hasMembership: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#hasMembership')

hasPost: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#hasPost')

hasPrimarySite: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#hasPrimarySite')

hasRegisteredSite: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#hasRegisteredSite')

hasSite: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#hasSite')

hasSubOrganization: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#hasSubOrganization')

hasUnit: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#hasUnit')

headOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#headOf')

heldBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#heldBy')

holds: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#holds')

identifier: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#identifier')

linkedTo: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#linkedTo')
```



```

location: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#location')
member: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#member')
memberDuring: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#memberDuring')
memberOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#memberOf')
organization: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#organization')
originalOrganization: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#originalOrganization')
postIn: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#postIn')
purpose: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#purpose')
remuneration: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#remuneration')
reportsTo: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#reportsTo')
resultedFrom: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#resultedFrom')
resultingOrganization: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#resultingOrganization')
role: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#role')
roleProperty: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#roleProperty')
siteAddress: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#siteAddress')
siteOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#siteOf')
subOrganizationOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#subOrganizationOf')
transitiveSubOrganizationOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/org#transitiveSubOrganizationOf')
unitOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/org#unitOf')

```

class rdflib.namespace.OWL

Bases: *DefinedNamespace*

The OWL 2 Schema vocabulary (OWL 2)

This ontology partially describes the built-in classes and properties that together form the basis of the RDF/XML syntax of OWL 2. The content of this ontology is based on Tables 6.1 and 6.2 in Section 6.4 of the OWL 2 RDF-Based Semantics specification, available at <http://www.w3.org/TR/owl2-rdf-based-semantics/>. Please note that those tables do not include the different annotations (labels, comments and `rdfs:isDefinedBy` links) used in this file. Also note that the descriptions provided in this ontology do not provide a complete and correct formal description of either the syntax or the semantics of the introduced terms (please see the OWL 2 recommendations for the complete and normative specifications). Furthermore, the information provided by this ontology may be misleading if not used with care. This ontology SHOULD NOT be imported into OWL ontologies. Importing this file into an OWL 2 DL ontology will cause it to become an OWL 2 Full ontology and may have other, unexpected, consequences.

Generated from: <http://www.w3.org/2002/07/owl#> Date: 2020-05-26 14:20:03.193795



```
AllDifferent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#AllDifferent')  
  
AllDisjointClasses: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#AllDisjointClasses')  
  
AllDisjointProperties: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#AllDisjointProperties')  
  
Annotation: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#Annotation')  
  
AnnotationProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#AnnotationProperty')  
  
AsymmetricProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#AsymmetricProperty')  
  
Axiom: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#Axiom')  
  
Class: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#Class')  
  
DataRange: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#DataRange')  
  
DatatypeProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#DatatypeProperty')  
  
DeprecatedClass: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#DeprecatedClass')  
  
DeprecatedProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#DeprecatedProperty')  
  
FunctionalProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#FunctionalProperty')  
  
InverseFunctionalProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#InverseFunctionalProperty')  
  
IrreflexiveProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#IrreflexiveProperty')  
  
NamedIndividual: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#NamedIndividual')  
  
NegativePropertyAssertion: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#NegativePropertyAssertion')  
  
Nothing: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#Nothing')  
  
ObjectProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#ObjectProperty')  
  
Ontology: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#Ontology')  
  
OntologyProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#OntologyProperty')
```

```
ReflexiveProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#ReflexiveProperty')  
  
Restriction: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#Restriction')  
  
SymmetricProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#SymmetricProperty')  
  
Thing: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#Thing')  
  
TransitiveProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#TransitiveProperty')  
  
allValuesFrom: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#allValuesFrom')  
  
annotatedProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#annotatedProperty')  
  
annotatedSource: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#annotatedSource')  
  
annotatedTarget: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#annotatedTarget')  
  
assertionProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#assertionProperty')  
  
backwardCompatibleWith: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#backwardCompatibleWith')  
  
bottomDataProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#bottomDataProperty')  
  
bottomObjectProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#bottomObjectProperty')  
  
cardinality: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#cardinality')  
  
complementOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#complementOf')  
  
datatypeComplementOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#datatypeComplementOf')  
  
deprecated: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#deprecated')  
  
differentFrom: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#differentFrom')  
  
disjointUnionOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#disjointUnionOf')  
  
disjointWith: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#disjointWith')
```

```

distinctMembers: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#distinctMembers')

equivalentClass: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#equivalentClass')

equivalentProperty: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#equivalentProperty')

hasKey: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#hasKey')

hasSelf: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#hasSelf')

hasValue: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#hasValue')

imports: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#imports')

incompatibleWith: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#incompatibleWith')

intersectionOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#intersectionOf')

inverseOf: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#inverseOf')

maxCardinality: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#maxCardinality')

maxQualifiedCardinality: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#maxQualifiedCardinality')

members: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#members')

minCardinality: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#minCardinality')

minQualifiedCardinality: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#minQualifiedCardinality')

onClass: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#onClass')

onDataRange: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#onDataRange')

onDatatype: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#onDatatype')

onProperties: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#onProperties')

onProperty: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#onProperty')

oneOf: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#oneOf')

priorVersion: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#priorVersion')

propertyChainAxiom: URIRef =
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#propertyChainAxiom')

```

```
propertyDisjointWith: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#propertyDisjointWith')  
  
qualifiedCardinality: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#qualifiedCardinality')  
  
rational: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#rational')  
  
real: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#real')  
  
sameAs: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#sameAs')  
  
someValuesFrom: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#someValuesFrom')  
  
sourceIndividual: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#sourceIndividual')  
  
targetIndividual: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#targetIndividual')  
  
targetValue: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#targetValue')  
  
topDataProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#topDataProperty')  
  
topObjectProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#topObjectProperty')  
  
unionOf: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#unionOf')  
  
versionIRI: URIRef = rdflib.term.URIRef('http://www.w3.org/2002/07/owl#versionIRI')  
  
versionInfo: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#versionInfo')  
  
withRestrictions: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2002/07/owl#withRestrictions')
```

```
class rdflib.namespace.PROF
```

```
    Bases: DefinedNamespace
```

```
    Profiles Vocabulary
```

This vocabulary is for describing relationships between standards/specifications, profiles of them and supporting artifacts such as validating resources. This model starts with [<http://dublincore.org/2012/06/14/dcterm#Standard{}>](*dct:Standard*) entities which can either be Base Specifications (a standard not profiling any other Standard) or Profiles (Standards which do profile others). Base Specifications or Profiles can have Resource Descriptors associated with them that defines implementing rules for the it. Resource Descriptors must indicate the role they play (to guide, to validate etc.) and the formalism they adhere to (*dct:format*) to allow for content negotiation. A vocabulary of Resource Roles are provided alongside this vocabulary but that list is extensible.

Generated from: <https://www.w3.org/ns/dx/prof/profilesont.ttl> Date: 2020-05-26 14:20:03.542924

```
    Profile: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/Profile')
```

```

ResourceDescriptor: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/ResourceDescriptor')

ResourceRole: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/ResourceRole')

hasArtifact: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/hasArtifact')

hasResource: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/hasResource')

hasRole: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/hasRole')

hasToken: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/hasToken')

isInheritedFrom: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/isInheritedFrom')

isProfileOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/isProfileOf')

isTransitiveProfileOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/dx/prof/isTransitiveProfileOf')

```

```
class rdflib.namespace.PROV
```

Bases: *DefinedNamespace*

W3C PROVenance Interchange Ontology (PROV-O)

This document is published by the Provenance Working Group ([http://www.w3.org/2011/prov/wiki/Main\\_Page](http://www.w3.org/2011/prov/wiki/Main_Page)). If you wish to make comments regarding this document, please send them to [public-prov-comments@w3.org](mailto:public-prov-comments@w3.org) (subscribe [public-prov-comments-request@w3.org](mailto:public-prov-comments-request@w3.org), archives <http://lists.w3.org/Archives/Public/public-prov-comments/>). All feedback is welcome.

PROV Access and Query Ontology

This document is published by the Provenance Working Group ([http://www.w3.org/2011/prov/wiki/Main\\_Page](http://www.w3.org/2011/prov/wiki/Main_Page)). If you wish to make comments regarding this document, please send them to [public-prov-comments@w3.org](mailto:public-prov-comments@w3.org) (subscribe [public-prov-comments-request@w3.org](mailto:public-prov-comments-request@w3.org), archives <http://lists.w3.org/Archives/Public/public-prov-comments/>). All feedback is welcome.

Dublin Core extensions of the W3C PROVenance Interchange Ontology (PROV-O)

This document is published by the Provenance Working Group ([http://www.w3.org/2011/prov/wiki/Main\\_Page](http://www.w3.org/2011/prov/wiki/Main_Page)). If you wish to make comments regarding this document, please send them to [public-prov-comments@w3.org](mailto:public-prov-comments@w3.org) (subscribe [public-prov-comments-request@w3.org](mailto:public-prov-comments-request@w3.org), archives <http://lists.w3.org/Archives/Public/public-prov-comments/>). All feedback is welcome.

W3C PROV Linking Across Provenance Bundles Ontology (PROV-LINKS)

This document is published by the Provenance Working Group ([http://www.w3.org/2011/prov/wiki/Main\\_Page](http://www.w3.org/2011/prov/wiki/Main_Page)). If you wish to make comments regarding this document, please send them to [public-prov-comments@w3.org](mailto:public-prov-comments@w3.org) (subscribe [public-prov-comments-request@w3.org](mailto:public-prov-comments-request@w3.org), archives <http://lists.w3.org/Archives/Public/public-prov-comments/>). All feedback is welcome.

W3C PROVenance Interchange Ontology (PROV-O) Dictionary Extension

This document is published by the Provenance Working Group ([http://www.w3.org/2011/prov/wiki/Main\\_Page](http://www.w3.org/2011/prov/wiki/Main_Page)). If you wish to make comments regarding this document, please send them to [public-prov-comments@w3.org](mailto:public-prov-comments@w3.org)

(subscribe [public-prov-comments-request@w3.org](mailto:public-prov-comments-request@w3.org), archives <http://lists.w3.org/Archives/Public/public-prov-comments/>). All feedback is welcome.

W3C PROVenance Interchange

This document is published by the Provenance Working Group ([http://www.w3.org/2011/prov/wiki/Main\\_Page](http://www.w3.org/2011/prov/wiki/Main_Page)). If you wish to make comments regarding this document, please send them to [public-prov-comments@w3.org](mailto:public-prov-comments@w3.org) (subscribe [public-prov-comments-request@w3.org](mailto:public-prov-comments-request@w3.org), archives <http://lists.w3.org/Archives/Public/public-prov-comments/>). All feedback is welcome.

Generated from: <http://www.w3.org/ns/prov> Date: 2020-05-26 14:20:04.650279

Accept: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Accept')`

Activity: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Activity')`

ActivityInfluence: `URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#ActivityInfluence')`

Agent: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Agent')`

AgentInfluence: `URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#AgentInfluence')`

Association: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Association')`

Attribution: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Attribution')`

Bundle: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Bundle')`

Collection: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Collection')`

Communication: `URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#Communication')`

Contribute: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Contribute')`

Contributor: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Contributor')`

Copyright: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Copyright')`

Create: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Create')`

Creator: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Creator')`

Delegation: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Delegation')`

Derivation: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Derivation')`

Dictionary: `URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Dictionary')`

DirectQueryService: `URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#DirectQueryService')`

EmptyCollection: `URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#EmptyCollection')`

EmptyDictionary: `URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#EmptyDictionary')`

```
End: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#End')

Entity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Entity')

EntityInfluence: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#EntityInfluence')

Generation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Generation')

Influence: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Influence')

Insertion: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Insertion')

InstantaneousEvent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#InstantaneousEvent')

Invalidation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Invalidation')

KeyEntityPair: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#KeyEntityPair')

Location: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Location')

Modify: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Modify')

Organization: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Organization')

Person: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Person')

Plan: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Plan')

PrimarySource: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#PrimarySource')

Publish: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Publish')

Publisher: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Publisher')

Quotation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Quotation')

Removal: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Removal')

Replace: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Replace')

Revision: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Revision')

RightsAssignment: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#RightsAssignment')

RightsHolder: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#RightsHolder')

Role: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Role')

ServiceDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#ServiceDescription')

SoftwareAgent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#SoftwareAgent')
```



```

Start: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Start')
Submit: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Submit')
Usage: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#Usage')
actedOnBehalfOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#actedOnBehalfOf')
activity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#activity')
activityOfInfluence: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#activityOfInfluence')
agent: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#agent')
agentOfInfluence: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#agentOfInfluence')
alternateOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#alternateOf')
aq: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#aq')
asInBundle: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#asInBundle')
atLocation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#atLocation')
atTime: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#atTime')
category: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#category')
component: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#component')
constraints: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#constraints')
contributed: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#contributed')
definition: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#definition')
derivedByInsertionFrom: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#derivedByInsertionFrom')
derivedByRemovalFrom: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#derivedByRemovalFrom')
describesService: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#describesService')
dictionary: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#dictionary')
dm: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#dm')
editorialNote: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#editorialNote')
editorsDefinition: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#editorsDefinition')
ended: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#ended')

```



```

endedAtTime: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#endedAtTime')

entity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#entity')

entityOfInfluence: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#entityOfInfluence')

generalizationOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#generalizationOf')

generated: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#generated')

generatedAsDerivation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#generatedAsDerivation')

generatedAtTime: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#generatedAtTime')

hadActivity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadActivity')

hadDelegate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadDelegate')

hadDerivation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#hadDerivation')

hadDictionaryMember: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#hadDictionaryMember')

hadGeneration: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#hadGeneration')

hadInfluence: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadInfluence')

hadMember: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadMember')

hadPlan: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadPlan')

hadPrimarySource: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#hadPrimarySource')

hadRevision: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadRevision')

hadRole: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadRole')

hadUsage: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#hadUsage')

has_anchor: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#has_anchor')

has_provenance: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#has_provenance')

has_query_service: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#has_query_service')

influenced: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#influenced')

influencer: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#influencer')

informed: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#informed')

```

```
insertedKeyEntityPair: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#insertedKeyEntityPair')  
  
invalidated: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#invalidated')  
  
invalidatedAtTime: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#invalidatedAtTime')  
  
inverse: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#inverse')  
  
locationOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#locationOf')  
  
mentionOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#mentionOf')  
  
n: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#n')  
  
order: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#order')  
  
pairEntity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#pairEntity')  
  
pairKey: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#pairKey')  
  
pingback: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#pingback')  
  
provenanceUriTemplate: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#provenanceUriTemplate')  
  
qualifiedAssociation: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedAssociation')  
  
qualifiedAssociationOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedAssociationOf')  
  
qualifiedAttribution: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedAttribution')  
  
qualifiedAttributionOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedAttributionOf')  
  
qualifiedCommunication: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedCommunication')  
  
qualifiedCommunicationOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedCommunicationOf')  
  
qualifiedDelegation: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedDelegation')  
  
qualifiedDelegationOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedDelegationOf')  
  
qualifiedDerivation: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedDerivation')  
  
qualifiedDerivationOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedDerivationOf')  
  
qualifiedEnd: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedEnd')
```

```
qualifiedEndOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedEndOf')  
  
qualifiedForm: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedForm')  
  
qualifiedGeneration: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedGeneration')  
  
qualifiedGenerationOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedGenerationOf')  
  
qualifiedInfluence: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedInfluence')  
  
qualifiedInfluenceOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedInfluenceOf')  
  
qualifiedInsertion: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedInsertion')  
  
qualifiedInvalidation: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedInvalidation')  
  
qualifiedInvalidationOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedInvalidationOf')  
  
qualifiedPrimarySource: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedPrimarySource')  
  
qualifiedQuotation: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedQuotation')  
  
qualifiedQuotationOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedQuotationOf')  
  
qualifiedRemoval: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedRemoval')  
  
qualifiedRevision: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedRevision')  
  
qualifiedSourceOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedSourceOf')  
  
qualifiedStart: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedStart')  
  
qualifiedStartOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedStartOf')  
  
qualifiedUsage: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedUsage')  
  
qualifiedUsingActivity: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/prov#qualifiedUsingActivity')
```

```
quotedAs: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#quotedAs')

removedKey: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#removedKey')

revisedEntity: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#revisedEntity')

sharesDefinitionWith: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#sharesDefinitionWith')

specializationOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#specializationOf')

started: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#started')

startedAtTime: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#startedAtTime')

todo: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#todo')

unqualifiedForm: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#unqualifiedForm')

used: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#used')

value: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#value')

wasActivityOfInfluence: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasActivityOfInfluence')

wasAssociateFor: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasAssociateFor')

wasAssociatedWith: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasAssociatedWith')

wasAttributedTo: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasAttributedTo')

wasDerivedFrom: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasDerivedFrom')

wasEndedBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#wasEndedBy')

wasGeneratedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasGeneratedBy')

wasInfluencedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasInfluencedBy')

wasInformedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasInformedBy')

wasInvalidatedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasInvalidatedBy')

wasMemberOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#wasMemberOf')
```

```

wasPlanOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#wasPlanOf')

wasPrimarySourceOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasPrimarySourceOf')

wasQuotedFrom: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasQuotedFrom')

wasRevisionOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasRevisionOf')

wasRoleIn: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#wasRoleIn')

wasStartedBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#wasStartedBy')

wasUsedBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/prov#wasUsedBy')

wasUsedInDerivation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/prov#wasUsedInDerivation')

class rdflib.namespace.QB
    Bases: DefinedNamespace

    Vocabulary for multi-dimensional (e.g. statistical) data publishing

    This vocabulary allows multi-dimensional data, such as statistics, to be published in RDF. It is based on the core
    information model from SDMX (and thus also DDI).

    Generated from: http://purl.org/linked-data/cube# Date: 2020-05-26 14:20:05.485176

    Attachable: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#Attachable')

    AttributeProperty: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#AttributeProperty')

    CodedProperty: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#CodedProperty')

    ComponentProperty: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#ComponentProperty')

    ComponentSet: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#ComponentSet')

    ComponentSpecification: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#ComponentSpecification')

    DataSet: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#DataSet')

    DataStructureDefinition: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#DataStructureDefinition')

    DimensionProperty: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#DimensionProperty')

    HierarchicalCodeList: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#HierarchicalCodeList')

```

```
MeasureProperty: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#MeasureProperty')  
  
Observation: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#Observation')  
  
ObservationGroup: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#ObservationGroup')  
  
Slice: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#Slice')  
  
SliceKey: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#SliceKey')  
  
attribute: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#attribute')  
  
codeList: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#codeList')  
  
component: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#component')  
  
componentAttachment: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#componentAttachment')  
  
componentProperty: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#componentProperty')  
  
componentRequired: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#componentRequired')  
  
concept: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#concept')  
  
dataSet: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#dataSet')  
  
dimension: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#dimension')  
  
hierarchyRoot: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#hierarchyRoot')  
  
measure: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#measure')  
  
measureDimension: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#measureDimension')  
  
measureType: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#measureType')  
  
observation: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#observation')  
  
observationGroup: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#observationGroup')  
  
order: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#order')  
  
parentChildProperty: URIRef =  
rdflib.term.URIRef('http://purl.org/linked-data/cube#parentChildProperty')
```

```

slice: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#slice')

sliceKey: URIRef = rdflib.term.URIRef('http://purl.org/linked-data/cube#sliceKey')

sliceStructure: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#sliceStructure')

structure: URIRef =
rdflib.term.URIRef('http://purl.org/linked-data/cube#structure')

class rdflib.namespace.RDF
    Bases: DefinedNamespace
    The RDF Concepts Vocabulary (RDF)
    This is the RDF Schema for the RDF vocabulary terms in the RDF Namespace, defined in RDF 1.1 Concepts.
    Generated from: http://www.w3.org/1999/02/22-rdf-syntax-ns# Date: 2020-05-26 14:20:05.642859
    dc:date "2019-12-16"
    Alt: URIRef = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#Alt')
    Bag: URIRef = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#Bag')
    CompoundLiteral: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#CompoundLiteral')
    HTML: URIRef = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#HTML')
    JSON: URIRef = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#JSON')
    List: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#List')
    PlainLiteral: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#PlainLiteral')
    Property: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#Property')
    Seq: URIRef = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#Seq')
    Statement: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#Statement')
    XMLLiteral: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#XMLLiteral')
    direction: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#direction')
    first: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#first')
    langString: URIRef =
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#langString')

```



```
language: URIRef =  
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#language')  
  
nil: URIRef = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#nil')  
  
object: URIRef =  
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#object')  
  
predicate: URIRef =  
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#predicate')  
  
rest: URIRef =  
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#rest')  
  
subject: URIRef =  
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#subject')  
  
type: URIRef =  
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#type')  
  
value: URIRef =  
rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#value')
```

```
class rdflib.namespace.RDFS
```

```
    Bases: DefinedNamespace
```

```
    The RDF Schema vocabulary (RDFS)
```

```
    Generated from: http://www.w3.org/2000/01/rdf-schema# Date: 2020-05-26 14:20:05.794866
```

```
    Class: URIRef = rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#Class')
```

```
    Container: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#Container')
```

```
    ContainerMembershipProperty: URIRef = rdflib.term.URIRef('http://www.w3.org/2000/  
01/rdf-schema#ContainerMembershipProperty')
```

```
    Datatype: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#Datatype')
```

```
    Literal: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#Literal')
```

```
    Resource: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#Resource')
```

```
    comment: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#comment')
```

```
    domain: URIRef = rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#domain')
```

```
    isDefinedBy: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#isDefinedBy')
```

```
    label: URIRef = rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#label')
```

```
    member: URIRef = rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#member')
```



```

range: URIRef = rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#range')

seeAlso: URIRef =
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#seeAlso')

subClassOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#subClassOf')

subPropertyOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#subPropertyOf')

class rdflib.namespace.SDO
    Bases: DefinedNamespace
    schema.org namespace elements
    3DModel, True, False & yield are not available as they collide with Python terms
    Generated from: https://schema.org/version/latest/schemaorg-current-https.jsonld Date: 2021-12-01 By:
    Nicholas J. Car

    AMRadioChannel: URIRef = rdflib.term.URIRef('https://schema.org/AMRadioChannel')

    APIReference: URIRef = rdflib.term.URIRef('https://schema.org/APIReference')

    Abdomen: URIRef = rdflib.term.URIRef('https://schema.org/Abdomen')

    AboutPage: URIRef = rdflib.term.URIRef('https://schema.org/AboutPage')

    AcceptAction: URIRef = rdflib.term.URIRef('https://schema.org/AcceptAction')

    Accommodation: URIRef = rdflib.term.URIRef('https://schema.org/Accommodation')

    AccountingService: URIRef =
rdflib.term.URIRef('https://schema.org/AccountingService')

    AchieveAction: URIRef = rdflib.term.URIRef('https://schema.org/AchieveAction')

    Action: URIRef = rdflib.term.URIRef('https://schema.org/Action')

    ActionAccessSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/ActionAccessSpecification')

    ActionStatusType: URIRef =
rdflib.term.URIRef('https://schema.org/ActionStatusType')

    ActivateAction: URIRef = rdflib.term.URIRef('https://schema.org/ActivateAction')

    ActivationFee: URIRef = rdflib.term.URIRef('https://schema.org/ActivationFee')

    ActiveActionStatus: URIRef =
rdflib.term.URIRef('https://schema.org/ActiveActionStatus')

    ActiveNotRecruiting: URIRef =
rdflib.term.URIRef('https://schema.org/ActiveNotRecruiting')

    AddAction: URIRef = rdflib.term.URIRef('https://schema.org/AddAction')

    AdministrativeArea: URIRef =
rdflib.term.URIRef('https://schema.org/AdministrativeArea')

```

```
AdultEntertainment: URIRef =  
rdflib.term.URIRef('https://schema.org/AdultEntertainment')  
  
AdvertiserContentArticle: URIRef =  
rdflib.term.URIRef('https://schema.org/AdvertiserContentArticle')  
  
AerobicActivity: URIRef = rdflib.term.URIRef('https://schema.org/AerobicActivity')  
  
AggregateOffer: URIRef = rdflib.term.URIRef('https://schema.org/AggregateOffer')  
  
AggregateRating: URIRef = rdflib.term.URIRef('https://schema.org/AggregateRating')  
  
AgreeAction: URIRef = rdflib.term.URIRef('https://schema.org/AgreeAction')  
  
Airline: URIRef = rdflib.term.URIRef('https://schema.org/Airline')  
  
Airport: URIRef = rdflib.term.URIRef('https://schema.org/Airport')  
  
AlbumRelease: URIRef = rdflib.term.URIRef('https://schema.org/AlbumRelease')  
  
AlignmentObject: URIRef = rdflib.term.URIRef('https://schema.org/AlignmentObject')  
  
AllWheelDriveConfiguration: URIRef =  
rdflib.term.URIRef('https://schema.org/AllWheelDriveConfiguration')  
  
AllergiesHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/AllergiesHealthAspect')  
  
AllocateAction: URIRef = rdflib.term.URIRef('https://schema.org/AllocateAction')  
  
AmpStory: URIRef = rdflib.term.URIRef('https://schema.org/AmpStory')  
  
AmusementPark: URIRef = rdflib.term.URIRef('https://schema.org/AmusementPark')  
  
AnaerobicActivity: URIRef =  
rdflib.term.URIRef('https://schema.org/AnaerobicActivity')  
  
AnalysisNewsArticle: URIRef =  
rdflib.term.URIRef('https://schema.org/AnalysisNewsArticle')  
  
AnatomicalStructure: URIRef =  
rdflib.term.URIRef('https://schema.org/AnatomicalStructure')  
  
AnatomicalSystem: URIRef =  
rdflib.term.URIRef('https://schema.org/AnatomicalSystem')  
  
Anesthesia: URIRef = rdflib.term.URIRef('https://schema.org/Anesthesia')  
  
AnimalShelter: URIRef = rdflib.term.URIRef('https://schema.org/AnimalShelter')  
  
Answer: URIRef = rdflib.term.URIRef('https://schema.org/Answer')  
  
Apartment: URIRef = rdflib.term.URIRef('https://schema.org/Apartment')  
  
ApartmentComplex: URIRef =  
rdflib.term.URIRef('https://schema.org/ApartmentComplex')  
  
Appearance: URIRef = rdflib.term.URIRef('https://schema.org/Appearance')
```

```
AppendAction: URIRef = rdflib.term.URIRef('https://schema.org/AppendAction')
ApplyAction: URIRef = rdflib.term.URIRef('https://schema.org/ApplyAction')
ApprovedIndication: URIRef =
rdflib.term.URIRef('https://schema.org/ApprovedIndication')
Aquarium: URIRef = rdflib.term.URIRef('https://schema.org/Aquarium')
ArchiveComponent: URIRef =
rdflib.term.URIRef('https://schema.org/ArchiveComponent')
ArchiveOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/ArchiveOrganization')
ArriveAction: URIRef = rdflib.term.URIRef('https://schema.org/ArriveAction')
ArtGallery: URIRef = rdflib.term.URIRef('https://schema.org/ArtGallery')
Artery: URIRef = rdflib.term.URIRef('https://schema.org/Artery')
Article: URIRef = rdflib.term.URIRef('https://schema.org/Article')
AskAction: URIRef = rdflib.term.URIRef('https://schema.org/AskAction')
AskPublicNewsArticle: URIRef =
rdflib.term.URIRef('https://schema.org/AskPublicNewsArticle')
AssessAction: URIRef = rdflib.term.URIRef('https://schema.org/AssessAction')
AssignAction: URIRef = rdflib.term.URIRef('https://schema.org/AssignAction')
Atlas: URIRef = rdflib.term.URIRef('https://schema.org/Atlas')
Attorney: URIRef = rdflib.term.URIRef('https://schema.org/Attorney')
Audience: URIRef = rdflib.term.URIRef('https://schema.org/Audience')
AudioObject: URIRef = rdflib.term.URIRef('https://schema.org/AudioObject')
AudioObjectSnapshot: URIRef =
rdflib.term.URIRef('https://schema.org/AudioObjectSnapshot')
Audiobook: URIRef = rdflib.term.URIRef('https://schema.org/Audiobook')
AudiobookFormat: URIRef = rdflib.term.URIRef('https://schema.org/AudiobookFormat')
AuthoritativeLegalValue: URIRef =
rdflib.term.URIRef('https://schema.org/AuthoritativeLegalValue')
AuthorizeAction: URIRef = rdflib.term.URIRef('https://schema.org/AuthorizeAction')
AutoBodyShop: URIRef = rdflib.term.URIRef('https://schema.org/AutoBodyShop')
AutoDealer: URIRef = rdflib.term.URIRef('https://schema.org/AutoDealer')
AutoPartsStore: URIRef = rdflib.term.URIRef('https://schema.org/AutoPartsStore')
AutoRental: URIRef = rdflib.term.URIRef('https://schema.org/AutoRental')
```

```
AutoRepair: URIRef = rdflib.term.URIRef('https://schema.org/AutoRepair')
AutoWash: URIRef = rdflib.term.URIRef('https://schema.org/AutoWash')
AutomatedTeller: URIRef = rdflib.term.URIRef('https://schema.org/AutomatedTeller')
AutomotiveBusiness: URIRef =
rdflib.term.URIRef('https://schema.org/AutomotiveBusiness')
Ayurvedic: URIRef = rdflib.term.URIRef('https://schema.org/Ayurvedic')
BackOrder: URIRef = rdflib.term.URIRef('https://schema.org/BackOrder')
BackgroundNewsArticle: URIRef =
rdflib.term.URIRef('https://schema.org/BackgroundNewsArticle')
Bacteria: URIRef = rdflib.term.URIRef('https://schema.org/Bacteria')
Bakery: URIRef = rdflib.term.URIRef('https://schema.org/Bakery')
Balance: URIRef = rdflib.term.URIRef('https://schema.org/Balance')
BankAccount: URIRef = rdflib.term.URIRef('https://schema.org/BankAccount')
BankOrCreditUnion: URIRef =
rdflib.term.URIRef('https://schema.org/BankOrCreditUnion')
BarOrPub: URIRef = rdflib.term.URIRef('https://schema.org/BarOrPub')
Barcode: URIRef = rdflib.term.URIRef('https://schema.org/Barcode')
BasicIncome: URIRef = rdflib.term.URIRef('https://schema.org/BasicIncome')
Beach: URIRef = rdflib.term.URIRef('https://schema.org/Beach')
BeautySalon: URIRef = rdflib.term.URIRef('https://schema.org/BeautySalon')
BedAndBreakfast: URIRef = rdflib.term.URIRef('https://schema.org/BedAndBreakfast')
BedDetails: URIRef = rdflib.term.URIRef('https://schema.org/BedDetails')
BedType: URIRef = rdflib.term.URIRef('https://schema.org/BedType')
BefriendAction: URIRef = rdflib.term.URIRef('https://schema.org/BefriendAction')
BenefitsHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/BenefitsHealthAspect')
BikeStore: URIRef = rdflib.term.URIRef('https://schema.org/BikeStore')
BioChemEntity: URIRef = rdflib.term.URIRef('https://schema.org/BioChemEntity')
Blog: URIRef = rdflib.term.URIRef('https://schema.org/Blog')
BlogPosting: URIRef = rdflib.term.URIRef('https://schema.org/BlogPosting')
BloodTest: URIRef = rdflib.term.URIRef('https://schema.org/BloodTest')
BoardingPolicyType: URIRef =
rdflib.term.URIRef('https://schema.org/BoardingPolicyType')
```

```
BoatReservation: URIRef = rdflib.term.URIRef('https://schema.org/BoatReservation')
BoatTerminal: URIRef = rdflib.term.URIRef('https://schema.org/BoatTerminal')
BoatTrip: URIRef = rdflib.term.URIRef('https://schema.org/BoatTrip')
BodyMeasurementArm: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementArm')
BodyMeasurementBust: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementBust')
BodyMeasurementChest: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementChest')
BodyMeasurementFoot: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementFoot')
BodyMeasurementHand: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementHand')
BodyMeasurementHead: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementHead')
BodyMeasurementHeight: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementHeight')
BodyMeasurementHips: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementHips')
BodyMeasurementInsideLeg: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementInsideLeg')
BodyMeasurementNeck: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementNeck')
BodyMeasurementTypeEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementTypeEnumeration')
BodyMeasurementUnderbust: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementUnderbust')
BodyMeasurementWaist: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementWaist')
BodyMeasurementWeight: URIRef =
rdflib.term.URIRef('https://schema.org/BodyMeasurementWeight')
BodyOfWater: URIRef = rdflib.term.URIRef('https://schema.org/BodyOfWater')
Bone: URIRef = rdflib.term.URIRef('https://schema.org/Bone')
Book: URIRef = rdflib.term.URIRef('https://schema.org/Book')
BookFormatType: URIRef = rdflib.term.URIRef('https://schema.org/BookFormatType')
BookSeries: URIRef = rdflib.term.URIRef('https://schema.org/BookSeries')
```

```
BookStore: URIRef = rdflib.term.URIRef('https://schema.org/BookStore')
BookmarkAction: URIRef = rdflib.term.URIRef('https://schema.org/BookmarkAction')
Boolean: URIRef = rdflib.term.URIRef('https://schema.org/Boolean')
BorrowAction: URIRef = rdflib.term.URIRef('https://schema.org/BorrowAction')
BowlingAlley: URIRef = rdflib.term.URIRef('https://schema.org/BowlingAlley')
BrainStructure: URIRef = rdflib.term.URIRef('https://schema.org/BrainStructure')
Brand: URIRef = rdflib.term.URIRef('https://schema.org/Brand')
BreadcrumbList: URIRef = rdflib.term.URIRef('https://schema.org/BreadcrumbList')
Brewery: URIRef = rdflib.term.URIRef('https://schema.org/Brewery')
Bridge: URIRef = rdflib.term.URIRef('https://schema.org/Bridge')
BroadcastChannel: URIRef =
rdflib.term.URIRef('https://schema.org/BroadcastChannel')
BroadcastEvent: URIRef = rdflib.term.URIRef('https://schema.org/BroadcastEvent')
BroadcastFrequencySpecification: URIRef =
rdflib.term.URIRef('https://schema.org/BroadcastFrequencySpecification')
BroadcastRelease: URIRef =
rdflib.term.URIRef('https://schema.org/BroadcastRelease')
BroadcastService: URIRef =
rdflib.term.URIRef('https://schema.org/BroadcastService')
BrokerageAccount: URIRef =
rdflib.term.URIRef('https://schema.org/BrokerageAccount')
BuddhistTemple: URIRef = rdflib.term.URIRef('https://schema.org/BuddhistTemple')
BusOrCoach: URIRef = rdflib.term.URIRef('https://schema.org/BusOrCoach')
BusReservation: URIRef = rdflib.term.URIRef('https://schema.org/BusReservation')
BusStation: URIRef = rdflib.term.URIRef('https://schema.org/BusStation')
BusStop: URIRef = rdflib.term.URIRef('https://schema.org/BusStop')
BusTrip: URIRef = rdflib.term.URIRef('https://schema.org/BusTrip')
BusinessAudience: URIRef =
rdflib.term.URIRef('https://schema.org/BusinessAudience')
BusinessEntityType: URIRef =
rdflib.term.URIRef('https://schema.org/BusinessEntityType')
BusinessEvent: URIRef = rdflib.term.URIRef('https://schema.org/BusinessEvent')
BusinessFunction: URIRef =
rdflib.term.URIRef('https://schema.org/BusinessFunction')
```

```
BusinessSupport: URIRef = rdflib.term.URIRef('https://schema.org/BusinessSupport')
BuyAction: URIRef = rdflib.term.URIRef('https://schema.org/BuyAction')
CDCPMDRecord: URIRef = rdflib.term.URIRef('https://schema.org/CDCPMDRecord')
CDFormat: URIRef = rdflib.term.URIRef('https://schema.org/CDFormat')
CT: URIRef = rdflib.term.URIRef('https://schema.org/CT')
CableOrSatelliteService: URIRef =
rdflib.term.URIRef('https://schema.org/CableOrSatelliteService')
CafeOrCoffeeShop: URIRef =
rdflib.term.URIRef('https://schema.org/CafeOrCoffeeShop')
Campground: URIRef = rdflib.term.URIRef('https://schema.org/Campground')
CampingPitch: URIRef = rdflib.term.URIRef('https://schema.org/CampingPitch')
Canal: URIRef = rdflib.term.URIRef('https://schema.org/Canal')
CancelAction: URIRef = rdflib.term.URIRef('https://schema.org/CancelAction')
Car: URIRef = rdflib.term.URIRef('https://schema.org/Car')
CarUsageType: URIRef = rdflib.term.URIRef('https://schema.org/CarUsageType')
Cardiovascular: URIRef = rdflib.term.URIRef('https://schema.org/Cardiovascular')
CardiovascularExam: URIRef =
rdflib.term.URIRef('https://schema.org/CardiovascularExam')
CaseSeries: URIRef = rdflib.term.URIRef('https://schema.org/CaseSeries')
Casino: URIRef = rdflib.term.URIRef('https://schema.org/Casino')
CassetteFormat: URIRef = rdflib.term.URIRef('https://schema.org/CassetteFormat')
CategoryCode: URIRef = rdflib.term.URIRef('https://schema.org/CategoryCode')
CategoryCodeSet: URIRef = rdflib.term.URIRef('https://schema.org/CategoryCodeSet')
CatholicChurch: URIRef = rdflib.term.URIRef('https://schema.org/CatholicChurch')
CausesHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/CausesHealthAspect')
Cemetery: URIRef = rdflib.term.URIRef('https://schema.org/Cemetery')
Chapter: URIRef = rdflib.term.URIRef('https://schema.org/Chapter')
CharitableIncorporatedOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/CharitableIncorporatedOrganization')
CheckAction: URIRef = rdflib.term.URIRef('https://schema.org/CheckAction')
CheckInAction: URIRef = rdflib.term.URIRef('https://schema.org/CheckInAction')
CheckOutAction: URIRef = rdflib.term.URIRef('https://schema.org/CheckOutAction')
```



```
CheckoutPage: URIRef = rdflib.term.URIRef('https://schema.org/CheckoutPage')

ChemicalSubstance: URIRef =
rdflib.term.URIRef('https://schema.org/ChemicalSubstance')

ChildCare: URIRef = rdflib.term.URIRef('https://schema.org/ChildCare')

ChildrensEvent: URIRef = rdflib.term.URIRef('https://schema.org/ChildrensEvent')

Chiropractic: URIRef = rdflib.term.URIRef('https://schema.org/Chiropractic')

ChooseAction: URIRef = rdflib.term.URIRef('https://schema.org/ChooseAction')

Church: URIRef = rdflib.term.URIRef('https://schema.org/Church')

City: URIRef = rdflib.term.URIRef('https://schema.org/City')

CityHall: URIRef = rdflib.term.URIRef('https://schema.org/CityHall')

CivicStructure: URIRef = rdflib.term.URIRef('https://schema.org/CivicStructure')

Claim: URIRef = rdflib.term.URIRef('https://schema.org/Claim')

ClaimReview: URIRef = rdflib.term.URIRef('https://schema.org/ClaimReview')

Class: URIRef = rdflib.term.URIRef('https://schema.org/Class')

CleaningFee: URIRef = rdflib.term.URIRef('https://schema.org/CleaningFee')

Clinician: URIRef = rdflib.term.URIRef('https://schema.org/Clinician')

Clip: URIRef = rdflib.term.URIRef('https://schema.org/Clip')

ClothingStore: URIRef = rdflib.term.URIRef('https://schema.org/ClothingStore')

CoOp: URIRef = rdflib.term.URIRef('https://schema.org/CoOp')

Code: URIRef = rdflib.term.URIRef('https://schema.org/Code')

CohortStudy: URIRef = rdflib.term.URIRef('https://schema.org/CohortStudy')

Collection: URIRef = rdflib.term.URIRef('https://schema.org/Collection')

CollectionPage: URIRef = rdflib.term.URIRef('https://schema.org/CollectionPage')

CollegeOrUniversity: URIRef =
rdflib.term.URIRef('https://schema.org/CollegeOrUniversity')

ComedyClub: URIRef = rdflib.term.URIRef('https://schema.org/ComedyClub')

ComedyEvent: URIRef = rdflib.term.URIRef('https://schema.org/ComedyEvent')

ComicCoverArt: URIRef = rdflib.term.URIRef('https://schema.org/ComicCoverArt')

ComicIssue: URIRef = rdflib.term.URIRef('https://schema.org/ComicIssue')

ComicSeries: URIRef = rdflib.term.URIRef('https://schema.org/ComicSeries')

ComicStory: URIRef = rdflib.term.URIRef('https://schema.org/ComicStory')
```



```
Comment: URIRef = rdflib.term.URIRef('https://schema.org/Comment')

CommentAction: URIRef = rdflib.term.URIRef('https://schema.org/CommentAction')

CommentPermission: URIRef =
rdflib.term.URIRef('https://schema.org/CommentPermission')

CommunicateAction: URIRef =
rdflib.term.URIRef('https://schema.org/CommunicateAction')

CommunityHealth: URIRef = rdflib.term.URIRef('https://schema.org/CommunityHealth')

CompilationAlbum: URIRef =
rdflib.term.URIRef('https://schema.org/CompilationAlbum')

CompleteDataFeed: URIRef =
rdflib.term.URIRef('https://schema.org/CompleteDataFeed')

Completed: URIRef = rdflib.term.URIRef('https://schema.org/Completed')

CompletedActionStatus: URIRef =
rdflib.term.URIRef('https://schema.org/CompletedActionStatus')

CompoundPriceSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/CompoundPriceSpecification')

ComputerLanguage: URIRef =
rdflib.term.URIRef('https://schema.org/ComputerLanguage')

ComputerStore: URIRef = rdflib.term.URIRef('https://schema.org/ComputerStore')

ConfirmAction: URIRef = rdflib.term.URIRef('https://schema.org/ConfirmAction')

Consortium: URIRef = rdflib.term.URIRef('https://schema.org/Consortium')

ConsumeAction: URIRef = rdflib.term.URIRef('https://schema.org/ConsumeAction')

ContactPage: URIRef = rdflib.term.URIRef('https://schema.org/ContactPage')

ContactPoint: URIRef = rdflib.term.URIRef('https://schema.org/ContactPoint')

ContactPointOption: URIRef =
rdflib.term.URIRef('https://schema.org/ContactPointOption')

ContagiousnessHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/ContagiousnessHealthAspect')

Continent: URIRef = rdflib.term.URIRef('https://schema.org/Continent')

ControlAction: URIRef = rdflib.term.URIRef('https://schema.org/ControlAction')

ConvenienceStore: URIRef =
rdflib.term.URIRef('https://schema.org/ConvenienceStore')

Conversation: URIRef = rdflib.term.URIRef('https://schema.org/Conversation')

CookAction: URIRef = rdflib.term.URIRef('https://schema.org/CookAction')

Corporation: URIRef = rdflib.term.URIRef('https://schema.org/Corporation')
```

```

CorrectionComment: URIRef =
rdflib.term.URIRef('https://schema.org/CorrectionComment')

Country: URIRef = rdflib.term.URIRef('https://schema.org/Country')

Course: URIRef = rdflib.term.URIRef('https://schema.org/Course')

CourseInstance: URIRef = rdflib.term.URIRef('https://schema.org/CourseInstance')

Courthouse: URIRef = rdflib.term.URIRef('https://schema.org/Courthouse')

CoverArt: URIRef = rdflib.term.URIRef('https://schema.org/CoverArt')

CovidTestingFacility: URIRef =
rdflib.term.URIRef('https://schema.org/CovidTestingFacility')

CreateAction: URIRef = rdflib.term.URIRef('https://schema.org/CreateAction')

CreativeWork: URIRef = rdflib.term.URIRef('https://schema.org/CreativeWork')

CreativeWorkSeason: URIRef =
rdflib.term.URIRef('https://schema.org/CreativeWorkSeason')

CreativeWorkSeries: URIRef =
rdflib.term.URIRef('https://schema.org/CreativeWorkSeries')

CreditCard: URIRef = rdflib.term.URIRef('https://schema.org/CreditCard')

Crematorium: URIRef = rdflib.term.URIRef('https://schema.org/Crematorium')

CriticReview: URIRef = rdflib.term.URIRef('https://schema.org/CriticReview')

CrossSectional: URIRef = rdflib.term.URIRef('https://schema.org/CrossSectional')

CssSelectorType: URIRef = rdflib.term.URIRef('https://schema.org/CssSelectorType')

CurrencyConversionService: URIRef =
rdflib.term.URIRef('https://schema.org/CurrencyConversionService')

DDxElement: URIRef = rdflib.term.URIRef('https://schema.org/DDxElement')

DJMixAlbum: URIRef = rdflib.term.URIRef('https://schema.org/DJMixaAlbum')

DVDFormat: URIRef = rdflib.term.URIRef('https://schema.org/DVDFormat')

DamagedCondition: URIRef =
rdflib.term.URIRef('https://schema.org/DamagedCondition')

DanceEvent: URIRef = rdflib.term.URIRef('https://schema.org/DanceEvent')

DanceGroup: URIRef = rdflib.term.URIRef('https://schema.org/DanceGroup')

DataCatalog: URIRef = rdflib.term.URIRef('https://schema.org/DataCatalog')

DataDownload: URIRef = rdflib.term.URIRef('https://schema.org/DataDownload')

DataFeed: URIRef = rdflib.term.URIRef('https://schema.org/DataFeed')

DataFeedItem: URIRef = rdflib.term.URIRef('https://schema.org/DataFeedItem')

```

```
DataType: URIRef = rdflib.term.URIRef('https://schema.org/DataType')
Dataset: URIRef = rdflib.term.URIRef('https://schema.org/Dataset')
Date: URIRef = rdflib.term.URIRef('https://schema.org/Date')
DateTime: URIRef = rdflib.term.URIRef('https://schema.org/DateTime')
DatedMoneySpecification: URIRef =
rdflib.term.URIRef('https://schema.org/DatedMoneySpecification')
DayOfWeek: URIRef = rdflib.term.URIRef('https://schema.org/DayOfWeek')
DaySpa: URIRef = rdflib.term.URIRef('https://schema.org/DaySpa')
DeactivateAction: URIRef =
rdflib.term.URIRef('https://schema.org/DeactivateAction')
DecontextualizedContent: URIRef =
rdflib.term.URIRef('https://schema.org/DecontextualizedContent')
DefenceEstablishment: URIRef =
rdflib.term.URIRef('https://schema.org/DefenceEstablishment')
DefinedRegion: URIRef = rdflib.term.URIRef('https://schema.org/DefinedRegion')
DefinedTerm: URIRef = rdflib.term.URIRef('https://schema.org/DefinedTerm')
DefinedTermSet: URIRef = rdflib.term.URIRef('https://schema.org/DefinedTermSet')
DefinitiveLegalValue: URIRef =
rdflib.term.URIRef('https://schema.org/DefinitiveLegalValue')
DeleteAction: URIRef = rdflib.term.URIRef('https://schema.org/DeleteAction')
DeliveryChargeSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/DeliveryChargeSpecification')
DeliveryEvent: URIRef = rdflib.term.URIRef('https://schema.org/DeliveryEvent')
DeliveryMethod: URIRef = rdflib.term.URIRef('https://schema.org/DeliveryMethod')
DeliveryTimeSettings: URIRef =
rdflib.term.URIRef('https://schema.org/DeliveryTimeSettings')
Demand: URIRef = rdflib.term.URIRef('https://schema.org/Demand')
DemoAlbum: URIRef = rdflib.term.URIRef('https://schema.org/DemoAlbum')
Dentist: URIRef = rdflib.term.URIRef('https://schema.org/Dentist')
Dentistry: URIRef = rdflib.term.URIRef('https://schema.org/Dentistry')
DepartAction: URIRef = rdflib.term.URIRef('https://schema.org/DepartAction')
DepartmentStore: URIRef = rdflib.term.URIRef('https://schema.org/DepartmentStore')
DepositAccount: URIRef = rdflib.term.URIRef('https://schema.org/DepositAccount')
```

```
Dermatologic: URIRef = rdflib.term.URIRef('https://schema.org/Dermatologic')
Dermatology: URIRef = rdflib.term.URIRef('https://schema.org/Dermatology')
DiabeticDiet: URIRef = rdflib.term.URIRef('https://schema.org/DiabeticDiet')
Diagnostic: URIRef = rdflib.term.URIRef('https://schema.org/Diagnostic')
DiagnosticLab: URIRef = rdflib.term.URIRef('https://schema.org/DiagnosticLab')
DiagnosticProcedure: URIRef =
rdflib.term.URIRef('https://schema.org/DiagnosticProcedure')
Diet: URIRef = rdflib.term.URIRef('https://schema.org/Diet')
DietNutrition: URIRef = rdflib.term.URIRef('https://schema.org/DietNutrition')
DietarySupplement: URIRef =
rdflib.term.URIRef('https://schema.org/DietarySupplement')
DigitalAudioTapeFormat: URIRef =
rdflib.term.URIRef('https://schema.org/DigitalAudioTapeFormat')
DigitalDocument: URIRef = rdflib.term.URIRef('https://schema.org/DigitalDocument')
DigitalDocumentPermission: URIRef =
rdflib.term.URIRef('https://schema.org/DigitalDocumentPermission')
DigitalDocumentPermissionType: URIRef =
rdflib.term.URIRef('https://schema.org/DigitalDocumentPermissionType')
DigitalFormat: URIRef = rdflib.term.URIRef('https://schema.org/DigitalFormat')
DisabilitySupport: URIRef =
rdflib.term.URIRef('https://schema.org/DisabilitySupport')
DisagreeAction: URIRef = rdflib.term.URIRef('https://schema.org/DisagreeAction')
Discontinued: URIRef = rdflib.term.URIRef('https://schema.org/Discontinued')
DiscoverAction: URIRef = rdflib.term.URIRef('https://schema.org/DiscoverAction')
DiscussionForumPosting: URIRef =
rdflib.term.URIRef('https://schema.org/DiscussionForumPosting')
DislikeAction: URIRef = rdflib.term.URIRef('https://schema.org/DislikeAction')
Distance: URIRef = rdflib.term.URIRef('https://schema.org/Distance')
DistanceFee: URIRef = rdflib.term.URIRef('https://schema.org/DistanceFee')
Distillery: URIRef = rdflib.term.URIRef('https://schema.org/Distillery')
DonateAction: URIRef = rdflib.term.URIRef('https://schema.org/DonateAction')
DoseSchedule: URIRef = rdflib.term.URIRef('https://schema.org/DoseSchedule')
DoubleBlindedTrial: URIRef =
rdflib.term.URIRef('https://schema.org/DoubleBlindedTrial')
```

```
DownloadAction: URIRef = rdflib.term.URIRef('https://schema.org/DownloadAction')
Downpayment: URIRef = rdflib.term.URIRef('https://schema.org/Downpayment')
DrawAction: URIRef = rdflib.term.URIRef('https://schema.org/DrawAction')
Drawing: URIRef = rdflib.term.URIRef('https://schema.org/Drawing')
DrinkAction: URIRef = rdflib.term.URIRef('https://schema.org/DrinkAction')
DriveWheelConfigurationValue: URIRef =
rdflib.term.URIRef('https://schema.org/DriveWheelConfigurationValue')
DrivingSchoolVehicleUsage: URIRef =
rdflib.term.URIRef('https://schema.org/DrivingSchoolVehicleUsage')
Drug: URIRef = rdflib.term.URIRef('https://schema.org/Drug')
DrugClass: URIRef = rdflib.term.URIRef('https://schema.org/DrugClass')
DrugCost: URIRef = rdflib.term.URIRef('https://schema.org/DrugCost')
DrugCostCategory: URIRef =
rdflib.term.URIRef('https://schema.org/DrugCostCategory')
DrugLegalStatus: URIRef = rdflib.term.URIRef('https://schema.org/DrugLegalStatus')
DrugPregnancyCategory: URIRef =
rdflib.term.URIRef('https://schema.org/DrugPregnancyCategory')
DrugPrescriptionStatus: URIRef =
rdflib.term.URIRef('https://schema.org/DrugPrescriptionStatus')
DrugStrength: URIRef = rdflib.term.URIRef('https://schema.org/DrugStrength')
DryCleaningOrLaundry: URIRef =
rdflib.term.URIRef('https://schema.org/DryCleaningOrLaundry')
Duration: URIRef = rdflib.term.URIRef('https://schema.org/Duration')
EBook: URIRef = rdflib.term.URIRef('https://schema.org/EBook')
EPRelease: URIRef = rdflib.term.URIRef('https://schema.org/EPRelease')
EUEnergyEfficiencyCategoryA: URIRef =
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryA')
EUEnergyEfficiencyCategoryA1Plus: URIRef =
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryA1Plus')
EUEnergyEfficiencyCategoryA2Plus: URIRef =
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryA2Plus')
EUEnergyEfficiencyCategoryA3Plus: URIRef =
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryA3Plus')
EUEnergyEfficiencyCategoryB: URIRef =
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryB')
```

```
EUEnergyEfficiencyCategoryC: URIRef =  
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryC')  
  
EUEnergyEfficiencyCategoryD: URIRef =  
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryD')  
  
EUEnergyEfficiencyCategoryE: URIRef =  
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryE')  
  
EUEnergyEfficiencyCategoryF: URIRef =  
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryF')  
  
EUEnergyEfficiencyCategoryG: URIRef =  
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyCategoryG')  
  
EUEnergyEfficiencyEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/EUEnergyEfficiencyEnumeration')  
  
Ear: URIRef = rdflib.term.URIRef('https://schema.org/Ear')  
  
EatAction: URIRef = rdflib.term.URIRef('https://schema.org/EatAction')  
  
EditedOrCroppedContent: URIRef =  
rdflib.term.URIRef('https://schema.org/EditedOrCroppedContent')  
  
EducationEvent: URIRef = rdflib.term.URIRef('https://schema.org/EducationEvent')  
  
EducationalAudience: URIRef =  
rdflib.term.URIRef('https://schema.org/EducationalAudience')  
  
EducationalOccupationalCredential: URIRef =  
rdflib.term.URIRef('https://schema.org/EducationalOccupationalCredential')  
  
EducationalOccupationalProgram: URIRef =  
rdflib.term.URIRef('https://schema.org/EducationalOccupationalProgram')  
  
EducationalOrganization: URIRef =  
rdflib.term.URIRef('https://schema.org/EducationalOrganization')  
  
EffectivenessHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/EffectivenessHealthAspect')  
  
Electrician: URIRef = rdflib.term.URIRef('https://schema.org/Electrician')  
  
ElectronicsStore: URIRef =  
rdflib.term.URIRef('https://schema.org/ElectronicsStore')  
  
ElementarySchool: URIRef =  
rdflib.term.URIRef('https://schema.org/ElementarySchool')  
  
EmailMessage: URIRef = rdflib.term.URIRef('https://schema.org/EmailMessage')  
  
Embassy: URIRef = rdflib.term.URIRef('https://schema.org/Embassy')  
  
Emergency: URIRef = rdflib.term.URIRef('https://schema.org/Emergency')  
  
EmergencyService: URIRef =  
rdflib.term.URIRef('https://schema.org/EmergencyService')
```

```
EmployeeRole: URIRef = rdflib.term.URIRef('https://schema.org/EmployeeRole')

EmployerAggregateRating: URIRef =
rdflib.term.URIRef('https://schema.org/EmployerAggregateRating')

EmployerReview: URIRef = rdflib.term.URIRef('https://schema.org/EmployerReview')

EmploymentAgency: URIRef =
rdflib.term.URIRef('https://schema.org/EmploymentAgency')

Endocrine: URIRef = rdflib.term.URIRef('https://schema.org/Endocrine')

EndorseAction: URIRef = rdflib.term.URIRef('https://schema.org/EndorseAction')

EndorsementRating: URIRef =
rdflib.term.URIRef('https://schema.org/EndorsementRating')

Energy: URIRef = rdflib.term.URIRef('https://schema.org/Energy')

EnergyConsumptionDetails: URIRef =
rdflib.term.URIRef('https://schema.org/EnergyConsumptionDetails')

EnergyEfficiencyEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/EnergyEfficiencyEnumeration')

EnergyStarCertified: URIRef =
rdflib.term.URIRef('https://schema.org/EnergyStarCertified')

EnergyStarEnergyEfficiencyEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/EnergyStarEnergyEfficiencyEnumeration')

EngineSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/EngineSpecification')

EnrollingByInvitation: URIRef =
rdflib.term.URIRef('https://schema.org/EnrollingByInvitation')

EntertainmentBusiness: URIRef =
rdflib.term.URIRef('https://schema.org/EntertainmentBusiness')

EntryPoint: URIRef = rdflib.term.URIRef('https://schema.org/EntryPoint')

Enumeration: URIRef = rdflib.term.URIRef('https://schema.org/Enumeration')

Episode: URIRef = rdflib.term.URIRef('https://schema.org/Episode')

Event: URIRef = rdflib.term.URIRef('https://schema.org/Event')

EventAttendanceModeEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/EventAttendanceModeEnumeration')

EventCancelled: URIRef = rdflib.term.URIRef('https://schema.org/EventCancelled')

EventMovedOnline: URIRef =
rdflib.term.URIRef('https://schema.org/EventMovedOnline')

EventPostponed: URIRef = rdflib.term.URIRef('https://schema.org/EventPostponed')
```



```
EventRescheduled: URIRef =  
rdflib.term.URIRef('https://schema.org/EventRescheduled')  
  
EventReservation: URIRef =  
rdflib.term.URIRef('https://schema.org/EventReservation')  
  
EventScheduled: URIRef = rdflib.term.URIRef('https://schema.org/EventScheduled')  
  
EventSeries: URIRef = rdflib.term.URIRef('https://schema.org/EventSeries')  
  
EventStatusType: URIRef = rdflib.term.URIRef('https://schema.org/EventStatusType')  
  
EventVenue: URIRef = rdflib.term.URIRef('https://schema.org/EventVenue')  
  
EvidenceLevelA: URIRef = rdflib.term.URIRef('https://schema.org/EvidenceLevelA')  
  
EvidenceLevelB: URIRef = rdflib.term.URIRef('https://schema.org/EvidenceLevelB')  
  
EvidenceLevelC: URIRef = rdflib.term.URIRef('https://schema.org/EvidenceLevelC')  
  
ExchangeRateSpecification: URIRef =  
rdflib.term.URIRef('https://schema.org/ExchangeRateSpecification')  
  
ExchangeRefund: URIRef = rdflib.term.URIRef('https://schema.org/ExchangeRefund')  
  
ExerciseAction: URIRef = rdflib.term.URIRef('https://schema.org/ExerciseAction')  
  
ExerciseGym: URIRef = rdflib.term.URIRef('https://schema.org/ExerciseGym')  
  
ExercisePlan: URIRef = rdflib.term.URIRef('https://schema.org/ExercisePlan')  
  
ExhibitionEvent: URIRef = rdflib.term.URIRef('https://schema.org/ExhibitionEvent')  
  
Eye: URIRef = rdflib.term.URIRef('https://schema.org/Eye')  
  
FAQPage: URIRef = rdflib.term.URIRef('https://schema.org/FAQPage')  
  
FDACategoryA: URIRef = rdflib.term.URIRef('https://schema.org/FDACategoryA')  
  
FDACategoryB: URIRef = rdflib.term.URIRef('https://schema.org/FDACategoryB')  
  
FDACategoryC: URIRef = rdflib.term.URIRef('https://schema.org/FDACategoryC')  
  
FDACategoryD: URIRef = rdflib.term.URIRef('https://schema.org/FDACategoryD')  
  
FDACategoryX: URIRef = rdflib.term.URIRef('https://schema.org/FDACategoryX')  
  
FDAnotEvaluated: URIRef = rdflib.term.URIRef('https://schema.org/FDAnotEvaluated')  
  
FMRadioChannel: URIRef = rdflib.term.URIRef('https://schema.org/FMRadioChannel')  
  
FailedActionStatus: URIRef =  
rdflib.term.URIRef('https://schema.org/FailedActionStatus')  
  
FastFoodRestaurant: URIRef =  
rdflib.term.URIRef('https://schema.org/FastFoodRestaurant')  
  
Female: URIRef = rdflib.term.URIRef('https://schema.org/Female')  
  
Festival: URIRef = rdflib.term.URIRef('https://schema.org/Festival')
```



```
FilmAction: URIRef = rdflib.term.URIRef('https://schema.org/FilmAction')

FinancialProduct: URIRef =
rdflib.term.URIRef('https://schema.org/FinancialProduct')

FinancialService: URIRef =
rdflib.term.URIRef('https://schema.org/FinancialService')

FindAction: URIRef = rdflib.term.URIRef('https://schema.org/FindAction')

FireStation: URIRef = rdflib.term.URIRef('https://schema.org/FireStation')

Flexibility: URIRef = rdflib.term.URIRef('https://schema.org/Flexibility')

Flight: URIRef = rdflib.term.URIRef('https://schema.org/Flight')

FlightReservation: URIRef =
rdflib.term.URIRef('https://schema.org/FlightReservation')

Float: URIRef = rdflib.term.URIRef('https://schema.org/Float')

FloorPlan: URIRef = rdflib.term.URIRef('https://schema.org/FloorPlan')

Florist: URIRef = rdflib.term.URIRef('https://schema.org/Florist')

FollowAction: URIRef = rdflib.term.URIRef('https://schema.org/FollowAction')

FoodEstablishment: URIRef =
rdflib.term.URIRef('https://schema.org/FoodEstablishment')

FoodEstablishmentReservation: URIRef =
rdflib.term.URIRef('https://schema.org/FoodEstablishmentReservation')

FoodEvent: URIRef = rdflib.term.URIRef('https://schema.org/FoodEvent')

FoodService: URIRef = rdflib.term.URIRef('https://schema.org/FoodService')

FourWheelDriveConfiguration: URIRef =
rdflib.term.URIRef('https://schema.org/FourWheelDriveConfiguration')

FreeReturn: URIRef = rdflib.term.URIRef('https://schema.org/FreeReturn')

Friday: URIRef = rdflib.term.URIRef('https://schema.org/Friday')

FrontWheelDriveConfiguration: URIRef =
rdflib.term.URIRef('https://schema.org/FrontWheelDriveConfiguration')

FullRefund: URIRef = rdflib.term.URIRef('https://schema.org/FullRefund')

FundingAgency: URIRef = rdflib.term.URIRef('https://schema.org/FundingAgency')

FundingScheme: URIRef = rdflib.term.URIRef('https://schema.org/FundingScheme')

Fungus: URIRef = rdflib.term.URIRef('https://schema.org/Fungus')

FurnitureStore: URIRef = rdflib.term.URIRef('https://schema.org/FurnitureStore')

Game: URIRef = rdflib.term.URIRef('https://schema.org/Game')
```

```
GamePlayMode: URIRef = rdflib.term.URIRef('https://schema.org/GamePlayMode')

GameServer: URIRef = rdflib.term.URIRef('https://schema.org/GameServer')

GameServerStatus: URIRef =
rdflib.term.URIRef('https://schema.org/GameServerStatus')

GardenStore: URIRef = rdflib.term.URIRef('https://schema.org/GardenStore')

GasStation: URIRef = rdflib.term.URIRef('https://schema.org/GasStation')

Gastroenterologic: URIRef =
rdflib.term.URIRef('https://schema.org/Gastroenterologic')

GatedResidenceCommunity: URIRef =
rdflib.term.URIRef('https://schema.org/GatedResidenceCommunity')

GenderType: URIRef = rdflib.term.URIRef('https://schema.org/GenderType')

Gene: URIRef = rdflib.term.URIRef('https://schema.org/Gene')

GeneralContractor: URIRef =
rdflib.term.URIRef('https://schema.org/GeneralContractor')

Genetic: URIRef = rdflib.term.URIRef('https://schema.org/Genetic')

Genitourinary: URIRef = rdflib.term.URIRef('https://schema.org/Genitourinary')

GeoCircle: URIRef = rdflib.term.URIRef('https://schema.org/GeoCircle')

GeoCoordinates: URIRef = rdflib.term.URIRef('https://schema.org/GeoCoordinates')

GeoShape: URIRef = rdflib.term.URIRef('https://schema.org/GeoShape')

GeospatialGeometry: URIRef =
rdflib.term.URIRef('https://schema.org/GeospatialGeometry')

Geriatric: URIRef = rdflib.term.URIRef('https://schema.org/Geriatric')

GettingAccessHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/GettingAccessHealthAspect')

GiveAction: URIRef = rdflib.term.URIRef('https://schema.org/GiveAction')

GlutenFreeDiet: URIRef = rdflib.term.URIRef('https://schema.org/GlutenFreeDiet')

GolfCourse: URIRef = rdflib.term.URIRef('https://schema.org/GolfCourse')

GovernmentBenefitsType: URIRef =
rdflib.term.URIRef('https://schema.org/GovernmentBenefitsType')

GovernmentBuilding: URIRef =
rdflib.term.URIRef('https://schema.org/GovernmentBuilding')

GovernmentOffice: URIRef =
rdflib.term.URIRef('https://schema.org/GovernmentOffice')

GovernmentOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/GovernmentOrganization')
```

```
GovernmentPermit: URIRef =  
rdflib.term.URIRef('https://schema.org/GovernmentPermit')  
  
GovernmentService: URIRef =  
rdflib.term.URIRef('https://schema.org/GovernmentService')  
  
Grant: URIRef = rdflib.term.URIRef('https://schema.org/Grant')  
  
GraphicNovel: URIRef = rdflib.term.URIRef('https://schema.org/GraphicNovel')  
  
GroceryStore: URIRef = rdflib.term.URIRef('https://schema.org/GroceryStore')  
  
GroupBoardingPolicy: URIRef =  
rdflib.term.URIRef('https://schema.org/GroupBoardingPolicy')  
  
Guide: URIRef = rdflib.term.URIRef('https://schema.org/Guide')  
  
Gynecologic: URIRef = rdflib.term.URIRef('https://schema.org/Gynecologic')  
  
HVACBusiness: URIRef = rdflib.term.URIRef('https://schema.org/HVACBusiness')  
  
Hackathon: URIRef = rdflib.term.URIRef('https://schema.org/Hackathon')  
  
HairSalon: URIRef = rdflib.term.URIRef('https://schema.org/HairSalon')  
  
HalalDiet: URIRef = rdflib.term.URIRef('https://schema.org/HalalDiet')  
  
Hardcover: URIRef = rdflib.term.URIRef('https://schema.org/Hardcover')  
  
HardwareStore: URIRef = rdflib.term.URIRef('https://schema.org/HardwareStore')  
  
Head: URIRef = rdflib.term.URIRef('https://schema.org/Head')  
  
HealthAndBeautyBusiness: URIRef =  
rdflib.term.URIRef('https://schema.org/HealthAndBeautyBusiness')  
  
HealthAspectEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/HealthAspectEnumeration')  
  
HealthCare: URIRef = rdflib.term.URIRef('https://schema.org/HealthCare')  
  
HealthClub: URIRef = rdflib.term.URIRef('https://schema.org/HealthClub')  
  
HealthInsurancePlan: URIRef =  
rdflib.term.URIRef('https://schema.org/HealthInsurancePlan')  
  
HealthPlanCostSharingSpecification: URIRef =  
rdflib.term.URIRef('https://schema.org/HealthPlanCostSharingSpecification')  
  
HealthPlanFormulary: URIRef =  
rdflib.term.URIRef('https://schema.org/HealthPlanFormulary')  
  
HealthPlanNetwork: URIRef =  
rdflib.term.URIRef('https://schema.org/HealthPlanNetwork')  
  
HealthTopicContent: URIRef =  
rdflib.term.URIRef('https://schema.org/HealthTopicContent')
```

```
HearingImpairedSupported: URIRef =  
rdflib.term.URIRef('https://schema.org/HearingImpairedSupported')  
  
Hematologic: URIRef = rdflib.term.URIRef('https://schema.org/Hematologic')  
  
HighSchool: URIRef = rdflib.term.URIRef('https://schema.org/HighSchool')  
  
HinduDiet: URIRef = rdflib.term.URIRef('https://schema.org/HinduDiet')  
  
HinduTemple: URIRef = rdflib.term.URIRef('https://schema.org/HinduTemple')  
  
HobbyShop: URIRef = rdflib.term.URIRef('https://schema.org/HobbyShop')  
  
HomeAndConstructionBusiness: URIRef =  
rdflib.term.URIRef('https://schema.org/HomeAndConstructionBusiness')  
  
HomeGoodsStore: URIRef = rdflib.term.URIRef('https://schema.org/HomeGoodsStore')  
  
Homeopathic: URIRef = rdflib.term.URIRef('https://schema.org/Homeopathic')  
  
Hospital: URIRef = rdflib.term.URIRef('https://schema.org/Hospital')  
  
Hostel: URIRef = rdflib.term.URIRef('https://schema.org/Hostel')  
  
Hotel: URIRef = rdflib.term.URIRef('https://schema.org/Hotel')  
  
HotelRoom: URIRef = rdflib.term.URIRef('https://schema.org/HotelRoom')  
  
House: URIRef = rdflib.term.URIRef('https://schema.org/House')  
  
HousePainter: URIRef = rdflib.term.URIRef('https://schema.org/HousePainter')  
  
HowItWorksHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/HowItWorksHealthAspect')  
  
HowOrWhereHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/HowOrWhereHealthAspect')  
  
HowTo: URIRef = rdflib.term.URIRef('https://schema.org/HowTo')  
  
HowToDirection: URIRef = rdflib.term.URIRef('https://schema.org/HowToDirection')  
  
HowToItem: URIRef = rdflib.term.URIRef('https://schema.org/HowToItem')  
  
HowToSection: URIRef = rdflib.term.URIRef('https://schema.org/HowToSection')  
  
HowToStep: URIRef = rdflib.term.URIRef('https://schema.org/HowToStep')  
  
HowToSupply: URIRef = rdflib.term.URIRef('https://schema.org/HowToSupply')  
  
HowToTip: URIRef = rdflib.term.URIRef('https://schema.org/HowToTip')  
  
HowToTool: URIRef = rdflib.term.URIRef('https://schema.org/HowToTool')  
  
HyperToc: URIRef = rdflib.term.URIRef('https://schema.org/HyperToc')  
  
HyperTocEntry: URIRef = rdflib.term.URIRef('https://schema.org/HyperTocEntry')  
  
IceCreamShop: URIRef = rdflib.term.URIRef('https://schema.org/IceCreamShop')
```

```
IgnoreAction: URIRef = rdflib.term.URIRef('https://schema.org/IgnoreAction')
ImageGallery: URIRef = rdflib.term.URIRef('https://schema.org/ImageGallery')
ImageObject: URIRef = rdflib.term.URIRef('https://schema.org/ImageObject')
ImageObjectSnapshot: URIRef =
rdflib.term.URIRef('https://schema.org/ImageObjectSnapshot')
ImagingTest: URIRef = rdflib.term.URIRef('https://schema.org/ImagingTest')
InForce: URIRef = rdflib.term.URIRef('https://schema.org/InForce')
InStock: URIRef = rdflib.term.URIRef('https://schema.org/InStock')
InStoreOnly: URIRef = rdflib.term.URIRef('https://schema.org/InStoreOnly')
IndividualProduct: URIRef =
rdflib.term.URIRef('https://schema.org/IndividualProduct')
Infectious: URIRef = rdflib.term.URIRef('https://schema.org/Infectious')
InfectiousAgentClass: URIRef =
rdflib.term.URIRef('https://schema.org/InfectiousAgentClass')
InfectiousDisease: URIRef =
rdflib.term.URIRef('https://schema.org/InfectiousDisease')
InformAction: URIRef = rdflib.term.URIRef('https://schema.org/InformAction')
IngredientsHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/IngredientsHealthAspect')
InsertAction: URIRef = rdflib.term.URIRef('https://schema.org/InsertAction')
InstallAction: URIRef = rdflib.term.URIRef('https://schema.org/InstallAction')
Installment: URIRef = rdflib.term.URIRef('https://schema.org/Installment')
InsuranceAgency: URIRef = rdflib.term.URIRef('https://schema.org/InsuranceAgency')
Intangible: URIRef = rdflib.term.URIRef('https://schema.org/Intangible')
Integer: URIRef = rdflib.term.URIRef('https://schema.org/Integer')
InteractAction: URIRef = rdflib.term.URIRef('https://schema.org/InteractAction')
InteractionCounter: URIRef =
rdflib.term.URIRef('https://schema.org/InteractionCounter')
InternationalTrial: URIRef =
rdflib.term.URIRef('https://schema.org/InternationalTrial')
InternetCafe: URIRef = rdflib.term.URIRef('https://schema.org/InternetCafe')
InvestmentFund: URIRef = rdflib.term.URIRef('https://schema.org/InvestmentFund')
InvestmentOrDeposit: URIRef =
rdflib.term.URIRef('https://schema.org/InvestmentOrDeposit')
```

```
InviteAction: URIRef = rdflib.term.URIRef('https://schema.org/InviteAction')
Invoice: URIRef = rdflib.term.URIRef('https://schema.org/Invoice')
InvoicePrice: URIRef = rdflib.term.URIRef('https://schema.org/InvoicePrice')
ItemAvailability: URIRef =
rdflib.term.URIRef('https://schema.org/ItemAvailability')
ItemList: URIRef = rdflib.term.URIRef('https://schema.org/ItemList')
ItemListOrderAscending: URIRef =
rdflib.term.URIRef('https://schema.org/ItemListOrderAscending')
ItemListOrderDescending: URIRef =
rdflib.term.URIRef('https://schema.org/ItemListOrderDescending')
ItemListOrderType: URIRef =
rdflib.term.URIRef('https://schema.org/ItemListOrderType')
ItemListUnordered: URIRef =
rdflib.term.URIRef('https://schema.org/ItemListUnordered')
ItemPage: URIRef = rdflib.term.URIRef('https://schema.org/ItemPage')
JewelryStore: URIRef = rdflib.term.URIRef('https://schema.org/JewelryStore')
JobPosting: URIRef = rdflib.term.URIRef('https://schema.org/JobPosting')
JoinAction: URIRef = rdflib.term.URIRef('https://schema.org/JoinAction')
Joint: URIRef = rdflib.term.URIRef('https://schema.org/Joint')
KosherDiet: URIRef = rdflib.term.URIRef('https://schema.org/KosherDiet')
LaboratoryScience: URIRef =
rdflib.term.URIRef('https://schema.org/LaboratoryScience')
LakeBodyOfWater: URIRef = rdflib.term.URIRef('https://schema.org/LakeBodyOfWater')
Landform: URIRef = rdflib.term.URIRef('https://schema.org/Landform')
LandmarksOrHistoricalBuildings: URIRef =
rdflib.term.URIRef('https://schema.org/LandmarksOrHistoricalBuildings')
Language: URIRef = rdflib.term.URIRef('https://schema.org/Language')
LaserDiscFormat: URIRef = rdflib.term.URIRef('https://schema.org/LaserDiscFormat')
LearningResource: URIRef =
rdflib.term.URIRef('https://schema.org/LearningResource')
LeaveAction: URIRef = rdflib.term.URIRef('https://schema.org/LeaveAction')
LeftHandDriving: URIRef = rdflib.term.URIRef('https://schema.org/LeftHandDriving')
LegalForceStatus: URIRef =
rdflib.term.URIRef('https://schema.org/LegalForceStatus')
```

```
LegalService: URIRef = rdflib.term.URIRef('https://schema.org/LegalService')
LegalValueLevel: URIRef = rdflib.term.URIRef('https://schema.org/LegalValueLevel')
Legislation: URIRef = rdflib.term.URIRef('https://schema.org/Legislation')
LegislationObject: URIRef =
rdflib.term.URIRef('https://schema.org/LegislationObject')
LegislativeBuilding: URIRef =
rdflib.term.URIRef('https://schema.org/LegislativeBuilding')
LeisureTimeActivity: URIRef =
rdflib.term.URIRef('https://schema.org/LeisureTimeActivity')
LendAction: URIRef = rdflib.term.URIRef('https://schema.org/LendAction')
Library: URIRef = rdflib.term.URIRef('https://schema.org/Library')
LibrarySystem: URIRef = rdflib.term.URIRef('https://schema.org/LibrarySystem')
LifestyleModification: URIRef =
rdflib.term.URIRef('https://schema.org/LifestyleModification')
Ligament: URIRef = rdflib.term.URIRef('https://schema.org/Ligament')
LikeAction: URIRef = rdflib.term.URIRef('https://schema.org/LikeAction')
LimitedAvailability: URIRef =
rdflib.term.URIRef('https://schema.org/LimitedAvailability')
LimitedByGuaranteeCharity: URIRef =
rdflib.term.URIRef('https://schema.org/LimitedByGuaranteeCharity')
LinkRole: URIRef = rdflib.term.URIRef('https://schema.org/LinkRole')
LiquorStore: URIRef = rdflib.term.URIRef('https://schema.org/LiquorStore')
ListItem: URIRef = rdflib.term.URIRef('https://schema.org/ListItem')
ListPrice: URIRef = rdflib.term.URIRef('https://schema.org/ListPrice')
ListenAction: URIRef = rdflib.term.URIRef('https://schema.org/ListenAction')
LiteraryEvent: URIRef = rdflib.term.URIRef('https://schema.org/LiteraryEvent')
LiveAlbum: URIRef = rdflib.term.URIRef('https://schema.org/LiveAlbum')
LiveBlogPosting: URIRef = rdflib.term.URIRef('https://schema.org/LiveBlogPosting')
LivingWithHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/LivingWithHealthAspect')
LoanOrCredit: URIRef = rdflib.term.URIRef('https://schema.org/LoanOrCredit')
LocalBusiness: URIRef = rdflib.term.URIRef('https://schema.org/LocalBusiness')
LocationFeatureSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/LocationFeatureSpecification')
```



```

LockerDelivery: URIRef = rdflib.term.URIRef('https://schema.org/LockerDelivery')
Locksmith: URIRef = rdflib.term.URIRef('https://schema.org/Locksmith')
LodgingBusiness: URIRef = rdflib.term.URIRef('https://schema.org/LodgingBusiness')
LodgingReservation: URIRef =
rdflib.term.URIRef('https://schema.org/LodgingReservation')
Longitudinal: URIRef = rdflib.term.URIRef('https://schema.org/Longitudinal')
LoseAction: URIRef = rdflib.term.URIRef('https://schema.org/LoseAction')
LowCalorieDiet: URIRef = rdflib.term.URIRef('https://schema.org/LowCalorieDiet')
LowFatDiet: URIRef = rdflib.term.URIRef('https://schema.org/LowFatDiet')
LowLactoseDiet: URIRef = rdflib.term.URIRef('https://schema.org/LowLactoseDiet')
LowSaltDiet: URIRef = rdflib.term.URIRef('https://schema.org/LowSaltDiet')
Lung: URIRef = rdflib.term.URIRef('https://schema.org/Lung')
LymphaticVessel: URIRef = rdflib.term.URIRef('https://schema.org/LymphaticVessel')
MRI: URIRef = rdflib.term.URIRef('https://schema.org/MRI')
MSRP: URIRef = rdflib.term.URIRef('https://schema.org/MSRP')
Male: URIRef = rdflib.term.URIRef('https://schema.org/Male')
Manuscript: URIRef = rdflib.term.URIRef('https://schema.org/Manuscript')
Map: URIRef = rdflib.term.URIRef('https://schema.org/Map')
MapCategoryType: URIRef = rdflib.term.URIRef('https://schema.org/MapCategoryType')
MarryAction: URIRef = rdflib.term.URIRef('https://schema.org/MarryAction')
Mass: URIRef = rdflib.term.URIRef('https://schema.org/Mass')
MathSolver: URIRef = rdflib.term.URIRef('https://schema.org/MathSolver')
MaximumDoseSchedule: URIRef =
rdflib.term.URIRef('https://schema.org/MaximumDoseSchedule')
MayTreatHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/MayTreatHealthAspect')
MeasurementTypeEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/MeasurementTypeEnumeration')
MediaGallery: URIRef = rdflib.term.URIRef('https://schema.org/MediaGallery')
MediaManipulationRatingEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/MediaManipulationRatingEnumeration')
MediaObject: URIRef = rdflib.term.URIRef('https://schema.org/MediaObject')
MediaReview: URIRef = rdflib.term.URIRef('https://schema.org/MediaReview')

```



```
MediaReviewItem: URIRef = rdflib.term.URIRef('https://schema.org/MediaReviewItem')

MediaSubscription: URIRef =
rdflib.term.URIRef('https://schema.org/MediaSubscription')

MedicalAudience: URIRef = rdflib.term.URIRef('https://schema.org/MedicalAudience')

MedicalAudienceType: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalAudienceType')

MedicalBusiness: URIRef = rdflib.term.URIRef('https://schema.org/MedicalBusiness')

MedicalCause: URIRef = rdflib.term.URIRef('https://schema.org/MedicalCause')

MedicalClinic: URIRef = rdflib.term.URIRef('https://schema.org/MedicalClinic')

MedicalCode: URIRef = rdflib.term.URIRef('https://schema.org/MedicalCode')

MedicalCondition: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalCondition')

MedicalConditionStage: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalConditionStage')

MedicalContraindication: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalContraindication')

MedicalDevice: URIRef = rdflib.term.URIRef('https://schema.org/MedicalDevice')

MedicalDevicePurpose: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalDevicePurpose')

MedicalEntity: URIRef = rdflib.term.URIRef('https://schema.org/MedicalEntity')

MedicalEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalEnumeration')

MedicalEvidenceLevel: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalEvidenceLevel')

MedicalGuideline: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalGuideline')

MedicalGuidelineContraindication: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalGuidelineContraindication')

MedicalGuidelineRecommendation: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalGuidelineRecommendation')

MedicalImagingTechnique: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalImagingTechnique')

MedicalIndication: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalIndication')

MedicalIntangible: URIRef =
rdflib.term.URIRef('https://schema.org/MedicalIntangible')
```

```
MedicalObservationalStudy: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalObservationalStudy')  
  
MedicalObservationalStudyDesign: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalObservationalStudyDesign')  
  
MedicalOrganization: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalOrganization')  
  
MedicalProcedure: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalProcedure')  
  
MedicalProcedureType: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalProcedureType')  
  
MedicalResearcher: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalResearcher')  
  
MedicalRiskCalculator: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalRiskCalculator')  
  
MedicalRiskEstimator: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalRiskEstimator')  
  
MedicalRiskFactor: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalRiskFactor')  
  
MedicalRiskScore: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalRiskScore')  
  
MedicalScholarlyArticle: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalScholarlyArticle')  
  
MedicalSign: URIRef = rdflib.term.URIRef('https://schema.org/MedicalSign')  
  
MedicalSignOrSymptom: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalSignOrSymptom')  
  
MedicalSpecialty: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalSpecialty')  
  
MedicalStudy: URIRef = rdflib.term.URIRef('https://schema.org/MedicalStudy')  
  
MedicalStudyStatus: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalStudyStatus')  
  
MedicalSymptom: URIRef = rdflib.term.URIRef('https://schema.org/MedicalSymptom')  
  
MedicalTest: URIRef = rdflib.term.URIRef('https://schema.org/MedicalTest')  
  
MedicalTestPanel: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalTestPanel')  
  
MedicalTherapy: URIRef = rdflib.term.URIRef('https://schema.org/MedicalTherapy')  
  
MedicalTrial: URIRef = rdflib.term.URIRef('https://schema.org/MedicalTrial')
```

```
MedicalTrialDesign: URIRef =  
rdflib.term.URIRef('https://schema.org/MedicalTrialDesign')  
  
MedicalWebPage: URIRef = rdflib.term.URIRef('https://schema.org/MedicalWebPage')  
  
MedicineSystem: URIRef = rdflib.term.URIRef('https://schema.org/MedicineSystem')  
  
MeetingRoom: URIRef = rdflib.term.URIRef('https://schema.org/MeetingRoom')  
  
MensClothingStore: URIRef =  
rdflib.term.URIRef('https://schema.org/MensClothingStore')  
  
Menu: URIRef = rdflib.term.URIRef('https://schema.org/Menu')  
  
MenuItem: URIRef = rdflib.term.URIRef('https://schema.org/MenuItem')  
  
MenuSection: URIRef = rdflib.term.URIRef('https://schema.org/MenuSection')  
  
MerchantReturnEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/MerchantReturnEnumeration')  
  
MerchantReturnFiniteReturnWindow: URIRef =  
rdflib.term.URIRef('https://schema.org/MerchantReturnFiniteReturnWindow')  
  
MerchantReturnNotPermitted: URIRef =  
rdflib.term.URIRef('https://schema.org/MerchantReturnNotPermitted')  
  
MerchantReturnPolicy: URIRef =  
rdflib.term.URIRef('https://schema.org/MerchantReturnPolicy')  
  
MerchantReturnPolicySeasonalOverride: URIRef =  
rdflib.term.URIRef('https://schema.org/MerchantReturnPolicySeasonalOverride')  
  
MerchantReturnUnlimitedWindow: URIRef =  
rdflib.term.URIRef('https://schema.org/MerchantReturnUnlimitedWindow')  
  
MerchantReturnUnspecified: URIRef =  
rdflib.term.URIRef('https://schema.org/MerchantReturnUnspecified')  
  
Message: URIRef = rdflib.term.URIRef('https://schema.org/Message')  
  
MiddleSchool: URIRef = rdflib.term.URIRef('https://schema.org/MiddleSchool')  
  
Midwifery: URIRef = rdflib.term.URIRef('https://schema.org/Midwifery')  
  
MinimumAdvertisedPrice: URIRef =  
rdflib.term.URIRef('https://schema.org/MinimumAdvertisedPrice')  
  
MisconceptionsHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/MisconceptionsHealthAspect')  
  
MixedEventAttendanceMode: URIRef =  
rdflib.term.URIRef('https://schema.org/MixedEventAttendanceMode')  
  
MixtapeAlbum: URIRef = rdflib.term.URIRef('https://schema.org/MixtapeAlbum')  
  
MobileApplication: URIRef =  
rdflib.term.URIRef('https://schema.org/MobileApplication')
```

```
MobilePhoneStore: URIRef =  
rdflib.term.URIRef('https://schema.org/MobilePhoneStore')  
  
MolecularEntity: URIRef = rdflib.term.URIRef('https://schema.org/MolecularEntity')  
  
Monday: URIRef = rdflib.term.URIRef('https://schema.org/Monday')  
  
MonetaryAmount: URIRef = rdflib.term.URIRef('https://schema.org/MonetaryAmount')  
  
MonetaryAmountDistribution: URIRef =  
rdflib.term.URIRef('https://schema.org/MonetaryAmountDistribution')  
  
MonetaryGrant: URIRef = rdflib.term.URIRef('https://schema.org/MonetaryGrant')  
  
MoneyTransfer: URIRef = rdflib.term.URIRef('https://schema.org/MoneyTransfer')  
  
MortgageLoan: URIRef = rdflib.term.URIRef('https://schema.org/MortgageLoan')  
  
Mosque: URIRef = rdflib.term.URIRef('https://schema.org/Mosque')  
  
Motel: URIRef = rdflib.term.URIRef('https://schema.org/Motel')  
  
Motorcycle: URIRef = rdflib.term.URIRef('https://schema.org/Motorcycle')  
  
MotorcycleDealer: URIRef =  
rdflib.term.URIRef('https://schema.org/MotorcycleDealer')  
  
MotorcycleRepair: URIRef =  
rdflib.term.URIRef('https://schema.org/MotorcycleRepair')  
  
MotorizedBicycle: URIRef =  
rdflib.term.URIRef('https://schema.org/MotorizedBicycle')  
  
Mountain: URIRef = rdflib.term.URIRef('https://schema.org/Mountain')  
  
MoveAction: URIRef = rdflib.term.URIRef('https://schema.org/MoveAction')  
  
Movie: URIRef = rdflib.term.URIRef('https://schema.org/Movie')  
  
MovieClip: URIRef = rdflib.term.URIRef('https://schema.org/MovieClip')  
  
MovieRentalStore: URIRef =  
rdflib.term.URIRef('https://schema.org/MovieRentalStore')  
  
MovieSeries: URIRef = rdflib.term.URIRef('https://schema.org/MovieSeries')  
  
MovieTheater: URIRef = rdflib.term.URIRef('https://schema.org/MovieTheater')  
  
MovingCompany: URIRef = rdflib.term.URIRef('https://schema.org/MovingCompany')  
  
MultiCenterTrial: URIRef =  
rdflib.term.URIRef('https://schema.org/MultiCenterTrial')  
  
MultiPlayer: URIRef = rdflib.term.URIRef('https://schema.org/MultiPlayer')  
  
MulticellularParasite: URIRef =  
rdflib.term.URIRef('https://schema.org/MulticellularParasite')  
  
Muscle: URIRef = rdflib.term.URIRef('https://schema.org/Muscle')
```

```
Musculoskeletal: URIRef = rdflib.term.URIRef('https://schema.org/Musculoskeletal')

MusculoskeletalExam: URIRef =
rdflib.term.URIRef('https://schema.org/MusculoskeletalExam')

Museum: URIRef = rdflib.term.URIRef('https://schema.org/Museum')

MusicAlbum: URIRef = rdflib.term.URIRef('https://schema.org/MusicAlbum')

MusicAlbumProductionType: URIRef =
rdflib.term.URIRef('https://schema.org/MusicAlbumProductionType')

MusicAlbumReleaseType: URIRef =
rdflib.term.URIRef('https://schema.org/MusicAlbumReleaseType')

MusicComposition: URIRef =
rdflib.term.URIRef('https://schema.org/MusicComposition')

MusicEvent: URIRef = rdflib.term.URIRef('https://schema.org/MusicEvent')

MusicGroup: URIRef = rdflib.term.URIRef('https://schema.org/MusicGroup')

MusicPlaylist: URIRef = rdflib.term.URIRef('https://schema.org/MusicPlaylist')

MusicRecording: URIRef = rdflib.term.URIRef('https://schema.org/MusicRecording')

MusicRelease: URIRef = rdflib.term.URIRef('https://schema.org/MusicRelease')

MusicReleaseFormatType: URIRef =
rdflib.term.URIRef('https://schema.org/MusicReleaseFormatType')

MusicStore: URIRef = rdflib.term.URIRef('https://schema.org/MusicStore')

MusicVenue: URIRef = rdflib.term.URIRef('https://schema.org/MusicVenue')

MusicVideoObject: URIRef =
rdflib.term.URIRef('https://schema.org/MusicVideoObject')

NGO: URIRef = rdflib.term.URIRef('https://schema.org/NGO')

NLNonprofitType: URIRef = rdflib.term.URIRef('https://schema.org/NLNonprofitType')

NailSalon: URIRef = rdflib.term.URIRef('https://schema.org/NailSalon')

Neck: URIRef = rdflib.term.URIRef('https://schema.org/Neck')

Nerve: URIRef = rdflib.term.URIRef('https://schema.org/Nerve')

Neuro: URIRef = rdflib.term.URIRef('https://schema.org/Neuro')

Neurologic: URIRef = rdflib.term.URIRef('https://schema.org/Neurologic')

NewCondition: URIRef = rdflib.term.URIRef('https://schema.org/NewCondition')

NewsArticle: URIRef = rdflib.term.URIRef('https://schema.org/NewsArticle')

NewsMediaOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/NewsMediaOrganization')
```

```
Newspaper: URIRef = rdflib.term.URIRef('https://schema.org/Newspaper')
NightClub: URIRef = rdflib.term.URIRef('https://schema.org/NightClub')
NoninvasiveProcedure: URIRef =
rdflib.term.URIRef('https://schema.org/NoninvasiveProcedure')
Nonprofit501a: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501a')
Nonprofit501c1: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c1')
Nonprofit501c10: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c10')
Nonprofit501c11: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c11')
Nonprofit501c12: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c12')
Nonprofit501c13: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c13')
Nonprofit501c14: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c14')
Nonprofit501c15: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c15')
Nonprofit501c16: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c16')
Nonprofit501c17: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c17')
Nonprofit501c18: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c18')
Nonprofit501c19: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c19')
Nonprofit501c2: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c2')
Nonprofit501c20: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c20')
Nonprofit501c21: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c21')
Nonprofit501c22: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c22')
Nonprofit501c23: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c23')
Nonprofit501c24: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c24')
Nonprofit501c25: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c25')
Nonprofit501c26: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c26')
Nonprofit501c27: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c27')
Nonprofit501c28: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c28')
Nonprofit501c3: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c3')
Nonprofit501c4: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c4')
Nonprofit501c5: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c5')
Nonprofit501c6: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c6')
Nonprofit501c7: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c7')
```

```
Nonprofit501c8: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c8')
Nonprofit501c9: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501c9')
Nonprofit501d: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501d')
Nonprofit501e: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501e')
Nonprofit501f: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501f')
Nonprofit501k: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501k')
Nonprofit501n: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501n')
Nonprofit501q: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit501q')
Nonprofit527: URIRef = rdflib.term.URIRef('https://schema.org/Nonprofit527')
NonprofitANBI: URIRef = rdflib.term.URIRef('https://schema.org/NonprofitANBI')
NonprofitSBBi: URIRef = rdflib.term.URIRef('https://schema.org/NonprofitSBBi')
NonprofitType: URIRef = rdflib.term.URIRef('https://schema.org/NonprofitType')
Nose: URIRef = rdflib.term.URIRef('https://schema.org/Nose')
NotInForce: URIRef = rdflib.term.URIRef('https://schema.org/NotInForce')
NotYetRecruiting: URIRef =
rdflib.term.URIRef('https://schema.org/NotYetRecruiting')
Notary: URIRef = rdflib.term.URIRef('https://schema.org/Notary')
NoteDigitalDocument: URIRef =
rdflib.term.URIRef('https://schema.org/NoteDigitalDocument')
Number: URIRef = rdflib.term.URIRef('https://schema.org/Number')
Nursing: URIRef = rdflib.term.URIRef('https://schema.org/Nursing')
NutritionInformation: URIRef =
rdflib.term.URIRef('https://schema.org/NutritionInformation')
OTC: URIRef = rdflib.term.URIRef('https://schema.org/OTC')
Observation: URIRef = rdflib.term.URIRef('https://schema.org/Observation')
Observational: URIRef = rdflib.term.URIRef('https://schema.org/Observational')
Obstetric: URIRef = rdflib.term.URIRef('https://schema.org/Obstetric')
Occupation: URIRef = rdflib.term.URIRef('https://schema.org/Occupation')
OccupationalActivity: URIRef =
rdflib.term.URIRef('https://schema.org/OccupationalActivity')
OccupationalExperienceRequirements: URIRef =
rdflib.term.URIRef('https://schema.org/OccupationalExperienceRequirements')
```



```
OccupationalTherapy: URIRef =  
rdflib.term.URIRef('https://schema.org/OccupationalTherapy')  
  
OceanBodyOfWater: URIRef =  
rdflib.term.URIRef('https://schema.org/OceanBodyOfWater')  
  
Offer: URIRef = rdflib.term.URIRef('https://schema.org/Offer')  
  
OfferCatalog: URIRef = rdflib.term.URIRef('https://schema.org/OfferCatalog')  
  
OfferForLease: URIRef = rdflib.term.URIRef('https://schema.org/OfferForLease')  
  
OfferForPurchase: URIRef =  
rdflib.term.URIRef('https://schema.org/OfferForPurchase')  
  
OfferItemCondition: URIRef =  
rdflib.term.URIRef('https://schema.org/OfferItemCondition')  
  
OfferShippingDetails: URIRef =  
rdflib.term.URIRef('https://schema.org/OfferShippingDetails')  
  
OfficeEquipmentStore: URIRef =  
rdflib.term.URIRef('https://schema.org/OfficeEquipmentStore')  
  
OfficialLegalValue: URIRef =  
rdflib.term.URIRef('https://schema.org/OfficialLegalValue')  
  
OfflineEventAttendanceMode: URIRef =  
rdflib.term.URIRef('https://schema.org/OfflineEventAttendanceMode')  
  
OfflinePermanently: URIRef =  
rdflib.term.URIRef('https://schema.org/OfflinePermanently')  
  
OfflineTemporarily: URIRef =  
rdflib.term.URIRef('https://schema.org/OfflineTemporarily')  
  
OnDemandEvent: URIRef = rdflib.term.URIRef('https://schema.org/OnDemandEvent')  
  
OnSitePickup: URIRef = rdflib.term.URIRef('https://schema.org/OnSitePickup')  
  
Oncologic: URIRef = rdflib.term.URIRef('https://schema.org/Oncologic')  
  
OneTimePayments: URIRef = rdflib.term.URIRef('https://schema.org/OneTimePayments')  
  
Online: URIRef = rdflib.term.URIRef('https://schema.org/Online')  
  
OnlineEventAttendanceMode: URIRef =  
rdflib.term.URIRef('https://schema.org/OnlineEventAttendanceMode')  
  
OnlineFull: URIRef = rdflib.term.URIRef('https://schema.org/OnlineFull')  
  
OnlineOnly: URIRef = rdflib.term.URIRef('https://schema.org/OnlineOnly')  
  
OpenTrial: URIRef = rdflib.term.URIRef('https://schema.org/OpenTrial')  
  
OpeningHoursSpecification: URIRef =  
rdflib.term.URIRef('https://schema.org/OpeningHoursSpecification')
```



```
OpinionNewsArticle: URIRef =  
rdflib.term.URIRef('https://schema.org/OpinionNewsArticle')  
  
Optician: URIRef = rdflib.term.URIRef('https://schema.org/Optician')  
  
Optometric: URIRef = rdflib.term.URIRef('https://schema.org/Optometric')  
  
Order: URIRef = rdflib.term.URIRef('https://schema.org/Order')  
  
OrderAction: URIRef = rdflib.term.URIRef('https://schema.org/OrderAction')  
  
OrderCancelled: URIRef = rdflib.term.URIRef('https://schema.org/OrderCancelled')  
  
OrderDelivered: URIRef = rdflib.term.URIRef('https://schema.org/OrderDelivered')  
  
OrderInTransit: URIRef = rdflib.term.URIRef('https://schema.org/OrderInTransit')  
  
OrderItem: URIRef = rdflib.term.URIRef('https://schema.org/OrderItem')  
  
OrderPaymentDue: URIRef = rdflib.term.URIRef('https://schema.org/OrderPaymentDue')  
  
OrderPickupAvailable: URIRef =  
rdflib.term.URIRef('https://schema.org/OrderPickupAvailable')  
  
OrderProblem: URIRef = rdflib.term.URIRef('https://schema.org/OrderProblem')  
  
OrderProcessing: URIRef = rdflib.term.URIRef('https://schema.org/OrderProcessing')  
  
OrderReturned: URIRef = rdflib.term.URIRef('https://schema.org/OrderReturned')  
  
OrderStatus: URIRef = rdflib.term.URIRef('https://schema.org/OrderStatus')  
  
Organization: URIRef = rdflib.term.URIRef('https://schema.org/Organization')  
  
OrganizationRole: URIRef =  
rdflib.term.URIRef('https://schema.org/OrganizationRole')  
  
OrganizeAction: URIRef = rdflib.term.URIRef('https://schema.org/OrganizeAction')  
  
OriginalMediaContent: URIRef =  
rdflib.term.URIRef('https://schema.org/OriginalMediaContent')  
  
OriginalShippingFees: URIRef =  
rdflib.term.URIRef('https://schema.org/OriginalShippingFees')  
  
Osteopathic: URIRef = rdflib.term.URIRef('https://schema.org/Osteopathic')  
  
Otolaryngologic: URIRef = rdflib.term.URIRef('https://schema.org/Otolaryngologic')  
  
OutOfStock: URIRef = rdflib.term.URIRef('https://schema.org/OutOfStock')  
  
OutletStore: URIRef = rdflib.term.URIRef('https://schema.org/OutletStore')  
  
OverviewHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/OverviewHealthAspect')  
  
OwnershipInfo: URIRef = rdflib.term.URIRef('https://schema.org/OwnershipInfo')  
  
PET: URIRef = rdflib.term.URIRef('https://schema.org/PET')
```

```
PaidLeave: URIRef = rdflib.term.URIRef('https://schema.org/PaidLeave')
PaintAction: URIRef = rdflib.term.URIRef('https://schema.org/PaintAction')
Painting: URIRef = rdflib.term.URIRef('https://schema.org/Painting')
PalliativeProcedure: URIRef =
rdflib.term.URIRef('https://schema.org/PalliativeProcedure')
Paperback: URIRef = rdflib.term.URIRef('https://schema.org/Paperback')
ParcelDelivery: URIRef = rdflib.term.URIRef('https://schema.org/ParcelDelivery')
ParcelService: URIRef = rdflib.term.URIRef('https://schema.org/ParcelService')
ParentAudience: URIRef = rdflib.term.URIRef('https://schema.org/ParentAudience')
ParentalSupport: URIRef = rdflib.term.URIRef('https://schema.org/ParentalSupport')
Park: URIRef = rdflib.term.URIRef('https://schema.org/Park')
ParkingFacility: URIRef = rdflib.term.URIRef('https://schema.org/ParkingFacility')
ParkingMap: URIRef = rdflib.term.URIRef('https://schema.org/ParkingMap')
PartiallyInForce: URIRef =
rdflib.term.URIRef('https://schema.org/PartiallyInForce')
Pathology: URIRef = rdflib.term.URIRef('https://schema.org/Pathology')
PathologyTest: URIRef = rdflib.term.URIRef('https://schema.org/PathologyTest')
Patient: URIRef = rdflib.term.URIRef('https://schema.org/Patient')
PatientExperienceHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/PatientExperienceHealthAspect')
PawnShop: URIRef = rdflib.term.URIRef('https://schema.org/PawnShop')
PayAction: URIRef = rdflib.term.URIRef('https://schema.org/PayAction')
PaymentAutomaticallyApplied: URIRef =
rdflib.term.URIRef('https://schema.org/PaymentAutomaticallyApplied')
PaymentCard: URIRef = rdflib.term.URIRef('https://schema.org/PaymentCard')
PaymentChargeSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/PaymentChargeSpecification')
PaymentComplete: URIRef = rdflib.term.URIRef('https://schema.org/PaymentComplete')
PaymentDeclined: URIRef = rdflib.term.URIRef('https://schema.org/PaymentDeclined')
PaymentDue: URIRef = rdflib.term.URIRef('https://schema.org/PaymentDue')
PaymentMethod: URIRef = rdflib.term.URIRef('https://schema.org/PaymentMethod')
PaymentPastDue: URIRef = rdflib.term.URIRef('https://schema.org/PaymentPastDue')
PaymentService: URIRef = rdflib.term.URIRef('https://schema.org/PaymentService')
```

```
PaymentStatusType: URIRef =  
rdflib.term.URIRef('https://schema.org/PaymentStatusType')  
  
Pediatric: URIRef = rdflib.term.URIRef('https://schema.org/Pediatric')  
  
PeopleAudience: URIRef = rdflib.term.URIRef('https://schema.org/PeopleAudience')  
  
PercutaneousProcedure: URIRef =  
rdflib.term.URIRef('https://schema.org/PercutaneousProcedure')  
  
PerformAction: URIRef = rdflib.term.URIRef('https://schema.org/PerformAction')  
  
PerformanceRole: URIRef = rdflib.term.URIRef('https://schema.org/PerformanceRole')  
  
PerformingArtsTheater: URIRef =  
rdflib.term.URIRef('https://schema.org/PerformingArtsTheater')  
  
PerformingGroup: URIRef = rdflib.term.URIRef('https://schema.org/PerformingGroup')  
  
Periodical: URIRef = rdflib.term.URIRef('https://schema.org/Periodical')  
  
Permit: URIRef = rdflib.term.URIRef('https://schema.org/Permit')  
  
Person: URIRef = rdflib.term.URIRef('https://schema.org/Person')  
  
PetStore: URIRef = rdflib.term.URIRef('https://schema.org/PetStore')  
  
Pharmacy: URIRef = rdflib.term.URIRef('https://schema.org/Pharmacy')  
  
PharmacySpecialty: URIRef =  
rdflib.term.URIRef('https://schema.org/PharmacySpecialty')  
  
Photograph: URIRef = rdflib.term.URIRef('https://schema.org/Photograph')  
  
PhotographAction: URIRef =  
rdflib.term.URIRef('https://schema.org/PhotographAction')  
  
PhysicalActivity: URIRef =  
rdflib.term.URIRef('https://schema.org/PhysicalActivity')  
  
PhysicalActivityCategory: URIRef =  
rdflib.term.URIRef('https://schema.org/PhysicalActivityCategory')  
  
PhysicalExam: URIRef = rdflib.term.URIRef('https://schema.org/PhysicalExam')  
  
PhysicalTherapy: URIRef = rdflib.term.URIRef('https://schema.org/PhysicalTherapy')  
  
Physician: URIRef = rdflib.term.URIRef('https://schema.org/Physician')  
  
Physiotherapy: URIRef = rdflib.term.URIRef('https://schema.org/Physiotherapy')  
  
Place: URIRef = rdflib.term.URIRef('https://schema.org/Place')  
  
PlaceOfWorship: URIRef = rdflib.term.URIRef('https://schema.org/PlaceOfWorship')  
  
PlaceboControlledTrial: URIRef =  
rdflib.term.URIRef('https://schema.org/PlaceboControlledTrial')  
  
PlanAction: URIRef = rdflib.term.URIRef('https://schema.org/PlanAction')
```

```

PlasticSurgery: URIRef = rdflib.term.URIRef('https://schema.org/PlasticSurgery')
Play: URIRef = rdflib.term.URIRef('https://schema.org/Play')
PlayAction: URIRef = rdflib.term.URIRef('https://schema.org/PlayAction')
Playground: URIRef = rdflib.term.URIRef('https://schema.org/Playground')
Plumber: URIRef = rdflib.term.URIRef('https://schema.org/Plumber')
PodcastEpisode: URIRef = rdflib.term.URIRef('https://schema.org/PodcastEpisode')
PodcastSeason: URIRef = rdflib.term.URIRef('https://schema.org/PodcastSeason')
PodcastSeries: URIRef = rdflib.term.URIRef('https://schema.org/PodcastSeries')
Podiatric: URIRef = rdflib.term.URIRef('https://schema.org/Podiatric')
PoliceStation: URIRef = rdflib.term.URIRef('https://schema.org/PoliceStation')
Pond: URIRef = rdflib.term.URIRef('https://schema.org/Pond')
PostOffice: URIRef = rdflib.term.URIRef('https://schema.org/PostOffice')
PostalAddress: URIRef = rdflib.term.URIRef('https://schema.org/PostalAddress')
PostalCodeRangeSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/PostalCodeRangeSpecification')
Poster: URIRef = rdflib.term.URIRef('https://schema.org/Poster')
PotentialActionStatus: URIRef =
rdflib.term.URIRef('https://schema.org/PotentialActionStatus')
PreOrder: URIRef = rdflib.term.URIRef('https://schema.org/PreOrder')
PreOrderAction: URIRef = rdflib.term.URIRef('https://schema.org/PreOrderAction')
PreSale: URIRef = rdflib.term.URIRef('https://schema.org/PreSale')
PregnancyHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/PregnancyHealthAspect')
PrependAction: URIRef = rdflib.term.URIRef('https://schema.org/PrependAction')
Preschool: URIRef = rdflib.term.URIRef('https://schema.org/Preschool')
PrescriptionOnly: URIRef =
rdflib.term.URIRef('https://schema.org/PrescriptionOnly')
PresentationDigitalDocument: URIRef =
rdflib.term.URIRef('https://schema.org/PresentationDigitalDocument')
PreventionHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/PreventionHealthAspect')
PreventionIndication: URIRef =
rdflib.term.URIRef('https://schema.org/PreventionIndication')

```

```
PriceComponentTypeEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/PriceComponentTypeEnumeration')  
  
PriceSpecification: URIRef =  
rdflib.term.URIRef('https://schema.org/PriceSpecification')  
  
PriceTypeEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/PriceTypeEnumeration')  
  
PrimaryCare: URIRef = rdflib.term.URIRef('https://schema.org/PrimaryCare')  
  
Prion: URIRef = rdflib.term.URIRef('https://schema.org/Prion')  
  
Product: URIRef = rdflib.term.URIRef('https://schema.org/Product')  
  
ProductCollection: URIRef =  
rdflib.term.URIRef('https://schema.org/ProductCollection')  
  
ProductGroup: URIRef = rdflib.term.URIRef('https://schema.org/ProductGroup')  
  
ProductModel: URIRef = rdflib.term.URIRef('https://schema.org/ProductModel')  
  
ProfessionalService: URIRef =  
rdflib.term.URIRef('https://schema.org/ProfessionalService')  
  
ProfilePage: URIRef = rdflib.term.URIRef('https://schema.org/ProfilePage')  
  
PrognosisHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/PrognosisHealthAspect')  
  
ProgramMembership: URIRef =  
rdflib.term.URIRef('https://schema.org/ProgramMembership')  
  
Project: URIRef = rdflib.term.URIRef('https://schema.org/Project')  
  
PronounceableText: URIRef =  
rdflib.term.URIRef('https://schema.org/PronounceableText')  
  
Property: URIRef = rdflib.term.URIRef('https://schema.org/Property')  
  
PropertyValue: URIRef = rdflib.term.URIRef('https://schema.org/PropertyValue')  
  
PropertyValueSpecification: URIRef =  
rdflib.term.URIRef('https://schema.org/PropertyValueSpecification')  
  
Protein: URIRef = rdflib.term.URIRef('https://schema.org/Protein')  
  
Protozoa: URIRef = rdflib.term.URIRef('https://schema.org/Protozoa')  
  
Psychiatric: URIRef = rdflib.term.URIRef('https://schema.org/Psychiatric')  
  
PsychologicalTreatment: URIRef =  
rdflib.term.URIRef('https://schema.org/PsychologicalTreatment')  
  
PublicHealth: URIRef = rdflib.term.URIRef('https://schema.org/PublicHealth')  
  
PublicHolidays: URIRef = rdflib.term.URIRef('https://schema.org/PublicHolidays')
```

```
PublicSwimmingPool: URIRef =  
rdflib.term.URIRef('https://schema.org/PublicSwimmingPool')  
  
PublicToilet: URIRef = rdflib.term.URIRef('https://schema.org/PublicToilet')  
  
PublicationEvent: URIRef =  
rdflib.term.URIRef('https://schema.org/PublicationEvent')  
  
PublicationIssue: URIRef =  
rdflib.term.URIRef('https://schema.org/PublicationIssue')  
  
PublicationVolume: URIRef =  
rdflib.term.URIRef('https://schema.org/PublicationVolume')  
  
Pulmonary: URIRef = rdflib.term.URIRef('https://schema.org/Pulmonary')  
  
QAPage: URIRef = rdflib.term.URIRef('https://schema.org/QAPage')  
  
QualitativeValue: URIRef =  
rdflib.term.URIRef('https://schema.org/QualitativeValue')  
  
QuantitativeValue: URIRef =  
rdflib.term.URIRef('https://schema.org/QuantitativeValue')  
  
QuantitativeValueDistribution: URIRef =  
rdflib.term.URIRef('https://schema.org/QuantitativeValueDistribution')  
  
Quantity: URIRef = rdflib.term.URIRef('https://schema.org/Quantity')  
  
Question: URIRef = rdflib.term.URIRef('https://schema.org/Question')  
  
Quiz: URIRef = rdflib.term.URIRef('https://schema.org/Quiz')  
  
Quotation: URIRef = rdflib.term.URIRef('https://schema.org/Quotation')  
  
QuoteAction: URIRef = rdflib.term.URIRef('https://schema.org/QuoteAction')  
  
RVPark: URIRef = rdflib.term.URIRef('https://schema.org/RVPark')  
  
RadiationTherapy: URIRef =  
rdflib.term.URIRef('https://schema.org/RadiationTherapy')  
  
RadioBroadcastService: URIRef =  
rdflib.term.URIRef('https://schema.org/RadioBroadcastService')  
  
RadioChannel: URIRef = rdflib.term.URIRef('https://schema.org/RadioChannel')  
  
RadioClip: URIRef = rdflib.term.URIRef('https://schema.org/RadioClip')  
  
RadioEpisode: URIRef = rdflib.term.URIRef('https://schema.org/RadioEpisode')  
  
RadioSeason: URIRef = rdflib.term.URIRef('https://schema.org/RadioSeason')  
  
RadioSeries: URIRef = rdflib.term.URIRef('https://schema.org/RadioSeries')  
  
RadioStation: URIRef = rdflib.term.URIRef('https://schema.org/RadioStation')  
  
Radiography: URIRef = rdflib.term.URIRef('https://schema.org/Radiography')
```

```
RandomizedTrial: URIRef = rdflib.term.URIRef('https://schema.org/RandomizedTrial')
Rating: URIRef = rdflib.term.URIRef('https://schema.org/Rating')
ReactAction: URIRef = rdflib.term.URIRef('https://schema.org/ReactAction')
ReadAction: URIRef = rdflib.term.URIRef('https://schema.org/ReadAction')
ReadPermission: URIRef = rdflib.term.URIRef('https://schema.org/ReadPermission')
RealEstateAgent: URIRef = rdflib.term.URIRef('https://schema.org/RealEstateAgent')
RealEstateListing: URIRef =
rdflib.term.URIRef('https://schema.org/RealEstateListing')
RearWheelDriveConfiguration: URIRef =
rdflib.term.URIRef('https://schema.org/RearWheelDriveConfiguration')
ReceiveAction: URIRef = rdflib.term.URIRef('https://schema.org/ReceiveAction')
Recipe: URIRef = rdflib.term.URIRef('https://schema.org/Recipe')
Recommendation: URIRef = rdflib.term.URIRef('https://schema.org/Recommendation')
RecommendedDoseSchedule: URIRef =
rdflib.term.URIRef('https://schema.org/RecommendedDoseSchedule')
Recruiting: URIRef = rdflib.term.URIRef('https://schema.org/Recruiting')
RecyclingCenter: URIRef = rdflib.term.URIRef('https://schema.org/RecyclingCenter')
RefundTypeEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/RefundTypeEnumeration')
RefurbishedCondition: URIRef =
rdflib.term.URIRef('https://schema.org/RefurbishedCondition')
RegisterAction: URIRef = rdflib.term.URIRef('https://schema.org/RegisterAction')
Registry: URIRef = rdflib.term.URIRef('https://schema.org/Registry')
ReimbursementCap: URIRef =
rdflib.term.URIRef('https://schema.org/ReimbursementCap')
RejectAction: URIRef = rdflib.term.URIRef('https://schema.org/RejectAction')
RelatedTopicsHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/RelatedTopicsHealthAspect')
RemixAlbum: URIRef = rdflib.term.URIRef('https://schema.org/RemixAlbum')
Renal: URIRef = rdflib.term.URIRef('https://schema.org/Renal')
RentAction: URIRef = rdflib.term.URIRef('https://schema.org/RentAction')
RentalCarReservation: URIRef =
rdflib.term.URIRef('https://schema.org/RentalCarReservation')
```



```
RentalVehicleUsage: URIRef =  
rdflib.term.URIRef('https://schema.org/RentalVehicleUsage')  
  
RepaymentSpecification: URIRef =  
rdflib.term.URIRef('https://schema.org/RepaymentSpecification')  
  
ReplaceAction: URIRef = rdflib.term.URIRef('https://schema.org/ReplaceAction')  
  
ReplyAction: URIRef = rdflib.term.URIRef('https://schema.org/ReplyAction')  
  
Report: URIRef = rdflib.term.URIRef('https://schema.org/Report')  
  
ReportageNewsArticle: URIRef =  
rdflib.term.URIRef('https://schema.org/ReportageNewsArticle')  
  
ReportedDoseSchedule: URIRef =  
rdflib.term.URIRef('https://schema.org/ReportedDoseSchedule')  
  
ResearchOrganization: URIRef =  
rdflib.term.URIRef('https://schema.org/ResearchOrganization')  
  
ResearchProject: URIRef = rdflib.term.URIRef('https://schema.org/ResearchProject')  
  
Researcher: URIRef = rdflib.term.URIRef('https://schema.org/Researcher')  
  
Reservation: URIRef = rdflib.term.URIRef('https://schema.org/Reservation')  
  
ReservationCancelled: URIRef =  
rdflib.term.URIRef('https://schema.org/ReservationCancelled')  
  
ReservationConfirmed: URIRef =  
rdflib.term.URIRef('https://schema.org/ReservationConfirmed')  
  
ReservationHold: URIRef = rdflib.term.URIRef('https://schema.org/ReservationHold')  
  
ReservationPackage: URIRef =  
rdflib.term.URIRef('https://schema.org/ReservationPackage')  
  
ReservationPending: URIRef =  
rdflib.term.URIRef('https://schema.org/ReservationPending')  
  
ReservationStatusType: URIRef =  
rdflib.term.URIRef('https://schema.org/ReservationStatusType')  
  
ReserveAction: URIRef = rdflib.term.URIRef('https://schema.org/ReserveAction')  
  
Reservoir: URIRef = rdflib.term.URIRef('https://schema.org/Reservoir')  
  
Residence: URIRef = rdflib.term.URIRef('https://schema.org/Residence')  
  
Resort: URIRef = rdflib.term.URIRef('https://schema.org/Resort')  
  
RespiratoryTherapy: URIRef =  
rdflib.term.URIRef('https://schema.org/RespiratoryTherapy')  
  
Restaurant: URIRef = rdflib.term.URIRef('https://schema.org/Restaurant')  
  
RestockingFees: URIRef = rdflib.term.URIRef('https://schema.org/RestockingFees')
```



```
RestrictedDiet: URIRef = rdflib.term.URIRef('https://schema.org/RestrictedDiet')

ResultsAvailable: URIRef =
rdflib.term.URIRef('https://schema.org/ResultsAvailable')

ResultsNotAvailable: URIRef =
rdflib.term.URIRef('https://schema.org/ResultsNotAvailable')

ResumeAction: URIRef = rdflib.term.URIRef('https://schema.org/ResumeAction')

Retail: URIRef = rdflib.term.URIRef('https://schema.org/Retail')

ReturnAction: URIRef = rdflib.term.URIRef('https://schema.org/ReturnAction')

ReturnAtKiosk: URIRef = rdflib.term.URIRef('https://schema.org/ReturnAtKiosk')

ReturnByMail: URIRef = rdflib.term.URIRef('https://schema.org/ReturnByMail')

ReturnFeesCustomerResponsibility: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnFeesCustomerResponsibility')

ReturnFeesEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnFeesEnumeration')

ReturnInStore: URIRef = rdflib.term.URIRef('https://schema.org/ReturnInStore')

ReturnLabelCustomerResponsibility: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnLabelCustomerResponsibility')

ReturnLabelDownloadAndPrint: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnLabelDownloadAndPrint')

ReturnLabelInBox: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnLabelInBox')

ReturnLabelSourceEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnLabelSourceEnumeration')

ReturnMethodEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnMethodEnumeration')

ReturnShippingFees: URIRef =
rdflib.term.URIRef('https://schema.org/ReturnShippingFees')

Review: URIRef = rdflib.term.URIRef('https://schema.org/Review')

ReviewAction: URIRef = rdflib.term.URIRef('https://schema.org/ReviewAction')

ReviewNewsArticle: URIRef =
rdflib.term.URIRef('https://schema.org/ReviewNewsArticle')

Rheumatologic: URIRef = rdflib.term.URIRef('https://schema.org/Rheumatologic')

RightHandDriving: URIRef =
rdflib.term.URIRef('https://schema.org/RightHandDriving')

RisksOrComplicationsHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/RisksOrComplicationsHealthAspect')
```

```
RiverBodyOfWater: URIRef =  
rdflib.term.URIRef('https://schema.org/RiverBodyOfWater')  
  
Role: URIRef = rdflib.term.URIRef('https://schema.org/Role')  
  
RoofingContractor: URIRef =  
rdflib.term.URIRef('https://schema.org/RoofingContractor')  
  
Room: URIRef = rdflib.term.URIRef('https://schema.org/Room')  
  
RsvpAction: URIRef = rdflib.term.URIRef('https://schema.org/RsvpAction')  
  
RsvpResponseMaybe: URIRef =  
rdflib.term.URIRef('https://schema.org/RsvpResponseMaybe')  
  
RsvpResponseNo: URIRef = rdflib.term.URIRef('https://schema.org/RsvpResponseNo')  
  
RsvpResponseType: URIRef =  
rdflib.term.URIRef('https://schema.org/RsvpResponseType')  
  
RsvpResponseYes: URIRef = rdflib.term.URIRef('https://schema.org/RsvpResponseYes')  
  
SRP: URIRef = rdflib.term.URIRef('https://schema.org/SRP')  
  
SafetyHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/SafetyHealthAspect')  
  
SaleEvent: URIRef = rdflib.term.URIRef('https://schema.org/SaleEvent')  
  
SalePrice: URIRef = rdflib.term.URIRef('https://schema.org/SalePrice')  
  
SatireOrParodyContent: URIRef =  
rdflib.term.URIRef('https://schema.org/SatireOrParodyContent')  
  
SatiricalArticle: URIRef =  
rdflib.term.URIRef('https://schema.org/SatiricalArticle')  
  
Saturday: URIRef = rdflib.term.URIRef('https://schema.org/Saturday')  
  
Schedule: URIRef = rdflib.term.URIRef('https://schema.org/Schedule')  
  
ScheduleAction: URIRef = rdflib.term.URIRef('https://schema.org/ScheduleAction')  
  
ScholarlyArticle: URIRef =  
rdflib.term.URIRef('https://schema.org/ScholarlyArticle')  
  
School: URIRef = rdflib.term.URIRef('https://schema.org/School')  
  
SchoolDistrict: URIRef = rdflib.term.URIRef('https://schema.org/SchoolDistrict')  
  
ScreeningEvent: URIRef = rdflib.term.URIRef('https://schema.org/ScreeningEvent')  
  
ScreeningHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/ScreeningHealthAspect')  
  
Sculpture: URIRef = rdflib.term.URIRef('https://schema.org/Sculpture')  
  
SeaBodyOfWater: URIRef = rdflib.term.URIRef('https://schema.org/SeaBodyOfWater')
```

```

SearchAction: URIRef = rdflib.term.URIRef('https://schema.org/SearchAction')

SearchResultsPage: URIRef =
rdflib.term.URIRef('https://schema.org/SearchResultsPage')

Season: URIRef = rdflib.term.URIRef('https://schema.org/Season')

Seat: URIRef = rdflib.term.URIRef('https://schema.org/Seat')

SeatingMap: URIRef = rdflib.term.URIRef('https://schema.org/SeatingMap')

SeeDoctorHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/SeeDoctorHealthAspect')

SeekToAction: URIRef = rdflib.term.URIRef('https://schema.org/SeekToAction')

SelfCareHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/SelfCareHealthAspect')

SelfStorage: URIRef = rdflib.term.URIRef('https://schema.org/SelfStorage')

SellAction: URIRef = rdflib.term.URIRef('https://schema.org/SellAction')

SendAction: URIRef = rdflib.term.URIRef('https://schema.org/SendAction')

Series: URIRef = rdflib.term.URIRef('https://schema.org/Series')

Service: URIRef = rdflib.term.URIRef('https://schema.org/Service')

ServiceChannel: URIRef = rdflib.term.URIRef('https://schema.org/ServiceChannel')

ShareAction: URIRef = rdflib.term.URIRef('https://schema.org/ShareAction')

SheetMusic: URIRef = rdflib.term.URIRef('https://schema.org/SheetMusic')

ShippingDeliveryTime: URIRef =
rdflib.term.URIRef('https://schema.org/ShippingDeliveryTime')

ShippingRateSettings: URIRef =
rdflib.term.URIRef('https://schema.org/ShippingRateSettings')

ShoeStore: URIRef = rdflib.term.URIRef('https://schema.org/ShoeStore')

ShoppingCenter: URIRef = rdflib.term.URIRef('https://schema.org/ShoppingCenter')

ShortStory: URIRef = rdflib.term.URIRef('https://schema.org/ShortStory')

SideEffectsHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/SideEffectsHealthAspect')

SingleBlindedTrial: URIRef =
rdflib.term.URIRef('https://schema.org/SingleBlindedTrial')

SingleCenterTrial: URIRef =
rdflib.term.URIRef('https://schema.org/SingleCenterTrial')

SingleFamilyResidence: URIRef =
rdflib.term.URIRef('https://schema.org/SingleFamilyResidence')

```

```
SinglePlayer: URIRef = rdflib.term.URIRef('https://schema.org/SinglePlayer')

SingleRelease: URIRef = rdflib.term.URIRef('https://schema.org/SingleRelease')

SiteNavigationElement: URIRef =
rdflib.term.URIRef('https://schema.org/SiteNavigationElement')

SizeGroupEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/SizeGroupEnumeration')

SizeSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/SizeSpecification')

SizeSystemEnumeration: URIRef =
rdflib.term.URIRef('https://schema.org/SizeSystemEnumeration')

SizeSystemImperial: URIRef =
rdflib.term.URIRef('https://schema.org/SizeSystemImperial')

SizeSystemMetric: URIRef =
rdflib.term.URIRef('https://schema.org/SizeSystemMetric')

SkiResort: URIRef = rdflib.term.URIRef('https://schema.org/SkiResort')

Skin: URIRef = rdflib.term.URIRef('https://schema.org/Skin')

SocialEvent: URIRef = rdflib.term.URIRef('https://schema.org/SocialEvent')

SocialMediaPosting: URIRef =
rdflib.term.URIRef('https://schema.org/SocialMediaPosting')

SoftwareApplication: URIRef =
rdflib.term.URIRef('https://schema.org/SoftwareApplication')

SoftwareSourceCode: URIRef =
rdflib.term.URIRef('https://schema.org/SoftwareSourceCode')

SoldOut: URIRef = rdflib.term.URIRef('https://schema.org/SoldOut')

SolveMathAction: URIRef = rdflib.term.URIRef('https://schema.org/SolveMathAction')

SomeProducts: URIRef = rdflib.term.URIRef('https://schema.org/SomeProducts')

SoundtrackAlbum: URIRef = rdflib.term.URIRef('https://schema.org/SoundtrackAlbum')

SpeakableSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/SpeakableSpecification')

SpecialAnnouncement: URIRef =
rdflib.term.URIRef('https://schema.org/SpecialAnnouncement')

Specialty: URIRef = rdflib.term.URIRef('https://schema.org/Specialty')

SpeechPathology: URIRef = rdflib.term.URIRef('https://schema.org/SpeechPathology')

SpokenWordAlbum: URIRef = rdflib.term.URIRef('https://schema.org/SpokenWordAlbum')
```

```
SportingGoodsStore: URIRef =  
rdflib.term.URIRef('https://schema.org/SportingGoodsStore')  
  
SportsActivityLocation: URIRef =  
rdflib.term.URIRef('https://schema.org/SportsActivityLocation')  
  
SportsClub: URIRef = rdflib.term.URIRef('https://schema.org/SportsClub')  
  
SportsEvent: URIRef = rdflib.term.URIRef('https://schema.org/SportsEvent')  
  
SportsOrganization: URIRef =  
rdflib.term.URIRef('https://schema.org/SportsOrganization')  
  
SportsTeam: URIRef = rdflib.term.URIRef('https://schema.org/SportsTeam')  
  
SpreadsheetDigitalDocument: URIRef =  
rdflib.term.URIRef('https://schema.org/SpreadsheetDigitalDocument')  
  
StadiumOrArena: URIRef = rdflib.term.URIRef('https://schema.org/StadiumOrArena')  
  
StagedContent: URIRef = rdflib.term.URIRef('https://schema.org/StagedContent')  
  
StagesHealthAspect: URIRef =  
rdflib.term.URIRef('https://schema.org/StagesHealthAspect')  
  
State: URIRef = rdflib.term.URIRef('https://schema.org/State')  
  
Statement: URIRef = rdflib.term.URIRef('https://schema.org/Statement')  
  
StatisticalPopulation: URIRef =  
rdflib.term.URIRef('https://schema.org/StatisticalPopulation')  
  
StatusEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/StatusEnumeration')  
  
SteeringPositionValue: URIRef =  
rdflib.term.URIRef('https://schema.org/SteeringPositionValue')  
  
Store: URIRef = rdflib.term.URIRef('https://schema.org/Store')  
  
StoreCreditRefund: URIRef =  
rdflib.term.URIRef('https://schema.org/StoreCreditRefund')  
  
StrengthTraining: URIRef =  
rdflib.term.URIRef('https://schema.org/StrengthTraining')  
  
StructuredValue: URIRef = rdflib.term.URIRef('https://schema.org/StructuredValue')  
  
StudioAlbum: URIRef = rdflib.term.URIRef('https://schema.org/StudioAlbum')  
  
SubscribeAction: URIRef = rdflib.term.URIRef('https://schema.org/SubscribeAction')  
  
Subscription: URIRef = rdflib.term.URIRef('https://schema.org/Subscription')  
  
Substance: URIRef = rdflib.term.URIRef('https://schema.org/Substance')  
  
SubwayStation: URIRef = rdflib.term.URIRef('https://schema.org/SubwayStation')  
  
Suite: URIRef = rdflib.term.URIRef('https://schema.org/Suite')
```

```
Sunday: URIRef = rdflib.term.URIRef('https://schema.org/Sunday')

SuperficialAnatomy: URIRef =
rdflib.term.URIRef('https://schema.org/SuperficialAnatomy')

Surgical: URIRef = rdflib.term.URIRef('https://schema.org/Surgical')

SurgicalProcedure: URIRef =
rdflib.term.URIRef('https://schema.org/SurgicalProcedure')

SuspendAction: URIRef = rdflib.term.URIRef('https://schema.org/SuspendAction')

Suspended: URIRef = rdflib.term.URIRef('https://schema.org/Suspended')

SymptomsHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/SymptomsHealthAspect')

Synagogue: URIRef = rdflib.term.URIRef('https://schema.org/Synagogue')

TVClip: URIRef = rdflib.term.URIRef('https://schema.org/TVClip')

TVEpisode: URIRef = rdflib.term.URIRef('https://schema.org/TVEpisode')

TVSeason: URIRef = rdflib.term.URIRef('https://schema.org/TVSeason')

TVSeries: URIRef = rdflib.term.URIRef('https://schema.org/TVSeries')

Table: URIRef = rdflib.term.URIRef('https://schema.org/Table')

TakeAction: URIRef = rdflib.term.URIRef('https://schema.org/TakeAction')

TattooParlor: URIRef = rdflib.term.URIRef('https://schema.org/TattooParlor')

Taxi: URIRef = rdflib.term.URIRef('https://schema.org/Taxi')

TaxiReservation: URIRef = rdflib.term.URIRef('https://schema.org/TaxiReservation')

TaxiService: URIRef = rdflib.term.URIRef('https://schema.org/TaxiService')

TaxiStand: URIRef = rdflib.term.URIRef('https://schema.org/TaxiStand')

TaxiVehicleUsage: URIRef =
rdflib.term.URIRef('https://schema.org/TaxiVehicleUsage')

Taxon: URIRef = rdflib.term.URIRef('https://schema.org/Taxon')

TechArticle: URIRef = rdflib.term.URIRef('https://schema.org/TechArticle')

TelevisionChannel: URIRef =
rdflib.term.URIRef('https://schema.org/TelevisionChannel')

TelevisionStation: URIRef =
rdflib.term.URIRef('https://schema.org/TelevisionStation')

TennisComplex: URIRef = rdflib.term.URIRef('https://schema.org/TennisComplex')

Terminated: URIRef = rdflib.term.URIRef('https://schema.org/Terminated')

Text: URIRef = rdflib.term.URIRef('https://schema.org/Text')
```

```
TextDigitalDocument: URIRef =  
rdflib.term.URIRef('https://schema.org/TextDigitalDocument')  
  
TheaterEvent: URIRef = rdflib.term.URIRef('https://schema.org/TheaterEvent')  
  
TheaterGroup: URIRef = rdflib.term.URIRef('https://schema.org/TheaterGroup')  
  
Therapeutic: URIRef = rdflib.term.URIRef('https://schema.org/Therapeutic')  
  
TherapeuticProcedure: URIRef =  
rdflib.term.URIRef('https://schema.org/TherapeuticProcedure')  
  
Thesis: URIRef = rdflib.term.URIRef('https://schema.org/Thesis')  
  
Thing: URIRef = rdflib.term.URIRef('https://schema.org/Thing')  
  
Throat: URIRef = rdflib.term.URIRef('https://schema.org/Throat')  
  
Thursday: URIRef = rdflib.term.URIRef('https://schema.org/Thursday')  
  
Ticket: URIRef = rdflib.term.URIRef('https://schema.org/Ticket')  
  
TieAction: URIRef = rdflib.term.URIRef('https://schema.org/TieAction')  
  
Time: URIRef = rdflib.term.URIRef('https://schema.org/Time')  
  
TipAction: URIRef = rdflib.term.URIRef('https://schema.org/TipAction')  
  
TireShop: URIRef = rdflib.term.URIRef('https://schema.org/TireShop')  
  
TollFree: URIRef = rdflib.term.URIRef('https://schema.org/TollFree')  
  
TouristAttraction: URIRef =  
rdflib.term.URIRef('https://schema.org/TouristAttraction')  
  
TouristDestination: URIRef =  
rdflib.term.URIRef('https://schema.org/TouristDestination')  
  
TouristInformationCenter: URIRef =  
rdflib.term.URIRef('https://schema.org/TouristInformationCenter')  
  
TouristTrip: URIRef = rdflib.term.URIRef('https://schema.org/TouristTrip')  
  
Toxicologic: URIRef = rdflib.term.URIRef('https://schema.org/Toxicologic')  
  
ToyStore: URIRef = rdflib.term.URIRef('https://schema.org/ToyStore')  
  
TrackAction: URIRef = rdflib.term.URIRef('https://schema.org/TrackAction')  
  
TradeAction: URIRef = rdflib.term.URIRef('https://schema.org/TradeAction')  
  
TraditionalChinese: URIRef =  
rdflib.term.URIRef('https://schema.org/TraditionalChinese')  
  
TrainReservation: URIRef =  
rdflib.term.URIRef('https://schema.org/TrainReservation')  
  
TrainStation: URIRef = rdflib.term.URIRef('https://schema.org/TrainStation')
```



```
TrainTrip: URIRef = rdflib.term.URIRef('https://schema.org/TrainTrip')

TransferAction: URIRef = rdflib.term.URIRef('https://schema.org/TransferAction')

TransformedContent: URIRef =
rdflib.term.URIRef('https://schema.org/TransformedContent')

TransitMap: URIRef = rdflib.term.URIRef('https://schema.org/TransitMap')

TravelAction: URIRef = rdflib.term.URIRef('https://schema.org/TravelAction')

TravelAgency: URIRef = rdflib.term.URIRef('https://schema.org/TravelAgency')

TreatmentIndication: URIRef =
rdflib.term.URIRef('https://schema.org/TreatmentIndication')

TreatmentsHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/TreatmentsHealthAspect')

Trip: URIRef = rdflib.term.URIRef('https://schema.org/Trip')

TripleBlindedTrial: URIRef =
rdflib.term.URIRef('https://schema.org/TripleBlindedTrial')

Tuesday: URIRef = rdflib.term.URIRef('https://schema.org/Tuesday')

TypeAndQuantityNode: URIRef =
rdflib.term.URIRef('https://schema.org/TypeAndQuantityNode')

TypesHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/TypesHealthAspect')

UKNonprofitType: URIRef = rdflib.term.URIRef('https://schema.org/UKNonprofitType')

UKTrust: URIRef = rdflib.term.URIRef('https://schema.org/UKTrust')

URL: URIRef = rdflib.term.URIRef('https://schema.org/URL')

USNonprofitType: URIRef = rdflib.term.URIRef('https://schema.org/USNonprofitType')

Ultrasound: URIRef = rdflib.term.URIRef('https://schema.org/Ultrasound')

UnRegisterAction: URIRef =
rdflib.term.URIRef('https://schema.org/UnRegisterAction')

UnemploymentSupport: URIRef =
rdflib.term.URIRef('https://schema.org/UnemploymentSupport')

UnincorporatedAssociationCharity: URIRef =
rdflib.term.URIRef('https://schema.org/UnincorporatedAssociationCharity')

UnitPriceSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/UnitPriceSpecification')

UnofficialLegalValue: URIRef =
rdflib.term.URIRef('https://schema.org/UnofficialLegalValue')

UpdateAction: URIRef = rdflib.term.URIRef('https://schema.org/UpdateAction')
```



```
Urologic: URIRef = rdflib.term.URIRef('https://schema.org/Urologic')

UsageOrScheduleHealthAspect: URIRef =
rdflib.term.URIRef('https://schema.org/UsageOrScheduleHealthAspect')

UseAction: URIRef = rdflib.term.URIRef('https://schema.org/UseAction')

UsedCondition: URIRef = rdflib.term.URIRef('https://schema.org/UsedCondition')

UserBlocks: URIRef = rdflib.term.URIRef('https://schema.org/UserBlocks')

UserCheckins: URIRef = rdflib.term.URIRef('https://schema.org/UserCheckins')

UserComments: URIRef = rdflib.term.URIRef('https://schema.org/UserComments')

UserDownloads: URIRef = rdflib.term.URIRef('https://schema.org/UserDownloads')

UserInteraction: URIRef = rdflib.term.URIRef('https://schema.org/UserInteraction')

UserLikes: URIRef = rdflib.term.URIRef('https://schema.org/UserLikes')

UserPageVisits: URIRef = rdflib.term.URIRef('https://schema.org/UserPageVisits')

UserPlays: URIRef = rdflib.term.URIRef('https://schema.org/UserPlays')

UserPlusOnes: URIRef = rdflib.term.URIRef('https://schema.org/UserPlusOnes')

UserReview: URIRef = rdflib.term.URIRef('https://schema.org/UserReview')

UserTweets: URIRef = rdflib.term.URIRef('https://schema.org/UserTweets')

VeganDiet: URIRef = rdflib.term.URIRef('https://schema.org/VeganDiet')

VegetarianDiet: URIRef = rdflib.term.URIRef('https://schema.org/VegetarianDiet')

Vehicle: URIRef = rdflib.term.URIRef('https://schema.org/Vehicle')

Vein: URIRef = rdflib.term.URIRef('https://schema.org/Vein')

VenueMap: URIRef = rdflib.term.URIRef('https://schema.org/VenueMap')

Vessel: URIRef = rdflib.term.URIRef('https://schema.org/Vessel')

VeterinaryCare: URIRef = rdflib.term.URIRef('https://schema.org/VeterinaryCare')

VideoGallery: URIRef = rdflib.term.URIRef('https://schema.org/VideoGallery')

VideoGame: URIRef = rdflib.term.URIRef('https://schema.org/VideoGame')

VideoGameClip: URIRef = rdflib.term.URIRef('https://schema.org/VideoGameClip')

VideoGameSeries: URIRef = rdflib.term.URIRef('https://schema.org/VideoGameSeries')

VideoObject: URIRef = rdflib.term.URIRef('https://schema.org/VideoObject')

VideoObjectSnapshot: URIRef =
rdflib.term.URIRef('https://schema.org/VideoObjectSnapshot')

ViewAction: URIRef = rdflib.term.URIRef('https://schema.org/ViewAction')
```

```
VinylFormat: URIRef = rdflib.term.URIRef('https://schema.org/VinylFormat')
VirtualLocation: URIRef = rdflib.term.URIRef('https://schema.org/VirtualLocation')
Virus: URIRef = rdflib.term.URIRef('https://schema.org/Virus')
VisualArtsEvent: URIRef = rdflib.term.URIRef('https://schema.org/VisualArtsEvent')
VisualArtwork: URIRef = rdflib.term.URIRef('https://schema.org/VisualArtwork')
VitalSign: URIRef = rdflib.term.URIRef('https://schema.org/VitalSign')
Volcano: URIRef = rdflib.term.URIRef('https://schema.org/Volcano')
VoteAction: URIRef = rdflib.term.URIRef('https://schema.org/VoteAction')
WPAdBlock: URIRef = rdflib.term.URIRef('https://schema.org/WPAdBlock')
WPFooter: URIRef = rdflib.term.URIRef('https://schema.org/WPFooter')
WPHeader: URIRef = rdflib.term.URIRef('https://schema.org/WPHeader')
WPSideBar: URIRef = rdflib.term.URIRef('https://schema.org/WPSideBar')
WantAction: URIRef = rdflib.term.URIRef('https://schema.org/WantAction')
WarrantyPromise: URIRef = rdflib.term.URIRef('https://schema.org/WarrantyPromise')
WarrantyScope: URIRef = rdflib.term.URIRef('https://schema.org/WarrantyScope')
WatchAction: URIRef = rdflib.term.URIRef('https://schema.org/WatchAction')
Waterfall: URIRef = rdflib.term.URIRef('https://schema.org/Waterfall')
WearAction: URIRef = rdflib.term.URIRef('https://schema.org/WearAction')
WearableMeasurementBack: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementBack')
WearableMeasurementChestOrBust: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementChestOrBust')
WearableMeasurementCollar: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementCollar')
WearableMeasurementCup: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementCup')
WearableMeasurementHeight: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementHeight')
WearableMeasurementHips: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementHips')
WearableMeasurementInseam: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementInseam')
WearableMeasurementLength: URIRef =
rdflib.term.URIRef('https://schema.org/WearableMeasurementLength')
```

```
WearableMeasurementOutsideLeg: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableMeasurementOutsideLeg')  
  
WearableMeasurementSleeve: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableMeasurementSleeve')  
  
WearableMeasurementTypeEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableMeasurementTypeEnumeration')  
  
WearableMeasurementWaist: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableMeasurementWaist')  
  
WearableMeasurementWidth: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableMeasurementWidth')  
  
WearableSizeGroupBig: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupBig')  
  
WearableSizeGroupBoys: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupBoys')  
  
WearableSizeGroupEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupEnumeration')  
  
WearableSizeGroupExtraShort: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupExtraShort')  
  
WearableSizeGroupExtraTall: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupExtraTall')  
  
WearableSizeGroupGirls: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupGirls')  
  
WearableSizeGroupHusky: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupHusky')  
  
WearableSizeGroupInfants: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupInfants')  
  
WearableSizeGroupJuniors: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupJuniors')  
  
WearableSizeGroupMaternity: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupMaternity')  
  
WearableSizeGroupMens: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupMens')  
  
WearableSizeGroupMisses: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupMisses')  
  
WearableSizeGroupPetite: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupPetite')  
  
WearableSizeGroupPlus: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupPlus')
```

```
WearableSizeGroupRegular: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupRegular')  
  
WearableSizeGroupShort: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupShort')  
  
WearableSizeGroupTall: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupTall')  
  
WearableSizeGroupWomens: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeGroupWomens')  
  
WearableSizeSystemAU: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemAU')  
  
WearableSizeSystemBR: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemBR')  
  
WearableSizeSystemCN: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemCN')  
  
WearableSizeSystemContinental: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemContinental')  
  
WearableSizeSystemDE: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemDE')  
  
WearableSizeSystemEN13402: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemEN13402')  
  
WearableSizeSystemEnumeration: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemEnumeration')  
  
WearableSizeSystemEurope: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemEurope')  
  
WearableSizeSystemFR: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemFR')  
  
WearableSizeSystemGS1: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemGS1')  
  
WearableSizeSystemIT: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemIT')  
  
WearableSizeSystemJP: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemJP')  
  
WearableSizeSystemMX: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemMX')  
  
WearableSizeSystemUK: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemUK')  
  
WearableSizeSystemUS: URIRef =  
rdflib.term.URIRef('https://schema.org/WearableSizeSystemUS')
```

```
WebAPI: URIRef = rdflib.term.URIRef('https://schema.org/WebAPI')
WebApplication: URIRef = rdflib.term.URIRef('https://schema.org/WebApplication')
WebContent: URIRef = rdflib.term.URIRef('https://schema.org/WebContent')
WebPage: URIRef = rdflib.term.URIRef('https://schema.org/WebPage')
WebPageElement: URIRef = rdflib.term.URIRef('https://schema.org/WebPageElement')
WebSite: URIRef = rdflib.term.URIRef('https://schema.org/WebSite')
Wednesday: URIRef = rdflib.term.URIRef('https://schema.org/Wednesday')
WesternConventional: URIRef =
rdflib.term.URIRef('https://schema.org/WesternConventional')
Wholesale: URIRef = rdflib.term.URIRef('https://schema.org/Wholesale')
WholesaleStore: URIRef = rdflib.term.URIRef('https://schema.org/WholesaleStore')
WinAction: URIRef = rdflib.term.URIRef('https://schema.org/WinAction')
Winery: URIRef = rdflib.term.URIRef('https://schema.org/Winery')
Withdrawn: URIRef = rdflib.term.URIRef('https://schema.org/Withdrawn')
WorkBasedProgram: URIRef =
rdflib.term.URIRef('https://schema.org/WorkBasedProgram')
WorkersUnion: URIRef = rdflib.term.URIRef('https://schema.org/WorkersUnion')
WriteAction: URIRef = rdflib.term.URIRef('https://schema.org/WriteAction')
WritePermission: URIRef = rdflib.term.URIRef('https://schema.org/WritePermission')
XPathType: URIRef = rdflib.term.URIRef('https://schema.org/XPathType')
XRay: URIRef = rdflib.term.URIRef('https://schema.org/XRay')
ZoneBoardingPolicy: URIRef =
rdflib.term.URIRef('https://schema.org/ZoneBoardingPolicy')
Zoo: URIRef = rdflib.term.URIRef('https://schema.org/Zoo')
about: URIRef = rdflib.term.URIRef('https://schema.org/about')
abridged: URIRef = rdflib.term.URIRef('https://schema.org/abridged')
abstract: URIRef = rdflib.term.URIRef('https://schema.org/abstract')
accelerationTime: URIRef =
rdflib.term.URIRef('https://schema.org/accelerationTime')
acceptedAnswer: URIRef = rdflib.term.URIRef('https://schema.org/acceptedAnswer')
acceptedOffer: URIRef = rdflib.term.URIRef('https://schema.org/acceptedOffer')
acceptedPaymentMethod: URIRef =
rdflib.term.URIRef('https://schema.org/acceptedPaymentMethod')
```

```

acceptsReservations: URIRef =
rdflib.term.URIRef('https://schema.org/acceptsReservations')

accessCode: URIRef = rdflib.term.URIRef('https://schema.org/accessCode')

accessMode: URIRef = rdflib.term.URIRef('https://schema.org/accessMode')

accessModeSufficient: URIRef =
rdflib.term.URIRef('https://schema.org/accessModeSufficient')

accessibilityAPI: URIRef = rdflib.term.URIRef('https://schema.org/accessibilityAPI')

accessibilityControl: URIRef =
rdflib.term.URIRef('https://schema.org/accessibilityControl')

accessibilityFeature: URIRef =
rdflib.term.URIRef('https://schema.org/accessibilityFeature')

accessibilityHazard: URIRef =
rdflib.term.URIRef('https://schema.org/accessibilityHazard')

accessibilitySummary: URIRef =
rdflib.term.URIRef('https://schema.org/accessibilitySummary')

accommodationCategory: URIRef =
rdflib.term.URIRef('https://schema.org/accommodationCategory')

accommodationFloorPlan: URIRef =
rdflib.term.URIRef('https://schema.org/accommodationFloorPlan')

accountId: URIRef = rdflib.term.URIRef('https://schema.org/accountId')

accountMinimumInflow: URIRef =
rdflib.term.URIRef('https://schema.org/accountMinimumInflow')

accountOverdraftLimit: URIRef =
rdflib.term.URIRef('https://schema.org/accountOverdraftLimit')

accountablePerson: URIRef =
rdflib.term.URIRef('https://schema.org/accountablePerson')

acquireLicensePage: URIRef =
rdflib.term.URIRef('https://schema.org/acquireLicensePage')

acquiredFrom: URIRef = rdflib.term.URIRef('https://schema.org/acquiredFrom')

acrissCode: URIRef = rdflib.term.URIRef('https://schema.org/acrissCode')

actionAccessibilityRequirement: URIRef =
rdflib.term.URIRef('https://schema.org/actionAccessibilityRequirement')

actionApplication: URIRef =
rdflib.term.URIRef('https://schema.org/actionApplication')

actionOption: URIRef = rdflib.term.URIRef('https://schema.org/actionOption')

actionPlatform: URIRef = rdflib.term.URIRef('https://schema.org/actionPlatform')

```

```
actionStatus: URIRef = rdflib.term.URIRef('https://schema.org/actionStatus')

actionableFeedbackPolicy: URIRef =
rdflib.term.URIRef('https://schema.org/actionableFeedbackPolicy')

activeIngredient: URIRef =
rdflib.term.URIRef('https://schema.org/activeIngredient')

activityDuration: URIRef =
rdflib.term.URIRef('https://schema.org/activityDuration')

activityFrequency: URIRef =
rdflib.term.URIRef('https://schema.org/activityFrequency')

actor: URIRef = rdflib.term.URIRef('https://schema.org/actor')

actors: URIRef = rdflib.term.URIRef('https://schema.org/actors')

addOn: URIRef = rdflib.term.URIRef('https://schema.org/addOn')

additionalName: URIRef = rdflib.term.URIRef('https://schema.org/additionalName')

additionalNumberOfGuests: URIRef =
rdflib.term.URIRef('https://schema.org/additionalNumberOfGuests')

additionalProperty: URIRef =
rdflib.term.URIRef('https://schema.org/additionalProperty')

additionalType: URIRef = rdflib.term.URIRef('https://schema.org/additionalType')

additionalVariable: URIRef =
rdflib.term.URIRef('https://schema.org/additionalVariable')

address: URIRef = rdflib.term.URIRef('https://schema.org/address')

addressCountry: URIRef = rdflib.term.URIRef('https://schema.org/addressCountry')

addressLocality: URIRef = rdflib.term.URIRef('https://schema.org/addressLocality')

addressRegion: URIRef = rdflib.term.URIRef('https://schema.org/addressRegion')

administrationRoute: URIRef =
rdflib.term.URIRef('https://schema.org/administrationRoute')

advanceBookingRequirement: URIRef =
rdflib.term.URIRef('https://schema.org/advanceBookingRequirement')

adverseOutcome: URIRef = rdflib.term.URIRef('https://schema.org/adverseOutcome')

affectedBy: URIRef = rdflib.term.URIRef('https://schema.org/affectedBy')

affiliation: URIRef = rdflib.term.URIRef('https://schema.org/affiliation')

afterMedia: URIRef = rdflib.term.URIRef('https://schema.org/afterMedia')

agent: URIRef = rdflib.term.URIRef('https://schema.org/agent')

aggregateRating: URIRef = rdflib.term.URIRef('https://schema.org/aggregateRating')
```



```
aircraft: URIRef = rdflib.term.URIRef('https://schema.org/aircraft')
album: URIRef = rdflib.term.URIRef('https://schema.org/album')
albumProductionType: URIRef =
rdflib.term.URIRef('https://schema.org/albumProductionType')
albumRelease: URIRef = rdflib.term.URIRef('https://schema.org/albumRelease')
albumReleaseType: URIRef =
rdflib.term.URIRef('https://schema.org/albumReleaseType')
albums: URIRef = rdflib.term.URIRef('https://schema.org/albums')
alcoholWarning: URIRef = rdflib.term.URIRef('https://schema.org/alcoholWarning')
algorithm: URIRef = rdflib.term.URIRef('https://schema.org/algorithm')
alignmentType: URIRef = rdflib.term.URIRef('https://schema.org/alignmentType')
alternateName: URIRef = rdflib.term.URIRef('https://schema.org/alternateName')
alternativeHeadline: URIRef =
rdflib.term.URIRef('https://schema.org/alternativeHeadline')
alternativeOf: URIRef = rdflib.term.URIRef('https://schema.org/alternativeOf')
alumni: URIRef = rdflib.term.URIRef('https://schema.org/alumni')
alumniOf: URIRef = rdflib.term.URIRef('https://schema.org/alumniOf')
amenityFeature: URIRef = rdflib.term.URIRef('https://schema.org/amenityFeature')
amount: URIRef = rdflib.term.URIRef('https://schema.org/amount')
amountOfThisGood: URIRef =
rdflib.term.URIRef('https://schema.org/amountOfThisGood')
announcementLocation: URIRef =
rdflib.term.URIRef('https://schema.org/announcementLocation')
annualPercentageRate: URIRef =
rdflib.term.URIRef('https://schema.org/annualPercentageRate')
answerCount: URIRef = rdflib.term.URIRef('https://schema.org/answerCount')
answerExplanation: URIRef =
rdflib.term.URIRef('https://schema.org/answerExplanation')
antagonist: URIRef = rdflib.term.URIRef('https://schema.org/antagonist')
appearance: URIRef = rdflib.term.URIRef('https://schema.org/appearance')
applicableLocation: URIRef =
rdflib.term.URIRef('https://schema.org/applicableLocation')
applicantLocationRequirements: URIRef =
rdflib.term.URIRef('https://schema.org/applicantLocationRequirements')
```



```
application: URIRef = rdflib.term.URIRef('https://schema.org/application')

applicationCategory: URIRef =
rdflib.term.URIRef('https://schema.org/applicationCategory')

applicationContact: URIRef =
rdflib.term.URIRef('https://schema.org/applicationContact')

applicationDeadline: URIRef =
rdflib.term.URIRef('https://schema.org/applicationDeadline')

applicationStartDate: URIRef =
rdflib.term.URIRef('https://schema.org/applicationStartDate')

applicationSubCategory: URIRef =
rdflib.term.URIRef('https://schema.org/applicationSubCategory')

applicationSuite: URIRef =
rdflib.term.URIRef('https://schema.org/applicationSuite')

appliesToDeliveryMethod: URIRef =
rdflib.term.URIRef('https://schema.org/appliesToDeliveryMethod')

appliesToPaymentMethod: URIRef =
rdflib.term.URIRef('https://schema.org/appliesToPaymentMethod')

archiveHeld: URIRef = rdflib.term.URIRef('https://schema.org/archiveHeld')

archivedAt: URIRef = rdflib.term.URIRef('https://schema.org/archivedAt')

area: URIRef = rdflib.term.URIRef('https://schema.org/area')

areaServed: URIRef = rdflib.term.URIRef('https://schema.org/areaServed')

arrivalAirport: URIRef = rdflib.term.URIRef('https://schema.org/arrivalAirport')

arrivalBoatTerminal: URIRef =
rdflib.term.URIRef('https://schema.org/arrivalBoatTerminal')

arrivalBusStop: URIRef = rdflib.term.URIRef('https://schema.org/arrivalBusStop')

arrivalGate: URIRef = rdflib.term.URIRef('https://schema.org/arrivalGate')

arrivalPlatform: URIRef = rdflib.term.URIRef('https://schema.org/arrivalPlatform')

arrivalStation: URIRef = rdflib.term.URIRef('https://schema.org/arrivalStation')

arrivalTerminal: URIRef = rdflib.term.URIRef('https://schema.org/arrivalTerminal')

arrivalTime: URIRef = rdflib.term.URIRef('https://schema.org/arrivalTime')

artEdition: URIRef = rdflib.term.URIRef('https://schema.org/artEdition')

artMedium: URIRef = rdflib.term.URIRef('https://schema.org/artMedium')

arterialBranch: URIRef = rdflib.term.URIRef('https://schema.org/arterialBranch')

artform: URIRef = rdflib.term.URIRef('https://schema.org/artform')
```

```
articleBody: URIRef = rdflib.term.URIRef('https://schema.org/articleBody')
articleSection: URIRef = rdflib.term.URIRef('https://schema.org/articleSection')
artist: URIRef = rdflib.term.URIRef('https://schema.org/artist')
artworkSurface: URIRef = rdflib.term.URIRef('https://schema.org/artworkSurface')
aspect: URIRef = rdflib.term.URIRef('https://schema.org/aspect')
assembly: URIRef = rdflib.term.URIRef('https://schema.org/assembly')
assemblyVersion: URIRef = rdflib.term.URIRef('https://schema.org/assemblyVersion')
assesses: URIRef = rdflib.term.URIRef('https://schema.org/assesses')
associatedAnatomy: URIRef =
rdflib.term.URIRef('https://schema.org/associatedAnatomy')
associatedArticle: URIRef =
rdflib.term.URIRef('https://schema.org/associatedArticle')
associatedClaimReview: URIRef =
rdflib.term.URIRef('https://schema.org/associatedClaimReview')
associatedDisease: URIRef =
rdflib.term.URIRef('https://schema.org/associatedDisease')
associatedMedia: URIRef = rdflib.term.URIRef('https://schema.org/associatedMedia')
associatedMediaReview: URIRef =
rdflib.term.URIRef('https://schema.org/associatedMediaReview')
associatedPathophysiology: URIRef =
rdflib.term.URIRef('https://schema.org/associatedPathophysiology')
associatedReview: URIRef =
rdflib.term.URIRef('https://schema.org/associatedReview')
athlete: URIRef = rdflib.term.URIRef('https://schema.org/athlete')
attendee: URIRef = rdflib.term.URIRef('https://schema.org/attendee')
attendees: URIRef = rdflib.term.URIRef('https://schema.org/attendees')
audience: URIRef = rdflib.term.URIRef('https://schema.org/audience')
audienceType: URIRef = rdflib.term.URIRef('https://schema.org/audienceType')
audio: URIRef = rdflib.term.URIRef('https://schema.org/audio')
authenticator: URIRef = rdflib.term.URIRef('https://schema.org/authenticator')
author: URIRef = rdflib.term.URIRef('https://schema.org/author')
availability: URIRef = rdflib.term.URIRef('https://schema.org/availability')
availabilityEnds: URIRef =
rdflib.term.URIRef('https://schema.org/availabilityEnds')
```

```
availabilityStarts: URIRef =  
rdflib.term.URIRef('https://schema.org/availabilityStarts')  
  
availableAtOrFrom: URIRef =  
rdflib.term.URIRef('https://schema.org/availableAtOrFrom')  
  
availableChannel: URIRef =  
rdflib.term.URIRef('https://schema.org/availableChannel')  
  
availableDeliveryMethod: URIRef =  
rdflib.term.URIRef('https://schema.org/availableDeliveryMethod')  
  
availableFrom: URIRef = rdflib.term.URIRef('https://schema.org/availableFrom')  
  
availableIn: URIRef = rdflib.term.URIRef('https://schema.org/availableIn')  
  
availableLanguage: URIRef =  
rdflib.term.URIRef('https://schema.org/availableLanguage')  
  
availableOnDevice: URIRef =  
rdflib.term.URIRef('https://schema.org/availableOnDevice')  
  
availableService: URIRef =  
rdflib.term.URIRef('https://schema.org/availableService')  
  
availableStrength: URIRef =  
rdflib.term.URIRef('https://schema.org/availableStrength')  
  
availableTest: URIRef = rdflib.term.URIRef('https://schema.org/availableTest')  
  
availableThrough: URIRef =  
rdflib.term.URIRef('https://schema.org/availableThrough')  
  
award: URIRef = rdflib.term.URIRef('https://schema.org/award')  
  
awards: URIRef = rdflib.term.URIRef('https://schema.org/awards')  
  
awayTeam: URIRef = rdflib.term.URIRef('https://schema.org/awayTeam')  
  
backstory: URIRef = rdflib.term.URIRef('https://schema.org/backstory')  
  
bankAccountType: URIRef = rdflib.term.URIRef('https://schema.org/bankAccountType')  
  
baseSalary: URIRef = rdflib.term.URIRef('https://schema.org/baseSalary')  
  
bccRecipient: URIRef = rdflib.term.URIRef('https://schema.org/bccRecipient')  
  
bed: URIRef = rdflib.term.URIRef('https://schema.org/bed')  
  
beforeMedia: URIRef = rdflib.term.URIRef('https://schema.org/beforeMedia')  
  
beneficiaryBank: URIRef = rdflib.term.URIRef('https://schema.org/beneficiaryBank')  
  
benefits: URIRef = rdflib.term.URIRef('https://schema.org/benefits')  
  
benefitsSummaryUrl: URIRef =  
rdflib.term.URIRef('https://schema.org/benefitsSummaryUrl')  
  
bestRating: URIRef = rdflib.term.URIRef('https://schema.org/bestRating')
```

```
billingAddress: URIRef = rdflib.term.URIRef('https://schema.org/billingAddress')
billingDuration: URIRef = rdflib.term.URIRef('https://schema.org/billingDuration')
billingIncrement: URIRef =
rdflib.term.URIRef('https://schema.org/billingIncrement')
billingPeriod: URIRef = rdflib.term.URIRef('https://schema.org/billingPeriod')
billingStart: URIRef = rdflib.term.URIRef('https://schema.org/billingStart')
bioChemInteraction: URIRef =
rdflib.term.URIRef('https://schema.org/bioChemInteraction')
bioChemSimilarity: URIRef =
rdflib.term.URIRef('https://schema.org/bioChemSimilarity')
biologicalRole: URIRef = rdflib.term.URIRef('https://schema.org/biologicalRole')
biomechanicalClass: URIRef =
rdflib.term.URIRef('https://schema.org/biomechanicalClass')
birthDate: URIRef = rdflib.term.URIRef('https://schema.org/birthDate')
birthPlace: URIRef = rdflib.term.URIRef('https://schema.org/birthPlace')
bitrate: URIRef = rdflib.term.URIRef('https://schema.org/bitrate')
blogPost: URIRef = rdflib.term.URIRef('https://schema.org/blogPost')
blogPosts: URIRef = rdflib.term.URIRef('https://schema.org/blogPosts')
bloodSupply: URIRef = rdflib.term.URIRef('https://schema.org/bloodSupply')
boardingGroup: URIRef = rdflib.term.URIRef('https://schema.org/boardingGroup')
boardingPolicy: URIRef = rdflib.term.URIRef('https://schema.org/boardingPolicy')
bodyLocation: URIRef = rdflib.term.URIRef('https://schema.org/bodyLocation')
bodyType: URIRef = rdflib.term.URIRef('https://schema.org/bodyType')
bookEdition: URIRef = rdflib.term.URIRef('https://schema.org/bookEdition')
bookFormat: URIRef = rdflib.term.URIRef('https://schema.org/bookFormat')
bookingAgent: URIRef = rdflib.term.URIRef('https://schema.org/bookingAgent')
bookingTime: URIRef = rdflib.term.URIRef('https://schema.org/bookingTime')
borrower: URIRef = rdflib.term.URIRef('https://schema.org/borrower')
box: URIRef = rdflib.term.URIRef('https://schema.org/box')
branch: URIRef = rdflib.term.URIRef('https://schema.org/branch')
branchCode: URIRef = rdflib.term.URIRef('https://schema.org/branchCode')
branchOf: URIRef = rdflib.term.URIRef('https://schema.org/branchOf')
```

```
brand: URIRef = rdflib.term.URIRef('https://schema.org/brand')

breadcrumb: URIRef = rdflib.term.URIRef('https://schema.org/breadcrumb')

breastfeedingWarning: URIRef =
rdflib.term.URIRef('https://schema.org/breastfeedingWarning')

broadcastAffiliateOf: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastAffiliateOf')

broadcastChannelId: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastChannelId')

broadcastDisplayName: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastDisplayName')

broadcastFrequency: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastFrequency')

broadcastFrequencyValue: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastFrequencyValue')

broadcastOfEvent: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastOfEvent')

broadcastServiceTier: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastServiceTier')

broadcastSignalModulation: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastSignalModulation')

broadcastSubChannel: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastSubChannel')

broadcastTimezone: URIRef =
rdflib.term.URIRef('https://schema.org/broadcastTimezone')

broadcaster: URIRef = rdflib.term.URIRef('https://schema.org/broadcaster')

broker: URIRef = rdflib.term.URIRef('https://schema.org/broker')

browserRequirements: URIRef =
rdflib.term.URIRef('https://schema.org/browserRequirements')

busName: URIRef = rdflib.term.URIRef('https://schema.org/busName')

busNumber: URIRef = rdflib.term.URIRef('https://schema.org/busNumber')

businessDays: URIRef = rdflib.term.URIRef('https://schema.org/businessDays')

businessFunction: URIRef =
rdflib.term.URIRef('https://schema.org/businessFunction')

buyer: URIRef = rdflib.term.URIRef('https://schema.org/buyer')

byArtist: URIRef = rdflib.term.URIRef('https://schema.org/byArtist')

byDay: URIRef = rdflib.term.URIRef('https://schema.org/byDay')
```

```
byMonth: URIRef = rdflib.term.URIRef('https://schema.org/byMonth')
byMonthDay: URIRef = rdflib.term.URIRef('https://schema.org/byMonthDay')
byMonthWeek: URIRef = rdflib.term.URIRef('https://schema.org/byMonthWeek')
callSign: URIRef = rdflib.term.URIRef('https://schema.org/callSign')
calories: URIRef = rdflib.term.URIRef('https://schema.org/calories')
candidate: URIRef = rdflib.term.URIRef('https://schema.org/candidate')
caption: URIRef = rdflib.term.URIRef('https://schema.org/caption')
carbohydrateContent: URIRef =
rdflib.term.URIRef('https://schema.org/carbohydrateContent')
cargoVolume: URIRef = rdflib.term.URIRef('https://schema.org/cargoVolume')
carrier: URIRef = rdflib.term.URIRef('https://schema.org/carrier')
carrierRequirements: URIRef =
rdflib.term.URIRef('https://schema.org/carrierRequirements')
cashBack: URIRef = rdflib.term.URIRef('https://schema.org/cashBack')
catalog: URIRef = rdflib.term.URIRef('https://schema.org/catalog')
catalogNumber: URIRef = rdflib.term.URIRef('https://schema.org/catalogNumber')
category: URIRef = rdflib.term.URIRef('https://schema.org/category')
causeOf: URIRef = rdflib.term.URIRef('https://schema.org/causeOf')
ccRecipient: URIRef = rdflib.term.URIRef('https://schema.org/ccRecipient')
character: URIRef = rdflib.term.URIRef('https://schema.org/character')
characterAttribute: URIRef =
rdflib.term.URIRef('https://schema.org/characterAttribute')
characterName: URIRef = rdflib.term.URIRef('https://schema.org/characterName')
cheatCode: URIRef = rdflib.term.URIRef('https://schema.org/cheatCode')
checkinTime: URIRef = rdflib.term.URIRef('https://schema.org/checkinTime')
checkoutTime: URIRef = rdflib.term.URIRef('https://schema.org/checkoutTime')
chemicalComposition: URIRef =
rdflib.term.URIRef('https://schema.org/chemicalComposition')
chemicalRole: URIRef = rdflib.term.URIRef('https://schema.org/chemicalRole')
childMaxAge: URIRef = rdflib.term.URIRef('https://schema.org/childMaxAge')
childMinAge: URIRef = rdflib.term.URIRef('https://schema.org/childMinAge')
childTaxon: URIRef = rdflib.term.URIRef('https://schema.org/childTaxon')
```

```
children: URIRef = rdflib.term.URIRef('https://schema.org/children')

cholesterolContent: URIRef =
rdflib.term.URIRef('https://schema.org/cholesterolContent')

circle: URIRef = rdflib.term.URIRef('https://schema.org/circle')

citation: URIRef = rdflib.term.URIRef('https://schema.org/citation')

claimInterpreter: URIRef =
rdflib.term.URIRef('https://schema.org/claimInterpreter')

claimReviewed: URIRef = rdflib.term.URIRef('https://schema.org/claimReviewed')

clinicalPharmacology: URIRef =
rdflib.term.URIRef('https://schema.org/clinicalPharmacology')

clinicalPharmacology: URIRef =
rdflib.term.URIRef('https://schema.org/clinicalPharmacology')

clipNumber: URIRef = rdflib.term.URIRef('https://schema.org/clipNumber')

closes: URIRef = rdflib.term.URIRef('https://schema.org/closes')

coach: URIRef = rdflib.term.URIRef('https://schema.org/coach')

code: URIRef = rdflib.term.URIRef('https://schema.org/code')

codeRepository: URIRef = rdflib.term.URIRef('https://schema.org/codeRepository')

codeSampleType: URIRef = rdflib.term.URIRef('https://schema.org/codeSampleType')

codeValue: URIRef = rdflib.term.URIRef('https://schema.org/codeValue')

codingSystem: URIRef = rdflib.term.URIRef('https://schema.org/codingSystem')

colleague: URIRef = rdflib.term.URIRef('https://schema.org/colleague')

colleagues: URIRef = rdflib.term.URIRef('https://schema.org/colleagues')

collection: URIRef = rdflib.term.URIRef('https://schema.org/collection')

collectionSize: URIRef = rdflib.term.URIRef('https://schema.org/collectionSize')

color: URIRef = rdflib.term.URIRef('https://schema.org/color')

colorist: URIRef = rdflib.term.URIRef('https://schema.org/colorist')

comment: URIRef = rdflib.term.URIRef('https://schema.org/comment')

commentCount: URIRef = rdflib.term.URIRef('https://schema.org/commentCount')

commentText: URIRef = rdflib.term.URIRef('https://schema.org/commentText')

commentTime: URIRef = rdflib.term.URIRef('https://schema.org/commentTime')

competencyRequired: URIRef =
rdflib.term.URIRef('https://schema.org/competencyRequired')

competitor: URIRef = rdflib.term.URIRef('https://schema.org/competitor')
```



```
composer: URIRef = rdflib.term.URIRef('https://schema.org/composer')

comprisedOf: URIRef = rdflib.term.URIRef('https://schema.org/comprisedOf')

conditionsOfAccess: URIRef =
rdflib.term.URIRef('https://schema.org/conditionsOfAccess')

confirmationNumber: URIRef =
rdflib.term.URIRef('https://schema.org/confirmationNumber')

connectedTo: URIRef = rdflib.term.URIRef('https://schema.org/connectedTo')

constrainingProperty: URIRef =
rdflib.term.URIRef('https://schema.org/constrainingProperty')

contactOption: URIRef = rdflib.term.URIRef('https://schema.org/contactOption')

contactPoint: URIRef = rdflib.term.URIRef('https://schema.org/contactPoint')

contactPoints: URIRef = rdflib.term.URIRef('https://schema.org/contactPoints')

contactType: URIRef = rdflib.term.URIRef('https://schema.org/contactType')

contactlessPayment: URIRef =
rdflib.term.URIRef('https://schema.org/contactlessPayment')

containedIn: URIRef = rdflib.term.URIRef('https://schema.org/containedIn')

containedInPlace: URIRef =
rdflib.term.URIRef('https://schema.org/containedInPlace')

containsPlace: URIRef = rdflib.term.URIRef('https://schema.org/containsPlace')

containsSeason: URIRef = rdflib.term.URIRef('https://schema.org/containsSeason')

contentLocation: URIRef = rdflib.term.URIRef('https://schema.org/contentLocation')

contentRating: URIRef = rdflib.term.URIRef('https://schema.org/contentRating')

contentReferenceTime: URIRef =
rdflib.term.URIRef('https://schema.org/contentReferenceTime')

contentSize: URIRef = rdflib.term.URIRef('https://schema.org/contentSize')

contentType: URIRef = rdflib.term.URIRef('https://schema.org/contentType')

contentUrl: URIRef = rdflib.term.URIRef('https://schema.org/contentUrl')

contraindication: URIRef =
rdflib.term.URIRef('https://schema.org/contraindication')

contributor: URIRef = rdflib.term.URIRef('https://schema.org/contributor')

cookTime: URIRef = rdflib.term.URIRef('https://schema.org/cookTime')

cookingMethod: URIRef = rdflib.term.URIRef('https://schema.org/cookingMethod')

copyrightHolder: URIRef = rdflib.term.URIRef('https://schema.org/copyrightHolder')
```



```

copyrightNotice: URIRef = rdflib.term.URIRef('https://schema.org/copyrightNotice')
copyrightYear: URIRef = rdflib.term.URIRef('https://schema.org/copyrightYear')
correction: URIRef = rdflib.term.URIRef('https://schema.org/correction')
correctionsPolicy: URIRef =
rdflib.term.URIRef('https://schema.org/correctionsPolicy')
costCategory: URIRef = rdflib.term.URIRef('https://schema.org/costCategory')
costCurrency: URIRef = rdflib.term.URIRef('https://schema.org/costCurrency')
costOrigin: URIRef = rdflib.term.URIRef('https://schema.org/costOrigin')
costPerUnit: URIRef = rdflib.term.URIRef('https://schema.org/costPerUnit')
countriesNotSupported: URIRef =
rdflib.term.URIRef('https://schema.org/countriesNotSupported')
countriesSupported: URIRef =
rdflib.term.URIRef('https://schema.org/countriesSupported')
countryOfAssembly: URIRef =
rdflib.term.URIRef('https://schema.org/countryOfAssembly')
countryOfLastProcessing: URIRef =
rdflib.term.URIRef('https://schema.org/countryOfLastProcessing')
countryOfOrigin: URIRef = rdflib.term.URIRef('https://schema.org/countryOfOrigin')
course: URIRef = rdflib.term.URIRef('https://schema.org/course')
courseCode: URIRef = rdflib.term.URIRef('https://schema.org/courseCode')
courseMode: URIRef = rdflib.term.URIRef('https://schema.org/courseMode')
coursePrerequisites: URIRef =
rdflib.term.URIRef('https://schema.org/coursePrerequisites')
courseWorkload: URIRef = rdflib.term.URIRef('https://schema.org/courseWorkload')
coverageEndTime: URIRef = rdflib.term.URIRef('https://schema.org/coverageEndTime')
coverageStartTime: URIRef =
rdflib.term.URIRef('https://schema.org/coverageStartTime')
creativeWorkStatus: URIRef =
rdflib.term.URIRef('https://schema.org/creativeWorkStatus')
creator: URIRef = rdflib.term.URIRef('https://schema.org/creator')
credentialCategory: URIRef =
rdflib.term.URIRef('https://schema.org/credentialCategory')
creditText: URIRef = rdflib.term.URIRef('https://schema.org/creditText')
creditedTo: URIRef = rdflib.term.URIRef('https://schema.org/creditedTo')

```

```
cssSelector: URIRef = rdflib.term.URIRef('https://schema.org/cssSelector')

currenciesAccepted: URIRef =
rdflib.term.URIRef('https://schema.org/currenciesAccepted')

currency: URIRef = rdflib.term.URIRef('https://schema.org/currency')

currentExchangeRate: URIRef =
rdflib.term.URIRef('https://schema.org/currentExchangeRate')

customer: URIRef = rdflib.term.URIRef('https://schema.org/customer')

customerRemorseReturnFees: URIRef =
rdflib.term.URIRef('https://schema.org/customerRemorseReturnFees')

customerRemorseReturnLabelSource: URIRef =
rdflib.term.URIRef('https://schema.org/customerRemorseReturnLabelSource')

customerRemorseReturnShippingFeesAmount: URIRef =
rdflib.term.URIRef('https://schema.org/customerRemorseReturnShippingFeesAmount')

cutoffTime: URIRef = rdflib.term.URIRef('https://schema.org/cutoffTime')

cvdCollectionDate: URIRef =
rdflib.term.URIRef('https://schema.org/cvdCollectionDate')

cvdFacilityCounty: URIRef =
rdflib.term.URIRef('https://schema.org/cvdFacilityCounty')

cvdFacilityId: URIRef = rdflib.term.URIRef('https://schema.org/cvdFacilityId')

cvdNumBeds: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumBeds')

cvdNumBedsOcc: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumBedsOcc')

cvdNumC19Died: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumC19Died')

cvdNumC19HOPats: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumC19HOPats')

cvdNumC19HospPats: URIRef =
rdflib.term.URIRef('https://schema.org/cvdNumC19HospPats')

cvdNumC19MechVentPats: URIRef =
rdflib.term.URIRef('https://schema.org/cvdNumC19MechVentPats')

cvdNumC190FMechVentPats: URIRef =
rdflib.term.URIRef('https://schema.org/cvdNumC190FMechVentPats')

cvdNumC190overflowPats: URIRef =
rdflib.term.URIRef('https://schema.org/cvdNumC190overflowPats')

cvdNumICUBeds: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumICUBeds')

cvdNumICUBedsOcc: URIRef =
rdflib.term.URIRef('https://schema.org/cvdNumICUBedsOcc')

cvdNumTotBeds: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumTotBeds')
```

```

cvdNumVent: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumVent')
cvdNumVentUse: URIRef = rdflib.term.URIRef('https://schema.org/cvdNumVentUse')
dataFeedElement: URIRef = rdflib.term.URIRef('https://schema.org/dataFeedElement')
dataset: URIRef = rdflib.term.URIRef('https://schema.org/dataset')
datasetTimeInterval: URIRef =
rdflib.term.URIRef('https://schema.org/datasetTimeInterval')
dateCreated: URIRef = rdflib.term.URIRef('https://schema.org/dateCreated')
dateDeleted: URIRef = rdflib.term.URIRef('https://schema.org/dateDeleted')
dateIssued: URIRef = rdflib.term.URIRef('https://schema.org/dateIssued')
dateModified: URIRef = rdflib.term.URIRef('https://schema.org/dateModified')
datePosted: URIRef = rdflib.term.URIRef('https://schema.org/datePosted')
datePublished: URIRef = rdflib.term.URIRef('https://schema.org/datePublished')
dateRead: URIRef = rdflib.term.URIRef('https://schema.org/dateRead')
dateReceived: URIRef = rdflib.term.URIRef('https://schema.org/dateReceived')
dateSent: URIRef = rdflib.term.URIRef('https://schema.org/dateSent')
dateVehicleFirstRegistered: URIRef =
rdflib.term.URIRef('https://schema.org/dateVehicleFirstRegistered')
dateline: URIRef = rdflib.term.URIRef('https://schema.org/dateline')
dayOfWeek: URIRef = rdflib.term.URIRef('https://schema.org/dayOfWeek')
deathDate: URIRef = rdflib.term.URIRef('https://schema.org/deathDate')
deathPlace: URIRef = rdflib.term.URIRef('https://schema.org/deathPlace')
defaultValue: URIRef = rdflib.term.URIRef('https://schema.org/defaultValue')
deliveryAddress: URIRef = rdflib.term.URIRef('https://schema.org/deliveryAddress')
deliveryLeadTime: URIRef =
rdflib.term.URIRef('https://schema.org/deliveryLeadTime')
deliveryMethod: URIRef = rdflib.term.URIRef('https://schema.org/deliveryMethod')
deliveryStatus: URIRef = rdflib.term.URIRef('https://schema.org/deliveryStatus')
deliveryTime: URIRef = rdflib.term.URIRef('https://schema.org/deliveryTime')
department: URIRef = rdflib.term.URIRef('https://schema.org/department')
departureAirport: URIRef =
rdflib.term.URIRef('https://schema.org/departureAirport')
departureBoatTerminal: URIRef =
rdflib.term.URIRef('https://schema.org/departureBoatTerminal')

```

```
departureBusStop: URIRef =  
rdflib.term.URIRef('https://schema.org/departureBusStop')  
  
departureGate: URIRef = rdflib.term.URIRef('https://schema.org/departureGate')  
  
departurePlatform: URIRef =  
rdflib.term.URIRef('https://schema.org/departurePlatform')  
  
departureStation: URIRef =  
rdflib.term.URIRef('https://schema.org/departureStation')  
  
departureTerminal: URIRef =  
rdflib.term.URIRef('https://schema.org/departureTerminal')  
  
departureTime: URIRef = rdflib.term.URIRef('https://schema.org/departureTime')  
  
dependencies: URIRef = rdflib.term.URIRef('https://schema.org/dependencies')  
  
depth: URIRef = rdflib.term.URIRef('https://schema.org/depth')  
  
description: URIRef = rdflib.term.URIRef('https://schema.org/description')  
  
device: URIRef = rdflib.term.URIRef('https://schema.org/device')  
  
diagnosis: URIRef = rdflib.term.URIRef('https://schema.org/diagnosis')  
  
diagram: URIRef = rdflib.term.URIRef('https://schema.org/diagram')  
  
diet: URIRef = rdflib.term.URIRef('https://schema.org/diet')  
  
dietFeatures: URIRef = rdflib.term.URIRef('https://schema.org/dietFeatures')  
  
differentialDiagnosis: URIRef =  
rdflib.term.URIRef('https://schema.org/differentialDiagnosis')  
  
directApply: URIRef = rdflib.term.URIRef('https://schema.org/directApply')  
  
director: URIRef = rdflib.term.URIRef('https://schema.org/director')  
  
directors: URIRef = rdflib.term.URIRef('https://schema.org/directors')  
  
disambiguatingDescription: URIRef =  
rdflib.term.URIRef('https://schema.org/disambiguatingDescription')  
  
discount: URIRef = rdflib.term.URIRef('https://schema.org/discount')  
  
discountCode: URIRef = rdflib.term.URIRef('https://schema.org/discountCode')  
  
discountCurrency: URIRef =  
rdflib.term.URIRef('https://schema.org/discountCurrency')  
  
discusses: URIRef = rdflib.term.URIRef('https://schema.org/discusses')  
  
discussionUrl: URIRef = rdflib.term.URIRef('https://schema.org/discussionUrl')  
  
diseasePreventionInfo: URIRef =  
rdflib.term.URIRef('https://schema.org/diseasePreventionInfo')
```

```
diseaseSpreadStatistics: URIRef =  
rdflib.term.URIRef('https://schema.org/diseaseSpreadStatistics')  
  
dissolutionDate: URIRef = rdflib.term.URIRef('https://schema.org/dissolutionDate')  
  
distance: URIRef = rdflib.term.URIRef('https://schema.org/distance')  
  
distinguishingSign: URIRef =  
rdflib.term.URIRef('https://schema.org/distinguishingSign')  
  
distribution: URIRef = rdflib.term.URIRef('https://schema.org/distribution')  
  
diversityPolicy: URIRef = rdflib.term.URIRef('https://schema.org/diversityPolicy')  
  
diversityStaffingReport: URIRef =  
rdflib.term.URIRef('https://schema.org/diversityStaffingReport')  
  
documentation: URIRef = rdflib.term.URIRef('https://schema.org/documentation')  
  
doesNotShip: URIRef = rdflib.term.URIRef('https://schema.org/doesNotShip')  
  
domainIncludes: URIRef = rdflib.term.URIRef('https://schema.org/domainIncludes')  
  
domiciledMortgage: URIRef =  
rdflib.term.URIRef('https://schema.org/domiciledMortgage')  
  
doorTime: URIRef = rdflib.term.URIRef('https://schema.org/doorTime')  
  
dosageForm: URIRef = rdflib.term.URIRef('https://schema.org/dosageForm')  
  
doseSchedule: URIRef = rdflib.term.URIRef('https://schema.org/doseSchedule')  
  
doseUnit: URIRef = rdflib.term.URIRef('https://schema.org/doseUnit')  
  
doseValue: URIRef = rdflib.term.URIRef('https://schema.org/doseValue')  
  
downPayment: URIRef = rdflib.term.URIRef('https://schema.org/downPayment')  
  
downloadUrl: URIRef = rdflib.term.URIRef('https://schema.org/downloadUrl')  
  
downvoteCount: URIRef = rdflib.term.URIRef('https://schema.org/downvoteCount')  
  
drainsTo: URIRef = rdflib.term.URIRef('https://schema.org/drainsTo')  
  
driveWheelConfiguration: URIRef =  
rdflib.term.URIRef('https://schema.org/driveWheelConfiguration')  
  
dropoffLocation: URIRef = rdflib.term.URIRef('https://schema.org/dropoffLocation')  
  
dropoffTime: URIRef = rdflib.term.URIRef('https://schema.org/dropoffTime')  
  
drug: URIRef = rdflib.term.URIRef('https://schema.org/drug')  
  
drugClass: URIRef = rdflib.term.URIRef('https://schema.org/drugClass')  
  
drugUnit: URIRef = rdflib.term.URIRef('https://schema.org/drugUnit')  
  
duns: URIRef = rdflib.term.URIRef('https://schema.org/duns')
```

```
duplicateTherapy: URIRef =  
rdflib.term.URIRef('https://schema.org/duplicateTherapy')  
  
duration: URIRef = rdflib.term.URIRef('https://schema.org/duration')  
  
durationOfWarranty: URIRef =  
rdflib.term.URIRef('https://schema.org/durationOfWarranty')  
  
duringMedia: URIRef = rdflib.term.URIRef('https://schema.org/duringMedia')  
  
earlyPrepaymentPenalty: URIRef =  
rdflib.term.URIRef('https://schema.org/earlyPrepaymentPenalty')  
  
editEIDR: URIRef = rdflib.term.URIRef('https://schema.org/editEIDR')  
  
editor: URIRef = rdflib.term.URIRef('https://schema.org/editor')  
  
eduQuestionType: URIRef = rdflib.term.URIRef('https://schema.org/eduQuestionType')  
  
educationRequirements: URIRef =  
rdflib.term.URIRef('https://schema.org/educationRequirements')  
  
educationalAlignment: URIRef =  
rdflib.term.URIRef('https://schema.org/educationalAlignment')  
  
educationalCredentialAwarded: URIRef =  
rdflib.term.URIRef('https://schema.org/educationalCredentialAwarded')  
  
educationalFramework: URIRef =  
rdflib.term.URIRef('https://schema.org/educationalFramework')  
  
educationalLevel: URIRef =  
rdflib.term.URIRef('https://schema.org/educationalLevel')  
  
educationalProgramMode: URIRef =  
rdflib.term.URIRef('https://schema.org/educationalProgramMode')  
  
educationalRole: URIRef = rdflib.term.URIRef('https://schema.org/educationalRole')  
  
educationalUse: URIRef = rdflib.term.URIRef('https://schema.org/educationalUse')  
  
elevation: URIRef = rdflib.term.URIRef('https://schema.org/elevation')  
  
eligibilityToWorkRequirement: URIRef =  
rdflib.term.URIRef('https://schema.org/eligibilityToWorkRequirement')  
  
eligibleCustomerType: URIRef =  
rdflib.term.URIRef('https://schema.org/eligibleCustomerType')  
  
eligibleDuration: URIRef =  
rdflib.term.URIRef('https://schema.org/eligibleDuration')  
  
eligibleQuantity: URIRef =  
rdflib.term.URIRef('https://schema.org/eligibleQuantity')  
  
eligibleRegion: URIRef = rdflib.term.URIRef('https://schema.org/eligibleRegion')
```

```
eligibleTransactionVolume: URIRef =  
rdflib.term.URIRef('https://schema.org/eligibleTransactionVolume')  
  
email: URIRef = rdflib.term.URIRef('https://schema.org/email')  
  
embedUrl: URIRef = rdflib.term.URIRef('https://schema.org/embedUrl')  
  
embeddedTextCaption: URIRef =  
rdflib.term.URIRef('https://schema.org/embeddedTextCaption')  
  
emissionsCO2: URIRef = rdflib.term.URIRef('https://schema.org/emissionsCO2')  
  
employee: URIRef = rdflib.term.URIRef('https://schema.org/employee')  
  
employees: URIRef = rdflib.term.URIRef('https://schema.org/employees')  
  
employerOverview: URIRef =  
rdflib.term.URIRef('https://schema.org/employerOverview')  
  
employmentType: URIRef = rdflib.term.URIRef('https://schema.org/employmentType')  
  
employmentUnit: URIRef = rdflib.term.URIRef('https://schema.org/employmentUnit')  
  
encodesBioChemEntity: URIRef =  
rdflib.term.URIRef('https://schema.org/encodesBioChemEntity')  
  
encodesCreativeWork: URIRef =  
rdflib.term.URIRef('https://schema.org/encodesCreativeWork')  
  
encoding: URIRef = rdflib.term.URIRef('https://schema.org/encoding')  
  
encodingFormat: URIRef = rdflib.term.URIRef('https://schema.org/encodingFormat')  
  
encodingType: URIRef = rdflib.term.URIRef('https://schema.org/encodingType')  
  
encodings: URIRef = rdflib.term.URIRef('https://schema.org/encodings')  
  
endDate: URIRef = rdflib.term.URIRef('https://schema.org/endDate')  
  
endOffset: URIRef = rdflib.term.URIRef('https://schema.org/endOffset')  
  
endTime: URIRef = rdflib.term.URIRef('https://schema.org/endTime')  
  
endorsee: URIRef = rdflib.term.URIRef('https://schema.org/endorsee')  
  
endorsers: URIRef = rdflib.term.URIRef('https://schema.org/endorsers')  
  
energyEfficiencyScaleMax: URIRef =  
rdflib.term.URIRef('https://schema.org/energyEfficiencyScaleMax')  
  
energyEfficiencyScaleMin: URIRef =  
rdflib.term.URIRef('https://schema.org/energyEfficiencyScaleMin')  
  
engineDisplacement: URIRef =  
rdflib.term.URIRef('https://schema.org/engineDisplacement')  
  
enginePower: URIRef = rdflib.term.URIRef('https://schema.org/enginePower')  
  
engineType: URIRef = rdflib.term.URIRef('https://schema.org/engineType')
```



```
entertainmentBusiness: URIRef =  
rdflib.term.URIRef('https://schema.org/entertainmentBusiness')  
  
epidemiology: URIRef = rdflib.term.URIRef('https://schema.org/epidemiology')  
  
episode: URIRef = rdflib.term.URIRef('https://schema.org/episode')  
  
episodeNumber: URIRef = rdflib.term.URIRef('https://schema.org/episodeNumber')  
  
episodes: URIRef = rdflib.term.URIRef('https://schema.org/episodes')  
  
equal: URIRef = rdflib.term.URIRef('https://schema.org/equal')  
  
error: URIRef = rdflib.term.URIRef('https://schema.org/error')  
  
estimatedCost: URIRef = rdflib.term.URIRef('https://schema.org/estimatedCost')  
  
estimatedFlightDuration: URIRef =  
rdflib.term.URIRef('https://schema.org/estimatedFlightDuration')  
  
estimatedSalary: URIRef = rdflib.term.URIRef('https://schema.org/estimatedSalary')  
  
estimatesRiskOf: URIRef = rdflib.term.URIRef('https://schema.org/estimatesRiskOf')  
  
ethicsPolicy: URIRef = rdflib.term.URIRef('https://schema.org/ethicsPolicy')  
  
event: URIRef = rdflib.term.URIRef('https://schema.org/event')  
  
eventAttendanceMode: URIRef =  
rdflib.term.URIRef('https://schema.org/eventAttendanceMode')  
  
eventSchedule: URIRef = rdflib.term.URIRef('https://schema.org/eventSchedule')  
  
eventStatus: URIRef = rdflib.term.URIRef('https://schema.org/eventStatus')  
  
events: URIRef = rdflib.term.URIRef('https://schema.org/events')  
  
evidenceLevel: URIRef = rdflib.term.URIRef('https://schema.org/evidenceLevel')  
  
evidenceOrigin: URIRef = rdflib.term.URIRef('https://schema.org/evidenceOrigin')  
  
exampleOfWork: URIRef = rdflib.term.URIRef('https://schema.org/exampleOfWork')  
  
exceptDate: URIRef = rdflib.term.URIRef('https://schema.org/exceptDate')  
  
exchangeRateSpread: URIRef =  
rdflib.term.URIRef('https://schema.org/exchangeRateSpread')  
  
executableLibraryName: URIRef =  
rdflib.term.URIRef('https://schema.org/executableLibraryName')  
  
exerciseCourse: URIRef = rdflib.term.URIRef('https://schema.org/exerciseCourse')  
  
exercisePlan: URIRef = rdflib.term.URIRef('https://schema.org/exercisePlan')  
  
exerciseRelatedDiet: URIRef =  
rdflib.term.URIRef('https://schema.org/exerciseRelatedDiet')  
  
exerciseType: URIRef = rdflib.term.URIRef('https://schema.org/exerciseType')
```



```
exifData: URIRef = rdflib.term.URIRef('https://schema.org/exifData')

expectedArrivalFrom: URIRef =
rdflib.term.URIRef('https://schema.org/expectedArrivalFrom')

expectedArrivalUntil: URIRef =
rdflib.term.URIRef('https://schema.org/expectedArrivalUntil')

expectedPrognosis: URIRef =
rdflib.term.URIRef('https://schema.org/expectedPrognosis')

expectsAcceptanceOf: URIRef =
rdflib.term.URIRef('https://schema.org/expectsAcceptanceOf')

experienceInPlaceOfEducation: URIRef =
rdflib.term.URIRef('https://schema.org/experienceInPlaceOfEducation')

experienceRequirements: URIRef =
rdflib.term.URIRef('https://schema.org/experienceRequirements')

expertConsiderations: URIRef =
rdflib.term.URIRef('https://schema.org/expertConsiderations')

expires: URIRef = rdflib.term.URIRef('https://schema.org/expires')

expressedIn: URIRef = rdflib.term.URIRef('https://schema.org/expressedIn')

familyName: URIRef = rdflib.term.URIRef('https://schema.org/familyName')

fatContent: URIRef = rdflib.term.URIRef('https://schema.org/fatContent')

faxNumber: URIRef = rdflib.term.URIRef('https://schema.org/faxNumber')

featureList: URIRef = rdflib.term.URIRef('https://schema.org/featureList')

feesAndCommissionsSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/feesAndCommissionsSpecification')

fiberContent: URIRef = rdflib.term.URIRef('https://schema.org/fiberContent')

fileFormat: URIRef = rdflib.term.URIRef('https://schema.org/fileFormat')

fileSize: URIRef = rdflib.term.URIRef('https://schema.org/fileSize')

financialAidEligible: URIRef =
rdflib.term.URIRef('https://schema.org/financialAidEligible')

firstAppearance: URIRef = rdflib.term.URIRef('https://schema.org/firstAppearance')

firstPerformance: URIRef =
rdflib.term.URIRef('https://schema.org/firstPerformance')

flightDistance: URIRef = rdflib.term.URIRef('https://schema.org/flightDistance')

flightNumber: URIRef = rdflib.term.URIRef('https://schema.org/flightNumber')

floorLevel: URIRef = rdflib.term.URIRef('https://schema.org/floorLevel')

floorLimit: URIRef = rdflib.term.URIRef('https://schema.org/floorLimit')
```

```
floorSize: URIRef = rdflib.term.URIRef('https://schema.org/floorSize')
followee: URIRef = rdflib.term.URIRef('https://schema.org/followee')
follows: URIRef = rdflib.term.URIRef('https://schema.org/follows')
followup: URIRef = rdflib.term.URIRef('https://schema.org/followup')
foodEstablishment: URIRef =
rdflib.term.URIRef('https://schema.org/foodEstablishment')
foodEvent: URIRef = rdflib.term.URIRef('https://schema.org/foodEvent')
foodWarning: URIRef = rdflib.term.URIRef('https://schema.org/foodWarning')
founder: URIRef = rdflib.term.URIRef('https://schema.org/founder')
founders: URIRef = rdflib.term.URIRef('https://schema.org/founders')
foundingDate: URIRef = rdflib.term.URIRef('https://schema.org/foundingDate')
foundingLocation: URIRef =
rdflib.term.URIRef('https://schema.org/foundingLocation')
free: URIRef = rdflib.term.URIRef('https://schema.org/free')
freeShippingThreshold: URIRef =
rdflib.term.URIRef('https://schema.org/freeShippingThreshold')
frequency: URIRef = rdflib.term.URIRef('https://schema.org/frequency')
fromLocation: URIRef = rdflib.term.URIRef('https://schema.org/fromLocation')
fuelCapacity: URIRef = rdflib.term.URIRef('https://schema.org/fuelCapacity')
fuelConsumption: URIRef = rdflib.term.URIRef('https://schema.org/fuelConsumption')
fuelEfficiency: URIRef = rdflib.term.URIRef('https://schema.org/fuelEfficiency')
fuelType: URIRef = rdflib.term.URIRef('https://schema.org/fuelType')
functionalClass: URIRef = rdflib.term.URIRef('https://schema.org/functionalClass')
fundedItem: URIRef = rdflib.term.URIRef('https://schema.org/fundedItem')
funder: URIRef = rdflib.term.URIRef('https://schema.org/funder')
game: URIRef = rdflib.term.URIRef('https://schema.org/game')
gameItem: URIRef = rdflib.term.URIRef('https://schema.org/gameItem')
gameLocation: URIRef = rdflib.term.URIRef('https://schema.org/gameLocation')
gamePlatform: URIRef = rdflib.term.URIRef('https://schema.org/gamePlatform')
gameServer: URIRef = rdflib.term.URIRef('https://schema.org/gameServer')
gameTip: URIRef = rdflib.term.URIRef('https://schema.org/gameTip')
gender: URIRef = rdflib.term.URIRef('https://schema.org/gender')
```

```
genre: URIRef = rdflib.term.URIRef('https://schema.org/genre')
geo: URIRef = rdflib.term.URIRef('https://schema.org/geo')
geoContains: URIRef = rdflib.term.URIRef('https://schema.org/geoContains')
geoCoveredBy: URIRef = rdflib.term.URIRef('https://schema.org/geoCoveredBy')
geoCovers: URIRef = rdflib.term.URIRef('https://schema.org/geoCovers')
geoCrosses: URIRef = rdflib.term.URIRef('https://schema.org/geoCrosses')
geoDisjoint: URIRef = rdflib.term.URIRef('https://schema.org/geoDisjoint')
geoEquals: URIRef = rdflib.term.URIRef('https://schema.org/geoEquals')
geoIntersects: URIRef = rdflib.term.URIRef('https://schema.org/geoIntersects')
geoMidpoint: URIRef = rdflib.term.URIRef('https://schema.org/geoMidpoint')
geoOverlaps: URIRef = rdflib.term.URIRef('https://schema.org/geoOverlaps')
geoRadius: URIRef = rdflib.term.URIRef('https://schema.org/geoRadius')
geoTouches: URIRef = rdflib.term.URIRef('https://schema.org/geoTouches')
geoWithin: URIRef = rdflib.term.URIRef('https://schema.org/geoWithin')
geographicArea: URIRef = rdflib.term.URIRef('https://schema.org/geographicArea')
gettingTestedInfo: URIRef =
rdflib.term.URIRef('https://schema.org/gettingTestedInfo')
givenName: URIRef = rdflib.term.URIRef('https://schema.org/givenName')
globalLocationNumber: URIRef =
rdflib.term.URIRef('https://schema.org/globalLocationNumber')
governmentBenefitsInfo: URIRef =
rdflib.term.URIRef('https://schema.org/governmentBenefitsInfo')
gracePeriod: URIRef = rdflib.term.URIRef('https://schema.org/gracePeriod')
grantee: URIRef = rdflib.term.URIRef('https://schema.org/grantee')
greater: URIRef = rdflib.term.URIRef('https://schema.org/greater')
greaterOrEqual: URIRef = rdflib.term.URIRef('https://schema.org/greaterOrEqual')
gtin: URIRef = rdflib.term.URIRef('https://schema.org/gtin')
gtin12: URIRef = rdflib.term.URIRef('https://schema.org/gtin12')
gtin13: URIRef = rdflib.term.URIRef('https://schema.org/gtin13')
gtin14: URIRef = rdflib.term.URIRef('https://schema.org/gtin14')
gtin8: URIRef = rdflib.term.URIRef('https://schema.org/gtin8')
guideline: URIRef = rdflib.term.URIRef('https://schema.org/guideline')
```

```
guidelineDate: URIRef = rdflib.term.URIRef('https://schema.org/guidelineDate')

guidelineSubject: URIRef =
rdflib.term.URIRef('https://schema.org/guidelineSubject')

handlingTime: URIRef = rdflib.term.URIRef('https://schema.org/handlingTime')

hasBioChemEntityPart: URIRef =
rdflib.term.URIRef('https://schema.org/hasBioChemEntityPart')

hasBioPolymerSequence: URIRef =
rdflib.term.URIRef('https://schema.org/hasBioPolymerSequence')

hasBroadcastChannel: URIRef =
rdflib.term.URIRef('https://schema.org/hasBroadcastChannel')

hasCategoryCode: URIRef = rdflib.term.URIRef('https://schema.org/hasCategoryCode')

hasCourse: URIRef = rdflib.term.URIRef('https://schema.org/hasCourse')

hasCourseInstance: URIRef =
rdflib.term.URIRef('https://schema.org/hasCourseInstance')

hasCredential: URIRef = rdflib.term.URIRef('https://schema.org/hasCredential')

hasDefinedTerm: URIRef = rdflib.term.URIRef('https://schema.org/hasDefinedTerm')

hasDeliveryMethod: URIRef =
rdflib.term.URIRef('https://schema.org/hasDeliveryMethod')

hasDigitalDocumentPermission: URIRef =
rdflib.term.URIRef('https://schema.org/hasDigitalDocumentPermission')

hasDriveThroughService: URIRef =
rdflib.term.URIRef('https://schema.org/hasDriveThroughService')

hasEnergyConsumptionDetails: URIRef =
rdflib.term.URIRef('https://schema.org/hasEnergyConsumptionDetails')

hasEnergyEfficiencyCategory: URIRef =
rdflib.term.URIRef('https://schema.org/hasEnergyEfficiencyCategory')

hasHealthAspect: URIRef = rdflib.term.URIRef('https://schema.org/hasHealthAspect')

hasMap: URIRef = rdflib.term.URIRef('https://schema.org/hasMap')

hasMeasurement: URIRef = rdflib.term.URIRef('https://schema.org/hasMeasurement')

hasMenu: URIRef = rdflib.term.URIRef('https://schema.org/hasMenu')

hasMenuItem: URIRef = rdflib.term.URIRef('https://schema.org/hasMenuItem')

hasMenuSection: URIRef = rdflib.term.URIRef('https://schema.org/hasMenuSection')

hasMerchantReturnPolicy: URIRef =
rdflib.term.URIRef('https://schema.org/hasMerchantReturnPolicy')
```

```

hasMolecularFunction: URIRef =
rdflib.term.URIRef('https://schema.org/hasMolecularFunction')

hasOccupation: URIRef = rdflib.term.URIRef('https://schema.org/hasOccupation')

hasOfferCatalog: URIRef = rdflib.term.URIRef('https://schema.org/hasOfferCatalog')

hasPOS: URIRef = rdflib.term.URIRef('https://schema.org/hasPOS')

hasPart: URIRef = rdflib.term.URIRef('https://schema.org/hasPart')

hasRepresentation: URIRef =
rdflib.term.URIRef('https://schema.org/hasRepresentation')

hasVariant: URIRef = rdflib.term.URIRef('https://schema.org/hasVariant')

headline: URIRef = rdflib.term.URIRef('https://schema.org/headline')

healthCondition: URIRef = rdflib.term.URIRef('https://schema.org/healthCondition')

healthPlanCoinsuranceOption: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanCoinsuranceOption')

healthPlanCoinsuranceRate: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanCoinsuranceRate')

healthPlanCopay: URIRef = rdflib.term.URIRef('https://schema.org/healthPlanCopay')

healthPlanCopayOption: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanCopayOption')

healthPlanCostSharing: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanCostSharing')

healthPlanDrugOption: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanDrugOption')

healthPlanDrugTier: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanDrugTier')

healthPlanId: URIRef = rdflib.term.URIRef('https://schema.org/healthPlanId')

healthPlanMarketingUrl: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanMarketingUrl')

healthPlanNetworkId: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanNetworkId')

healthPlanNetworkTier: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanNetworkTier')

healthPlanPharmacyCategory: URIRef =
rdflib.term.URIRef('https://schema.org/healthPlanPharmacyCategory')

healthcareReportingData: URIRef =
rdflib.term.URIRef('https://schema.org/healthcareReportingData')

height: URIRef = rdflib.term.URIRef('https://schema.org/height')

```

```
highPrice: URIRef = rdflib.term.URIRef('https://schema.org/highPrice')

hiringOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/hiringOrganization')

holdingArchive: URIRef = rdflib.term.URIRef('https://schema.org/holdingArchive')

homeLocation: URIRef = rdflib.term.URIRef('https://schema.org/homeLocation')

homeTeam: URIRef = rdflib.term.URIRef('https://schema.org/homeTeam')

honorificPrefix: URIRef = rdflib.term.URIRef('https://schema.org/honorificPrefix')

honorificSuffix: URIRef = rdflib.term.URIRef('https://schema.org/honorificSuffix')

hospitalAffiliation: URIRef =
rdflib.term.URIRef('https://schema.org/hospitalAffiliation')

hostingOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/hostingOrganization')

hoursAvailable: URIRef = rdflib.term.URIRef('https://schema.org/hoursAvailable')

howPerformed: URIRef = rdflib.term.URIRef('https://schema.org/howPerformed')

httpMethod: URIRef = rdflib.term.URIRef('https://schema.org/httpMethod')

iataCode: URIRef = rdflib.term.URIRef('https://schema.org/iataCode')

icaoCode: URIRef = rdflib.term.URIRef('https://schema.org/icaoCode')

identifier: URIRef = rdflib.term.URIRef('https://schema.org/identifier')

identifyingExam: URIRef = rdflib.term.URIRef('https://schema.org/identifyingExam')

identifyingTest: URIRef = rdflib.term.URIRef('https://schema.org/identifyingTest')

illustrator: URIRef = rdflib.term.URIRef('https://schema.org/illustrator')

image: URIRef = rdflib.term.URIRef('https://schema.org/image')

imagingTechnique: URIRef =
rdflib.term.URIRef('https://schema.org/imagingTechnique')

inAlbum: URIRef = rdflib.term.URIRef('https://schema.org/inAlbum')

inBroadcastLineup: URIRef =
rdflib.term.URIRef('https://schema.org/inBroadcastLineup')

inChI: URIRef = rdflib.term.URIRef('https://schema.org/inChI')

inChIKey: URIRef = rdflib.term.URIRef('https://schema.org/inChIKey')

inCodeSet: URIRef = rdflib.term.URIRef('https://schema.org/inCodeSet')

inDefinedTermSet: URIRef =
rdflib.term.URIRef('https://schema.org/inDefinedTermSet')

inLanguage: URIRef = rdflib.term.URIRef('https://schema.org/inLanguage')
```

```
inPlaylist: URIRef = rdflib.term.URIRef('https://schema.org/inPlaylist')

inProductGroupWithID: URIRef =
rdflib.term.URIRef('https://schema.org/inProductGroupWithID')

inStoreReturnsOffered: URIRef =
rdflib.term.URIRef('https://schema.org/inStoreReturnsOffered')

inSupportOf: URIRef = rdflib.term.URIRef('https://schema.org/inSupportOf')

incentiveCompensation: URIRef =
rdflib.term.URIRef('https://schema.org/incentiveCompensation')

incentives: URIRef = rdflib.term.URIRef('https://schema.org/incentives')

includedComposition: URIRef =
rdflib.term.URIRef('https://schema.org/includedComposition')

includedDataCatalog: URIRef =
rdflib.term.URIRef('https://schema.org/includedDataCatalog')

includedInDataCatalog: URIRef =
rdflib.term.URIRef('https://schema.org/includedInDataCatalog')

includedInHealthInsurancePlan: URIRef =
rdflib.term.URIRef('https://schema.org/includedInHealthInsurancePlan')

includedRiskFactor: URIRef =
rdflib.term.URIRef('https://schema.org/includedRiskFactor')

includesAttraction: URIRef =
rdflib.term.URIRef('https://schema.org/includesAttraction')

includesHealthPlanFormulary: URIRef =
rdflib.term.URIRef('https://schema.org/includesHealthPlanFormulary')

includesHealthPlanNetwork: URIRef =
rdflib.term.URIRef('https://schema.org/includesHealthPlanNetwork')

includesObject: URIRef = rdflib.term.URIRef('https://schema.org/includesObject')

increasesRiskOf: URIRef = rdflib.term.URIRef('https://schema.org/increasesRiskOf')

industry: URIRef = rdflib.term.URIRef('https://schema.org/industry')

ineligibleRegion: URIRef =
rdflib.term.URIRef('https://schema.org/ineligibleRegion')

infectiousAgent: URIRef = rdflib.term.URIRef('https://schema.org/infectiousAgent')

infectiousAgentClass: URIRef =
rdflib.term.URIRef('https://schema.org/infectiousAgentClass')

ingredients: URIRef = rdflib.term.URIRef('https://schema.org/ingredients')

inker: URIRef = rdflib.term.URIRef('https://schema.org/inker')

insertion: URIRef = rdflib.term.URIRef('https://schema.org/insertion')
```



```
installUrl: URIRef = rdflib.term.URIRef('https://schema.org/installUrl')
instructor: URIRef = rdflib.term.URIRef('https://schema.org/instructor')
instrument: URIRef = rdflib.term.URIRef('https://schema.org/instrument')
intensity: URIRef = rdflib.term.URIRef('https://schema.org/intensity')
interactingDrug: URIRef = rdflib.term.URIRef('https://schema.org/interactingDrug')
interactionCount: URIRef =
rdflib.term.URIRef('https://schema.org/interactionCount')
interactionService: URIRef =
rdflib.term.URIRef('https://schema.org/interactionService')
interactionStatistic: URIRef =
rdflib.term.URIRef('https://schema.org/interactionStatistic')
interactionType: URIRef = rdflib.term.URIRef('https://schema.org/interactionType')
interactivityType: URIRef =
rdflib.term.URIRef('https://schema.org/interactivityType')
interestRate: URIRef = rdflib.term.URIRef('https://schema.org/interestRate')
interpretedAsClaim: URIRef =
rdflib.term.URIRef('https://schema.org/interpretedAsClaim')
inventoryLevel: URIRef = rdflib.term.URIRef('https://schema.org/inventoryLevel')
inverseOf: URIRef = rdflib.term.URIRef('https://schema.org/inverseOf')
isAcceptingNewPatients: URIRef =
rdflib.term.URIRef('https://schema.org/isAcceptingNewPatients')
isAccessibleForFree: URIRef =
rdflib.term.URIRef('https://schema.org/isAccessibleForFree')
isAccessoryOrSparePartFor: URIRef =
rdflib.term.URIRef('https://schema.org/isAccessoryOrSparePartFor')
isAvailableGenerically: URIRef =
rdflib.term.URIRef('https://schema.org/isAvailableGenerically')
isBasedOn: URIRef = rdflib.term.URIRef('https://schema.org/isBasedOn')
isBasedOnUrl: URIRef = rdflib.term.URIRef('https://schema.org/isBasedOnUrl')
isConsumableFor: URIRef = rdflib.term.URIRef('https://schema.org/isConsumableFor')
isEncodedByBioChemEntity: URIRef =
rdflib.term.URIRef('https://schema.org/isEncodedByBioChemEntity')
isFamilyFriendly: URIRef =
rdflib.term.URIRef('https://schema.org/isFamilyFriendly')
isGift: URIRef = rdflib.term.URIRef('https://schema.org/isGift')
```



```

isInvolvedInBiologicalProcess: URIRef =
rdflib.term.URIRef('https://schema.org/isInvolvedInBiologicalProcess')

isLiveBroadcast: URIRef = rdflib.term.URIRef('https://schema.org/isLiveBroadcast')

isLocatedInSubcellularLocation: URIRef =
rdflib.term.URIRef('https://schema.org/isLocatedInSubcellularLocation')

isPartOf: URIRef = rdflib.term.URIRef('https://schema.org/isPartOf')

isPartOfBioChemEntity: URIRef =
rdflib.term.URIRef('https://schema.org/isPartOfBioChemEntity')

isPlanForApartment: URIRef =
rdflib.term.URIRef('https://schema.org/isPlanForApartment')

isProprietary: URIRef = rdflib.term.URIRef('https://schema.org/isProprietary')

isRelatedTo: URIRef = rdflib.term.URIRef('https://schema.org/isRelatedTo')

isResizable: URIRef = rdflib.term.URIRef('https://schema.org/isResizable')

isSimilarTo: URIRef = rdflib.term.URIRef('https://schema.org/isSimilarTo')

isUnlabelledFallback: URIRef =
rdflib.term.URIRef('https://schema.org/isUnlabelledFallback')

isVariantOf: URIRef = rdflib.term.URIRef('https://schema.org/isVariantOf')

isbn: URIRef = rdflib.term.URIRef('https://schema.org/isbn')

isicV4: URIRef = rdflib.term.URIRef('https://schema.org/isicV4')

isrcCode: URIRef = rdflib.term.URIRef('https://schema.org/isrcCode')

issn: URIRef = rdflib.term.URIRef('https://schema.org/issn')

issueNumber: URIRef = rdflib.term.URIRef('https://schema.org/issueNumber')

issuedBy: URIRef = rdflib.term.URIRef('https://schema.org/issuedBy')

issuedThrough: URIRef = rdflib.term.URIRef('https://schema.org/issuedThrough')

iswcCode: URIRef = rdflib.term.URIRef('https://schema.org/iswcCode')

item: URIRef = rdflib.term.URIRef('https://schema.org/item')

itemCondition: URIRef = rdflib.term.URIRef('https://schema.org/itemCondition')

itemDefectReturnFees: URIRef =
rdflib.term.URIRef('https://schema.org/itemDefectReturnFees')

itemDefectReturnLabelSource: URIRef =
rdflib.term.URIRef('https://schema.org/itemDefectReturnLabelSource')

itemDefectReturnShippingFeesAmount: URIRef =
rdflib.term.URIRef('https://schema.org/itemDefectReturnShippingFeesAmount')

itemListElement: URIRef = rdflib.term.URIRef('https://schema.org/itemListElement')

```

```
itemListOrder: URIRef = rdflib.term.URIRef('https://schema.org/itemListOrder')
itemLocation: URIRef = rdflib.term.URIRef('https://schema.org/itemLocation')
itemOffered: URIRef = rdflib.term.URIRef('https://schema.org/itemOffered')
itemReviewed: URIRef = rdflib.term.URIRef('https://schema.org/itemReviewed')
itemShipped: URIRef = rdflib.term.URIRef('https://schema.org/itemShipped')
itinerary: URIRef = rdflib.term.URIRef('https://schema.org/itinerary')
iupacName: URIRef = rdflib.term.URIRef('https://schema.org/iupacName')
jobBenefits: URIRef = rdflib.term.URIRef('https://schema.org/jobBenefits')
jobImmediateStart: URIRef =
rdflib.term.URIRef('https://schema.org/jobImmediateStart')
jobLocation: URIRef = rdflib.term.URIRef('https://schema.org/jobLocation')
jobLocationType: URIRef = rdflib.term.URIRef('https://schema.org/jobLocationType')
jobStartDate: URIRef = rdflib.term.URIRef('https://schema.org/jobStartDate')
jobTitle: URIRef = rdflib.term.URIRef('https://schema.org/jobTitle')
jurisdiction: URIRef = rdflib.term.URIRef('https://schema.org/jurisdiction')
keywords: URIRef = rdflib.term.URIRef('https://schema.org/keywords')
knownVehicleDamages: URIRef =
rdflib.term.URIRef('https://schema.org/knownVehicleDamages')
knows: URIRef = rdflib.term.URIRef('https://schema.org/knows')
knowsAbout: URIRef = rdflib.term.URIRef('https://schema.org/knowsAbout')
knowsLanguage: URIRef = rdflib.term.URIRef('https://schema.org/knowsLanguage')
labelDetails: URIRef = rdflib.term.URIRef('https://schema.org/labelDetails')
landlord: URIRef = rdflib.term.URIRef('https://schema.org/landlord')
language: URIRef = rdflib.term.URIRef('https://schema.org/language')
lastReviewed: URIRef = rdflib.term.URIRef('https://schema.org/lastReviewed')
latitude: URIRef = rdflib.term.URIRef('https://schema.org/latitude')
layoutImage: URIRef = rdflib.term.URIRef('https://schema.org/layoutImage')
learningResourceType: URIRef =
rdflib.term.URIRef('https://schema.org/learningResourceType')
leaseLength: URIRef = rdflib.term.URIRef('https://schema.org/leaseLength')
legalName: URIRef = rdflib.term.URIRef('https://schema.org/legalName')
legalStatus: URIRef = rdflib.term.URIRef('https://schema.org/legalStatus')
```

```
legislationApplies: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationApplies')  
  
legislationChanges: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationChanges')  
  
legislationConsolidates: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationConsolidates')  
  
legislationDate: URIRef = rdflib.term.URIRef('https://schema.org/legislationDate')  
  
legislationDateVersion: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationDateVersion')  
  
legislationIdentifier: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationIdentifier')  
  
legislationJurisdiction: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationJurisdiction')  
  
legislationLegalForce: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationLegalForce')  
  
legislationLegalValue: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationLegalValue')  
  
legislationPassedBy: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationPassedBy')  
  
legislationResponsible: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationResponsible')  
  
legislationTransposes: URIRef =  
rdflib.term.URIRef('https://schema.org/legislationTransposes')  
  
legislationType: URIRef = rdflib.term.URIRef('https://schema.org/legislationType')  
  
leiCode: URIRef = rdflib.term.URIRef('https://schema.org/leiCode')  
  
lender: URIRef = rdflib.term.URIRef('https://schema.org/lender')  
  
lesser: URIRef = rdflib.term.URIRef('https://schema.org/lesser')  
  
lesserOrEqual: URIRef = rdflib.term.URIRef('https://schema.org/lesserOrEqual')  
  
letterer: URIRef = rdflib.term.URIRef('https://schema.org/letterer')  
  
license: URIRef = rdflib.term.URIRef('https://schema.org/license')  
  
line: URIRef = rdflib.term.URIRef('https://schema.org/line')  
  
linkRelationship: URIRef =  
rdflib.term.URIRef('https://schema.org/linkRelationship')  
  
liveBlogUpdate: URIRef = rdflib.term.URIRef('https://schema.org/liveBlogUpdate')  
  
loanMortgageMandateAmount: URIRef =  
rdflib.term.URIRef('https://schema.org/loanMortgageMandateAmount')
```

```
loanPaymentAmount: URIRef =  
rdflib.term.URIRef('https://schema.org/loanPaymentAmount')  
  
loanPaymentFrequency: URIRef =  
rdflib.term.URIRef('https://schema.org/loanPaymentFrequency')  
  
loanRepaymentForm: URIRef =  
rdflib.term.URIRef('https://schema.org/loanRepaymentForm')  
  
loanTerm: URIRef = rdflib.term.URIRef('https://schema.org/loanTerm')  
  
loanType: URIRef = rdflib.term.URIRef('https://schema.org/loanType')  
  
location: URIRef = rdflib.term.URIRef('https://schema.org/location')  
  
locationCreated: URIRef = rdflib.term.URIRef('https://schema.org/locationCreated')  
  
lodgingUnitDescription: URIRef =  
rdflib.term.URIRef('https://schema.org/lodgingUnitDescription')  
  
lodgingUnitType: URIRef = rdflib.term.URIRef('https://schema.org/lodgingUnitType')  
  
logo: URIRef = rdflib.term.URIRef('https://schema.org/logo')  
  
longitude: URIRef = rdflib.term.URIRef('https://schema.org/longitude')  
  
loser: URIRef = rdflib.term.URIRef('https://schema.org/loser')  
  
lowPrice: URIRef = rdflib.term.URIRef('https://schema.org/lowPrice')  
  
lyricist: URIRef = rdflib.term.URIRef('https://schema.org/lyricist')  
  
lyrics: URIRef = rdflib.term.URIRef('https://schema.org/lyrics')  
  
mainContentOfPage: URIRef =  
rdflib.term.URIRef('https://schema.org/mainContentOfPage')  
  
mainEntity: URIRef = rdflib.term.URIRef('https://schema.org/mainEntity')  
  
mainEntityOfPage: URIRef =  
rdflib.term.URIRef('https://schema.org/mainEntityOfPage')  
  
maintainer: URIRef = rdflib.term.URIRef('https://schema.org/maintainer')  
  
makesOffer: URIRef = rdflib.term.URIRef('https://schema.org/makesOffer')  
  
manufacturer: URIRef = rdflib.term.URIRef('https://schema.org/manufacturer')  
  
map: URIRef = rdflib.term.URIRef('https://schema.org/map')  
  
mapType: URIRef = rdflib.term.URIRef('https://schema.org/mapType')  
  
maps: URIRef = rdflib.term.URIRef('https://schema.org/maps')  
  
marginOfError: URIRef = rdflib.term.URIRef('https://schema.org/marginOfError')  
  
masthead: URIRef = rdflib.term.URIRef('https://schema.org/masthead')  
  
material: URIRef = rdflib.term.URIRef('https://schema.org/material')
```

```
materialExtent: URIRef = rdflib.term.URIRef('https://schema.org/materialExtent')
mathExpression: URIRef = rdflib.term.URIRef('https://schema.org/mathExpression')
maxPrice: URIRef = rdflib.term.URIRef('https://schema.org/maxPrice')
maxValue: URIRef = rdflib.term.URIRef('https://schema.org/maxValue')
maximumAttendeeCapacity: URIRef =
rdflib.term.URIRef('https://schema.org/maximumAttendeeCapacity')
maximumEnrollment: URIRef =
rdflib.term.URIRef('https://schema.org/maximumEnrollment')
maximumIntake: URIRef = rdflib.term.URIRef('https://schema.org/maximumIntake')
maximumPhysicalAttendeeCapacity: URIRef =
rdflib.term.URIRef('https://schema.org/maximumPhysicalAttendeeCapacity')
maximumVirtualAttendeeCapacity: URIRef =
rdflib.term.URIRef('https://schema.org/maximumVirtualAttendeeCapacity')
mealService: URIRef = rdflib.term.URIRef('https://schema.org/mealService')
measuredProperty: URIRef =
rdflib.term.URIRef('https://schema.org/measuredProperty')
measuredValue: URIRef = rdflib.term.URIRef('https://schema.org/measuredValue')
measurementTechnique: URIRef =
rdflib.term.URIRef('https://schema.org/measurementTechnique')
mechanismOfAction: URIRef =
rdflib.term.URIRef('https://schema.org/mechanismOfAction')
mediaAuthenticityCategory: URIRef =
rdflib.term.URIRef('https://schema.org/mediaAuthenticityCategory')
mediaItemAppearance: URIRef =
rdflib.term.URIRef('https://schema.org/mediaItemAppearance')
median: URIRef = rdflib.term.URIRef('https://schema.org/median')
medicalAudience: URIRef = rdflib.term.URIRef('https://schema.org/medicalAudience')
medicalSpecialty: URIRef =
rdflib.term.URIRef('https://schema.org/medicalSpecialty')
medicineSystem: URIRef = rdflib.term.URIRef('https://schema.org/medicineSystem')
meetsEmissionStandard: URIRef =
rdflib.term.URIRef('https://schema.org/meetsEmissionStandard')
member: URIRef = rdflib.term.URIRef('https://schema.org/member')
memberOf: URIRef = rdflib.term.URIRef('https://schema.org/memberOf')
members: URIRef = rdflib.term.URIRef('https://schema.org/members')
```

```
membershipNumber: URIRef =  
rdflib.term.URIRef('https://schema.org/membershipNumber')  
  
membershipPointsEarned: URIRef =  
rdflib.term.URIRef('https://schema.org/membershipPointsEarned')  
  
memoryRequirements: URIRef =  
rdflib.term.URIRef('https://schema.org/memoryRequirements')  
  
mentions: URIRef = rdflib.term.URIRef('https://schema.org/mentions')  
  
menu: URIRef = rdflib.term.URIRef('https://schema.org/menu')  
  
menuAddOn: URIRef = rdflib.term.URIRef('https://schema.org/menuAddOn')  
  
merchant: URIRef = rdflib.term.URIRef('https://schema.org/merchant')  
  
merchantReturnDays: URIRef =  
rdflib.term.URIRef('https://schema.org/merchantReturnDays')  
  
merchantReturnLink: URIRef =  
rdflib.term.URIRef('https://schema.org/merchantReturnLink')  
  
messageAttachment: URIRef =  
rdflib.term.URIRef('https://schema.org/messageAttachment')  
  
mileageFromOdometer: URIRef =  
rdflib.term.URIRef('https://schema.org/mileageFromOdometer')  
  
minPrice: URIRef = rdflib.term.URIRef('https://schema.org/minPrice')  
  
minValue: URIRef = rdflib.term.URIRef('https://schema.org/minValue')  
  
minimumPaymentDue: URIRef =  
rdflib.term.URIRef('https://schema.org/minimumPaymentDue')  
  
missionCoveragePrioritiesPolicy: URIRef =  
rdflib.term.URIRef('https://schema.org/missionCoveragePrioritiesPolicy')  
  
model: URIRef = rdflib.term.URIRef('https://schema.org/model')  
  
modelDate: URIRef = rdflib.term.URIRef('https://schema.org/modelDate')  
  
modifiedTime: URIRef = rdflib.term.URIRef('https://schema.org/modifiedTime')  
  
molecularFormula: URIRef =  
rdflib.term.URIRef('https://schema.org/molecularFormula')  
  
molecularWeight: URIRef = rdflib.term.URIRef('https://schema.org/molecularWeight')  
  
monoisotopicMolecularWeight: URIRef =  
rdflib.term.URIRef('https://schema.org/monoisotopicMolecularWeight')  
  
monthlyMinimumRepaymentAmount: URIRef =  
rdflib.term.URIRef('https://schema.org/monthlyMinimumRepaymentAmount')  
  
monthsOfExperience: URIRef =  
rdflib.term.URIRef('https://schema.org/monthsOfExperience')
```

```
mpn: URIRef = rdflib.term.URIRef('https://schema.org/mpn')

multipleValues: URIRef = rdflib.term.URIRef('https://schema.org/multipleValues')

muscleAction: URIRef = rdflib.term.URIRef('https://schema.org/muscleAction')

musicArrangement: URIRef =
rdflib.term.URIRef('https://schema.org/musicArrangement')

musicBy: URIRef = rdflib.term.URIRef('https://schema.org/musicBy')

musicCompositionForm: URIRef =
rdflib.term.URIRef('https://schema.org/musicCompositionForm')

musicGroupMember: URIRef =
rdflib.term.URIRef('https://schema.org/musicGroupMember')

musicReleaseFormat: URIRef =
rdflib.term.URIRef('https://schema.org/musicReleaseFormat')

musicalKey: URIRef = rdflib.term.URIRef('https://schema.org/musicalKey')

naics: URIRef = rdflib.term.URIRef('https://schema.org/naics')

name: URIRef = rdflib.term.URIRef('https://schema.org/name')

namedPosition: URIRef = rdflib.term.URIRef('https://schema.org/namedPosition')

nationality: URIRef = rdflib.term.URIRef('https://schema.org/nationality')

naturalProgression: URIRef =
rdflib.term.URIRef('https://schema.org/naturalProgression')

negativeNotes: URIRef = rdflib.term.URIRef('https://schema.org/negativeNotes')

nerve: URIRef = rdflib.term.URIRef('https://schema.org/nerve')

nerveMotor: URIRef = rdflib.term.URIRef('https://schema.org/nerveMotor')

netWorth: URIRef = rdflib.term.URIRef('https://schema.org/netWorth')

newsUpdatesAndGuidelines: URIRef =
rdflib.term.URIRef('https://schema.org/newsUpdatesAndGuidelines')

nextItem: URIRef = rdflib.term.URIRef('https://schema.org/nextItem')

noBylinesPolicy: URIRef = rdflib.term.URIRef('https://schema.org/noBylinesPolicy')

nonEqual: URIRef = rdflib.term.URIRef('https://schema.org/nonEqual')

nonProprietaryName: URIRef =
rdflib.term.URIRef('https://schema.org/nonProprietaryName')

nonprofitStatus: URIRef = rdflib.term.URIRef('https://schema.org/nonprofitStatus')

normalRange: URIRef = rdflib.term.URIRef('https://schema.org/normalRange')

nsn: URIRef = rdflib.term.URIRef('https://schema.org/nsn')
```



```
numAdults: URIRef = rdflib.term.URIRef('https://schema.org/numAdults')

numChildren: URIRef = rdflib.term.URIRef('https://schema.org/numChildren')

numConstraints: URIRef = rdflib.term.URIRef('https://schema.org/numConstraints')

numTracks: URIRef = rdflib.term.URIRef('https://schema.org/numTracks')

numberOfAccommodationUnits: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfAccommodationUnits')

numberOfAirbags: URIRef = rdflib.term.URIRef('https://schema.org/numberOfAirbags')

numberOfAvailableAccommodationUnits: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfAvailableAccommodationUnits')

numberOfAxles: URIRef = rdflib.term.URIRef('https://schema.org/numberOfAxles')

numberOfBathroomsTotal: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfBathroomsTotal')

numberOfBedrooms: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfBedrooms')

numberOfBeds: URIRef = rdflib.term.URIRef('https://schema.org/numberOfBeds')

numberOfCredits: URIRef = rdflib.term.URIRef('https://schema.org/numberOfCredits')

numberOfDoors: URIRef = rdflib.term.URIRef('https://schema.org/numberOfDoors')

numberOfEmployees: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfEmployees')

numberOfEpisodes: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfEpisodes')

numberOfForwardGears: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfForwardGears')

numberOfFullBathrooms: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfFullBathrooms')

numberOfItems: URIRef = rdflib.term.URIRef('https://schema.org/numberOfItems')

numberOfLoanPayments: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfLoanPayments')

numberOfPages: URIRef = rdflib.term.URIRef('https://schema.org/numberOfPages')

numberOfPartialBathrooms: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfPartialBathrooms')

numberOfPlayers: URIRef = rdflib.term.URIRef('https://schema.org/numberOfPlayers')

numberOfPreviousOwners: URIRef =
rdflib.term.URIRef('https://schema.org/numberOfPreviousOwners')

numberOfRooms: URIRef = rdflib.term.URIRef('https://schema.org/numberOfRooms')
```



```
numberOfSeasons: URIRef = rdflib.term.URIRef('https://schema.org/numberOfSeasons')

numberedPosition: URIRef =
rdflib.term.URIRef('https://schema.org/numberedPosition')

nutrition: URIRef = rdflib.term.URIRef('https://schema.org/nutrition')

object: URIRef = rdflib.term.URIRef('https://schema.org/object')

observationDate: URIRef = rdflib.term.URIRef('https://schema.org/observationDate')

observedNode: URIRef = rdflib.term.URIRef('https://schema.org/observedNode')

occupancy: URIRef = rdflib.term.URIRef('https://schema.org/occupancy')

occupationLocation: URIRef =
rdflib.term.URIRef('https://schema.org/occupationLocation')

occupationalCategory: URIRef =
rdflib.term.URIRef('https://schema.org/occupationalCategory')

occupationalCredentialAwarded: URIRef =
rdflib.term.URIRef('https://schema.org/occupationalCredentialAwarded')

offerCount: URIRef = rdflib.term.URIRef('https://schema.org/offerCount')

offeredBy: URIRef = rdflib.term.URIRef('https://schema.org/offeredBy')

offers: URIRef = rdflib.term.URIRef('https://schema.org/offers')

offersPrescriptionByMail: URIRef =
rdflib.term.URIRef('https://schema.org/offersPrescriptionByMail')

openingHours: URIRef = rdflib.term.URIRef('https://schema.org/openingHours')

openingHoursSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/openingHoursSpecification')

opens: URIRef = rdflib.term.URIRef('https://schema.org/opens')

operatingSystem: URIRef = rdflib.term.URIRef('https://schema.org/operatingSystem')

opponent: URIRef = rdflib.term.URIRef('https://schema.org/opponent')

option: URIRef = rdflib.term.URIRef('https://schema.org/option')

orderDate: URIRef = rdflib.term.URIRef('https://schema.org/orderDate')

orderDelivery: URIRef = rdflib.term.URIRef('https://schema.org/orderDelivery')

orderItemNumber: URIRef = rdflib.term.URIRef('https://schema.org/orderItemNumber')

orderItemStatus: URIRef = rdflib.term.URIRef('https://schema.org/orderItemStatus')

orderNumber: URIRef = rdflib.term.URIRef('https://schema.org/orderNumber')

orderQuantity: URIRef = rdflib.term.URIRef('https://schema.org/orderQuantity')

orderStatus: URIRef = rdflib.term.URIRef('https://schema.org/orderStatus')
```

```
orderedItem: URIRef = rdflib.term.URIRef('https://schema.org/orderedItem')
organizer: URIRef = rdflib.term.URIRef('https://schema.org/organizer')
originAddress: URIRef = rdflib.term.URIRef('https://schema.org/originAddress')
originalMediaContextDescription: URIRef =
rdflib.term.URIRef('https://schema.org/originalMediaContextDescription')
originalMediaLink: URIRef =
rdflib.term.URIRef('https://schema.org/originalMediaLink')
originatesFrom: URIRef = rdflib.term.URIRef('https://schema.org/originatesFrom')
overdosage: URIRef = rdflib.term.URIRef('https://schema.org/overdosage')
ownedFrom: URIRef = rdflib.term.URIRef('https://schema.org/ownedFrom')
ownedThrough: URIRef = rdflib.term.URIRef('https://schema.org/ownedThrough')
ownershipFundingInfo: URIRef =
rdflib.term.URIRef('https://schema.org/ownershipFundingInfo')
owns: URIRef = rdflib.term.URIRef('https://schema.org/owns')
pageEnd: URIRef = rdflib.term.URIRef('https://schema.org/pageEnd')
pageStart: URIRef = rdflib.term.URIRef('https://schema.org/pageStart')
pagination: URIRef = rdflib.term.URIRef('https://schema.org/pagination')
parent: URIRef = rdflib.term.URIRef('https://schema.org/parent')
parentItem: URIRef = rdflib.term.URIRef('https://schema.org/parentItem')
parentOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/parentOrganization')
parentService: URIRef = rdflib.term.URIRef('https://schema.org/parentService')
parentTaxon: URIRef = rdflib.term.URIRef('https://schema.org/parentTaxon')
parents: URIRef = rdflib.term.URIRef('https://schema.org/parents')
partOfEpisode: URIRef = rdflib.term.URIRef('https://schema.org/partOfEpisode')
partOfInvoice: URIRef = rdflib.term.URIRef('https://schema.org/partOfInvoice')
partOfOrder: URIRef = rdflib.term.URIRef('https://schema.org/partOfOrder')
partOfSeason: URIRef = rdflib.term.URIRef('https://schema.org/partOfSeason')
partOfSeries: URIRef = rdflib.term.URIRef('https://schema.org/partOfSeries')
partOfSystem: URIRef = rdflib.term.URIRef('https://schema.org/partOfSystem')
partOfTVSeries: URIRef = rdflib.term.URIRef('https://schema.org/partOfTVSeries')
partOfTrip: URIRef = rdflib.term.URIRef('https://schema.org/partOfTrip')
```

```
participant: URIRef = rdflib.term.URIRef('https://schema.org/participant')
partySize: URIRef = rdflib.term.URIRef('https://schema.org/partySize')
passengerPriorityStatus: URIRef =
rdflib.term.URIRef('https://schema.org/passengerPriorityStatus')
passengerSequenceNumber: URIRef =
rdflib.term.URIRef('https://schema.org/passengerSequenceNumber')
pathophysiology: URIRef = rdflib.term.URIRef('https://schema.org/pathophysiology')
pattern: URIRef = rdflib.term.URIRef('https://schema.org/pattern')
payload: URIRef = rdflib.term.URIRef('https://schema.org/payload')
paymentAccepted: URIRef = rdflib.term.URIRef('https://schema.org/paymentAccepted')
paymentDue: URIRef = rdflib.term.URIRef('https://schema.org/paymentDue')
paymentDueDate: URIRef = rdflib.term.URIRef('https://schema.org/paymentDueDate')
paymentMethod: URIRef = rdflib.term.URIRef('https://schema.org/paymentMethod')
paymentMethodId: URIRef = rdflib.term.URIRef('https://schema.org/paymentMethodId')
paymentStatus: URIRef = rdflib.term.URIRef('https://schema.org/paymentStatus')
paymentUrl: URIRef = rdflib.term.URIRef('https://schema.org/paymentUrl')
penciler: URIRef = rdflib.term.URIRef('https://schema.org/penciler')
percentile10: URIRef = rdflib.term.URIRef('https://schema.org/percentile10')
percentile25: URIRef = rdflib.term.URIRef('https://schema.org/percentile25')
percentile75: URIRef = rdflib.term.URIRef('https://schema.org/percentile75')
percentile90: URIRef = rdflib.term.URIRef('https://schema.org/percentile90')
performTime: URIRef = rdflib.term.URIRef('https://schema.org/performTime')
performer: URIRef = rdflib.term.URIRef('https://schema.org/performer')
performerIn: URIRef = rdflib.term.URIRef('https://schema.org/performerIn')
performers: URIRef = rdflib.term.URIRef('https://schema.org/performers')
permissionType: URIRef = rdflib.term.URIRef('https://schema.org/permissionType')
permissions: URIRef = rdflib.term.URIRef('https://schema.org/permissions')
permitAudience: URIRef = rdflib.term.URIRef('https://schema.org/permitAudience')
permittedUsage: URIRef = rdflib.term.URIRef('https://schema.org/permittedUsage')
petsAllowed: URIRef = rdflib.term.URIRef('https://schema.org/petsAllowed')
phoneticText: URIRef = rdflib.term.URIRef('https://schema.org/phoneticText')
```

```
photo: URIRef = rdflib.term.URIRef('https://schema.org/photo')

photos: URIRef = rdflib.term.URIRef('https://schema.org/photos')

physicalRequirement: URIRef =
rdflib.term.URIRef('https://schema.org/physicalRequirement')

physiologicalBenefits: URIRef =
rdflib.term.URIRef('https://schema.org/physiologicalBenefits')

pickupLocation: URIRef = rdflib.term.URIRef('https://schema.org/pickupLocation')

pickupTime: URIRef = rdflib.term.URIRef('https://schema.org/pickupTime')

playMode: URIRef = rdflib.term.URIRef('https://schema.org/playMode')

playerType: URIRef = rdflib.term.URIRef('https://schema.org/playerType')

playersOnline: URIRef = rdflib.term.URIRef('https://schema.org/playersOnline')

polygon: URIRef = rdflib.term.URIRef('https://schema.org/polygon')

populationType: URIRef = rdflib.term.URIRef('https://schema.org/populationType')

position: URIRef = rdflib.term.URIRef('https://schema.org/position')

positiveNotes: URIRef = rdflib.term.URIRef('https://schema.org/positiveNotes')

possibleComplication: URIRef =
rdflib.term.URIRef('https://schema.org/possibleComplication')

possibleTreatment: URIRef =
rdflib.term.URIRef('https://schema.org/possibleTreatment')

postOfficeBoxNumber: URIRef =
rdflib.term.URIRef('https://schema.org/postOfficeBoxNumber')

postOp: URIRef = rdflib.term.URIRef('https://schema.org/postOp')

postalCode: URIRef = rdflib.term.URIRef('https://schema.org/postalCode')

postalCodeBegin: URIRef = rdflib.term.URIRef('https://schema.org/postalCodeBegin')

postalCodeEnd: URIRef = rdflib.term.URIRef('https://schema.org/postalCodeEnd')

postalCodePrefix: URIRef =
rdflib.term.URIRef('https://schema.org/postalCodePrefix')

postalCodeRange: URIRef = rdflib.term.URIRef('https://schema.org/postalCodeRange')

potentialAction: URIRef = rdflib.term.URIRef('https://schema.org/potentialAction')

potentialUse: URIRef = rdflib.term.URIRef('https://schema.org/potentialUse')

preOp: URIRef = rdflib.term.URIRef('https://schema.org/preOp')

predecessorOf: URIRef = rdflib.term.URIRef('https://schema.org/predecessorOf')
```

```

pregnancyCategory: URIRef =
rdflib.term.URIRef('https://schema.org/pregnancyCategory')

pregnancyWarning: URIRef =
rdflib.term.URIRef('https://schema.org/pregnancyWarning')

prepTime: URIRef = rdflib.term.URIRef('https://schema.org/prepTime')

preparation: URIRef = rdflib.term.URIRef('https://schema.org/preparation')

prescribingInfo: URIRef = rdflib.term.URIRef('https://schema.org/prescribingInfo')

prescriptionStatus: URIRef =
rdflib.term.URIRef('https://schema.org/prescriptionStatus')

previousItem: URIRef = rdflib.term.URIRef('https://schema.org/previousItem')

previousStartDate: URIRef =
rdflib.term.URIRef('https://schema.org/previousStartDate')

price: URIRef = rdflib.term.URIRef('https://schema.org/price')

priceComponent: URIRef = rdflib.term.URIRef('https://schema.org/priceComponent')

priceComponentType: URIRef =
rdflib.term.URIRef('https://schema.org/priceComponentType')

priceCurrency: URIRef = rdflib.term.URIRef('https://schema.org/priceCurrency')

priceRange: URIRef = rdflib.term.URIRef('https://schema.org/priceRange')

priceSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/priceSpecification')

priceType: URIRef = rdflib.term.URIRef('https://schema.org/priceType')

priceValidUntil: URIRef = rdflib.term.URIRef('https://schema.org/priceValidUntil')

primaryImageOfPage: URIRef =
rdflib.term.URIRef('https://schema.org/primaryImageOfPage')

primaryPrevention: URIRef =
rdflib.term.URIRef('https://schema.org/primaryPrevention')

printColumn: URIRef = rdflib.term.URIRef('https://schema.org/printColumn')

printEdition: URIRef = rdflib.term.URIRef('https://schema.org/printEdition')

printPage: URIRef = rdflib.term.URIRef('https://schema.org/printPage')

printSection: URIRef = rdflib.term.URIRef('https://schema.org/printSection')

procedure: URIRef = rdflib.term.URIRef('https://schema.org/procedure')

procedureType: URIRef = rdflib.term.URIRef('https://schema.org/procedureType')

processingTime: URIRef = rdflib.term.URIRef('https://schema.org/processingTime')

```

```
processorRequirements: URIRef =  
rdflib.term.URIRef('https://schema.org/processorRequirements')  
  
producer: URIRef = rdflib.term.URIRef('https://schema.org/producer')  
  
produces: URIRef = rdflib.term.URIRef('https://schema.org/produces')  
  
productGroupID: URIRef = rdflib.term.URIRef('https://schema.org/productGroupID')  
  
productID: URIRef = rdflib.term.URIRef('https://schema.org/productID')  
  
productSupported: URIRef =  
rdflib.term.URIRef('https://schema.org/productSupported')  
  
productionCompany: URIRef =  
rdflib.term.URIRef('https://schema.org/productionCompany')  
  
productionDate: URIRef = rdflib.term.URIRef('https://schema.org/productionDate')  
  
proficiencyLevel: URIRef =  
rdflib.term.URIRef('https://schema.org/proficiencyLevel')  
  
programMembershipUsed: URIRef =  
rdflib.term.URIRef('https://schema.org/programMembershipUsed')  
  
programName: URIRef = rdflib.term.URIRef('https://schema.org/programName')  
  
programPrerequisites: URIRef =  
rdflib.term.URIRef('https://schema.org/programPrerequisites')  
  
programType: URIRef = rdflib.term.URIRef('https://schema.org/programType')  
  
programmingLanguage: URIRef =  
rdflib.term.URIRef('https://schema.org/programmingLanguage')  
  
programmingModel: URIRef =  
rdflib.term.URIRef('https://schema.org/programmingModel')  
  
propertyID: URIRef = rdflib.term.URIRef('https://schema.org/propertyID')  
  
proprietaryName: URIRef = rdflib.term.URIRef('https://schema.org/proprietaryName')  
  
proteinContent: URIRef = rdflib.term.URIRef('https://schema.org/proteinContent')  
  
provider: URIRef = rdflib.term.URIRef('https://schema.org/provider')  
  
providerMobility: URIRef =  
rdflib.term.URIRef('https://schema.org/providerMobility')  
  
providesBroadcastService: URIRef =  
rdflib.term.URIRef('https://schema.org/providesBroadcastService')  
  
providesService: URIRef = rdflib.term.URIRef('https://schema.org/providesService')  
  
publicAccess: URIRef = rdflib.term.URIRef('https://schema.org/publicAccess')  
  
publicTransportClosuresInfo: URIRef =  
rdflib.term.URIRef('https://schema.org/publicTransportClosuresInfo')
```

```

publication: URIRef = rdflib.term.URIRef('https://schema.org/publication')
publicationType: URIRef = rdflib.term.URIRef('https://schema.org/publicationType')
publishedBy: URIRef = rdflib.term.URIRef('https://schema.org/publishedBy')
publishedOn: URIRef = rdflib.term.URIRef('https://schema.org/publishedOn')
publisher: URIRef = rdflib.term.URIRef('https://schema.org/publisher')
publisherImprint: URIRef =
rdflib.term.URIRef('https://schema.org/publisherImprint')
publishingPrinciples: URIRef =
rdflib.term.URIRef('https://schema.org/publishingPrinciples')
purchaseDate: URIRef = rdflib.term.URIRef('https://schema.org/purchaseDate')
qualifications: URIRef = rdflib.term.URIRef('https://schema.org/qualifications')
quarantineGuidelines: URIRef =
rdflib.term.URIRef('https://schema.org/quarantineGuidelines')
query: URIRef = rdflib.term.URIRef('https://schema.org/query')
quest: URIRef = rdflib.term.URIRef('https://schema.org/quest')
question: URIRef = rdflib.term.URIRef('https://schema.org/question')
rangeIncludes: URIRef = rdflib.term.URIRef('https://schema.org/rangeIncludes')
ratingCount: URIRef = rdflib.term.URIRef('https://schema.org/ratingCount')
ratingExplanation: URIRef =
rdflib.term.URIRef('https://schema.org/ratingExplanation')
ratingValue: URIRef = rdflib.term.URIRef('https://schema.org/ratingValue')
readBy: URIRef = rdflib.term.URIRef('https://schema.org/readBy')
readonlyValue: URIRef = rdflib.term.URIRef('https://schema.org/readonlyValue')
realEstateAgent: URIRef = rdflib.term.URIRef('https://schema.org/realEstateAgent')
recipe: URIRef = rdflib.term.URIRef('https://schema.org/recipe')
recipeCategory: URIRef = rdflib.term.URIRef('https://schema.org/recipeCategory')
recipeCuisine: URIRef = rdflib.term.URIRef('https://schema.org/recipeCuisine')
recipeIngredient: URIRef =
rdflib.term.URIRef('https://schema.org/recipeIngredient')
recipeInstructions: URIRef =
rdflib.term.URIRef('https://schema.org/recipeInstructions')
recipeYield: URIRef = rdflib.term.URIRef('https://schema.org/recipeYield')
recipient: URIRef = rdflib.term.URIRef('https://schema.org/recipient')

```



```
recognizedBy: URIRef = rdflib.term.URIRef('https://schema.org/recognizedBy')

recognizingAuthority: URIRef =
rdflib.term.URIRef('https://schema.org/recognizingAuthority')

recommendationStrength: URIRef =
rdflib.term.URIRef('https://schema.org/recommendationStrength')

recommendedIntake: URIRef =
rdflib.term.URIRef('https://schema.org/recommendedIntake')

recordLabel: URIRef = rdflib.term.URIRef('https://schema.org/recordLabel')

recordedAs: URIRef = rdflib.term.URIRef('https://schema.org/recordedAs')

recordedAt: URIRef = rdflib.term.URIRef('https://schema.org/recordedAt')

recordedIn: URIRef = rdflib.term.URIRef('https://schema.org/recordedIn')

recordingOf: URIRef = rdflib.term.URIRef('https://schema.org/recordingOf')

recourseLoan: URIRef = rdflib.term.URIRef('https://schema.org/recourseLoan')

referenceQuantity: URIRef =
rdflib.term.URIRef('https://schema.org/referenceQuantity')

referencesOrder: URIRef = rdflib.term.URIRef('https://schema.org/referencesOrder')

refundType: URIRef = rdflib.term.URIRef('https://schema.org/refundType')

regionDrained: URIRef = rdflib.term.URIRef('https://schema.org/regionDrained')

regionsAllowed: URIRef = rdflib.term.URIRef('https://schema.org/regionsAllowed')

relatedAnatomy: URIRef = rdflib.term.URIRef('https://schema.org/relatedAnatomy')

relatedCondition: URIRef =
rdflib.term.URIRef('https://schema.org/relatedCondition')

relatedDrug: URIRef = rdflib.term.URIRef('https://schema.org/relatedDrug')

relatedLink: URIRef = rdflib.term.URIRef('https://schema.org/relatedLink')

relatedStructure: URIRef =
rdflib.term.URIRef('https://schema.org/relatedStructure')

relatedTherapy: URIRef = rdflib.term.URIRef('https://schema.org/relatedTherapy')

relatedTo: URIRef = rdflib.term.URIRef('https://schema.org/relatedTo')

releaseDate: URIRef = rdflib.term.URIRef('https://schema.org/releaseDate')

releaseNotes: URIRef = rdflib.term.URIRef('https://schema.org/releaseNotes')

releaseOf: URIRef = rdflib.term.URIRef('https://schema.org/releaseOf')

releasedEvent: URIRef = rdflib.term.URIRef('https://schema.org/releasedEvent')
```



```
relevantOccupation: URIRef =  
rdflib.term.URIRef('https://schema.org/relevantOccupation')  
  
relevantSpecialty: URIRef =  
rdflib.term.URIRef('https://schema.org/relevantSpecialty')  
  
remainingAttendeeCapacity: URIRef =  
rdflib.term.URIRef('https://schema.org/remainingAttendeeCapacity')  
  
renegotiableLoan: URIRef =  
rdflib.term.URIRef('https://schema.org/renegotiableLoan')  
  
repeatCount: URIRef = rdflib.term.URIRef('https://schema.org/repeatCount')  
repeatFrequency: URIRef = rdflib.term.URIRef('https://schema.org/repeatFrequency')  
repetitions: URIRef = rdflib.term.URIRef('https://schema.org/repetitions')  
replacee: URIRef = rdflib.term.URIRef('https://schema.org/replacee')  
replacer: URIRef = rdflib.term.URIRef('https://schema.org/replacer')  
replyToUrl: URIRef = rdflib.term.URIRef('https://schema.org/replyToUrl')  
reportNumber: URIRef = rdflib.term.URIRef('https://schema.org/reportNumber')  
representativeOfPage: URIRef =  
rdflib.term.URIRef('https://schema.org/representativeOfPage')  
  
requiredCollateral: URIRef =  
rdflib.term.URIRef('https://schema.org/requiredCollateral')  
  
requiredGender: URIRef = rdflib.term.URIRef('https://schema.org/requiredGender')  
requiredMaxAge: URIRef = rdflib.term.URIRef('https://schema.org/requiredMaxAge')  
requiredMinAge: URIRef = rdflib.term.URIRef('https://schema.org/requiredMinAge')  
  
requiredQuantity: URIRef =  
rdflib.term.URIRef('https://schema.org/requiredQuantity')  
  
requirements: URIRef = rdflib.term.URIRef('https://schema.org/requirements')  
  
requiresSubscription: URIRef =  
rdflib.term.URIRef('https://schema.org/requiresSubscription')  
  
reservationFor: URIRef = rdflib.term.URIRef('https://schema.org/reservationFor')  
reservationId: URIRef = rdflib.term.URIRef('https://schema.org/reservationId')  
  
reservationStatus: URIRef =  
rdflib.term.URIRef('https://schema.org/reservationStatus')  
  
reservedTicket: URIRef = rdflib.term.URIRef('https://schema.org/reservedTicket')  
  
responsibilities: URIRef =  
rdflib.term.URIRef('https://schema.org/responsibilities')  
  
restPeriods: URIRef = rdflib.term.URIRef('https://schema.org/restPeriods')
```

```
restockingFee: URIRef = rdflib.term.URIRef('https://schema.org/restockingFee')
result: URIRef = rdflib.term.URIRef('https://schema.org/result')
resultComment: URIRef = rdflib.term.URIRef('https://schema.org/resultComment')
resultReview: URIRef = rdflib.term.URIRef('https://schema.org/resultReview')
returnFees: URIRef = rdflib.term.URIRef('https://schema.org/returnFees')
returnLabelSource: URIRef =
rdflib.term.URIRef('https://schema.org/returnLabelSource')
returnMethod: URIRef = rdflib.term.URIRef('https://schema.org/returnMethod')
returnPolicyCategory: URIRef =
rdflib.term.URIRef('https://schema.org/returnPolicyCategory')
returnPolicyCountry: URIRef =
rdflib.term.URIRef('https://schema.org/returnPolicyCountry')
returnPolicySeasonalOverride: URIRef =
rdflib.term.URIRef('https://schema.org/returnPolicySeasonalOverride')
returnShippingFeesAmount: URIRef =
rdflib.term.URIRef('https://schema.org/returnShippingFeesAmount')
review: URIRef = rdflib.term.URIRef('https://schema.org/review')
reviewAspect: URIRef = rdflib.term.URIRef('https://schema.org/reviewAspect')
reviewBody: URIRef = rdflib.term.URIRef('https://schema.org/reviewBody')
reviewCount: URIRef = rdflib.term.URIRef('https://schema.org/reviewCount')
reviewRating: URIRef = rdflib.term.URIRef('https://schema.org/reviewRating')
reviewedBy: URIRef = rdflib.term.URIRef('https://schema.org/reviewedBy')
reviews: URIRef = rdflib.term.URIRef('https://schema.org/reviews')
riskFactor: URIRef = rdflib.term.URIRef('https://schema.org/riskFactor')
risks: URIRef = rdflib.term.URIRef('https://schema.org/risks')
roleName: URIRef = rdflib.term.URIRef('https://schema.org/roleName')
roofLoad: URIRef = rdflib.term.URIRef('https://schema.org/roofLoad')
rsvpResponse: URIRef = rdflib.term.URIRef('https://schema.org/rsvpResponse')
runsTo: URIRef = rdflib.term.URIRef('https://schema.org/runsTo')
runtime: URIRef = rdflib.term.URIRef('https://schema.org/runtime')
runtimePlatform: URIRef = rdflib.term.URIRef('https://schema.org/runtimePlatform')
rxcul: URIRef = rdflib.term.URIRef('https://schema.org/rxcui')
```

```
safetyConsideration: URIRef =  
rdflib.term.URIRef('https://schema.org/safetyConsideration')  
  
salaryCurrency: URIRef = rdflib.term.URIRef('https://schema.org/salaryCurrency')  
  
salaryUponCompletion: URIRef =  
rdflib.term.URIRef('https://schema.org/salaryUponCompletion')  
  
sameAs: URIRef = rdflib.term.URIRef('https://schema.org/sameAs')  
  
sampleType: URIRef = rdflib.term.URIRef('https://schema.org/sampleType')  
  
saturatedFatContent: URIRef =  
rdflib.term.URIRef('https://schema.org/saturatedFatContent')  
  
scheduleTimezone: URIRef =  
rdflib.term.URIRef('https://schema.org/scheduleTimezone')  
  
scheduledPaymentDate: URIRef =  
rdflib.term.URIRef('https://schema.org/scheduledPaymentDate')  
  
scheduledTime: URIRef = rdflib.term.URIRef('https://schema.org/scheduledTime')  
  
schemaVersion: URIRef = rdflib.term.URIRef('https://schema.org/schemaVersion')  
  
schoolClosuresInfo: URIRef =  
rdflib.term.URIRef('https://schema.org/schoolClosuresInfo')  
  
screenCount: URIRef = rdflib.term.URIRef('https://schema.org/screenCount')  
  
screenshot: URIRef = rdflib.term.URIRef('https://schema.org/screenshot')  
  
sdDatePublished: URIRef = rdflib.term.URIRef('https://schema.org/sdDatePublished')  
  
sdLicense: URIRef = rdflib.term.URIRef('https://schema.org/sdLicense')  
  
sdPublisher: URIRef = rdflib.term.URIRef('https://schema.org/sdPublisher')  
  
season: URIRef = rdflib.term.URIRef('https://schema.org/season')  
  
seasonNumber: URIRef = rdflib.term.URIRef('https://schema.org/seasonNumber')  
  
seasons: URIRef = rdflib.term.URIRef('https://schema.org/seasons')  
  
seatNumber: URIRef = rdflib.term.URIRef('https://schema.org/seatNumber')  
  
seatRow: URIRef = rdflib.term.URIRef('https://schema.org/seatRow')  
  
seatSection: URIRef = rdflib.term.URIRef('https://schema.org/seatSection')  
  
seatingCapacity: URIRef = rdflib.term.URIRef('https://schema.org/seatingCapacity')  
  
seatingType: URIRef = rdflib.term.URIRef('https://schema.org/seatingType')  
  
secondaryPrevention: URIRef =  
rdflib.term.URIRef('https://schema.org/secondaryPrevention')  
  
securityClearanceRequirement: URIRef =  
rdflib.term.URIRef('https://schema.org/securityClearanceRequirement')
```

```
securityScreening: URIRef =  
rdflib.term.URIRef('https://schema.org/securityScreening')  
  
seeks: URIRef = rdflib.term.URIRef('https://schema.org/seeks')  
  
seller: URIRef = rdflib.term.URIRef('https://schema.org/seller')  
  
sender: URIRef = rdflib.term.URIRef('https://schema.org/sender')  
  
sensoryRequirement: URIRef =  
rdflib.term.URIRef('https://schema.org/sensoryRequirement')  
  
sensoryUnit: URIRef = rdflib.term.URIRef('https://schema.org/sensoryUnit')  
  
serialNumber: URIRef = rdflib.term.URIRef('https://schema.org/serialNumber')  
  
seriousAdverseOutcome: URIRef =  
rdflib.term.URIRef('https://schema.org/seriousAdverseOutcome')  
  
serverStatus: URIRef = rdflib.term.URIRef('https://schema.org/serverStatus')  
  
servesCuisine: URIRef = rdflib.term.URIRef('https://schema.org/servesCuisine')  
  
serviceArea: URIRef = rdflib.term.URIRef('https://schema.org/serviceArea')  
  
serviceAudience: URIRef = rdflib.term.URIRef('https://schema.org/serviceAudience')  
  
serviceLocation: URIRef = rdflib.term.URIRef('https://schema.org/serviceLocation')  
  
serviceOperator: URIRef = rdflib.term.URIRef('https://schema.org/serviceOperator')  
  
serviceOutput: URIRef = rdflib.term.URIRef('https://schema.org/serviceOutput')  
  
servicePhone: URIRef = rdflib.term.URIRef('https://schema.org/servicePhone')  
  
servicePostalAddress: URIRef =  
rdflib.term.URIRef('https://schema.org/servicePostalAddress')  
  
serviceSmsNumber: URIRef =  
rdflib.term.URIRef('https://schema.org/serviceSmsNumber')  
  
serviceType: URIRef = rdflib.term.URIRef('https://schema.org/serviceType')  
  
serviceUrl: URIRef = rdflib.term.URIRef('https://schema.org/serviceUrl')  
  
servingSize: URIRef = rdflib.term.URIRef('https://schema.org/servingSize')  
  
sha256: URIRef = rdflib.term.URIRef('https://schema.org/sha256')  
  
sharedContent: URIRef = rdflib.term.URIRef('https://schema.org/sharedContent')  
  
shippingDestination: URIRef =  
rdflib.term.URIRef('https://schema.org/shippingDestination')  
  
shippingDetails: URIRef = rdflib.term.URIRef('https://schema.org/shippingDetails')  
  
shippingLabel: URIRef = rdflib.term.URIRef('https://schema.org/shippingLabel')  
  
shippingRate: URIRef = rdflib.term.URIRef('https://schema.org/shippingRate')
```

```

shippingSettingsLink: URIRef =
rdflib.term.URIRef('https://schema.org/shippingSettingsLink')

sibling: URIRef = rdflib.term.URIRef('https://schema.org/sibling')

siblings: URIRef = rdflib.term.URIRef('https://schema.org/siblings')

signDetected: URIRef = rdflib.term.URIRef('https://schema.org/signDetected')

signOrSymptom: URIRef = rdflib.term.URIRef('https://schema.org/signOrSymptom')

significance: URIRef = rdflib.term.URIRef('https://schema.org/significance')

significantLink: URIRef = rdflib.term.URIRef('https://schema.org/significantLink')

significantLinks: URIRef =
rdflib.term.URIRef('https://schema.org/significantLinks')

size: URIRef = rdflib.term.URIRef('https://schema.org/size')

sizeGroup: URIRef = rdflib.term.URIRef('https://schema.org/sizeGroup')

sizeSystem: URIRef = rdflib.term.URIRef('https://schema.org/sizeSystem')

skills: URIRef = rdflib.term.URIRef('https://schema.org/skills')

sku: URIRef = rdflib.term.URIRef('https://schema.org/sku')

slogan: URIRef = rdflib.term.URIRef('https://schema.org/slogan')

smiles: URIRef = rdflib.term.URIRef('https://schema.org/smiles')

smokingAllowed: URIRef = rdflib.term.URIRef('https://schema.org/smokingAllowed')

sodiumContent: URIRef = rdflib.term.URIRef('https://schema.org/sodiumContent')

softwareAddOn: URIRef = rdflib.term.URIRef('https://schema.org/softwareAddOn')

softwareHelp: URIRef = rdflib.term.URIRef('https://schema.org/softwareHelp')

softwareRequirements: URIRef =
rdflib.term.URIRef('https://schema.org/softwareRequirements')

softwareVersion: URIRef = rdflib.term.URIRef('https://schema.org/softwareVersion')

sourceOrganization: URIRef =
rdflib.term.URIRef('https://schema.org/sourceOrganization')

sourcedFrom: URIRef = rdflib.term.URIRef('https://schema.org/sourcedFrom')

spatial: URIRef = rdflib.term.URIRef('https://schema.org/spatial')

spatialCoverage: URIRef = rdflib.term.URIRef('https://schema.org/spatialCoverage')

speakable: URIRef = rdflib.term.URIRef('https://schema.org/speakable')

specialCommitments: URIRef =
rdflib.term.URIRef('https://schema.org/specialCommitments')

```

```

specialOpeningHoursSpecification: URIRef =
rdflib.term.URIRef('https://schema.org/specialOpeningHoursSpecification')

specialty: URIRef = rdflib.term.URIRef('https://schema.org/specialty')

speechToTextMarkup: URIRef =
rdflib.term.URIRef('https://schema.org/speechToTextMarkup')

speed: URIRef = rdflib.term.URIRef('https://schema.org/speed')

spokenByCharacter: URIRef =
rdflib.term.URIRef('https://schema.org/spokenByCharacter')

sponsor: URIRef = rdflib.term.URIRef('https://schema.org/sponsor')

sport: URIRef = rdflib.term.URIRef('https://schema.org/sport')

sportsActivityLocation: URIRef =
rdflib.term.URIRef('https://schema.org/sportsActivityLocation')

sportsEvent: URIRef = rdflib.term.URIRef('https://schema.org/sportsEvent')

sportsTeam: URIRef = rdflib.term.URIRef('https://schema.org/sportsTeam')

spouse: URIRef = rdflib.term.URIRef('https://schema.org/spouse')

stage: URIRef = rdflib.term.URIRef('https://schema.org/stage')

stageAsNumber: URIRef = rdflib.term.URIRef('https://schema.org/stageAsNumber')

starRating: URIRef = rdflib.term.URIRef('https://schema.org/starRating')

startDate: URIRef = rdflib.term.URIRef('https://schema.org/startDate')

startOffset: URIRef = rdflib.term.URIRef('https://schema.org/startOffset')

startTime: URIRef = rdflib.term.URIRef('https://schema.org/startTime')

status: URIRef = rdflib.term.URIRef('https://schema.org/status')

steeringPosition: URIRef =
rdflib.term.URIRef('https://schema.org/steeringPosition')

step: URIRef = rdflib.term.URIRef('https://schema.org/step')

stepValue: URIRef = rdflib.term.URIRef('https://schema.org/stepValue')

steps: URIRef = rdflib.term.URIRef('https://schema.org/steps')

storageRequirements: URIRef =
rdflib.term.URIRef('https://schema.org/storageRequirements')

streetAddress: URIRef = rdflib.term.URIRef('https://schema.org/streetAddress')

strengthUnit: URIRef = rdflib.term.URIRef('https://schema.org/strengthUnit')

strengthValue: URIRef = rdflib.term.URIRef('https://schema.org/strengthValue')

structuralClass: URIRef = rdflib.term.URIRef('https://schema.org/structuralClass')

```

```
study: URIRef = rdflib.term.URIRef('https://schema.org/study')
studyDesign: URIRef = rdflib.term.URIRef('https://schema.org/studyDesign')
studyLocation: URIRef = rdflib.term.URIRef('https://schema.org/studyLocation')
studySubject: URIRef = rdflib.term.URIRef('https://schema.org/studySubject')
subEvent: URIRef = rdflib.term.URIRef('https://schema.org/subEvent')
subEvents: URIRef = rdflib.term.URIRef('https://schema.org/subEvents')
subOrganization: URIRef = rdflib.term.URIRef('https://schema.org/subOrganization')
subReservation: URIRef = rdflib.term.URIRef('https://schema.org/subReservation')
subStageSuffix: URIRef = rdflib.term.URIRef('https://schema.org/subStageSuffix')
subStructure: URIRef = rdflib.term.URIRef('https://schema.org/subStructure')
subTest: URIRef = rdflib.term.URIRef('https://schema.org/subTest')
subTrip: URIRef = rdflib.term.URIRef('https://schema.org/subTrip')
subjectOf: URIRef = rdflib.term.URIRef('https://schema.org/subjectOf')
subtitleLanguage: URIRef =
rdflib.term.URIRef('https://schema.org/subtitleLanguage')
successorOf: URIRef = rdflib.term.URIRef('https://schema.org/successorOf')
sugarContent: URIRef = rdflib.term.URIRef('https://schema.org/sugarContent')
suggestedAge: URIRef = rdflib.term.URIRef('https://schema.org/suggestedAge')
suggestedAnswer: URIRef = rdflib.term.URIRef('https://schema.org/suggestedAnswer')
suggestedGender: URIRef = rdflib.term.URIRef('https://schema.org/suggestedGender')
suggestedMaxAge: URIRef = rdflib.term.URIRef('https://schema.org/suggestedMaxAge')
suggestedMeasurement: URIRef =
rdflib.term.URIRef('https://schema.org/suggestedMeasurement')
suggestedMinAge: URIRef = rdflib.term.URIRef('https://schema.org/suggestedMinAge')
suitableForDiet: URIRef = rdflib.term.URIRef('https://schema.org/suitableForDiet')
superEvent: URIRef = rdflib.term.URIRef('https://schema.org/superEvent')
supersededBy: URIRef = rdflib.term.URIRef('https://schema.org/supersededBy')
supply: URIRef = rdflib.term.URIRef('https://schema.org/supply')
supplyTo: URIRef = rdflib.term.URIRef('https://schema.org/supplyTo')
supportingData: URIRef = rdflib.term.URIRef('https://schema.org/supportingData')
surface: URIRef = rdflib.term.URIRef('https://schema.org/surface')
```



```
target: URIRef = rdflib.term.URIRef('https://schema.org/target')

targetCollection: URIRef =
rdflib.term.URIRef('https://schema.org/targetCollection')

targetDescription: URIRef =
rdflib.term.URIRef('https://schema.org/targetDescription')

targetName: URIRef = rdflib.term.URIRef('https://schema.org/targetName')

targetPlatform: URIRef = rdflib.term.URIRef('https://schema.org/targetPlatform')

targetPopulation: URIRef =
rdflib.term.URIRef('https://schema.org/targetPopulation')

targetProduct: URIRef = rdflib.term.URIRef('https://schema.org/targetProduct')

targetUrl: URIRef = rdflib.term.URIRef('https://schema.org/targetUrl')

taxID: URIRef = rdflib.term.URIRef('https://schema.org/taxID')

taxonRank: URIRef = rdflib.term.URIRef('https://schema.org/taxonRank')

taxonomicRange: URIRef = rdflib.term.URIRef('https://schema.org/taxonomicRange')

teaches: URIRef = rdflib.term.URIRef('https://schema.org/teaches')

telephone: URIRef = rdflib.term.URIRef('https://schema.org/telephone')

temporal: URIRef = rdflib.term.URIRef('https://schema.org/temporal')

temporalCoverage: URIRef =
rdflib.term.URIRef('https://schema.org/temporalCoverage')

termCode: URIRef = rdflib.term.URIRef('https://schema.org/termCode')

termDuration: URIRef = rdflib.term.URIRef('https://schema.org/termDuration')

termsOfService: URIRef = rdflib.term.URIRef('https://schema.org/termsOfService')

termsPerYear: URIRef = rdflib.term.URIRef('https://schema.org/termsPerYear')

text: URIRef = rdflib.term.URIRef('https://schema.org/text')

textValue: URIRef = rdflib.term.URIRef('https://schema.org/textValue')

thumbnail: URIRef = rdflib.term.URIRef('https://schema.org/thumbnail')

thumbnailUrl: URIRef = rdflib.term.URIRef('https://schema.org/thumbnailUrl')

tickerSymbol: URIRef = rdflib.term.URIRef('https://schema.org/tickerSymbol')

ticketNumber: URIRef = rdflib.term.URIRef('https://schema.org/ticketNumber')

ticketToken: URIRef = rdflib.term.URIRef('https://schema.org/ticketToken')

ticketedSeat: URIRef = rdflib.term.URIRef('https://schema.org/ticketedSeat')

timeOfDay: URIRef = rdflib.term.URIRef('https://schema.org/timeOfDay')
```



```
timeRequired: URIRef = rdflib.term.URIRef('https://schema.org/timeRequired')
timeToComplete: URIRef = rdflib.term.URIRef('https://schema.org/timeToComplete')
tissueSample: URIRef = rdflib.term.URIRef('https://schema.org/tissueSample')
title: URIRef = rdflib.term.URIRef('https://schema.org/title')
titleEIDR: URIRef = rdflib.term.URIRef('https://schema.org/titleEIDR')
toLocation: URIRef = rdflib.term.URIRef('https://schema.org/toLocation')
toRecipient: URIRef = rdflib.term.URIRef('https://schema.org/toRecipient')
tocContinuation: URIRef = rdflib.term.URIRef('https://schema.org/tocContinuation')
tocEntry: URIRef = rdflib.term.URIRef('https://schema.org/tocEntry')
tongueWeight: URIRef = rdflib.term.URIRef('https://schema.org/tongueWeight')
tool: URIRef = rdflib.term.URIRef('https://schema.org/tool')
torque: URIRef = rdflib.term.URIRef('https://schema.org/torque')
totalJobOpenings: URIRef =  
rdflib.term.URIRef('https://schema.org/totalJobOpenings')
totalPaymentDue: URIRef = rdflib.term.URIRef('https://schema.org/totalPaymentDue')
totalPrice: URIRef = rdflib.term.URIRef('https://schema.org/totalPrice')
totalTime: URIRef = rdflib.term.URIRef('https://schema.org/totalTime')
tourBookingPage: URIRef = rdflib.term.URIRef('https://schema.org/tourBookingPage')
touristType: URIRef = rdflib.term.URIRef('https://schema.org/touristType')
track: URIRef = rdflib.term.URIRef('https://schema.org/track')
trackingNumber: URIRef = rdflib.term.URIRef('https://schema.org/trackingNumber')
trackingUrl: URIRef = rdflib.term.URIRef('https://schema.org/trackingUrl')
tracks: URIRef = rdflib.term.URIRef('https://schema.org/tracks')
trailer: URIRef = rdflib.term.URIRef('https://schema.org/trailer')
trailerWeight: URIRef = rdflib.term.URIRef('https://schema.org/trailerWeight')
trainName: URIRef = rdflib.term.URIRef('https://schema.org/trainName')
trainNumber: URIRef = rdflib.term.URIRef('https://schema.org/trainNumber')
trainingSalary: URIRef = rdflib.term.URIRef('https://schema.org/trainingSalary')
transFatContent: URIRef = rdflib.term.URIRef('https://schema.org/transFatContent')
transcript: URIRef = rdflib.term.URIRef('https://schema.org/transcript')
transitTime: URIRef = rdflib.term.URIRef('https://schema.org/transitTime')
```

```
transitTimeLabel: URIRef =  
rdflib.term.URIRef('https://schema.org/transitTimeLabel')  
  
translationOfWork: URIRef =  
rdflib.term.URIRef('https://schema.org/translationOfWork')  
  
translator: URIRef = rdflib.term.URIRef('https://schema.org/translator')  
  
transmissionMethod: URIRef =  
rdflib.term.URIRef('https://schema.org/transmissionMethod')  
  
travelBans: URIRef = rdflib.term.URIRef('https://schema.org/travelBans')  
  
trialDesign: URIRef = rdflib.term.URIRef('https://schema.org/trialDesign')  
  
tributary: URIRef = rdflib.term.URIRef('https://schema.org/tributary')  
  
typeOfBed: URIRef = rdflib.term.URIRef('https://schema.org/typeOfBed')  
  
typeOfGood: URIRef = rdflib.term.URIRef('https://schema.org/typeOfGood')  
  
typicalAgeRange: URIRef = rdflib.term.URIRef('https://schema.org/typicalAgeRange')  
  
typicalCreditsPerTerm: URIRef =  
rdflib.term.URIRef('https://schema.org/typicalCreditsPerTerm')  
  
typicalTest: URIRef = rdflib.term.URIRef('https://schema.org/typicalTest')  
  
underName: URIRef = rdflib.term.URIRef('https://schema.org/underName')  
  
unitCode: URIRef = rdflib.term.URIRef('https://schema.org/unitCode')  
  
unitText: URIRef = rdflib.term.URIRef('https://schema.org/unitText')  
  
unnamedSourcesPolicy: URIRef =  
rdflib.term.URIRef('https://schema.org/unnamedSourcesPolicy')  
  
unsaturatedFatContent: URIRef =  
rdflib.term.URIRef('https://schema.org/unsaturatedFatContent')  
  
uploadDate: URIRef = rdflib.term.URIRef('https://schema.org/uploadDate')  
  
upvoteCount: URIRef = rdflib.term.URIRef('https://schema.org/upvoteCount')  
  
url: URIRef = rdflib.term.URIRef('https://schema.org/url')  
  
urlTemplate: URIRef = rdflib.term.URIRef('https://schema.org/urlTemplate')  
  
usageInfo: URIRef = rdflib.term.URIRef('https://schema.org/usageInfo')  
  
usedToDiagnose: URIRef = rdflib.term.URIRef('https://schema.org/usedToDiagnose')  
  
userInteractionCount: URIRef =  
rdflib.term.URIRef('https://schema.org/userInteractionCount')  
  
usesDevice: URIRef = rdflib.term.URIRef('https://schema.org/usesDevice')  
  
usesHealthPlanIdStandard: URIRef =  
rdflib.term.URIRef('https://schema.org/usesHealthPlanIdStandard')
```

```
utterances: URIRef = rdflib.term.URIRef('https://schema.org/utterances')
validFor: URIRef = rdflib.term.URIRef('https://schema.org/validFor')
validFrom: URIRef = rdflib.term.URIRef('https://schema.org/validFrom')
validIn: URIRef = rdflib.term.URIRef('https://schema.org/validIn')
validThrough: URIRef = rdflib.term.URIRef('https://schema.org/validThrough')
validUntil: URIRef = rdflib.term.URIRef('https://schema.org/validUntil')
value: URIRef = rdflib.term.URIRef('https://schema.org/value')
valueAddedTaxIncluded: URIRef =
rdflib.term.URIRef('https://schema.org/valueAddedTaxIncluded')
valueMaxLength: URIRef = rdflib.term.URIRef('https://schema.org/valueMaxLength')
valueMinLength: URIRef = rdflib.term.URIRef('https://schema.org/valueMinLength')
valueName: URIRef = rdflib.term.URIRef('https://schema.org/valueName')
valuePattern: URIRef = rdflib.term.URIRef('https://schema.org/valuePattern')
valueReference: URIRef = rdflib.term.URIRef('https://schema.org/valueReference')
valueRequired: URIRef = rdflib.term.URIRef('https://schema.org/valueRequired')
variableMeasured: URIRef =
rdflib.term.URIRef('https://schema.org/variableMeasured')
variantCover: URIRef = rdflib.term.URIRef('https://schema.org/variantCover')
variesBy: URIRef = rdflib.term.URIRef('https://schema.org/variesBy')
vatID: URIRef = rdflib.term.URIRef('https://schema.org/vatID')
vehicleConfiguration: URIRef =
rdflib.term.URIRef('https://schema.org/vehicleConfiguration')
vehicleEngine: URIRef = rdflib.term.URIRef('https://schema.org/vehicleEngine')
vehicleIdentificationNumber: URIRef =
rdflib.term.URIRef('https://schema.org/vehicleIdentificationNumber')
vehicleInteriorColor: URIRef =
rdflib.term.URIRef('https://schema.org/vehicleInteriorColor')
vehicleInteriorType: URIRef =
rdflib.term.URIRef('https://schema.org/vehicleInteriorType')
vehicleModelDate: URIRef =
rdflib.term.URIRef('https://schema.org/vehicleModelDate')
vehicleSeatingCapacity: URIRef =
rdflib.term.URIRef('https://schema.org/vehicleSeatingCapacity')
```

```
vehicleSpecialUsage: URIRef =  
rdflib.term.URIRef('https://schema.org/vehicleSpecialUsage')  
  
vehicleTransmission: URIRef =  
rdflib.term.URIRef('https://schema.org/vehicleTransmission')  
  
vendor: URIRef = rdflib.term.URIRef('https://schema.org/vendor')  
  
verificationFactCheckingPolicy: URIRef =  
rdflib.term.URIRef('https://schema.org/verificationFactCheckingPolicy')  
  
version: URIRef = rdflib.term.URIRef('https://schema.org/version')  
  
video: URIRef = rdflib.term.URIRef('https://schema.org/video')  
  
videoFormat: URIRef = rdflib.term.URIRef('https://schema.org/videoFormat')  
  
videoFrameSize: URIRef = rdflib.term.URIRef('https://schema.org/videoFrameSize')  
  
videoQuality: URIRef = rdflib.term.URIRef('https://schema.org/videoQuality')  
  
volumeNumber: URIRef = rdflib.term.URIRef('https://schema.org/volumeNumber')  
  
warning: URIRef = rdflib.term.URIRef('https://schema.org/warning')  
  
warranty: URIRef = rdflib.term.URIRef('https://schema.org/warranty')  
  
warrantyPromise: URIRef = rdflib.term.URIRef('https://schema.org/warrantyPromise')  
  
warrantyScope: URIRef = rdflib.term.URIRef('https://schema.org/warrantyScope')  
  
webCheckinTime: URIRef = rdflib.term.URIRef('https://schema.org/webCheckinTime')  
  
webFeed: URIRef = rdflib.term.URIRef('https://schema.org/webFeed')  
  
weight: URIRef = rdflib.term.URIRef('https://schema.org/weight')  
  
weightTotal: URIRef = rdflib.term.URIRef('https://schema.org/weightTotal')  
  
wheelbase: URIRef = rdflib.term.URIRef('https://schema.org/wheelbase')  
  
width: URIRef = rdflib.term.URIRef('https://schema.org/width')  
  
winner: URIRef = rdflib.term.URIRef('https://schema.org/winner')  
  
wordCount: URIRef = rdflib.term.URIRef('https://schema.org/wordCount')  
  
workExample: URIRef = rdflib.term.URIRef('https://schema.org/workExample')  
  
workFeatured: URIRef = rdflib.term.URIRef('https://schema.org/workFeatured')  
  
workHours: URIRef = rdflib.term.URIRef('https://schema.org/workHours')  
  
workLocation: URIRef = rdflib.term.URIRef('https://schema.org/workLocation')  
  
workPerformed: URIRef = rdflib.term.URIRef('https://schema.org/workPerformed')  
  
workPresented: URIRef = rdflib.term.URIRef('https://schema.org/workPresented')  
  
workTranslation: URIRef = rdflib.term.URIRef('https://schema.org/workTranslation')
```

```

workload: URIRef = rdflib.term.URIRef('https://schema.org/workload')
worksFor: URIRef = rdflib.term.URIRef('https://schema.org/worksFor')
worstRating: URIRef = rdflib.term.URIRef('https://schema.org/worstRating')
xpath: URIRef = rdflib.term.URIRef('https://schema.org/xpath')
yearBuilt: URIRef = rdflib.term.URIRef('https://schema.org/yearBuilt')
yearlyRevenue: URIRef = rdflib.term.URIRef('https://schema.org/yearlyRevenue')
yearsInOperation: URIRef =
rdflib.term.URIRef('https://schema.org/yearsInOperation')

```

```
class rdflib.namespace.SH
```

```
    Bases: DefinedNamespace
```

```
    W3C Shapes Constraint Language (SHACL) Vocabulary
```

```
    This vocabulary defines terms used in SHACL, the W3C Shapes Constraint Language.
```

```
    Generated from: https://www.w3.org/ns/shacl.ttl Date: 2020-05-26 14:20:08.041103
```

```

AbstractResult: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#AbstractResult')

```

```

AndConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#AndConstraintComponent')

```

```
BlankNode: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#BlankNode')
```

```

BlankNodeOrIRI: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#BlankNodeOrIRI')

```

```

BlankNodeOrLiteral: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#BlankNodeOrLiteral')

```

```

ClassConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ClassConstraintComponent')

```

```

ClosedConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ClosedConstraintComponent')

```

```

ConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ConstraintComponent')

```

```

DatatypeConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#DatatypeConstraintComponent')

```

```

DisjointConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#DisjointConstraintComponent')

```

```

EqualsConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#EqualsConstraintComponent')

```

```

ExpressionConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ExpressionConstraintComponent')

```

```
Function: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Function')

HasValueConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#HasValueConstraintComponent')

IRI: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#IRI')

IRIOrLiteral: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#IRIOrLiteral')

InConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#InConstraintComponent')

Info: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Info')

JSConstraint: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSConstraint')

JSConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSConstraintComponent')

JSExecutable: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSExecutable')

JSFunction: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSFunction')

JSLibrary: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSLibrary')

JSRule: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSRule')

JSTarget: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSTarget')

JSTargetType: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSTargetType')

JSValidator: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#JSValidator')

LanguageInConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#LanguageInConstraintComponent')

LessThanConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#LessThanConstraintComponent')

LessThanOrEqualsConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#LessThanOrEqualsConstraintComponent')

Literal: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Literal')

MaxCountConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MaxCountConstraintComponent')

MaxExclusiveConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MaxExclusiveConstraintComponent')

MaxInclusiveConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MaxInclusiveConstraintComponent')
```

```
MaxLengthConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MaxLengthConstraintComponent')  
  
MinCountConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MinCountConstraintComponent')  
  
MinExclusiveConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MinExclusiveConstraintComponent')  
  
MinInclusiveConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MinInclusiveConstraintComponent')  
  
MinLengthConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#MinLengthConstraintComponent')  
  
NodeConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#NodeConstraintComponent')  
  
NodeKind: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#NodeKind')  
  
NodeKindConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#NodeKindConstraintComponent')  
  
NodeShape: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#NodeShape')  
  
NotConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#NotConstraintComponent')  
  
OrConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#OrConstraintComponent')  
  
Parameter: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Parameter')  
  
Parameterizable: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#Parameterizable')  
  
PatternConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#PatternConstraintComponent')  
  
PrefixDeclaration: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#PrefixDeclaration')  
  
PropertyConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#PropertyConstraintComponent')  
  
PropertyGroup: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#PropertyGroup')  
  
PropertyShape: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#PropertyShape')  
  
QualifiedMaxCountConstraintComponent: URIRef = rdflib.term.URIRef('http://www.w3.  
org/ns/shacl#QualifiedMaxCountConstraintComponent')  
  
QualifiedMinCountConstraintComponent: URIRef = rdflib.term.URIRef('http://www.w3.  
org/ns/shacl#QualifiedMinCountConstraintComponent')
```



```
ResultAnnotation: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ResultAnnotation')  
  
Rule: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Rule')  
  
SPARQLAskExecutable: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLAskExecutable')  
  
SPARQLAskValidator: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLAskValidator')  
  
SPARQLConstraint: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLConstraint')  
  
SPARQLConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLConstraintComponent')  
  
SPARQLConstructExecutable: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLConstructExecutable')  
  
SPARQLExecutable: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLExecutable')  
  
SPARQLFunction: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLFunction')  
  
SPARQLRule: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLRule')  
  
SPARQLSelectExecutable: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLSelectExecutable')  
  
SPARQLSelectValidator: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLSelectValidator')  
  
SPARQLTarget: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLTarget')  
  
SPARQLTargetType: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLTargetType')  
  
SPARQLUpdateExecutable: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#SPARQLUpdateExecutable')  
  
Severity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Severity')  
  
Shape: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Shape')  
  
Target: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Target')  
  
TargetType: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#TargetType')  
  
TripleRule: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#TripleRule')  
  
UniqueLangConstraintComponent: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#UniqueLangConstraintComponent')  
  
ValidationReport: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ValidationReport')
```



```

ValidationResult: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ValidationResult')

Validator: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Validator')

Violation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Violation')

Warning: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#Warning')

XoneConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#XoneConstraintComponent')

alternativePath: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#alternativePath')

annotationProperty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#annotationProperty')

annotationValue: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#annotationValue')

annotationVarName: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#annotationVarName')

ask: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#ask')

closed: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#closed')

condition: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#condition')

conforms: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#conforms')

construct: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#construct')

datatype: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#datatype')

deactivated: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#deactivated')

declare: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#declare')

defaultValue: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#defaultValue')

description: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#description')

detail: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#detail')

disjoint: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#disjoint')

entailment: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#entailment')

equals: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#equals')

expression: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#expression')

filterShape: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#filterShape')

flags: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#flags')

```

```
focusNode: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#focusNode')
group: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#group')
hasValue: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#hasValue')
ignoredProperties: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#ignoredProperties')
intersection: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#intersection')
inversePath: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#inversePath')
js: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#js')
jsFunctionName: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#jsFunctionName')
jsLibrary: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#jsLibrary')
jsLibraryURL: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#jsLibraryURL')
labelTemplate: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#labelTemplate')
languageIn: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#languageIn')
lessThan: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#lessThan')
lessThanOrEquals: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#lessThanOrEquals')
maxCount: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#maxCount')
maxExclusive: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#maxExclusive')
maxInclusive: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#maxInclusive')
maxLength: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#maxLength')
message: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#message')
minCount: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#minCount')
minExclusive: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#minExclusive')
minInclusive: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#minInclusive')
minLength: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#minLength')
name: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#name')
namespace: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#namespace')
```

```

node: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#node')

nodeKind: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#nodeKind')

nodeValidator: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#nodeValidator')

nodes: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#nodes')

object: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#object')

oneOrMorePath: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#oneOrMorePath')

optional: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#optional')

order: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#order')

parameter: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#parameter')

path: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#path')

pattern: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#pattern')

predicate: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#predicate')

prefix: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#prefix')

prefixes: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#prefixes')

property: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#property')

propertyValidator: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#propertyValidator')

qualifiedMaxCount: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#qualifiedMaxCount')

qualifiedMinCount: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#qualifiedMinCount')

qualifiedValueShape: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#qualifiedValueShape')

qualifiedValueShapesDisjoint: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#qualifiedValueShapesDisjoint')

result: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#result')

resultAnnotation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#resultAnnotation')

resultMessage: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#resultMessage')

resultPath: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#resultPath')

resultSeverity: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#resultSeverity')

```

```
returnType: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#returnType')
rule: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#rule')
select: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#select')
severity: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#severity')
shapesGraph: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#shapesGraph')
shapesGraphWellFormed: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#shapesGraphWellFormed')
sourceConstraint: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#sourceConstraint')
sourceConstraintComponent: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#sourceConstraintComponent')
sourceShape: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#sourceShape')
sparql: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#sparql')
subject: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#subject')
suggestedShapesGraph: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#suggestedShapesGraph')
target: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#target')
targetClass: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#targetClass')
targetNode: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#targetNode')
targetObjectsOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#targetObjectsOf')
targetSubjectsOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#targetSubjectsOf')
this: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#this')
union: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#union')
uniqueLang: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#uniqueLang')
update: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#update')
validator: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#validator')
value: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#value')
xone: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/shacl#xone')
zeroOrMorePath: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#zeroOrMorePath')
zeroOrOnePath: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/shacl#zeroOrOnePath')
```

```
class rdflib.namespace.SKOS
```

Bases: *DefinedNamespace*

SKOS Vocabulary

An RDF vocabulary for describing the basic structure and content of concept schemes such as thesauri, classification schemes, subject heading lists, taxonomies, ‘folksonomies’, other types of controlled vocabulary, and also concept schemes embedded in glossaries and terminologies.

Generated from: <https://www.w3.org/2009/08/skos-reference/skos.rdf> Date: 2020-05-26 14:20:08.489187

Collection: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#Collection')
```

Concept: *URIRef* = `rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#Concept')`

ConceptScheme: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#ConceptScheme')
```

OrderedCollection: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#OrderedCollection')
```

altLabel: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#altLabel')
```

broadMatch: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#broadMatch')
```

broader: *URIRef* = `rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#broader')`

broaderTransitive: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#broaderTransitive')
```

changeNote: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#changeNote')
```

closeMatch: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#closeMatch')
```

definition: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#definition')
```

editorialNote: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#editorialNote')
```

exactMatch: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#exactMatch')
```

example: *URIRef* = `rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#example')`

hasTopConcept: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#hasTopConcept')
```

hiddenLabel: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#hiddenLabel')
```

historyNote: *URIRef* =

```
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#historyNote')
```

```
inScheme: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#inScheme')

mappingRelation: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#mappingRelation')

member: URIRef = rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#member')

memberList: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#memberList')

narrowMatch: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#narrowMatch')

narrower: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#narrower')

narrowerTransitive: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#narrowerTransitive')

notation: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#notation')

note: URIRef = rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#note')

prefLabel: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#prefLabel')

related: URIRef = rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#related')

relatedMatch: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#relatedMatch')

scopeNote: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#scopeNote')

semanticRelation: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#semanticRelation')

topConceptOf: URIRef =
rdflib.term.URIRef('http://www.w3.org/2004/02/skos/core#topConceptOf')
```

```
class rdflib.namespace.SOSA
```

```
    Bases: DefinedNamespace
```

```
    Sensor, Observation, Sample, and Actuator (SOSA) Ontology
```

```
    This ontology is based on the SSN Ontology by the W3C Semantic Sensor Networks Incubator Group (SSN-XG),
    together with considerations from the W3C/OGC Spatial Data on the Web Working Group.
```

```
    Generated from: http://www.w3.org/ns/sosa/ Date: 2020-05-26 14:20:08.792504
```

```
    ActuableProperty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/sosa/ActuableProperty')
```

```
    Actuation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Actuation')
```

```
    Actuator: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Actuator')
```

```
FeatureOfInterest: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/FeatureOfInterest')  
  
ObservableProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/ObservableProperty')  
  
Observation: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Observation')  
  
Platform: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Platform')  
  
Procedure: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Procedure')  
  
Result: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Result')  
  
Sample: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Sample')  
  
Sampler: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Sampler')  
  
Sampling: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Sampling')  
  
Sensor: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/Sensor')  
  
actsOnProperty: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/actsOnProperty')  
  
hasFeatureOfInterest: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/hasFeatureOfInterest')  
  
hasResult: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/hasResult')  
  
hasSample: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/hasSample')  
  
hasSimpleResult: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/hasSimpleResult')  
  
hosts: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/hosts')  
  
isActedOnBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/isActedOnBy')  
  
isFeatureOfInterestOf: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/isFeatureOfInterestOf')  
  
isHostedBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/isHostedBy')  
  
isObservedBy: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/isObservedBy')  
  
isResultOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/isResultOf')  
  
isSampleOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/isSampleOf')  
  
madeActuation: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/madeActuation')  
  
madeByActuator: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/madeByActuator')  
  
madeBySampler: URIRef =  
rdflib.term.URIRef('http://www.w3.org/ns/sosa/madeBySampler')
```



```
madeBySensor: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/madeBySensor')

madeObservation: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/sosa/madeObservation')

madeSampling: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/madeSampling')

observedProperty: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/sosa/observedProperty')

observes: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/observes')

phenomenonTime: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/sosa/phenomenonTime')

resultTime: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/sosa/resultTime')

usedProcedure: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/sosa/usedProcedure')
```

```
class rdflib.namespace.SSN
```

```
    Bases: DefinedNamespace
```

```
    Semantic Sensor Network Ontology
```

This ontology describes sensors, actuators and observations, and related concepts. It does not describe domain concepts, time, locations, etc. these are intended to be included from other ontologies via OWL imports.

Generated from: <http://www.w3.org/ns/ssn/> Date: 2020-05-26 14:20:09.068204

```
Deployment: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/Deployment')
```

```
Input: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/Input')
```

```
Output: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/Output')
```

```
Property: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/Property')
```

```
Stimulus: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/Stimulus')
```

```
System: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/System')
```

```
deployedOnPlatform: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/ssn/deployedOnPlatform')
```

```
deployedSystem: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/ssn/deployedSystem')
```

```
detects: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/detects')
```

```
forProperty: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/forProperty')
```

```
hasDeployment: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/ssn/hasDeployment')
```

```
hasInput: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/hasInput')
```

```
hasOutput: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/hasOutput')
```

```
hasProperty: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/hasProperty')
```



```

hasSubSystem: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/hasSubSystem')

implementedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/ssn/implementedBy')

implements: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/implements')

inDeployment: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/inDeployment')

isPropertyOf: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/isPropertyOf')

isProxyFor: URIRef = rdflib.term.URIRef('http://www.w3.org/ns/ssn/isProxyFor')

wasOriginatedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/ns/ssn/wasOriginatedBy')

class rdflib.namespace.TIME
    Bases: DefinedNamespace
    OWL-Time
    Generated from: http://www.w3.org/2006/time# Date: 2020-05-26 14:20:10.531265
    DateTimeDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#DateTimeDescription')

    DateTimeInterval: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#DateTimeInterval')

    DayOfWeek: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#DayOfWeek')

    Duration: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Duration')

    DurationDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#DurationDescription')

    Friday: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Friday')

    GeneralDateTimeDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#GeneralDateTimeDescription')

    GeneralDurationDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#GeneralDurationDescription')

    Instant: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Instant')

    Interval: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Interval')

    January: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#January')

    Monday: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Monday')

    MonthOfYear: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#MonthOfYear')

    ProperInterval: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#ProperInterval')

    Saturday: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Saturday')

```

```

Sunday: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Sunday')

TRS: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#TRS')

TemporalDuration: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#TemporalDuration')

TemporalEntity: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#TemporalEntity')

TemporalPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#TemporalPosition')

TemporalUnit: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#TemporalUnit')

Thursday: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Thursday')

TimePosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#TimePosition')

TimeZone: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#TimeZone')

Tuesday: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Tuesday')

Wednesday: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Wednesday')

Year: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#Year')

after: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#after')

before: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#before')

day: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#day')

dayOfWeek: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#dayOfWeek')

dayOfYear: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#dayOfYear')

days: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#days')

generalDay: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#generalDay')

generalMonth: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#generalMonth')

generalYear: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#generalYear')

hasBeginning: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#hasBeginning')

hasDateTimeDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#hasDateTimeDescription')

hasDuration: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#hasDuration')

hasDurationDescription: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#hasDurationDescription')

```

```
hasEnd: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#hasEnd')

hasTRS: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#hasTRS')

hasTemporalDuration: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#hasTemporalDuration')

hasTime: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#hasTime')

hasXSDDuration: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#hasXSDDuration')

hour: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#hour')

hours: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#hours')

inDateTime: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#inDateTime')

inTemporalPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#inTemporalPosition')

inTimePosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#inTimePosition')

inXSDDate: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#inXSDDate')

inXSDDateTime: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#inXSDDateTime')

inXSDDateTimeStamp: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#inXSDDateTimeStamp')

inXSDgYear: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#inXSDgYear')

inXSDgYearMonth: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#inXSDgYearMonth')

inside: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#inside')

intervalAfter: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalAfter')

intervalBefore: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalBefore')

intervalContains: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalContains')

intervalDisjoint: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalDisjoint')

intervalDuring: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalDuring')

intervalEquals: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalEquals')
```

```

intervalFinishedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalFinishedBy')

intervalFinishes: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalFinishes')

intervalIn: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#intervalIn')

intervalMeets: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalMeets')

intervalMetBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalMetBy')

intervalOverlappedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalOverlappedBy')

intervalOverlaps: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalOverlaps')

intervalStartedBy: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalStartedBy')

intervalStarts: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#intervalStarts')

minute: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#minute')

minutes: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#minutes')

month: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#month')

monthOfYear: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#monthOfYear')

months: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#months')

nominalPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#nominalPosition')

numericDuration: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#numericDuration')

numericPosition: URIRef =
rdflib.term.URIRef('http://www.w3.org/2006/time#numericPosition')

second: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#second')

seconds: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#seconds')

timeZone: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#timeZone')

unitDay: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitDay')

unitHour: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitHour')

unitMinute: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitMinute')

unitMonth: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitMonth')

```

```

unitSecond: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitSecond')
unitType: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitType')
unitWeek: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitWeek')
unitYear: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#unitYear')
week: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#week')
weeks: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#weeks')
xsdDateTime: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#xsdDateTime')
year: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#year')
years: URIRef = rdflib.term.URIRef('http://www.w3.org/2006/time#years')

```

```
class rdflib.namespace.VANN
```

Bases: *DefinedNamespace*

VANN: A vocabulary for annotating vocabulary descriptions

This document describes a vocabulary for annotating descriptions of vocabularies with examples and usage notes.

Generated from: <https://vocab.org/vann/vann-vocab-20100607.rdf> Date: 2020-05-26 14:21:15.580430

```
changes: URIRef = rdflib.term.URIRef('http://purl.org/vocab/vann/changes')
```

```
example: URIRef = rdflib.term.URIRef('http://purl.org/vocab/vann/example')
```

```
preferredNamespacePrefix: URIRef =
rdflib.term.URIRef('http://purl.org/vocab/vann/preferredNamespacePrefix')
```

```
preferredNamespaceUri: URIRef =
rdflib.term.URIRef('http://purl.org/vocab/vann/preferredNamespaceUri')
```

```
termGroup: URIRef = rdflib.term.URIRef('http://purl.org/vocab/vann/termGroup')
```

```
usageNote: URIRef = rdflib.term.URIRef('http://purl.org/vocab/vann/usageNote')
```

```
class rdflib.namespace.VOID
```

Bases: *DefinedNamespace*

Vocabulary of Interlinked Datasets (VoID)

The Vocabulary of Interlinked Datasets (VoID) is an RDF Schema vocabulary for expressing metadata about RDF datasets. It is intended as a bridge between the publishers and users of RDF data, with applications ranging from data discovery to cataloging and archiving of datasets. This document provides a formal definition of the new RDF classes and properties introduced for VoID. It is a companion to the main specification document for VoID, <http://www.w3.org/TR/void/> Describing Linked Datasets with the VoID Vocabulary.

Generated from: <http://rdfs.org/ns/void#> Date: 2020-05-26 14:20:11.911298

```
Dataset: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#Dataset')
```

```
DatasetDescription: URIRef =
rdflib.term.URIRef('http://rdfs.org/ns/void#DatasetDescription')
```

```
Linkset: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#Linkset')
```

```
TechnicalFeature: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#TechnicalFeature')  
  
classPartition: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#classPartition')  
  
classes: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#classes')  
  
dataDump: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#dataDump')  
  
distinctObjects: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#distinctObjects')  
  
distinctSubjects: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#distinctSubjects')  
  
documents: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#documents')  
  
entities: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#entities')  
  
exampleResource: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#exampleResource')  
  
feature: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#feature')  
  
inDataset: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#inDataset')  
  
linkPredicate: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#linkPredicate')  
  
objectsTarget: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#objectsTarget')  
  
openSearchDescription: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#openSearchDescription')  
  
properties: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#properties')  
  
property: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#property')  
  
propertyPartition: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#propertyPartition')  
  
rootResource: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#rootResource')  
  
sparqlEndpoint: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#sparqlEndpoint')  
  
subjectsTarget: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#subjectsTarget')  
  
subset: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#subset')  
  
target: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#target')  
  
triples: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#triples')  
  
uriLookupEndpoint: URIRef =  
rdflib.term.URIRef('http://rdfs.org/ns/void#uriLookupEndpoint')
```

```

uriRegexPattern: URIRef =
rdflib.term.URIRef('http://rdfs.org/ns/void#uriRegexPattern')

uriSpace: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#uriSpace')

vocabulary: URIRef = rdflib.term.URIRef('http://rdfs.org/ns/void#vocabulary')

class rdflib.namespace.WGS
    Bases: DefinedNamespace
    Basic Geo (WGS84 lat/long) Vocabulary
    The HTML Specification for the vocabulary can be found here <https://www.w3.org/2003/01/geo/>.
    Point: URIRef =
rdflib.term.URIRef('https://www.w3.org/2003/01/geo/wgs84_pos#Point')

    SpatialThing: URIRef =
rdflib.term.URIRef('https://www.w3.org/2003/01/geo/wgs84_pos#SpatialThing')

    alt: URIRef = rdflib.term.URIRef('https://www.w3.org/2003/01/geo/wgs84_pos#alt')

    lat: URIRef = rdflib.term.URIRef('https://www.w3.org/2003/01/geo/wgs84_pos#lat')

    lat_long: URIRef =
rdflib.term.URIRef('https://www.w3.org/2003/01/geo/wgs84_pos#lat_long')

    location: URIRef =
rdflib.term.URIRef('https://www.w3.org/2003/01/geo/wgs84_pos#location')

    long: URIRef = rdflib.term.URIRef('https://www.w3.org/2003/01/geo/wgs84_pos#long')

class rdflib.namespace.XSD
    Bases: DefinedNamespace
    W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes
    Generated from: ../schemas/datatypes.xsd Date: 2021-09-05 20:37+10
    Assertions: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#Assertions')

    ENTITIES: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#ENTITIES')

    ENTITY: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#ENTITY')

    ID: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#ID')

    IDREF: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#IDREF')

    IDREFS: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#IDREFS')

    NCName: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#NCName')

    NMTOKEN: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#NMTOKEN')

    NMTOKENS: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#NMTOKENS')

    NOTATION: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#NOTATION')

```



```
Name: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#Name')
QName: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#QName')
anyURI: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#anyURI')
base64Binary: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#base64Binary')
boolean: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#boolean')
bounded: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#bounded')
byte: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#byte')
cardinality: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#cardinality')
date: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#date')
dateTime: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dateTime')
dateTimeStamp: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dateTimeStamp')
day: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#day')
dayTimeDuration: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dayTimeDuration')
decimal: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#decimal')
double: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#double')
duration: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#duration')
enumeration: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#enumeration')
explicitTimezone: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#explicitTimezone')
float: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#float')
fractionDigits: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#fractionDigits')
gDay: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#gDay')
gMonth: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#gMonth')
gMonthDay: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#gMonthDay')
gYear: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#gYear')
gYearMonth: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#gYearMonth')
```



```
hexBinary: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#hexBinary')  
  
hour: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#hour')  
  
int: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#int')  
  
integer: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer')  
  
language: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#language')  
  
length: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#length')  
  
long: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#long')  
  
maxExclusive: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#maxExclusive')  
  
maxInclusive: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#maxInclusive')  
  
maxLength: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#maxLength')  
  
minExclusive: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#minExclusive')  
  
minInclusive: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#minInclusive')  
  
minLength: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#minLength')  
  
minute: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#minute')  
  
month: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#month')  
  
negativeInteger: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#negativeInteger')  
  
nonNegativeInteger: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#nonNegativeInteger')  
  
nonPositiveInteger: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#nonPositiveInteger')  
  
normalizedString: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#normalizedString')  
  
numeric: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#numeric')  
  
ordered: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#ordered')  
  
pattern: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#pattern')  
  
positiveInteger: URIRef =  
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#positiveInteger')
```

```
second: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#second')
short: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#short')
string: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#string')
time: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#time')
timezoneOffset: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#timezoneOffset')
token: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#token')
totalDigits: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#totalDigits')
unsignedByte: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#unsignedByte')
unsignedInt: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#unsignedInt')
unsignedLong: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#unsignedLong')
unsignedShort: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#unsignedShort')
whiteSpace: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#whiteSpace')
year: URIRef = rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#year')
yearMonthDuration: URIRef =
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#yearMonthDuration')
```

```
rdflib.namespace.is_ncname(name)
```

**Parameters**

*name* (*str*) –

**Return type**

*int*

```
rdflib.namespace.split_uri(uri, split_start=['Ll', 'Lu', 'Lo', 'Lt', 'Nl', 'Nd'])
```

**Parameters**

- *uri* (*str*) –
- *split\_start* (*List[str]*) –

**Return type**

*Tuple[str, str]*

## rdflib.plugins package

### Subpackages

## rdflib.plugins.parsers package

### Submodules

## rdflib.plugins.parsers.RDFVOC module

**class** rdflib.plugins.parsers.RDFVOC.RDFVOC

Bases: *RDF*

Description: *URIRef* =

rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#Description')

ID: *URIRef* = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#ID')

RDF: *URIRef* = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#RDF')

about: *URIRef* =

rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#about')

datatype: *URIRef* =

rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#datatype')

li: *URIRef* = rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#li')

nodeID: *URIRef* =

rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#nodeID')

parseType: *URIRef* =

rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#parseType')

resource: *URIRef* =

rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#resource')

## rdflib.plugins.parsers.hextr module

This is a rdflib plugin for parsing Hextuple files, which are Newline-Delimited JSON (ndjson) files, into Conjunctive. The store that backs the graph *must* be able to handle contexts, i.e. multiple graphs.

**class** rdflib.plugins.parsers.hextr.HextuplesParser

Bases: *Parser*

An RDFLib parser for Hextuples

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.hextr', '__doc__':
'\n An RDFLib parser for Hextuples\n\n ', '__init__': <function
HextuplesParser.__init__>, '_load_json_line': <function
HextuplesParser._load_json_line>, '_parse_hextuple': <function
HextuplesParser._parse_hextuple>, 'parse': <function HextuplesParser.parse>,
'__dict__': <attribute '__dict__' of 'HextuplesParser' objects>, '__weakref__':
<attribute '__weakref__' of 'HextuplesParser' objects>, '__annotations__': {}})
```

```
__init__()  
__module__ = 'rdflib.plugins.parsers.hexst'  
__weakref__  
    list of weak references to the object (if defined)  
parse(source, graph, **kwargs)
```

**Parameters**

- **source** (*InputSource*) –
- **graph** (*Graph*) –
- **kwargs** (*Any*) –

**Return type**

None

**rdflib.plugins.parsers.jsonld module**

This parser will interpret a JSON-LD document as an RDF Graph. See:

<http://json-ld.org/>

Example usage:

```
>>> from rdflib import Graph, URIRef, Literal  
>>> test_json = '''  
... {  
...     "@context": {  
...         "dc": "http://purl.org/dc/terms/",  
...         "rdf": "http://www.w3.org/1999/02/22-rdf-syntax-ns#",  
...         "rdfs": "http://www.w3.org/2000/01/rdf-schema#"  
...     },  
...     "@id": "http://example.org/about",  
...     "dc:title": {  
...         "@language": "en",  
...         "@value": "Someone's Homepage"  
...     }  
... }  
... '''  
>>> g = Graph().parse(data=test_json, format='json-ld')  
>>> list(g) == [(URIRef('http://example.org/about'),  
...     URIRef('http://purl.org/dc/terms/title'),  
...     Literal("Someone's Homepage", lang='en'))]  
True
```

**class rdflib.plugins.parsers.jsonld.JsonLDParser**

Bases: *Parser*

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.jsonld', '__init__':  
<function JsonLDParser.__init__>, 'parse': <function JsonLDParser.parse>,  
'__dict__': <attribute '__dict__' of 'JsonLDParser' objects>, '__weakref__':  
<attribute '__weakref__' of 'JsonLDParser' objects>, '__doc__': None,  
'__annotations__': {}})
```

```

__init__()

__module__ = 'rdflib.plugins.parsers.jsonld'

__weakref__
    list of weak references to the object (if defined)

parse(source, sink, **kwargs)

```

#### Parameters

- **source** (*InputSource*) –
- **sink** (*Graph*) –
- **kwargs** (*Any*) –

#### Return type

*None*

```
rdflib.plugins.parsers.jsonld.to_rdf(data, dataset, base=None, context_data=None, version=None,
                                     generalized_rdf=False, allow_lists_of_lists=None)
```

#### Parameters

- **data** (*Any*) –
- **dataset** (*Graph*) –
- **base** (*Optional[str]*) –
- **context\_data** (*Optional[bool]*) –
- **version** (*Optional[float]*) –
- **generalized\_rdf** (*bool*) –
- **allow\_lists\_of\_lists** (*Optional[bool]*) –

### rdflib.plugins.parsers.notation3 module

notation3.py - Standalone Notation3 Parser Derived from CWM, the Closed World Machine

Authors of the original suite:

- Dan Connolly <@ @>
- Tim Berners-Lee <@ @>
- Yosi Scharf <@ @>
- Joseph M. Reagle Jr. <reagle@w3.org>
- Rich Salz <rsalz@zolera.com>

<http://www.w3.org/2000/10/swap/notation3.py>

Copyright 2000-2007, World Wide Web Consortium. Copyright 2001, MIT. Copyright 2001, Zolera Systems Inc.

License: W3C Software License <http://www.w3.org/Consortium/Legal/copyright-software>

Modified by Sean B. Palmer Copyright 2007, Sean B. Palmer.

Modified to work with rdflib by Gunnar Aastrand Grimnes Copyright 2010, Gunnar A. Grimnes

**exception** rdflib.plugins.parsers.notation3.**BadSyntax**(*uri, lines, argstr, i, why*)

Bases: [SyntaxError](#)

**Parameters**

- **uri** ([str](#)) –
- **lines** ([int](#)) –
- **argstr** ([str](#)) –
- **i** ([int](#)) –
- **why** ([str](#)) –

**\_\_init\_\_**(*uri, lines, argstr, i, why*)

**Parameters**

- **uri** ([str](#)) –
- **lines** ([int](#)) –
- **argstr** ([str](#)) –
- **i** ([int](#)) –
- **why** ([str](#)) –

**\_\_module\_\_** = 'rdflib.plugins.parsers.notation3'

**\_\_str\_\_**()

Return str(self).

**Return type**

[str](#)

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**property message:** [str](#)

**class** rdflib.plugins.parsers.notation3.**Formula**(*parent*)

Bases: [object](#)

**Parameters**

**parent** ([Graph](#)) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.notation3',
'number': 0, '__init__': <function Formula.__init__>, '__str__': <function
Formula.__str__>, 'id': <function Formula.id>, 'newBlankNode': <function
Formula.newBlankNode>, 'newUniversal': <function Formula.newUniversal>,
'declareExistential': <function Formula.declareExistential>, 'close': <function
Formula.close>, '__dict__': <attribute '__dict__' of 'Formula' objects>,
'__weakref__': <attribute '__weakref__' of 'Formula' objects>, '__doc__': None,
'__annotations__': {'existentials': 'Dict[str, BNode]', 'universals': 'Dict[str,
BNode]'}})
```

**\_\_init\_\_**(*parent*)

**Parameters**

**parent** ([Graph](#)) –

```

__module__ = 'rdflib.plugins.parsers.notation3'

__str__()
    Return str(self).

    Return type
        str

__weakref__
    list of weak references to the object (if defined)

close()

    Return type
        QuotedGraph

declareExistential(x)

    Parameters
        x (str) –

    Return type
        None

id()

    Return type
        BNode

newBlankNode(uri=None, why=None)

    Parameters
        • uri (Optional[str]) –
        • why (Optional[Any]) –

    Return type
        BNode

newUniversal(uri, why=None)

    Parameters
        • uri (str) –
        • why (Optional[Any]) –

    Return type
        Variable

number = 0

class rdflib.plugins.parsers.notation3.N3Parser
    Bases: TurtleParser
    An RDFLib parser for Notation3
    See http://www.w3.org/DesignIssues/Notation3.html

    __init__()

    __module__ = 'rdflib.plugins.parsers.notation3'

```

**parse**(*source*, *graph*, *encoding*='utf-8')

**Parameters**

- **source** (*InputSource*) –
- **graph** (*Graph*) –
- **encoding** (*Optional*[*str*]) –

**Return type**

*None*

**class** `rdflib.plugins.parsers.notation3.RDFSink`(*graph*)

Bases: *object*

**Parameters**

**graph** (*Graph*) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.notation3',  
'__init__': <function RDFSink.__init__>, 'newFormula': <function  
RDFSink.newFormula>, 'newGraph': <function RDFSink.newGraph>, 'newSymbol':  
<function RDFSink.newSymbol>, 'newBlankNode': <function RDFSink.newBlankNode>,  
'newLiteral': <function RDFSink.newLiteral>, 'newList': <function  
RDFSink.newList>, 'newSet': <function RDFSink.newSet>, 'setDefaultNamespace':  
<function RDFSink.setDefaultNamespace>, 'makeStatement': <function  
RDFSink.makeStatement>, 'normalise': <function RDFSink.normalise>, 'intern':  
<function RDFSink.intern>, 'bind': <function RDFSink.bind>, 'startDoc': <function  
RDFSink.startDoc>, 'endDoc': <function RDFSink.endDoc>, '__dict__': <attribute  
'__dict__' of 'RDFSink' objects>, '__weakref__': <attribute '__weakref__' of  
'RDFSink' objects>, '__doc__': None, '__annotations__': {'rootFormula':  
'Optional[Formula]'}}})
```

**\_\_init\_\_**(*graph*)

**Parameters**

**graph** (*Graph*) –

**\_\_module\_\_** = 'rdflib.plugins.parsers.notation3'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**bind**(*pf<sub>x</sub>*, *uri*)

**Return type**

*None*

**endDoc**(*formula*)

**Parameters**

**formula** (*Optional*[*Formula*]) –

**Return type**

*None*

**intern**(*something*)

**Parameters**

**something** (*TypeVar*(*\_AnyT*)) –



**Return type**

`TypeVar(_AnyT)`

**makeStatement**(*quadruple*, *why=None*)

**Parameters**

- **quadruple** (`Tuple[Union[Formula, Graph, None], Node, Node, Node]`) –
- **why** (`Optional[Any]`) –

**Return type**

`None`

**newBlankNode**(*arg=None*, *uri=None*, *why=None*)

**Parameters**

- **arg** (`Union[Formula, Graph, Any, None]`) –
- **uri** (`Optional[str]`) –
- **why** (`Optional[Callable[[], None]]`) –

**Return type**

`BNode`

**newFormula**()

**Return type**

`Formula`

**newGraph**(*identifier*)

**Parameters**

**identifier** (`Identifier`) –

**Return type**

`Graph`

**newList**(*n*, *f*)

**Parameters**

- **n** (`List[Any]`) –
- **f** (`Optional[Formula]`) –

**Return type**

`IdentifiedNode`

**newLiteral**(*s*, *dt*, *lang*)

**Parameters**

- **s** (`str`) –
- **dt** (`Optional[URIRef]`) –
- **lang** (`Optional[str]`) –

**Return type**

`Literal`

**newSet**(\*args)

**Parameters**

**args** (*TypeVar*(*\_AnyT*)) –

**Return type**

*Set*[*TypeVar*(*\_AnyT*)]

**newSymbol**(\*args)

**Parameters**

**args** (*str*) –

**Return type**

*URIRef*

**normalise**(*f*, *n*)

**Parameters**

- **f** (*Optional*[*Formula*]) –
- **n** (*Union*[*Tuple*[*int*, *str*], *bool*, *int*, *Decimal*, *float*, *TypeVar*(*\_AnyT*)]) –

**Return type**

*Union*[*URIRef*, *Literal*, *BNode*, *TypeVar*(*\_AnyT*)]

**setDefaultNamespace**(\*args)

**Parameters**

**args** (*bytes*) –

**Return type**

*str*

**startDoc**(*formula*)

**Parameters**

**formula** (*Optional*[*Formula*]) –

**Return type**

*None*

**class** `rdflib.plugins.parsers.notation3.SinkParser`(*store*, *openFormula*=*None*, *thisDoc*="",  
*baseURI*=*None*, *genPrefix*="", *why*=*None*,  
*turtle*=*False*)

Bases: *object*

**Parameters**

- **store** (*RDFSink*) –
- **openFormula** (*Optional*[*Formula*]) –
- **thisDoc** (*str*) –
- **baseURI** (*Optional*[*str*]) –
- **genPrefix** (*str*) –
- **why** (*Optional*[*Callable*[[], *None*]]) –
- **turtle** (*bool*) –

**BadSyntax**(*argstr*, *i*, *msg*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **msg** (*str*) –

**Return type**

*NoReturn*

**UEScape**(*argstr*, *i*, *startline*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **startline** (*int*) –

**Return type**

*Tuple*[*int*, *str*]

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.notation3',
'__init__': <function SinkParser.__init__>, 'here': <function SinkParser.here>,
'formula': <function SinkParser.formula>, 'loadStream': <function
SinkParser.loadStream>, 'loadBuf': <function SinkParser.loadBuf>, 'feed':
<function SinkParser.feed>, 'directiveOrStatement': <function
SinkParser.directiveOrStatement>, 'tok': <function SinkParser.tok>, 'sparqlTok':
<function SinkParser.sparqlTok>, 'directive': <function SinkParser.directive>,
'sparqlDirective': <function SinkParser.sparqlDirective>, 'bind': <function
SinkParser.bind>, 'setKeywords': <function SinkParser.setKeywords>, 'startDoc':
<function SinkParser.startDoc>, 'endDoc': <function SinkParser.endDoc>,
'makeStatement': <function SinkParser.makeStatement>, 'statement': <function
SinkParser.statement>, 'subject': <function SinkParser.subject>, 'verb': <function
SinkParser.verb>, 'prop': <function SinkParser.prop>, 'item': <function
SinkParser.item>, 'blankNode': <function SinkParser.blankNode>, 'path': <function
SinkParser.path>, 'anonymousNode': <function SinkParser.anonymousNode>, 'node':
<function SinkParser.node>, 'property_list': <function SinkParser.property_list>,
'commaSeparatedList': <function SinkParser.commaSeparatedList>, 'objectList':
<function SinkParser.objectList>, 'checkDot': <function SinkParser.checkDot>,
'uri_ref2': <function SinkParser.uri_ref2>, 'skipSpace': <function
SinkParser.skipSpace>, 'variable': <function SinkParser.variable>, 'bareWord':
<function SinkParser.bareWord>, 'qname': <function SinkParser.qname>, 'object':
<function SinkParser.object>, 'nodeOrLiteral': <function SinkParser.nodeOrLiteral>,
'uriOf': <function SinkParser.uriOf>, 'strconst': <function SinkParser.strconst>,
'_unicodeEscape': <function SinkParser._unicodeEscape>, 'uEscape': <function
SinkParser.uEscape>, 'UEScape': <function SinkParser.UEscape>, 'BadSyntax':
<function SinkParser.BadSyntax>, '__dict__': <attribute '__dict__' of 'SinkParser'
objects>, '__weakref__': <attribute '__weakref__' of 'SinkParser' objects>,
'__doc__': None, '__annotations__': {'_anonymousNodes': 'Dict[str, BNode]',
'_variables': 'Dict[str, Variable]', '_parentVariables': 'Dict[str, Variable]',
'_reason2': 'Optional[Callable[..., None]]', '_baseURI': 'Optional[str]',
'_formula': 'Optional[Formula]', '_context': 'Optional[Formula]',
'_parentContext': 'Optional[Formula]'}}
```

**\_\_init\_\_**(*store*, *openFormula*=None, *thisDoc*="", *baseURI*=None, *genPrefix*="", *why*=None, *turtle*=False)

note: namespace names should *not* end in # ; the # will get added during qname processing

**Parameters**

- **store** (*RDFSink*) –
- **openFormula** (*Optional[Formula]*) –
- **thisDoc** (*str*) –
- **baseURI** (*Optional[str]*) –
- **genPrefix** (*str*) –
- **why** (*Optional[Callable[[], None]]*) –
- **turtle** (*bool*) –

**\_\_module\_\_** = 'rdflib.plugins.parsers.notation3'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**anonymousNode**(*ln*)

Remember or generate a term for one of these \_: anonymous nodes

**Parameters**

**ln** (*str*) –

**Return type**

*BNode*

**bareWord**(*argstr*, *i*, *res*)

abc -> :abc

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence[Any]*) –

**Return type**

*int*

**bind**(*qn*, *uri*)

**Parameters**

- **qn** (*str*) –
- **uri** (*bytes*) –

**Return type**

*None*

**blankNode**(*uri*=None)

**Parameters**

**uri** (*Optional[str]*) –

**Return type**

*BNode*

**checkDot**(*argstr*, *i*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –

**Return type**

*int*

**commaSeparatedList**(*argstr*, *j*, *res*, *what*)

return value: -1 bad syntax; >1 new position in argstr res has things found appended

**Parameters**

- **argstr** (*str*) –
- **j** (*int*) –
- **res** (*MutableSequence*[*Any*]) –
- **what** (*Callable*[[*str*, *int*, *MutableSequence*[*Any*]], *int*) –

**Return type**

*int*

**directive**(*argstr*, *i*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –

**Return type**

*int*

**directiveOrStatement**(*argstr*, *h*)

**Parameters**

- **argstr** (*str*) –
- **h** (*int*) –

**Return type**

*int*

**endDoc**()

Signal end of document and stop parsing. returns formula

**Return type**

*Optional*[*Formula*]

**feed**(*octets*)

Feed an octet stream to the parser

if BadSyntax is raised, the string passed in the exception object is the remainder after any statements have been parsed. So if there is more data to feed to the parser, it should be straightforward to recover.

**Parameters**

**octets** (*Union*[*str*, *bytes*]) –

**Return type**

*None*

**formula()**

**Return type**

`Optional[Formula]`

**here(*i*)**

String generated from position in file

This is for repeatability when referring people to bnodes in a document. This has diagnostic uses less formally, as it should point one to which bnode the arbitrary identifier actually is. It gives the line and character number of the '[' character or path character which introduced the blank node. The first blank node is boringly \_L1C1. It used to be used only for tracking, but for tests in general it makes the canonical ordering of bnodes repeatable.

**Parameters**

**i** (`int`) –

**Return type**

`str`

**item(*argstr*, *i*, *res*)**

**Parameters**

- **argstr** (`str`) –
- **res** (`MutableSequence[Any]`) –

**Return type**

`int`

**loadBuf(*buf*)**

Parses a buffer and returns its top level formula

**Parameters**

**buf** (`Union[str, bytes]`) –

**Return type**

`Optional[Formula]`

**loadStream(*stream*)**

**Parameters**

**stream** (`Union[IO[str], IO[bytes]]`) –

**Return type**

`Optional[Formula]`

**makeStatement(*quadruple*)**

**Return type**

`None`

**node(*argstr*, *i*, *res*, *subjectAlready=None*)**

Parse the <node> production. Space is now skipped once at the beginning instead of in multiple calls to self.skipSpace().

**Parameters**

- **argstr** (`str`) –
- **i** (`int`) –
- **res** (`MutableSequence[Any]`) –

- **subjectAlready** (*Optional*[*Node*]) –

**Return type**

*int*

**nodeOrLiteral**(*argstr*, *i*, *res*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence*[*Any*]) –

**Return type**

*int*

**object**(*argstr*, *i*, *res*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence*[*Any*]) –

**Return type**

*int*

**objectList**(*argstr*, *i*, *res*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence*[*Any*]) –

**Return type**

*int*

**path**(*argstr*, *i*, *res*)

Parse the path production.

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence*[*Any*]) –

**Return type**

*int*

**prop**(*argstr*, *i*, *res*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence*[*Any*]) –

**Return type**

`int`

**property\_list**(*argstr*, *i*, *subj*)

Parse property list Leaves the terminating punctuation in the buffer

**Parameters**

- **argstr** (`str`) –
- **i** (`int`) –
- **subj** (`Node`) –

**Return type**

`int`

**qname**(*argstr*, *i*, *res*)

xyz:def -> ('xyz', 'def') If not in keywords and keywordsSet: def -> ('', 'def') :def -> ('', 'def')

**Parameters**

- **argstr** (`str`) –
- **i** (`int`) –
- **res** (`MutableSequence[Union[Identifier, Tuple[str, str]]]`) –

**Return type**

`int`

**setKeywords**(*k*)

Takes a list of strings

**Parameters**

**k** (`Optional[List[str]]`) –

**Return type**

`None`

**skipSpace**(*argstr*, *i*)

Skip white space, newlines and comments. return -1 if EOF, else position of first non-ws character

**Parameters**

- **argstr** (`str`) –
- **i** (`int`) –

**Return type**

`int`

**sparqlDirective**(*argstr*, *i*)

turtle and trig support BASE/PREFIX without @ and without terminating .

**Parameters**

- **argstr** (`str`) –
- **i** (`int`) –

**Return type**

`int`



**sparqlTok**(*tok, argstr, i*)

Check for SPARQL keyword. Space must have been stripped on entry and we must not be at end of file.  
Case insensitive and not preceded by @

**Parameters**

- **tok** (*str*) –
- **argstr** (*str*) –
- **i** (*int*) –

**Return type**

*int*

**startDoc**()

**Return type**

*None*

**statement**(*argstr, i*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –

**Return type**

*int*

**strconst**(*argstr, i, delim*)

parse an N3 string constant delimited by delim. return index, val

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **delim** (*str*) –

**Return type**

*Tuple[int, str]*

**subject**(*argstr, i, res*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence[Any]*) –

**Return type**

*int*

**tok**(*tok, argstr, i, colon=False*)

Check for keyword. Space must have been stripped on entry and we must not be at end of file.

if colon, then keyword followed by colon is ok (@prefix:<blah> is ok, rdf:type shortcut a must be followed by ws)

**Parameters**

- **tok** (*str*) –

- **argstr** (*str*) –
- **i** (*int*) –
- **colon** (*bool*) –

**Return type**

*int*

**uEscape**(*argstr*, *i*, *startline*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **startline** (*int*) –

**Return type**

*Tuple*[*int*, *str*]

**uriOf**(*sym*)

**Parameters**

**sym** (*Union*[*Identifier*, *Tuple*[*str*, *str*]]) –

**Return type**

*str*

**uri\_ref2**(*argstr*, *i*, *res*)

Generate uri from n3 representation.

Note that the RDF convention of directly concatenating NS and local name is now used though I prefer inserting a '#' to make the namespaces look more like what XML folks expect.

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence*[*Any*]) –

**Return type**

*int*

**variable**(*argstr*, *i*, *res*)

?abc -> variable(:abc)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –

**Return type**

*int*

**verb**(*argstr*, *i*, *res*)

has \_prop\_ is \_prop\_ of a = \_prop\_ >- prop -> <- prop -< \_operator\_

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –

- **res** (`MutableSequence[Any]`) –

**Return type**

`int`

**class** `rdflib.plugins.parsers.notation3.TurtleParser`

Bases: `Parser`

An RDFLib parser for Turtle

See <http://www.w3.org/TR/turtle/>

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.notation3',
'__doc__': '\n An RDFLib parser for Turtle\n\n See http://www.w3.org/TR/turtle/\n',
'__init__': <function TurtleParser.__init__>, 'parse': <function TurtleParser.parse>,
'__dict__': <attribute '__dict__' of 'TurtleParser' objects>,
'__weakref__': <attribute '__weakref__' of 'TurtleParser' objects>,
'__annotations__': {}})
```

```
__init__()
```

```
__module__ = 'rdflib.plugins.parsers.notation3'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
parse(source, graph, encoding='utf-8', turtle=True)
```

**Parameters**

- **source** (`InputSource`) –
- **graph** (`Graph`) –
- **encoding** (`Optional[str]`) –
- **turtle** (`bool`) –

**Return type**

`None`

`rdflib.plugins.parsers.notation3.base()`

The base URI for this process - the Web equiv of cwd

Relative or absolute unix-standard filenames parsed relative to this yield the URI of the file. If we had a reliable way of getting a computer name, we should put it in the hostname just to prevent ambiguity

**Return type**

`str`

`rdflib.plugins.parsers.notation3.hexify(ustr)`

Use URL encoding to return an ASCII string corresponding to the given UTF8 string

```
>>> hexify("http://example/a b")
b'http://example/a%20b'
```

**Parameters**

**ustr** (`str`) –

**Return type**

`bytes`

`rdflib.plugins.parsers.notation3.join(here, there)`

join an absolute URI and URI reference (non-ascii characters are supported/doctested; haven't checked the details of the IRI spec though)

`here` is assumed to be absolute. `there` is URI reference.

```
>>> join('http://example/x/y/z', '../abc')
'http://example/x/abc'
```

Raise `ValueError` if there uses relative path syntax but here has no hierarchical path.

```
>>> join('mid:foo@example', '../foo')
Traceback (most recent call last):
  raise ValueError(here)
ValueError: Base <mid:foo@example> has no slash
after colon - with relative '../foo'.
```

```
>>> join('http://example/x/y/z', '')
'http://example/x/y/z'
```

```
>>> join('mid:foo@example', '#foo')
'mid:foo@example#foo'
```

We grok IRIs

```
>>> len(u'Andr\xe9')
5
```

```
>>> join('http://example.org/', u'#Andr\xe9')
u'http://example.org/#Andr\xe9'
```

#### Parameters

- **here** (`str`) –
- **there** (`str`) –

#### Return type

`str`

`rdflib.plugins.parsers.notation3.runNamespace()`

Returns a URI suitable as a namespace for run-local objects

#### Return type

`str`

`rdflib.plugins.parsers.notation3.splitFragP(uriref, punc=0)`

split a URI reference before the fragment

Punctuation is kept.

e.g.

```
>>> splitFragP("abc#def")
('abc', '#def')
```

```
>>> splitFragP("abcdef")
('abcdef', '')
```

**Parameters**

- **uriref** (*str*) –
- **punc** (*int*) –

**Return type**

`Tuple[str, str]`

`rdflib.plugins.parsers.notation3.uniqueURI()`

A unique URI

**Return type**

*str*

**rdflib.plugins.parsers.nquads module**

This is a rdflib plugin for parsing NQuad files into Conjunctive graphs that can be used and queried. The store that backs the graph *must* be able to handle contexts.

```
>>> from rdflib import ConjunctiveGraph, URIRef, Namespace
>>> g = ConjunctiveGraph()
>>> data = open("test/data/nquads/rdflib/example.nquads", "rb")
>>> g.parse(data, format="nquads")
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> assert len(g.store) == 449
>>> # There should be 16 separate contexts
>>> assert len([x for x in g.store.contexts()]) == 16
>>> # is the name of entity E10009 "Arco Publications"?
>>> # (in graph http://bibliographica.org/entity/E10009)
>>> # Looking for:
>>> # <http://bibliographica.org/entity/E10009>
>>> # <http://xmlns.com/foaf/0.1/name>
>>> # "Arco Publications"
>>> # <http://bibliographica.org/entity/E10009>
>>> s = URIRef("http://bibliographica.org/entity/E10009")
>>> FOAF = Namespace("http://xmlns.com/foaf/0.1/")
>>> assert(g.value(s, FOAF.name).eq("Arco Publications"))
```

**class** `rdflib.plugins.parsers.nquads.NQuadsParser`(*sink=None, bnode\_context=None*)

Bases: *W3CNTriplesParser*

**Parameters**

- **sink** (`Union[DummySink, NTGraphSink, None]`) –
- **bnode\_context** (`Optional[MutableMapping[str, BNode]]`) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.nquads', 'parse':  
<function NQuadsParser.parse>, 'parseline': <function NQuadsParser.parseline>,  
'__dict__': <attribute '__dict__' of 'NQuadsParser' objects>, '__weakref__':  
<attribute '__weakref__' of 'NQuadsParser' objects>, '__doc__': None,  
'__annotations__': {'sink': "Union[DummySink, 'NTGraphSink']", 'buffer':  
'Optional[str]', 'file': 'Optional[Union[TextIO, codecs.StreamReader]]', 'line':  
'Optional[str]'}}})
```

```
__module__ = 'rdflib.plugins.parsers.nquads'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
buffer: Optional[str]
```

```
file: Optional[Union[TextIO, codecs.StreamReader]]
```

```
line: Optional[str]
```

```
parse(inputsource, sink, bnode_context=None, **kwargs)
```

Parse inputsource as an N-Quads file.

#### Parameters

- **inputsource** (*InputSource*) – the source of N-Quads-formatted data
- **sink** (*ConjunctiveGraph*) – where to send parsed triples
- **bnode\_context** (*Optional[MutableMapping[str, BNode]]*) – a dict mapping blank node identifiers to *rdflib.term.BNode* instances. See *.W3CNTriplesParser.parse*
- **kwargs** (*Any*) –

#### Return type

*ConjunctiveGraph*

```
parseline(bnode_context=None)
```

#### Parameters

**bnode\_context** (*Optional[MutableMapping[str, BNode]]*) –

#### Return type

*None*

```
sink: Union[DummySink, 'NTGraphSink']
```

## rdflib.plugins.parsers.ntriples module

N-Triples Parser License: GPL 2, W3C, BSD, or MIT Author: Sean B. Palmer, inamidst.com

```
class rdflib.plugins.parsers.ntriples.DummySink
```

Bases: *object*

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.ntriples',  
'__init__': <function DummySink.__init__>, 'triple': <function DummySink.triple>,  
'__dict__': <attribute '__dict__' of 'DummySink' objects>, '__weakref__':  
<attribute '__weakref__' of 'DummySink' objects>, '__doc__': None,  
'__annotations__': {}}})
```

```

__init__()

__module__ = 'rdflib.plugins.parsers.ntriples'

__weakref__
    list of weak references to the object (if defined)

triple(s, p, o)

class rdflib.plugins.parsers.ntriples.NTGraphSink(graph)
    Bases: object

        Parameters
            graph (Graph) –

__init__(graph)

        Parameters
            graph (Graph) –

__module__ = 'rdflib.plugins.parsers.ntriples'

__slots__ = ('g',)

g

triple(s, p, o)

        Parameters
            • s (Node) –
            • p (Node) –
            • o (Node) –

        Return type
            None

class rdflib.plugins.parsers.ntriples.NTParser
    Bases: Parser

    parser for the ntriples format, often stored with the .nt extension

    See http://www.w3.org/TR/rdf-testcases/#ntriples

__module__ = 'rdflib.plugins.parsers.ntriples'

__slots__ = ()

classmethod parse(source, sink, **kwargs)
    Parse the NT format

        Parameters
            • source (InputSource) – the source of NT-formatted data
            • sink (Graph) – where to send parsed triples
            • kwargs (Any) – Additional arguments to pass to .W3CNTriplesParser.parse

        Return type
            None

```

```
class rdflib.plugins.parsers.ntriples.W3CNTriplesParser(sink=None, bnode_context=None)
```

Bases: *object*

An N-Triples Parser. This is a legacy-style Triples parser for N-Triples provided by W3C Usage:

```
p = W3CNTriplesParser(sink=MySink())
sink = p.parse(f) # file; use parsestring for a string
```

To define a context in which blank node identifiers refer to the same blank node across instances of *NTriplesParser*, pass the same dict as *bnode\_context* to each instance. By default, a new blank node context is created for each instance of *W3CNTriplesParser*.

#### Parameters

- **sink** (*Union*[*DummySink*, *NTGraphSink*, *None*]) –
- **bnode\_context** (*Optional*[*MutableMapping*[*str*, *BNode*]]) –

```
__init__(sink=None, bnode_context=None)
```

#### Parameters

- **sink** (*Union*[*DummySink*, *NTGraphSink*, *None*]) –
- **bnode\_context** (*Optional*[*MutableMapping*[*str*, *BNode*]]) –

```
__module__ = 'rdflib.plugins.parsers.ntriples'
```

```
__slots__ = ('_bnode_ids', 'sink', 'buffer', 'file', 'line')
```

```
buffer: Optional[str]
```

```
eat(pattern)
```

#### Parameters

**pattern** (*Pattern*[*str*]) –

#### Return type

*Match*[*str*]

```
file: Union[TextIO, StreamReader, None]
```

```
line: Optional[str]
```

```
literal()
```

#### Return type

*Union*[*Literal*[*False*], *Literal*]

```
nodeid(bnode_context=None)
```

#### Parameters

**bnode\_context** (*Optional*[*MutableMapping*[*str*, *BNode*]]) –

#### Return type

*Union*[*Literal*[*False*], *BNode*]

```
object(bnode_context=None)
```

#### Parameters

**bnode\_context** (*Optional*[*MutableMapping*[*str*, *BNode*]]) –

#### Return type

*Union*[*URIRef*, *BNode*, *Literal*]



**parse**(*f*, *bnode\_context*=None)

Parse *f* as an N-Triples file.

**Parameters**

- **f** (`Union[TextIO, IO[bytes], StreamReader]`) – the N-Triples source
- **bnode\_context** (`Optional[MutableMapping[str, BNode]]`) – a dict mapping blank node identifiers (e.g., `a` in `_:a`) to `~rdflib.term.BNode` instances. An empty dict can be passed in to define a distinct context for a given call to *parse*.

**Return type**

`Union[DummySink, NTGraphSink]`

**parseline**(*bnode\_context*=None)

**Parameters**

**bnode\_context** (`Optional[MutableMapping[str, BNode]]`) –

**Return type**

`None`

**parsestring**(*s*, *\*\*kwargs*)

Parse *s* as an N-Triples string.

**Parameters**

**s** (`Union[bytes, bytearray, str]`) –

**Return type**

`None`

**peek**(*token*)

**Parameters**

**token** (`str`) –

**Return type**

`bool`

**predicate**()

**Return type**

`URIRef`

**readline**()

Read an N-Triples line from buffered input.

**Return type**

`Optional[str]`

**sink**: `Union[DummySink, NTGraphSink]`

**subject**(*bnode\_context*=None)

**Return type**

`Union[BNode, URIRef]`

**uriref**()

**Return type**

`Union[Literal[False], URIRef]`

`rdflib.plugins.parsers.ntriples.unquote(s)`

Unquote an N-Triples string.

**Parameters**

**s** (*str*) –

**Return type**

*str*

`rdflib.plugins.parsers.ntriples.uriquote(uri)`

**Parameters**

**uri** (*str*) –

**Return type**

*str*

### `rdflib.plugins.parsers.rdfxml` module

An RDF/XML parser for RDFLib

**class** `rdflib.plugins.parsers.rdfxml.BagID`(*value: str, base: str | None = None*)

Bases: *URIRef*

`__init__`(*val*)

`__module__` = `'rdflib.plugins.parsers.rdfxml'`

`__slots__` = `['li']`

`li`

`next_li`()

**class** `rdflib.plugins.parsers.rdfxml.ElementHandler`

Bases: *object*

`__init__`()

`__module__` = `'rdflib.plugins.parsers.rdfxml'`

`__slots__` = `['start', 'char', 'end', 'li', 'id', 'base', 'subject', 'predicate', 'object', 'list', 'language', 'datatype', 'declared', 'data']`

`base`

`char`

`data`

`datatype`

`declared`

`end`

`id`

`language`

```

li
list
next_li()
object
predicate
start
subject

```

```
class rdflib.plugins.parsers.rdfxml.RDFXMLHandler(store)
```

```
    Bases: ContentHandler
```

```
        Parameters
```

```
            store (Graph) –
```

```
    __init__(store)
```

```
        Parameters
```

```
            store (Graph) –
```

```
    __module__ = 'rdflib.plugins.parsers.rdfxml'
```

```
    absolutize(uri)
```

```
        Parameters
```

```
            uri (str) –
```

```
        Return type
```

```
            URIRef
```

```
    add_reified(sid, spo)
```

```
        Parameters
```

- sid (Identifier) –
- spo (Tuple[Node, Node, Node]) –

```
    characters(content)
```

```
        Receive notification of character data.
```

The Parser will call this method to report each chunk of character data. SAX parsers may return all contiguous character data in a single chunk, or they may split it into several chunks; however, all of the characters in any single event must come from the same external entity so that the Locator provides useful information.

```
        Parameters
```

```
            content (str) –
```

```
        Return type
```

```
            None
```

```
    convert(name, qname, attrs)
```

```
        Parameters
```

- name (Tuple[Optional[str], str]) –
- attrs (AttributesImpl) –

**Return type**`Tuple[URIRef, Dict[URIRef, str]]`**property current:** `ElementHandler` | `None`**document\_element\_start**(*name*, *qname*, *attrs*)**Parameters**

- **name** (`Tuple[str, str]`) –
- **attrs** (`AttributesImpl`) –

**Return type**`None`**endElementNS**(*name*, *qname*)

Signals the end of an element in namespace mode.

The name parameter contains the name of the element type, just as with the startElementNS event.

**Parameters****name** (`Tuple[Optional[str], str]`) –**Return type**`None`**endPrefixMapping**(*prefix*)

End the scope of a prefix-URI mapping.

See startPrefixMapping for details. This event will always occur after the corresponding endElement event, but the order of endPrefixMapping events is not otherwise guaranteed.

**Parameters****prefix** (`Optional[str]`) –**Return type**`None`**error**(*message*)**Parameters****message** (`str`) –**Return type**`NoReturn`**get\_current**()**Return type**`Optional[ElementHandler]`**get\_next**()**Return type**`Optional[ElementHandler]`**get\_parent**()**Return type**`Optional[ElementHandler]`

**ignorableWhitespace**(*content*)

Receive notification of ignorable whitespace in element content.

Validating Parsers must use this method to report each chunk of ignorable whitespace (see the W3C XML 1.0 recommendation, section 2.10): non-validating parsers may also use this method if they are capable of parsing and using content models.

SAX parsers may return all contiguous whitespace in a single chunk, or they may split it into several chunks; however, all of the characters in any single event must come from the same external entity, so that the Locator provides useful information.

**Return type**

`None`

**list\_node\_element\_end**(*name*, *qname*)**Parameters**

**name** (`Tuple[str, str]`) –

**Return type**

`None`

**literal\_element\_char**(*data*)**Parameters**

**data** (`str`) –

**Return type**

`None`

**literal\_element\_end**(*name*, *qname*)**Parameters**

**name** (`Tuple[str, str]`) –

**Return type**

`None`

**literal\_element\_start**(*name*, *qname*, *attrs*)**Parameters**

- **name** (`Tuple[str, str]`) –
- **attrs** (`AttributesImpl`) –

**Return type**

`None`

**property next:** `ElementHandler` | `None`

**node\_element\_end**(*name*, *qname*)**Parameters**

**name** (`Tuple[str, str]`) –

**Return type**

`None`

**node\_element\_start**(*name*, *qname*, *attrs*)**Parameters**

- **name** (`Tuple[str, str]`) –

- **attrs** (`AttributesImpl`) –

**Return type**

`None`

**property parent:** `ElementHandler` | `None`

**processingInstruction**(*target, data*)

Receive notification of a processing instruction.

The Parser will invoke this method once for each processing instruction found: note that processing instructions may occur before or after the main document element.

A SAX parser should never report an XML declaration (XML 1.0, section 2.8) or a text declaration (XML 1.0, section 4.3.1) using this method.

**Return type**

`None`

**property\_element\_char**(*data*)

**Parameters**

**data** (`str`) –

**Return type**

`None`

**property\_element\_end**(*name, qname*)

**Parameters**

**name** (`Tuple[str, str]`) –

**Return type**

`None`

**property\_element\_start**(*name, qname, attrs*)

**Parameters**

- **name** (`Tuple[str, str]`) –
- **attrs** (`AttributesImpl`) –

**Return type**

`None`

**reset**()

**Return type**

`None`

**setDocumentLocator**(*locator*)

Called by the parser to give the application a locator for locating the origin of document events.

SAX parsers are strongly encouraged (though not absolutely required) to supply a locator: if it does so, it must supply the locator to the application by invoking this method before invoking any of the other methods in the `DocumentHandler` interface.

The locator allows the application to determine the end position of any document-related event, even if the parser is not reporting an error. Typically, the application will use this information for reporting its own errors (such as character content that does not match an application's business rules). The information returned by the locator is probably not sufficient for use with a search engine.

Note that the locator will return correct information only during the invocation of the events in this interface. The application should not attempt to use it at any other time.

**Parameters**

**locator** (*Locator*) –

**startDocument()**

Receive notification of the beginning of a document.

The SAX parser will invoke this method only once, before any other methods in this interface or in DTD-Handler (except for setDocumentLocator).

**Return type**

*None*

**startElementNS**(*name, qname, attrs*)

Signals the start of an element in namespace mode.

The name parameter contains the name of the element type as a (uri, localname) tuple, the qname parameter the raw XML 1.0 name used in the source document, and the attrs parameter holds an instance of the Attributes class containing the attributes of the element.

The uri part of the name tuple is None for elements which have no namespace.

**Parameters**

- **name** (*Tuple[Optional[str], str]*) –
- **attrs** (*AttributesImpl*) –

**Return type**

*None*

**startPrefixMapping**(*prefix, namespace*)

Begin the scope of a prefix-URI Namespace mapping.

The information from this event is not necessary for normal Namespace processing: the SAX XML reader will automatically replace prefixes for element and attribute names when the <http://xml.org/sax/features/namespaces> feature is true (the default).

There are cases, however, when applications need to use prefixes in character data or in attribute values, where they cannot safely be expanded automatically; the start/endPrefixMapping event supplies the information to the application to expand prefixes in those contexts itself, if necessary.

Note that start/endPrefixMapping events are not guaranteed to be properly nested relative to each-other: all startPrefixMapping events will occur before the corresponding startElement event, and all endPrefixMapping events will occur after the corresponding endElement event, but their order is not guaranteed.

**Parameters**

- **prefix** (*Optional[str]*) –
- **namespace** (*str*) –

**Return type**

*None*

**class** rdflib.plugins.parsers.rdfxml.**RDFXMLParser**

Bases: *Parser*

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.rdfxml', '__init__':  
<function RDFXMLParser.__init__>, 'parse': <function RDFXMLParser.parse>,  
'__dict__': <attribute '__dict__' of 'RDFXMLParser' objects>, '__weakref__':  
<attribute '__weakref__' of 'RDFXMLParser' objects>, '__doc__': None,  
'__annotations__': {}})
```

```
__init__()
```

```
__module__ = 'rdflib.plugins.parsers.rdfxml'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
parse(source, sink, **args)
```

#### Parameters

- **source** (*InputSource*) –
- **sink** (*Graph*) –
- **args** (*Any*) –

#### Return type

*None*

```
rdflib.plugins.parsers.rdfxml.create_parser(target, store)
```

#### Parameters

- **target** (*InputSource*) –
- **store** (*Graph*) –

#### Return type

*XMLReader*

### rdflib.plugins.parsers.trig module

```
class rdflib.plugins.parsers.trig.TrigParser
```

Bases: *Parser*

An RDFLib parser for TriG

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.trig', '__doc__':  
'\n An RDFLib parser for TriG\n\n ', '__init__': <function TrigParser.__init__>,  
'parse': <function TrigParser.parse>, '__dict__': <attribute '__dict__' of  
'TrigParser' objects>, '__weakref__': <attribute '__weakref__' of 'TrigParser'  
objects>, '__annotations__': {}})
```

```
__init__()
```

```
__module__ = 'rdflib.plugins.parsers.trig'
```

```
__weakref__
```

list of weak references to the object (if defined)



**parse**(*source*, *graph*, *encoding*='utf-8')

**Parameters**

- **source** (*InputSource*) –
- **graph** (*Graph*) –
- **encoding** (*str*) –

**Return type**

*None*

```
class rdflib.plugins.parsers.trig.TrigSinkParser(store, openFormula=None, thisDoc="",
                                                baseURI=None, genPrefix="", why=None,
                                                turtle=False)
```

Bases: *SinkParser*

**Parameters**

- **store** (*RDFSink*) –
- **openFormula** (*Optional[Formula]*) –
- **thisDoc** (*str*) –
- **baseURI** (*Optional[str]*) –
- **genPrefix** (*str*) –
- **why** (*Optional[Callable[[], None]]*) –
- **turtle** (*bool*) –

```
__module__ = 'rdflib.plugins.parsers.trig'
```

**directiveOrStatement**(*argstr*, *h*)

**Parameters**

- **argstr** (*str*) –
- **h** (*int*) –

**Return type**

*int*

**graph**(*argstr*, *i*)

Parse trig graph, i.e.

```
<urn:graphname> = { .. triples .. }
```

return -1 if it doesn't look like a graph-decl raise Exception if it looks like a graph, but isn't.

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –

**Return type**

*int*

**labelOrSubject**(*argstr*, *i*, *res*)

**Parameters**

- **argstr** (*str*) –
- **i** (*int*) –
- **res** (*MutableSequence[Any]*) –

**Return type**

*int*

`rdflib.plugins.parsers.trig.becauseSubGraph(*args, **kwargs)`

### **rdflib.plugins.parsers.trix module**

A TriX parser for RDFLib

**class** `rdflib.plugins.parsers.trix.TriXHandler`(*store*)

Bases: *ContentHandler*

An Sax Handler for TriX. See <http://sw.nokia.com/trix/>

**Parameters**

**store** (*Store*) –

**\_\_init\_\_**(*store*)

**Parameters**

**store** (*Store*) –

**\_\_module\_\_** = `'rdflib.plugins.parsers.trix'`

**characters**(*content*)

Receive notification of character data.

The Parser will call this method to report each chunk of character data. SAX parsers may return all contiguous character data in a single chunk, or they may split it into several chunks; however, all of the characters in any single event must come from the same external entity so that the Locator provides useful information.

**Parameters**

**content** (*str*) –

**Return type**

*None*

**endElementNS**(*name, qname*)

Signals the end of an element in namespace mode.

The name parameter contains the name of the element type, just as with the startElementNS event.

**Parameters**

**name** (*Tuple[Optional[str], str]*) –

**Return type**

*None*

**endPrefixMapping**(*prefix*)

End the scope of a prefix-URI mapping.

See startPrefixMapping for details. This event will always occur after the corresponding endElement event, but the order of endPrefixMapping events is not otherwise guaranteed.

**Parameters**

**prefix** (*Optional[str]*) –

**Return type**

`None`

**error**(*message*)

**Parameters**

**message** (`str`) –

**Return type**

`NoReturn`

**get\_bnode**(*label*)

**Parameters**

**label** (`str`) –

**Return type**

`BNode`

**ignorableWhitespace**(*content*)

Receive notification of ignorable whitespace in element content.

Validating Parsers must use this method to report each chunk of ignorable whitespace (see the W3C XML 1.0 recommendation, section 2.10): non-validating parsers may also use this method if they are capable of parsing and using content models.

SAX parsers may return all contiguous whitespace in a single chunk, or they may split it into several chunks; however, all of the characters in any single event must come from the same external entity, so that the Locator provides useful information.

**Return type**

`None`

**processingInstruction**(*target*, *data*)

Receive notification of a processing instruction.

The Parser will invoke this method once for each processing instruction found: note that processing instructions may occur before or after the main document element.

A SAX parser should never report an XML declaration (XML 1.0, section 2.8) or a text declaration (XML 1.0, section 4.3.1) using this method.

**Return type**

`None`

**reset**()

**Return type**

`None`

**setDocumentLocator**(*locator*)

Called by the parser to give the application a locator for locating the origin of document events.

SAX parsers are strongly encouraged (though not absolutely required) to supply a locator: if it does so, it must supply the locator to the application by invoking this method before invoking any of the other methods in the DocumentHandler interface.

The locator allows the application to determine the end position of any document-related event, even if the parser is not reporting an error. Typically, the application will use this information for reporting its own errors (such as character content that does not match an application's business rules). The information returned by the locator is probably not sufficient for use with a search engine.

Note that the locator will return correct information only during the invocation of the events in this interface. The application should not attempt to use it at any other time.

**Parameters**

**locator** (*Locator*) –

**startDocument()**

Receive notification of the beginning of a document.

The SAX parser will invoke this method only once, before any other methods in this interface or in DTD-Handler (except for setDocumentLocator).

**Return type**

*None*

**startElementNS**(*name, qname, attrs*)

Signals the start of an element in namespace mode.

The name parameter contains the name of the element type as a (uri, localname) tuple, the qname parameter the raw XML 1.0 name used in the source document, and the attrs parameter holds an instance of the Attributes class containing the attributes of the element.

The uri part of the name tuple is None for elements which have no namespace.

**Parameters**

- **name** (*Tuple[Optional[str], str]*) –
- **attrs** (*AttributesImpl*) –

**Return type**

*None*

**startPrefixMapping**(*prefix, namespace*)

Begin the scope of a prefix-URI Namespace mapping.

The information from this event is not necessary for normal Namespace processing: the SAX XML reader will automatically replace prefixes for element and attribute names when the <http://xml.org/sax/features/namespaces> feature is true (the default).

There are cases, however, when applications need to use prefixes in character data or in attribute values, where they cannot safely be expanded automatically; the start/endPrefixMapping event supplies the information to the application to expand prefixes in those contexts itself, if necessary.

Note that start/endPrefixMapping events are not guaranteed to be properly nested relative to each-other: all startPrefixMapping events will occur before the corresponding startElement event, and all endPrefixMapping events will occur after the corresponding endElement event, but their order is not guaranteed.

**Parameters**

- **prefix** (*Optional[str]*) –
- **namespace** (*str*) –

**Return type**

*None*

**class** rdflib.plugins.parsers.trix.TriXParser

Bases: *Parser*

A parser for TriX. See <http://sw.nokia.com/trix/>

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.parsers.trix', '__doc__':
'A parser for TriX. See http://sw.nokia.com/trix/', '__init__': <function
TriXParser.__init__>, 'parse': <function TriXParser.parse>, '__dict__': <attribute
'__dict__' of 'TriXParser' objects>, '__weakref__': <attribute '__weakref__' of
'TriXParser' objects>, '__annotations__': {}})
```

```
__init__()
```

```
__module__ = 'rdflib.plugins.parsers.trix'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
parse(source, sink, **args)
```

#### Parameters

- **source** (*InputSource*) –
- **sink** (*Graph*) –
- **args** (*Any*) –

#### Return type

*None*

```
rdflib.plugins.parsers.trix.create_parser(store)
```

#### Parameters

**store** (*Store*) –

#### Return type

*XMLReader*

## Module contents

### rdflib.plugins.serializers package

#### Submodules

### rdflib.plugins.serializers.hext module

HextuplesSerializer RDF graph serializer for RDFLib. See <<https://github.com/ontola/hextuples>> for details about the format.

```
class rdflib.plugins.serializers.hext.HextuplesSerializer(store)
```

Bases: *Serializer*

Serializes RDF graphs to NTriples format.

#### Parameters

**store** (*Union[Graph, ConjunctiveGraph]*) –

```
__init__(store)
```

#### Parameters

**store** (*Union[Graph, ConjunctiveGraph]*) –

```
__module__ = 'rdflib.plugins.serializers.hex'
```

**base:** `Optional[str]`

**encoding:** `str`

**serialize**(*stream*, *base=None*, *encoding='utf-8'*, *\*\*kwargs*)

Abstract method

**Parameters**

- **stream** (`IO[bytes]`) –
- **base** (`Optional[str]`) –
- **encoding** (`Optional[str]`) –

**store:** `Graph`

### rdflib.plugins.serializers.jsonld module

This serializer will output an RDF Graph as a JSON-LD formatted document. See:

<http://json-ld.org/>

Example usage:

```
>>> from rdflib import Graph
>>> testrdf = '''
... @prefix dc: <http://purl.org/dc/terms/> .
... <http://example.org/about>
...   dc:title "Someone's Homepage"@en .
... '''

>>> g = Graph().parse(data=testrdf, format='n3')

>>> print(g.serialize(format='json-ld', indent=4))
[
  {
    "@id": "http://example.org/about",
    "http://purl.org/dc/terms/title": [
      {
        "@language": "en",
        "@value": "Someone's Homepage"
      }
    ]
  }
]
```

**class** `rdflib.plugins.serializers.jsonld.JsonLDSerializer`(*store*)

Bases: `Serializer`

**Parameters**

**store** (`Graph`) –

```
__init__(store)
```

Parameters

**store** (*Graph*) –

```
__module__ = 'rdflib.plugins.serializers.jsonld'
```

**base:** *Optional[str]*

**encoding:** *str*

```
serialize(stream, base=None, encoding=None, **kwargs)
```

Abstract method

Parameters

- **stream** (*IO[bytes]*) –
- **base** (*Optional[str]*) –
- **encoding** (*Optional[str]*) –

**store:** *Graph*

```
rdflib.plugins.serializers.jsonld.from_rdf(graph, context_data=None, base=None,
                                           use_native_types=False, use_rdf_type=False,
                                           auto_compact=False, startnode=None, index=False)
```

### rdflib.plugins.serializers.longturtle module

LongTurtle RDF graph serializer for RDFLib. See <<http://www.w3.org/TeamSubmission/turtle/>> for syntax specification.

This variant, longturtle as opposed to just turtle, makes some small format changes to turtle - the original turtle serializer. It:

- uses PREFIX instead of @prefix
- uses BASE instead of @base
- adds a new line at RDF.type, or ‘a’
- adds a newline and an indent for all triples with more than one object (object list)
- **adds a new line and ‘;’ for the last triple in a set with ‘.’**  
on the start of the next line
- uses default encoding (encode()) is used instead of “latin-1”
- Nicholas Car, 2023

```
class rdflib.plugins.serializers.longturtle.LongTurtleSerializer(store)
```

Bases: *RecursiveSerializer*

```
__init__(store)
```

```
__module__ = 'rdflib.plugins.serializers.longturtle'
```

```
addNamespace(prefix, namespace)
```

**base:** *Optional[str]*

```
doList(l_)
encoding: str
endDocument()
getQName(uri, gen_prefix=True)
indentString = ' '
isValidList(l_)
    Checks if l is a valid RDF list, i.e. no nodes have other properties.
label(node, position)
objectList(objects)
p_default(node, position, newline=False)
p_squared(node, position)
path(node, position, newline=False)
predicateList(subject, newline=False)
preprocessTriple(triple)
reset()
s_default(subject)
s_squared(subject)
serialize(stream, base=None, encoding=None, spacious=None, **args)
    Abstract method
short_name = 'longturtle'
startDocument()
statement(subject)
store: Graph
verb(node, newline=False)
```

### rdflib.plugins.serializers.n3 module

Notation 3 (N3) RDF graph serializer for RDFLib.

```
class rdflib.plugins.serializers.n3.N3Serializer(store, parent=None)
```

Bases: [\*TurtleSerializer\*](#)

#### Parameters

**store** ([\*Graph\*](#)) –

**\_\_init\_\_**(store, parent=None)

#### Parameters

**store** ([\*Graph\*](#)) –



```

__module__ = 'rdflib.plugins.serializers.n3'

base: Optional[str]

encoding: str

endDocument()

getQName(uri, gen_prefix=True)

indent(modifier=0)
    Returns indent string multiplied by the depth

p_clause(node, position)

path(node, position, newline=False)

preprocessTriple(triple)

reset()

s_clause(subject)

short_name = 'n3'

statement(subject)

store: Graph

```

### rdflib.plugins.serializers.nquads module

```

class rdflib.plugins.serializers.nquads.NQuadsSerializer(store)
    Bases: Serializer

    Parameters
        store (Graph) –

    __init__(store)

    Parameters
        store (Graph) –

    __module__ = 'rdflib.plugins.serializers.nquads'

    base: Optional[str]

    encoding: str

    serialize(stream, base=None, encoding=None, **args)
        Abstract method

    Parameters
        • stream (IO[bytes]) –
        • base (Optional[str]) –
        • encoding (Optional[str]) –

    store: Graph

```

**rdflib.plugins.serializers.nt module**

```
class rdflib.plugins.serializers.nt.NTSerializer(store)
```

Bases: *Serializer*

Serializes RDF graphs to NTriples format.

**Parameters**

**store** (*Graph*) –

**\_\_init\_\_**(*store*)

**Parameters**

**store** (*Graph*) –

**\_\_module\_\_** = 'rdflib.plugins.serializers.nt'

**base**: *Optional*[*str*]

**encoding**: *str*

**serialize**(*stream*, *base=None*, *encoding='utf-8'*, *\*\*args*)

Abstract method

**Parameters**

- **stream** (*IO*[*bytes*]) –
- **base** (*Optional*[*str*]) –
- **encoding** (*Optional*[*str*]) –

**Return type**

*None*

**store**: *Graph*

**rdflib.plugins.serializers.rdfxml module**

```
class rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer(store, max_depth=3)
```

Bases: *Serializer*

**Parameters**

**store** (*Graph*) –

**\_\_init\_\_**(*store*, *max\_depth=3*)

**Parameters**

**store** (*Graph*) –

**\_\_module\_\_** = 'rdflib.plugins.serializers.rdfxml'

**base**: *Optional*[*str*]

**encoding**: *str*

**predicate**(*predicate*, *object*, *depth=1*)

**serialize**(*stream*, *base=None*, *encoding=None*, *\*\*args*)

Abstract method

**Parameters**

- **stream** (*IO[bytes]*) –
- **base** (*Optional[str]*) –
- **encoding** (*Optional[str]*) –

**store:** *Graph*

**subject**(*subject*, *depth=1*)

**Parameters**

- **subject** (*IdentifiedNode*) –
- **depth** (*int*) –

**class** `rdflib.plugins.serializers.rdfxml.XMLSerializer`(*store*)

Bases: *Serializer*

**Parameters**

**store** (*Graph*) –

**\_\_init\_\_**(*store*)

**Parameters**

**store** (*Graph*) –

**\_\_module\_\_** = `'rdflib.plugins.serializers.rdfxml'`

**base:** *Optional[str]*

**encoding:** *str*

**predicate**(*predicate*, *object*, *depth=1*)

**serialize**(*stream*, *base=None*, *encoding=None*, *\*\*args*)

Abstract method

**Parameters**

- **stream** (*IO[bytes]*) –
- **base** (*Optional[str]*) –
- **encoding** (*Optional[str]*) –

**store:** *Graph*

**subject**(*subject*, *depth=1*)

`rdflib.plugins.serializers.rdfxml.fix`(*val*)

strip off `_`: from nodeIDs... as they are not valid NCNames

**rdflib.plugins.serializers.trig module**

Trig RDF graph serializer for RDFLib. See <<http://www.w3.org/TR/trig/>> for syntax specification.

```
class rdflib.plugins.serializers.trig.TrigSerializer(store)
    Bases: TurtleSerializer

    Parameters
        store (Union[Graph, ConjunctiveGraph]) –

    __init__(store)

    Parameters
        store (Union[Graph, ConjunctiveGraph]) –

    __module__ = 'rdflib.plugins.serializers.trig'

    base: Optional[str]

    encoding: str

    indentString = ' '

    preprocess()

    Return type
        None

    reset()

    Return type
        None

    serialize(stream, base=None, encoding=None, spacious=None, **args)
        Abstract method

    Parameters
        • stream (IO[bytes]) –
        • base (Optional[str]) –
        • encoding (Optional[str]) –
        • spacious (Optional[bool]) –

    short_name = 'trig'

    store: Graph
```

**rdflib.plugins.serializers.trix module**

```
class rdflib.plugins.serializers.trix.TriXSerializer(store)
    Bases: Serializer

    Parameters
        store (Graph) –
```

```

__init__(store)

    Parameters
        store (Graph) –

__module__ = 'rdflib.plugins.serializers.trix'

base: Optional[str]

encoding: str

serialize(stream, base=None, encoding=None, **args)
    Abstract method

    Parameters
        • stream (IO[bytes]) –
        • base (Optional[str]) –
        • encoding (Optional[str]) –

store: Graph

```

### rdflib.plugins.serializers.turtle module

Turtle RDF graph serializer for RDFLib. See <<http://www.w3.org/TeamSubmission/turtle/>> for syntax specification.

```
class rdflib.plugins.serializers.turtle.RecursiveSerializer(store)
```

Bases: *Serializer*

```

__init__(store)

__module__ = 'rdflib.plugins.serializers.turtle'

addNamespace(prefix, uri)

base: Optional[str]

buildPredicateHash(subject)
    Build a hash key by predicate to a list of objects for the given subject

checkSubject(subject)
    Check to see if the subject should be serialized yet

encoding: str

indent(modifier=0)
    Returns indent string multiplied by the depth

indentString = ' '

isDone(subject)
    Return true if subject is serialized

maxDepth = 10

orderSubjects()

```

```
predicateOrder =
[rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#type'),
rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#label')]

preprocess()

preprocessTriple(spo)

reset()

roundtrip_prefixes = ()

sortProperties(properties)
    Take a hash from predicate uris to lists of values. Sort the lists of values. Return a sorted list of properties.

store: Graph

subjectDone(subject)
    Mark a subject as done.

topClasses = [rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#Class')]

write(text)
    Write text in given encoding.

class rdflib.plugins.serializers.turtle.TurtleSerializer(store)
    Bases: RecursiveSerializer
    __init__(store)
    __module__ = 'rdflib.plugins.serializers.turtle'
    addNamespace(prefix, namespace)
    base: Optional[str]
    doList(l_)
    encoding: str
    endDocument()
    getQName(uri, gen_prefix=True)
    indentString = ' '
    isValidList(l_)
        Checks if l is a valid RDF list, i.e. no nodes have other properties.
    label(node, position)
    objectList(objects)
    p_default(node, position, newline=False)
    p_squared(node, position, newline=False)
    path(node, position, newline=False)
    predicateList(subject, newline=False)
```

```

preprocessTriple(triple)

reset()

s_default(subject)

s_squared(subject)

serialize(stream, base=None, encoding=None, spacious=None, **args)
    Abstract method

short_name = 'turtle'

startDocument()

statement(subject)

store: Graph

verb(node, newline=False)

```

### rdflib.plugins.serializers.xmlwriter module

```

class rdflib.plugins.serializers.xmlwriter.XMLWriter(stream, namespace_manager, encoding=None,
                                                    decl=1, extra_ns=None)

```

Bases: `object`

```

__dict__ = mappingproxy({'__module__': 'rdflib.plugins.serializers.xmlwriter',
                          '__init__': <function XMLWriter.__init__>, '_XMLWriter__get_indent': <function
XMLWriter.__get_indent>, 'indent': <property object>,
                          '_XMLWriter__close_start_tag': <function XMLWriter.__close_start_tag>, 'push':
<function XMLWriter.push>, 'pop': <function XMLWriter.pop>, 'element': <function
XMLWriter.element>, 'namespaces': <function XMLWriter.namespaces>, 'attribute':
<function XMLWriter.attribute>, 'text': <function XMLWriter.text>, 'qname':
<function XMLWriter.qname>, '__dict__': <attribute '__dict__' of 'XMLWriter'
objects>, '__weakref__': <attribute '__weakref__' of 'XMLWriter' objects>,
                          '__doc__': None, '__annotations__': {}})

```

```

__init__(stream, namespace_manager, encoding=None, decl=1, extra_ns=None)

```

```

__module__ = 'rdflib.plugins.serializers.xmlwriter'

```

```

__weakref__

```

list of weak references to the object (if defined)

```

attribute(uri, value)

```

```

element(uri, content, attributes={})

```

Utility method for adding a complete simple element

```

property indent

```

```

namespaces(namespaces=None)

```

```

pop(uri=None)

```

```

push(uri)

```

**qname**(*uri*)

Compute qname for a uri using our extra namespaces, or the given namespace manager

**text**(*text*)

## Module contents

**rdflib.plugins.shared package**

## Subpackages

**rdflib.plugins.shared.jsonld package**

## Submodules

**rdflib.plugins.shared.jsonld.context module**

Implementation of the JSON-LD Context structure. See:

<http://json-ld.org/>

**class** `rdflib.plugins.shared.jsonld.context.Context`(*source=None, base=None, version=None*)

Bases: `object`

### Parameters

- **source** (`Optional[Any]`) –
- **base** (`Optional[str]`) –
- **version** (`Optional[float]`) –



```

__dict__ = mappingproxy({'__module__': 'rdflib.plugins.shared.jsonld.context',
'__init__': <function Context.__init__>, 'base': <property object>, 'subcontext':
<function Context.subcontext>, '_subcontext': <function Context._subcontext>,
'clear': <function Context._clear>, 'get_context_for_term': <function
Context.get_context_for_term>, 'get_context_for_type': <function
Context.get_context_for_type>, 'get_id': <function Context.get_id>, 'get_type':
<function Context.get_type>, 'get_language': <function Context.get_language>,
'get_value': <function Context.get_value>, 'get_graph': <function
Context.get_graph>, 'get_list': <function Context.get_list>, 'get_set': <function
Context.get_set>, 'get_rev': <function Context.get_rev>, '_get': <function
Context._get>, 'get_key': <function Context.get_key>, 'get_keys': <function
Context.get_keys>, 'lang_key': <property object>, 'id_key': <property object>,
'type_key': <property object>, 'value_key': <property object>, 'list_key':
<property object>, 'rev_key': <property object>, 'graph_key': <property object>,
'add_term': <function Context.add_term>, 'find_term': <function
Context.find_term>, 'resolve': <function Context.resolve>, 'resolve_iri':
<function Context.resolve_iri>, 'isblank': <function Context.isblank>, 'expand':
<function Context.expand>, 'shrink_iri': <function Context.shrink_iri>,
'to_symbol': <function Context.to_symbol>, 'load': <function Context.load>,
'_accept_term': <function Context._accept_term>, '_prep_sources': <function
Context._prep_sources>, '_fetch_context': <function Context._fetch_context>,
'_read_source': <function Context._read_source>, '_read_term': <function
Context._read_term>, '_rec_expand': <function Context._rec_expand>, '_prep_expand':
<function Context._prep_expand>, '_get_source_id': <function
Context._get_source_id>, '_term_dict': <function Context._term_dict>, 'to_dict':
<function Context.to_dict>, '__dict__': <attribute '__dict__' of 'Context'
objects>, '__weakref__': <attribute '__weakref__' of 'Context' objects>, '__doc__':
None, '__annotations__': {'version': 'float', 'vocab': 'Optional[str]', '_base':
'Optional[str]', 'terms': 'Dict[str, Any]', '_alias': 'Dict[str, List[str]]',
'_lookup': 'Dict[Tuple[str, Any, Union[Defined, str], bool], Term]', '_prefixes':
'Dict[str, Any]', 'parent': 'Optional[Context]', '_context_cache': 'Dict[str,
Any]'}}})

```

```
__init__(source=None, base=None, version=None)
```

#### Parameters

- **source** ([Optional\[Any\]](#)) –
- **base** ([Optional\[str\]](#)) –
- **version** ([Optional\[float\]](#)) –

```
__module__ = 'rdflib.plugins.shared.jsonld.context'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
add_term(name, idref, coercion=0, container=0, index=None, language=0, reverse=False, context=0,
         prefix=None, protected=False)
```

#### Parameters

- **name** ([str](#)) –
- **idref** ([str](#)) –
- **coercion** ([Union\[Defined, str\]](#)) –

- **container** (`Union[Collection[Any], str, Defined]`) –
- **index** (`Union[str, Defined, None]`) –
- **language** (`Union[str, Defined, None]`) –
- **reverse** (`bool`) –
- **context** (`Any`) –
- **prefix** (`Optional[bool]`) –
- **protected** (`bool`) –

**property base:** `str | None`

**expand**(*term\_curie\_or\_iri*, *use\_vocab=True*)

**Parameters**

- **term\_curie\_or\_iri** (`Any`) –
- **use\_vocab** (`bool`) –

**Return type**

`Optional[str]`

**find\_term**(*idref*, *coercion=None*, *container=0*, *language=None*, *reverse=False*)

**Parameters**

- **idref** (`str`) –
- **coercion** (`Union[str, Defined, None]`) –
- **container** (`Union[Defined, str]`) –
- **language** (`Optional[str]`) –
- **reverse** (`bool`) –

**get\_context\_for\_term**(*term*)

**Parameters**

**term** (`Optional[Term]`) –

**Return type**

`Context`

**get\_context\_for\_type**(*node*)

**Parameters**

**node** (`Any`) –

**Return type**

`Optional[Context]`

**get\_graph**(*obj*)

**Parameters**

**obj** (`Dict[str, Any]`) –

**Return type**

`Any`

**get\_id**(*obj*)

**Parameters**

**obj** (`Dict[str, Any]`) –

**Return type**

`Any`

**get\_key**(*key*)

**Parameters**

**key** (`str`) –

**Return type**

`str`

**get\_keys**(*key*)

**Parameters**

**key** (`str`) –

**Return type**

`Generator[str, None, None]`

**get\_language**(*obj*)

**Parameters**

**obj** (`Dict[str, Any]`) –

**Return type**

`Any`

**get\_list**(*obj*)

**Parameters**

**obj** (`Dict[str, Any]`) –

**Return type**

`Any`

**get\_rev**(*obj*)

**Parameters**

**obj** (`Dict[str, Any]`) –

**Return type**

`Any`

**get\_set**(*obj*)

**Parameters**

**obj** (`Dict[str, Any]`) –

**Return type**

`Any`

**get\_type**(*obj*)

**Parameters**

**obj** (`Dict[str, Any]`) –

**Return type**

`Any`

**get\_value**(*obj*)

Parameters

**obj** (`Dict[str, Any]`) –

Return type

`Any`

**property graph\_key**

**property id\_key**

**isblank**(*ref*)

Parameters

**ref** (`str`) –

Return type

`bool`

**property lang\_key**

**property list\_key**

**load**(*source*, *base=None*, *referenced\_contexts=None*)

Parameters

- **source** (`Union[List[Any], Any, None]`) –
- **base** (`Optional[str]`) –
- **referenced\_contexts** (`Optional[Set[Any]]`) –

**resolve**(*curie\_or\_iri*)

Parameters

**curie\_or\_iri** (`str`) –

Return type

`str`

**resolve\_iri**(*iri*)

Parameters

**iri** (`str`) –

Return type

`str`

**property rev\_key**

**shrink\_iri**(*iri*)

Parameters

**iri** (`str`) –

Return type

`str`

**subcontext**(*source*, *propagate=True*)

Parameters

- **source** (`Any`) –

- **propagate** (*bool*) –

**Return type**  
*Context*

**to\_dict()**

Returns a dictionary representation of the context that can be serialized to JSON.

**Return type**  
*Dict[str, Any]*

**Returns**  
a dictionary representation of the context.

**to\_symbol(*iri*)**

**Parameters**  
**iri** (*str*) –

**Return type**  
*Optional[str]*

**property type\_key**

**property value\_key**

**class** `rdflib.plugins.shared.jsonld.context.Defined`

Bases: *int*

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.shared.jsonld.context',
'__dict__': <attribute '__dict__' of 'Defined' objects>, '__doc__': None,
'__annotations__': {}})
```

```
__module__ = 'rdflib.plugins.shared.jsonld.context'
```

**class** `rdflib.plugins.shared.jsonld.context.Term(id, name, type, container, index, language, reverse, context, prefix, protected)`

Bases: *tuple*

**\_\_getnewargs\_\_()**

Return self as a plain tuple. Used by copy and pickle.

```
__module__ = 'rdflib.plugins.shared.jsonld.context'
```

```
static __new__(_cls, id, name, type=0, container=0, index=0, language=0, reverse=False, context=0,
prefix=False, protected=False)
```

Create new instance of Term(*id, name, type, container, index, language, reverse, context, prefix, protected*)

**\_\_repr\_\_()**

Return a nicely formatted representation string

```
__slots__ = ()
```

**container**

Alias for field number 3

**context**

Alias for field number 7

**id**  
Alias for field number 0

**index**  
Alias for field number 4

**language**  
Alias for field number 5

**name**  
Alias for field number 1

**prefix**  
Alias for field number 8

**protected**  
Alias for field number 9

**reverse**  
Alias for field number 6

**type**  
Alias for field number 2

### rdflib.plugins.shared.jsonld.errors module

**exception** rdflib.plugins.shared.jsonld.errors.JSONLDException

Bases: `ValueError`

**\_\_module\_\_** = 'rdflib.plugins.shared.jsonld.errors'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

### rdflib.plugins.shared.jsonld.keys module

### rdflib.plugins.shared.jsonld.util module

rdflib.plugins.shared.jsonld.util.**context\_from\_urlinputsource**(*source*)

Please note that JSON-LD documents served with the application/ld+json media type MUST have all context information, including references to external contexts, within the body of the document. Contexts linked via a <http://www.w3.org/ns/json-ld#context> HTTP Link Header MUST be ignored for such documents.

**Parameters**

**source** (*URLInputSource*) –

**Return type**

`Optional[str]`

rdflib.plugins.shared.jsonld.util.**norm\_url**(*base, url*)

```

>>> norm_url('http://example.org/', '/one')
'http://example.org/one'
>>> norm_url('http://example.org/', '/one#')
'http://example.org/one#'
>>> norm_url('http://example.org/one', 'two')
'http://example.org/two'
>>> norm_url('http://example.org/one/', 'two')
'http://example.org/one/two'
>>> norm_url('http://example.org/', 'http://example.net/one')
'http://example.net/one'
>>> norm_url('http://example.org/', 'http://example.org//one')
'http://example.org//one'

```

**Parameters**

- **base** (*str*) –
- **url** (*str*) –

**Return type***str*

rdflib.plugins.shared.jsonld.util.**source\_to\_json**(*source*)

**Parameters**

**source** (Union[IO[bytes], TextIO, *InputSource*, *str*, bytes, PurePath, None]) –

**Return type***Optional*[Any]

rdflib.plugins.shared.jsonld.util.**split\_iri**(*iri*)

**Parameters**

**iri** (*str*) –

**Return type***Tuple*[*str*, *Optional*[*str*]]**Module contents****Module contents**

rdflib.plugins.sparql package

**Subpackages**

rdflib.plugins.sparql.results package

**Submodules**

rdflib.plugins.sparql.results.csvresults module

```
class rdflib.plugins.sparql.results.csvresults.CSVResultParser
    Bases: ResultParser
    __init__()
    __module__ = 'rdflib.plugins.sparql.results.csvresults'
    convertTerm(t)
        Parameters
            t (str) –
        Return type
            Union[BNode, URIRef, Literal, None]
    parse(source, content_type=None)
        return a Result object
        Parameters
            • source (IO) –
            • content_type (Optional[str]) –
        Return type
            Result
    parseRow(row, v)
        Parameters
            • row (List[str]) –
            • v (List[Variable]) –
        Return type
            Dict[Variable, Union[BNode, URIRef, Literal]]
class rdflib.plugins.sparql.results.csvresults.CSVResultSerializer(result)
    Bases: ResultSerializer
    Parameters
        result (SPARQLResult) –
    __init__(result)
        Parameters
            result (SPARQLResult) –
    __module__ = 'rdflib.plugins.sparql.results.csvresults'
    serialize(stream, encoding='utf-8', **kwargs)
        return a string properly serialized
        Parameters
            • stream (IO) –
            • encoding (str) –
        Return type
            None
```



**serializeTerm**(*term*, *encoding*)

**Parameters**

- **term** (*Optional*[*Identifier*]) –
- **encoding** (*str*) –

**Return type**

*Union*[*str*, *Identifier*]

## rdflib.plugins.sparql.results.graph module

**class** rdflib.plugins.sparql.results.graph.GraphResultParser

Bases: *ResultParser*

**\_\_module\_\_** = 'rdflib.plugins.sparql.results.graph'

**parse**(*source*, *content\_type*)

return a Result object

**Parameters**

- **source** (*IO*) –
- **content\_type** (*Optional*[*str*]) –

**Return type**

*Result*

## rdflib.plugins.sparql.results.jsonresults module

**class** rdflib.plugins.sparql.results.jsonresults.JSONResult(*json*)

Bases: *Result*

**Parameters**

**json** (*Dict*[*str*, *Any*]) –

**\_\_init\_\_**(*json*)

**Parameters**

**json** (*Dict*[*str*, *Any*]) –

**\_\_module\_\_** = 'rdflib.plugins.sparql.results.jsonresults'

**askAnswer**: *Optional*[*bool*]

**graph**: *Optional*['Graph']

**vars**: *Optional*[*List*['Variable']]

variables contained in the result.

**class** rdflib.plugins.sparql.results.jsonresults.JSONResultParser

Bases: *ResultParser*

**\_\_module\_\_** = 'rdflib.plugins.sparql.results.jsonresults'

**parse**(*source*, *content\_type*=None)

return a Result object

**Parameters**

- **source** (IO) –
- **content\_type** (Optional[str]) –

**Return type**

*Result*

**class** rdflib.plugins.sparql.results.jsonresults.JSONResultSerializer(*result*)

Bases: *ResultSerializer*

**Parameters**

**result** (*Result*) –

**\_\_init\_\_**(*result*)

**Parameters**

**result** (*Result*) –

**\_\_module\_\_** = 'rdflib.plugins.sparql.results.jsonresults'

**serialize**(*stream*, *encoding*=None)

return a string properly serialized

**Parameters**

- **stream** (IO) –
- **encoding** (Optional[str]) –

**Return type**

None

rdflib.plugins.sparql.results.jsonresults.parseJsonTerm(*d*)

rdflib object (Literal, URIRef, BNode) for the given json-format dict.

**input is like:**

{ 'type': 'uri', 'value': 'http://famegame.com/2006/01/username' } { 'type': 'literal', 'value': 'drewp' }

**Parameters**

**d** (Dict[str, str]) –

**Return type**

*Identifier*

rdflib.plugins.sparql.results.jsonresults.termToJSON(*self*, *term*)

**Parameters**

- **self** (*JSONResultSerializer*) –
- **term** (Optional[*Identifier*]) –

**Return type**

Optional[Dict[str, str]]

**rdflib.plugins.sparql.results.rdfresults module**

```
class rdflib.plugins.sparql.results.rdfresults.RDFResult(source, **kwargs)
```

Bases: [Result](#)

**Parameters**

- **source** ([Union](#)[[IO](#), [Graph](#)]) –
- **kwargs** ([Any](#)) –

```
__init__(source, **kwargs)
```

**Parameters**

- **source** ([Union](#)[[IO](#), [Graph](#)]) –
- **kwargs** ([Any](#)) –

```
__module__ = 'rdflib.plugins.sparql.results.rdfresults'
```

```
askAnswer: Optional[bool]
```

```
graph: Optional['Graph']
```

```
vars: Optional[List['Variable']]
```

variables contained in the result.

```
class rdflib.plugins.sparql.results.rdfresults.RDFResultParser
```

Bases: [ResultParser](#)

```
__module__ = 'rdflib.plugins.sparql.results.rdfresults'
```

```
parse(source, **kwargs)
```

return a Result object

**Parameters**

- **source** ([Union](#)[[IO](#), [Graph](#)]) –
- **kwargs** ([Any](#)) –

**Return type**

[Result](#)

**rdflib.plugins.sparql.results.tsvresults module**

This implements the Tab Separated SPARQL Result Format

It is implemented with pyparsing, reusing the elements from the SPARQL Parser

```
class rdflib.plugins.sparql.results.tsvresults.TSVResultParser
```

Bases: [ResultParser](#)

```
__module__ = 'rdflib.plugins.sparql.results.tsvresults'
```

```
convertTerm(t)
```

**Parameters**

**t** ([Union](#)[[object](#), [Literal](#), [BNode](#), [CompValue](#), [URIRef](#)]) –

**Return type**`Union[object, BNode, URIRef, Literal, None]`**parse**(*source*, *content\_type*=None)

return a Result object

**Parameters**

- **source** (`IO`) –
- **content\_type** (`Optional[str]`) –

**Return type**`Result`**rdflib.plugins.sparql.results.txtresults module****class** `rdflib.plugins.sparql.results.txtresults.TXTResultSerializer`(*result*)Bases: `ResultSerializer`

A write only QueryResult serializer for text/ascii tables

**Parameters****result** (`Result`) –**\_\_module\_\_** = `'rdflib.plugins.sparql.results.txtresults'`**serialize**(*stream*, *encoding*, *namespace\_manager*=None)

return a text table of query results

**Parameters**

- **stream** (`IO`) –
- **encoding** (`str`) –
- **namespace\_manager** (`Optional[NamespaceManager]`) –

**Return type**`None`**rdflib.plugins.sparql.results.xmlresults module****class** `rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter`(*output*, *encoding*='utf-8')Bases: `object`

Python saxutils-based SPARQL XML Writer

**Parameters**

- **output** (`IO`) –
- **encoding** (`str`) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.results.xmlresults',
'__doc__': '\n Python saxutils-based SPARQL XML Writer\n ', '__init__': <function
SPARQLXMLWriter.__init__>, 'write_header': <function SPARQLXMLWriter.write_header>,
'write_ask': <function SPARQLXMLWriter.write_ask>, 'write_results_header':
<function SPARQLXMLWriter.write_results_header>, 'write_start_result': <function
SPARQLXMLWriter.write_start_result>, 'write_end_result': <function
SPARQLXMLWriter.write_end_result>, 'write_binding': <function
SPARQLXMLWriter.write_binding>, 'close': <function SPARQLXMLWriter.close>,
'__dict__': <attribute '__dict__' of 'SPARQLXMLWriter' objects>, '__weakref__':
<attribute '__weakref__' of 'SPARQLXMLWriter' objects>, '__annotations__': {}})
```

```
__init__(output, encoding='utf-8')
```

#### Parameters

- **output** (*IO*) –
- **encoding** (*str*) –

```
__module__ = 'rdflib.plugins.sparql.results.xmlresults'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
close()
```

#### Return type

*None*

```
write_ask(val)
```

#### Parameters

- **val** (*bool*) –

#### Return type

*None*

```
write_binding(name, val)
```

#### Parameters

- **name** (*Variable*) –
- **val** (*Identifier*) –

#### Return type

*None*

```
write_end_result()
```

#### Return type

*None*

```
write_header(allvarsL)
```

#### Parameters

- **allvarsL** (*Sequence[Variable]*) –

#### Return type

*None*

**write\_results\_header()**

**Return type**

*None*

**write\_start\_result()**

**Return type**

*None*

**class** rdflib.plugins.sparql.results.xmlresults.**XMLResult**(*source, content\_type=None*)

Bases: *Result*

**Parameters**

- **source** (*IO*) –
- **content\_type** (*Optional[str]*) –

**\_\_init\_\_**(*source, content\_type=None*)

**Parameters**

- **source** (*IO*) –
- **content\_type** (*Optional[str]*) –

**\_\_module\_\_** = 'rdflib.plugins.sparql.results.xmlresults'

**askAnswer**: *Optional[bool]*

**graph**: *Optional['Graph']*

**vars**: *Optional[List['Variable']]*

variables contained in the result.

**class** rdflib.plugins.sparql.results.xmlresults.**XMLResultParser**

Bases: *ResultParser*

**\_\_module\_\_** = 'rdflib.plugins.sparql.results.xmlresults'

**parse**(*source, content\_type=None*)

return a Result object

**Parameters**

- **source** (*IO*) –
- **content\_type** (*Optional[str]*) –

**Return type**

*Result*

**class** rdflib.plugins.sparql.results.xmlresults.**XMLResultSerializer**(*result*)

Bases: *ResultSerializer*

**Parameters**

**result** (*Result*) –

**\_\_init\_\_**(*result*)

**Parameters**

**result** (*Result*) –

```
__module__ = 'rdflib.plugins.sparql.results.xmlresults'
```

```
serialize(stream, encoding='utf-8', **kwargs)
```

return a string properly serialized

#### Parameters

- **stream** (*IO*) –
- **encoding** (*str*) –
- **kwargs** (*Any*) –

#### Return type

*None*

```
rdflib.plugins.sparql.results.xmlresults.log = <Logger
```

```
rdflib.plugins.sparql.results.xmlresults (WARNING)>
```

A Parser for SPARQL results in XML:

<http://www.w3.org/TR/rdf-sparql-XMLres/>

Bits and pieces borrowed from: <http://projects.bigasterisk.com/sparqlhttp/>

Authors: Drew Perttula, Gunnar Aastrand Grimnes

```
rdflib.plugins.sparql.results.xmlresults.parseTerm(element)
```

rdflib object (Literal, URIRef, BNode) for the given elementtree element

#### Parameters

**element** (*Element*) –

#### Return type

*Union*[*URIRef*, *Literal*, *BNode*]

## Module contents

Parsers and serializers for SPARQL Result formats

## Submodules

### rdflib.plugins.sparql.aggregates module

```
class rdflib.plugins.sparql.aggregates.Accumulator(aggregation)
```

Bases: *object*

abstract base class for different aggregation functions

#### Parameters

**aggregation** (*CompValue*) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.aggregates',
'__doc__': 'abstract base class for different aggregation functions', '__init__':
<function Accumulator.__init__>, 'dont_care': <function Accumulator.dont_care>,
'use_row': <function Accumulator.use_row>, 'set_value': <function
Accumulator.set_value>, '__dict__': <attribute '__dict__' of 'Accumulator'
objects>, '__weakref__': <attribute '__weakref__' of 'Accumulator' objects>,
'__annotations__': {'get_value': 'Callable[[], Optional[Literal]]', 'update':
"Callable[[FrozenBindings, 'Aggregator'], None]", 'seen': 'Set[Any]'}})
```

**\_\_init\_\_**(*aggregation*)

**Parameters**

**aggregation** (*CompValue*) –

**\_\_module\_\_** = 'rdflib.plugins.sparql.aggregates'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**dont\_care**(*row*)

skips distinct test

**Parameters**

**row** (*FrozenBindings*) –

**Return type**

*bool*

**set\_value**(*bindings*)

sets final value in bindings

**Parameters**

**bindings** (*MutableMapping*[*Variable*, *Identifier*]) –

**Return type**

*None*

**use\_row**(*row*)

tests distinct with set

**Parameters**

**row** (*FrozenBindings*) –

**Return type**

*bool*

**class** rdflib.plugins.sparql.aggregates.**Aggregator**(*aggregations*)

Bases: *object*

combines different Accumulator objects

**Parameters**

**aggregations** (*List*[*CompValue*]) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.aggregates',
'__doc__': 'combines different Accumulator objects', 'accumulator_classes':
{'Aggregate_Count': <class 'rdflib.plugins.sparql.aggregates.Counter'>,
'Aggregate_Sample': <class 'rdflib.plugins.sparql.aggregates.Sample'>,
'Aggregate_Sum': <class 'rdflib.plugins.sparql.aggregates.Sum'>, 'Aggregate_Avg':
<class 'rdflib.plugins.sparql.aggregates.Average'>, 'Aggregate_Min': <class
'rdflib.plugins.sparql.aggregates.Minimum'>, 'Aggregate_Max': <class
'rdflib.plugins.sparql.aggregates.Maximum'>, 'Aggregate_GroupConcat': <class
'rdflib.plugins.sparql.aggregates.GroupConcat'>}, '__init__': <function
Aggregator.__init__>, 'update': <function Aggregator.update>, 'get_bindings':
<function Aggregator.get_bindings>, '__dict__': <attribute '__dict__' of
'Aggregator' objects>, '__weakref__': <attribute '__weakref__' of 'Aggregator'
objects>, '__annotations__': {'bindings': 'Dict[Variable, Identifier]',
'accumulators': 'Dict[str, Accumulator]'}})
```



```

__init__(aggregations)

    Parameters
        aggregations (List[CompValue]) –

__module__ = 'rdflib.plugins.sparql.aggregates'

__weakref__
    list of weak references to the object (if defined)

accumulator_classes = {'Aggregate_Avg': <class
'rdflib.plugins.sparql.aggregates.Average'>, 'Aggregate_Count': <class
'rdflib.plugins.sparql.aggregates.Counter'>, 'Aggregate_GroupConcat': <class
'rdflib.plugins.sparql.aggregates.GroupConcat'>, 'Aggregate_Max': <class
'rdflib.plugins.sparql.aggregates.Maximum'>, 'Aggregate_Min': <class
'rdflib.plugins.sparql.aggregates.Minimum'>, 'Aggregate_Sample': <class
'rdflib.plugins.sparql.aggregates.Sample'>, 'Aggregate_Sum': <class
'rdflib.plugins.sparql.aggregates.Sum'>}

get_bindings()
    calculate and set last values

    Return type
        Mapping[Variable, Identifier]

update(row)
    update all own accumulators

    Parameters
        row (FrozenBindings) –

    Return type
        None

class rdflib.plugins.sparql.aggregates.Average(aggregation)
    Bases: Accumulator

    Parameters
        aggregation (CompValue) –

    __init__(aggregation)

    Parameters
        aggregation (CompValue) –

    __module__ = 'rdflib.plugins.sparql.aggregates'

get_value()

    Return type
        Literal

seen: Set[Any]

update(row, aggregator)

    Parameters
        • row (FrozenBindings) –

```

- **aggregator** (*Aggregator*) –

**Return type**

*None*

**class** `rdflib.plugins.sparql.aggregates.Counter`(*aggregation*)

Bases: *Accumulator*

**Parameters**

**aggregation** (*CompValue*) –

**\_\_init\_\_**(*aggregation*)

**Parameters**

**aggregation** (*CompValue*) –

**\_\_module\_\_** = 'rdflib.plugins.sparql.aggregates'

**eval\_full\_row**(*row*)

**Parameters**

**row** (*FrozenBindings*) –

**Return type**

*FrozenBindings*

**eval\_row**(*row*)

**Parameters**

**row** (*FrozenBindings*) –

**Return type**

*Identifier*

**get\_value**()

**Return type**

*Literal*

**seen:** *Set*[*Any*]

**update**(*row*, *aggregator*)

**Parameters**

- **row** (*FrozenBindings*) –

- **aggregator** (*Aggregator*) –

**Return type**

*None*

**use\_row**(*row*)

tests distinct with set

**Parameters**

**row** (*FrozenBindings*) –

**Return type**

*bool*

```

class rdflib.plugins.sparql.aggregates.Extremum(aggregation)
    Bases: Accumulator
    abstract base class for Minimum and Maximum

    Parameters
        aggregation (CompValue) –

    __init__(aggregation)

    Parameters
        aggregation (CompValue) –

    __module__ = 'rdflib.plugins.sparql.aggregates'

    get_value: Callable[[], Optional[Literal]]

    seen: Set[Any]

    set_value(bindings)
        sets final value in bindings

    Parameters
        bindings (MutableMapping[Variable, Identifier]) –

    Return type
        None

    update(row, aggregator)

    Parameters
        • row (FrozenBindings) –
        • aggregator (Aggregator) –

    Return type
        None

class rdflib.plugins.sparql.aggregates.GroupConcat(aggregation)
    Bases: Accumulator

    Parameters
        aggregation (CompValue) –

    __annotations__ = {'value': 'List[Literal]'}

    __init__(aggregation)

    Parameters
        aggregation (CompValue) –

    __module__ = 'rdflib.plugins.sparql.aggregates'

    get_value()

    Return type
        Literal

    update(row, aggregator)

    Parameters
        • row (FrozenBindings) –

```

- **aggregator** (*Aggregator*) –

**Return type**

*None*

**value:** *List[Literal]*

**class** `rdflib.plugins.sparql.aggregates.Maximum`(*aggregation*)

Bases: *Extremum*

**Parameters**

**aggregation** (*CompValue*) –

**\_\_module\_\_** = `'rdflib.plugins.sparql.aggregates'`

**compare**(*val1*, *val2*)

**Parameters**

• **val1** (*TypeVar*(*\_ValueT*, *Variable*, *BNode*, *URIRef*, *Literal*)) –

• **val2** (*TypeVar*(*\_ValueT*, *Variable*, *BNode*, *URIRef*, *Literal*)) –

**Return type**

*TypeVar*(*\_ValueT*, *Variable*, *BNode*, *URIRef*, *Literal*)

**get\_value:** *Callable[[], Optional[Literal]]*

**seen:** *Set[Any]*

**value:** *Any*

**class** `rdflib.plugins.sparql.aggregates.Minimum`(*aggregation*)

Bases: *Extremum*

**Parameters**

**aggregation** (*CompValue*) –

**\_\_module\_\_** = `'rdflib.plugins.sparql.aggregates'`

**compare**(*val1*, *val2*)

**Parameters**

• **val1** (*TypeVar*(*\_ValueT*, *Variable*, *BNode*, *URIRef*, *Literal*)) –

• **val2** (*TypeVar*(*\_ValueT*, *Variable*, *BNode*, *URIRef*, *Literal*)) –

**Return type**

*TypeVar*(*\_ValueT*, *Variable*, *BNode*, *URIRef*, *Literal*)

**get\_value:** *Callable[[], Optional[Literal]]*

**seen:** *Set[Any]*

**value:** *Any*

**class** `rdflib.plugins.sparql.aggregates.Sample`(*aggregation*)

Bases: *Accumulator*

takes the first eligible value

**\_\_init\_\_**(*aggregation*)

```
__module__ = 'rdflib.plugins.sparql.aggregates'
```

```
get_value()
```

**Return type**

*None*

```
seen: Set[Any]
```

```
update(row, aggregator)
```

**Parameters**

- **row** (*FrozenBindings*) –
- **aggregator** (*Aggregator*) –

**Return type**

*None*

```
class rdflib.plugins.sparql.aggregates.Sum(aggregation)
```

Bases: *Accumulator*

**Parameters**

**aggregation** (*CompValue*) –

```
__init__(aggregation)
```

**Parameters**

**aggregation** (*CompValue*) –

```
__module__ = 'rdflib.plugins.sparql.aggregates'
```

```
get_value()
```

**Return type**

*Literal*

```
seen: Set[Any]
```

```
update(row, aggregator)
```

**Parameters**

- **row** (*FrozenBindings*) –
- **aggregator** (*Aggregator*) –

**Return type**

*None*

```
rdflib.plugins.sparql.aggregates.type_safe_numbers(*args)
```

**Parameters**

**args** (*Union*[*Decimal*, *float*, *int*]) –

**Return type**

*Iterable*[*Union*[*float*, *int*]]

**rdflib.plugins.sparql.algebra module**

`rdflib.plugins.sparql.algebra.BGP(triples=None)`

**Parameters**

**triples** (`Optional[List[Tuple[Identifier, Identifier, Identifier]]]`) –

**Return type**

*CompValue*

**exception** `rdflib.plugins.sparql.algebra.ExpressionNotCoveredException`

Bases: `Exception`

**\_\_module\_\_** = `'rdflib.plugins.sparql.algebra'`

**\_\_weakref\_\_**

list of weak references to the object (if defined)

`rdflib.plugins.sparql.algebra.Extend(p, expr, var)`

**Parameters**

- **p** (*CompValue*) –
- **expr** (`Union[Identifier, Expr]`) –
- **var** (*Variable*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.Filter(expr, p)`

**Parameters**

- **expr** (*Expr*) –
- **p** (*CompValue*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.Graph(term, graph)`

**Parameters**

- **term** (*Identifier*) –
- **graph** (*CompValue*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.Group(p, expr=None)`

**Parameters**

- **p** (*CompValue*) –
- **expr** (`Optional[List[Variable]]`) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.Join(p1, p2)`

**Parameters**

- **p1** (*CompValue*) –
- **p2** (*Optional[CompValue]*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.LeftJoin(p1, p2, expr)`

**Parameters**

- **p1** (*CompValue*) –
- **p2** (*CompValue*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.Minus(p1, p2)`

**Parameters**

- **p1** (*CompValue*) –
- **p2** (*CompValue*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.OrderBy(p, expr)`

**Parameters**

- **p** (*CompValue*) –
- **expr** (*List[CompValue]*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.Project(p, PV)`

**Parameters**

- **p** (*CompValue*) –
- **PV** (*List[Variable]*) –

**Return type**

*CompValue*

**exception** `rdflib.plugins.sparql.algebra.StopTraversal(rv)`

Bases: *Exception*

**Parameters**

**rv** (*bool*) –

`__init__(rv)`

**Parameters**

**rv** (*bool*) –

```
__module__ = 'rdflib.plugins.sparql.algebra'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
rdflib.plugins.sparql.algebra.ToMultiSet(p)
```

**Parameters**

**p** (`Union[List[Dict[Variable, str]], CompValue]`) –

**Return type**

`CompValue`

```
rdflib.plugins.sparql.algebra.Union(p1, p2)
```

**Parameters**

- **p1** (`CompValue`) –

- **p2** (`CompValue`) –

**Return type**

`CompValue`

```
rdflib.plugins.sparql.algebra.Values(res)
```

**Parameters**

**res** (`List[Dict[Variable, str]]`) –

**Return type**

`CompValue`

```
rdflib.plugins.sparql.algebra.analyse(n, children)
```

Some things can be lazily joined. This propegates whether they can up the tree and sets lazy flags for all joins

**Parameters**

- **n** (`Any`) –

- **children** (`Any`) –

**Return type**

`bool`

```
rdflib.plugins.sparql.algebra.collectAndRemoveFilters(parts)
```

FILTER expressions apply to the whole group graph pattern in which they appear.

<http://www.w3.org/TR/sparql11-query/#sparqlCollectFilters>

**Parameters**

**parts** (`List[CompValue]`) –

**Return type**

`Optional[Expr]`

```
rdflib.plugins.sparql.algebra.pprintAlgebra(q)
```

**Return type**

`None`

```
rdflib.plugins.sparql.algebra.reorderTriples(l_)
```

Reorder triple patterns so that we execute the ones with most bindings first



**Parameters**

`l_ (Iterable[Tuple[Identifier, Identifier, Identifier]])` –

**Return type**

`List[Tuple[Identifier, Identifier, Identifier]]`

`rdflib.plugins.sparql.algebra.simplify(n)`

Remove joins to empty BGPs

**Parameters**

`n (Any)` –

**Return type**

`Optional[CompValue]`

`rdflib.plugins.sparql.algebra.translate(q)`

<http://www.w3.org/TR/sparql11-query/#convertSolMod>

**Parameters**

`q (CompValue)` –

**Return type**

`Tuple[Optional[CompValue], List[Variable]]`

`rdflib.plugins.sparql.algebra.translateAggregates(q, M)`

**Parameters**

• `q (CompValue)` –

• `M (CompValue)` –

**Return type**

`Tuple[CompValue, List[Tuple[Variable, Variable]]]`

`rdflib.plugins.sparql.algebra.translateAlgebra(query_algebra)`

Translates a SPARQL 1.1 algebra tree into the corresponding query string.

**Parameters**

`query_algebra (Query)` – An algebra returned by *translateQuery*.

**Return type**

`str`

**Returns**

The query form generated from the SPARQL 1.1 algebra tree for SELECT queries.

`rdflib.plugins.sparql.algebra.translateExists(e)`

Translate the graph pattern used by EXISTS and NOT EXISTS <http://www.w3.org/TR/sparql11-query/#sparqlCollectFilters>

**Parameters**

`e (Union[Expr, Literal, Variable, URIRef])` –

**Return type**

`Union[Expr, Literal, Variable, URIRef]`

`rdflib.plugins.sparql.algebra.translateGraphGraphPattern(graphPattern)`

**Parameters**

`graphPattern (CompValue)` –

**Return type**

`CompValue`

`rdflib.plugins.sparql.algebra.translateGroupGraphPattern(graphPattern)`

<http://www.w3.org/TR/sparql11-query/#convertGraphPattern>

**Parameters**

**graphPattern** (*CompValue*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.translateGroupOrUnionGraphPattern(graphPattern)`

**Parameters**

**graphPattern** (*CompValue*) –

**Return type**

*Optional[CompValue]*

`rdflib.plugins.sparql.algebra.translateInlineData(graphPattern)`

**Parameters**

**graphPattern** (*CompValue*) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.algebra.translatePName(p, prologue)`

Expand prefixed/relative URIs

**Parameters**

- **p** (*Union[CompValue, str]*) –
- **prologue** (*Prologue*) –

**Return type**

*Optional[Identifier]*

`rdflib.plugins.sparql.algebra.translatePath(p)`

Translate PropertyPath expressions

**Parameters**

**p** (*Union[CompValue, URIRef]*) –

**Return type**

*Optional[Path]*

`rdflib.plugins.sparql.algebra.translatePrologue(p, base, initNs=None, prologue=None)`

**Parameters**

- **p** (*ParseResults*) –
- **base** (*Optional[str]*) –
- **initNs** (*Optional[Mapping[str, Any]]*) –
- **prologue** (*Optional[Prologue]*) –

**Return type**

*Prologue*

`rdflib.plugins.sparql.algebra.translateQuads(quads)`

**Parameters**

**quads** (*CompValue*) –

**Return type**

`Tuple[List[Tuple[Identifier, Identifier, Identifier]], DefaultDict[str, List[Tuple[Identifier, Identifier, Identifier]]]]`

`rdflib.plugins.sparql.algebra.translateQuery(q, base=None, initNs=None)`

Translate a query-parsetree to a SPARQL Algebra Expression

Return a `rdflib.plugins.sparql.sparql.Query` object

**Parameters**

- **q** (`ParseResults`) –
- **base** (`Optional[str]`) –
- **initNs** (`Optional[Mapping[str, Any]]`) –

**Return type**

`Query`

`rdflib.plugins.sparql.algebra.translateUpdate(q, base=None, initNs=None)`

Returns a list of SPARQL Update Algebra expressions

**Parameters**

- **q** (`CompValue`) –
- **base** (`Optional[str]`) –
- **initNs** (`Optional[Mapping[str, Any]]`) –

**Return type**

`Update`

`rdflib.plugins.sparql.algebra.translateUpdate1(u, prologue)`

**Parameters**

- **u** (`CompValue`) –
- **prologue** (`Prologue`) –

**Return type**

`CompValue`

`rdflib.plugins.sparql.algebra.translateValues(v)`

**Parameters**

**v** (`CompValue`) –

**Return type**

`Union[List[Dict[Variable, str]], CompValue]`

`rdflib.plugins.sparql.algebra.traverse(tree, visitPre=<function <lambda>>, visitPost=<function <lambda>>, complete=None)`

Traverse tree, visit each node with visit function visit function may raise `StopTraversal` to stop traversal if `complete!=None`, it is returned on complete traversal, otherwise the transformed tree is returned

**Parameters**

- **visitPre** (`Callable[[Any], Any]`) –
- **visitPost** (`Callable[[Any], Any]`) –
- **complete** (`Optional[bool]`) –

**Return type**

*Any*

`rdflib.plugins.sparql.algebra.triples(l)`

**Parameters**

**1** (`Union[List[List[Identifier]], List[Tuple[Identifier, Identifier, Identifier]]`) –

**Return type**

`List[Tuple[Identifier, Identifier, Identifier]]`

## rdflib.plugins.sparql.datatypes module

`rdflib.plugins.sparql.datatypes.type_promotion(t1, t2)`

**Parameters**

- **t1** (`URIRef`) –
- **t2** (`Optional[URIRef]`) –

**Return type**

`URIRef`

## rdflib.plugins.sparql.evaluate module

`rdflib.plugins.sparql.evaluate.evalAggregateJoin(ctx, agg)`

**Parameters**

- **ctx** (`QueryContext`) –
- **agg** (`CompValue`) –

**Return type**

`Generator[FrozenBindings, None, None]`

`rdflib.plugins.sparql.evaluate.evalAskQuery(ctx, query)`

**Parameters**

- **ctx** (`QueryContext`) –
- **query** (`CompValue`) –

**Return type**

`Mapping[str, Union[str, bool]]`

`rdflib.plugins.sparql.evaluate.evalBGP(ctx, bgp)`

A basic graph pattern

**Parameters**

- **ctx** (`QueryContext`) –
- **bgp** (`List[Tuple[Identifier, Identifier, Identifier]]`) –

**Return type**

`Generator[FrozenBindings, None, None]`

`rdflib.plugins.sparql.evaluate.evalConstructQuery(ctx, query)`

**Parameters**

- **ctx** (*QueryContext*) –
- **query** (*CompValue*) –

**Return type**

`Mapping[str, Union[str, Graph]]`

`rdflib.plugins.sparql.evaluate.evalDescribeQuery(ctx, query)`

**Parameters**

**ctx** (*QueryContext*) –

**Return type**

`Dict[str, Union[str, Graph]]`

`rdflib.plugins.sparql.evaluate.evalDistinct(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

**Return type**

`Generator[FrozenBindings, None, None]`

`rdflib.plugins.sparql.evaluate.evalExtend(ctx, extend)`

**Parameters**

- **ctx** (*QueryContext*) –
- **extend** (*CompValue*) –

**Return type**

`Generator[FrozenBindings, None, None]`

`rdflib.plugins.sparql.evaluate.evalFilter(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

**Return type**

`Generator[FrozenBindings, None, None]`

`rdflib.plugins.sparql.evaluate.evalGraph(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

**Return type**

`Generator[FrozenBindings, None, None]`

`rdflib.plugins.sparql.evaluate.evalGroup(ctx, group)`

[http://www.w3.org/TR/sparql11-query/#defn\\_algGroup](http://www.w3.org/TR/sparql11-query/#defn_algGroup)

**Parameters**

- **ctx** (*QueryContext*) –
- **group** (*CompValue*) –

`rdflib.plugins.sparql.evaluate.evalJoin(ctx, join)`

**Parameters**

- **ctx** (*QueryContext*) –
- **join** (*CompValue*) –

**Return type**

*Generator[FrozenDict, None, None]*

`rdflib.plugins.sparql.evaluate.evalLazyJoin(ctx, join)`

A lazy join will push the variables bound in the first part to the second part, essentially doing the join implicitly hopefully evaluating much fewer triples

**Parameters**

- **ctx** (*QueryContext*) –
- **join** (*CompValue*) –

**Return type**

*Generator[FrozenBindings, None, None]*

`rdflib.plugins.sparql.evaluate.evalLeftJoin(ctx, join)`

**Parameters**

- **ctx** (*QueryContext*) –
- **join** (*CompValue*) –

**Return type**

*Generator[FrozenBindings, None, None]*

`rdflib.plugins.sparql.evaluate.evalMinus(ctx, minus)`

**Parameters**

- **ctx** (*QueryContext*) –
- **minus** (*CompValue*) –

**Return type**

*Generator[FrozenDict, None, None]*

`rdflib.plugins.sparql.evaluate.evalMultiset(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

`rdflib.plugins.sparql.evaluate.evalOrderBy(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

**Return type**

*Generator[FrozenBindings, None, None]*

`rdflib.plugins.sparql.evaluate.evalPart(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

**Return type**

*Any*

`rdflib.plugins.sparql.evaluate.evalProject(ctx, project)`

**Parameters**

- **ctx** (*QueryContext*) –
- **project** (*CompValue*) –

`rdflib.plugins.sparql.evaluate.evalQuery(graph, query, initBindings=None, base=None)`

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in SERVICE directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Parameters**

- **graph** (*Graph*) –
- **query** (*Query*) –
- **initBindings** (*Optional*[*Mapping*[*str*, *Identifier*]]) –
- **base** (*Optional*[*str*]) –

**Return type**

*Mapping*[*Any*, *Any*]

`rdflib.plugins.sparql.evaluate.evalReduced(ctx, part)`

apply REDUCED to result

REDUCED is not as strict as DISTINCT, but if the incoming rows were sorted it should produce the same result with limited extra memory and time per incoming row.

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

**Return type**

`Generator[FrozenBindings, None, None]`

`rdflib.plugins.sparql.evaluate.evalSelectQuery(ctx, query)`

**Parameters**

- **ctx** (*QueryContext*) –
- **query** (*CompValue*) –

**Return type**

`Mapping[str, Union[str, List[Variable], Iterable[FrozenDict]]]`

`rdflib.plugins.sparql.evaluate.evalServiceQuery(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

`rdflib.plugins.sparql.evaluate.evalSlice(ctx, slice)`

**Parameters**

- **ctx** (*QueryContext*) –
- **slice** (*CompValue*) –

`rdflib.plugins.sparql.evaluate.evalUnion(ctx, union)`

**Parameters**

- **ctx** (*QueryContext*) –
- **union** (*CompValue*) –

**Return type**

`Iterable[FrozenBindings]`

`rdflib.plugins.sparql.evaluate.evalValues(ctx, part)`

**Parameters**

- **ctx** (*QueryContext*) –
- **part** (*CompValue*) –

**Return type**

`Generator[FrozenBindings, None, None]`

## **rdflib.plugins.sparql.evalutils module**

## **rdflib.plugins.sparql.operators module**

`rdflib.plugins.sparql.operators.AdditiveExpression(e, ctx)`

**Parameters**

- **e** (*Expr*) –
- **ctx** (*Union[QueryContext, FrozenBindings]*) –



**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_ABS(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-abs>**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_BNODE(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-bnode>**Return type***BNode*`rdflib.plugins.sparql.operators.Builtin_BOUND(e, ctx)`<http://www.w3.org/TR/sparql11-query/#func-bound>**Parameters****e** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_CEIL(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-ceil>**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_COALESCE(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-coalesce>**Parameters****expr** (*Expr*) –`rdflib.plugins.sparql.operators.Builtin_CONCAT(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-concat>**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_CONTAINS(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-strcontains>**Parameters****expr** (*Expr*) –**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_DATATYPE(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Optional*[*str*]

`rdflib.plugins.sparql.operators.Builtin_DAY(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_ENCODE_FOR_URI(expr, ctx)`

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_EXISTS(e, ctx)`

**Parameters**

- **e** (*Expr*) –
- **ctx** (*FrozenBindings*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_FLOOR(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-floor>

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_HOURS(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_IF(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-if>

**Parameters**

**expr** (*Expr*) –

`rdflib.plugins.sparql.operators.Builtin_IRI(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-iri>

**Parameters**

- **expr** (*Expr*) –

- **ctx** (*FrozenBindings*) –

**Return type***URIRef*

`rdflib.plugins.sparql.operators.Builtin_LANG(e, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-lang>

Returns the language tag of *ltrl*, if it has one. It returns "" if *ltrl* has no language tag. Note that the RDF data model does not include literals with an empty language tag.

**Parameters**

**e** (*Expr*) –

**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_LANGMATCHES(e, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-langMatches>

**Parameters**

**e** (*Expr*) –

**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_LCASE(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_MD5(expr, ctx)`

**Parameters**

**expr** (*Expr*) –

**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_MINUTES(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_MONTH(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_NOW(e, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-now>

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_RAND(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#idp2133952>

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_REGEX(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-regex> Invokes the XPath fn:matches function to match text against a regular expression pattern. The regular expression language is defined in XQuery 1.0 and XPath 2.0 Functions and Operators section 7.6.1 Regular Expression Syntax

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_REPLACE(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-substr>

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_ROUND(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-round>

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_SECONDS(e, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-seconds>

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_SHA1(expr, ctx)`

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_SHA256(expr, ctx)`

**Parameters**

**expr** (*Expr*) –

**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_SHA384(expr, ctx)`**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_SHA512(expr, ctx)`**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_STR(e, ctx)`**Parameters****e** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_STRAFTER(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-strafter>**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_STRBEFORE(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-strbefore>**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_STRDT(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-strdt>**Parameters****expr** (*Expr*) –**Return type***Literal*`rdflib.plugins.sparql.operators.Builtin_STRENDS(expr, ctx)`<http://www.w3.org/TR/sparql11-query/#func-strends>**Parameters****expr** (*Expr*) –**Return type***Literal*

`rdflib.plugins.sparql.operators.Builtin_STRLANG(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-strlang>

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_STRLEN(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_STRSTARTS(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-strstarts>

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_STRUUID(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-strdt>

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_SUBSTR(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-substr>

**Parameters**

**expr** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_TIMEZONE(e, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-timezone>

**Return type**

*Literal*

**Returns**

the timezone part of arg as an `xsd:dayTimeDuration`.

**Raises**

an error if there is no timezone.

**Parameters**

**e** (*Expr*) –

`rdflib.plugins.sparql.operators.Builtin_TZ(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_UCASE(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_UUID(expr, ctx)`

<http://www.w3.org/TR/sparql11-query/#func-strdt>

**Parameters**

**expr** (*Expr*) –

**Return type**

*URIRef*

`rdflib.plugins.sparql.operators.Builtin_YEAR(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_isBLANK(expr, ctx)`

**Parameters**

- **expr** (*Expr*) –
- **ctx** (*FrozenBindings*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_isIRI(expr, ctx)`

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_isLITERAL(expr, ctx)`

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_isNUMERIC(expr, ctx)`

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.Builtin_sameTerm(e, ctx)`

**Parameters**

**e** (*Expr*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.operators.ConditionalAndExpression(e, ctx)`

**Parameters**

- **e** (*Expr*) –

- **ctx** (*Union*[*QueryContext*, *FrozenBindings*]) –

**Return type**  
*Literal*

`rdflib.plugins.sparql.operators.ConditionalOrExpression(e, ctx)`

**Parameters**

- **e** (*Expr*) –
- **ctx** (*Union*[*QueryContext*, *FrozenBindings*]) –

**Return type**  
*Literal*

`rdflib.plugins.sparql.operators.EBV(rt)`

Effective Boolean Value (EBV)

- If the argument is a typed literal with a datatype of `xsd:boolean`, the EBV is the value of that argument.
- If the argument is a plain literal or a typed literal with a datatype of `xsd:string`, the EBV is false if the operand value has zero length; otherwise the EBV is true.
- If the argument is a numeric type or a typed literal with a datatype derived from a numeric type, the EBV is false if the operand value is NaN or is numerically equal to zero; otherwise the EBV is true.
- All other arguments, including unbound arguments, produce a type error.

**Parameters**

**rt** (*Union*[*Identifier*, *SPARQLError*, *Expr*]) –

**Return type**  
*bool*

`rdflib.plugins.sparql.operators.Function(e, ctx)`

Custom functions and casts

**Parameters**

- **e** (*Expr*) –
- **ctx** (*FrozenBindings*) –

**Return type**  
*Node*

`rdflib.plugins.sparql.operators.MultiplicativeExpression(e, ctx)`

**Parameters**

- **e** (*Expr*) –
- **ctx** (*Union*[*QueryContext*, *FrozenBindings*]) –

**Return type**  
*Literal*

`rdflib.plugins.sparql.operators.RelationalExpression(e, ctx)`

**Parameters**

- **e** (*Expr*) –
- **ctx** (*Union*[*QueryContext*, *FrozenBindings*]) –



**Return type***Literal*`rdflib.plugins.sparql.operators.UnaryMinus(expr, ctx)`**Parameters**

- **expr** (*Expr*) –
- **ctx** (*FrozenBindings*) –

**Return type***Literal*`rdflib.plugins.sparql.operators.UnaryNot(expr, ctx)`**Parameters**

- **expr** (*Expr*) –
- **ctx** (*FrozenBindings*) –

**Return type***Literal*`rdflib.plugins.sparql.operators.UnaryPlus(expr, ctx)`**Parameters**

- **expr** (*Expr*) –
- **ctx** (*FrozenBindings*) –

**Return type***Literal*`rdflib.plugins.sparql.operators.and_(*args)`**Parameters****args** (*Expr*) –**Return type***Expr*`rdflib.plugins.sparql.operators.calculateDuration(obj1, obj2)`

returns the duration Literal between two datetime

**Parameters**

- **obj1** (*Union[date, datetime]*) –
- **obj2** (*Union[date, datetime]*) –

**Return type***Literal*`rdflib.plugins.sparql.operators.calculateFinalDateTime(obj1, dt1, obj2, dt2, operation)`

Calculates the final dateTime/date/time resultant after addition/ subtraction of duration/dayTimeDuration/yearMonthDuration

**Parameters**

- **obj1** (*Union[date, datetime]*) –
- **dt1** (*URIRef*) –
- **obj2** (*Union[Duration, timedelta]*) –

- **dt2** (*URIRef*) –
- **operation** (*str*) –

**Return type**  
*Literal*

`rdflib.plugins.sparql.operators.custom_function(uri, override=False, raw=False)`

Decorator version of `register_custom_function()`.

**Parameters**

- **uri** (*URIRef*) –
- **override** (*bool*) –
- **raw** (*bool*) –

**Return type**  
`Callable[[Callable[[Expr, FrozenBindings], Node]], Callable[[Expr, FrozenBindings], Node]]`

`rdflib.plugins.sparql.operators.date(e)`

**Parameters**  
**e** (*Literal*) –

**Return type**  
*date*

`rdflib.plugins.sparql.operators.dateTimeObjects(expr)`

return a dataTime/date/time/duration/dayTimeDuration/yearMonthDuration python objects from a literal

**Parameters**  
**expr** (*Literal*) –

**Return type**  
*Any*

`rdflib.plugins.sparql.operators.datetime(e)`

**Parameters**  
**e** (*Literal*) –

**Return type**  
*datetime*

`rdflib.plugins.sparql.operators.default_cast(e, ctx)`

**Parameters**

- **e** (*Expr*) –
- **ctx** (*FrozenBindings*) –

**Return type**  
*Literal*

`rdflib.plugins.sparql.operators.isCompatibleDateTimeDatatype(obj1, dt1, obj2, dt2)`

Returns a boolean indicating if first object is compatible with operation(+/-) over second object.

**Parameters**

- **obj1** (*Union[date, datetime]*) –
- **dt1** (*URIRef*) –

- **obj2** (`Union[Duration, timedelta]`) –
- **dt2** (`URIRef`) –

**Return type**`bool``rdflib.plugins.sparql.operators.literal(s)`**Parameters****s** (`Literal`) –**Return type**`Literal``rdflib.plugins.sparql.operators.not_(arg)`**Return type**`Expr``rdflib.plugins.sparql.operators.numeric(expr)`return a number from a literal <http://www.w3.org/TR/xpath20/#promotion>or `TypeError`**Parameters****expr** (`Literal`) –**Return type**`Any``rdflib.plugins.sparql.operators.register_custom_function(uri, func, override=False, raw=False)`

Register a custom SPARQL function.

By default, the function will be passed the RDF terms in the argument list. If `raw` is `True`, the function will be passed an `Expression` and a `Context`.The function must return an RDF term, or raise a `SparqlError`.**Parameters**

- **uri** (`URIRef`) –
- **func** (`Callable[[Expr, FrozenBindings], Node]`) –
- **override** (`bool`) –
- **raw** (`bool`) –

**Return type**`None``rdflib.plugins.sparql.operators.simplify(expr)`**Parameters****expr** (`Any`) –**Return type**`Any``rdflib.plugins.sparql.operators.string(s)`Make sure the passed thing is a string literal i.e. plain literal, `xsd:string` literal or lang-tagged literal**Parameters****s** (`Literal`) –

**Return type***Literal*`rdflib.plugins.sparql.operators.unregister_custom_function(uri, func=None)`

The ‘func’ argument is included for compatibility with existing code. A previous implementation checked that the function associated with the given uri was actually ‘func’, but this is not necessary as the uri should uniquely identify the function.

**Parameters**

- **uri** (*URIRef*) –
- **func** (*Optional[Callable[... Any]]*) –

**Return type***None***rdflib.plugins.sparql.parser module**

SPARQL 1.1 Parser

based on pyparsing

`rdflib.plugins.sparql.parser.expandBNodeTriples(terms)`

expand [ ?p ?o ] syntax for implicit bnodes

**Parameters****terms** (*ParseResults*) –**Return type***List[Any]*`rdflib.plugins.sparql.parser.expandCollection(terms)`

expand ( 1 2 3 ) notation for collections

**Parameters****terms** (*ParseResults*) –**Return type***List[List[Any]]*`rdflib.plugins.sparql.parser.expandTriples(terms)`

Expand ; and , syntax for repeat predicates, subjects

**Parameters****terms** (*ParseResults*) –**Return type***List[Any]*`rdflib.plugins.sparql.parser.expandUnicodeEscapes(q)`

The syntax of the SPARQL Query Language is expressed over code points in Unicode [UNICODE]. The encoding is always UTF-8 [RFC3629]. Unicode code points may also be expressed using an uXXXX (U+0 to U+FFFF) or UXXXXXXXX syntax (for U+10000 onwards) where X is a hexadecimal digit [0-9A-F]

**Parameters****q** (*str*) –**Return type***str*

`rdflib.plugins.sparql.parser.neg(literal)`

**Parameters**

**literal** (*Literal*) –

**Return type**

*Literal*

`rdflib.plugins.sparql.parser.parseQuery(q)`

**Parameters**

**q** (`Union[str, bytes, TextIO, BinaryIO]`) –

**Return type**

`ParseResults`

`rdflib.plugins.sparql.parser.parseUpdate(q)`

**Parameters**

**q** (`Union[str, bytes, TextIO, BinaryIO]`) –

**Return type**

*CompValue*

`rdflib.plugins.sparql.parser.setDataType(terms)`

**Parameters**

**terms** (`Tuple[Any, Optional[str]]`) –

**Return type**

*Literal*

`rdflib.plugins.sparql.parser.setLanguage(terms)`

**Parameters**

**terms** (`Tuple[Any, Optional[str]]`) –

**Return type**

*Literal*

## rdflib.plugins.sparql.parserutils module

`class rdflib.plugins.sparql.parserutils.Comp(name, expr)`

Bases: `TokenConverter`

A pyparsing token for grouping together things with a label Any sub-tokens that are not Params will be ignored.

Returns `CompValue` / `Expr` objects - depending on whether `evalFn` is set.

**Parameters**

- **name** (`str`) –
- **expr** (`ParserElement`) –

`__abstractmethods__ = frozenset({})`

`__init__(name, expr)`

**Parameters**

- **name** (`str`) –

```
    • expr (ParserElement) –
__module__ = 'rdflib.plugins.sparql.parserutils'
__slotnames__ = []
postParse(instring, loc, tokenList)

    Parameters
    • instring (str) –
    • loc (int) –
    • tokenList (ParseResults) –

    Return type
    Union[Expr, CompValue]
setEvalFn(evalfn)

    Parameters
    evalfn (Callable[[Any, Any], Any]) –

    Return type
    Comp

class rdflib.plugins.sparql.parserutils.CompValue(name, **values)
    Bases: OrderedDict

    The result of parsing a Comp Any included Params are available as Dict keys or as attributes

    Parameters
    name (str) –

    __getattr__(a)

    Parameters
    a (str) –

    Return type
    Any

    __getitem__(a)
    x.__getitem__(y) <==> x[y]

    __init__(name, **values)

    Parameters
    name (str) –

    __module__ = 'rdflib.plugins.sparql.parserutils'

    __repr__()
    Return repr(self).

    Return type
    str

    __str__()
    Return str(self).

    Return type
    str
```

**clone()**

**Return type**

*CompValue*

**get**(*a*, *variables=False*, *errors=False*)

Return the value for key if key is in the dictionary, else default.

**Parameters**

- **variables** (*bool*) –
- **errors** (*bool*) –

**class** rdflib.plugins.sparql.parserutils.**Expr**(*name*, *evalfn=None*, *\*\*values*)

Bases: *CompValue*

A CompValue that is evaluable

**Parameters**

- **name** (*str*) –
- **evalfn** (*Optional[Callable[[Any, Any], Any]]*) –

**\_\_init\_\_**(*name*, *evalfn=None*, *\*\*values*)

**Parameters**

- **name** (*str*) –
- **evalfn** (*Optional[Callable[[Any, Any], Any]]*) –

**\_\_module\_\_** = 'rdflib.plugins.sparql.parserutils'

**eval**(*ctx={}*)

**Parameters**

**ctx** (*Any*) –

**Return type**

*Union[SPARQLError, Any]*

**class** rdflib.plugins.sparql.parserutils.**Param**(*name*, *expr*, *isList=False*)

Bases: *TokenConverter*

A pyparsing token for labelling a part of the parse-tree if isList is true repeat occurrences of ParamList have their values merged in a list

**Parameters**

- **name** (*str*) –
- **isList** (*bool*) –

**\_\_abstractmethods\_\_** = frozenset({})

**\_\_init\_\_**(*name*, *expr*, *isList=False*)

**Parameters**

- **name** (*str*) –
- **isList** (*bool*) –

```
__module__ = 'rdflib.plugins.sparql.parserutils'
```

```
__slotnames__ = []
```

```
postParse2(tokenList)
```

Parameters

**tokenList** (`Union[List[Any], ParseResults]`) –

Return type

*ParamValue*

```
class rdflib.plugins.sparql.parserutils.ParamList(name, expr)
```

Bases: *Param*

A shortcut for a Param with isList=True

Parameters

**name** (`str`) –

```
__abstractmethods__ = frozenset({})
```

```
__init__(name, expr)
```

Parameters

**name** (`str`) –

```
__module__ = 'rdflib.plugins.sparql.parserutils'
```

```
customName: str
```

```
failAction: typing.Optional[ParseFailAction]
```

```
ignoreExprs: List['ParserElement']
```

```
parseAction: List[ParseAction]
```

```
resultsName: str
```

```
suppress_warnings_: List[Diagnostics]
```

```
class rdflib.plugins.sparql.parserutils.ParamValue(name, tokenList, isList)
```

Bases: `object`

The result of parsing a Param This just keeps the name/value All cleverness is in the CompValue

Parameters

- **name** (`str`) –
- **tokenList** (`Union[List[Any], ParseResults]`) –
- **isList** (`bool`) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.parserutils',  
'__doc__': '\n The result of parsing a Param\n This just keeps the name/value\n All  
cleverness is in the CompValue\n ', '__init__': <function ParamValue.__init__>,  
'__str__': <function ParamValue.__str__>, '__dict__': <attribute '__dict__' of  
'ParamValue' objects>, '__weakref__': <attribute '__weakref__' of 'ParamValue'  
objects>, '__annotations__': {}})
```



`__init__(name, tokenList, isList)`

**Parameters**

- **name** (`str`) –
- **tokenList** (`Union[List[Any], ParseResults]`) –
- **isList** (`bool`) –

`__module__` = 'rdflib.plugins.sparql.parserutils'

`__str__()`

Return str(self).

**Return type**

`str`

`__weakref__`

list of weak references to the object (if defined)

`rdflib.plugins.sparql.parserutils.prettify_parsetree(t, indent="", depth=0)`

**Parameters**

- **t** (`ParseResults`) –
- **indent** (`str`) –
- **depth** (`int`) –

**Return type**

`str`

`rdflib.plugins.sparql.parserutils.value(ctx, val, variables=False, errors=False)`

utility function for evaluating something...

Variables will be looked up in the context Normally, non-bound vars is an error, set variables=True to return unbound vars

Normally, an error raises the error, set errors=True to return error

**Parameters**

- **ctx** (`FrozenBindings`) –
- **val** (`Any`) –
- **variables** (`bool`) –
- **errors** (`bool`) –

**Return type**

`Any`

**rdflib.plugins.sparql.processor module**

Code for tying SPARQL Engine into RDFLib

These should be automatically registered with RDFLib

```
class rdflib.plugins.sparql.processor.SPARQLProcessor(graph)
```

Bases: *Processor*

```
__init__(graph)
```

```
__module__ = 'rdflib.plugins.sparql.processor'
```

```
query(strOrQuery, initBindings=None, initNs=None, base=None, DEBUG=False)
```

Evaluate a query with the given initial bindings, and initial namespaces. The given base is used to resolve relative URIs in the query and will be overridden by any BASE given in the query.

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in SERVICE directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Parameters**

- **strOrQuery** (*Union[str, Query]*) –
- **initBindings** (*Optional[Mapping[str, Identifier]]*) –
- **initNs** (*Optional[Mapping[str, Any]]*) –
- **base** (*Optional[str]*) –
- **DEBUG** (*bool*) –

**Return type**

*Mapping[str, Any]*

```
class rdflib.plugins.sparql.processor.SPARQLResult(res)
```

Bases: *Result*

**Parameters**

**res** (*Mapping[str, Any]*) –

```
__init__(res)
```

**Parameters**

**res** (*Mapping[str, Any]*) –

```
__module__ = 'rdflib.plugins.sparql.processor'
```

**askAnswer:** *Optional[bool]*

**graph:** *Optional['Graph']*

**vars:** *Optional[List['Variable']]*

variables contained in the result.

```
class rdflib.plugins.sparql.processor.SPARQLUpdateProcessor(graph)
```

Bases: [UpdateProcessor](#)

```
__init__(graph)
```

```
__module__ = 'rdflib.plugins.sparql.processor'
```

```
update(strOrQuery, initBindings=None, initNs=None)
```

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in SERVICE directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib [Security Considerations](#) documentation.

#### Parameters

- **strOrQuery** ([Union](#)[[str](#), [Update](#)]) –
- **initBindings** ([Optional](#)[[Mapping](#)[[str](#), [Identifier](#)]]) –
- **initNs** ([Optional](#)[[Mapping](#)[[str](#), [Any](#)]]) –

#### Return type

[None](#)

```
rdflib.plugins.sparql.processor.prepareQuery(queryString, initNs=None, base=None)
```

Parse and translate a SPARQL Query

#### Parameters

- **queryString** ([str](#)) –
- **initNs** ([Optional](#)[[Mapping](#)[[str](#), [Any](#)]]) –
- **base** ([Optional](#)[[str](#)]) –

#### Return type

[Query](#)

```
rdflib.plugins.sparql.processor.prepareUpdate(updateString, initNs=None, base=None)
```

Parse and translate a SPARQL Update

#### Parameters

- **updateString** ([str](#)) –
- **initNs** ([Optional](#)[[Mapping](#)[[str](#), [Any](#)]]) –
- **base** ([Optional](#)[[str](#)]) –

#### Return type

[Update](#)

```
rdflib.plugins.sparql.processor.processUpdate(graph, updateString, initBindings=None, initNs=None,
                                              base=None)
```

Process a SPARQL Update Request returns Nothing on success or raises Exceptions on error

#### Parameters

- **graph** (*Graph*) –
- **updateString** (*str*) –
- **initBindings** (*Optional*[*Mapping*[*str*, *Identifier*]]) –
- **initNs** (*Optional*[*Mapping*[*str*, *Any*]]) –
- **base** (*Optional*[*str*]) –

**Return type**

*None*

## rdflib.plugins.sparql.sparql module

**exception** rdflib.plugins.sparql.sparql.**AlreadyBound**

Bases: *SPARQLError*

Raised when trying to bind a variable that is already bound!

**\_\_init\_\_**()

**\_\_module\_\_** = 'rdflib.plugins.sparql.sparql'

**class** rdflib.plugins.sparql.sparql.**Bindings**(*outer=None*, *d=[]*)

Bases: *MutableMapping*

A single level of a stack of variable-value bindings. Each dict keeps a reference to the dict below it, any failed lookup is propagated back

In python 3.3 this could be a *collections.ChainMap*

**Parameters**

**outer** (*Optional*[*Bindings*]) –

**\_\_abstractmethods\_\_** = *frozenset*({})

**\_\_contains\_\_**(*key*)

**Parameters**

**key** (*Any*) –

**Return type**

*bool*

**\_\_delitem\_\_**(*key*)

**Parameters**

**key** (*str*) –

**Return type**

*None*

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.sparql', '__doc__':
'\n\n A single level of a stack of variable-value bindings.\n Each dict keeps a
reference to the dict below it,\n any failed lookup is propegated back\n\n In python
3.3 this could be a collections.ChainMap\n ', '__init__': <function
Bindings.__init__>, '__getitem__': <function Bindings.__getitem__>, '__contains__':
<function Bindings.__contains__>, '__setitem__': <function Bindings.__setitem__>,
'__delitem__': <function Bindings.__delitem__>, '__len__': <function
Bindings.__len__>, '__iter__': <function Bindings.__iter__>, '__str__': <function
Bindings.__str__>, '__repr__': <function Bindings.__repr__>, '__dict__':
<attribute '__dict__' of 'Bindings' objects>, '__weakref__': <attribute
'__weakref__' of 'Bindings' objects>, '__abstractmethods__': frozenset(),
'__abc_impl': <_abc._abc_data object>, '__annotations__': {'_d': 'Dict[str,
str]'}}})
```

```
__getitem__(key)
```

**Parameters**

**key** (*str*) –

**Return type**

*str*

```
__init__(outer=None, d=[])
```

**Parameters**

**outer** (*Optional[Bindings]*) –

```
__iter__()
```

**Return type**

*Generator[str, None, None]*

```
__len__()
```

**Return type**

*int*

```
__module__ = 'rdflib.plugins.sparql.sparql'
```

```
__repr__()
```

Return repr(self).

**Return type**

*str*

```
__setitem__(key, value)
```

**Parameters**

- **key** (*str*) –
- **value** (*Any*) –

**Return type**

*None*

```
__str__()
```

Return str(self).

**Return type**

*str*

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**class** rdflib.plugins.sparql.sparql.**FrozenBindings**(ctx, \*args, \*\*kwargs)

Bases: *FrozenDict*

**Parameters**

ctx (*QueryContext*) –

**\_\_abstractmethods\_\_** = frozenset({})

**\_\_getitem\_\_**(key)

**Parameters**

key (*Union*[*Identifier*, *str*]) –

**Return type**

*Identifier*

**\_\_init\_\_**(ctx, \*args, \*\*kwargs)

**Parameters**

ctx (*QueryContext*) –

**\_\_module\_\_** = 'rdflib.plugins.sparql.sparql'

**property** bnodes: *Mapping*[*Identifier*, *BNode*]

**forget**(before, \_except=None)

return a frozen dict only of bindings made in self since before

**Parameters**

• before (*QueryContext*) –

• \_except (*Optional*[*Container*[*Variable*]]) –

**Return type**

*FrozenBindings*

**merge**(other)

**Parameters**

other (*Mapping*[*Identifier*, *Identifier*]) –

**Return type**

*FrozenBindings*

**property** now: *datetime*

**project**(vars)

**Parameters**

vars (*Container*[*Variable*]) –

**Return type**

*FrozenBindings*

**property** prologue: *Prologue* | *None*

**remember**(*these*)

return a frozen dict only of bindings in these

**Return type**

*FrozenBindings*

**class** rdflib.plugins.sparql.sparql.FrozenDict(\*args, \*\*kwargs)

Bases: *Mapping*

An immutable hashable dict

Taken from <http://stackoverflow.com/a/2704866/81121>

**Parameters**

- **args** (*Any*) –
- **kwargs** (*Any*) –

**\_\_abstractmethods\_\_** = frozenset({})

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.sparql', '__doc__':
'\n An immutable hashable dict\n\n Taken from
http://stackoverflow.com/a/2704866/81121\n\n ', '__init__': <function
FrozenDict.__init__>, '__iter__': <function FrozenDict.__iter__>, '__len__':
<function FrozenDict.__len__>, '__getitem__': <function FrozenDict.__getitem__>,
'__hash__': <function FrozenDict.__hash__>, 'project': <function
FrozenDict.project>, 'disjointDomain': <function FrozenDict.disjointDomain>,
'compatible': <function FrozenDict.compatible>, 'merge': <function
FrozenDict.merge>, '__str__': <function FrozenDict.__str__>, '__repr__': <function
FrozenDict.__repr__>, '__dict__': <attribute '__dict__' of 'FrozenDict' objects>,
'__weakref__': <attribute '__weakref__' of 'FrozenDict' objects>,
'__abstractmethods__': frozenset(), '_abc_impl': <_abc._abc_data object>,
'__annotations__': {'_d': 'Dict[Identifier, Identifier]', '_hash':
'Optional[int]'}})
```

**\_\_getitem\_\_**(*key*)

**Parameters**

**key** (*Identifier*) –

**Return type**

*Identifier*

**\_\_hash\_\_**()

Return hash(self).

**Return type**

*int*

**\_\_init\_\_**(\*args, \*\*kwargs)

**Parameters**

- **args** (*Any*) –
- **kwargs** (*Any*) –

**\_\_iter\_\_**()

`__len__()`

Return type

`int`

`__module__ = 'rdflib.plugins.sparql.sparql'`

`__repr__()`

Return `repr(self)`.

Return type

`str`

`__str__()`

Return `str(self)`.

Return type

`str`

`__weakref__`

list of weak references to the object (if defined)

`compatible(other)`

Parameters

***other*** (`Mapping`[`Identifier`, `Identifier`]) –

Return type

`bool`

`disjointDomain(other)`

Parameters

***other*** (`Mapping`[`Identifier`, `Identifier`]) –

Return type

`bool`

`merge(other)`

Parameters

***other*** (`Mapping`[`Identifier`, `Identifier`]) –

Return type

`FrozenDict`

`project(vars)`

Parameters

***vars*** (`Container`[`Variable`]) –

Return type

`FrozenDict`

`exception rdflib.plugins.sparql.sparql.NotBoundError(msg=None)`

Bases: `SPARQLError`

Parameters

***msg*** (`Optional`[`str`]) –



```
__init__(msg=None)
```

**Parameters**

**msg** (Optional[str]) –

```
__module__ = 'rdflib.plugins.sparql.sparql'
```

```
class rdflib.plugins.sparql.sparql.Prologue
```

Bases: `object`

A class for holding prefixing bindings and base URI information

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.sparql', '__doc__':
'\n A class for holding prefixing bindings and base URI information\n ', '__init__':
<function Prologue.__init__>, 'resolvePName': <function Prologue.resolvePName>,
'bind': <function Prologue.bind>, 'absolutize': <function Prologue.absolutize>,
'__dict__': <attribute '__dict__' of 'Prologue' objects>, '__weakref__':
<attribute '__weakref__' of 'Prologue' objects>, '__annotations__': {'base':
'Optional[str]'}})
```

```
__init__()
```

```
__module__ = 'rdflib.plugins.sparql.sparql'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
absolutize(iri)
```

Apply BASE / PREFIXes to URIs (and to datatypes in Literals)

TODO: Move resolving URIs to pre-processing

**Parameters**

**iri** (Union[CompValue, str, None]) –

**Return type**

Union[CompValue, str, None]

```
bind(prefix, uri)
```

**Parameters**

- **prefix** (Optional[str]) –
- **uri** (Any) –

**Return type**

None

```
resolvePName(prefix, localname)
```

**Parameters**

- **prefix** (Optional[str]) –
- **localname** (Optional[str]) –

**Return type**

[URIRef](#)

```
class rdflib.plugins.sparql.sparql.Query(prologue, algebra)
```

Bases: `object`

A parsed and translated query

**Parameters**

- **prologue** (*Prologue*) –
- **algebra** (*CompValue*) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.sparql', '__doc__':  
'\n A parsed and translated query\n ', '__init__': <function Query.__init__>,  
'__dict__': <attribute '__dict__' of 'Query' objects>, '__weakref__': <attribute  
'__weakref__' of 'Query' objects>, '__annotations__': {'_original_args':  
'Tuple[str, Mapping[str, str], Optional[str]]'}}
```

```
__init__(prologue, algebra)
```

**Parameters**

- **prologue** (*Prologue*) –
- **algebra** (*CompValue*) –

```
__module__ = 'rdflib.plugins.sparql.sparql'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
class rdflib.plugins.sparql.sparql.QueryContext(graph=None, bindings=None, initBindings=None)
```

Bases: `object`

Query context - passed along when evaluating the query

**Parameters**

- **graph** (*Optional[Graph]*) –
- **bindings** (*Union[Bindings, FrozenBindings, List[Any], None]*) –
- **initBindings** (*Optional[Mapping[str, Identifier]]*) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.sparql', '__doc__':  
'\n Query context - passed along when evaluating the query\n ', '__init__':  
<function QueryContext.__init__>, 'now': <property object>, 'clone': <function  
QueryContext.clone>, 'dataset': <property object>, 'load': <function  
QueryContext.load>, '__getitem__': <function QueryContext.__getitem__>, 'get':  
<function QueryContext.get>, 'solution': <function QueryContext.solution>,  
'__setitem__': <function QueryContext.__setitem__>, 'pushGraph': <function  
QueryContext.pushGraph>, 'push': <function QueryContext.push>, 'clean': <function  
QueryContext.clean>, 'thaw': <function QueryContext.thaw>, '__dict__': <attribute  
'__dict__' of 'QueryContext' objects>, '__weakref__': <attribute '__weakref__' of  
'QueryContext' objects>, '__annotations__': {'graph': 'Optional[Graph]',  
'dataset': 'Optional[ConjunctiveGraph]', 'prologue': 'Optional[Prologue]',  
'now': 'Optional[datetime.datetime]', 'bnodes': 't.MutableMapping[Identifier,  
BNode]'}}
```

```
__getitem__(key)
```

**Parameters**

- **key** (*Union[str, Path]*) –

**Return type**`Union[str, Path, None]``__init__(graph=None, bindings=None, initBindings=None)`**Parameters**

- **graph** (`Optional[Graph]`) –
- **bindings** (`Union[Bindings, FrozenBindings, List[Any], None]`) –
- **initBindings** (`Optional[Mapping[str, Identifier]]`) –

`__module__ = 'rdflib.plugins.sparql.sparql'``__setitem__(key, value)`**Parameters**

- **key** (`str`) –
- **value** (`str`) –

**Return type**`None``__weakref__`

list of weak references to the object (if defined)

`clean()`**Return type**`QueryContext``clone(bindings=None)`**Parameters****bindings** (`Union[Bindings, FrozenBindings, List[Any], None]`) –**Return type**`QueryContext`**property dataset:** `ConjunctiveGraph`

“current dataset

`get(key, default=None)`**Parameters**

- **key** (`str`) –
- **default** (`Optional[Any]`) –

**Return type**`Any``load(source, default=False, **kwargs)`

Load data from the source into the query context's.

**Parameters**

- **source** (`URIRef`) – The source to load from.
- **default** (`bool`) – If `True`, triples from the source will be added to the default graph, otherwise it will be loaded into a graph with source URI as its name.

- **kwargs** (*Any*) – Keyword arguments to pass to `rdflib.graph.Graph.parse()`.

**Return type**

*None*

**property now:** *datetime*

**push()**

**Return type**

*QueryContext*

**pushGraph(*graph*)**

**Parameters**

**graph** (*Optional[Graph]*) –

**Return type**

*QueryContext*

**solution(*vars=None*)**

Return a static copy of the current variable bindings as dict

**Parameters**

**vars** (*Optional[Iterable[Variable]]*) –

**Return type**

*FrozenBindings*

**thaw(*frozenbindings*)**

Create a new read/write query context from the given solution

**Parameters**

**frozenbindings** (*FrozenBindings*) –

**Return type**

*QueryContext*

**exception** `rdflib.plugins.sparql.sparql.SPARQLError(msg=None)`

Bases: *Exception*

**Parameters**

**msg** (*Optional[str]*) –

**\_\_init\_\_** (*msg=None*)

**Parameters**

**msg** (*Optional[str]*) –

**\_\_module\_\_** = `'rdflib.plugins.sparql.sparql'`

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**exception** `rdflib.plugins.sparql.sparql.SPARQLTypeError(msg)`

Bases: *SPARQLError*

**Parameters**

**msg** (*Optional[str]*) –

```
__init__(msg)
```

**Parameters**

**msg** (*Optional*[*str*]) –

```
__module__ = 'rdflib.plugins.sparql.sparql'
```

```
class rdflib.plugins.sparql.sparql.Update(prologue, algebra)
```

Bases: *object*

A parsed and translated update

**Parameters**

- **prologue** (*Prologue*) –
- **algebra** (*List*[*CompValue*]) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.sparql.sparql', '__doc__':
'\n A parsed and translated update\n ', '__init__': <function Update.__init__>,
'__dict__': <attribute '__dict__' of 'Update' objects>, '__weakref__': <attribute
'__weakref__' of 'Update' objects>, '__annotations__': {'_original_args':
'Tuple[str, Mapping[str, str], Optional[str]]'}})
```

```
__init__(prologue, algebra)
```

**Parameters**

- **prologue** (*Prologue*) –
- **algebra** (*List*[*CompValue*]) –

```
__module__ = 'rdflib.plugins.sparql.sparql'
```

```
__weakref__
```

list of weak references to the object (if defined)

## rdflib.plugins.sparql.update module

Code for carrying out Update Operations

```
rdflib.plugins.sparql.update.evalAdd(ctx, u)
```

add all triples from src to dst

<http://www.w3.org/TR/sparql11-update/#add>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

*None*

```
rdflib.plugins.sparql.update.evalClear(ctx, u)
```

<http://www.w3.org/TR/sparql11-update/#clear>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalCopy(ctx, u)`

remove all triples from dst add all triples from src to dst

<http://www.w3.org/TR/sparql11-update/#copy>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalCreate(ctx, u)`

<http://www.w3.org/TR/sparql11-update/#create>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalDeleteData(ctx, u)`

<http://www.w3.org/TR/sparql11-update/#deleteData>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalDeleteWhere(ctx, u)`

<http://www.w3.org/TR/sparql11-update/#deleteWhere>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalDrop(ctx, u)`

<http://www.w3.org/TR/sparql11-update/#drop>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalInsertData(ctx, u)`

<http://www.w3.org/TR/sparql11-update/#insertData>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalLoad(ctx, u)`

<http://www.w3.org/TR/sparql11-update/#load>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalModify(ctx, u)`

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalMove(ctx, u)`

remove all triples from dst add all triples from src to dst remove all triples from src

<http://www.w3.org/TR/sparql11-update/#move>

**Parameters**

- **ctx** (*QueryContext*) –
- **u** (*CompValue*) –

**Return type**

None

`rdflib.plugins.sparql.update.evalUpdate(graph, update, initBindings=None)`

<http://www.w3.org/TR/sparql11-update/#updateLanguage>

‘A request is a sequence of operations [...] Implementations MUST ensure that operations of a single request are executed in a fashion that guarantees the same effects as executing them in lexical order.

Operations all result either in success or failure.

If multiple operations are present in a single request, then a result of failure from any operation MUST abort the sequence of operations, causing the subsequent operations to be ignored.’

This will return None on success and raise Exceptions on error

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in SERVICE directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

#### Parameters

- **graph** (*Graph*) –
- **update** (*Update*) –
- **initBindings** (*Optional*[*Mapping*[*str*, *Identifier*]]) –

#### Return type

*None*

### Module contents

SPARQL implementation for RDFLib

New in version 4.0.

```
rdflib.plugins.sparql.CUSTOM_EVALS = {}
```

Custom evaluation functions

These must be functions taking (ctx, part) and raise NotImplementedError if they cannot handle a certain part

```
rdflib.plugins.sparql.prepareQuery(queryString, initNs=None, base=None)
```

Parse and translate a SPARQL Query

#### Parameters

- **queryString** (*str*) –
- **initNs** (*Optional*[*Mapping*[*str*, *Any*]]) –
- **base** (*Optional*[*str*]) –

#### Return type

*Query*

```
rdflib.plugins.sparql.prepareUpdate(updateString, initNs=None, base=None)
```

Parse and translate a SPARQL Update

#### Parameters

- **updateString** (*str*) –
- **initNs** (*Optional*[*Mapping*[*str*, *Any*]]) –
- **base** (*Optional*[*str*]) –

#### Return type

*Update*

```
rdflib.plugins.sparql.processUpdate(graph, updateString, initBindings=None, initNs=None, base=None)
```

Process a SPARQL Update Request returns Nothing on success or raises Exceptions on error

#### Parameters



- **graph** (*Graph*) –
- **updateString** (*str*) –
- **initBindings** (*Optional*[*Mapping*[*str*, *Identifier*]]) –
- **initNs** (*Optional*[*Mapping*[*str*, *Any*]]) –
- **base** (*Optional*[*str*]) –

**Return type**

*None*

## rdflib.plugins.stores package

### Submodules

#### rdflib.plugins.stores.auditable module

This wrapper intercepts calls through the store interface and implements thread-safe logging of destructive operations (adds / removes) in reverse. This is persisted on the store instance and the reverse operations are executed In order to return the store to the state it was when the transaction began Since the reverse operations are persisted on the store, the store itself acts as a transaction.

Calls to commit or rollback, flush the list of reverse operations This provides thread-safe atomicity and isolation (assuming concurrent operations occur with different store instances), but no durability (transactions are persisted in memory and wont be available to reverse operations after the system fails): A and I out of ACID.

**class** `rdflib.plugins.stores.auditable.AuditableStore`(*store*)

Bases: *Store*

#### Parameters

**store** (*Store*) –

**\_\_init\_\_**(*store*)

identifier: URIRef of the Store. Defaults to CWD configuration: string containing information open can use to connect to datastore.

#### Parameters

**store** (*Store*) –

**\_\_len\_\_**(*context=None*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

#### Parameters

**context** (*Optional*[*Graph*]) – a graph instance to query or None

**\_\_module\_\_** = 'rdflib.plugins.stores.auditable'

**add**(*triple*, *context*, *quoted=False*)

Adds the given statement to a specific context or to the model. The quoted argument is interpreted by formula-aware stores to indicate this statement is quoted/hypothetical It should be an error to not specify a context and have the quoted argument be True. It should also be an error for the quoted argument to be True when the store is not formula-aware.

#### Parameters

- **triple** (*Tuple*[*Node*, *Node*, *Node*]) –

- **context** (*Graph*) –
- **quoted** (*bool*) –

**Return type**

*None*

**bind**(*prefix*, *namespace*, *override=True*)

**Parameters**

- **override** (*bool*) – rebind, even if the given namespace is already bound to another prefix.
- **prefix** (*str*) –
- **namespace** (*URIRef*) –

**Return type**

*None*

**close**(*commit\_pending\_transaction=False*)

This closes the database connection. The `commit_pending_transaction` parameter specifies whether to commit all pending transactions before closing (if the store is transactional).

**Parameters**

**commit\_pending\_transaction** (*bool*) –

**Return type**

*None*

**commit**()

**Return type**

*None*

**contexts**(*triple=None*)

Generator over all contexts in the graph. If `triple` is specified, a generator over all contexts the triple is in. if store is `graph_aware`, may also return empty contexts

**Return type**

*Generator[Graph, None, None]*

**Returns**

a generator over Nodes

**Parameters**

**triple** (*Optional[Tuple[Node, Node, Node]]*) –

**destroy**(*configuration*)

This destroys the instance of the store identified by the configuration string.

**Parameters**

**configuration** (*str*) –

**Return type**

*None*

**namespace**(*prefix*)

**Parameters**

**prefix** (*str*) –

**Return type**

*Optional[URIRef]*

**namespaces()**

**Return type**

`Iterator[Tuple[str, URIRef]]`

**open(configuration, create=True)**

Opens the store specified by the configuration string. If create is True a store will be created if it does not already exist. If create is False and a store does not already exist an exception is raised. An exception is also raised if a store exists, but there is insufficient permissions to open the store. This should return one of: VALID\_STORE, CORRUPTED\_STORE, or NO\_STORE

**Parameters**

- **configuration** (`str`) –
- **create** (`bool`) –

**Return type**

`Optional[int]`

**prefix(namespace)**

**Parameters**

**namespace** (`URIRef`) –

**Return type**

`Optional[str]`

**query(\*args, \*\*kw)**

If stores provide their own SPARQL implementation, override this.

queryGraph is None, a URIRef or ‘\_\_UNION\_\_’ If None the graph is specified in the query-string/object If URIRef it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried (This is used by ConjunctiveGraphs Values other than None obviously only makes sense for context-aware stores.)

**Parameters**

- **args** (`Any`) –
- **kw** (`Any`) –

**Return type**

`Result`

**remove(spo, context=None)**

Remove the set of triples matching the pattern from the store

**Parameters**

- **spo** (`Tuple[Optional[Node], Optional[Node], Optional[Node]]`) –
- **context** (`Optional[Graph]`) –

**Return type**

`None`

**rollback()**

**Return type**

`None`

**triples**(*triple*, *context=None*)

A generator over all the triples matching the pattern. Pattern can include any objects for used for comparing against nodes in the store, for example, REGEXTerm, URIRef, Literal, BNode, Variable, Graph, QuotedGraph, Date? DateRange?

**Parameters**

- **context** (Optional[Graph]) – A conjunctive query can be indicated by either providing a value of None, or a specific context can be queries by passing a Graph instance (if store is context aware).
- **triple** (Tuple[Optional[Node], Optional[Node], Optional[Node]]) –

**Return type**

Iterator[Tuple[Tuple[Node, Node, Node], Iterator[Optional[Graph]]]]

## rdflib.plugins.stores.berkeleydb module

**class** rdflib.plugins.stores.berkeleydb.BerkeleyDB(*configuration=None*, *identifier=None*)

Bases: Store

A store that allows for on-disk persistent using BerkeleyDB, a fast key/value DB.

This store implementation used to be known, previous to rdflib 6.0.0 as ‘Sleepycat’ due to that being the then name of the Python wrapper for BerkeleyDB.

This store allows for quads as well as triples. See examples of use in both the *examples.berkeleydb\_example* and *test/test\_store/test\_store\_berkeleydb.py* files.

**NOTE on installation:**

To use this store, you must have BerkeleyDB installed on your system separately to Python (brew install berkeley-db on a Mac) and also have the BerkeleyDB Python wrapper installed (pip install berkeleydb). You may need to install BerkeleyDB Python wrapper like this: YES\_I\_HAVE\_THE\_RIGHT\_TO\_USE\_THIS\_BERKELEY\_DB\_VERSION=1 pip install berkeleydb

**Parameters**

- **configuration** (Optional[str]) –
- **identifier** (Optional[Identifier]) –

**\_\_annotations\_\_** = {'db\_env': 'db.DBEnv'}

**\_\_init\_\_**(*configuration=None*, *identifier=None*)

identifier: URIRef of the Store. Defaults to CWD configuration: string containing information open can use to connect to datastore.

**Parameters**

- **configuration** (Optional[str]) –
- **identifier** (Optional[Identifier]) –

**\_\_len\_\_**(*context=None*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

**Parameters**

**context** (Optional[Graph]) – a graph instance to query or None

**Return type**`int``__module__ = 'rdflib.plugins.stores.berkeleydb'``add(triple, context, quoted=False, txn=None)`

Add a triple to the store of triples.

**Parameters**

- **triple** (`Tuple[Node, Node, Node]`) –
- **context** (`Graph`) –
- **quoted** (`bool`) –
- **txn** (`Optional[Any]`) –

**Return type**`None``add_graph(graph)`

Add a graph to the store, no effect if the graph already exists. :type graph: `Graph` :param graph: a Graph instance

**Return type**`None``bind(prefix, namespace, override=True)`**Parameters**

- **override** (`bool`) – rebind, even if the given namespace is already bound to another prefix.
- **prefix** (`str`) –
- **namespace** (`URIRef`) –

**Return type**`None``close(commit_pending_transaction=False)`

This closes the database connection. The `commit_pending_transaction` parameter specifies whether to commit all pending transactions before closing (if the store is transactional).

**Parameters**

**commit\_pending\_transaction** (`bool`) –

**Return type**`None``context_aware: bool = True``contexts(triple=None)`

Generator over all contexts in the graph. If triple is specified, a generator over all contexts the triple is in. if store is `graph_aware`, may also return empty contexts

**Return type**`Generator[Graph, None, None]`**Returns**

a generator over Nodes

**Parameters****triple** (*Optional*[*Tuple*[*Node*, *Node*, *Node*]]) –**db\_env**: *db*.DBEnv = None**formula\_aware**: *bool* = True**graph\_aware**: *bool* = True**property identifier**: *Identifier* | None**is\_open**()**Return type***bool***namespace**(*prefix*)**Parameters****prefix** (*str*) –**Return type***Optional*[*URIRef*]**namespaces**()**Return type***Generator*[*Tuple*[*str*, *URIRef*], None, None]**open**(*path*, *create*=True)

Opens the store specified by the configuration string. If *create* is True a store will be created if it does not already exist. If *create* is False and a store does not already exist an exception is raised. An exception is also raised if a store exists, but there is insufficient permissions to open the store. This should return one of: VALID\_STORE, CORRUPTED\_STORE, or NO\_STORE

**Parameters**

- **path** (*str*) –
- **create** (*bool*) –

**Return type***Optional*[*int*]**prefix**(*namespace*)**Parameters****namespace** (*URIRef*) –**Return type***Optional*[*str*]**remove**(*spo*, *context*, *txn*=None)

Remove the set of triples matching the pattern from the store

**Parameters**

- **spo** (*Tuple*[*Optional*[*Node*], *Optional*[*Node*], *Optional*[*Node*]]) –
- **context** (*Optional*[*Graph*]) –
- **txn** (*Optional*[*Any*]) –

**Return type**`None`**remove\_graph**(*graph*)

Remove a graph from the store, this should also remove all triples in the graph

**Parameters**

- **graphid** – a Graph instance
- **graph** (*Graph*) –

**sync**()**Return type**`None`**transaction\_aware**: `bool = False`**triples**(*spo, context=None, txn=None*)

A generator over all the triples matching

**Parameters**

- **spo** (*Tuple*[*Optional*[*Node*], *Optional*[*Node*], *Optional*[*Node*]]) –
- **context** (*Optional*[*Graph*]) –
- **txn** (*Optional*[*Any*]) –

**Return type**`Generator`[*Tuple*[*Tuple*[*Node*, *Node*, *Node*], *Generator*[*Optional*[*Graph*], *None*, *None*]], *None*, *None*]**rdflib.plugins.stores.concurrent module****class** `rdflib.plugins.stores.concurrent.ConcurrentStore`(*store*)Bases: `object`

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.stores.concurrent',
'__init__': <function ConcurrentStore.__init__>, 'add': <function
ConcurrentStore.add>, 'remove': <function ConcurrentStore.remove>, 'triples':
<function ConcurrentStore.triples>, '__len__': <function ConcurrentStore.__len__>,
'_ConcurrentStore__begin_read': <function ConcurrentStore.__begin_read>,
'_ConcurrentStore__end_read': <function ConcurrentStore.__end_read>, '__dict__':
<attribute '__dict__' of 'ConcurrentStore' objects>, '__weakref__': <attribute
'__weakref__' of 'ConcurrentStore' objects>, '__doc__': None, '__annotations__':
{}})
```

`__init__`(*store*)`__len__`()`__module__` = `'rdflib.plugins.stores.concurrent'``__weakref__`

list of weak references to the object (if defined)

**add**(*triple*)

**remove**(*triple*)

**triples**(*triple*)

**class** rdflib.plugins.stores.concurrent.**ResponsibleGenerator**(*gen, cleanup*)

Bases: [object](#)

A generator that will help clean up when it is done being used.

**\_\_del\_\_**()

**\_\_init\_\_**(*gen, cleanup*)

**\_\_iter\_\_**()

**\_\_module\_\_** = 'rdflib.plugins.stores.concurrent'

**\_\_next\_\_**()

**\_\_slots\_\_** = ['cleanup', 'gen']

**cleanup**

**gen**

## rdflib.plugins.stores.memory module

**class** rdflib.plugins.stores.memory.**Memory**(*configuration=None, identifier=None*)

Bases: [Store](#)

An in memory implementation of a triple store.

Same as SimpleMemory above, but is Context-aware, Graph-aware, and Formula-aware Authors: Ashley Sommer

### Parameters

- **configuration** ([Optional\[str\]](#)) –
- **identifier** ([Optional\[Identifier\]](#)) –

**\_\_init\_\_**(*configuration=None, identifier=None*)

identifier: URIRef of the Store. Defaults to CWD configuration: string containing information open can use to connect to datastore.

### Parameters

- **configuration** ([Optional\[str\]](#)) –
- **identifier** ([Optional\[Identifier\]](#)) –

**\_\_len\_\_**(*context=None*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

### Parameters

**context** ([Optional\[Graph\]](#)) – a graph instance to query or None

### Return type

[int](#)



```
__module__ = 'rdflib.plugins.stores.memory'
```

```
add(triple, context, quoted=False)
```

Add a triple to the store of triples.

#### Parameters

- **triple** (`Tuple[Node, Node, Node]`) –
- **context** (`Graph`) –
- **quoted** (`bool`) –

#### Return type

`None`

```
add_graph(graph)
```

Add a graph to the store, no effect if the graph already exists. :type graph: `Graph` :param graph: a Graph instance

#### Return type

`None`

```
bind(prefix, namespace, override=True)
```

#### Parameters

- **override** (`bool`) – rebind, even if the given namespace is already bound to another prefix.
- **prefix** (`str`) –
- **namespace** (`URIRef`) –

#### Return type

`None`

```
context_aware: bool = True
```

```
contexts(triple=None)
```

Generator over all contexts in the graph. If triple is specified, a generator over all contexts the triple is in. if store is graph\_aware, may also return empty contexts

#### Return type

`Generator[Graph, None, None]`

#### Returns

a generator over Nodes

#### Parameters

**triple** (`Optional[Tuple[Node, Node, Node]]`) –

```
formula_aware: bool = True
```

```
graph_aware: bool = True
```

```
namespace(prefix)
```

#### Parameters

**prefix** (`str`) –

#### Return type

`Optional[URIRef]`

**namespaces()**

**Return type**

`Iterator[Tuple[str, URIRef]]`

**prefix(namespace)**

**Parameters**

**namespace** (*URIRef*) –

**Return type**

`Optional[str]`

**query(query, initNs, initBindings, queryGraph, \*\*kwargs)**

If stores provide their own SPARQL implementation, override this.

queryGraph is None, a *URIRef* or ‘\_\_UNION\_\_’ If None the graph is specified in the query-string/object  
If *URIRef* it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried  
(This is used by *ConjunctiveGraphs* Values other than None obviously only makes sense for context-aware stores.)

**Parameters**

- **query** (*Union[Query, str]*) –
- **initNs** (*Mapping[str, Any]*) –
- **initBindings** (*Mapping[str, Identifier]*) –
- **queryGraph** (*str*) –

**Return type**

*Result*

**remove(triple\_pattern, context=None)**

Remove the set of triples matching the pattern from the store

**Parameters**

- **triple\_pattern** (*Tuple[Optional[Node], Optional[Node], Optional[Node]]*) –
- **context** (*Optional[Graph]*) –

**Return type**

*None*

**remove\_graph(graph)**

Remove a graph from the store, this should also remove all triples in the graph

**Parameters**

- **graphid** – a *Graph* instance
- **graph** (*Graph*) –

**Return type**

*None*

**triples(triple\_pattern, context=None)**

A generator over all the triples matching

**Parameters**

- **triple\_pattern** (*Tuple[Optional[Node], Optional[Node], Optional[Node]]*) –
- **context** (*Optional[Graph]*) –

**Return type**

`Generator[Tuple[Tuple[Node, Node, Node], Generator[Optional[Graph], None, None]], None, None]`

**update**(*update*, *initNs*, *initBindings*, *queryGraph*, *\*\*kwargs*)

If stores provide their own (SPARQL) Update implementation, override this.

*queryGraph* is `None`, a `URIRef` or `'__UNION__'` If `None` the graph is specified in the query-string/object If `URIRef` it specifies the graph to query, If `'__UNION__'` the union of all named graphs should be queried (This is used by `ConjunctiveGraphs` Values other than `None` obviously only makes sense for context-aware stores.)

**Parameters**

- **update** (`Union[Update, Any]`) –
- **initNs** (`Mapping[str, Any]`) –
- **initBindings** (`Mapping[str, Identifier]`) –
- **queryGraph** (`str`) –

**Return type**

`None`

**class** `rdflib.plugins.stores.memory.SimpleMemory`(*configuration=None*, *identifier=None*)

Bases: `Store`

A fast naive in memory implementation of a triple store.

This triple store uses nested dictionaries to store triples. Each triple is stored in two such indices as follows `spo[s][p][o] = 1` and `pos[p][o][s] = 1`.

Authors: Michel Pelletier, Daniel Krech, Stefan Niederhauser

**Parameters**

- **configuration** (`Optional[str]`) –
- **identifier** (`Optional[Identifier]`) –

**\_\_init\_\_**(*configuration=None*, *identifier=None*)

*identifier*: `URIRef` of the Store. Defaults to CWD configuration: string containing information open can use to connect to datastore.

**Parameters**

- **configuration** (`Optional[str]`) –
- **identifier** (`Optional[Identifier]`) –

**\_\_len\_\_**(*context=None*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

**Parameters**

**context** (`Optional[Graph]`) – a graph instance to query or `None`

**Return type**

`int`

**\_\_module\_\_** = `'rdflib.plugins.stores.memory'`

**add**(triple, context, quoted=False)

Add a triple to the store of triples.

**Parameters**

- **triple** (Tuple[Node, Node, Node]) –
- **context** (Graph) –
- **quoted** (bool) –

**Return type**

None

**bind**(prefix, namespace, override=True)

**Parameters**

- **override** (bool) – rebind, even if the given namespace is already bound to another prefix.
- **prefix** (str) –
- **namespace** (URIRef) –

**Return type**

None

**namespace**(prefix)

**Parameters**

- **prefix** (str) –

**Return type**

Optional[URIRef]

**namespaces**()

**Return type**

Iterator[Tuple[str, URIRef]]

**prefix**(namespace)

**Parameters**

- **namespace** (URIRef) –

**Return type**

Optional[str]

**query**(query, initNs, initBindings, queryGraph, \*\*kwargs)

If stores provide their own SPARQL implementation, override this.

queryGraph is None, a URIRef or ‘\_\_UNION\_\_’ If None the graph is specified in the query-string/object If URIRef it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried (This is used by ConjunctiveGraphs Values other than None obviously only makes sense for context-aware stores.)

**Parameters**

- **query** (Union[Query, str]) –
- **initNs** (Mapping[str, Any]) –
- **initBindings** (Mapping[str, Identifier]) –
- **queryGraph** (str) –

- **kwargs** (*Any*) –

**Return type**

*Result*

**remove**(*triple\_pattern*, *context=None*)

Remove the set of triples matching the pattern from the store

**Parameters**

- **triple\_pattern** (*Tuple*[*Optional*[*Node*], *Optional*[*Node*], *Optional*[*Node*]]) –
- **context** (*Optional*[*Graph*]) –

**Return type**

*None*

**triples**(*triple\_pattern*, *context=None*)

A generator over all the triples matching

**Parameters**

- **triple\_pattern** (*Tuple*[*Optional*[*Node*], *Optional*[*Node*], *Optional*[*Node*]]) –
- **context** (*Optional*[*Graph*]) –

**Return type**

*Iterator*[*Tuple*[*Tuple*[*Node*, *Node*, *Node*], *Iterator*[*Optional*[*Graph*]]]

**update**(*update*, *initNs*, *initBindings*, *queryGraph*, *\*\*kwargs*)

If stores provide their own (SPARQL) Update implementation, override this.

*queryGraph* is *None*, a *URIRef* or ‘\_\_UNION\_\_’ If *None* the graph is specified in the query-string/object If *URIRef* it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried (This is used by *ConjunctiveGraphs* Values other than *None* obviously only makes sense for context-aware stores.)

**Parameters**

- **update** (*Union*[*Update*, *str*]) –
- **initNs** (*Mapping*[*str*, *Any*]) –
- **initBindings** (*Mapping*[*str*, *Identifier*]) –
- **queryGraph** (*str*) –
- **kwargs** (*Any*) –

**Return type**

*None*

### rdflib.plugins.stores.regexmatching module

This wrapper intercepts calls through the store interface which make use of the *REGEXTerm* class to represent matches by REGEX instead of literal comparison.

Implemented for stores that don’t support this and essentially provides the support by replacing the *REGEXTerms* by wildcards (*None*) and matching against the results from the store it’s wrapping.

**class** *rdflib.plugins.stores.regexmatching.REGEXMatching*(*storage*)

Bases: *Store*

**\_\_init\_\_**(*storage*)

identifier: URIRef of the Store. Defaults to CWD configuration: string containing information open can use to connect to datastore.

**\_\_len\_\_**(*context=None*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

**Parameters**

**context** – a graph instance to query or None

**\_\_module\_\_** = 'rdflib.plugins.stores.regexmatching'

**add**(*triple, context, quoted=False*)

Adds the given statement to a specific context or to the model. The quoted argument is interpreted by formula-aware stores to indicate this statement is quoted/hypothetical It should be an error to not specify a context and have the quoted argument be True. It should also be an error for the quoted argument to be True when the store is not formula-aware.

**bind**(*prefix, namespace, override=True*)

**Parameters**

**override** – rebind, even if the given namespace is already bound to another prefix.

**close**(*commit\_pending\_transaction=False*)

This closes the database connection. The commit\_pending\_transaction parameter specifies whether to commit all pending transactions before closing (if the store is transactional).

**commit**()

**contexts**(*triple=None*)

Generator over all contexts in the graph. If triple is specified, a generator over all contexts the triple is in.

if store is graph\_aware, may also return empty contexts

**Returns**

a generator over Nodes

**destroy**(*configuration*)

This destroys the instance of the store identified by the configuration string.

**namespace**(*prefix*)

**namespaces**()

**open**(*configuration, create=True*)

Opens the store specified by the configuration string. If create is True a store will be created if it does not already exist. If create is False and a store does not already exist an exception is raised. An exception is also raised if a store exists, but there is insufficient permissions to open the store. This should return one of: VALID\_STORE, CORRUPTED\_STORE, or NO\_STORE

**prefix**(*namespace*)

**remove**(*triple, context=None*)

Remove the set of triples matching the pattern from the store

**remove\_context**(*identifier*)

**rollback**()

**triples**(*triple*, *context=None*)

A generator over all the triples matching the pattern. Pattern can include any objects for used for comparing against nodes in the store, for example, REGEXTerm, URIRef, Literal, BNode, Variable, Graph, QuotedGraph, Date? DateRange?

#### Parameters

**context** – A conjunctive query can be indicated by either providing a value of None, or a specific context can be queries by passing a Graph instance (if store is context aware).

**class** rdflib.plugins.stores.regexmatching.REGEXTerm(*expr*)

Bases: `str`

REGEXTerm can be used in any term slot and is interpreted as a request to perform a REGEX match (not a string comparison) using the value (pre-compiled) for checking rdf:type matches

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.stores.regexmatching',
'__doc__': '\n REGEXTerm can be used in any term slot and is interpreted as a
request to\n perform a REGEX match (not a string comparison) using the value\n
(pre-compiled) for checking rdf:type matches\n ', '__init__': <function
REGEXTerm.__init__>, '__reduce__': <function REGEXTerm.__reduce__>, '__dict__':
<attribute '__dict__' of 'REGEXTerm' objects>, '__weakref__': <attribute
'__weakref__' of 'REGEXTerm' objects>, '__annotations__': {}})
```

`__init__`(*expr*)

`__module__` = 'rdflib.plugins.stores.regexmatching'

`__reduce__`()

Helper for pickle.

`__weakref__`

list of weak references to the object (if defined)

rdflib.plugins.stores.regexmatching.regexCompareQuad(*quad*, *regexQuad*)

### rdflib.plugins.stores.sparqlconnector module

**class** rdflib.plugins.stores.sparqlconnector.SPARQLConnector(*query\_endpoint=None*,  
*update\_endpoint=None*,  
*returnFormat='xml'*, *method='GET'*,  
*auth=None*, *\*\*kwargs*)

Bases: `object`

this class deals with nitty gritty details of talking to a SPARQL server

#### Parameters

- **query\_endpoint** (Optional[`str`]) –
- **update\_endpoint** (Optional[`str`]) –
- **returnFormat** (`str`) –
- **method** (Literal['GET', 'POST', 'POST\_FORM']) –
- **auth** (Optional[Tuple[`str`, `str`]]) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugins.stores.sparqlconnector',
'__doc__': '\n this class deals with nitty gritty details of talking to a SPARQL
server\n ', '__init__': <function SPARQLConnector.__init__>, 'method': <property
object>, 'query': <function SPARQLConnector.query>, 'update': <function
SPARQLConnector.update>, '__dict__': <attribute '__dict__' of 'SPARQLConnector'
objects>, '__weakref__': <attribute '__weakref__' of 'SPARQLConnector' objects>,
'__annotations__': {'method': 'str'}})
```

```
__init__(query_endpoint=None, update_endpoint=None, returnFormat='xml', method='GET', auth=None,
**kwargs)
```

auth, if present, must be a tuple of (username, password) used for Basic Authentication

Any additional keyword arguments will be passed to to the request, and can be used to setup timeouts etc.

#### Parameters

- **query\_endpoint** (Optional[str]) –
- **update\_endpoint** (Optional[str]) –
- **returnFormat** (str) –
- **method** (Literal['GET', 'POST', 'POST\_FORM']) –
- **auth** (Optional[Tuple[str, str]]) –

```
__module__ = 'rdflib.plugins.stores.sparqlconnector'
```

```
__weakref__
```

list of weak references to the object (if defined)

**property method:** `str`

```
query(query, default_graph=None, named_graph=None)
```

#### Parameters

- **query** (str) –
- **default\_graph** (Optional[str]) –
- **named\_graph** (Optional[str]) –

#### Return type

`Result`

```
update(query, default_graph=None, named_graph=None)
```

#### Parameters

- **query** (str) –
- **default\_graph** (Optional[str]) –
- **named\_graph** (Optional[str]) –

#### Return type

`None`

**exception** `rdflib.plugins.stores.sparqlconnector.SPARQLConnectorException`

Bases: `Exception`

```
__module__ = 'rdflib.plugins.stores.sparqlconnector'
```



**\_\_weakref\_\_**

list of weak references to the object (if defined)

**rdflib.plugins.stores.sparqlstore module**

This is an RDFLib store around Ivan Herman et al.'s SPARQL service wrapper. This was first done in layer-cake, and then ported to RDFLib

```
class rdflib.plugins.stores.sparqlstore.SPARQLStore(query_endpoint=None, sparql11=True,
                                                    context_aware=True, node_to_sparql=<function
                                                    _node_to_sparql>, returnFormat='xml',
                                                    auth=None, **sparqlconnector_kwargs)
```

Bases: *SPARQLConnector*, *Store*

An RDFLib store around a SPARQL endpoint

This is context-aware and should work as expected when a context is specified.

For ConjunctiveGraphs, reading is done from the “default graph”. Exactly what this means depends on your endpoint, because SPARQL does not offer a simple way to query the union of all graphs as it would be expected for a ConjunctiveGraph. This is why we recommend using Dataset instead, which is motivated by the SPARQL 1.1.

Fuseki/TDB has a flag for specifying that the default graph is the union of all graphs (`tdb:unionDefaultGraph` in the Fuseki config).

**Warning:** By default the SPARQL Store does not support blank-nodes!

As blank-nodes act as variables in SPARQL queries, there is no way to query for a particular blank node without using non-standard SPARQL extensions.

See <http://www.w3.org/TR/sparql11-query/#BGPsparqlBNodes>

You can make use of such extensions through the `node_to_sparql` argument. For example if you want to transform `BNode('0001')` into “<bnode:b0001>”, you can use a function like this:

```
>>> def my_bnode_ext(node):
...     if isinstance(node, BNode):
...         return '<bnode:b%s>' % node
...     return _node_to_sparql(node)
>>> store = SPARQLStore('http://dbpedia.org/sparql',
...                     node_to_sparql=my_bnode_ext)
```

You can request a particular result serialization with the `returnFormat` parameter. This is a string that must have a matching plugin registered. Built in is support for `xml`, `json`, `csv`, `tsv` and `application/rdf+xml`.

The underlying `SPARQLConnector` uses the `urllib` library. Any extra `kwargs` passed to the `SPARQLStore` connector are passed to `urllib` when doing HTTP calls. I.e. you have full control of cookies/auth/headers.

Form example:

```
>>> store = SPARQLStore('...my endpoint ...', auth=('user', 'pass'))
```

will use HTTP basic auth.

**Parameters**

- **query\_endpoint** (*Optional*[*str*]) –
- **sparql11** (*bool*) –
- **context\_aware** (*bool*) –
- **node\_to\_sparql** (*Callable*[[*Node*], *str*]) –
- **returnFormat** (*str*) –
- **auth** (*Optional*[*Tuple*[*str*, *str*]]) –

**\_\_init\_\_** (*query\_endpoint=None*, *sparql11=True*, *context\_aware=True*, *node\_to\_sparql=<function \_node\_to\_sparql>*, *returnFormat='xml'*, *auth=None*, *\*\*sparqlconnector\_kwargs*)

*auth*, if present, must be a tuple of (username, password) used for Basic Authentication

Any additional keyword arguments will be passed to the request, and can be used to setup timeouts etc.

#### Parameters

- **query\_endpoint** (*Optional*[*str*]) –
- **sparql11** (*bool*) –
- **context\_aware** (*bool*) –
- **node\_to\_sparql** (*Callable*[[*Node*], *str*]) –
- **returnFormat** (*str*) –
- **auth** (*Optional*[*Tuple*[*str*, *str*]]) –

**\_\_len\_\_** (*context=None*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

#### Parameters

**context** (*Optional*[*Graph*]) – a graph instance to query or None

#### Return type

*int*

**\_\_module\_\_** = 'rdflib.plugins.stores.sparqlstore'

**add** (*\_*, *context=None*, *quoted=False*)

Adds the given statement to a specific context or to the model. The quoted argument is interpreted by formula-aware stores to indicate this statement is quoted/hypothetical. It should be an error to not specify a context and have the quoted argument be True. It should also be an error for the quoted argument to be True when the store is not formula-aware.

#### Parameters

- *\_* (*Tuple*[*Node*, *Node*, *Node*]) –
- **context** (*Optional*[*Graph*]) –
- **quoted** (*bool*) –

#### Return type

*None*

**addN** (*quads*)

Adds each item in the list of statements to a specific context. The quoted argument is interpreted by formula-aware stores to indicate this statement is quoted/hypothetical. Note that the default implementation is a redirect to add

**Parameters**

**quads** (*Iterable*[*Tuple*[*Node*, *Node*, *Node*, *Graph*]]) –

**Return type**

*None*

**add\_graph**(*graph*)

Add a graph to the store, no effect if the graph already exists. :type graph: *Graph* :param graph: a Graph instance

**Return type**

*None*

**bind**(*prefix*, *namespace*, *override=True*)

**Parameters**

- **override** (*bool*) – rebind, even if the given namespace is already bound to another prefix.
- **prefix** (*str*) –
- **namespace** (*URIRef*) –

**Return type**

*None*

**commit**()

**Return type**

*None*

**contexts**(*triple=None*)

Iterates over results to “SELECT ?NAME { GRAPH ?NAME { ?s ?p ?o } }” or “SELECT ?NAME { GRAPH ?NAME { } }” if triple is *None*.

Returns instances of this store with the SPARQL wrapper object updated via addNamedGraph(?NAME).

This causes a named-graph-uri key / value pair to be sent over the protocol.

Please note that some SPARQL endpoints are not able to find empty named graphs.

**Parameters**

**triple** (*Optional*[*Tuple*[*Node*, *Node*, *Node*]]) –

**Return type**

*Generator*[*IdentifiedNode*, *None*, *None*]

**create**(*configuration*)

**Parameters**

**configuration** (*str*) –

**Return type**

*None*

**destroy**(*configuration*)

This destroys the instance of the store identified by the configuration string.

**Parameters**

**configuration** (*str*) –

**Return type**

*None*

**formula\_aware:** bool = False

**graph\_aware:** bool = True

**namespace**(*prefix*)

**Parameters**

**prefix** (str) –

**Return type**

Optional[URIRef]

**namespaces**()

**Return type**

Iterator[Tuple[str, URIRef]]

**objects**(*subject=None, predicate=None*)

A generator of objects with the given subject and predicate

**Parameters**

- **subject** (Optional[Node]) –
- **predicate** (Optional[Node]) –

**Return type**

Generator[Node, None, None]

**open**(*configuration, create=False*)

This method is included so that calls to this Store via Graph, e.g. Graph(“SPARQLStore”), can set the required parameters

**Parameters**

- **configuration** (str) –
- **create** (bool) –

**Return type**

Optional[int]

**predicate\_objects**(*subject=None*)

A generator of (predicate, object) tuples for the given subject

**Parameters**

**subject** (Optional[Node]) –

**Return type**

Generator[Tuple[Node, Node], None, None]

**predicates**(*subject=None, object=None*)

A generator of predicates with the given subject and object

**Parameters**

- **subject** (Optional[Node]) –
- **object** (Optional[Node]) –

**Return type**

Generator[Node, None, None]

**prefix**(*namespace*)

**Parameters**

**namespace** (*URIRef*) –

**Return type**

*Optional*[*str*]

**query**(*query*, *initNs=None*, *initBindings=None*, *queryGraph=None*, *DEBUG=False*)

If stores provide their own SPARQL implementation, override this.

*queryGraph* is *None*, a *URIRef* or ‘\_\_UNION\_\_’ If *None* the graph is specified in the query-string/object If *URIRef* it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried (This is used by *ConjunctiveGraphs* Values other than *None* obviously only makes sense for context-aware stores.)

**Parameters**

- **query** (*Union*[*Query*, *str*]) –
- **initNs** (*Optional*[*Mapping*[*str*, *Any*]]) –
- **initBindings** (*Optional*[*Mapping*[*str*, *Identifier*]]) –
- **queryGraph** (*Optional*[*str*]) –
- **DEBUG** (*bool*) –

**Return type**

*Result*

**regex\_matching** = 0

**remove**(\_, *context*)

Remove the set of triples matching the pattern from the store

**Parameters**

- **\_** (*Tuple*[*Optional*[*Node*], *Optional*[*Node*], *Optional*[*Node*]]) –
- **context** (*Optional*[*Graph*]) –

**Return type**

*None*

**remove\_graph**(*graph*)

Remove a graph from the store, this should also remove all triples in the graph

**Parameters**

- **graphid** – a *Graph* instance
- **graph** (*Graph*) –

**Return type**

*None*

**rollback**()

**Return type**

*None*

**subject\_objects**(*predicate=None*)

A generator of (subject, object) tuples for the given predicate

**Parameters**

**predicate** (*Optional[Node]*) –

**Return type**

*Generator[Tuple[Node, Node], None, None]*

**subject\_predicates**(*object=None*)

A generator of (subject, predicate) tuples for the given object

**Parameters**

**object** (*Optional[Node]*) –

**Return type**

*Generator[Tuple[Node, Node], None, None]*

**subjects**(*predicate=None, object=None*)

A generator of subjects with the given predicate and object

**Parameters**

- **predicate** (*Optional[Node]*) –

- **object** (*Optional[Node]*) –

**Return type**

*Generator[Node, None, None]*

**transaction\_aware:** `bool = False`

**triples**(*spo, context=None*)

- tuple (**s**, **o**, **p**) the triple used as filter for the SPARQL select. (None, None, None) means anything.
- context **context** the graph effectively calling this method.

Returns a tuple of triples executing essentially a SPARQL like `SELECT ?subj ?pred ?obj WHERE { ?subj ?pred ?obj }`

**context** may include three parameter to refine the underlying query:

- **LIMIT**: an integer to limit the number of results
- **OFFSET**: an integer to enable paging of results
- **ORDERBY**: an instance of `Variable('s')`, `Variable('o')` or `Variable('p')` or, by default, the first 'None' from the given triple

**Warning:**

- Using **LIMIT** or **OFFSET** automatically include **ORDERBY** otherwise this is because the results are retrieved in a not deterministic way (depends on the walking path on the graph)
- Using **OFFSET** without defining **LIMIT** will discard the first **OFFSET** - 1 results

```
a_graph.LIMIT = limit
a_graph.OFFSET = offset
triple_generator = a_graph.triples(mytriple):
# do something
```

(continues on next page)

(continued from previous page)

```
# Removes LIMIT and OFFSET if not required for the next triple() calls
del a_graph.LIMIT
del a_graph.OFFSET
```

**Parameters**

- **spo** (Tuple[Optional[Node], Optional[Node], Optional[Node]]) –
- **context** (Optional[Graph]) –

**Return type**

Iterator[Tuple[Tuple[Node, Node, Node], None]]

**triples\_choices**(\_, context=None)

A variant of triples that can take a list of terms instead of a single term in any slot. Stores can implement this to optimize the response time from the import default ‘fallback’ implementation, which will iterate over each term in the list and dispatch to triples.

**Parameters**

- **\_** (Tuple[Union[Node, List[Node]], Union[Node, List[Node]], Union[Node, List[Node]]]) –
- **context** (Optional[Graph]) –

**Return type**

Generator[Tuple[Tuple[Node, Node, Node], Iterator[Optional[Graph]]], None, None]

**update**(query, initNs={}, initBindings={}, queryGraph=None, DEBUG=False)

If stores provide their own (SPARQL) Update implementation, override this.

queryGraph is None, a URIRef or ‘\_\_UNION\_\_’ If None the graph is specified in the query-string/object If URIRef it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried (This is used by ConjunctiveGraphs Values other than None obviously only makes sense for context-aware stores.)

**Parameters**

- **query** (Union[Update, str]) –
- **initNs** (Dict[str, Any]) –
- **initBindings** (Dict[str, Identifier]) –
- **queryGraph** (Optional[Identifier]) –
- **DEBUG** (bool) –

**Return type**

None

```
class rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore(query_endpoint=None,
                                                         update_endpoint=None, sparql11=True,
                                                         context_aware=True,
                                                         postAsEncoded=True,
                                                         autocommit=True, dirty_reads=False,
                                                         **kws)
```

Bases: *SPARQLStore*

A store using SPARQL queries for reading and SPARQL Update for changes.

This can be context-aware, if so, any changes will be to the given named graph only.

In favor of the SPARQL 1.1 motivated Dataset, we advise against using this with `ConjunctiveGraphs`, as it reads and writes from and to the “default graph”. Exactly what this means depends on the endpoint and can result in confusion.

For Graph objects, everything works as expected.

See the *SPARQLStore* base class for more information.

## Parameters

- `query_endpoint` (Optional[str]) –
- `update_endpoint` (Optional[str]) –
- `sparql11` (bool) –
- `context_aware` (bool) –
- `postAsEncoded` (bool) –
- `autocommit` (bool) –
- `dirty_reads` (bool) –

BLOCK\_END = '}'

```
BLOCK_FINDING_PATTERN = re.compile('(P<block_start>{)|(P<block_end>}|(?P<block_content>(\\'([^\\\\\\\\]|\\\\\\\\.)*)'|\"([^\"]\\\\\\\\|\\\\\\\\.)*\")|(\\'\\\\'\\\\'(\\'\\\\'\\\\')?(\\'\\\\'\\\\\\\\\\\\\\\\|\\\\\\\\\\\\\\\\.)*)\\\\'\\\\'\\\\'|(\"\"\"(\"\"\"|\"\"\")?([^\"]\\\\\\\\\\\\\\\\|\\\\\\\\\\\\\\\\.)*\"\"\"))(<[<>'\"{}^\\\\\\\\])
```

BLOCK\_START = '{'

[illegible][illegible]

```
COMMENT = '#[^\x0D\x0A]*(\x0D\x0A|\\Z)'
```

**ESCAPED** = '\\\\.'

```
IRIREF = '<([^>"{}|^`\\]\\\\\\\\[\\\\x00-\\\\x20])*>'
```

```
STRING_LITERAL1 = "'([^\\"
```

```
STRING_LITERAL2 = '"([^\\"\\\\]|\\\\\\\\.)*"'
```

```
STRING_LITERAL_LONG1 = '''(''|')?([^\\"\\\\]|\\\\\\\\.)*'''
```

```
STRING_LITERAL_LONG2 = '""'(('|"')?([^\\"\\\\]|\\\\\\\\.))*''
```

```
String = '\([^\\"\\\\]|\\\.)*\'|"(("[^"]*"|'\''))?([^\\"\\\\]|\\\.)*'
```



**\_\_init\_\_**(*query\_endpoint=None, update\_endpoint=None, sparql11=True, context\_aware=True, postAsEncoded=True, autocommit=True, dirty\_reads=False, \*\*kwargs*)

:param autocommit if set, the store will commit after every writing operations. If False, we only make queries on the server once commit is called.

:param dirty\_reads if set, we do not commit before reading. So you cannot read what you wrote before manually calling commit.

#### Parameters

- **query\_endpoint** (*Optional[str]*) –
- **update\_endpoint** (*Optional[str]*) –
- **sparql11** (*bool*) –
- **context\_aware** (*bool*) –
- **postAsEncoded** (*bool*) –
- **autocommit** (*bool*) –
- **dirty\_reads** (*bool*) –

**\_\_len\_\_**(*\*args, \*\*kwargs*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

#### Parameters

- **context** – a graph instance to query or None
- **args** (*Any*) –
- **kwargs** (*Any*) –

#### Return type

*int*

**\_\_module\_\_** = 'rdflib.plugins.stores.sparqlstore'

**add**(*spo, context=None, quoted=False*)

Add a triple to the store of triples.

#### Parameters

- **spo** (*Tuple[Node, Node, Node]*) –
- **context** (*Optional[Graph]*) –
- **quoted** (*bool*) –

#### Return type

*None*

**addN**(*quads*)

Add a list of quads to the store.

#### Parameters

**quads** (*Iterable[Tuple[Node, Node, Node, Graph]]*) –

#### Return type

*None*

**add\_graph**(*graph*)

Add a graph to the store, no effect if the graph already exists. :type graph: *Graph* :param graph: a Graph instance

**Return type***None***commit**()

add(), addN(), and remove() are transactional to reduce overhead of many small edits. Read and update() calls will automatically commit any outstanding edits. This should behave as expected most of the time, except that alternating writes and reads can degenerate to the original call-per-triple situation that originally existed.

**Return type***None***contexts**(\*args, \*\*kwargs)

Iterates over results to “SELECT ?NAME { GRAPH ?NAME { ?s ?p ?o } }” or “SELECT ?NAME { GRAPH ?NAME { } }” if triple is *None*.

Returns instances of this store with the SPARQL wrapper object updated via addNamedGraph(?NAME).

This causes a named-graph-uri key / value pair to be sent over the protocol.

Please note that some SPARQL endpoints are not able to find empty named graphs.

**Parameters**

- **args** (*Any*) –
- **kwargs** (*Any*) –

**Return type***Generator*[*IdentifiedNode*, *None*, *None*]**nsBindings**: Dict[str, Any]**objects**(*subject=None*, *predicate=None*)

A generator of objects with the given subject and predicate

**Parameters**

- **subject** (*Optional*[*Node*]) –
- **predicate** (*Optional*[*Node*]) –

**Return type***Generator*[*Node*, *None*, *None*]**open**(*configuration*, *create=False*)

sets the endpoint URLs for this SPARQLStore

**Parameters**

- **configuration** (*Union*[*str*, *Tuple*[*str*, *str*]]) – either a tuple of (query\_endpoint, update\_endpoint), or a string with the endpoint which is configured as query and update endpoint
- **create** (*bool*) – if True an exception is thrown.

**Return type***None*

**predicate\_objects**(*subject=None*)

A generator of (predicate, object) tuples for the given subject

**Parameters**

**subject** (Optional[Node]) –

**Return type**

Generator[Tuple[Node, Node], None, None]

**predicates**(*subject=None, object=None*)

A generator of predicates with the given subject and object

**Parameters**

- **subject** (Optional[Node]) –
- **object** (Optional[Node]) –

**Return type**

Generator[Node, None, None]

**query**(\*args, \*\*kwargs)

If stores provide their own SPARQL implementation, override this.

queryGraph is None, a URIRef or ‘\_\_UNION\_\_’ If None the graph is specified in the query-string/object  
If URIRef it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried  
(This is used by ConjunctiveGraphs Values other than None obviously only makes sense for context-aware stores.)

**Parameters**

- **args** (Any) –
- **kwargs** (Any) –

**Return type**

Result

**remove**(*spo, context*)

Remove a triple from the store

**Parameters**

- **spo** (Tuple[Optional[Node], Optional[Node], Optional[Node]]) –
- **context** (Optional[Graph]) –

**Return type**

None

**remove\_graph**(*graph*)

Remove a graph from the store, this should also remove all triples in the graph

**Parameters**

- **graphid** – a Graph instance
- **graph** (Graph) –

**Return type**

None

**rollback()**

**Return type**

`None`

**setTimeout(*timeout*)**

**Return type**

`None`

**subject\_objects(*predicate=None*)**

A generator of (subject, object) tuples for the given predicate

**Parameters**

**predicate** (`Optional[Node]`) –

**Return type**

`Generator[Tuple[Node, Node], None, None]`

**subject\_predicates(*object=None*)**

A generator of (subject, predicate) tuples for the given object

**Parameters**

**object** (`Optional[Node]`) –

**Return type**

`Generator[Tuple[Node, Node], None, None]`

**subjects(*predicate=None, object=None*)**

A generator of subjects with the given predicate and object

**Parameters**

- **predicate** (`Optional[Node]`) –
- **object** (`Optional[Node]`) –

**Return type**

`Generator[Node, None, None]`

**triples(\*args, \*\*kwargs)**

- tuple (**s**, **o**, **p**) the triple used as filter for the SPARQL select. (None, None, None) means anything.
- context **context** the graph effectively calling this method.

Returns a tuple of triples executing essentially a SPARQL like `SELECT ?subj ?pred ?obj WHERE { ?subj ?pred ?obj }`

**context** may include three parameter to refine the underlying query:

- **LIMIT**: an integer to limit the number of results
- **OFFSET**: an integer to enable paging of results
- **ORDERBY**: an instance of `Variable('s')`, `Variable('o')` or `Variable('p')` or, by default, the first 'None' from the given triple

**Warning:**

- Using **LIMIT** or **OFFSET** automatically include **ORDERBY** otherwise this is because the results are retrieved in a not deterministic way (depends on the walking path on the graph)

- Using OFFSET without defining LIMIT will discard the first OFFSET - 1 results

```
a_graph.LIMIT = limit
a_graph.OFFSET = offset
triple_generator = a_graph.triples(mytriple):
# do something
# Removes LIMIT and OFFSET if not required for the next triple() calls
del a_graph.LIMIT
del a_graph.OFFSET
```

#### Parameters

- **args** (*Any*) –
- **kwargs** (*Any*) –

#### Return type

`Iterator[Tuple[Tuple[Node, Node, Node], None]]`

**update**(*query*, *initNs*={}, *initBindings*={}, *queryGraph*=None, *DEBUG*=False)

Perform a SPARQL Update Query against the endpoint, INSERT, LOAD, DELETE etc. Setting *initNs* adds PREFIX declarations to the beginning of the update. Setting *initBindings* adds inline VALUES to the beginning of every WHERE clause. By the SPARQL grammar, all operations that support variables (namely INSERT and DELETE) require a WHERE clause. Important: *initBindings* fails if the update contains the substring 'WHERE {' which does not denote a WHERE clause, e.g. if it is part of a literal.

#### Context-aware query rewriting

- **When:** If context-awareness is enabled and the graph is not the default graph of the store.
- **Why:** To ensure consistency with the *Memory* store. The graph must accept “local” SPARQL requests (requests with no GRAPH keyword) as if it was the default graph.
- **What is done:** These “local” queries are rewritten by this store. The content of each block of a SPARQL Update operation is wrapped in a GRAPH block except if the block is empty. This basically causes INSERT, INSERT DATA, DELETE, DELETE DATA and WHERE to operate only on the context.
- **Example:** "INSERT DATA { <urn:michel> <urn:likes> <urn:pizza> }" is converted into "INSERT DATA { GRAPH <urn:graph> { <urn:michel> <urn:likes> <urn:pizza> } }".
- **Warning:** Queries are presumed to be “local” but this assumption is **not checked**. For instance, if the query already contains GRAPH blocks, the latter will be wrapped in new GRAPH blocks.
- **Warning:** A simplified grammar is used that should tolerate extensions of the SPARQL grammar. Still, the process may fail in uncommon situations and produce invalid output.

#### Parameters

- **query** (*Union[Update, str]*) –
- **initNs** (*Dict[str, Any]*) –
- **initBindings** (*Dict[str, Identifier]*) –
- **queryGraph** (*Optional[str]*) –

- `DEBUG` (`bool`) –

```
where_pattern = re.compile('(P<where>WHERE\\s*\\{)', re.IGNORECASE)
```

## Module contents

This package contains modules for additional RDFLib stores

## Module contents

Default plugins for rdflib.

This is a namespace package and contains the default plugins for rdflib.

## rdflib.tools package

### Submodules

#### rdflib.tools.chunk\_serializer module

This file provides a single function *serialize\_in\_chunks()* which can serialize a Graph into a number of NT files with a maximum number of triples or maximum file size.

There is an option to preserve any prefixes declared for the original graph in the first file, which will be a Turtle file.

```
rdflib.tools.chunk_serializer.serialize_in_chunks(g, max_triples=10000, max_file_size_kb=None,  
                                                  file_name_stem='chunk', output_dir=None,  
                                                  write_prefixes=False)
```

Serializes a given Graph into a series of n-triples with a given length.

#### Parameters

- **g** (*Graph*) – The graph to serialize.
- **max\_file\_size\_kb** (*Optional[int]*) – Maximum size per NT file in kB (1,000 bytes) Equivalent to ~6,000 triples, depending on Literal sizes.
- **max\_triples** (*int*) – Maximum size per NT file in triples Equivalent to lines in file.  
If both this parameter and `max_file_size_kb` are set, `max_file_size_kb` will be used.
- **file\_name\_stem** (*str*) – Prefix of each file name. e.g. “chunk” = chunk\_000001.nt, chunk\_000002.nt...
- **output\_dir** (*Optional[Path]*) – The directory you want the files to be written to.
- **write\_prefixes** (*bool*) – The first file created is a Turtle file containing original graph prefixes.

#### Return type

`None`

See `../test/test_tools/test_chunk_serializer.py` for examples of this in use.

## rdflib.tools.csv2rdf module

A commandline tool for semi-automatically converting CSV to RDF.

See also <https://github.com/RDFLib/pyTARQL> in the RDFlib family of tools

try: csv2rdf --help

**class** rdflib.tools.csv2rdf.CSV2RDF

Bases: `object`

```
__dict__ = mappingproxy({'__module__': 'rdflib.tools.csv2rdf', '__init__':
<function CSV2RDF.__init__>, 'triple': <function CSV2RDF.triple>, 'convert':
<function CSV2RDF.convert>, '__dict__': <attribute '__dict__' of 'CSV2RDF'
objects>, '__weakref__': <attribute '__weakref__' of 'CSV2RDF' objects>, '__doc__':
None, '__annotations__': {}})
```

`__init__()`

`__module__` = 'rdflib.tools.csv2rdf'

`__weakref__`

list of weak references to the object (if defined)

**convert**(*csvreader*)

**triple**(*s, p, o*)

## rdflib.tools.defined\_namespace\_creator module

rdflib.tools.defined\_namespace\_creator.get\_target\_namespace\_elements(*g, target\_namespace*)

### Parameters

- *g* (*Graph*) –
- *target\_namespace* (*str*) –

### Return type

`Tuple[List[Tuple[str, str]], List[str]]`

rdflib.tools.defined\_namespace\_creator.make\_dn\_file(*output\_file\_name, target\_namespace, elements\_strs, object\_id, fail*)

### Parameters

- *output\_file\_name* (*Path*) –
- *target\_namespace* (*str*) –
- *elements\_strs* (*Iterable[str]*) –
- *object\_id* (*str*) –
- *fail* (*bool*) –

### Return type

`None`

```
rdflib.tools.defined_namespace_creator.validate_namespace(namespace)
```

**Parameters**

**namespace** (*str*) –

**Return type**

*None*

```
rdflib.tools.defined_namespace_creator.validate_object_id(object_id)
```

**Parameters**

**object\_id** (*str*) –

**Return type**

*None*

### rdflib.tools.graphisomorphism module

A commandline tool for testing if RDF graphs are isomorphic, i.e. equal if BNode labels are ignored.

```
class rdflib.tools.graphisomorphism.IsomorphicTestableGraph(**kargs)
```

Bases: *Graph*

Ported from: <http://www.w3.org/2001/sw/DataAccess/proto-tests/tools/rdfdiff.py> (Sean B Palmer's RDF Graph Isomorphism Tester)

```
__eq__(G)
```

Graph isomorphism testing.

```
__hash__ = None
```

```
__init__(**kargs)
```

```
__module__ = 'rdflib.tools.graphisomorphism'
```

```
__ne__(G)
```

Negative graph isomorphism testing.

```
hashtriples()
```

```
internal_hash()
```

This is defined instead of `__hash__` to avoid a circular recursion scenario with the Memory store for rdflib which requires a hash lookup in order to return a generator of triples

```
vhash(term, done=False)
```

```
vhashtriple(triple, term, done)
```

```
vhashtriples(term, done)
```

```
rdflib.tools.graphisomorphism.main()
```



### rdflib.tools.rdf2dot module

A commandline tool for drawing RDF graphs in Graphviz DOT format

You can draw the graph of an RDF file directly:

```
rdflib.tools.rdf2dot.main()
```

```
rdflib.tools.rdf2dot.rdf2dot(g, stream, opts={})
```

Convert the RDF graph to DOT writes the dot output to the stream

### rdflib.tools.rdfpipe module

A commandline tool for parsing RDF in different formats and serializing the resulting graph to a chosen format.

```
rdflib.tools.rdfpipe.main()
```

```
rdflib.tools.rdfpipe.make_option_parser()
```

```
rdflib.tools.rdfpipe.parse_and_serialize(input_files, input_format, guess, outfile, output_format,
                                         ns_bindings, store_conn="", store_type=None)
```

### rdflib.tools.rdfs2dot module

A commandline tool for drawing RDFS Class diagrams in Graphviz DOT format

You can draw the graph of an RDFS file directly:

```
rdflib.tools.rdfs2dot.main()
```

```
rdflib.tools.rdfs2dot.rdfs2dot(g, stream, opts={})
```

Convert the RDFS schema in a graph writes the dot output to the stream

## Module contents

Various commandline tools for working with RDFLib

## Submodules

### rdflib.collection module

```
class rdflib.collection.Collection(graph, uri, seq=[])
```

Bases: `object`

See “Emulating container types”: <https://docs.python.org/reference/datamodel.html#emulating-container-types>

```

>>> from rdflib.term import Literal
>>> from rdflib.graph import Graph
>>> from pprint import pprint
>>> listname = BNode()
>>> g = Graph('Memory')
>>> listItem1 = BNode()

```

(continues on next page)

(continued from previous page)

```

>>> listItem2 = BNode()
>>> g.add((listname, RDF.first, Literal(1)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listname, RDF.rest, listItem1))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem1, RDF.first, Literal(2)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem1, RDF.rest, listItem2))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem2, RDF.rest, RDF.nil))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem2, RDF.first, Literal(3)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> c = Collection(g, listname)
>>> pprint([term.n3() for term in c])
[u'"1"^^<http://www.w3.org/2001/XMLSchema#integer>',
 u'"2"^^<http://www.w3.org/2001/XMLSchema#integer>',
 u'"3"^^<http://www.w3.org/2001/XMLSchema#integer>']

```

```

>>> Literal(1) in c
True
>>> len(c)
3
>>> c._get_container(1) == listItem1
True
>>> c.index(Literal(2)) == 1
True

```

### Parameters

- **graph** (*Graph*) –
- **uri** (*Node*) –
- **seq** (*List[Node]*) –

**\_\_delitem\_\_** (*key*)

```

>>> from rdflib.namespace import RDF, RDFS
>>> from rdflib import Graph
>>> from pprint import pformat
>>> g = Graph()
>>> a = BNode('foo')
>>> b = BNode('bar')
>>> c = BNode('baz')
>>> g.add((a, RDF.first, RDF.type))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((a, RDF.rest, b))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((b, RDF.first, RDFS.label))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((b, RDF.rest, c))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>

```

(continues on next page)

(continued from previous page)

```

>>> g.add((c, RDF.first, RDFS.comment))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((c, RDF.rest, RDF.nil))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> len(g)
6
>>> def listAncestry(node, graph):
...     for i in graph.subjects(RDF.rest, node):
...         yield i
>>> [str(node.n3())
...     for node in g.transitiveClosure(listAncestry, RDF.nil)]
['_:baz', ' _:bar', ' _:foo']
>>> lst = Collection(g, a)
>>> len(lst)
3
>>> b == lst._get_container(1)
True
>>> c == lst._get_container(2)
True
>>> del lst[1]
>>> len(lst)
2
>>> len(g)
4

```

**Parameters****key** (`int`) –**Return type**`None`

```
__dict__ = mappingproxy({'__module__': 'rdflib.collection', '__doc__': '\n See
"Emulating container types":\n
https://docs.python.org/reference/datamodel.html#emulating-container-types\n\n >>>
from rdflib.term import Literal\n >>> from rdflib.graph import Graph\n >>> from
pprint import pprint\n >>> listname = BNode()\n >>> g = Graph(\`Memory\`)\n >>>
listItem1 = BNode()\n >>> listItem2 = BNode()\n >>> g.add((listname, RDF.first,
Literal(1))) # doctest: +ELLIPSIS\n <Graph identifier=... (<class
\`rdflib.graph.Graph\`>)>\n >>> g.add((listname, RDF.rest, listItem1)) # doctest:
+ELLIPSIS\n <Graph identifier=... (<class \`rdflib.graph.Graph\`>)>\n >>>
g.add((listItem1, RDF.first, Literal(2))) # doctest: +ELLIPSIS\n <Graph
identifier=... (<class \`rdflib.graph.Graph\`>)>\n >>> g.add((listItem1, RDF.rest,
listItem2)) # doctest: +ELLIPSIS\n <Graph identifier=... (<class
\`rdflib.graph.Graph\`>)>\n >>> g.add((listItem2, RDF.rest, RDF.nil)) # doctest:
+ELLIPSIS\n <Graph identifier=... (<class \`rdflib.graph.Graph\`>)>\n >>>
g.add((listItem2, RDF.first, Literal(3))) # doctest: +ELLIPSIS\n <Graph
identifier=... (<class \`rdflib.graph.Graph\`>)>\n >>> c = Collection(g,listname)\n
>>> pprint([term.n3() for term in c])\n
[u\'"1"^^<http://www.w3.org/2001/XMLSchema#integer>\',\n
u\'"2"^^<http://www.w3.org/2001/XMLSchema#integer>\',\n
u\'"3"^^<http://www.w3.org/2001/XMLSchema#integer>\']\n\n >>> Literal(1) in c\n
True\n >>> len(c)\n 3\n >>> c._get_container(1) == listItem1\n True\n >>>
c.index(Literal(2)) == 1\n True\n ', '__init__': <function Collection.__init__>,
'n3': <function Collection.n3>, '_get_container': <function
Collection._get_container>, '__len__': <function Collection.__len__>, 'index':
<function Collection.index>, '__getitem__': <function Collection.__getitem__>,
'__setitem__': <function Collection.__setitem__>, '__delitem__': <function
Collection.__delitem__>, '__iter__': <function Collection.__iter__>, '_end':
<function Collection._end>, 'append': <function Collection.append>, '__iadd__':
<function Collection.__iadd__>, 'clear': <function Collection.clear>, '__dict__':
<attribute \'__dict__\' of \'Collection\' objects>, '__weakref__': <attribute
\'__weakref__\' of \'Collection\' objects>, '__annotations__': {}}}
```

`__getitem__(key)`

TODO

**Parameters**

**key** (`int`) –

**Return type**

`Node`

`__iadd__(other)`

**Parameters**

**other** (`Iterable[Node]`) –

`__init__(graph, uri, seq=[])`

**Parameters**

- **graph** (`Graph`) –
- **uri** (`Node`) –
- **seq** (`List[Node]`) –

`__iter__()`

Iterator over items in Collections

**Return type**`Iterator[Node]``__len__()`

length of items in collection.

**Return type**`int``__module__ = 'rdflib.collection'``__setitem__(key, value)`

TODO

**Parameters**

- **key** (`int`) –
- **value** (`Node`) –

**Return type**`None``__weakref__`

list of weak references to the object (if defined)

`append(item)`

```

>>> from rdflib.term import Literal
>>> from rdflib.graph import Graph
>>> listname = BNode()
>>> g = Graph()
>>> c = Collection(g, listname, [Literal(1), Literal(2)])
>>> links = [
...     list(g.subjects(object=i, predicate=RDF.first))[0] for i in c]
>>> len([i for i in links if (i, RDF.rest, RDF.nil) in g])
1

```

**Parameters****item** (`Node`) –**Return type**`Collection``clear()``index(item)`

Returns the 0-based numerical index of the item in the list

**Parameters****item** (`Node`) –**Return type**`int``n3()`

```

>>> from rdflib.term import Literal
>>> from rdflib.graph import Graph
>>> listname = BNode()
>>> g = Graph('Memory')
>>> listItem1 = BNode()
>>> listItem2 = BNode()
>>> g.add((listname, RDF.first, Literal(1)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listname, RDF.rest, listItem1))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem1, RDF.first, Literal(2)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem1, RDF.rest, listItem2))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem2, RDF.rest, RDF.nil))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((listItem2, RDF.first, Literal(3)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> c = Collection(g, listname)
>>> print(c.n3())
( "1"^^<http://www.w3.org/2001/XMLSchema#integer>
:rtype: :py:class:`str`

```

```

"2"^^<http://www.w3.org/2001/XMLSchema#integer>
XMLSchema#integer> )

```

```

"3"^^<http://www.w3.org/2001/

```

## rdflib.compare module

A collection of utilities for canonicalizing and inspecting graphs.

Among other things, they solve of the problem of deterministic bnode comparisons.

Warning: the time to canonicalize bnodes may increase exponentially on degenerate larger graphs. Use with care!

Example of comparing two graphs:

```

>>> g1 = Graph().parse(format='n3', data='''
...   @prefix : <http://example.org/ns#> .
...   <http://example.org> :rel
...     <http://example.org/same>,
...     [ :label "Same" ],
...     <http://example.org/a>,
...     [ :label "A" ] .
... ''')
>>> g2 = Graph().parse(format='n3', data='''
...   @prefix : <http://example.org/ns#> .
...   <http://example.org> :rel
...     <http://example.org/same>,
...     [ :label "Same" ],
...     <http://example.org/b>,
...     [ :label "B" ] .
... ''')
>>>

```

(continues on next page)

(continued from previous page)

```
>>> iso1 = to_isomorphic(g1)
>>> iso2 = to_isomorphic(g2)
```

These are not isomorphic:

```
>>> iso1 == iso2
False
```

Diff the two graphs:

```
>>> in_both, in_first, in_second = graph_diff(iso1, iso2)
```

Present in both:

```
>>> def dump_nt_sorted(g):
...     for l in sorted(g.serialize(format='nt').splitlines()):
...         if l: print(l.decode('ascii'))

>>> dump_nt_sorted(in_both)
<http://example.org>
  <http://example.org/ns#rel> <http://example.org/same> .
<http://example.org>
  <http://example.org/ns#rel> _:cbcaabaaba17fecbc304a64f8edee4335e .
_:cbcaabaaba17fecbc304a64f8edee4335e
  <http://example.org/ns#label> "Same" .
```

Only in first:

```
>>> dump_nt_sorted(in_first)
<http://example.org>
  <http://example.org/ns#rel> <http://example.org/a> .
<http://example.org>
  <http://example.org/ns#rel> _:cb124e4c6da0579f810c0ffe4eff485bd9 .
_:cb124e4c6da0579f810c0ffe4eff485bd9
  <http://example.org/ns#label> "A" .
```

Only in second:

```
>>> dump_nt_sorted(in_second)
<http://example.org>
  <http://example.org/ns#rel> <http://example.org/b> .
<http://example.org>
  <http://example.org/ns#rel> _:cb558f30e21ddfc05ca53108348338ade8 .
_:cb558f30e21ddfc05ca53108348338ade8
  <http://example.org/ns#label> "B" .
```

```
class rdflib.compare.IsomorphicGraph(**kwargs)
```

Bases: [ConjunctiveGraph](#)

An implementation of the RGDA1 graph digest algorithm.

An implementation of RGDA1 (publication below), a combination of Sayers & Karp's graph digest algorithm using sum and SHA-256 <<http://www.hpl.hp.com/techreports/2003/HPL-2003-235R1.pdf>> and traces <<http://pallini.di.uniroma1.it>>, an average case polynomial time algorithm for graph canonicalization.

McCusker, J. P. (2015). WebSig: A Digital Signature Framework for the Web. Rensselaer Polytechnic Institute, Troy, NY. <http://gradworks.umi.com/3727015.pdf>

`__eq__(other)`

Graph isomorphism testing.

`__hash__()`

Return hash(self).

`__init__(*kwargs)`

`__module__ = 'rdflib.compare'`

`__ne__(other)`

Negative graph isomorphism testing.

`graph_digest(stats=None)`

Synonym for `IsomorphicGraph.internal_hash`.

`internal_hash(stats=None)`

This is defined instead of `__hash__` to avoid a circular recursion scenario with the Memory store for rdflib which requires a hash lookup in order to return a generator of triples.

`rdflib.compare.graph_diff(g1, g2)`

Returns three sets of triples: “in both”, “in first” and “in second”.

#### Parameters

- `g1 (Graph)` –
- `g2 (Graph)` –

#### Return type

`Tuple[Graph, Graph, Graph]`

`rdflib.compare.isomorphic(graph1, graph2)`

Compare graph for equality.

Uses an algorithm to compute unique hashes which takes bnodes into account.

Examples:

```
>>> g1 = Graph().parse(format='n3', data='''
...   @prefix : <http://example.org/ns#> .
...   <http://example.org> :rel <http://example.org/a> .
...   <http://example.org> :rel <http://example.org/b> .
...   <http://example.org> :rel [ :label "A bnode." ] .
... ''')
>>> g2 = Graph().parse(format='n3', data='''
...   @prefix ns: <http://example.org/ns#> .
...   <http://example.org> ns:rel [ ns:label "A bnode." ] .
...   <http://example.org> ns:rel <http://example.org/b>,
...   <http://example.org/a> .
... ''')
>>> isomorphic(g1, g2)
True

>>> g3 = Graph().parse(format='n3', data='''
...   @prefix : <http://example.org/ns#> .
```

(continues on next page)



(continued from previous page)

```

...     <http://example.org> :rel <http://example.org/a> .
...     <http://example.org> :rel <http://example.org/b> .
...     <http://example.org> :rel <http://example.org/c> .
...     '''
>>> isomorphic(g1, g3)
False

```

**Parameters**

- **graph1** (*Graph*) –
- **graph2** (*Graph*) –

**Return type***bool*

`rdflib.compare.similar(g1, g2)`

Checks if the two graphs are “similar”.

Checks if the two graphs are “similar”, by comparing sorted triples where all bnodes have been replaced by a singular mock bnode (the `_MOCK_BNODE`).

This is a much cheaper, but less reliable, alternative to the comparison algorithm in `isomorphic`.

**Parameters**

- **g1** (*Graph*) –
- **g2** (*Graph*) –

`rdflib.compare.to_canonical_graph(g1, stats=None)`

Creates a canonical, read-only graph.

Creates a canonical, read-only graph where all bnode id:s are based on deterministical SHA-256 checksums, correlated with the graph contents.

**Parameters**

- **g1** (*Graph*) –
- **stats** (*Optional[Dict[str, Union[int, str]]]*) –

**Return type***ReadOnlyGraphAggregate*

`rdflib.compare.to_isomorphic(graph)`

**Parameters**

**graph** (*Graph*) –

**Return type***IsomorphicGraph*

### rdflib.compat module

Utility functions and objects to ease Python 2/3 compatibility, and different versions of support libraries.

`rdflib.compat.ascii(stream)`

`rdflib.compat.bopen(*args, **kwargs)`

`rdflib.compat.cast_bytes(s, enc='utf-8')`

`rdflib.compat.decodeStringEscape(s)`

`rdflib.compat.decodeUnicodeEscape(escaped)`

**Parameters**

**escaped** (`str`) –

**Return type**

`str`

`rdflib.compat.sign(n)`

### rdflib.container module

`class rdflib.container.Alt(graph, uri, seq=[])`

Bases: `Container`

`__init__(graph, uri, seq=[])`

Creates a Container

**Parameters**

- **graph** – a Graph instance
- **uri** – URI or Blank Node of the Container
- **seq** – the elements of the Container
- **rtype** – the type of Container, one of “Bag”, “Seq” or “Alt”

`__module__ = 'rdflib.container'`

`anyone()`

`class rdflib.container.Bag(graph, uri, seq=[])`

Bases: `Container`

Unordered container (no preference order of elements)

`__init__(graph, uri, seq=[])`

Creates a Container

**Parameters**

- **graph** – a Graph instance
- **uri** – URI or Blank Node of the Container
- **seq** – the elements of the Container
- **rtype** – the type of Container, one of “Bag”, “Seq” or “Alt”

```
__module__ = 'rdflib.container'
```

```
class rdflib.container.Container(graph, uri, seq=[], rtype='Bag')
```

Bases: `object`

A class for constructing RDF containers, as per <https://www.w3.org/TR/rdf11-mt/#rdf-containers>

Basic usage, creating a Bag and adding to it:

```
>>> from rdflib import Graph, BNode, Literal, Bag
>>> g = Graph()
>>> b = Bag(g, BNode(), [Literal("One"), Literal("Two"), Literal("Three")])
>>> print(g.serialize(format="turtle"))
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .

[] a rdf:Bag ;
   rdf:_1 "One" ;
   rdf:_2 "Two" ;
   rdf:_3 "Three" .

>>> # print out an item using an index reference
>>> print(b[2])
Two

>>> # add a new item
>>> b.append(Literal("Hello"))
<rdflib.container.Bag object at ...>
>>> print(g.serialize(format="turtle"))
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .

[] a rdf:Bag ;
   rdf:_1 "One" ;
   rdf:_2 "Two" ;
   rdf:_3 "Three" ;
   rdf:_4 "Hello" .
```

```
__delitem__(key)
```

Removing the item with index key or predicate `rdf:_key`

```
__dict__ = mappingproxy({'__module__': 'rdflib.container', '__doc__': 'A class for
constructing RDF containers, as per
https://www.w3.org/TR/rdf11-mt/#rdf-containers\n\n Basic usage, creating a ``Bag``
and adding to it:\n\n >>> from rdflib import Graph, BNode, Literal, Bag\n >>> g =
Graph()\n >>> b = Bag(g, BNode(), [Literal("One"), Literal("Two"),
Literal("Three")])\n >>> print(g.serialize(format="turtle"))\n @prefix rdf:
<http://www.w3.org/1999/02/22-rdf-syntax-ns#> .\n <BLANKLINE>\n [] a rdf:Bag ;\n
rdf:_1 "One" ;\n rdf:_2 "Two" ;\n rdf:_3 "Three" .\n <BLANKLINE>\n <BLANKLINE>\n\n
>>> # print out an item using an index reference\n >>> print(b[2])\n Two\n\n >>> #
add a new item\n >>> b.append(Literal("Hello")) # doctest: +ELLIPSIS\n
<rdflib.container.Bag object at ...>\n >>> print(g.serialize(format="turtle"))\n
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .\n <BLANKLINE>\n [] a
rdf:Bag ;\n rdf:_1 "One" ;\n rdf:_2 "Two" ;\n rdf:_3 "Three" ;\n rdf:_4 "Hello" .\n
<BLANKLINE>\n <BLANKLINE>\n\n ', '__init__': <function Container.__init__>, 'n3':
<function Container.n3>, '_get_container': <function Container._get_container>,
'_len__': <function Container._len__>, 'type_of_container': <function
Container.type_of_container>, 'index': <function Container.index>, '__getitem__':
<function Container._getitem__>, '__setitem__': <function Container._setitem__>,
'_delitem__': <function Container._delitem__>, 'items': <function
Container.items>, 'end': <function Container.end>, 'append': <function
Container.append>, 'append_multiple': <function Container.append_multiple>,
'clear': <function Container.clear>, '__dict__': <attribute '__dict__' of
'Container' objects>, '__weakref__': <attribute '__weakref__' of 'Container'
objects>, '__annotations__': {}}}
```

**\_\_getitem\_\_**(*key*)

Returns item of the container at index key

**\_\_init\_\_**(*graph, uri, seq=[], rtype='Bag'*)

Creates a Container

#### Parameters

- **graph** – a Graph instance
- **uri** – URI or Blank Node of the Container
- **seq** – the elements of the Container
- **rtype** – the type of Container, one of “Bag”, “Seq” or “Alt”

**\_\_len\_\_**()

Number of items in container

**\_\_module\_\_** = 'rdflib.container'

**\_\_setitem\_\_**(*key, value*)

Sets the item at index key or predicate rdf:\_key of the container to value

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**append**(*item*)

Adding item to the end of the container

**append\_multiple**(*other*)

Adding multiple elements to the container to the end which are in python list other

**clear()**

Removing all elements from the container

**end()**

**index(*item*)**

Returns the 1-based numerical index of the item in the container

**items()**

Returns a list of all items in the container

**n3()**

**type\_of\_container()**

**exception** `rdflib.container.NoElementException`(*message='rdf:Alt Container is empty'*)

Bases: `Exception`

**\_\_init\_\_**(*message='rdf:Alt Container is empty'*)

**\_\_module\_\_** = `'rdflib.container'`

**\_\_str\_\_**()

Return str(self).

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**class** `rdflib.container.Seq`(*graph, uri, seq=[]*)

Bases: `Container`

**\_\_init\_\_**(*graph, uri, seq=[]*)

Creates a Container

#### Parameters

- **graph** – a Graph instance
- **uri** – URI or Blank Node of the Container
- **seq** – the elements of the Container
- **rtype** – the type of Container, one of “Bag”, “Seq” or “Alt”

**\_\_module\_\_** = `'rdflib.container'`

**add\_at\_position**(*pos, item*)

## rdflib.events module

### Dirt Simple Events

A Dispatcher (or a subclass of Dispatcher) stores event handlers that are ‘fired’ simple event objects when interesting things happen.

Create a dispatcher:

```
>>> d = Dispatcher()
```

Now create a handler for the event and subscribe it to the dispatcher to handle Event events. A handler is a simple function or method that accepts the event as an argument:

```
>>> def handler1(event): print(repr(event))
>>> d.subscribe(Event, handler1)
<rdflib.events.Dispatcher object at ...>
```

Now dispatch a new event into the dispatcher, and see handler1 get fired:

```
>>> d.dispatch(Event(foo='bar', data='yours', used_by='the event handlers'))
<rdflib.events.Event ['data', 'foo', 'used_by']>
```

### **class** rdflib.events.Dispatcher

Bases: `object`

An object that can dispatch events to a privately managed group of subscribers.

**\_\_annotations\_\_** = {'\_dispatch\_map': 'Optional[Dict[Any, Any]]'}

**\_\_dict\_\_** = `mappingproxy({'__module__': 'rdflib.events', '__annotations__': {'_dispatch_map': 'Optional[Dict[Any, Any]]'}, '__doc__': '\n An object that can dispatch events to a privately managed group of\n subscribers.\n ', '_dispatch_map': None, 'set_map': <function Dispatcher.set_map>, 'get_map': <function Dispatcher.get_map>, 'subscribe': <function Dispatcher.subscribe>, 'dispatch': <function Dispatcher.dispatch>, '__dict__': <attribute '__dict__' of 'Dispatcher' objects>, '__weakref__': <attribute '__weakref__' of 'Dispatcher' objects>})`

**\_\_module\_\_** = 'rdflib.events'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**dispatch**(*event*)

Dispatch the given event to the subscribed handlers for the event's type

**get\_map**()

**set\_map**(*amap*)

#### **Parameters**

**amap** (`Dict[Any, Any]`) –

**subscribe**(*event\_type*, *handler*)

Subscribe the given handler to an event\_type. Handlers are called in the order they are subscribed.

### **class** rdflib.events.Event(*\*\*kw*)

Bases: `object`

An event is a container for attributes. The source of an event creates this object, or a subclass, gives it any kind of data that the events handlers need to handle the event, and then calls `notify(event)`.

The target of an event registers a function to handle the event it is interested with `subscribe()`. When a sources calls `notify(event)`, each subscriber to that event will be called in no particular order.

```
__dict__ = mappingproxy({'__module__': 'rdflib.events', '__doc__': '\n An event is
a container for attributes. The source of an event\n creates this object, or a
subclass, gives it any kind of data that\n the events handlers need to handle the
event, and then calls\n notify(event).\n\n The target of an event registers a
function to handle the event it\n is interested with subscribe(). When a sources
calls\n notify(event), each subscriber to that event will be called in no\n
particular order.\n ', '__init__': <function Event.__init__>, '__repr__':
<function Event.__repr__>, '__dict__': <attribute '__dict__' of 'Event' objects>,
'__weakref__': <attribute '__weakref__' of 'Event' objects>, '__annotations__':
{}})
```

```
__init__(**kw)
```

```
__module__ = 'rdflib.events'
```

```
__repr__()
```

```
Return repr(self).
```

```
__weakref__
```

```
list of weak references to the object (if defined)
```

## rdflib.exceptions module

TODO:

**exception** rdflib.exceptions.**Error**(msg=None)

Bases: [Exception](#)

Base class for rdflib exceptions.

### Parameters

**msg** (Optional[str]) –

```
__init__(msg=None)
```

### Parameters

**msg** (Optional[str]) –

```
__module__ = 'rdflib.exceptions'
```

```
__weakref__
```

```
list of weak references to the object (if defined)
```

**exception** rdflib.exceptions.**ParserError**(msg)

Bases: [Error](#)

RDF Parser error.

### Parameters

**msg** (str) –

```
__init__(msg)
```

### Parameters

**msg** (str) –

```
__module__ = 'rdflib.exceptions'
```

`__str__()`

Return `str(self)`.

**Return type**

`str`

**exception** `rdflib.exceptions.UniquenessError(values)`

Bases: `Error`

A uniqueness assumption was made in the context, and that is not true

**Parameters**

**values** (`Any`) –

`__init__(values)`

**Parameters**

**values** (`Any`) –

`__module__` = `'rdflib.exceptions'`

## rdflib.graph module

RDFLib defines the following kinds of Graphs:

- `Graph`
- `QuotedGraph`
- `ConjunctiveGraph`
- `Dataset`

## Graph

An RDF graph is a set of RDF triples. Graphs support the python `in` operator, as well as iteration and some operations like union, difference and intersection.

see `Graph`

## Conjunctive Graph

A Conjunctive Graph is the most relevant collection of graphs that are considered to be the boundary for closed world assumptions. This boundary is equivalent to that of the store instance (which is itself uniquely identified and distinct from other instances of `Store` that signify other Conjunctive Graphs). It is equivalent to all the named graphs within it and associated with a `_default_` graph which is automatically assigned a `BNode` for an identifier - if one isn't given.

see `ConjunctiveGraph`



## Quoted graph

The notion of an RDF graph [14] is extended to include the concept of a formula node. A formula node may occur wherever any other kind of node can appear. Associated with a formula node is an RDF graph that is completely disjoint from all other graphs; i.e. has no nodes in common with any other graph. (It may contain the same labels as other RDF graphs; because this is, by definition, a separate graph, considerations of tidiness do not apply between the graph at a formula node and any other graph.)

This is intended to map the idea of “{ N3-expression }” that is used by N3 into an RDF graph upon which RDF semantics is defined.

see [QuotedGraph](#)

## Dataset

The RDF 1.1 Dataset, a small extension to the Conjunctive Graph. The primary term is “graphs in the datasets” and not “contexts with quads” so there is a separate method to set/retrieve a graph in a dataset and to operate with dataset graphs. As a consequence of this approach, dataset graphs cannot be identified with blank nodes, a name is always required (RDFLib will automatically add a name if one is not provided at creation time). This implementation includes a convenience method to directly add a single quad to a dataset graph.

see [Dataset](#)

## Working with graphs

Instantiating Graphs with default store (Memory) and default identifier (a BNode):

```
>>> g = Graph()
>>> g.store.__class__
<class 'rdflib.plugins.stores.memory.Memory'>
>>> g.identifier.__class__
<class 'rdflib.term.BNode'>
```

Instantiating Graphs with a Memory store and an identifier - <https://rdflib.github.io>:

```
>>> g = Graph('Memory', URIRef("https://rdflib.github.io"))
>>> g.identifier
rdflib.term.URIRef('https://rdflib.github.io')
>>> str(g)
"<https://rdflib.github.io> a rdflib:Graph;rdflib:storage
[a rdflib:Store;rdflib:label 'Memory']."
```

Creating a ConjunctiveGraph - The top level container for all named Graphs in a “database”:

```
>>> g = ConjunctiveGraph()
>>> str(g.default_context)
"[a rdflib:Graph;rdflib:storage [a rdflib:Store;rdflib:label 'Memory']]."
```

Adding / removing reified triples to Graph and iterating over it directly or via triple pattern:

```
>>> g = Graph()
>>> statementId = BNode()
>>> print(len(g))
```

(continues on next page)

(continued from previous page)

```

0
>>> g.add((statementId, RDF.type, RDF.Statement))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((statementId, RDF.subject,
...       URIRef("https://rdflib.github.io/store/ConjunctiveGraph")))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((statementId, RDF.predicate, namespace.RDFS.label))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((statementId, RDF.object, Literal("Conjunctive Graph")))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> print(len(g))
4
>>> for s, p, o in g:
...     print(type(s))
...
<class 'rdflib.term.BNode'>
<class 'rdflib.term.BNode'>
<class 'rdflib.term.BNode'>
<class 'rdflib.term.BNode'>

```

```

>>> for s, p, o in g.triples((None, RDF.object, None)):
...     print(o)
...
Conjunctive Graph
>>> g.remove((statementId, RDF.type, RDF.Statement))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> print(len(g))
3

```

None terms in calls to `triples()` can be thought of as “open variables”.

Graph support set-theoretic operators, you can add/subtract graphs, as well as intersection (with multiplication operator  $g1 * g2$ ) and xor ( $g1 \wedge g2$ ).

Note that BNode IDs are kept when doing set-theoretic operations, this may or may not be what you want. Two named graphs within the same application probably want share BNode IDs, two graphs with data from different sources probably not. If your BNode IDs are all generated by RDFLib they are UUIDs and unique.

```

>>> g1 = Graph()
>>> g2 = Graph()
>>> u = URIRef("http://example.com/foo")
>>> g1.add([u, namespace.RDFS.label, Literal("foo")])
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g1.add([u, namespace.RDFS.label, Literal("bar")])
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g2.add([u, namespace.RDFS.label, Literal("foo")])
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g2.add([u, namespace.RDFS.label, Literal("bing")])
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> len(g1 + g2) # adds bing as label
3
>>> len(g1 - g2) # removes foo
1

```

(continues on next page)

(continued from previous page)

```
>>> len(g1 * g2) # only foo
1
>>> g1 += g2 # now g1 contains everything
```

Graph Aggregation - ConjunctiveGraphs and ReadOnlyGraphAggregate within the same store:

```
>>> store = plugin.get("Memory", Store)()
>>> g1 = Graph(store)
>>> g2 = Graph(store)
>>> g3 = Graph(store)
>>> stmt1 = BNode()
>>> stmt2 = BNode()
>>> stmt3 = BNode()
>>> g1.add((stmt1, RDF.type, RDF.Statement))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g1.add((stmt1, RDF.subject,
...     URIRef('https://rdflib.github.io/store/ConjunctiveGraph')))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g1.add((stmt1, RDF.predicate, namespace.RDFS.label))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g1.add((stmt1, RDF.object, Literal('Conjunctive Graph')))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g2.add((stmt2, RDF.type, RDF.Statement))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g2.add((stmt2, RDF.subject,
...     URIRef('https://rdflib.github.io/store/ConjunctiveGraph')))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g2.add((stmt2, RDF.predicate, RDF.type))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g2.add((stmt2, RDF.object, namespace.RDFS.Class))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g3.add((stmt3, RDF.type, RDF.Statement))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g3.add((stmt3, RDF.subject,
...     URIRef('https://rdflib.github.io/store/ConjunctiveGraph')))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g3.add((stmt3, RDF.predicate, namespace.RDFS.comment))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g3.add((stmt3, RDF.object, Literal(
...     'The top-level aggregate graph - The sum ' +
...     'of all named graphs within a Store')))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> len(list(ConjunctiveGraph(store).subjects(RDF.type, RDF.Statement)))
3
>>> len(list(ReadOnlyGraphAggregate([g1,g2]).subjects(
...     RDF.type, RDF.Statement)))
2
```

ConjunctiveGraphs have a `quads()` method which returns quads instead of triples, where the fourth item is the Graph (or subclass thereof) instance in which the triple was asserted:

```
>>> uniqueGraphNames = set(
```

(continues on next page)

(continued from previous page)

```

...     [graph.identifier for s, p, o, graph in ConjunctiveGraph(store
...     ).quads((None, RDF.predicate, None))]]
>>> len(uniqueGraphNames)
3
>>> unionGraph = ReadOnlyGraphAggregate([g1, g2])
>>> uniqueGraphNames = set(
...     [graph.identifier for s, p, o, graph in unionGraph.quads(
...     (None, RDF.predicate, None))]]
>>> len(uniqueGraphNames)
2

```

Parsing N3 from a string

```

>>> g2 = Graph()
>>> src = '''
... @prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
... @prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
... [ a rdf:Statement ;
...   rdf:subject <https://rdflib.github.io/store#ConjunctiveGraph>;
...   rdf:predicate rdfs:label;
...   rdf:object "Conjunctive Graph" ] .
... '''
>>> g2 = g2.parse(data=src, format="n3")
>>> print(len(g2))
4

```

Using Namespace class:

```

>>> RDFLib = Namespace("https://rdflib.github.io/")
>>> RDFLib.ConjunctiveGraph
rdflib.term.URIRef('https://rdflib.github.io/ConjunctiveGraph')
>>> RDFLib["Graph"]
rdflib.term.URIRef('https://rdflib.github.io/Graph')

```

**class** rdflib.graph.BatchAddGraph(graph, batch\_size=1000, batch\_addn=False)

Bases: `object`

Wrapper around graph that turns batches of calls to Graph's add (and optionally, addN) into calls to batched calls to addN.

#### Parameters

- graph: The graph to wrap
- batch\_size: The maximum number of triples to buffer before passing to Graph's addN
- batch\_addn: If True, then even calls to *addN* will be batched according to batch\_size

graph: The wrapped graph count: The number of triples buffered since initialization or the last call to reset batch:  
The current buffer of triples

#### Parameters

- **graph** (*Graph*) –
- **batch\_size** (*int*) –
- **batch\_addn** (*bool*) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.graph', '__doc__': "\n Wrapper
around graph that turns batches of calls to Graph's add\n (and optionally, addN)
into calls to batched calls to addN`.\n\n :Parameters:\n\n - graph: The graph to
wrap\n - batch_size: The maximum number of triples to buffer before passing to\n
Graph's addN\n - batch_addn: If True, then even calls to `addN` will be batched
according to\n batch_size\n\n graph: The wrapped graph\n count: The number of
triples buffered since initialization or the last call to reset\n batch: The
current buffer of triples\n\n ", '__init__': <function BatchAddGraph.__init__>,
'reset': <function BatchAddGraph.reset>, 'add': <function BatchAddGraph.add>,
'addN': <function BatchAddGraph.addN>, '__enter__': <function
BatchAddGraph.__enter__>, '__exit__': <function BatchAddGraph.__exit__>,
'__dict__': <attribute '__dict__' of 'BatchAddGraph' objects>, '__weakref__':
<attribute '__weakref__' of 'BatchAddGraph' objects>, '__annotations__': {}})
```

```
__enter__()
```

**Return type**

*BatchAddGraph*

```
__exit__(*exc)
```

**Return type**

*None*

```
__init__(graph, batch_size=1000, batch_addn=False)
```

**Parameters**

- **graph** (*Graph*) –
- **batch\_size** (*int*) –
- **batch\_addn** (*bool*) –

```
__module__ = 'rdflib.graph'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
add(triple_or_quad)
```

Add a triple to the buffer

**Parameters**

- **triple** – The triple to add
- **triple\_or\_quad** (*Union[Tuple[Node, Node, Node], Tuple[Node, Node, Node, Graph]]*) –

**Return type**

*BatchAddGraph*

```
addN(quads)
```

**Parameters**

**quads** (*Iterable[Tuple[Node, Node, Node, Graph]]*) –

**Return type**

*BatchAddGraph*

**reset()**

Manually clear the buffered triples and reset the count to zero

**Return type**

*BatchAddGraph*

**class** rdflib.graph.**ConjunctiveGraph**(store='default', identifier=None, default\_graph\_base=None)

Bases: *Graph*

A ConjunctiveGraph is an (unnamed) aggregation of all the named graphs in a store.

It has a default graph, whose name is associated with the graph throughout its life. `__init__()` can take an identifier to use as the name of this default graph or it will assign a BNode.

All methods that add triples work against this default graph.

All queries are carried out against the union of all graphs.

**Parameters**

- **store** (*Union[Store, str]*) –
- **identifier** (*Union[IdentifiedNode, str, None]*) –
- **default\_graph\_base** (*Optional[str]*) –

**\_\_contains\_\_**(*triple\_or\_quad*)

Support for 'triple/quad in graph' syntax

**Parameters**

**triple\_or\_quad** (*Union[Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]], Tuple[Optional[Node], Union[Path, Node, None], Optional[Node], Optional[Graph]]]*) –

**Return type**

*bool*

**\_\_init\_\_**(store='default', identifier=None, default\_graph\_base=None)

**Parameters**

- **store** (*Union[Store, str]*) –
- **identifier** (*Union[IdentifiedNode, str, None]*) –
- **default\_graph\_base** (*Optional[str]*) –

**\_\_len\_\_**()

Number of triples in the entire conjunctive graph

**Return type**

*int*

**\_\_module\_\_** = 'rdflib.graph'

**\_\_reduce\_\_**()

Helper for pickle.

**Return type**

*Tuple[Type[Graph], Tuple[Store, IdentifiedNode]]*

**\_\_str\_\_()**

Return str(self).

**Return type**

`str`

**add(*triple\_or\_quad*)**

Add a triple or quad to the store.

if a triple is given it is added to the default context

**Parameters**

- **self** (`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`) –
- **triple\_or\_quad** (`Union[Tuple[Node, Node, Node], Tuple[Node, Node, Node, Optional[Graph]]]`) –

**Return type**

`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`

**addN(*quads*)**

Add a sequence of triples with context

**Parameters**

- **self** (`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`) –
- **quads** (`Iterable[Tuple[Node, Node, Node, Graph]]`) –

**Return type**

`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`

**context\_id(*uri, context\_id=None*)**

URI#context

**Parameters**

- **uri** (`str`) –
- **context\_id** (`Optional[str]`) –

**Return type**

`URIRef`

**contexts(*triple=None*)**

Iterate over all contexts in the graph

If triple is specified, iterate over all contexts the triple is in.

**Parameters**

**triple** (`Optional[Tuple[Node, Node, Node]]`) –

**Return type**

`Generator[Graph, None, None]`

**get\_context(*identifier, quoted=False, base=None*)**

Return a context graph for the given identifier

identifier must be a URIRef or BNode.

**Parameters**

- **identifier** (`Union[IdentifiedNode, str, None]`) –
- **quoted** (`bool`) –

- **base** (`Optional[str]`) –

**Return type**

`Graph`

**get\_graph**(*identifier*)

Returns the graph identified by given identifier

**Parameters**

- **identifier** (`IdentifiedNode`) –

**Return type**

`Optional[Graph]`

**parse**(*source=None, publicID=None, format=None, location=None, file=None, data=None, \*\*args*)

Parse source adding the resulting triples to its own context (sub graph of this graph).

See `rdflib.graph.Graph.parse()` for documentation on arguments.

If the source is in a format that does not support named graphs it's triples will be added to the default graph (i.e. `Dataset.default_context`).

**Returns**

The graph into which the source was parsed. In the case of n3 it returns the root context.

**Caution:** This method can access directly or indirectly requested network or file resources, for example, when parsing JSON-LD documents with `@context` directives that point to a network location.

When processing untrusted or potentially malicious documents, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

*Changed in 7.0:* The `publicID` argument is no longer used as the identifier (i.e. name) of the default graph as was the case before version 7.0. In the case of sources that do not support named graphs, the `publicID` parameter will also not be used as the name for the graph that the data is loaded into, and instead the triples from sources that do not support named graphs will be loaded into the default graph (i.e. `ConjunctionGraph.default_context`).

**Parameters**

- **source** (`Union[IO[bytes], TextIO, InputSource, str, bytes, PurePath, None]`) –
- **publicID** (`Optional[str]`) –
- **format** (`Optional[str]`) –
- **location** (`Optional[str]`) –
- **file** (`Union[BinaryIO, TextIO, None]`) –
- **data** (`Union[str, bytes, None]`) –
- **args** (`Any`) –

**Return type**

`Graph`

**quads**(*triple\_or\_quad=None*)

Iterate over all the quads in the entire conjunctive graph



**Parameters**

**triple\_or\_quad** (Union[Tuple[Optional[Node], Optional[Node], Optional[Node]], Tuple[Optional[Node], Optional[Node], Optional[Node], Optional[Graph]], None) –

**Return type**

Generator[Tuple[Node, Node, Node, Optional[Graph]], None, None]

**remove**(triple\_or\_quad)

Removes a triple or quads

if a triple is given it is removed from all contexts

a quad is removed from the given context only

**Parameters**

- **self** (TypeVar(\_ConjunctiveGraphT, bound= ConjunctiveGraph)) –
- **triple\_or\_quad** (Union[Tuple[Node, Node, Node], Tuple[Node, Node, Node, Optional[Graph]]]) –

**Return type**

TypeVar(\_ConjunctiveGraphT, bound= ConjunctiveGraph)

**remove\_context**(context)

Removes the given context from the graph

**Parameters**

**context** (Graph) –

**Return type**

None

**triples**(triple\_or\_quad, context=None)

Iterate over all the triples in the entire conjunctive graph

For legacy reasons, this can take the context to query either as a fourth element of the quad, or as the explicit context keyword parameter. The kw param takes precedence.

**Parameters**

- **triple\_or\_quad** (Union[Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]], Tuple[Optional[Node], Union[Path, Node, None], Optional[Node], Optional[Graph]]]) –
- **context** (Optional[Graph]) –

**Return type**

Generator[Union[Tuple[Node, Node, Node], Tuple[Node, Path, Node]], None, None]

**triples\_choices**(triple, context=None)

Iterate over all the triples in the entire conjunctive graph

**Parameters**

- **triple** (Union[Tuple[List[Node], Node, Node], Tuple[Node, List[Node], Node], Tuple[Node, Node, List[Node]]]) –
- **context** (Optional[Graph]) –

**Return type**

Generator[Tuple[Node, Node, Node], None, None]

**class** rdflib.graph.Dataset(*store='default', default\_union=False, default\_graph\_base=None*)

Bases: [ConjunctiveGraph](#)

RDF 1.1 Dataset. Small extension to the Conjunctive Graph: - the primary term is graphs in the datasets and not contexts with quads, so there is a separate method to set/retrieve a graph in a dataset and operate with graphs - graphs cannot be identified with blank nodes - added a method to directly add a single quad

Examples of usage:

```
>>> # Create a new Dataset
>>> ds = Dataset()
>>> # simple triples goes to default graph
>>> ds.add((URIRef("http://example.org/a"),
...         URIRef("http://www.example.org/b"),
...         Literal("foo")))
<Graph identifier=... (<class 'rdflib.graph.Dataset'>)>
>>>
>>> # Create a graph in the dataset, if the graph name has already been
>>> # used, the corresponding graph will be returned
>>> # (ie, the Dataset keeps track of the constituent graphs)
>>> g = ds.graph(URIRef("http://www.example.com/gr"))
>>>
>>> # add triples to the new graph as usual
>>> g.add(
...     (URIRef("http://example.org/x"),
...      URIRef("http://example.org/y"),
...      Literal("bar")))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> # alternatively: add a quad to the dataset -> goes to the graph
>>> ds.add(
...     (URIRef("http://example.org/x"),
...      URIRef("http://example.org/z"),
...      Literal("foo-bar"), g))
<Graph identifier=... (<class 'rdflib.graph.Dataset'>)>
>>>
>>> # querying triples return them all regardless of the graph
>>> for t in ds.triples((None, None, None)):
...     print(t)
(rdflib.term.URIRef("http://example.org/a"),
 rdflib.term.URIRef("http://www.example.org/b"),
 rdflib.term.Literal("foo"))
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/z"),
 rdflib.term.Literal("foo-bar"))
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/y"),
 rdflib.term.Literal("bar"))
>>>
>>> # querying quads() return quads; the fourth argument can be unrestricted
>>> # (None) or restricted to a graph
>>> for q in ds.quads((None, None, None, None)):
...     print(q)
(rdflib.term.URIRef("http://example.org/a"),
 rdflib.term.URIRef("http://www.example.org/b"),
```

(continues on next page)

(continued from previous page)

```

rdflib.term.Literal("foo"),
None)
(rdflib.term.URIRef("http://example.org/x"),
rdflib.term.URIRef("http://example.org/y"),
rdflib.term.Literal("bar"),
rdflib.term.URIRef("http://www.example.com/gr"))
(rdflib.term.URIRef("http://example.org/x"),
rdflib.term.URIRef("http://example.org/z"),
rdflib.term.Literal("foo-bar"),
rdflib.term.URIRef("http://www.example.com/gr"))
>>>
>>> # unrestricted looping is equivalent to iterating over the entire Dataset
>>> for q in ds:
...     print(q)
(rdflib.term.URIRef("http://example.org/a"),
rdflib.term.URIRef("http://www.example.org/b"),
rdflib.term.Literal("foo"),
None)
(rdflib.term.URIRef("http://example.org/x"),
rdflib.term.URIRef("http://example.org/y"),
rdflib.term.Literal("bar"),
rdflib.term.URIRef("http://www.example.com/gr"))
(rdflib.term.URIRef("http://example.org/x"),
rdflib.term.URIRef("http://example.org/z"),
rdflib.term.Literal("foo-bar"),
rdflib.term.URIRef("http://www.example.com/gr"))
>>>
>>> # restricting iteration to a graph:
>>> for q in ds.quads((None, None, None, g)):
...     print(q)
(rdflib.term.URIRef("http://example.org/x"),
rdflib.term.URIRef("http://example.org/y"),
rdflib.term.Literal("bar"),
rdflib.term.URIRef("http://www.example.com/gr"))
(rdflib.term.URIRef("http://example.org/x"),
rdflib.term.URIRef("http://example.org/z"),
rdflib.term.Literal("foo-bar"),
rdflib.term.URIRef("http://www.example.com/gr"))
>>> # Note that in the call above -
>>> # ds.quads((None, None, None, "http://www.example.com/gr"))
>>> # would have been accepted, too
>>>
>>> # graph names in the dataset can be queried:
>>> for c in ds.graphs():
...     print(c) # doctest:
DEFAULT
http://www.example.com/gr
>>> # A graph can be created without specifying a name; a skolemized genid
>>> # is created on the fly
>>> h = ds.graph()
>>> for c in ds.graphs():
...     print(c)

```

(continues on next page)

(continued from previous page)

```

DEFAULT
https://rdflib.github.io/.well-known/genid/rdflib/N...
http://www.example.com/gr
>>> # Note that the Dataset.graphs() call returns names of empty graphs,
>>> # too. This can be restricted:
>>> for c in ds.graphs(empty=False):
...     print(c)
DEFAULT
http://www.example.com/gr
>>>
>>> # a graph can also be removed from a dataset via ds.remove_graph(g)

```

New in version 4.0.

#### Parameters

- **store** (`Union[Store, str]`) –
- **default\_union** (`bool`) –
- **default\_graph\_base** (`Optional[str]`) –

`__getstate__()`

#### Return type

`Tuple[Store, IdentifiedNode, Graph, bool]`

`__init__(store='default', default_union=False, default_graph_base=None)`

#### Parameters

- **store** (`Union[Store, str]`) –
- **default\_union** (`bool`) –
- **default\_graph\_base** (`Optional[str]`) –

`__iter__()`

Iterates over all quads in the store

#### Return type

`Generator[Tuple[Node, Node, Node, Optional[IdentifiedNode]], None, None]`

`__module__ = 'rdflib.graph'`

`__reduce__()`

Helper for pickle.

#### Return type

`Tuple[Type[Dataset], Tuple[Store, bool]]`

`__setstate__(state)`

#### Parameters

**state** (`Tuple[Store, IdentifiedNode, Graph, bool]`) –

#### Return type

`None`

**\_\_str\_\_()**

Return str(self).

**Return type**

`str`

**add\_graph(g)**

alias of graph for consistency

**Parameters**

**g** (`Union[IdentifiedNode, Graph, str, None]`) –

**Return type**

`Graph`

**contexts(triple=None)**

Iterate over all contexts in the graph

If triple is specified, iterate over all contexts the triple is in.

**Parameters**

**triple** (`Optional[Tuple[Node, Node, Node]]`) –

**Return type**

`Generator[Graph, None, None]`

**default\_context:** `Graph`

**graph(identifier=None, base=None)**

**Parameters**

• **identifier** (`Union[IdentifiedNode, Graph, str, None]`) –

• **base** (`Optional[str]`) –

**Return type**

`Graph`

**graphs(triple=None)**

Iterate over all contexts in the graph

If triple is specified, iterate over all contexts the triple is in.

**Parameters**

**triple** (`Optional[Tuple[Node, Node, Node]]`) –

**Return type**

`Generator[Graph, None, None]`

**parse(source=None, publicID=None, format=None, location=None, file=None, data=None, \*\*args)**

Parse an RDF source adding the resulting triples to the Graph.

See `rdflib.graph.Graph.parse()` for documentation on arguments.

The source is specified using one of source, location, file or data.

If the source is in a format that does not support named graphs it's triples will be added to the default graph (i.e. `Dataset.default_context`).

**Caution:** This method can access directly or indirectly requested network or file resources, for example, when parsing JSON-LD documents with `@context` directives that point to a network location.

When processing untrusted or potentially malicious documents, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

*Changed in 7.0:* The `publicID` argument is no longer used as the identifier (i.e. name) of the default graph as was the case before version 7.0. In the case of sources that do not support named graphs, the `publicID` parameter will also not be used as the name for the graph that the data is loaded into, and instead the triples from sources that do not support named graphs will be loaded into the default graph (i.e. `ConjunctionGraph.default_context`).

#### Parameters

- **source** (`Union[IO[bytes], TextIO, InputSource, str, bytes, PurePath, None]`) –
- **publicID** (`Optional[str]`) –
- **format** (`Optional[str]`) –
- **location** (`Optional[str]`) –
- **file** (`Union[BinaryIO, TextIO, None]`) –
- **data** (`Union[str, bytes, None]`) –
- **args** (`Any`) –

#### Return type

`Graph`

**quads**(*quad=None*)

Iterate over all the quads in the entire conjunctive graph

#### Parameters

**quad** (`Union[Tuple[Optional[Node], Optional[Node], Optional[Node]], Tuple[Optional[Node], Optional[Node], Optional[Node], Optional[Graph]], None]`) –

#### Return type

`Generator[Tuple[Node, Node, Node, Optional[IdentifiedNode]], None, None]`

**remove\_graph**(*g*)

#### Parameters

- **self** (`TypeVar(_DatasetT, bound= Dataset)`) –
- **g** (`Union[IdentifiedNode, Graph, str, None]`) –

#### Return type

`TypeVar(_DatasetT, bound= Dataset)`

```
class rdflib.graph.Graph(store='default', identifier=None, namespace_manager=None, base=None,
                        bind_namespaces='rdflib')
```

Bases: `Node`

An RDF Graph

The constructor accepts one argument, the “store” that will be used to store the graph data (see the “store” package for stores currently shipped with rdflib).

Stores can be context-aware or unaware. Unaware stores take up (some) less space but cannot support features that require context, such as true merging/demerging of sub-graphs and provenance.

Even if used with a context-aware store, Graph will only expose the quads which belong to the default graph. To access the rest of the data, *ConjunctiveGraph* or *Dataset* classes can be used instead.

The Graph constructor can take an identifier which identifies the Graph by name. If none is given, the graph is assigned a BNode for its identifier.

For more on named graphs, see: <http://www.w3.org/2004/03/trix/>

#### Parameters

- **store** (`Union[Store, str]`) –
- **identifier** (`Union[IdentifiedNode, str, None]`) –
- **namespace\_manager** (`Optional[NamespaceManager]`) –
- **base** (`Optional[str]`) –
- **bind\_namespaces** (`Literal['core', 'rdflib', 'none']`) –

`__add__` (*other*)

Set-theoretic union BNode IDs are not changed.

#### Parameters

**other** (*Graph*) –

#### Return type

*Graph*

`__and__` (*other*)

Set-theoretic intersection. BNode IDs are not changed.

#### Parameters

**other** (*Graph*) –

#### Return type

*Graph*

`__cmp__` (*other*)

#### Return type

`int`

`__contains__` (*triple*)

Support for ‘triple in graph’ syntax

#### Parameters

**triple** (`Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]]`) –

#### Return type

`bool`

```

__dict__ = mappingproxy({'__module__': 'rdflib.graph', '__doc__': 'An RDF
Graph\n\n The constructor accepts one argument, the "store"\n that will be used to
store the graph data (see the "store"\n package for stores currently shipped with
rdflib).\n\n Stores can be context-aware or unaware. Unaware stores take up\n (some)
less space but cannot support features that require\n context, such as true
merging/demerging of sub-graphs and\n provenance.\n\n Even if used with a
context-aware store, Graph will only expose the quads which\n belong to the default
graph. To access the rest of the data, `ConjunctiveGraph` or\n `Dataset` classes can
be used instead.\n\n The Graph constructor can take an identifier which identifies
the Graph\n by name. If none is given, the graph is assigned a BNode for its\n
identifier.\n\n For more on named graphs, see: http://www.w3.org/2004/03/trix/\n ',
'__init__': <function Graph.__init__>, 'store': <property object>, 'identifier':
<property object>, 'namespace_manager': <property object>, '__repr__': <function
Graph.__repr__>, '__str__': <function Graph.__str__>, 'toPython': <function
Graph.toPython>, 'destroy': <function Graph.destroy>, 'commit': <function
Graph.commit>, 'rollback': <function Graph.rollback>, 'open': <function
Graph.open>, 'close': <function Graph.close>, 'add': <function Graph.add>, 'addN':
<function Graph.addN>, 'remove': <function Graph.remove>, 'triples': <function
Graph.triples>, '__getitem__': <function Graph.__getitem__>, '__len__': <function
Graph.__len__>, '__iter__': <function Graph.__iter__>, '__contains__': <function
Graph.__contains__>, '__hash__': <function Graph.__hash__>, '__cmp__': <function
Graph.__cmp__>, '__eq__': <function Graph.__eq__>, '__lt__': <function
Graph.__lt__>, '__le__': <function Graph.__le__>, '__gt__': <function
Graph.__gt__>, '__ge__': <function Graph.__ge__>, '__iadd__': <function
Graph.__iadd__>, '__isub__': <function Graph.__isub__>, '__add__': <function
Graph.__add__>, '__mul__': <function Graph.__mul__>, '__sub__': <function
Graph.__sub__>, '__xor__': <function Graph.__xor__>, '__or__': <function
Graph.__add__>, '__and__': <function Graph.__mul__>, 'set': <function Graph.set>,
'subjects': <function Graph.subjects>, 'predicates': <function Graph.predicates>,
'objects': <function Graph.objects>, 'subject_predicates': <function
Graph.subject_predicates>, 'subject_objects': <function Graph.subject_objects>,
'predicate_objects': <function Graph.predicate_objects>, 'triples_choices':
<function Graph.triples_choices>, 'value': <function Graph.value>, 'items':
<function Graph.items>, 'transitiveClosure': <function Graph.transitiveClosure>,
'transitive_objects': <function Graph.transitive_objects>, 'transitive_subjects':
<function Graph.transitive_subjects>, 'qname': <function Graph.qname>,
'compute_qname': <function Graph.compute_qname>, 'bind': <function Graph.bind>,
'namespaces': <function Graph.namespaces>, 'absolutize': <function
Graph.absolutize>, 'serialize': <function Graph.serialize>, 'print': <function
Graph.print>, 'parse': <function Graph.parse>, 'query': <function Graph.query>,
'update': <function Graph.update>, 'n3': <function Graph.n3>, '__reduce__':
<function Graph.__reduce__>, 'isomorphic': <function Graph.isomorphic>,
'connected': <function Graph.connected>, 'all_nodes': <function Graph.all_nodes>,
'collection': <function Graph.collection>, 'resource': <function Graph.resource>,
'_process_skolem_tuples': <function Graph._process_skolem_tuples>, 'skolemize':
<function Graph.skolemize>, 'de_skolemize': <function Graph.de_skolemize>, 'cbd':
<function Graph.cbd>, '__dict__': <attribute '__dict__' of 'Graph' objects>,
'__weakref__': <attribute '__weakref__' of 'Graph' objects>, '__annotations__':
{'__identifier': '_ContextIdentifierType', '__store': 'Store'}})

```

`__eq__(other)`

Return self==value.

Return type



`bool``__ge__(other)`

Return self&gt;=value.

**Parameters****other** (*Graph*) –**Return type**`bool``__getitem__(item)`

A graph can be “sliced” as a shortcut for the triples method The python slice syntax is (ab)used for specifying triples. A generator over matches is returned, the returned tuples include only the parts not given

```
>>> import rdflib
>>> g = rdflib.Graph()
>>> g.add((rdflib.URIRef("urn:bob"), namespace.RDFS.label, rdflib.Literal("Bob"
↪)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
```

```
>>> list(g[rdflib.URIRef("urn:bob")]) # all triples about bob
[(rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#label'), rdflib.term.
↪Literal('Bob'))]
```

```
>>> list(g[:namespace.RDFS.label]) # all label triples
[(rdflib.term.URIRef('urn:bob'), rdflib.term.Literal('Bob'))]
```

```
>>> list(g[:,rdflib.Literal("Bob")]) # all triples with bob as object
[(rdflib.term.URIRef('urn:bob'), rdflib.term.URIRef('http://www.w3.org/2000/01/
↪rdf-schema#label'))]
```

Combined with SPARQL paths, more complex queries can be written concisely:

Name of all Bobs friends:

```
g[bob : FOAF.knows/FOAF.name ]
```

Some label for Bob:

```
g[bob : DC.title|FOAF.name|RDFS.label]
```

All friends and friends of friends of Bob

```
g[bob : FOAF.knows * "+"]
```

etc.

New in version 4.0.

`__gt__(other)`

Return self&gt;value.

**Return type**`bool``__hash__()`

Return hash(self).

**Return type**`int`

**\_\_iadd\_\_**(*other*)

Add all triples in Graph *other* to Graph. BNode IDs are not changed.

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **other** (`Iterable[Tuple[Node, Node, Node]]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**\_\_init\_\_**(*store='default', identifier=None, namespace\_manager=None, base=None, bind\_namespaces='rdflib'*)

**Parameters**

- **store** (`Union[Store, str]`) –
- **identifier** (`Union[IdentifiedNode, str, None]`) –
- **namespace\_manager** (`Optional[NamespaceManager]`) –
- **base** (`Optional[str]`) –
- **bind\_namespaces** (`Literal['core', 'rdflib', 'none']`) –

**\_\_isub\_\_**(*other*)

Subtract all triples in Graph *other* from Graph. BNode IDs are not changed.

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **other** (`Iterable[Tuple[Node, Node, Node]]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**\_\_iter\_\_**()

Iterates over all triples in the store

**Return type**

`Generator[Tuple[Node, Node, Node], None, None]`

**\_\_le\_\_**(*other*)

Return self<=value.

**Parameters**

- **other** (`Graph`) –

**Return type**

`bool`

**\_\_len\_\_**()

Returns the number of triples in the graph

If context is specified then the number of triples in the context is returned instead.

**Return type**

`int`

```

__lt__(other)
    Return self<value.

    Return type
    bool

__module__ = 'rdflib.graph'

__mul__(other)
    Set-theoretic intersection. BNode IDs are not changed.

    Parameters
    other (Graph) –

    Return type
    Graph

__or__(other)
    Set-theoretic union BNode IDs are not changed.

    Parameters
    other (Graph) –

    Return type
    Graph

__reduce__()
    Helper for pickle.

    Return type
    Tuple[Type[Graph], Tuple[Store, IdentifiedNode]]

__repr__()
    Return repr(self).

    Return type
    str

__str__()
    Return str(self).

    Return type
    str

__sub__(other)
    Set-theoretic difference. BNode IDs are not changed.

    Parameters
    other (Graph) –

    Return type
    Graph

__weakref__
    list of weak references to the object (if defined)

__xor__(other)
    Set-theoretic XOR. BNode IDs are not changed.

    Parameters
    other (Graph) –

```

**Return type***Graph***absolutize**(*uri*, *defrag=1*)

Turn uri into an absolute URI if it's not one already

**Parameters**

- **uri** (*str*) –
- **defrag** (*int*) –

**Return type***URIRef***add**(*triple*)

Add a triple with self as context

**Parameters**

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **triple** (*Tuple*[*Node*, *Node*, *Node*]) –

**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**addN**(*quads*)

Add a sequence of triple with context

**Parameters**

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **quads** (*Iterable*[*Tuple*[*Node*, *Node*, *Node*, *Graph*]]) –

**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**all\_nodes**()**Return type***Set*[*Node*]**bind**(*prefix*, *namespace*, *override=True*, *replace=False*)

Bind prefix to namespace

If override is True will bind namespace to given prefix even if namespace was already bound to a different prefix.

if replace, replace any existing prefix with the new namespace

for example: graph.bind("foaf", "http://xmlns.com/foaf/0.1/")

**Parameters**

- **prefix** (*Optional*[*str*]) –
- **namespace** (*Any*) –
- **override** (*bool*) –
- **replace** (*bool*) –

**Return type***None*

**cbd**(*resource*, \*, *target\_graph=None*)

Retrieves the Concise Bounded Description of a Resource from a Graph

Concise Bounded Description (CBD) is defined in [1] as:

Given a particular node (the starting node) in a particular RDF graph (the source graph), a subgraph of that particular graph, taken to comprise a concise bounded description of the resource denoted by the starting node, can be identified as follows:

1. **Include in the subgraph all statements in the source graph where the subject of the statement is the**  
starting node;
2. **Recursively, for all statements identified in the subgraph thus far having a blank node object, include**  
in the subgraph all statements in the source graph where the subject of the statement is the blank node in question and which are not already included in the subgraph.
3. **Recursively, for all statements included in the subgraph thus far, for all reifications of each statement**  
in the source graph, include the concise bounded description beginning from the `rdf:Statement` node of each reification.

This results in a subgraph where the object nodes are either URI references, literals, or blank nodes not serving as the subject of any statement in the graph.

[1] <https://www.w3.org/Submission/CBD/>

#### Parameters

- **resource** (*Node*) – a `URIRef` object, of the Resource for queried for
- **target\_graph** (*Optional[Graph]*) – Optionally, a graph to add the CBD to; otherwise, a new graph is created for the CBD

#### Return type

*Graph*

#### Returns

a `Graph`, subgraph of self if no graph was provided otherwise the provided graph

**close**(*commit\_pending\_transaction=False*)

Close the graph store

Might be necessary for stores that require closing a connection to a database or releasing some resource.

#### Parameters

- **commit\_pending\_transaction** (*bool*) –

#### Return type

*None*

**collection**(*identifier*)

Create a new `Collection` instance.

Parameters:

- **identifier**: a `URIRef` or `BNode` instance.

Example:

```
>>> graph = Graph()
>>> uri = URIRef("http://example.org/resource")
>>> collection = graph.collection(uri)
```

(continues on next page)

(continued from previous page)

```

>>> assert isinstance(collection, Collection)
>>> assert collection.uri is uri
>>> assert collection.graph is graph
>>> collection += [ Literal(1), Literal(2) ]

```

**Parameters****identifier** (*Node*) –**Return type***Collection***commit()**

Commits active transactions

**Parameters****self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**compute\_qname(uri, generate=True)****Parameters**

- **uri** (*str*) –
- **generate** (*bool*) –

**Return type***Tuple*[*str*, *URIRef*, *str*]**connected()**

Check if the Graph is connected

The Graph is considered undirectional.

Performs a search on the Graph, starting from a random node. Then iteratively goes depth-first through the triplets where the node is subject and object. Return True if all nodes have been visited and False if it cannot continue and there are still unvisited nodes left.

**Return type***bool***de\_skolemize(new\_graph=None, uriref=None)****Parameters**

- **new\_graph** (*Optional*[*Graph*]) –
- **uriref** (*Optional*[*URIRef*]) –

**Return type***Graph***destroy(configuration)**

Destroy the store identified by configuration if supported

**Parameters**

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **configuration** (*str*) –

**Return type**`TypeVar(_GraphT, bound= Graph)`**property identifier:** `IdentifiedNode`**isomorphic**(*other*)

does a very basic check if these graphs are the same If no BNodes are involved, this is accurate.

See `rdflib.compare` for a correct implementation of isomorphism checks

**Parameters**

**other** (`Graph`) –

**Return type**`bool`**items**(*list*)

Generator over all items in the resource specified by list

list is an RDF collection.

**Parameters**

**list** (`Node`) –

**Return type**`Generator[Node, None, None]`**n3**()

Return an n3 identifier for the Graph

**Return type**`str`**property namespace\_manager:** `NamespaceManager`

this graph's namespace-manager

**namespaces**()

Generator over all the prefix, namespace tuples

**Return type**`Generator[Tuple[str, URIRef], None, None]`**objects**(*subject=None, predicate=None, unique=False*)

A generator of (optionally unique) objects with the given subject and predicate

**Parameters**

- **subject** (`Optional[Node]`) –
- **predicate** (`Union[None, Path, Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Node, None, None]`**open**(*configuration, create=False*)

Open the graph store

Might be necessary for stores that require opening a connection to a database or acquiring some resource.

**Parameters**

- **configuration** (`str`) –

- **create** (*bool*) –

**Return type***Optional*[*int*]

**parse**(*source=None, publicID=None, format=None, location=None, file=None, data=None, \*\*args*)

Parse an RDF source adding the resulting triples to the Graph.

The source is specified using one of source, location, file or data.

**Caution:** This method can access directly or indirectly requested network or file resources, for example, when parsing JSON-LD documents with `@context` directives that point to a network location.

When processing untrusted or potentially malicious documents, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Parameters**

- **source** (*Union*[*IO*[*bytes*], *TextIO*, *InputSource*, *str*, *bytes*, *PurePath*, *None*]) – An *InputSource*, file-like object, *Path* like object, or string. In the case of a string the string is the location of the source.
- **location** (*Optional*[*str*]) – A string indicating the relative or absolute URL of the source. *Graph*’s *absolutize* method is used if a relative location is specified.
- **file** (*Union*[*BinaryIO*, *TextIO*, *None*]) – A file-like object.
- **data** (*Union*[*str*, *bytes*, *None*]) – A string containing the data to be parsed.
- **format** (*Optional*[*str*]) – Used if format can not be determined from source, e.g. file extension or Media Type. Defaults to text/turtle. Format support can be extended with plugins, but “xml”, “n3” (use for turtle), “nt” & “trix” are built in.
- **publicID** (*Optional*[*str*]) – the logical URI to use as the document base. If None specified the document location is used (at least in the case where there is a document location). This is used as the base URI when resolving relative URIs in the source document, as defined in *IETF RFC 3986*, given the source document does not define a base URI.

**Return type***Graph***Returns**

*self*, i.e. the *Graph* instance.

Examples:

```
>>> my_data = '''
... <rdf:RDF
...   xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
...   xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
... >
... <rdf:Description>
...   <rdfs:label>Example</rdfs:label>
...   <rdfs:comment>This is really just an example.</rdfs:comment>
... </rdf:Description>
```

(continues on next page)



(continued from previous page)

```

... </rdf:RDF>
... '''
>>> import os, tempfile
>>> fd, file_name = tempfile.mkstemp()
>>> f = os.fdopen(fd, "w")
>>> dummy = f.write(my_data) # Returns num bytes written
>>> f.close()

```

```

>>> g = Graph()
>>> result = g.parse(data=my_data, format="application/rdf+xml")
>>> len(g)
2

```

```

>>> g = Graph()
>>> result = g.parse(location=file_name, format="application/rdf+xml")
>>> len(g)
2

```

```

>>> g = Graph()
>>> with open(file_name, "r") as f:
...     result = g.parse(f, format="application/rdf+xml")
>>> len(g)
2

```

```

>>> os.remove(file_name)

```

```

>>> # default turtle parsing
>>> result = g.parse(data="<http://example.com/a> <http://example.com/a> <http://
↳ /example.com/a> .")
>>> len(g)
3

```

**Parameters****args** (*Any*) –**predicate\_objects** (*subject=None, unique=False*)

A generator of (optionally unique) (predicate, object) tuples for the given subject

**Parameters**

- **subject** (*Optional[Node]*) –
- **unique** (*bool*) –

**Return type***Generator[Tuple[Node, Node], None, None]***predicates** (*subject=None, object=None, unique=False*)

A generator of (optionally unique) predicates with the given subject and object

**Parameters**

- **subject** (*Optional[Node]*) –

- **object** (`Optional[Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Node, None, None]`

```
print(format='turtle', encoding='utf-8', out=None)
```

**Parameters**

- **format** (`str`) –
- **encoding** (`str`) –
- **out** (`Optional[TextIO]`) –

**Return type**`None`

```
qname(uri)
```

**Parameters****uri** (`str`) –**Return type**`str`

```
query(query_object, processor='sparql', result='sparql', initNs=None, initBindings=None,
      use_store_provided=True, **kwargs)
```

Query this graph.

A type of ‘prepared queries’ can be realised by providing initial variable bindings with `initBindings`

Initial namespaces are used to resolve prefixes used in the query, if none are given, the namespaces from the graph’s namespace manager are used.

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in `SERVICE` directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Returntype**`Result`**Parameters**

- **query\_object** (`Union[str, Query]`) –
- **processor** (`Union[str, Processor]`) –
- **result** (`Union[str, Type[Result]]`) –
- **initNs** (`Optional[Mapping[str, Any]]`) –
- **initBindings** (`Optional[Mapping[str, Identifier]]`) –
- **use\_store\_provided** (`bool`) –
- **kwargs** (`Any`) –

### Return type

*Result*

### **remove**(triple)

Remove a triple from the graph

If the triple does not provide a context attribute, removes the triple from all contexts.

### Parameters

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **triple** (*Tuple*[*Optional*[*Node*], *Optional*[*Node*], *Optional*[*Node*]]) –

### Return type

*TypeVar*(*\_GraphT*, bound= *Graph*)

### **resource**(identifier)

Create a new Resource instance.

Parameters:

- **identifier**: a URIRef or BNode instance.

Example:

```
>>> graph = Graph()
>>> uri = URIRef("http://example.org/resource")
>>> resource = graph.resource(uri)
>>> assert isinstance(resource, Resource)
>>> assert resource.identifier is uri
>>> assert resource.graph is graph
```

### Parameters

**identifier** (*Union*[*Node*, *str*]) –

### Return type

*Resource*

### **rollback**()

Rollback active transactions

### Parameters

**self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –

### Return type

*TypeVar*(*\_GraphT*, bound= *Graph*)

### **serialize**(destination=None, format='turtle', base=None, encoding=None, \*\*args)

Serialize the graph.

### Parameters

- **destination** (*Union*[*str*, *PurePath*, *IO*[*bytes*], *None*]) – The destination to serialize the graph to. This can be a path as a *str* or *PurePath* object, or it can be a *IO*[*bytes*] like object. If this parameter is not supplied the serialized graph will be returned.
- **format** (*str*) – The format that the output should be written in. This value references a *Serializer* plugin. Format support can be extended with plugins, but "xml", "n3", "turtle", "nt", "pretty-xml", "trix", "trig", "nquads", "json-ld" and "hex" are built in. Defaults to "turtle".

- **base** (`Optional[str]`) – The base IRI for formats that support it. For the turtle format this will be used as the `@base` directive.
- **encoding** (`Optional[str]`) – Encoding of output.
- **args** (`Any`) – Additional arguments to pass to the `Serializer` that will be used.
- **self** (`TypeVar(_GraphT, bound= Graph)`) –

**Returns**

The serialized graph if `destination` is `None`. The serialized graph is returned as `str` if no encoding is specified, and as `bytes` if an encoding is specified.

**Return type**

`bytes` if `destination` is `None` and `encoding` is not `None`.

**Return type**

`str` if `destination` is `None` and `encoding` is `None`.

**Returns**

`self` (i.e. the `Graph` instance) if `destination` is not `None`.

**Return type**

`Graph` if `destination` is not `None`.

**set(triple)**

Convenience method to update the value of object

Remove any existing triples for subject and predicate before adding (subject, predicate, object).

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **triple** (`Tuple[Node, Node, Node]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**skolemize(new\_graph=None, bnode=None, authority=None, basepath=None)****Parameters**

- **new\_graph** (`Optional[Graph]`) –
- **bnode** (`Optional[BNode]`) –
- **authority** (`Optional[str]`) –
- **basepath** (`Optional[str]`) –

**Return type**

`Graph`

**property store: Store****subject\_objects(predicate=None, unique=False)**

A generator of (optionally unique) (subject, object) tuples for the given predicate

**Parameters**

- **predicate** (`Union[None, Path, Node]`) –
- **unique** (`bool`) –

**Return type**

`Generator[Tuple[Node, Node], None, None]`

**subject\_predicates**(*object=None, unique=False*)

A generator of (optionally unique) (subject, predicate) tuples for the given object

**Parameters**

- **object** (Optional[Node]) –
- **unique** (bool) –

**Return type**

Generator[Tuple[Node, Node], None, None]

**subjects**(*predicate=None, object=None, unique=False*)

A generator of (optionally unique) subjects with the given predicate and object

**Parameters**

- **predicate** (Union[None, Path, Node]) –
- **object** (Optional[Node]) –
- **unique** (bool) –

**Return type**

Generator[Node, None, None]

**toPython()**

**Parameters**

**self** (TypeVar(\_GraphT, bound= Graph)) –

**Return type**

TypeVar(\_GraphT, bound= Graph)

**transitiveClosure**(*func, arg, seen=None*)

Generates transitive closure of a user-defined function against the graph

```
>>> from rdflib.collection import Collection
>>> g=Graph()
>>> a=BNode("foo")
>>> b=BNode("bar")
>>> c=BNode("baz")
>>> g.add((a,RDF.first,RDF.type))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((a,RDF.rest,b))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((b,RDF.first,namespace.RDFS.label))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((b,RDF.rest,c))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((c,RDF.first,namespace.RDFS.comment))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((c,RDF.rest,RDF.nil))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> def topList(node,g):
...     for s in g.subjects(RDF.rest, node):
...         yield s
>>> def reverseList(node,g):
...     for f in g.objects(node, RDF.first):
```

(continues on next page)

(continued from previous page)

```
...     print(f)
...     for s in g.subjects(RDF.rest, node):
...         yield s
```

```
>>> [rt for rt in g.transitiveClosure(
...     topList, RDF.nil)]
[rdflib.term.BNode('baz'),
 rdflib.term.BNode('bar'),
 rdflib.term.BNode('foo')]
```

```
>>> [rt for rt in g.transitiveClosure(
...     reverseList, RDF.nil)]
http://www.w3.org/2000/01/rdf-schema#comment
http://www.w3.org/2000/01/rdf-schema#label
http://www.w3.org/1999/02/22-rdf-syntax-ns#type
[rdflib.term.BNode('baz'),
 rdflib.term.BNode('bar'),
 rdflib.term.BNode('foo')]
```

**Parameters**

- **func** (Callable[[TypeVar(\_TCArgT), *Graph*], Iterable[TypeVar(\_TCArgT)]] –
- **arg** (TypeVar(\_TCArgT)) –
- **seen** (Optional[Dict[TypeVar(\_TCArgT), int]]) –

**transitive\_objects**(*subject*, *predicate*, *remember=None*)

Transitively generate objects for the *predicate* relationship

Generated objects belong to the depth first transitive closure of the *predicate* relationship starting at *subject*.

**Parameters**

- **subject** (Optional[*Node*]) –
- **predicate** (Optional[*Node*]) –
- **remember** (Optional[Dict[Optional[*Node*], int]]) –

**Return type**

Generator[Optional[*Node*], None, None]

**transitive\_subjects**(*predicate*, *object*, *remember=None*)

Transitively generate subjects for the *predicate* relationship

Generated subjects belong to the depth first transitive closure of the *predicate* relationship starting at *object*.

**Parameters**

- **predicate** (Optional[*Node*]) –
- **object** (Optional[*Node*]) –
- **remember** (Optional[Dict[Optional[*Node*], int]]) –

**Return type**`Generator[Optional[Node], None, None]`**triples**(*triple*)

Generator over the triple store

Returns triples that match the given triple pattern. If triple pattern does not provide a context, all contexts will be searched.

**Parameters**

**triple** (`Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]]`) –

**Return type**`Generator[Union[Tuple[Node, Node, Node], Tuple[Node, Path, Node]], None, None]`**triples\_choices**(*triple*, *context=None*)**Parameters**

- **triple** (`Union[Tuple[List[Node], Node, Node], Tuple[Node, List[Node], Node], Tuple[Node, Node, List[Node]]]`) –
- **context** (`Optional[Graph]`) –

**Return type**`Generator[Tuple[Node, Node, Node], None, None]`**update**(*update\_object*, *processor='sparql'*, *initNs=None*, *initBindings=None*, *use\_store\_provided=True*, *\*\*kwargs*)

Update this graph with the given update query.

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in SERVICE directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Parameters**

- **update\_object** (`Union[Update, str]`) –
- **processor** (`Union[str, UpdateProcessor]`) –
- **initNs** (`Optional[Mapping[str, Any]]`) –
- **initBindings** (`Optional[Mapping[str, Identifier]]`) –
- **use\_store\_provided** (`bool`) –
- **kwargs** (`Any`) –

**Return type**`None`**value**(*subject=None*, *predicate=rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#value')*, *object=None*, *default=None*, *any=True*)

Get a value for a pair of two criteria

Exactly one of subject, predicate, object must be None. Useful if one knows that there may only be one value.

It is one of those situations that occur a lot, hence this ‘macro’ like utility

Parameters: subject, predicate, object – exactly one must be None default – value to be returned if no values found any – if True, return any value in the case there is more than one, else, raise UniquenessError

#### Parameters

- **subject** (`Optional[Node]`) –
- **predicate** (`Optional[Node]`) –
- **object** (`Optional[Node]`) –
- **default** (`Optional[Node]`) –
- **any** (`bool`) –

#### Return type

`Optional[Node]`

**exception** `rdflib.graph.ModificationException`

Bases: `Exception`

`__init__()`

`__module__` = `'rdflib.graph'`

`__str__()`

Return `str(self)`.

#### Return type

`str`

`__weakref__`

list of weak references to the object (if defined)

**class** `rdflib.graph.QuotedGraph(store, identifier)`

Bases: `Graph`

Quoted Graphs are intended to implement Notation 3 formulae. They are associated with a required identifier that the N3 parser *must* provide in order to maintain consistent formulae identification for scenarios such as implication and other such processing.

#### Parameters

- **store** (`Union[Store, str]`) –
- **identifier** (`Union[IdentifiedNode, str, None]`) –

`__init__(store, identifier)`

#### Parameters

- **store** (`Union[Store, str]`) –
- **identifier** (`Union[IdentifiedNode, str, None]`) –

`__module__` = `'rdflib.graph'`



**\_\_reduce\_\_()**

Helper for pickle.

**Return type**

`Tuple[Type[Graph], Tuple[Store, IdentifiedNode]]`

**\_\_str\_\_()**

Return str(self).

**Return type**

`str`

**add(triple)**

Add a triple with self as context

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **triple** (`Tuple[Node, Node, Node]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**addN(quads)**

Add a sequence of triple with context

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **quads** (`Iterable[Tuple[Node, Node, Node, Graph]]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**n3()**

Return an n3 identifier for the Graph

**Return type**

`str`

**class rdflib.graph.ReadOnlyGraphAggregate(graphs, store='default')**

Bases: `ConjunctiveGraph`

Utility class for treating a set of graphs as a single graph

Only read operations are supported (hence the name). Essentially a `ConjunctiveGraph` over an explicit subset of the entire store.

**Parameters**

- **graphs** (`List[Graph]`) –
- **store** (`Union[str, Store]`) –

**\_\_cmp\_\_(other)**

**Return type**

`int`

**\_\_contains\_\_**(*triple\_or\_quad*)

Support for 'triple/quad in graph' syntax

**Parameters**

**triple\_or\_quad** (Union[Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]], Tuple[Optional[Node], Union[Path, Node, None], Optional[Node], Optional[Graph]]]) –

**Return type**

bool

**\_\_hash\_\_**()

Return hash(self).

**Return type**

NoReturn

**\_\_iadd\_\_**(*other*)

Add all triples in Graph other to Graph. BNode IDs are not changed.

**Parameters**

- **self** (TypeVar(\_GraphT, bound= Graph)) –
- **other** (Iterable[Tuple[Node, Node, Node]]) –

**Return type**

NoReturn

**\_\_init\_\_**(*graphs, store='default'*)

**Parameters**

- **graphs** (List[Graph]) –
- **store** (Union[str, Store]) –

**\_\_isub\_\_**(*other*)

Subtract all triples in Graph other from Graph. BNode IDs are not changed.

**Parameters**

- **self** (TypeVar(\_GraphT, bound= Graph)) –
- **other** (Iterable[Tuple[Node, Node, Node]]) –

**Return type**

NoReturn

**\_\_len\_\_**()

Number of triples in the entire conjunctive graph

**Return type**

int

**\_\_module\_\_** = 'rdflib.graph'

**\_\_reduce\_\_**()

Helper for pickle.

**Return type**

NoReturn

**\_\_repr\_\_()**

Return repr(self).

**Return type**

`str`

**absolutize(uri, defrag=1)**

Turn uri into an absolute URI if it's not one already

**Parameters**

- **uri** (`str`) –
- **defrag** (`int`) –

**Return type**

`NoReturn`

**add(triple)**

Add a triple or quad to the store.

if a triple is given it is added to the default context

**Parameters**

**triple** (`Union[Tuple[Node, Node, Node], Tuple[Node, Node, Node, Optional[Graph]]]`) –

**Return type**

`NoReturn`

**addN(quads)**

Add a sequence of triples with context

**Parameters**

**quads** (`Iterable[Tuple[Node, Node, Node, Graph]]`) –

**Return type**

`NoReturn`

**bind(prefix, namespace, override=True)**

Bind prefix to namespace

If override is True will bind namespace to given prefix even if namespace was already bound to a different prefix.

if replace, replace any existing prefix with the new namespace

for example: graph.bind("foaf", "http://xmlns.com/foaf/0.1/")

**Parameters**

- **prefix** (`Optional[str]`) –
- **namespace** (`Any`) –
- **override** (`bool`) –

**Return type**

`NoReturn`

**close()**

Close the graph store

Might be necessary for stores that require closing a connection to a database or releasing some resource.

**Return type**`None`**commit()**

Commits active transactions

**Return type**`NoReturn`**compute\_qname(uri, generate=True)****Parameters**

- **uri** (`str`) –
- **generate** (`bool`) –

**Return type**`Tuple[str, URIRef, str]`**default\_context:** `Graph`**destroy(configuration)**

Destroy the store identified by configuration if supported

**Parameters**

**configuration** (`str`) –

**Return type**`NoReturn`**n3()**

Return an n3 identifier for the Graph

**Return type**`NoReturn`**namespaces()**

Generator over all the prefix, namespace tuples

**Return type**`Generator[Tuple[str, URIRef], None, None]`**open(configuration, create=False)**

Open the graph store

Might be necessary for stores that require opening a connection to a database or acquiring some resource.

**Parameters**

- **configuration** (`str`) –
- **create** (`bool`) –

**Return type**`None`**parse(source, publicID=None, format=None, \*\*args)**

Parse source adding the resulting triples to its own context (sub graph of this graph).

See `rdflib.graph.Graph.parse()` for documentation on arguments.

If the source is in a format that does not support named graphs it's triples will be added to the default graph (i.e. `Dataset.default_context`).

**Returns**

The graph into which the source was parsed. In the case of n3 it returns the root context.

**Caution:** This method can access directly or indirectly requested network or file resources, for example, when parsing JSON-LD documents with @context directives that point to a network location.

When processing untrusted or potentially malicious documents, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

*Changed in 7.0:* The `publicID` argument is no longer used as the identifier (i.e. name) of the default graph as was the case before version 7.0. In the case of sources that do not support named graphs, the `publicID` parameter will also not be used as the name for the graph that the data is loaded into, and instead the triples from sources that do not support named graphs will be loaded into the default graph (i.e. `ConjunctionGraph.default_context`).

**Parameters**

- **source** (`Union[IO[bytes], TextIO, InputSource, str, bytes, PurePath, None]`) –
- **publicID** (`Optional[str]`) –
- **format** (`Optional[str]`) –
- **args** (`Any`) –

**Return type**

`NoReturn`

**qname**(*uri*)

**Parameters**

**uri** (`str`) –

**Return type**

`str`

**quads**(*triple\_or\_quad*)

Iterate over all the quads in the entire aggregate graph

**Parameters**

**triple\_or\_quad** (`Union[Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]], Tuple[Optional[Node], Union[Path, Node, None], Optional[Node], Optional[Graph]]]`) –

**Return type**

`Generator[Tuple[Node, Union[Path, Node], Node, Graph], None, None]`

**remove**(*triple*)

Removes a triple or quads

if a triple is given it is removed from all contexts

a quad is removed from the given context only

**Parameters**

**triple** (`Union[Tuple[Node, Node, Node], Tuple[Node, Node, Node, Optional[Graph]]]`)

–

**Return type**`NoReturn`**rollback()**

Rollback active transactions

**Return type**`NoReturn`**triples(triple)**

Iterate over all the triples in the entire conjunctive graph

For legacy reasons, this can take the context to query either as a fourth element of the quad, or as the explicit context keyword parameter. The kw param takes precedence.

**Parameters**

**triple** (`Union[Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]]]`) –

**Return type**`Generator[Union[Tuple[Node, Node, Node], Tuple[Node, Path, Node]], None, None]`**triples\_choices(triple, context=None)**

Iterate over all the triples in the entire conjunctive graph

**Parameters**

- **triple** (`Union[Tuple[List[Node], Node, Node], Tuple[Node, List[Node], Node], Tuple[Node, Node, List[Node]]]`) –

- **context** (`Optional[Graph]`) –

**Return type**`Generator[Tuple[Node, Node, Node], None, None]`**class rdflib.graph.Seq(graph, subject)**

Bases: `object`

Wrapper around an RDF Seq resource

It implements a container type in Python with the order of the items returned corresponding to the Seq content. It is based on the natural ordering of the predicate names `_1`, `_2`, `_3`, etc, which is the ‘implementation’ of a sequence in RDF terms.

**Parameters**

- **graph** (`Graph`) –
- **subject** (`Node`) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.graph', '__doc__': "Wrapper around an RDF Seq resource\n\n It implements a container type in Python with the order of the items\n returned corresponding to the Seq content. It is based on the natural\n ordering of the predicate names _1, _2, _3, etc, which is the\n 'implementation' of a sequence in RDF terms.\n ", '__init__': <function Seq.__init__>, 'toPython': <function Seq.toPython>, '__iter__': <function Seq.__iter__>, '__len__': <function Seq.__len__>, '__getitem__': <function Seq.__getitem__>, '__dict__': <attribute '__dict__' of 'Seq' objects>, '__weakref__': <attribute '__weakref__' of 'Seq' objects>, '__annotations__': {'_list': 'List[Tuple[int, _ObjectType]]'}})
```

**\_\_getitem\_\_(index)**

Item given by index from the Seq

**Return type***Node***\_\_init\_\_**(*graph*, *subject*)

Parameters:

- **graph:**  
the graph containing the Seq
- **subject:**  
the subject of a Seq. Note that the init does not check whether this is a Seq, this is done in whoever creates this instance!

**Parameters**

- **graph** (*Graph*) –
- **subject** (*Node*) –

**\_\_iter\_\_**()

Generator over the items in the Seq

**Return type***Generator*[*Node*, *None*, *None*]**\_\_len\_\_**()

Length of the Seq

**Return type***int***\_\_module\_\_** = 'rdflib.graph'**\_\_weakref\_\_**

list of weak references to the object (if defined)

**toPython**()**Return type***Seq***exception** rdflib.graph.UnSupportedAggregateOperationBases: *Exception***\_\_init\_\_**()**\_\_module\_\_** = 'rdflib.graph'**\_\_str\_\_**()

Return str(self).

**Return type***str***\_\_weakref\_\_**

list of weak references to the object (if defined)

## rdflib.parser module

Parser plugin interface.

This module defines the parser plugin interface and contains other related parser support code.

The module is mainly useful for those wanting to write a parser that can plugin to rdflib. If you are wanting to invoke a parser you likely want to do so through the Graph class parse method.

**class** rdflib.parser.FileInputSource(*file*)

Bases: *InputSource*

**Parameters**

**file** (*Union*[*BinaryIO*, *TextIO*, *TextIOBase*, *RawIOBase*, *BufferedIOBase*]) –

**\_\_init\_\_**(*file*)

**Parameters**

**file** (*Union*[*BinaryIO*, *TextIO*, *TextIOBase*, *RawIOBase*, *BufferedIOBase*]) –

**\_\_module\_\_** = 'rdflib.parser'

**\_\_repr\_\_**()

Return repr(self).

**Return type**

*str*

**class** rdflib.parser.InputSource(*system\_id=None*)

Bases: *InputSource*

TODO:

**Parameters**

**system\_id** (*Optional*[*str*]) –

**\_\_init\_\_**(*system\_id=None*)

**Parameters**

**system\_id** (*Optional*[*str*]) –

**\_\_module\_\_** = 'rdflib.parser'

**close**()

**Return type**

*None*

**class** rdflib.parser.Parser

Bases: *object*

**\_\_init\_\_**()

**\_\_module\_\_** = 'rdflib.parser'

**\_\_slots\_\_** = ()

**parse**(*source, sink*)

**Parameters**

- **source** (*InputSource*) –



- **sink** (*Graph*) –

**Return type**

*None*

**class** rdflib.parser.**PythonInputSource**(*data*, *system\_id=None*)

Bases: *InputSource*

Constructs an RDFLib Parser InputSource from a Python data structure, for example, loaded from JSON with `json.load` or `json.loads`:

```
>>> import json
>>> as_string = """{
...   "@context" : {"ex" : "http://example.com/ns#"},
...   "@graph": [{"@type": "ex:item", "@id": "#example"}]}"""
>>> as_python = json.loads(as_string)
>>> source = create_input_source(data=as_python)
>>> isinstance(source, PythonInputSource)
True
```

**Parameters**

- **data** (*Any*) –
- **system\_id** (*Optional[str]*) –

**\_\_init\_\_**(*data*, *system\_id=None*)

**Parameters**

- **data** (*Any*) –
- **system\_id** (*Optional[str]*) –

**\_\_module\_\_** = 'rdflib.parser'

**close**()

**Return type**

*None*

**content\_type**: *Optional[str]*

**getPublicId**()

Returns the public identifier of this InputSource.

**Return type**

*Optional[str]*

**getSystemId**()

Returns the system identifier of this InputSource.

**Return type**

*Optional[str]*

**setPublicId**(*public\_id*)

Sets the public identifier of this InputSource.

**Parameters**

- **public\_id** (*Optional[str]*) –

**Return type**`None`**setSystemId**(*system\_id*)

Sets the system identifier of this InputSource.

**Parameters****system\_id** (`Optional[str]`) –**Return type**`None`**class** `rdflib.parser.StringInputSource`(*value*, *encoding*='utf-8', *system\_id*=None)Bases: `InputSource`

Constructs an RDFLib Parser InputSource from a Python String or Bytes

**Parameters**

- **value** (`Union[str, bytes]`) –
- **encoding** (`str`) –
- **system\_id** (`Optional[str]`) –

`__init__`(*value*, *encoding*='utf-8', *system\_id*=None)**Parameters**

- **value** (`Union[str, bytes]`) –
- **encoding** (`str`) –
- **system\_id** (`Optional[str]`) –

`__module__` = 'rdflib.parser'`content_type`: `Optional[str]`**class** `rdflib.parser.URLInputSource`(*system\_id*=None, *format*=None)Bases: `InputSource`

Constructs an RDFLib Parser InputSource from a URL to read it from the Web.

**Parameters**

- **system\_id** (`Optional[str]`) –
- **format** (`Optional[str]`) –

`__annotations__` = {'links': 'List[str]'}  
`__init__`(*system\_id*=None, *format*=None)**Parameters**

- **system\_id** (`Optional[str]`) –
- **format** (`Optional[str]`) –

`__module__` = 'rdflib.parser'

```

__repr__()
    Return repr(self).

    Return type
        str

get_alternates(type_=None)

    Parameters
        type_ (Optional[str]) –

    Return type
        List[str]

classmethod get_links(response)

    Parameters
        response (addinfourl) –

    Return type
        List[str]

classmethod getallmatchingheaders(message, name)

    Parameters
        message (Message) –

    Return type
        List[str]

links: List[str]

```

### rdflib.paths module

This module implements the SPARQL 1.1 Property path operators, as defined in:

<http://www.w3.org/TR/sparql11-query/#propertypaths>

In SPARQL the syntax is as follows:

Syntax	Matches
iri	An IRI. A path of length one.
^elt	Inverse path (object to subject).
elt1 / elt2	A sequence path of elt1 followed by elt2.
elt1   elt2	A alternative path of elt1 or elt2 (all possibilities are tried).
elt*	A path that connects the subject and object of the path by zero or more matches of elt.
elt+	A path that connects the subject and object of the path by one or more matches of elt.
elt?	A path that connects the subject and object of the path by zero or one matches of elt.
!iri or !(iri <sub>1</sub>   ...  iri <sub>n</sub> )	Negated property set. An IRI which is not one of iri <sub>1</sub> ...iri <sub>n</sub> . !iri is short for !(iri).
!^iri or !(^iri <sub>1</sub>   ...  ^iri <sub>n</sub> )	Negated property set where the excluded matches are based on reversed path. That is, not one of iri <sub>1</sub> ...iri <sub>n</sub> as reverse paths. !^iri is short for !(^iri).
!(iri <sub>1</sub>   ...  iri <sub>j</sub>  ^iri <sub>j+1</sub>   ...  ^iri <sub>n</sub> )	A combination of forward and reverse properties in a negated property set.
(elt)	A group path elt, brackets control precedence.

This module is used internally by the SPARQL engine, but the property paths can also be used to query RDFLib Graphs directly.

Where possible the SPARQL syntax is mapped to Python operators, and property path objects can be constructed from existing URIRRefs.

```
>>> from rdflib import Graph, Namespace
>>> from rdflib.namespace import FOAF
```

```
>>> ~FOAF.knows
Path(~http://xmlns.com/foaf/0.1/knows)
```

```
>>> FOAF.knows/FOAF.name
Path(http://xmlns.com/foaf/0.1/knows / http://xmlns.com/foaf/0.1/name)
```

```
>>> FOAF.name|FOAF.givenName
Path(http://xmlns.com/foaf/0.1/name | http://xmlns.com/foaf/0.1/givenName)
```

Modifiers (?, \*, +) are done using \* (the multiplication operator) and the strings '?', '+', also defined as constants in this file.

```
>>> FOAF.knows*OneOrMore
Path(http://xmlns.com/foaf/0.1/knows+)
```

The path objects can also be used with the normal graph methods.

First some example data:

```
>>> g=Graph()
```

```
>>> g=g.parse(data='''
... @prefix : <ex:> .
...
... :a :p1 :c ; :p2 :f .
... :c :p2 :e ; :p3 :g .
... :g :p3 :h ; :p2 :j .
... :h :p3 :a ; :p2 :g .
...
... :q :px :q .
...
... ''', format='n3')
```

```
>>> e = Namespace('ex:')
```

Graph contains:

```
>>> (e.a, e.p1/e.p2, e.e) in g
True
```

Graph generator functions, triples, subjects, objects, etc. :

```
>>> list(g.objects(e.c, (e.p3*OneOrMore)/e.p2))
[rdflib.term.URIRef('ex:j'), rdflib.term.URIRef('ex:g'),
 rdflib.term.URIRef('ex:f')]
```

A more complete set of tests:

```
>>> list(eval_path(g, (None, e.p1/e.p2, None)))==[(e.a, e.e)]
True
>>> list(eval_path(g, (e.a, e.p1|e.p2, None)))==[(e.a,e.c), (e.a,e.f)]
True
>>> list(eval_path(g, (e.c, ~e.p1, None))) == [ (e.c, e.a) ]
True
>>> list(eval_path(g, (e.a, e.p1*ZeroOrOne, None))) == [(e.a, e.a), (e.a, e.c)]
True
>>> list(eval_path(g, (e.c, e.p3*OneOrMore, None))) == [
...     (e.c, e.g), (e.c, e.h), (e.c, e.a)]
True
>>> list(eval_path(g, (e.c, e.p3*ZeroOrMore, None))) == [(e.c, e.c),
...     (e.c, e.g), (e.c, e.h), (e.c, e.a)]
True
>>> list(eval_path(g, (e.a, -e.p1, None))) == [(e.a, e.f)]
True
>>> list(eval_path(g, (e.a, -(e.p1|e.p2), None))) == []
True
>>> list(eval_path(g, (e.g, ~~e.p2, None))) == [(e.g, e.j)]
True
>>> list(eval_path(g, (e.e, ~(e.p1/e.p2), None))) == [(e.e, e.a)]
True
>>> list(eval_path(g, (e.a, e.p1/e.p3/e.p3, None))) == [(e.a, e.h)]
True
```

```
>>> list(eval_path(g, (e.q, e.px*OneOrMore, None)))
[(rdflib.term.URIRef('ex:q'), rdflib.term.URIRef('ex:q'))]
```

```
>>> list(eval_path(g, (None, e.p1|e.p2, e.c)))
[(rdflib.term.URIRef('ex:a'), rdflib.term.URIRef('ex:c'))]
```

```
>>> list(eval_path(g, (None, ~e.p1, e.a))) == [ (e.c, e.a) ]
True
>>> list(eval_path(g, (None, e.p1*ZeroOrOne, e.c)))
[(rdflib.term.URIRef('ex:c'), rdflib.term.URIRef('ex:c')),
 (rdflib.term.URIRef('ex:a'), rdflib.term.URIRef('ex:c'))]
```

```
>>> list(eval_path(g, (None, e.p3*OneOrMore, e.a)))
[(rdflib.term.URIRef('ex:h'), rdflib.term.URIRef('ex:a')),
 (rdflib.term.URIRef('ex:g'), rdflib.term.URIRef('ex:a')),
 (rdflib.term.URIRef('ex:c'), rdflib.term.URIRef('ex:a'))]
```

```
>>> list(eval_path(g, (None, e.p3*ZeroOrMore, e.a)))
[(rdflib.term.URIRef('ex:a'), rdflib.term.URIRef('ex:a')),
 (rdflib.term.URIRef('ex:h'), rdflib.term.URIRef('ex:a')),
 (rdflib.term.URIRef('ex:g'), rdflib.term.URIRef('ex:a')),
 (rdflib.term.URIRef('ex:c'), rdflib.term.URIRef('ex:a'))]
```

```
>>> list(eval_path(g, (None, -e.p1, e.f))) == [(e.a, e.f)]
True
```

(continues on next page)

(continued from previous page)

```
>>> list(eval_path(g, (None, ~(e.p1|e.p2), e.c))) == []
True
>>> list(eval_path(g, (None, ~~e.p2, e.j))) == [(e.g, e.j)]
True
>>> list(eval_path(g, (None, ~(e.p1/e.p2), e.a))) == [(e.e, e.a)]
True
>>> list(eval_path(g, (None, e.p1/e.p3/e.p3, e.h))) == [(e.a, e.h)]
True
```

```
>>> list(eval_path(g, (e.q, e.px*OneOrMore, None)))
[(rdflib.term.URIRef('ex:q'), rdflib.term.URIRef('ex:q'))]
```

```
>>> list(eval_path(g, (e.c, (e.p2|e.p3)*ZeroOrMore, e.j)))
[(rdflib.term.URIRef('ex:c'), rdflib.term.URIRef('ex:j'))]
```

No vars specified:

```
>>> sorted(list(eval_path(g, (None, e.p3*OneOrMore, None))))
[(rdflib.term.URIRef('ex:c'), rdflib.term.URIRef('ex:a')),
 (rdflib.term.URIRef('ex:c'), rdflib.term.URIRef('ex:g')),
 (rdflib.term.URIRef('ex:c'), rdflib.term.URIRef('ex:h')),
 (rdflib.term.URIRef('ex:g'), rdflib.term.URIRef('ex:a')),
 (rdflib.term.URIRef('ex:g'), rdflib.term.URIRef('ex:h')),
 (rdflib.term.URIRef('ex:h'), rdflib.term.URIRef('ex:a'))]
```

```
class rdflib.paths.AlternativePath(*args)
```

Bases: *Path*

#### Parameters

**args** (*Union*[*Path*, *URIRef*]) –

**\_\_init\_\_** (\*args)

#### Parameters

**args** (*Union*[*Path*, *URIRef*]) –

**\_\_module\_\_** = 'rdflib.paths'

**\_\_repr\_\_** ()

Return repr(self).

#### Return type

*str*

**eval** (graph, subj=None, obj=None)

#### Parameters

- **graph** (*Graph*) –
- **subj** (*Optional*[*Node*]) –
- **obj** (*Optional*[*Node*]) –

#### Return type

*Generator*[*Tuple*[*Node*, *Node*], None, None]

```

n3(namespace_manager=None)

    Parameters
        namespace_manager (Optional[NamespaceManager]) –

    Return type
        str

class rdflib.paths.InvPath(arg)
    Bases: Path

    Parameters
        arg (Union[Path, URIRef]) –

    __init__(arg)

    Parameters
        arg (Union[Path, URIRef]) –

    __module__ = 'rdflib.paths'

    __repr__()
        Return repr(self).

    Return type
        str

eval(graph, subj=None, obj=None)

    Parameters
        • graph (Graph) –
        • subj (Optional[Node]) –
        • obj (Optional[Node]) –

    Return type
        Generator[Tuple[Node, Node], None, None]

n3(namespace_manager=None)

    Parameters
        namespace_manager (Optional[NamespaceManager]) –

    Return type
        str

class rdflib.paths.MulPath(path, mod)
    Bases: Path

    Parameters
        • path (Union[Path, URIRef]) –
        • mod (Literal['*', '+', '?']) –

    __init__(path, mod)

    Parameters
        • path (Union[Path, URIRef]) –
        • mod (Literal['*', '+', '?']) –

```

```
__module__ = 'rdflib.paths'
```

```
__repr__()
```

Return repr(self).

**Return type**

`str`

```
eval(graph, subj=None, obj=None, first=True)
```

**Parameters**

- **graph** (*Graph*) –
- **subj** (*Optional[Node]*) –
- **obj** (*Optional[Node]*) –
- **first** (*bool*) –

**Return type**

`Generator[Tuple[Node, Node], None, None]`

```
n3(namespace_manager=None)
```

**Parameters**

**namespace\_manager** (*Optional[NamespaceManager]*) –

**Return type**

`str`

```
class rdflib.paths.NegatedPath(arg)
```

Bases: *Path*

**Parameters**

**arg** (*Union[AlternativePath, InvPath, URIRef]*) –

```
__init__(arg)
```

**Parameters**

**arg** (*Union[AlternativePath, InvPath, URIRef]*) –

```
__module__ = 'rdflib.paths'
```

```
__repr__()
```

Return repr(self).

**Return type**

`str`

```
eval(graph, subj=None, obj=None)
```

```
n3(namespace_manager=None)
```

**Parameters**

**namespace\_manager** (*Optional[NamespaceManager]*) –

**Return type**

`str`

```
class rdflib.paths.Path
```

Bases: *object*



```

__annotations__ = {'__invert__': "Callable[['Path'], 'InvPath']", '__mul__':
"Callable[['Path', str], 'MulPath']", '__neg__': "Callable[['Path'],
'NegatedPath']", '__or__': "Callable[['Path', Union['URIRef', 'Path']],
'AlternativePath']", '__truediv__': "Callable[['Path', Union['URIRef', 'Path']],
'SequencePath']"}

__dict__ = mappingproxy({'__module__': 'rdflib.paths', '__annotations__':
{'__or__': "Callable[['Path', Union['URIRef', 'Path']], 'AlternativePath']",
'__invert__': "Callable[['Path'], 'InvPath']", '__neg__': "Callable[['Path'],
'NegatedPath']", '__truediv__': "Callable[['Path', Union['URIRef', 'Path']],
'SequencePath']", '__mul__': "Callable[['Path', str], 'MulPath']"}, 'eval':
<function Path.eval>, '__hash__': <function Path.__hash__>, '__eq__': <function
Path.__eq__>, '__lt__': <function Path.__lt__>, '__dict__': <attribute '__dict__'
of 'Path' objects>, '__weakref__': <attribute '__weakref__' of 'Path' objects>,
'__doc__': None, '__gt__': <function _gt_from_lt>, '__le__': <function
_le_from_lt>, '__ge__': <function _ge_from_lt>, '__invert__': <function inv_path>,
'__neg__': <function neg_path>, '__mul__': <function mul_path>, '__or__':
<function path_alternative>, '__truediv__': <function path_sequence>})

__eq__(other)
    Return self==value.

__ge__(other, NotImplemented=NotImplemented)
    Return a >= b. Computed by @total_ordering from (not a < b).

__gt__(other, NotImplemented=NotImplemented)
    Return a > b. Computed by @total_ordering from (not a < b) and (a != b).

__hash__()
    Return hash(self).

__invert__()
    inverse path

    Parameters
        p (Union[URIRef, Path]) –

    Return type
        InvPath

__le__(other, NotImplemented=NotImplemented)
    Return a <= b. Computed by @total_ordering from (a < b) or (a == b).

__lt__(other)
    Return self<value.

    Parameters
        other (Any) –

    Return type
        bool

__module__ = 'rdflib.paths'

__mul__(mul)
    cardinality path

    Parameters

```

- **p** (`Union[URIRef, Path]`) –
- **mul** (`Literal['*', '+', '?']`) –

**Return type**  
`MulPath`

**\_\_neg\_\_()**

negated path

**Parameters**

- p** (`Union[URIRef, AlternativePath, InvPath]`) –

**Return type**  
`NegatedPath`

**\_\_or\_\_(other)**

alternative path

**Parameters**

- **self** (`Union[URIRef, Path]`) –
- **other** (`Union[URIRef, Path]`) –

**\_\_truediv\_\_(other)**

sequence path

**Parameters**

- **self** (`Union[URIRef, Path]`) –
- **other** (`Union[URIRef, Path]`) –

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**eval**(*graph*, *subj*=None, *obj*=None)

**Parameters**

- **graph** (`Graph`) –
- **subj** (`Optional[Node]`) –
- **obj** (`Optional[Node]`) –

**Return type**  
`Iterator[Tuple[Node, Node]]`

**class** `rdflib.paths.PathList`(*iterable*=(), /)

Bases: `list`

**\_\_dict\_\_** = `mappingproxy({'__module__': 'rdflib.paths', '__dict__': <attribute '__dict__' of 'PathList' objects>, '__weakref__': <attribute '__weakref__' of 'PathList' objects>, '__doc__': None, '__annotations__': {}})`

**\_\_module\_\_** = 'rdflib.paths'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

```
class rdflib.paths.SequencePath(*args)
```

Bases: *Path*

**Parameters**

**args** (Union[*Path*, *URIRef*]) –

```
__init__(*args)
```

**Parameters**

**args** (Union[*Path*, *URIRef*]) –

```
__module__ = 'rdflib.paths'
```

```
__repr__()
```

Return repr(self).

**Return type**

*str*

```
eval(graph, subj=None, obj=None)
```

**Parameters**

- **graph** (*Graph*) –
- **subj** (Optional[*Node*]) –
- **obj** (Optional[*Node*]) –

**Return type**

Generator[Tuple[*Node*, *Node*], None, None]

```
n3(namespace_manager=None)
```

**Parameters**

**namespace\_manager** (Optional[*NamespaceManager*]) –

**Return type**

*str*

```
rdflib.paths.evalPath(graph, t)
```

**Parameters**

- **graph** (*Graph*) –
- **t** (Tuple[Optional[*Node*], Union[None, *Path*, *Node*], Optional[*Node*]]) –

**Return type**

Iterator[Tuple[*Node*, *Node*]]

```
rdflib.paths.eval_path(graph, t)
```

**Parameters**

- **graph** (*Graph*) –
- **t** (Tuple[Optional[*Node*], Union[None, *Path*, *Node*], Optional[*Node*]]) –

**Return type**

Iterator[Tuple[*Node*, *Node*]]

`rdflib.paths.inv_path(p)`

inverse path

**Parameters**

`p` (`Union[URIRef, Path]`) –

**Return type**

`InvPath`

`rdflib.paths.mul_path(p, mul)`

cardinality path

**Parameters**

- `p` (`Union[URIRef, Path]`) –
- `mul` (`Literal['*', '+', '?']`) –

**Return type**

`MulPath`

`rdflib.paths.neg_path(p)`

negated path

**Parameters**

`p` (`Union[URIRef, AlternativePath, InvPath]`) –

**Return type**

`NegatedPath`

`rdflib.paths.path_alternative(self, other)`

alternative path

**Parameters**

- `self` (`Union[URIRef, Path]`) –
- `other` (`Union[URIRef, Path]`) –

`rdflib.paths.path_sequence(self, other)`

sequence path

**Parameters**

- `self` (`Union[URIRef, Path]`) –
- `other` (`Union[URIRef, Path]`) –

## rdflib.plugin module

Plugin support for rdf.

There are a number of plugin points for rdf: parser, serializer, store, query processor, and query result. Plugins can be registered either through setuptools entry\_points or by calling `rdf.plugin.register` directly.

If you have a package that uses a setuptools based setup.py you can add the following to your setup:

```
entry_points = {
    'rdf.plugins.parser': [
        'nt = rdf.plugins.parsers.ntriples:NTParser',
    ],
}
```

(continues on next page)

(continued from previous page)

```
'rdf.plugins.serializer': [
    'nt =      rdf.plugins.serializers.NTSerializer:NTSerializer',
],
}
```

See the [setuptools](#) dynamic discovery of services and plugins for more information.

```
class rdflib.plugin.PKGPlugin(name, kind, ep)
```

Bases: [Plugin](#)[[PluginT](#)]

#### Parameters

- **name** ([str](#)) –
- **kind** ([Type](#)[[TypeVar](#)([PluginT](#))]) –
- **ep** ([EntryPoint](#)) –

```
__init__(name, kind, ep)
```

#### Parameters

- **name** ([str](#)) –
- **kind** ([Type](#)[[TypeVar](#)([PluginT](#))]) –
- **ep** ([EntryPoint](#)) –

```
__module__ = 'rdflib.plugin'
```

```
__orig_bases__ = (rdflib.plugin.Plugin[~PluginT],)
```

```
__parameters__ = (~PluginT,)
```

```
getClass()
```

#### Return type

[Type](#)[[TypeVar](#)([PluginT](#))]

```
class rdflib.plugin.Plugin(name, kind, module_path, class_name)
```

Bases: [Generic](#)[[PluginT](#)]

#### Parameters

- **name** ([str](#)) –
- **kind** ([Type](#)[[TypeVar](#)([PluginT](#))]) –
- **module\_path** ([str](#)) –
- **class\_name** ([str](#)) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.plugin', '__init__': <function
Plugin.__init__>, 'getClass': <function Plugin.getClass>, '__orig_bases__':
(typing.Generic[~PluginT],), '__dict__': <attribute '__dict__' of 'Plugin'
objects>, '__weakref__': <attribute '__weakref__' of 'Plugin' objects>, '__doc__':
None, '__parameters__': (~PluginT,), '__annotations__': {'_class':
'Optional[Type[PluginT]]'}})
```

```
__init__(name, kind, module_path, class_name)
```

**Parameters**

- **name** (`str`) –
- **kind** (`Type[TypeVar(PluginT)]`) –
- **module\_path** (`str`) –
- **class\_name** (`str`) –

```
__module__ = 'rdflib.plugin'
```

```
__orig_bases__ = (typing.Generic[~PluginT],)
```

```
__parameters__ = (~PluginT,)
```

```
__weakref__
```

list of weak references to the object (if defined)

```
getClass()
```

**Return type**

`Type[TypeVar(PluginT)]`

```
exception rdflib.plugin.PluginException(msg=None)
```

Bases: `Error`

**Parameters**

**msg** (`Optional[str]`) –

```
__module__ = 'rdflib.plugin'
```

```
class rdflib.plugin.PluginT
```

A generic type variable for plugins

alias of `TypeVar('PluginT')`

```
__module__ = 'rdflib.plugin'
```

```
rdflib.plugin.get(name, kind)
```

Return the class for the specified (name, kind). Raises a `PluginException` if unable to do so.

**Parameters**

- **name** (`str`) –
- **kind** (`Type[TypeVar(PluginT)]`) –

**Return type**

`Type[TypeVar(PluginT)]`

```
rdflib.plugin.plugins(name=None, kind=None)
```

A generator of the plugins.

Pass in name and kind to filter... else leave `None` to match all.

**Parameters**

- **name** (`Optional[str]`) –
- **kind** (`Optional[Type[TypeVar(PluginT)]]`) –

**Return type**`Iterator[Plugin[TypeVar(PluginT)]]``rdflib.plugin.register(name, kind, module_path, class_name)`

Register the plugin for (name, kind). The module\_path and class\_name should be the path to a plugin class.

**Parameters**

- **name** (`str`) –
- **kind** (`Type[Any]`) –

**rdflib.query module**`class rdflib.query.EncodeOnlyUnicode(stream)`

Bases: `object`

This is a crappy work-around for <http://bugs.python.org/issue11649>

**Parameters**`stream` (`BinaryIO`) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.query', '__doc__': '\n This is a
crappy work-around for\n http://bugs.python.org/issue11649\n\n\n ', '__init__':
<function EncodeOnlyUnicode.__init__>, 'write': <function EncodeOnlyUnicode.write>,
'__getattr__': <function EncodeOnlyUnicode.__getattr__>, '__dict__': <attribute
'__dict__' of 'EncodeOnlyUnicode' objects>, '__weakref__': <attribute '__weakref__'
of 'EncodeOnlyUnicode' objects>, '__annotations__': {}})
```

`__getattr__(name)`**Parameters**`name` (`str`) –**Return type**`Any``__init__(stream)`**Parameters**`stream` (`BinaryIO`) –`__module__ = 'rdflib.query'``__weakref__`

list of weak references to the object (if defined)

`write(arg)``class rdflib.query.Processor(graph)`

Bases: `object`

Query plugin interface.

This module is useful for those wanting to write a query processor that can plugin to rdf. If you are wanting to execute a query you likely want to do so through the Graph class query method.

**Parameters**`graph` (`Graph`) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.query', '__doc__': '\n Query plugin
interface.\n\n This module is useful for those wanting to write a query processor\n
that can plugin to rdf. If you are wanting to execute a query you\n likely want to
do so through the Graph class query method.\n\n ', '__init__': <function
Processor.__init__>, 'query': <function Processor.query>, '__dict__': <attribute
'__dict__' of 'Processor' objects>, '__weakref__': <attribute '__weakref__' of
'Processor' objects>, '__annotations__': {}})
```

```
__init__(graph)
```

**Parameters**

**graph** (*Graph*) –

```
__module__ = 'rdflib.query'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
query(strOrQuery, initBindings={}, initNs={}, DEBUG=False)
```

**Parameters**

- **strOrQuery** (*Union[str, Query]*) –
- **initBindings** (*Mapping[str, Identifier]*) –
- **initNs** (*Mapping[str, Any]*) –
- **DEBUG** (*bool*) –

**Return type**

*Mapping[str, Any]*

```
class rdflib.query.Result(type_)
```

Bases: *object*

A common class for representing query result.

There is a bit of magic here that makes this appear like different Python objects, depending on the type of result.

If the type is “SELECT”, iterating will yield lists of *ResultRow* objects

If the type is “ASK”, iterating will yield a single bool (or bool(result) will return the same bool)

If the type is “CONSTRUCT” or “DESCRIBE” iterating will yield the triples.

len(result) also works.

**Parameters**

**type\_** (*str*) –

```
__bool__()
```

**Return type**

*bool*



```
__dict__ = mappingproxy({'__module__': 'rdflib.query', '__doc__': '\n A common
class for representing query result.\n\n There is a bit of magic here that makes
this appear like different\n Python objects, depending on the type of result.\n\n If
the type is "SELECT", iterating will yield lists of ResultRow objects\n\n If the
type is "ASK", iterating will yield a single bool (or\n bool(result) will return the
same bool)\n\n If the type is "CONSTRUCT" or "DESCRIBE" iterating will yield the\n
triples.\n\n len(result) also works.\n\n ', '__init__': <function Result.__init__>,
'bindings': <property object>, 'parse': <staticmethod object>, 'serialize':
<function Result.serialize>, '__len__': <function Result.__len__>, '__bool__':
<function Result.__bool__>, '__iter__': <function Result.__iter__>, '__getattr__':
<function Result.__getattr__>, '__eq__': <function Result.__eq__>, '__dict__':
<attribute '__dict__' of 'Result' objects>, '__weakref__': <attribute '__weakref__'
of 'Result' objects>, '__hash__': None, '__annotations__': {'vars':
"Optional[List['Variable']]", '_bindings': "MutableSequence[Mapping['Variable',
'Identifier']]", '_genbindings': "Optional[Iterator[Mapping['Variable',
'Identifier']]", 'askAnswer': 'Optional[bool]', 'graph': "Optional['Graph']"}}})
```

**\_\_eq\_\_**(*other*)

Return self==value.

**Parameters**

**other** (*Any*) –

**Return type**

*bool*

**\_\_getattr\_\_**(*name*)

**Parameters**

**name** (*str*) –

**Return type**

*Any*

**\_\_hash\_\_** = None

**\_\_init\_\_**(*type\_*)

**Parameters**

**type\_** (*str*) –

**\_\_iter\_\_**()

**Return type**

*Iterator[Union[Tuple[Node, Node, Node], bool, ResultRow]]*

**\_\_len\_\_**()

**Return type**

*int*

**\_\_module\_\_** = 'rdflib.query'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**property bindings:** *MutableSequence[Mapping[Variable, Identifier]]*

a list of variable bindings as dicts

```
static parse(source=None, format=None, content_type=None, **kwargs)
```

**Parameters**

- **source** (Optional[IO]) –
- **format** (Optional[str]) –
- **content\_type** (Optional[str]) –
- **kwargs** (Any) –

**Return type**

*Result*

```
serialize(destination=None, encoding='utf-8', format='xml', **args)
```

Serialize the query result.

The `format` argument determines the Serializer class to use.

- `csv`: *CSVResultSerializer*
- `json`: *JSONResultSerializer*
- `txt`: *TXTResultSerializer*
- `xml`: *XMLResultSerializer*

**Parameters**

- **destination** (Union[str, IO, None]) – Path of file output or BufferedIOBase object to write the output to.
- **encoding** (str) – Encoding of output.
- **format** (str) – One of ['csv', 'json', 'txt', 'xml']
- **args** (Any) –

**Return type**

Optional[bytes]

**Returns**

bytes

```
vars: Optional[List[Variable]]
```

variables contained in the result.

```
exception rdflib.query.ResultException
```

Bases: *Exception*

```
__module__ = 'rdflib.query'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
class rdflib.query.ResultParser
```

Bases: *object*

```
__dict__ = mappingproxy({'__module__': 'rdflib.query', '__init__': <function  
ResultParser.__init__>, 'parse': <function ResultParser.parse>, '__dict__':  
<attribute '__dict__' of 'ResultParser' objects>, '__weakref__': <attribute  
'__weakref__' of 'ResultParser' objects>, '__doc__': None, '__annotations__': {}})
```

```
__init__()
```

```
__module__ = 'rdflib.query'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
parse(source, **kwargs)
```

return a Result object

#### Parameters

- **source** (*IO*) –
- **kwargs** (*Any*) –

#### Return type

*Result*

```
class rdflib.query.ResultRow(values: Mapping[Variable, Identifier], labels: List[Variable])
```

Bases: Tuple[Identifier, ...]

a single result row allows accessing bindings as attributes or with []

```
>>> from rdflib import URIRef, Variable
>>> rr=ResultRow({ Variable('a'): URIRef('urn:cake') }, [Variable('a')])
```

```
>>> rr[0]
rdflib.term.URIRef(u'urn:cake')
>>> rr[1]
Traceback (most recent call last):
...
IndexError: tuple index out of range
```

```
>>> rr.a
rdflib.term.URIRef(u'urn:cake')
>>> rr.b
Traceback (most recent call last):
...
AttributeError: b
```

```
>>> rr['a']
rdflib.term.URIRef(u'urn:cake')
>>> rr['b']
Traceback (most recent call last):
...
KeyError: 'b'
```

```
>>> rr[Variable('a')]
rdflib.term.URIRef(u'urn:cake')
```

New in version 4.0.

```
__annotations__ = {'labels': 'Mapping[str, int]'}
```

```
__dict__ = mappingproxy({'__module__': 'rdflib.query', '__annotations__':
{'labels': 'Mapping[str, int]'}, '__doc__': "\n a single result row\n allows
accessing bindings as attributes or with []\n\n >>> from rdflib import URIRef,
Variable\n >>> rr=ResultRow({ Variable('a'):  URIRef('urn:cake') },
[Variable('a')])\n\n >>> rr[0]\n rdflib.term.URIRef(u'urn:cake')\n\n >>> rr[1]\n
Traceback (most recent call last):\n ...\n IndexError:  tuple index out of range\n\n
>>> rr.a\n rdflib.term.URIRef(u'urn:cake')\n\n >>> rr.b\n Traceback (most recent call
last):\n ...\n AttributeError:  b\n\n >>> rr['a']\n
rdflib.term.URIRef(u'urn:cake')\n\n >>> rr['b']\n Traceback (most recent call last):\n
...\n KeyError:  'b'\n\n >>> rr[Variable('a')]\n rdflib.term.URIRef(u'urn:cake')\n\n
.. versionadded:: 4.0\n\n ", '__new__': <staticmethod object>, '__getattr__':
<function ResultRow.__getattr__>, '__getitem__': <function ResultRow.__getitem__>,
'get': <function ResultRow.get>, 'asdict': <function ResultRow.asdict>,
'__orig_bases__': (typing.Tuple[ForwardRef('Identifier'), ...],), '__dict__':
<attribute '__dict__' of 'ResultRow' objects>, '__parameters__': {})
```

`__getattr__(name)`

**Parameters**

**name** (`str`) –

**Return type**

`Identifier`

`__getitem__(name)`

Return self[key].

**Parameters**

**name** (`Union[str, int, Any]`) –

**Return type**

`Identifier`

`__module__ = 'rdflib.query'`

`static __new__(cls, values, labels)`

**Parameters**

• **values** (`Mapping[Variable, Identifier]`) –

• **labels** (`List[Variable]`) –

`__orig_bases__ = (typing.Tuple[ForwardRef('Identifier'), ...],)`

`__parameters__ = ()`

`asdict()`

**Return type**

`Dict[str, Identifier]`

`get(name, default=None)`

**Parameters**

• **name** (`str`) –

• **default** (`Optional[Identifier]`) –

**Return type**

`Optional[Identifier]`

labels: Mapping[str, int]

class rdflib.query.ResultSerializer(*result*)

Bases: object

Parameters

result (*Result*) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.query', '__init__': <function
ResultSerializer.__init__>, 'serialize': <function ResultSerializer.serialize>,
'__dict__': <attribute '__dict__' of 'ResultSerializer' objects>, '__weakref__':
<attribute '__weakref__' of 'ResultSerializer' objects>, '__doc__': None,
'__annotations__': {}})
```

\_\_init\_\_(*result*)

Parameters

result (*Result*) –

\_\_module\_\_ = 'rdflib.query'

\_\_weakref\_\_

list of weak references to the object (if defined)

serialize(*stream*, *encoding*='utf-8', *\*\*kwargs*)

return a string properly serialized

Parameters

- stream (*IO*) –
- encoding (*str*) –
- kwargs (*Any*) –

Return type

None

class rdflib.query.UpdateProcessor(*graph*)

Bases: object

Update plugin interface.

This module is useful for those wanting to write an update processor that can plugin to rdflib. If you are wanting to execute an update statement you likely want to do so through the Graph class update method.

New in version 4.0.

Parameters

graph (*Graph*) –

```
__dict__ = mappingproxy({'__module__': 'rdflib.query', '__doc__': '\n Update
plugin interface.\n\n This module is useful for those wanting to write an update\n
processor that can plugin to rdflib. If you are wanting to execute\n an update
statement you likely want to do so through the Graph\n class update method.\n\n ..
versionadded:: 4.0\n\n ', '__init__': <function UpdateProcessor.__init__>,
'update': <function UpdateProcessor.update>, '__dict__': <attribute '__dict__' of
'UpdateProcessor' objects>, '__weakref__': <attribute '__weakref__' of
'UpdateProcessor' objects>, '__annotations__': {}})
```

```
__init__(graph)
```

**Parameters**

**graph** (*Graph*) –

```
__module__ = 'rdflib.query'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
update(strOrQuery, initBindings={}, initNs={})
```

**Parameters**

- **strOrQuery** (*Union[str, Update]*) –

- **initBindings** (*Mapping[str, Identifier]*) –

- **initNs** (*Mapping[str, Any]*) –

**Return type**

*None*

## rdflib.resource module

The *Resource* class wraps a *Graph* and a resource reference (i.e. a *rdflib.term.URIRef* or *rdflib.term.BNode*) to support a resource-oriented way of working with a graph.

It contains methods directly corresponding to those methods of the Graph interface that relate to reading and writing data. The difference is that a Resource also binds a resource identifier, making it possible to work without tracking both the graph and a current subject. This makes for a “resource oriented” style, as compared to the triple orientation of the Graph API.

Resulting generators are also wrapped so that any resource reference values (*rdflib.term.URIRef* and *rdflib.term.BNode*) are in turn wrapped as Resources. (Note that this behaviour differs from the corresponding methods in *Graph*, where no such conversion takes place.)

## Basic Usage Scenario

Start by importing things we need and define some namespaces:

```
>>> from rdflib import *
>>> FOAF = Namespace("http://xmlns.com/foaf/0.1/")
>>> CV = Namespace("http://purl.org/captsolo/resume-rdf/0.2/cv#")
```

Load some RDF data:

```
>>> graph = Graph().parse(format='n3', data='''
... @prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
... @prefix xsd: <http://www.w3.org/2001/XMLSchema#>.
... @prefix foaf: <http://xmlns.com/foaf/0.1/> .
... @prefix cv: <http://purl.org/captsolo/resume-rdf/0.2/cv#> .
...
... @base <http://example.org/> .
...
... </person/some1#self> a foaf:Person;
```

(continues on next page)

(continued from previous page)

```

...     rdfs:comment "Just a Python & RDF hacker."@en;
...     foaf:depiction </images/person/some1.jpg>;
...     foaf:homepage <http://example.net/>;
...     foaf:name "Some Body" .
...
... </images/person/some1.jpg> a foaf:Image;
...     rdfs:label "some 1"@en;
...     rdfs:comment "Just an image"@en;
...     foaf:thumbnail </images/person/some1-thumb.jpg> .
...
... </images/person/some1-thumb.jpg> a foaf:Image .
...
... [] a cv:CV;
...     cv:aboutPerson </person/some1#self>;
...     cv:hasWorkHistory [ cv:employedIn </#company>;
...                         cv:startDate "2009-09-04"^^xsd:date ] .
... '''

```

Create a Resource:

```

>>> person = Resource(
...     graph, URIRef("http://example.org/person/some1#self"))

```

Retrieve some basic facts:

```

>>> person.identifier
rdflib.term.URIRef(u'http://example.org/person/some1#self')

>>> person.value(FOAF.name)
rdflib.term.Literal(u'Some Body')

>>> person.value(RDFS.comment)
rdflib.term.Literal(u'Just a Python & RDF hacker.', lang=u'en')

```

Resources can be sliced (like graphs, but the subject is fixed):

```

>>> for name in person[FOAF.name]:
...     print(name)
Some Body
>>> person[FOAF.name : Literal("Some Body")]
True

```

Resources as unicode are represented by their identifiers as unicode:

```

>>> %(unicode)s(person)
u'Resource(http://example.org/person/some1#self')

```

Resource references are also Resources, so you can easily get e.g. a qname for the type of a resource, like:

```

>>> person.value(RDF.type).qname()
u'foaf:Person'

```

Or for the predicates of a resource:

```
>>> sorted(
...     p.qname() for p in person.predicates()
... )
[u'foaf:depiction', u'foaf:homepage',
 u'foaf:name', u'rdf:type', u'rdfs:comment']
```

Follow relations and get more data from their Resources as well:

```
>>> for pic in person.objects(FOAF.depiction):
...     print(pic.identifier)
...     print(pic.value(RDF.type).qname())
...     print(pic.value(FOAF.thumbnail).identifier)
http://example.org/images/person/some1.jpg
foaf:Image
http://example.org/images/person/some1-thumb.jpg

>>> for cv in person.subjects(CV.aboutPerson):
...     work = list(cv.objects(CV.hasWorkHistory))[0]
...     print(work.value(CV.employedIn).identifier)
...     print(work.value(CV.startDate))
http://example.org/#company
2009-09-04
```

It's just as easy to work with the predicates of a resource:

```
>>> for s, p in person.subject_predicates():
...     print(s.value(RDF.type).qname())
...     print(p.qname())
...     for s, o in p.subject_objects():
...         print(s.value(RDF.type).qname())
...         print(o.value(RDF.type).qname())
cv:CV
cv:aboutPerson
cv:CV
foaf:Person
```

This is useful for e.g. inspection:

```
>>> thumb_ref = URIRef("http://example.org/images/person/some1-thumb.jpg")
>>> thumb = Resource(graph, thumb_ref)
>>> for p, o in thumb.predicate_objects():
...     print(p.qname())
...     print(o.qname())
rdf:type
foaf:Image
```



## Schema Example

With this artificial schema data:

```
>>> graph = Graph().parse(format='n3', data='''
... @prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
... @prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
... @prefix owl: <http://www.w3.org/2002/07/owl#> .
... @prefix v: <http://example.org/def/v#> .
...
... v:Artifact a owl:Class .
...
... v:Document a owl:Class;
...     rdfs:subClassOf v:Artifact .
...
... v:Paper a owl:Class;
...     rdfs:subClassOf v:Document .
...
... v:Choice owl:oneOf (v:One v:Other) .
...
... v:Stuff a rdf:Seq; rdf:_1 v:One; rdf:_2 v:Other .
...
... ''')
```

From this class:

```
>>> artifact = Resource(graph, URIRef("http://example.org/def/v#Artifact"))
```

we can get at subclasses:

```
>>> subclasses = list(artifact.transitive_subjects(RDFS.subClassOf))
>>> [c.qname() for c in subclasses]
[u'v:Artifact', u'v:Document', u'v:Paper']
```

and superclasses from the last subclass:

```
>>> [c.qname() for c in subclasses[-1].transitive_objects(RDFS.subClassOf)]
[u'v:Paper', u'v:Document', u'v:Artifact']
```

Get items from the Choice:

```
>>> choice = Resource(graph, URIRef("http://example.org/def/v#Choice"))
>>> [it.qname() for it in choice.value(OWL.oneOf).items()]
[u'v:One', u'v:Other']
```

On add, other resources are auto-unboxed:

```
>>> paper = Resource(graph, URIRef("http://example.org/def/v#Paper"))
>>> paper.add(RDFS.subClassOf, artifact)
>>> artifact in paper.objects(RDFS.subClassOf) # checks Resource instance
True
>>> (paper._identifier, RDFS.subClassOf, artifact._identifier) in graph
True
```

## Technical Details

Comparison is based on graph and identifier:

```
>>> g1 = Graph()
>>> t1 = Resource(g1, URIRef("http://example.org/thing"))
>>> t2 = Resource(g1, URIRef("http://example.org/thing"))
>>> t3 = Resource(g1, URIRef("http://example.org/other"))
>>> t4 = Resource(Graph(), URIRef("http://example.org/other"))

>>> t1 is t2
False

>>> t1 == t2
True
>>> t1 != t2
False

>>> t1 == t3
False
>>> t1 != t3
True

>>> t3 != t4
True

>>> t3 < t1 and t1 > t3
True
>>> t1 >= t1 and t1 >= t3
True
>>> t1 <= t1 and t3 <= t1
True

>>> t1 < t1 or t1 < t3 or t3 > t1 or t3 > t3
False
```

Hash is computed from graph and identifier:

```
>>> g1 = Graph()
>>> t1 = Resource(g1, URIRef("http://example.org/thing"))

>>> hash(t1) == hash(Resource(g1, URIRef("http://example.org/thing")))
True

>>> hash(t1) == hash(Resource(Graph(), t1.identifier))
False
>>> hash(t1) == hash(Resource(Graph(), URIRef("http://example.org/thing")))
False
```

The Resource class is suitable as a base class for mapper toolkits. For example, consider this utility for accessing RDF properties via qname-like attributes:

```
>>> class Item(Resource):
... 
```

(continues on next page)

(continued from previous page)

```

...     def __getattr__(self, p):
...         return list(self.objects(self._to_ref(*p.split('_', 1))))
...
...     def _to_ref(self, pfx, name):
...         return URIRef(self._graph.store.namespace(pfx) + name)

```

It works as follows:

```

>>> graph = Graph().parse(format='n3', data='''
... @prefix rdfs: <http://www.w3.org/2000/01/rdf-schema#> .
... @prefix foaf: <http://xmlns.com/foaf/0.1/> .
...
... @base <http://example.org/> .
... </person/some1#self>
...     foaf:name "Some Body";
...     foaf:depiction </images/person/some1.jpg> .
... </images/person/some1.jpg> rdfs:comment "Just an image"@en .
... ''')

>>> person = Item(graph, URIRef("http://example.org/person/some1#self"))

>>> print(person.foaf_name[0])
Some Body

```

The mechanism for wrapping references as resources cooperates with subclasses. Therefore, accessing referenced resources automatically creates new `Item` objects:

```

>>> isinstance(person.foaf_depiction[0], Item)
True

>>> print(person.foaf_depiction[0].rdfs_comment[0])
Just an image

```

```

class rdflib.resource.Resource(graph, subject)
    Bases: object

```

```
__dict__ = mappingproxy({'__module__': 'rdflib.resource', '__init__': <function
Resource.__init__>, 'graph': <property object>, 'identifier': <property object>,
'__hash__': <function Resource.__hash__>, '__eq__': <function Resource.__eq__>,
'__ne__': <function Resource.__ne__>, '__lt__': <function Resource.__lt__>,
'__gt__': <function Resource.__gt__>, '__le__': <function Resource.__le__>,
'__ge__': <function Resource.__ge__>, '__unicode__': <function
Resource.__unicode__>, 'add': <function Resource.add>, 'remove': <function
Resource.remove>, 'set': <function Resource.set>, 'subjects': <function
Resource.subjects>, 'predicates': <function Resource.predicates>, 'objects':
<function Resource.objects>, 'subject_predicates': <function
Resource.subject_predicates>, 'subject_objects': <function
Resource.subject_objects>, 'predicate_objects': <function
Resource.predicate_objects>, 'value': <function Resource.value>, 'items':
<function Resource.items>, 'transitive_objects': <function
Resource.transitive_objects>, 'transitive_subjects': <function
Resource.transitive_subjects>, 'qname': <function Resource.qname>,
'_resource_pairs': <function Resource._resource_pairs>, '_resource_triples':
<function Resource._resource_triples>, '_resources': <function
Resource._resources>, '_cast': <function Resource._cast>, '__iter__': <function
Resource.__iter__>, '__getitem__': <function Resource.__getitem__>, '__setitem__':
<function Resource.__setitem__>, '_new': <function Resource._new>, '__str__':
<function Resource.__str__>, '__repr__': <function Resource.__repr__>, '__dict__':
<attribute '__dict__' of 'Resource' objects>, '__weakref__': <attribute
'__weakref__' of 'Resource' objects>, '__doc__': None, '__annotations__': {}})
```

**\_\_eq\_\_**(*other*)

Return self==value.

**\_\_ge\_\_**(*other*)

Return self>=value.

**\_\_getitem\_\_**(*item*)

**\_\_gt\_\_**(*other*)

Return self>value.

**\_\_hash\_\_**()

Return hash(self).

**\_\_init\_\_**(*graph, subject*)

**\_\_iter\_\_**()

**\_\_le\_\_**(*other*)

Return self<=value.

**\_\_lt\_\_**(*other*)

Return self<value.

**\_\_module\_\_** = 'rdflib.resource'

**\_\_ne\_\_**(*other*)

Return self!=value.

**\_\_repr\_\_**()

Return repr(self).

```

__setitem__(item, value)

__str__()
    Return str(self).

__unicode__()

__weakref__
    list of weak references to the object (if defined)

add(p, o)

property graph

property identifier

items()

objects(predicate=None)

predicate_objects()

predicates(o=None)

qname()

remove(p, o=None)

set(p, o)

subject_objects()

subject_predicates()

subjects(predicate=None)

transitive_objects(predicate, remember=None)

transitive_subjects(predicate, remember=None)

value(p=rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#value'), o=None, default=None,
      any=True)

```

### rdflib.serializer module

```
class rdflib.serializer.Serializer(store)
```

Bases: `object`

#### Parameters

`store` (`Graph`) –

```

__dict__ = mappingproxy({'__module__': 'rdflib.serializer', '__init__': <function
Serializer.__init__>, 'serialize': <function Serializer.serialize>, 'relativize':
<function Serializer.relativize>, '__dict__': <attribute '__dict__' of 'Serializer'
objects>, '__weakref__': <attribute '__weakref__' of 'Serializer' objects>,
'__doc__': None, '__annotations__': {'store': "'Graph'", 'encoding': 'str',
'base': 'Optional[str]'}})

```

```
__init__(store)

    Parameters
        store (Graph) –

__module__ = 'rdflib.serializer'

__weakref__
    list of weak references to the object (if defined)

relativize(uri)

    Parameters
        uri (TypeVar(_StrT, bound= str)) –

    Return type
        Union[TypeVar(_StrT, bound= str), URIRef]

serialize(stream, base=None, encoding=None, **args)
    Abstract method

    Parameters
        • stream (IO[bytes]) –
        • base (Optional[str]) –
        • encoding (Optional[str]) –
        • args (Any) –

    Return type
        None
```

## rdflib.store module

```
class rdflib.store.NodePickler
```

```
    Bases: object
```

```
    __dict__ = mappingproxy({'__module__': 'rdflib.store', '__init__': <function
    NodePickler.__init__>, '_get_ids': <function NodePickler._get_ids>, 'register':
    <function NodePickler.register>, 'loads': <function NodePickler.loads>, 'dumps':
    <function NodePickler.dumps>, '__getstate__': <function NodePickler.__getstate__>,
    '__setstate__': <function NodePickler.__setstate__>, '__dict__': <attribute
    '__dict__' of 'NodePickler' objects>, '__weakref__': <attribute '__weakref__' of
    'NodePickler' objects>, '__doc__': None, '__annotations__': {'_objects':
    'Dict[str, Any]', '_ids': 'Dict[Any, str]'}})
```

```
    __getstate__()
```

```
        Return type
```

```
            Mapping[str, Any]
```

```
    __init__()
```

```
    __module__ = 'rdflib.store'
```

**\_\_setstate\_\_**(*state*)

**Parameters**

**state** (`Mapping[str, Any]`) –

**Return type**

`None`

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**dumps**(*obj*, *protocol=None*, *bin=None*)

**Parameters**

- **obj** (`Node`) –
- **protocol** (`Optional[Any]`) –
- **bin** (`Optional[Any]`) –

**loads**(*s*)

**Parameters**

**s** (`bytes`) –

**Return type**

`Node`

**register**(*object*, *id*)

**Parameters**

- **object** (`Any`) –
- **id** (`str`) –

**Return type**

`None`

**class** `rdflib.store.Store`(*configuration=None*, *identifier=None*)

Bases: `object`

**Parameters**

- **configuration** (`Optional[str]`) –
- **identifier** (`Optional[Identifier]`) –

**\_\_annotations\_\_** = {'context\_aware': 'bool', 'formula\_aware': 'bool',  
'graph\_aware': 'bool', 'transaction\_aware': 'bool'}

```
__dict__ = mappingproxy({'__module__': 'rdflib.store', '__annotations__':
{'context_aware': 'bool', 'formula_aware': 'bool', 'transaction_aware': 'bool',
'graph_aware': 'bool', '__node_pickler': 'Optional[NodePickler]'},
'context_aware': False, 'formula_aware': False, 'transaction_aware': False,
'graph_aware': False, '__init__': <function Store.__init__>, 'node_pickler':
<property object>, 'create': <function Store.create>, 'open': <function
Store.open>, 'close': <function Store.close>, 'destroy': <function Store.destroy>,
'gc': <function Store.gc>, 'add': <function Store.add>, 'addN': <function
Store.addN>, 'remove': <function Store.remove>, 'triples_choices': <function
Store.triples_choices>, 'triples': <function Store.triples>, '__len__': <function
Store.__len__>, 'contexts': <function Store.contexts>, 'query': <function
Store.query>, 'update': <function Store.update>, 'bind': <function Store.bind>,
'prefix': <function Store.prefix>, 'namespace': <function Store.namespace>,
'namespaces': <function Store.namespaces>, 'commit': <function Store.commit>,
'rollback': <function Store.rollback>, 'add_graph': <function Store.add_graph>,
'remove_graph': <function Store.remove_graph>, '__dict__': <attribute '__dict__'
of 'Store' objects>, '__weakref__': <attribute '__weakref__' of 'Store' objects>,
'__doc__': None})
```

**\_\_init\_\_**(*configuration=None, identifier=None*)

identifier: URIRef of the Store. Defaults to CWD configuration: string containing information open can use to connect to datastore.

#### Parameters

- **configuration** (*Optional[str]*) –
- **identifier** (*Optional[Identifier]*) –

**\_\_len\_\_**(*context=None*)

Number of statements in the store. This should only account for non- quoted (asserted) statements if the context is not specified, otherwise it should return the number of statements in the formula or context given.

#### Parameters

- **context** (*Optional[Graph]*) – a graph instance to query or None

#### Return type

*int*

**\_\_module\_\_** = 'rdflib.store'

**\_\_weakref\_\_**

list of weak references to the object (if defined)

**add**(*triple, context, quoted=False*)

Adds the given statement to a specific context or to the model. The quoted argument is interpreted by formula-aware stores to indicate this statement is quoted/hypothetical It should be an error to not specify a context and have the quoted argument be True. It should also be an error for the quoted argument to be True when the store is not formula-aware.

#### Parameters

- **triple** (*Tuple[Node, Node, Node]*) –
- **context** (*Graph*) –
- **quoted** (*bool*) –

#### Return type

*None*



### **addN(*quads*)**

Adds each item in the list of statements to a specific context. The quoted argument is interpreted by formula-aware stores to indicate this statement is quoted/hypothetical. Note that the default implementation is a redirect to add

#### **Parameters**

**quads** (*Iterable*[*Tuple*[*Node*, *Node*, *Node*, *Graph*]]) –

#### **Return type**

*None*

### **add\_graph(*graph*)**

Add a graph to the store, no effect if the graph already exists. :type graph: *Graph* :param graph: a Graph instance

#### **Return type**

*None*

### **bind(*prefix*, *namespace*, *override*=*True*)**

#### **Parameters**

- **override** (*bool*) – rebind, even if the given namespace is already bound to another prefix.
- **prefix** (*str*) –
- **namespace** (*URIRef*) –

#### **Return type**

*None*

### **close(*commit\_pending\_transaction*=*False*)**

This closes the database connection. The *commit\_pending\_transaction* parameter specifies whether to commit all pending transactions before closing (if the store is transactional).

#### **Parameters**

**commit\_pending\_transaction** (*bool*) –

#### **Return type**

*None*

### **commit()**

#### **Return type**

*None*

**context\_aware:** *bool* = *False*

### **contexts(*triple*=*None*)**

Generator over all contexts in the graph. If triple is specified, a generator over all contexts the triple is in. if store is *graph\_aware*, may also return empty contexts

#### **Return type**

*Generator*[*Graph*, *None*, *None*]

#### **Returns**

a generator over Nodes

#### **Parameters**

**triple** (*Optional*[*Tuple*[*Node*, *Node*, *Node*]]) –

**create**(*configuration*)

**Parameters**

**configuration** (*str*) –

**Return type**

*None*

**destroy**(*configuration*)

This destroys the instance of the store identified by the configuration string.

**Parameters**

**configuration** (*str*) –

**Return type**

*None*

**formula\_aware:** *bool* = *False*

**gc**()

Allows the store to perform any needed garbage collection

**Return type**

*None*

**graph\_aware:** *bool* = *False*

**namespace**(*prefix*)

**Parameters**

**prefix** (*str*) –

**Return type**

*Optional*[*URIRef*]

**namespaces**()

**Return type**

*Iterator*[*Tuple*[*str*, *URIRef*]]

**property node\_pickler:** *NodePickler*

**open**(*configuration*, *create=False*)

Opens the store specified by the configuration string. If create is True a store will be created if it does not already exist. If create is False and a store does not already exist an exception is raised. An exception is also raised if a store exists, but there is insufficient permissions to open the store. This should return one of: *VALID\_STORE*, *CORRUPTED\_STORE*, or *NO\_STORE*

**Parameters**

- **configuration** (*str*) –

- **create** (*bool*) –

**Return type**

*Optional*[*int*]

**prefix**(*namespace*)

**Parameters**

**namespace** (*URIRef*) –

**Return type**`Optional[str]`**query**(*query*, *initNs*, *initBindings*, *queryGraph*, *\*\*kwargs*)

If stores provide their own SPARQL implementation, override this.

*queryGraph* is `None`, a `URIRef` or `'__UNION__'` If `None` the graph is specified in the query-string/object If `URIRef` it specifies the graph to query, If `'__UNION__'` the union of all named graphs should be queried (This is used by `ConjunctiveGraphs` Values other than `None` obviously only makes sense for context-aware stores.)

**Parameters**

- **query** (`Union[Query, str]`) –
- **initNs** (`Mapping[str, Any]`) –
- **initBindings** (`Mapping[str, Identifier]`) –
- **queryGraph** (`str`) –
- **kwargs** (`Any`) –

**Return type**`Result`**remove**(*triple*, *context=None*)

Remove the set of triples matching the pattern from the store

**Parameters**

- **triple** (`Tuple[Optional[Node], Optional[Node], Optional[Node]]`) –
- **context** (`Optional[Graph]`) –

**Return type**`None`**remove\_graph**(*graph*)

Remove a graph from the store, this should also remove all triples in the graph

**Parameters**

- **graphid** – a `Graph` instance
- **graph** (`Graph`) –

**Return type**`None`**rollback**()**Return type**`None`**transaction\_aware:** `bool = False`**triples**(*triple\_pattern*, *context=None*)

A generator over all the triples matching the pattern. Pattern can include any objects for used for comparing against nodes in the store, for example, `REGEXTerm`, `URIRef`, `Literal`, `BNode`, `Variable`, `Graph`, `QuotedGraph`, `Date?` `DateRange?`

**Parameters**

- **context** (`Optional[Graph]`) – A conjunctive query can be indicated by either providing a value of `None`, or a specific context can be queries by passing a `Graph` instance (if store is context aware).
- **triple\_pattern** (`Tuple[Optional[Node], Optional[Node], Optional[Node]]`) –

**Return type**`Iterator[Tuple[Tuple[Node, Node, Node], Iterator[Optional[Graph]]]]`**triples\_choices**(*triple*, *context=None*)

A variant of triples that can take a list of terms instead of a single term in any slot. Stores can implement this to optimize the response time from the default ‘fallback’ implementation, which will iterate over each term in the list and dispatch to triples

**Parameters**

- **triple** (`Union[Tuple[List[Node], Node, Node], Tuple[Node, List[Node], Node], Tuple[Node, Node, List[Node]]]`) –
- **context** (`Optional[Graph]`) –

**Return type**`Generator[Tuple[Tuple[Node, Node, Node], Iterator[Optional[Graph]]], None, None]`**update**(*update*, *initNs*, *initBindings*, *queryGraph*, *\*\*kwargs*)

If stores provide their own (SPARQL) Update implementation, override this.

*queryGraph* is `None`, a `URIRef` or ‘\_\_UNION\_\_’ If `None` the graph is specified in the query-string/object If `URIRef` it specifies the graph to query, If ‘\_\_UNION\_\_’ the union of all named graphs should be queried (This is used by `ConjunctiveGraphs` Values other than `None` obviously only makes sense for context-aware stores.)

**Parameters**

- **update** (`Union[Update, str]`) –
- **initNs** (`Mapping[str, Any]`) –
- **initBindings** (`Mapping[str, Identifier]`) –
- **queryGraph** (`str`) –
- **kwargs** (`Any`) –

**Return type**`None`**class** `rdflib.store.StoreCreatedEvent`(*\*\*kw*)Bases: `Event`

This event is fired when the Store is created, it has the following attribute:

- **configuration**: string used to create the store

`__module__ = 'rdflib.store'`**class** `rdflib.store.TripleAddedEvent`(*\*\*kw*)Bases: `Event`

This event is fired when a triple is added, it has the following attributes:

- the triple added to the graph
- the context of the triple, if any

- the graph to which the triple was added

```
__module__ = 'rdflib.store'
```

```
class rdflib.store.TripleRemovedEvent(**kw)
```

Bases: *Event*

This event is fired when a triple is removed, it has the following attributes:

- the triple removed from the graph
- the context of the triple, if any
- the graph from which the triple was removed

```
__module__ = 'rdflib.store'
```

### rdflib.term module

This module defines the different types of terms. Terms are the kinds of objects that can appear in a quoted/asserted triple. This includes those that are core to RDF:

- *Blank Nodes*
- *URI References*
- *Literals* (which consist of a literal value, datatype and language tag)

Those that extend the RDF model into N3:

- *Formulae*
- *Universal Quantifications (Variables)*

And those that are primarily for matching against 'Nodes' in the underlying Graph:

- REGEX Expressions
- Date Ranges
- Numerical Ranges

```
class rdflib.term.BNode(value: str | None = None, _sn_gen: ~typing.Callable[[], str] = <function
    _serial_number_generator.<locals>._generator>, _prefix: str = 'N')
```

Bases: *IdentifiedNode*

RDF 1.1's Blank Nodes Section: <https://www.w3.org/TR/rdf11-concepts/#section-blank-nodes>

Blank Nodes are local identifiers for unnamed nodes in RDF graphs that are used in some concrete RDF syntaxes or RDF store implementations. They are always locally scoped to the file or RDF store, and are not persistent or portable identifiers for blank nodes. The identifiers for Blank Nodes are not part of the RDF abstract syntax, but are entirely dependent on particular concrete syntax or implementation (such as Turtle, JSON-LD).

—

RDFLib's BNode class makes unique IDs for all the Blank Nodes in a Graph but you should *never* expect, or reply on, BNodes' IDs to match across graphs, or even for multiple copies of the same graph, if they are regenerated from some non-RDFLib source, such as loading from RDF data.

```
__module__ = 'rdflib.term'
```

```
static __new__(cls, value=None, _sn_gen=<function _serial_number_generator.<locals>._generator>,
              _prefix='N')
```

# only store implementations should pass in a value

**Parameters**

- **value** (Optional[str]) –
- **\_sn\_gen** (Callable[[], str]) –
- **\_prefix** (str) –

**Return type**

*BNode*

```
__reduce__()
```

Helper for pickle.

**Return type**

Tuple[Type[BNode], Tuple[str]]

```
__repr__()
```

Return repr(self).

**Return type**

str

```
__slots__ = ()
```

```
n3(namespace_manager=None)
```

**Parameters**

**namespace\_manager** (Optional[NamespaceManager]) –

**Return type**

str

```
skolemize(authority=None, basepath=None)
```

Create a URIRef “skolem” representation of the BNode, in accordance with <http://www.w3.org/TR/rdf11-concepts/#section-skolemization>

New in version 4.0.

**Parameters**

- **authority** (Optional[str]) –
- **basepath** (Optional[str]) –

**Return type**

*URIRef*

```
class rdflib.term.IdentifiedNode(value: str)
```

Bases: *Identifier*

An abstract class, primarily defined to identify Nodes that are not Literals.

The name “Identified Node” is not explicitly defined in the RDF specification, but can be drawn from this section: <https://www.w3.org/TR/rdf-concepts/#section-URI-Vocabulary>

```
__dict__ = mappingproxy({'__module__': 'rdflib.term', '__doc__': '\n An abstract
class, primarily defined to identify Nodes that are not Literals.\n\n The name
"Identified Node" is not explicitly defined in the RDF specification, but can be
drawn from this section:
https://www.w3.org/TR/rdf-concepts/#section-URI-Vocabulary\n ', '__getnewargs__':
<function IdentifiedNode.__getnewargs__>, 'toPython': <function
IdentifiedNode.toPython>, '__dict__': <attribute '__dict__' of 'IdentifiedNode'
objects>, '__weakref__': <attribute '__weakref__' of 'IdentifiedNode' objects>,
'__annotations__': {}})
```

```
__getnewargs__()
```

**Return type**

`Tuple[str]`

```
__module__ = 'rdflib.term'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
toPython()
```

**Return type**

`str`

```
class rdflib.term.Identifier(value: str)
```

Bases: `Node`, `str`

See <http://www.w3.org/2002/07/rdf-identifier-terminology/> regarding choice of terminology.

```
__eq__(other)
```

Equality for Nodes.

```
>>> BNode("foo")==None
False
>>> BNode("foo")==URIRef("foo")
False
>>> URIRef("foo")==BNode("foo")
False
>>> BNode("foo")!=URIRef("foo")
True
>>> URIRef("foo")!=BNode("foo")
True
>>> Variable('a")!=URIRef('a')
True
>>> Variable('a")!=Variable('a')
False
```

**Parameters**

**other** (`Any`) –

**Return type**

`bool`

```
__ge__(other)
```

Return self>=value.

**Parameters****other** (*Any*) –**Return type***bool***\_\_gt\_\_**(*other*)

This implements ordering for Nodes,

This tries to implement this: <http://www.w3.org/TR/sparql11-query/#modOrderBy>

Variables are not included in the SPARQL list, but they are greater than BNodes and smaller than everything else

**Parameters****other** (*Any*) –**Return type***bool***\_\_hash\_\_**()

Return hash(self).

**\_\_le\_\_**(*other*)

Return self&lt;=value.

**Parameters****other** (*Any*) –**Return type***bool***\_\_lt\_\_**(*other*)

Return self&lt;value.

**Parameters****other** (*Any*) –**Return type***bool***\_\_module\_\_** = 'rdflib.term'**\_\_ne\_\_**(*other*)

Return self!=value.

**Parameters****other** (*Any*) –**Return type***bool***static** **\_\_new\_\_**(*cls, value*)**Parameters****value** (*str*) –**Return type***Identifier***\_\_slots\_\_** = ()



**eq**(*other*)

A “semantic”/interpreted equality function, by default, same as `__eq__`

**Parameters**

**other** (*Any*) –

**Return type**

`bool`

**neq**(*other*)

A “semantic”/interpreted not equal function, by default, same as `__ne__`

**Parameters**

**other** (*Any*) –

**Return type**

`bool`

**startswith**(*prefix*, *start=Ellipsis*, *end=Ellipsis*)

Return True if S starts with the specified prefix, False otherwise. With optional start, test S beginning at that position. With optional end, stop comparing S at that position. prefix can also be a tuple of strings to try.

**Parameters**

**prefix** (*str*) –

**Return type**

`bool`

**class** `rdflib.term.Literal`(*lexical\_or\_value: Any*, *lang: str | None = None*, *datatype: str | None = None*, *normalize: bool | None = None*)

Bases: `Identifier`

RDF 1.1’s Literals Section: <http://www.w3.org/TR/rdf-concepts/#section-Graph-Literal>

Literals are used for values such as strings, numbers, and dates.

A literal in an RDF graph consists of two or three elements:

- a lexical form, being a Unicode string, which SHOULD be in Normal Form C
- a datatype IRI, being an IRI identifying a datatype that determines how the lexical form maps to a literal value, and
- if and only if the datatype IRI is <http://www.w3.org/1999/02/22-rdf-syntax-ns#langString>, a non-empty language tag. The language tag MUST be well-formed according to section 2.2.9 of [Tags for identifying languages](#).

A literal is a language-tagged string if the third element is present. Lexical representations of language tags MAY be converted to lower case. The value space of language tags is always in lower case.

—

For valid XSD datatypes, the lexical form is optionally normalized at construction time. Default behaviour is set by `rdflib.NORMALIZE_LITERALS` and can be overridden by the `normalize` parameter to `__new__`

Equality and hashing of Literals are done based on the lexical form, i.e.:

```
>>> from rdflib.namespace import XSD
```

```
>>> Literal('01') != Literal('1') # clear - strings differ
True
```

but with data-type they get normalized:

```
>>> Literal('01', datatype=XSD.integer) != Literal('1', datatype=XSD.integer)
False
```

unless disabled:

```
>>> Literal('01', datatype=XSD.integer, normalize=False) != Literal('1',
↳datatype=XSD.integer)
True
```

Value based comparison is possible:

```
>>> Literal('01', datatype=XSD.integer).eq(Literal('1', datatype=XSD.float))
True
```

The eq method also provides limited support for basic python types:

```
>>> Literal(1).eq(1) # fine - int compatible with xsd:integer
True
>>> Literal('a').eq('b') # fine - str compatible with plain-lit
False
>>> Literal('a', datatype=XSD.string).eq('a') # fine - str compatible with
↳xsd:string
True
>>> Literal('a').eq(1) # not fine, int incompatible with plain-lit
NotImplemented
```

Greater-than/less-than ordering comparisons are also done in value space, when compatible datatypes are used. Incompatible datatypes are ordered by DT, or by lang-tag. For other nodes the ordering is None < BNode < URIRef < Literal

Any comparison with non-rdflib Node are “NotImplemented” In PY3 this is an error.

```
>>> from rdflib import Literal, XSD
>>> lit2006 = Literal('2006-01-01',datatype=XSD.date)
>>> lit2006.toPython()
datetime.date(2006, 1, 1)
>>> lit2006 < Literal('2007-01-01',datatype=XSD.date)
True
>>> Literal(datetime.utcnow()).datatype
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dateTime')
>>> Literal(1) > Literal(2) # by value
False
>>> Literal(1) > Literal(2.0) # by value
False
>>> Literal('1') > Literal(1) # by DT
True
>>> Literal('1') < Literal('1') # by lexical form
False
>>> Literal('a', lang='en') > Literal('a', lang='fr') # by lang-tag
False
>>> Literal(1) > URIRef('foo') # by node-type
True
```

The > < operators will eat this NotImplemented and throw a TypeError (py3k):

```
>>> Literal(1).__gt__(2.0)
NotImplemented
```

`__abs__()`

**Return type**

*Literal*

```
>>> abs(Literal(-1))
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
```

```
>>> from rdflib.namespace import XSD
>>> abs(Literal("-1", datatype=XSD.integer))
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
```

```
>>> abs(Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: Not a number; rdflib.term.Literal('1')
```

`__add__(val)`

```
>>> from rdflib.namespace import XSD
>>> Literal(1) + 1
rdflib.term.Literal('2', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
>>> Literal("1") + "1"
rdflib.term.Literal('11')
```

```
# Handling dateTime/date/time based operations in Literals >>> a = Literal('2006-01-01T20:50:00',
datatype=XSD.dateTime) >>> b = Literal('P31D', datatype=XSD.duration) >>> (a + b)
rdflib.term.Literal('2006-02-01T20:50:00', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dateTime'))
>>> from rdflib.namespace import XSD >>> a = Literal('2006-07-01T20:52:00', datatype=XSD.dateTime) >>> b = Literal('P122DT15H58M', datatype=XSD.duration)
>>> (a + b) rdflib.term.Literal('2006-11-01T12:50:00', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dateTime'))
```

**Parameters**

**val** (*Any*) –

**Return type**

*Literal*

```
__annotations__ = {'_datatype': typing.Optional[rdflib.term.URIRef], '_ill_typed':
typing.Optional[bool], '_language': typing.Optional[str], '_value': typing.Any}
```

`__bool__()`

Is the Literal “True” This is used for if statements, bool(literal), etc.

**Return type**

*bool*

`__eq__(other)`

Literals are only equal to other literals.

“Two literals are equal if and only if all of the following hold: \* The strings of the two lexical forms compare equal, character by character. \* Either both or neither have language tags. \* The language tags, if any, compare equal. \* Either both or neither have datatype URIs. \* The two datatype URIs, if any, compare equal, character by character.” – 6.5.1 Literal Equality (RDF: Concepts and Abstract Syntax)

```
>>> Literal("1", datatype=URIRef("foo")) == Literal("1", datatype=URIRef("foo"))
True
>>> Literal("1", datatype=URIRef("foo")) == Literal("1", datatype=URIRef("foo2
→"))
False
```

```
>>> Literal("1", datatype=URIRef("foo")) == Literal("2", datatype=URIRef("foo"))
False
>>> Literal("1", datatype=URIRef("foo")) == "asdf"
False
>>> from rdflib import XSD
>>> Literal('2007-01-01', datatype=XSD.date) == Literal('2007-01-01',
→datatype=XSD.date)
True
>>> Literal('2007-01-01', datatype=XSD.date) == date(2007, 1, 1)
False
>>> Literal("one", lang="en") == Literal("one", lang="en")
True
>>> Literal("hast", lang='en') == Literal("hast", lang='de')
False
>>> Literal("1", datatype=XSD.integer) == Literal(1)
True
>>> Literal("1", datatype=XSD.integer) == Literal("01", datatype=XSD.integer)
True
```

**Parameters**

**other** (*Any*) –

**Return type**

*bool*

`__ge__(other)`

Return self>=value.

**Parameters**

**other** (*Any*) –

**Return type**

*bool*

`__getstate__()`**Return type**

*Tuple[None, Dict[str, Optional[str]]]*

`__gt__(other)`

This implements ordering for Literals, the other comparison methods delegate here

This tries to implement this: <http://www.w3.org/TR/sparql11-query/#modOrderBy>

In short, Literals with compatible data-types are ordered in value space, i.e. >>> from rdflib import XSD

```
>>> Literal(1) > Literal(2) # int/int
False
>>> Literal(2.0) > Literal(1) # double/int
True
>>> from decimal import Decimal
>>> Literal(Decimal("3.3")) > Literal(2.0) # decimal/double
True
>>> Literal(Decimal("3.3")) < Literal(4.0) # decimal/double
True
>>> Literal('b') > Literal('a') # plain lit/plain lit
True
>>> Literal('b') > Literal('a', datatype=XSD.string) # plain lit/xsd:str
True
```

Incompatible datatype mismatches ordered by DT

```
>>> Literal(1) > Literal("2") # int>string
False
```

Langtagged literals by lang tag >>> Literal("a", lang="en") > Literal("a", lang="fr") False

#### Parameters

**other** (Any) –

#### Return type

bool

**\_\_hash\_\_()**

```
>>> from rdflib.namespace import XSD
>>> a = {Literal('1', datatype=XSD.integer): 'one'}
:rtype: :py:class:`int`
```

```
>>> Literal('1', datatype=XSD.double) in a
False
```

“Called for the key object for dictionary operations, and by the built-in function hash(). Should return a 32-bit integer usable as a hash value for dictionary operations. The only required property is that objects which compare equal have the same hash value; it is advised to somehow mix together (e.g., using exclusive or) the hash values for the components of the object that also play a part in comparison of objects.” – 3.4.1 Basic customization (Python)

“Two literals are equal if and only if all of the following hold: \* The strings of the two lexical forms compare equal, character by character. \* Either both or neither have language tags. \* The language tags, if any, compare equal. \* Either both or neither have datatype URIs. \* The two datatype URIs, if any, compare equal, character by character.” – 6.5.1 Literal Equality (RDF: Concepts and Abstract Syntax)

**\_\_invert\_\_()**

#### Return type

Literal

```
>>> ~(Literal(-1))
rdflib.term.Literal('0', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
```

```
>>> from rdflib.namespace import XSD
>>> ~( Literal("-1", datatype=XSD.integer))
rdflib.term.Literal('0', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
```

Not working:

```
>>> ~(Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: Not a number; rdflib.term.Literal('1')
```

`__le__(other)`

```
>>> from rdflib.namespace import XSD
>>> Literal('2007-01-01T10:00:00', datatype=XSD.dateTime
...        ) <= Literal('2007-01-01T10:00:00', datatype=XSD.dateTime)
True
```

**Parameters**

**other** (Any) –

**Return type**

bool

`__lt__(other)`

Return self<value.

**Parameters**

**other** (Any) –

**Return type**

bool

`__module__ = 'rdflib.term'`

`__neg__()`

```
>>> (- Literal(1))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
>>> (- Literal(10.5))
rdflib.term.Literal('-10.5', datatype=rdflib.term.URIRef('http://www.w3.org/
↳2001/XMLSchema#double'))
>>> from rdflib.namespace import XSD
:rtype: :py:class:`~rdflib.term.Literal`
```

```
>>> (- Literal("1", datatype=XSD.integer))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
```

```
>>> (- Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
```

(continues on next page)

(continued from previous page)

```
TypeError: Not a number; rdflib.term.Literal('1')
>>>
```

**static** `__new__(cls, lexical_or_value, lang=None, datatype=None, normalize=None)`

**Parameters**

- `lexical_or_value` (*Any*) –
- `lang` (*Optional[str]*) –
- `datatype` (*Optional[str]*) –
- `normalize` (*Optional[bool]*) –

**Return type**

*Literal*

`__pos__()`

```
>>> (+ Literal(1))
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
↪XMLSchema#integer')
>>> (+ Literal(-1))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
↪XMLSchema#integer')
>>> from rdflib.namespace import XSD
:rtype: :py:class: `~rdflib.term.Literal`
```

```
>>> (+ Literal("-1", datatype=XSD.integer))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
↪XMLSchema#integer'))
```

```
>>> (+ Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: Not a number; rdflib.term.Literal('1')
```

`__reduce__()`

Helper for pickle.

**Return type**

*Tuple*[*Type*[*Literal*], *Tuple*[*str*, *Optional*[*str*], *Optional*[*str*]]]

`__repr__()`

Return repr(self).

**Return type**

*str*

`__setstate__(arg)`

**Parameters**

`arg` (*Tuple*[*Any*, *Dict*[*str*, *Any*]]) –

**Return type**

*None*

```
__slots__ = ('_language', '_datatype', '_value', '_ill_typed')
__sub__(val)
```

```
>>> from rdflib.namespace import XSD
>>> Literal(2) - 1
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
>>> Literal(1.1) - 1.0
rdflib.term.Literal('0.100000000000000009', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#double'))
>>> Literal(1.1) - 1
rdflib.term.Literal('0.1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#decimal'))
>>> Literal(1.1, datatype=XSD.float) - Literal(1.0, datatype=XSD.float)
rdflib.term.Literal('0.100000000000000009', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#float'))
>>> Literal("1.1") - 1.0
Traceback (most recent call last):
...
TypeError: Not a number; rdflib.term.Literal('1.1')
>>> Literal(1.1, datatype=XSD.integer) - Literal(1.0, datatype=XSD.integer)
rdflib.term.Literal('0.100000000000000009', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
```

```
# Handling dateTime/date/time based operations in Literals >>> a = Literal('2006-01-01T20:50:00',
datatype=XSD.dateTime) >>> b = Literal('2006-02-01T20:50:00', datatype=XSD.dateTime) >>> (b -
a) rdflib.term.Literal('P31D', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#duration'))
>>> from rdflib.namespace import XSD >>> a = Literal('2006-07-01T20:52:00',
datatype=XSD.dateTime) >>> b = Literal('2006-11-01T12:50:00', datatype=XSD.dateTime)
>>> (a - b) rdflib.term.Literal('-P122DT15H58M', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#duration'))
>>> (b - a) rdflib.term.Literal('P122DT15H58M', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#duration'))
```

#### Parameters

**val** (*Any*) –

#### Return type

*Literal*

**property datatype:** *URIRef* | *None*

**eq**(*other*)

Compare the value of this literal with something else

Either, with the value of another literal comparisons are then done in literal “value space”, and according to the rules of XSD subtype-substitution/type-promotion

OR, with a python object:

basestring objects can be compared with plain-literals, or those with datatype xsd:string

bool objects with xsd:boolean

a int, long or float with numeric xsd types

isodate date,time,datetime objects with xsd:date,xsd:time or xsd:datetime

Any other operations returns NotImplemented



**Parameters****other** (*Any*) –**Return type***bool***property ill\_typed:** *bool* | *None*

For *recognized datatype IRIs*, this value will be *True* if the literal is ill formed, otherwise it will be *False*. *Literal.value* (i.e. the *literal value*) should always be defined if this property is *False*, but should not be considered reliable if this property is *True*.

If the literal's datatype is *None* or not in the set of *recognized datatype IRIs* this value will be *None*.

**property language:** *str* | *None***n3**(*namespace\_manager=None*)

Returns a representation in the N3 format.

Examples:

```
>>> Literal("foo").n3()
'"foo"'
```

Strings with newlines or triple-quotes:

```
>>> Literal("foo\nbar").n3()
'"""foo\nbar"""'
```

```
>>> Literal("'\"'").n3()
'"\'\\"''
```

```
>>> Literal('"""').n3()
'"\\""\\""\\"''
```

Language:

```
>>> Literal("hello", lang="en").n3()
'"hello"@en'
```

Datatypes:

```
>>> Literal(1).n3()
'"1"^^<http://www.w3.org/2001/XMLSchema#integer>'
```

```
>>> Literal(1.0).n3()
'"1.0"^^<http://www.w3.org/2001/XMLSchema#double>'
```

```
>>> Literal(True).n3()
'"true"^^<http://www.w3.org/2001/XMLSchema#boolean>'
```

Datatype and language isn't allowed (datatype takes precedence):

```
>>> Literal(1, lang="en").n3()
'"1"^^<http://www.w3.org/2001/XMLSchema#integer>'
```

Custom datatype:

```
>>> footype = URIRef("http://example.org/ns#foo")
>>> Literal("1", datatype=footype).n3()
'"1"^^<http://example.org/ns#foo>'
```

Passing a namespace-manager will use it to abbreviate datatype URIs:

```
>>> from rdflib import Graph
>>> Literal(1).n3(Graph().namespace_manager)
'"1"^^xsd:integer'
```

#### Parameters

**namespace\_manager** (*Optional*[*NamespaceManager*]) –

#### Return type

*str*

#### **neq**(*other*)

A “semantic”/interpreted not equal function, by default, same as `__ne__`

#### Parameters

**other** (*Any*) –

#### Return type

*bool*

#### **normalize**()

Returns a new literal with a normalised lexical representation of this literal >>> from rdflib import XSD >>> Literal("01", datatype=XSD.integer, normalize=False).normalize() rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))

Illegal lexical forms for the datatype given are simply passed on >>> Literal("a", datatype=XSD.integer, normalize=False) rdflib.term.Literal('a', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))

#### Return type

*Literal*

#### **toPython**()

Returns an appropriate python datatype derived from this RDF Literal

#### Return type

*Any*

**property value:** *Any*

#### **class** rdflib.term.Node

Bases: *object*

A Node in the Graph.

**\_\_module\_\_** = 'rdflib.term'

**\_\_slots\_\_** = ()

#### **class** rdflib.term.URIRef(*value: str, base: str | None = None*)

Bases: *IdentifiedNode*

RDF 1.1’s IRI Section <https://www.w3.org/TR/rdf11-concepts/#section-IRIs>

---

**Note:** Documentation on RDF outside of RDFLib uses the term IRI or URI whereas this class is called `URIRef`. This is because it was made when the first version of the RDF specification was current, and it used the term *URIRef*, see [RDF 1.0 URIRef](#)

---

An IRI (Internationalized Resource Identifier) within an RDF graph is a Unicode string that conforms to the syntax defined in RFC 3987.

IRIs in the RDF abstract syntax MUST be absolute, and MAY contain a fragment identifier.

IRIs are a generalization of URIs [RFC3986] that permits a wider range of Unicode characters.

`__add__(other)`

Return self+value.

**Return type**

*URIRef*

```
__annotations__ = {'__invert__': typing.Callable[[ForwardRef('URIRef')],
ForwardRef('InvPath')], '__neg__': typing.Callable[[ForwardRef('URIRef')],
ForwardRef('NegatedPath')], '__or__': typing.Callable[[ForwardRef('URIRef'),
typing.Union[ForwardRef('URIRef'), ForwardRef('Path')]],
ForwardRef('AlternativePath')], '__truediv__':
typing.Callable[[ForwardRef('URIRef'), typing.Union[ForwardRef('URIRef'),
ForwardRef('Path')]], ForwardRef('SequencePath')]]}
```

`__invert__()`

inverse path

**Parameters**

**p** (*Union*[*URIRef*, *Path*]) –

**Return type**

*InvPath*

`__mod__(other)`

Return self%value.

**Return type**

*URIRef*

`__module__ = 'rdflib.term'`

`__mul__(mul)`

cardinality path

**Parameters**

- **p** (*Union*[*URIRef*, *Path*]) –
- **mul** (*Literal*['\*', '+', '?']) –

**Return type**

*MulPath*

`__neg__()`

negated path

**Parameters**

**p** (*Union*[*URIRef*, *AlternativePath*, *InvPath*]) –

**Return type***NegatedPath***static** `__new__(cls, value, base=None)`**Parameters**

- **value** (*str*) –
- **base** (*Optional[str]*) –

**Return type***URIRef*`__or__(other)`

alternative path

**Parameters**

- **self** (*Union[URIRef, Path]*) –
- **other** (*Union[URIRef, Path]*) –

`__radd__(other)`**Return type***URIRef*`__reduce__()`

Helper for pickle.

**Return type***Tuple[Type[URIRef], Tuple[str]]*`__repr__()`

Return repr(self).

**Return type***str*`__slots__ = ()``__truediv__(other)`

sequence path

**Parameters**

- **self** (*Union[URIRef, Path]*) –
- **other** (*Union[URIRef, Path]*) –

`de_skolemize()`

Create a Blank Node from a skolem URI, in accordance with <http://www.w3.org/TR/rdf11-concepts/#section-skolemization>. This function accepts only rdflib type skolemization, to provide a round-tripping within the system. :rtype: *BNode*

New in version 4.0.

`defrag()`**Return type***URIRef*

**property fragment:** `str`

Return the URL Fragment

```
>>> URIRef("http://example.com/some/path/#some-fragment").fragment
'some-fragment'
>>> URIRef("http://example.com/some/path/").fragment
''
```

**n3(namespace\_manager=None)**

This will do a limited check for valid URIs, essentially just making sure that the string includes no illegal characters (<, >, ", {, }, |, \, `, ^)

**Parameters**

**namespace\_manager** (`Optional[NamespaceManager]`) – if not None, will be used to make up a prefixed name

**Return type**

`str`

**class rdflib.term.Variable(value: str)**

Bases: `Identifier`

A Variable - this is used for querying, or in Formula aware graphs, where Variables can be stored

**\_\_module\_\_** = 'rdflib.term'

**static \_\_new\_\_(cls, value)**

**Parameters**

**value** (`str`) –

**Return type**

`Variable`

**\_\_reduce\_\_()**

Helper for pickle.

**Return type**

`Tuple[Type[Variable], Tuple[str]]`

**\_\_repr\_\_()**

Return repr(self).

**Return type**

`str`

**\_\_slots\_\_** = ()

**n3(namespace\_manager=None)**

**Parameters**

**namespace\_manager** (`Optional[NamespaceManager]`) –

**Return type**

`str`

**toPython()**

**Return type**

`str`

`rdflib.term.bind(datatype, pythontype, constructor=None, lexicalizer=None, datatype_specific=False)`

register a new datatype<->pythontype binding

#### Parameters

- **constructor** (`Optional[Callable[[str], Any]]`) – an optional function for converting lexical forms into a Python instances, if not given the pythontype is used directly
- **lexicalizer** (`Optional[Callable[[Any], Union[str, bytes]]]`) – an optional function for converting python objects to lexical form, if not given object.\_\_str\_\_ is used
- **datatype\_specific** (`bool`) – makes the lexicalizer function be accessible from the pair (pythontype, datatype) if set to True or from the pythontype otherwise. False by default
- **datatype** (`str`) –
- **pythontype** (`Type[Any]`) –

#### Return type

`None`

### rdflib.util module

`rdflib.util.date_time(t=None, local_time_zone=False)`

<http://www.w3.org/TR/NOTE-datetime> ex: 1997-07-16T19:20:30Z

```
>>> date_time(1126482850)
'2005-09-11T23:54:10Z'
```

@@ this will change depending on where it is run #>>> date\_time(1126482850, local\_time\_zone=True) #'2005-09-11T19:54:10-04:00'

```
>>> date_time(1)
'1970-01-01T00:00:01Z'
```

```
>>> date_time(0)
'1970-01-01T00:00:00Z'
```

`rdflib.util.find_roots(graph, prop, roots=None)`

Find the roots in some sort of transitive hierarchy.

`find_roots(graph, rdflib.RDFS.subClassOf)` will return a set of all roots of the sub-class hierarchy

Assumes triple of the form (child, prop, parent), i.e. the direction of `RDFS.subClassOf` or `SKOS.broader`

#### Parameters

- **graph** (`Graph`) –
- **prop** (`URIRef`) –
- **roots** (`Optional[Set[Node]]`) –

#### Return type

`Set[Node]`

`rdflib.util.first(seq)`

return the first element in a python sequence for graphs, use `graph.value` instead

#### Parameters

**seq** (`Iterable[TypeVar(_AnyT)]`) –

**Return type**`Optional[TypeVar(_AnyT)]``rdflib.util.from_n3(s, default=None, backend=None, nsm=None)`

Creates the Identifier corresponding to the given n3 string.

```

>>> from rdflib.term import URIRef, Literal
>>> from rdflib.namespace import NamespaceManager
>>> from_n3('<http://ex.com/foo>') == URIRef('http://ex.com/foo')
True
>>> from_n3('"foo"@de') == Literal('foo', lang='de')
True
>>> from_n3('"""multi\nline\nstring"""@en') == Literal(
...     'multi\nline\nstring', lang='en')
True
>>> from_n3('42') == Literal(42)
True
>>> from_n3(Literal(42).n3()) == Literal(42)
True
>>> from_n3('"42"^^xsd:integer') == Literal(42)
True
>>> from rdflib import RDFS
>>> from_n3('rdfs:label') == RDFS['label']
True
>>> nsm = NamespaceManager(rdflib.graph.Graph())
>>> nsm.bind('dbpedia', 'http://dbpedia.org/resource/')
>>> berlin = URIRef('http://dbpedia.org/resource/Berlin')
>>> from_n3('dbpedia:Berlin', nsm=nsm) == berlin
True

```

**Parameters**

- **s** (`str`) –
- **default** (`Optional[str]`) –
- **backend** (`Optional[str]`) –
- **nsm** (`Optional[NamespaceManager]`) –

**Return type**`Union[Node, str, None]`

`rdflib.util.get_tree(graph, root, prop, mapper=<function <lambda>>, sortkey=None, done=None, dir='down')`

Return a nested list/tuple structure representing the tree built by the transitive property given, starting from the root given

i.e.

```

get_tree(graph,
         rdflib.URIRef("http://xmlns.com/foaf/0.1/Person"), rdflib.RDFS.subClassOf)

```

will return the structure for the subClassTree below person.

`dir='down'` assumes triple of the form (child, prop, parent), i.e. the direction of `RDFS.subClassOf` or `SKOS.broader` Any other `dir` traverses in the other direction

**Parameters**

- **graph** (*Graph*) –
- **root** (*Node*) –
- **prop** (*URIRef*) –
- **mapper** (*Callable*[[*Node*], *Node*]) –
- **sortkey** (*Optional*[*Callable*[[*Any*], *Any*]]) –
- **done** (*Optional*[*Set*[*Node*]]) –
- **dir** (*str*) –

**Return type**

*Optional*[*Tuple*[*Node*, *List*[*Any*]]]

`rdflib.util.guess_format(fpath, fmap=None)`

Guess RDF serialization based on file suffix. Uses SUFFIX\_FORMAT\_MAP unless `fmap` is provided. Examples:

```
>>> guess_format('path/to/file.rdf')
'xml'
>>> guess_format('path/to/file.owl')
'xml'
>>> guess_format('path/to/file.ttl')
'turtle'
>>> guess_format('path/to/file.json')
'json-ld'
>>> guess_format('path/to/file.xhtml')
'rdfa'
>>> guess_format('path/to/file.svg')
'rdfa'
>>> guess_format('path/to/file.xhtml', {'xhtml': 'grddl'})
'grddl'
```

This also works with just the suffixes, with or without leading dot, and regardless of letter case:

```
>>> guess_format('.rdf')
'xml'
>>> guess_format('rdf')
'xml'
>>> guess_format('RDF')
'xml'
```

**Parameters**

- **fpath** (*str*) –
- **fmap** (*Optional*[*Dict*[*str*, *str*]]) –

**Return type**

*Optional*[*str*]

`rdflib.util.list2set(seq)`

Return a new list without duplicates. Preserves the order, unlike `set(seq)`

**Parameters**

**seq** (*Iterable*[*TypeVar*(*\_HashableT*, bound=*Hashable*)] –



**Return type**`List[TypeVar(_HashableT, bound= Hashable)]``rdflib.util.more_than(sequence, number)`

Returns 1 if sequence has more items than number and 0 if not.

**Parameters**

- **sequence** (`Iterable[Any]`) –
- **number** (`int`) –

**Return type**`int``rdflib.util.parse_date_time(val)`

always returns seconds in UTC

# tests are written like this to make any errors easier to understand >>> parse\_date\_time('2005-09-11T23:54:10Z') - 1126482850.0 0.0

```
>>> parse_date_time('2005-09-11T16:54:10-07:00') - 1126482850.0
0.0
```

```
>>> parse_date_time('1970-01-01T00:00:01Z') - 1.0
0.0
```

```
>>> parse_date_time('1970-01-01T00:00:00Z') - 0.0
0.0
>>> parse_date_time("2005-09-05T10:42:00") - 1125916920.0
0.0
```

**Parameters**`val (str)` –**Return type**`int``rdflib.util.to_term(s, default=None)`

Creates and returns an Identifier of type corresponding to the pattern of the given positional argument string s:

‘’ returns the default keyword argument value or None

‘<s>’ returns `URIRef(s)` (i.e. without angle brackets)“s” returns `Literal(s)` (i.e. without doublequotes)‘\_s’ returns `BNode(s)` (i.e. without leading underscore)**Parameters**

- **s** (`Optional[str]`) –
- **default** (`Optional[Identifier]`) –

**Return type**`Optional[Identifier]`

`rdflib.util.uniq(sequence, strip=0)`

removes duplicate strings from the sequence.

**Parameters**

- **sequence** (`Iterable[str]`) –
- **strip** (`int`) –

**Return type**

`Set[str]`

## rdflib.void module

`rdflib.void.generateVoID(g, dataset=None, res=None, distinctForPartitions=True)`

Returns a new graph with a VoID description of the passed dataset

For more info on Vocabulary of Interlinked Datasets (VoID), see: <http://vocab.deri.ie/void>

This only makes two passes through the triples (once to detect the types of things)

The tradeoff is that lots of temporary structures are built up in memory meaning lots of memory may be consumed :) I imagine at least a few copies of your original graph.

the `distinctForPartitions` parameter controls whether `distinctSubjects/objects` are tracked for each `class/propertyPartition` this requires more memory again

## Module contents

A pure Python package providing the core RDF constructs.

The package is intended to provide the core RDF types and interfaces for working with RDF. The package defines a plugin interface for parsers, stores, and serializers that other packages can use to implement parsers, stores, and serializers that will plug into the `rdflib` package.

The primary interface `rdflib` exposes to work with RDF is `rdflib.graph.Graph`.

A tiny example:

```
>>> from rdflib import Graph, URIRef, Literal
```

```
>>> g = Graph()
>>> result = g.parse("http://www.w3.org/2000/10/swap/test/meet/blue.rdf")
```

```
>>> print("graph has %s statements." % len(g))
graph has 4 statements.
>>>
>>> for s, p, o in g:
...     if (s, p, o) not in g:
...         raise Exception("It better be!")
```

```
>>> s = g.serialize(format='nt')
>>>
>>> sorted(g) == [
...     (URIRef("http://meetings.example.com/cal#m1"),
...     URIRef("http://www.example.org/meeting_organization#homePage"),
```

(continues on next page)

(continued from previous page)

```

...   URIRef("http://meetings.example.com/m1/hp")),
...   (URIRef("http://www.example.org/people#fred"),
...    URIRef("http://www.example.org/meeting_organization#attending"),
...    URIRef("http://meetings.example.com/cal#m1")),
...   (URIRef("http://www.example.org/people#fred"),
...    URIRef("http://www.example.org/personal_details#GivenName"),
...    Literal("Fred")),
...   (URIRef("http://www.example.org/people#fred"),
...    URIRef("http://www.example.org/personal_details#hasEmail"),
...    URIRef("mailto:fred@example.com"))
... ]
True

```

```

class rdflib.BNode(value: str | None = None, _sn_gen: ~typing.Callable[[], str] = <function
    _serial_number_generator.<locals>._generator>, _prefix: str = 'N')

```

Bases: *IdentifiedNode*

RDF 1.1's Blank Nodes Section: <https://www.w3.org/TR/rdf11-concepts/#section-blank-nodes>

Blank Nodes are local identifiers for unnamed nodes in RDF graphs that are used in some concrete RDF syntaxes or RDF store implementations. They are always locally scoped to the file or RDF store, and are not persistent or portable identifiers for blank nodes. The identifiers for Blank Nodes are not part of the RDF abstract syntax, but are entirely dependent on particular concrete syntax or implementation (such as Turtle, JSON-LD).

—

RDFLib's BNode class makes unique IDs for all the Blank Nodes in a Graph but you should *never* expect, or reply on, BNodes' IDs to match across graphs, or even for multiple copies of the same graph, if they are regenerated from some non-RDFLib source, such as loading from RDF data.

```
__annotations__ = {}
```

```
__module__ = 'rdflib.term'
```

```

static __new__(cls, value=None, _sn_gen=<function _serial_number_generator.<locals>._generator>,
    _prefix='N')

```

# only store implementations should pass in a value

#### Parameters

- **value** (Optional[str]) –
- **\_sn\_gen** (Callable[[], str]) –
- **\_prefix** (str) –

#### Return type

*BNode*

```
__reduce__()
```

Helper for pickle.

#### Return type

Tuple[Type[BNode], Tuple[str]]

```
__repr__()
```

Return repr(self).

**Return type**`str``__slots__ = ()``n3(namespace_manager=None)`**Parameters**`namespace_manager` (`Optional[NamespaceManager]`) –**Return type**`str``skolemize(authority=None, basepath=None)`

Create a `URIRef` “skolem” representation of the `BNode`, in accordance with <http://www.w3.org/TR/rdf11-concepts/#section-skolemization>

New in version 4.0.

**Parameters**

- `authority` (`Optional[str]`) –
- `basepath` (`Optional[str]`) –

**Return type**`URIRef``class rdflib.ConjunctiveGraph(store='default', identifier=None, default_graph_base=None)`

Bases: `Graph`

A `ConjunctiveGraph` is an (unnamed) aggregation of all the named graphs in a store.

It has a default graph, whose name is associated with the graph throughout its life. `__init__()` can take an identifier to use as the name of this default graph or it will assign a `BNode`.

All methods that add triples work against this default graph.

All queries are carried out against the union of all graphs.

**Parameters**

- `store` (`Union[Store, str]`) –
- `identifier` (`Union[IdentifiedNode, str, None]`) –
- `default_graph_base` (`Optional[str]`) –

```
__annotations__ = {'__identifier': 'ContextIdentifierType', '__store': 'Store',  
'default_context': 'ContextType'}
```

`__contains__(triple_or_quad)`

Support for ‘triple/quad in graph’ syntax

**Parameters**`triple_or_quad` (`Union[Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]], Tuple[Optional[Node], Union[Path, Node, None], Optional[Node], Optional[Graph]]]`) –**Return type**`bool`

**\_\_init\_\_**(*store='default', identifier=None, default\_graph\_base=None*)

**Parameters**

- **store** (`Union[Store, str]`) –
- **identifier** (`Union[IdentifiedNode, str, None]`) –
- **default\_graph\_base** (`Optional[str]`) –

**\_\_len\_\_**()

Number of triples in the entire conjunctive graph

**Return type**

`int`

**\_\_module\_\_** = 'rdflib.graph'

**\_\_reduce\_\_**()

Helper for pickle.

**Return type**

`Tuple[Type[Graph], Tuple[Store, IdentifiedNode]]`

**\_\_str\_\_**()

Return str(self).

**Return type**

`str`

**add**(*triple\_or\_quad*)

Add a triple or quad to the store.

if a triple is given it is added to the default context

**Parameters**

- **self** (`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`) –
- **triple\_or\_quad** (`Union[Tuple[Node, Node, Node], Tuple[Node, Node, Node, Optional[Graph]]]`) –

**Return type**

`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`

**addN**(*quads*)

Add a sequence of triples with context

**Parameters**

- **self** (`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`) –
- **quads** (`Iterable[Tuple[Node, Node, Node, Graph]]`) –

**Return type**

`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`

**context\_id**(*uri, context\_id=None*)

URI#context

**Parameters**

- **uri** (`str`) –
- **context\_id** (`Optional[str]`) –

**Return type**

[\*URIRef\*](#)

**contexts**(*triple=None*)

Iterate over all contexts in the graph

If triple is specified, iterate over all contexts the triple is in.

**Parameters**

**triple** ([\*Optional\*](#)[[\*Tuple\*](#)[*Node*, *Node*, *Node*]]) –

**Return type**

[\*Generator\*](#)[[\*Graph\*](#), *None*, *None*]

**default\_context:** [\*Graph\*](#)

**get\_context**(*identifier*, *quoted=False*, *base=None*)

Return a context graph for the given identifier

identifier must be a [\*URIRef\*](#) or [\*BNode\*](#).

**Parameters**

- **identifier** ([\*Union\*](#)[[\*IdentifiedNode\*](#), *str*, *None*]) –
- **quoted** (*bool*) –
- **base** ([\*Optional\*](#)[*str*]) –

**Return type**

[\*Graph\*](#)

**get\_graph**(*identifier*)

Returns the graph identified by given identifier

**Parameters**

**identifier** ([\*IdentifiedNode\*](#)) –

**Return type**

[\*Optional\*](#)[[\*Graph\*](#)]

**parse**(*source=None*, *publicID=None*, *format=None*, *location=None*, *file=None*, *data=None*, *\*\*args*)

Parse source adding the resulting triples to its own context (sub graph of this graph).

See [\*rdflib.graph.Graph.parse\(\)\*](#) for documentation on arguments.

If the source is in a format that does not support named graphs it's triples will be added to the default graph (i.e. [\*Dataset.default\\_context\*](#)).

**Returns**

The graph into which the source was parsed. In the case of n3 it returns the root context.

**Caution:** This method can access directly or indirectly requested network or file resources, for example, when parsing JSON-LD documents with `@context` directives that point to a network location.

When processing untrusted or potentially malicious documents, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib [\*Security Considerations\*](#) documentation.

*Changed in 7.0:* The `publicID` argument is no longer used as the identifier (i.e. name) of the default graph as was the case before version 7.0. In the case of sources that do not support named graphs, the `publicID` parameter will also not be used as the name for the graph that the data is loaded into, and instead the triples from sources that do not support named graphs will be loaded into the default graph (i.e. `ConjunctiveGraph.default_context`).

#### Parameters

- **source** (`Union[IO[bytes], TextIO, InputSource, str, bytes, PurePath, None]`) –
- **publicID** (`Optional[str]`) –
- **format** (`Optional[str]`) –
- **location** (`Optional[str]`) –
- **file** (`Union[BinaryIO, TextIO, None]`) –
- **data** (`Union[str, bytes, None]`) –
- **args** (`Any`) –

#### Return type

`Graph`

**quads**(*triple\_or\_quad=None*)

Iterate over all the quads in the entire conjunctive graph

#### Parameters

**triple\_or\_quad** (`Union[Tuple[Optional[Node], Optional[Node], Optional[Node]], Tuple[Optional[Node], Optional[Node], Optional[Node], Optional[Graph]], None]`) –

#### Return type

`Generator[Tuple[Node, Node, Node, Optional[Graph]], None, None]`

**remove**(*triple\_or\_quad*)

Removes a triple or quads

if a triple is given it is removed from all contexts

a quad is removed from the given context only

#### Parameters

- **self** (`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`) –
- **triple\_or\_quad** (`Union[Tuple[Node, Node, Node], Tuple[Node, Node, Node, Optional[Graph]]]`) –

#### Return type

`TypeVar(_ConjunctiveGraphT, bound= ConjunctiveGraph)`

**remove\_context**(*context*)

Removes the given context from the graph

#### Parameters

**context** (`Graph`) –

#### Return type

`None`

**triples**(*triple\_or\_quad*, *context=None*)

Iterate over all the triples in the entire conjunctive graph

For legacy reasons, this can take the context to query either as a fourth element of the quad, or as the explicit context keyword parameter. The kw param takes precedence.

**Parameters**

- **triple\_or\_quad** (Union[Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]], Tuple[Optional[Node], Union[Path, Node, None], Optional[Node], Optional[Graph]]]) –
- **context** (Optional[Graph]) –

**Return type**

Generator[Union[Tuple[Node, Node, Node], Tuple[Node, Path, Node]], None, None]

**triples\_choices**(*triple*, *context=None*)

Iterate over all the triples in the entire conjunctive graph

**Parameters**

- **triple** (Union[Tuple[List[Node], Node, Node], Tuple[Node, List[Node], Node], Tuple[Node, Node, List[Node]]]) –
- **context** (Optional[Graph]) –

**Return type**

Generator[Tuple[Node, Node, Node], None, None]

**class** `rdflib.Dataset`(*store='default'*, *default\_union=False*, *default\_graph\_base=None*)

Bases: *ConjunctiveGraph*

RDF 1.1 Dataset. Small extension to the Conjunctive Graph: - the primary term is graphs in the datasets and not contexts with quads, so there is a separate method to set/retrieve a graph in a dataset and operate with graphs - graphs cannot be identified with blank nodes - added a method to directly add a single quad

Examples of usage:

```
>>> # Create a new Dataset
>>> ds = Dataset()
>>> # simple triples goes to default graph
>>> ds.add((URIRef("http://example.org/a"),
...         URIRef("http://www.example.org/b"),
...         Literal("foo")))
<Graph identifier=... (<class 'rdflib.graph.Dataset'>)>
>>>
>>> # Create a graph in the dataset, if the graph name has already been
>>> # used, the corresponding graph will be returned
>>> # (ie, the Dataset keeps track of the constituent graphs)
>>> g = ds.graph(URIRef("http://www.example.com/gr"))
>>>
>>> # add triples to the new graph as usual
>>> g.add(
...     (URIRef("http://example.org/x"),
...      URIRef("http://example.org/y"),
...      Literal("bar")))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> # alternatively: add a quad to the dataset -> goes to the graph
```

(continues on next page)



(continued from previous page)

```

>>> ds.add(
...     (URIRef("http://example.org/x"),
...     URIRef("http://example.org/z"),
...     Literal("foo-bar"),g) )
<Graph identifier=... (<class 'rdflib.graph.Dataset'>)>
>>>
>>> # querying triples return them all regardless of the graph
>>> for t in ds.triples((None,None,None)):
...     print(t)
(rdflib.term.URIRef("http://example.org/a"),
 rdflib.term.URIRef("http://www.example.org/b"),
 rdflib.term.Literal("foo"))
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/z"),
 rdflib.term.Literal("foo-bar"))
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/y"),
 rdflib.term.Literal("bar"))
>>>
>>> # querying quads() return quads; the fourth argument can be unrestricted
>>> # (None) or restricted to a graph
>>> for q in ds.quads((None, None, None, None)):
...     print(q)
(rdflib.term.URIRef("http://example.org/a"),
 rdflib.term.URIRef("http://www.example.org/b"),
 rdflib.term.Literal("foo"),
 None)
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/y"),
 rdflib.term.Literal("bar"),
 rdflib.term.URIRef("http://www.example.com/gr"))
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/z"),
 rdflib.term.Literal("foo-bar"),
 rdflib.term.URIRef("http://www.example.com/gr"))
>>>
>>> # unrestricted looping is equivalent to iterating over the entire Dataset
>>> for q in ds:
...     print(q)
(rdflib.term.URIRef("http://example.org/a"),
 rdflib.term.URIRef("http://www.example.org/b"),
 rdflib.term.Literal("foo"),
 None)
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/y"),
 rdflib.term.Literal("bar"),
 rdflib.term.URIRef("http://www.example.com/gr"))
(rdflib.term.URIRef("http://example.org/x"),
 rdflib.term.URIRef("http://example.org/z"),
 rdflib.term.Literal("foo-bar"),
 rdflib.term.URIRef("http://www.example.com/gr"))
>>>

```

(continues on next page)

(continued from previous page)

```

>>> # restricting iteration to a graph:
>>> for q in ds.quads((None, None, None, g)):
...     print(q)
(rdfli.term.URIRef("http://example.org/x"),
 rdfli.term.URIRef("http://example.org/y"),
 rdfli.term.Literal("bar"),
 rdfli.term.URIRef("http://www.example.com/gr"))
(rdfli.term.URIRef("http://example.org/x"),
 rdfli.term.URIRef("http://example.org/z"),
 rdfli.term.Literal("foo-bar"),
 rdfli.term.URIRef("http://www.example.com/gr"))
>>> # Note that in the call above -
>>> # ds.quads((None, None, None, "http://www.example.com/gr"))
>>> # would have been accepted, too
>>>
>>> # graph names in the dataset can be queried:
>>> for c in ds.graphs():
...     print(c) # doctest:
DEFAULT
http://www.example.com/gr
>>> # A graph can be created without specifying a name; a skolemized genid
>>> # is created on the fly
>>> h = ds.graph()
>>> for c in ds.graphs():
...     print(c)
DEFAULT
https://rdflib.github.io/.well-known/genid/rdflib/N...
http://www.example.com/gr
>>> # Note that the Dataset.graphs() call returns names of empty graphs,
>>> # too. This can be restricted:
>>> for c in ds.graphs(empty=False):
...     print(c)
DEFAULT
http://www.example.com/gr
>>>
>>> # a graph can also be removed from a dataset via ds.remove_graph(g)

```

New in version 4.0.

#### Parameters

- **store** (Union[Store, str]) –
- **default\_union** (bool) –
- **default\_graph\_base** (Optional[str]) –

```
__annotations__ = {'__identifier': '_ContextIdentifierType', '__store': 'Store',
'__default_context': '_ContextType'}
```

```
__getstate__()
```

#### Return type

```
Tuple[Store, IdentifiedNode, Graph, bool]
```

```
__init__(store='default', default_union=False, default_graph_base=None)
```

**Parameters**

- **store** (`Union[Store, str]`) –
- **default\_union** (`bool`) –
- **default\_graph\_base** (`Optional[str]`) –

**\_\_iter\_\_()**

Iterates over all quads in the store

**Return type**`Generator[Tuple[Node, Node, Node, Optional[IdentifiedNode]], None, None]`**\_\_module\_\_** = 'rdflib.graph'**\_\_reduce\_\_()**

Helper for pickle.

**Return type**`Tuple[Type[Dataset], Tuple[Store, bool]]`**\_\_setstate\_\_**(*state*)**Parameters****state** (`Tuple[Store, IdentifiedNode, Graph, bool]`) –**Return type**`None`**\_\_str\_\_()**

Return str(self).

**Return type**`str`**add\_graph**(*g*)

alias of graph for consistency

**Parameters****g** (`Union[IdentifiedNode, Graph, str, None]`) –**Return type**`Graph`**contexts**(*triple=None*)

Iterate over all contexts in the graph

If triple is specified, iterate over all contexts the triple is in.

**Parameters****triple** (`Optional[Tuple[Node, Node, Node]]`) –**Return type**`Generator[Graph, None, None]`**default\_context:** `Graph`**graph**(*identifier=None, base=None*)**Parameters**

- **identifier** (`Union[IdentifiedNode, Graph, str, None]`) –

- **base** (`Optional[str]`) –

**Return type**

`Graph`

**graphs** (`triple=None`)

Iterate over all contexts in the graph

If triple is specified, iterate over all contexts the triple is in.

**Parameters**

- **triple** (`Optional[Tuple[Node, Node, Node]]`) –

**Return type**

`Generator[Graph, None, None]`

**parse** (`source=None, publicID=None, format=None, location=None, file=None, data=None, **args`)

Parse an RDF source adding the resulting triples to the Graph.

See `rdflib.graph.Graph.parse()` for documentation on arguments.

The source is specified using one of source, location, file or data.

If the source is in a format that does not support named graphs it's triples will be added to the default graph (i.e. `Dataset.default_context`).

**Caution:** This method can access directly or indirectly requested network or file resources, for example, when parsing JSON-LD documents with `@context` directives that point to a network location.

When processing untrusted or potentially malicious documents, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

*Changed in 7.0:* The `publicID` argument is no longer used as the identifier (i.e. name) of the default graph as was the case before version 7.0. In the case of sources that do not support named graphs, the `publicID` parameter will also not be used as the name for the graph that the data is loaded into, and instead the triples from sources that do not support named graphs will be loaded into the default graph (i.e. `ConjunctionGraph.default_context`).

**Parameters**

- **source** (`Union[IO[bytes], TextIO, InputSource, str, bytes, PurePath, None]`) –
- **publicID** (`Optional[str]`) –
- **format** (`Optional[str]`) –
- **location** (`Optional[str]`) –
- **file** (`Union[BinaryIO, TextIO, None]`) –
- **data** (`Union[str, bytes, None]`) –
- **args** (`Any`) –

**Return type**

`Graph`

**quads** (`quad=None`)

Iterate over all the quads in the entire conjunctive graph

**Parameters**

**quad** (Union[Tuple[Optional[Node], Optional[Node], Optional[Node]], Tuple[Optional[Node], Optional[Node], Optional[Node], Optional[Graph]], None]) –

**Return type**

Generator[Tuple[Node, Node, Node, Optional[IdentifiedNode]], None, None]

**remove\_graph**(g)

**Parameters**

- **self** (TypeVar(\_DatasetT, bound= Dataset)) –
- **g** (Union[IdentifiedNode, Graph, str, None]) –

**Return type**

TypeVar(\_DatasetT, bound= Dataset)

```
class rdflib.Graph(store='default', identifier=None, namespace_manager=None, base=None,
                  bind_namespaces='rdflib')
```

Bases: [Node](#)

An RDF Graph

The constructor accepts one argument, the “store” that will be used to store the graph data (see the “store” package for stores currently shipped with rdflib).

Stores can be context-aware or unaware. Unaware stores take up (some) less space but cannot support features that require context, such as true merging/demerging of sub-graphs and provenance.

Even if used with a context-aware store, Graph will only expose the quads which belong to the default graph. To access the rest of the data, *ConjunctiveGraph* or *Dataset* classes can be used instead.

The Graph constructor can take an identifier which identifies the Graph by name. If none is given, the graph is assigned a BNode for its identifier.

For more on named graphs, see: <http://www.w3.org/2004/03/trix/>

**Parameters**

- **store** (Union[Store, str]) –
- **identifier** (Union[IdentifiedNode, str, None]) –
- **namespace\_manager** (Optional[NamespaceManager]) –
- **base** (Optional[str]) –
- **bind\_namespaces** (Literal['core', 'rdflib', 'none']) –

**\_\_add\_\_**(other)

Set-theoretic union BNode IDs are not changed.

**Parameters**

**other** ([Graph](#)) –

**Return type**

[Graph](#)

**\_\_and\_\_**(other)

Set-theoretic intersection. BNode IDs are not changed.

**Parameters**

**other** ([Graph](#)) –

**Return type**

*Graph*

`__annotations__ = {'__identifier': '_ContextIdentifierType', '__store': 'Store'}`

`__cmp__` (*other*)

**Return type**

*int*

`__contains__` (*triple*)

Support for ‘triple in graph’ syntax

**Parameters**

**triple** (`Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]]`) –

**Return type**

*bool*

```

__dict__ = mappingproxy({'__module__': 'rdflib.graph', '__doc__': 'An RDF
Graph\n\n The constructor accepts one argument, the "store"\n that will be used to
store the graph data (see the "store"\n package for stores currently shipped with
rdflib).\n\n Stores can be context-aware or unaware. Unaware stores take up\n (some)
less space but cannot support features that require\n context, such as true
merging/demerging of sub-graphs and\n provenance.\n\n Even if used with a
context-aware store, Graph will only expose the quads which\n belong to the default
graph. To access the rest of the data, `ConjunctiveGraph` or\n `Dataset` classes can
be used instead.\n\n The Graph constructor can take an identifier which identifies
the Graph\n by name. If none is given, the graph is assigned a BNode for its\n
identifier.\n\n For more on named graphs, see: http://www.w3.org/2004/03/trix/\n ',
'__init__': <function Graph.__init__>, 'store': <property object>, 'identifier':
<property object>, 'namespace_manager': <property object>, '__repr__': <function
Graph.__repr__>, '__str__': <function Graph.__str__>, 'toPython': <function
Graph.toPython>, 'destroy': <function Graph.destroy>, 'commit': <function
Graph.commit>, 'rollback': <function Graph.rollback>, 'open': <function
Graph.open>, 'close': <function Graph.close>, 'add': <function Graph.add>, 'addN':
<function Graph.addN>, 'remove': <function Graph.remove>, 'triples': <function
Graph.triples>, '__getitem__': <function Graph.__getitem__>, '__len__': <function
Graph.__len__>, '__iter__': <function Graph.__iter__>, '__contains__': <function
Graph.__contains__>, '__hash__': <function Graph.__hash__>, '__cmp__': <function
Graph.__cmp__>, '__eq__': <function Graph.__eq__>, '__lt__': <function
Graph.__lt__>, '__le__': <function Graph.__le__>, '__gt__': <function
Graph.__gt__>, '__ge__': <function Graph.__ge__>, '__iadd__': <function
Graph.__iadd__>, '__isub__': <function Graph.__isub__>, '__add__': <function
Graph.__add__>, '__mul__': <function Graph.__mul__>, '__sub__': <function
Graph.__sub__>, '__xor__': <function Graph.__xor__>, '__or__': <function
Graph.__add__>, '__and__': <function Graph.__mul__>, 'set': <function Graph.set>,
'subjects': <function Graph.subjects>, 'predicates': <function Graph.predicates>,
'objects': <function Graph.objects>, 'subject_predicates': <function
Graph.subject_predicates>, 'subject_objects': <function Graph.subject_objects>,
'predicate_objects': <function Graph.predicate_objects>, 'triples_choices':
<function Graph.triples_choices>, 'value': <function Graph.value>, 'items':
<function Graph.items>, 'transitiveClosure': <function Graph.transitiveClosure>,
'transitive_objects': <function Graph.transitive_objects>, 'transitive_subjects':
<function Graph.transitive_subjects>, 'qname': <function Graph.qname>,
'compute_qname': <function Graph.compute_qname>, 'bind': <function Graph.bind>,
'namespaces': <function Graph.namespaces>, 'absolutize': <function
Graph.absolutize>, 'serialize': <function Graph.serialize>, 'print': <function
Graph.print>, 'parse': <function Graph.parse>, 'query': <function Graph.query>,
'update': <function Graph.update>, 'n3': <function Graph.n3>, '__reduce__':
<function Graph.__reduce__>, 'isomorphic': <function Graph.isomorphic>,
'connected': <function Graph.connected>, 'all_nodes': <function Graph.all_nodes>,
'collection': <function Graph.collection>, 'resource': <function Graph.resource>,
'_process_skolem_tuples': <function Graph._process_skolem_tuples>, 'skolemize':
<function Graph.skolemize>, 'de_skolemize': <function Graph.de_skolemize>, 'cbd':
<function Graph.cbd>, '__dict__': <attribute '__dict__' of 'Graph' objects>,
'__weakref__': <attribute '__weakref__' of 'Graph' objects>, '__annotations__':
{'__identifier': '_ContextIdentifierType', '__store': 'Store'}})

```

`__eq__(other)`

Return self==value.

Return type

`bool``__ge__(other)`

Return self&gt;=value.

**Parameters****other** (*Graph*) –**Return type**`bool``__getitem__(item)`

A graph can be “sliced” as a shortcut for the triples method. The python slice syntax is (ab)used for specifying triples. A generator over matches is returned, the returned tuples include only the parts not given

```
>>> import rdflib
>>> g = rdflib.Graph()
>>> g.add((rdflib.URIRef("urn:bob"), namespace.RDFS.label, rdflib.Literal("Bob"
↪)))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
```

```
>>> list(g[rdflib.URIRef("urn:bob")]) # all triples about bob
[(rdflib.term.URIRef('http://www.w3.org/2000/01/rdf-schema#label'), rdflib.term.
↪Literal('Bob'))]
```

```
>>> list(g[:namespace.RDFS.label]) # all label triples
[(rdflib.term.URIRef('urn:bob'), rdflib.term.Literal('Bob'))]
```

```
>>> list(g[:,rdflib.Literal("Bob")]) # all triples with bob as object
[(rdflib.term.URIRef('urn:bob'), rdflib.term.URIRef('http://www.w3.org/2000/01/
↪rdf-schema#label'))]
```

Combined with SPARQL paths, more complex queries can be written concisely:

Name of all Bobs friends:

```
g[bob : FOAF.knows/FOAF.name ]
```

Some label for Bob:

```
g[bob : DC.title|FOAF.name|RDFS.label]
```

All friends and friends of friends of Bob

```
g[bob : FOAF.knows * "+"]
```

etc.

New in version 4.0.

`__gt__(other)`

Return self&gt;value.

**Return type**`bool``__hash__()`

Return hash(self).

**Return type**`int`



**\_\_iadd\_\_**(*other*)

Add all triples in Graph *other* to Graph. BNode IDs are not changed.

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **other** (`Iterable[Tuple[Node, Node, Node]]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**\_\_init\_\_**(*store='default', identifier=None, namespace\_manager=None, base=None, bind\_namespaces='rdflib'*)

**Parameters**

- **store** (`Union[Store, str]`) –
- **identifier** (`Union[IdentifiedNode, str, None]`) –
- **namespace\_manager** (`Optional[NamespaceManager]`) –
- **base** (`Optional[str]`) –
- **bind\_namespaces** (`Literal['core', 'rdflib', 'none']`) –

**\_\_isub\_\_**(*other*)

Subtract all triples in Graph *other* from Graph. BNode IDs are not changed.

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **other** (`Iterable[Tuple[Node, Node, Node]]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**\_\_iter\_\_**()

Iterates over all triples in the store

**Return type**

`Generator[Tuple[Node, Node, Node], None, None]`

**\_\_le\_\_**(*other*)

Return self<=value.

**Parameters**

- **other** (`Graph`) –

**Return type**

`bool`

**\_\_len\_\_**()

Returns the number of triples in the graph

If context is specified then the number of triples in the context is returned instead.

**Return type**

`int`

**\_\_lt\_\_**(*other*)  
Return self<value.  
**Return type**  
*bool*

**\_\_module\_\_** = 'rdflib.graph'

**\_\_mul\_\_**(*other*)  
Set-theoretic intersection. BNode IDs are not changed.  
**Parameters**  
**other** (*Graph*) –  
**Return type**  
*Graph*

**\_\_or\_\_**(*other*)  
Set-theoretic union BNode IDs are not changed.  
**Parameters**  
**other** (*Graph*) –  
**Return type**  
*Graph*

**\_\_reduce\_\_**()  
Helper for pickle.  
**Return type**  
*Tuple*[*Type*[*Graph*], *Tuple*[*Store*, *IdentifiedNode*]]

**\_\_repr\_\_**()  
Return repr(self).  
**Return type**  
*str*

**\_\_str\_\_**()  
Return str(self).  
**Return type**  
*str*

**\_\_sub\_\_**(*other*)  
Set-theoretic difference. BNode IDs are not changed.  
**Parameters**  
**other** (*Graph*) –  
**Return type**  
*Graph*

**\_\_weakref\_\_**  
list of weak references to the object (if defined)

**\_\_xor\_\_**(*other*)  
Set-theoretic XOR. BNode IDs are not changed.  
**Parameters**  
**other** (*Graph*) –

**Return type***Graph***absolutize**(*uri*, *defrag=1*)

Turn uri into an absolute URI if it's not one already

**Parameters**

- **uri** (*str*) –
- **defrag** (*int*) –

**Return type***URIRef***add**(*triple*)

Add a triple with self as context

**Parameters**

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **triple** (*Tuple*[*Node*, *Node*, *Node*]) –

**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**addN**(*quads*)

Add a sequence of triple with context

**Parameters**

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **quads** (*Iterable*[*Tuple*[*Node*, *Node*, *Node*, *Graph*]]) –

**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**all\_nodes**()**Return type***Set*[*Node*]**bind**(*prefix*, *namespace*, *override=True*, *replace=False*)

Bind prefix to namespace

If override is True will bind namespace to given prefix even if namespace was already bound to a different prefix.

if replace, replace any existing prefix with the new namespace

for example: graph.bind("foaf", "http://xmlns.com/foaf/0.1/")

**Parameters**

- **prefix** (*Optional*[*str*]) –
- **namespace** (*Any*) –
- **override** (*bool*) –
- **replace** (*bool*) –

**Return type***None*

**cbd**(*resource*, \*, *target\_graph=None*)

Retrieves the Concise Bounded Description of a Resource from a Graph

Concise Bounded Description (CBD) is defined in [1] as:

Given a particular node (the starting node) in a particular RDF graph (the source graph), a subgraph of that particular graph, taken to comprise a concise bounded description of the resource denoted by the starting node, can be identified as follows:

1. **Include in the subgraph all statements in the source graph where the subject of the statement is the**  
starting node;
2. **Recursively, for all statements identified in the subgraph thus far having a blank node object, include**  
in the subgraph all statements in the source graph where the subject of the statement is the blank node in question and which are not already included in the subgraph.
3. **Recursively, for all statements included in the subgraph thus far, for all reifications of each statement**  
in the source graph, include the concise bounded description beginning from the `rdf:Statement` node of each reification.

This results in a subgraph where the object nodes are either URI references, literals, or blank nodes not serving as the subject of any statement in the graph.

[1] <https://www.w3.org/Submission/CBD/>

#### Parameters

- **resource** (*Node*) – a `URIRef` object, of the Resource for queried for
- **target\_graph** (*Optional[Graph]*) – Optionally, a graph to add the CBD to; otherwise, a new graph is created for the CBD

#### Return type

*Graph*

#### Returns

a `Graph`, subgraph of self if no graph was provided otherwise the provided graph

**close**(*commit\_pending\_transaction=False*)

Close the graph store

Might be necessary for stores that require closing a connection to a database or releasing some resource.

#### Parameters

- **commit\_pending\_transaction** (*bool*) –

#### Return type

*None*

**collection**(*identifier*)

Create a new `Collection` instance.

Parameters:

- **identifier**: a `URIRef` or `BNode` instance.

Example:

```
>>> graph = Graph()
>>> uri = URIRef("http://example.org/resource")
>>> collection = graph.collection(uri)
```

(continues on next page)

(continued from previous page)

```
>>> assert isinstance(collection, Collection)
>>> assert collection.uri is uri
>>> assert collection.graph is graph
>>> collection += [ Literal(1), Literal(2) ]
```

**Parameters****identifier** (*Node*) –**Return type***Collection***commit()**

Commits active transactions

**Parameters****self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**compute\_qname(uri, generate=True)****Parameters**

- **uri** (*str*) –
- **generate** (*bool*) –

**Return type***Tuple*[*str*, *URIRef*, *str*]**connected()**

Check if the Graph is connected

The Graph is considered undirectional.

Performs a search on the Graph, starting from a random node. Then iteratively goes depth-first through the triplets where the node is subject and object. Return True if all nodes have been visited and False if it cannot continue and there are still unvisited nodes left.

**Return type***bool***de\_skolemize(new\_graph=None, uriref=None)****Parameters**

- **new\_graph** (*Optional*[*Graph*]) –
- **uriref** (*Optional*[*URIRef*]) –

**Return type***Graph***destroy(configuration)**

Destroy the store identified by configuration if supported

**Parameters**

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **configuration** (*str*) –

**Return type**`TypeVar(_GraphT, bound= Graph)`**property identifier:** `IdentifiedNode`**isomorphic**(*other*)

does a very basic check if these graphs are the same If no BNodes are involved, this is accurate.

See `rdflib.compare` for a correct implementation of isomorphism checks

**Parameters****other** (`Graph`) –**Return type**`bool`**items**(*list*)

Generator over all items in the resource specified by list

list is an RDF collection.

**Parameters****list** (`Node`) –**Return type**`Generator[Node, None, None]`**n3**()

Return an n3 identifier for the Graph

**Return type**`str`**property namespace\_manager:** `NamespaceManager`

this graph's namespace-manager

**namespaces**()

Generator over all the prefix, namespace tuples

**Return type**`Generator[Tuple[str, URIRef], None, None]`**objects**(*subject=None, predicate=None, unique=False*)

A generator of (optionally unique) objects with the given subject and predicate

**Parameters**

- **subject** (`Optional[Node]`) –
- **predicate** (`Union[None, Path, Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Node, None, None]`**open**(*configuration, create=False*)

Open the graph store

Might be necessary for stores that require opening a connection to a database or acquiring some resource.

**Parameters**

- **configuration** (`str`) –

- **create** (*bool*) –

**Return type***Optional*[*int*]

**parse**(*source=None, publicID=None, format=None, location=None, file=None, data=None, \*\*args*)

Parse an RDF source adding the resulting triples to the Graph.

The source is specified using one of source, location, file or data.

**Caution:** This method can access directly or indirectly requested network or file resources, for example, when parsing JSON-LD documents with `@context` directives that point to a network location.

When processing untrusted or potentially malicious documents, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Parameters**

- **source** (*Union*[*IO*[*bytes*], *TextIO*, *InputSource*, *str*, *bytes*, *PurePath*, *None*]) – An *InputSource*, file-like object, *Path* like object, or string. In the case of a string the string is the location of the source.
- **location** (*Optional*[*str*]) – A string indicating the relative or absolute URL of the source. *Graph*’s *absolutize* method is used if a relative location is specified.
- **file** (*Union*[*BinaryIO*, *TextIO*, *None*]) – A file-like object.
- **data** (*Union*[*str*, *bytes*, *None*]) – A string containing the data to be parsed.
- **format** (*Optional*[*str*]) – Used if format can not be determined from source, e.g. file extension or Media Type. Defaults to text/turtle. Format support can be extended with plugins, but “xml”, “n3” (use for turtle), “nt” & “trix” are built in.
- **publicID** (*Optional*[*str*]) – the logical URI to use as the document base. If None specified the document location is used (at least in the case where there is a document location). This is used as the base URI when resolving relative URIs in the source document, as defined in *IETF RFC 3986*, given the source document does not define a base URI.

**Return type***Graph***Returns**

*self*, i.e. the *Graph* instance.

Examples:

```
>>> my_data = '''
... <rdf:RDF
...   xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
...   xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
... >
... <rdf:Description>
...   <rdfs:label>Example</rdfs:label>
...   <rdfs:comment>This is really just an example.</rdfs:comment>
... </rdf:Description>
```

(continues on next page)

(continued from previous page)

```

... </rdf:RDF>
... '''
>>> import os, tempfile
>>> fd, file_name = tempfile.mkstemp()
>>> f = os.fdopen(fd, "w")
>>> dummy = f.write(my_data) # Returns num bytes written
>>> f.close()

```

```

>>> g = Graph()
>>> result = g.parse(data=my_data, format="application/rdf+xml")
>>> len(g)
2

```

```

>>> g = Graph()
>>> result = g.parse(location=file_name, format="application/rdf+xml")
>>> len(g)
2

```

```

>>> g = Graph()
>>> with open(file_name, "r") as f:
...     result = g.parse(f, format="application/rdf+xml")
>>> len(g)
2

```

```

>>> os.remove(file_name)

```

```

>>> # default turtle parsing
>>> result = g.parse(data="<http://example.com/a> <http://example.com/a> <http://
↳ /example.com/a> .")
>>> len(g)
3

```

**Parameters****args** (*Any*) –**predicate\_objects** (*subject=None, unique=False*)

A generator of (optionally unique) (predicate, object) tuples for the given subject

**Parameters**

- **subject** (*Optional[Node]*) –
- **unique** (*bool*) –

**Return type***Generator[Tuple[Node, Node], None, None]***predicates** (*subject=None, object=None, unique=False*)

A generator of (optionally unique) predicates with the given subject and object

**Parameters**

- **subject** (*Optional[Node]*) –



- **object** (`Optional[Node]`) –
- **unique** (`bool`) –

**Return type**`Generator[Node, None, None]``print(format='turtle', encoding='utf-8', out=None)`**Parameters**

- **format** (`str`) –
- **encoding** (`str`) –
- **out** (`Optional[TextIO]`) –

**Return type**`None``qname(uri)`**Parameters**`uri` (`str`) –**Return type**`str`

`query(query_object, processor='sparql', result='sparql', initNs=None, initBindings=None, use_store_provided=True, **kwargs)`

Query this graph.

A type of ‘prepared queries’ can be realised by providing initial variable bindings with `initBindings`

Initial namespaces are used to resolve prefixes used in the query, if none are given, the namespaces from the graph’s namespace manager are used.

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in `SERVICE` directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Returntype**`Result`**Parameters**

- **query\_object** (`Union[str, Query]`) –
- **processor** (`Union[str, Processor]`) –
- **result** (`Union[str, Type[Result]]`) –
- **initNs** (`Optional[Mapping[str, Any]]`) –
- **initBindings** (`Optional[Mapping[str, Identifier]]`) –
- **use\_store\_provided** (`bool`) –
- **kwargs** (`Any`) –

**Return type***Result***remove(*triple*)**

Remove a triple from the graph

If the triple does not provide a context attribute, removes the triple from all contexts.

**Parameters**

- **self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –
- **triple** (*Tuple*[*Optional*[*Node*], *Optional*[*Node*], *Optional*[*Node*]]) –

**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**resource(*identifier*)**

Create a new Resource instance.

Parameters:

- **identifier**: a URIRef or BNode instance.

Example:

```
>>> graph = Graph()
>>> uri = URIRef("http://example.org/resource")
>>> resource = graph.resource(uri)
>>> assert isinstance(resource, Resource)
>>> assert resource.identifier is uri
>>> assert resource.graph is graph
```

**Parameters****identifier** (*Union*[*Node*, *str*]) –**Return type***Resource***rollback()**

Rollback active transactions

**Parameters****self** (*TypeVar*(*\_GraphT*, bound= *Graph*)) –**Return type***TypeVar*(*\_GraphT*, bound= *Graph*)**serialize(*destination=None*, *format='turtle'*, *base=None*, *encoding=None*, *\*\*args*)**

Serialize the graph.

**Parameters**

- **destination** (*Union*[*str*, *PurePath*, *IO*[*bytes*], *None*]) – The destination to serialize the graph to. This can be a path as a *str* or *PurePath* object, or it can be a *IO*[*bytes*] like object. If this parameter is not supplied the serialized graph will be returned.
- **format** (*str*) – The format that the output should be written in. This value references a *Serializer* plugin. Format support can be extended with plugins, but "xml", "n3", "turtle", "nt", "pretty-xml", "trix", "trig", "nquads", "json-ld" and "hex" are built in. Defaults to "turtle".

- **base** (`Optional[str]`) – The base IRI for formats that support it. For the turtle format this will be used as the `@base` directive.
- **encoding** (`Optional[str]`) – Encoding of output.
- **args** (`Any`) – Additional arguments to pass to the `Serializer` that will be used.
- **self** (`TypeVar(_GraphT, bound= Graph)`) –

**Returns**

The serialized graph if `destination` is `None`. The serialized graph is returned as `str` if no encoding is specified, and as `bytes` if an encoding is specified.

**Return type**

`bytes` if `destination` is `None` and `encoding` is not `None`.

**Return type**

`str` if `destination` is `None` and `encoding` is `None`.

**Returns**

`self` (i.e. the `Graph` instance) if `destination` is not `None`.

**Return type**

`Graph` if `destination` is not `None`.

**set(triple)**

Convenience method to update the value of object

Remove any existing triples for subject and predicate before adding (subject, predicate, object).

**Parameters**

- **self** (`TypeVar(_GraphT, bound= Graph)`) –
- **triple** (`Tuple[Node, Node, Node]`) –

**Return type**

`TypeVar(_GraphT, bound= Graph)`

**skolemize(new\_graph=None, bnode=None, authority=None, basepath=None)****Parameters**

- **new\_graph** (`Optional[Graph]`) –
- **bnode** (`Optional[BNode]`) –
- **authority** (`Optional[str]`) –
- **basepath** (`Optional[str]`) –

**Return type**

`Graph`

**property store: Store****subject\_objects(predicate=None, unique=False)**

A generator of (optionally unique) (subject, object) tuples for the given predicate

**Parameters**

- **predicate** (`Union[None, Path, Node]`) –
- **unique** (`bool`) –

**Return type**

`Generator[Tuple[Node, Node], None, None]`

**subject\_predicates**(*object=None, unique=False*)

A generator of (optionally unique) (subject, predicate) tuples for the given object

**Parameters**

- **object** (Optional[Node]) –
- **unique** (bool) –

**Return type**

Generator[Tuple[Node, Node], None, None]

**subjects**(*predicate=None, object=None, unique=False*)

A generator of (optionally unique) subjects with the given predicate and object

**Parameters**

- **predicate** (Union[None, Path, Node]) –
- **object** (Optional[Node]) –
- **unique** (bool) –

**Return type**

Generator[Node, None, None]

**toPython()**

**Parameters**

**self** (TypeVar(\_GraphT, bound= Graph)) –

**Return type**

TypeVar(\_GraphT, bound= Graph)

**transitiveClosure**(*func, arg, seen=None*)

Generates transitive closure of a user-defined function against the graph

```
>>> from rdflib.collection import Collection
>>> g=Graph()
>>> a=BNode("foo")
>>> b=BNode("bar")
>>> c=BNode("baz")
>>> g.add((a,RDF.first,RDF.type))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((a,RDF.rest,b))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((b,RDF.first,namespace.RDFS.label))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((b,RDF.rest,c))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((c,RDF.first,namespace.RDFS.comment))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> g.add((c,RDF.rest,RDF.nil))
<Graph identifier=... (<class 'rdflib.graph.Graph'>)>
>>> def topList(node,g):
...     for s in g.subjects(RDF.rest, node):
...         yield s
>>> def reverseList(node,g):
...     for f in g.objects(node, RDF.first):
```

(continues on next page)

(continued from previous page)

```
...     print(f)
...     for s in g.subjects(RDF.rest, node):
...         yield s
```

```
>>> [rt for rt in g.transitiveClosure(
...     topList, RDF.nil)]
[rdflib.term.BNode('baz'),
 rdflib.term.BNode('bar'),
 rdflib.term.BNode('foo')]
```

```
>>> [rt for rt in g.transitiveClosure(
...     reverseList, RDF.nil)]
http://www.w3.org/2000/01/rdf-schema#comment
http://www.w3.org/2000/01/rdf-schema#label
http://www.w3.org/1999/02/22-rdf-syntax-ns#type
[rdflib.term.BNode('baz'),
 rdflib.term.BNode('bar'),
 rdflib.term.BNode('foo')]
```

**Parameters**

- **func** (Callable[[TypeVar(\_TCArgT), *Graph*], Iterable[TypeVar(\_TCArgT)]] –
- **arg** (TypeVar(\_TCArgT)) –
- **seen** (Optional[Dict[TypeVar(\_TCArgT), int]]) –

**transitive\_objects**(*subject*, *predicate*, *remember=None*)

Transitively generate objects for the *predicate* relationship

Generated objects belong to the depth first transitive closure of the *predicate* relationship starting at *subject*.

**Parameters**

- **subject** (Optional[*Node*]) –
- **predicate** (Optional[*Node*]) –
- **remember** (Optional[Dict[Optional[*Node*], int]]) –

**Return type**

Generator[Optional[*Node*], None, None]

**transitive\_subjects**(*predicate*, *object*, *remember=None*)

Transitively generate subjects for the *predicate* relationship

Generated subjects belong to the depth first transitive closure of the *predicate* relationship starting at *object*.

**Parameters**

- **predicate** (Optional[*Node*]) –
- **object** (Optional[*Node*]) –
- **remember** (Optional[Dict[Optional[*Node*], int]]) –

**Return type**

`Generator[Optional[Node], None, None]`

**triples**(*triple*)

Generator over the triple store

Returns triples that match the given triple pattern. If triple pattern does not provide a context, all contexts will be searched.

**Parameters**

**triple** (`Tuple[Optional[Node], Union[Path, Node, None], Optional[Node]]`) –

**Return type**

`Generator[Union[Tuple[Node, Node, Node], Tuple[Node, Path, Node]], None, None]`

**triples\_choices**(*triple*, *context=None*)

**Parameters**

- **triple** (`Union[Tuple[List[Node], Node, Node], Tuple[Node, List[Node], Node], Tuple[Node, Node, List[Node]]]`) –
- **context** (`Optional[Graph]`) –

**Return type**

`Generator[Tuple[Node, Node, Node], None, None]`

**update**(*update\_object*, *processor='sparql'*, *initNs=None*, *initBindings=None*, *use\_store\_provided=True*, *\*\*kwargs*)

Update this graph with the given update query.

**Caution:** This method can access indirectly requested network endpoints, for example, query processing will attempt to access network endpoints specified in SERVICE directives.

When processing untrusted or potentially malicious queries, measures should be taken to restrict network and file access.

For information on available security measures, see the RDFLib *Security Considerations* documentation.

**Parameters**

- **update\_object** (`Union[Update, str]`) –
- **processor** (`Union[str, UpdateProcessor]`) –
- **initNs** (`Optional[Mapping[str, Any]]`) –
- **initBindings** (`Optional[Mapping[str, Identifier]]`) –
- **use\_store\_provided** (`bool`) –
- **kwargs** (`Any`) –

**Return type**

`None`

**value**(*subject=None*, *predicate=rdflib.term.URIRef('http://www.w3.org/1999/02/22-rdf-syntax-ns#value')*, *object=None*, *default=None*, *any=True*)

Get a value for a pair of two criteria

Exactly one of subject, predicate, object must be None. Useful if one knows that there may only be one value.

It is one of those situations that occur a lot, hence this ‘macro’ like utility

Parameters: subject, predicate, object – exactly one must be None default – value to be returned if no values found any – if True, return any value in the case there is more than one, else, raise UniquenessError

#### Parameters

- **subject** (Optional[Node]) –
- **predicate** (Optional[Node]) –
- **object** (Optional[Node]) –
- **default** (Optional[Node]) –
- **any** (bool) –

#### Return type

Optional[Node]

```
class rdflib IdentifiedNode(value: str)
```

Bases: *Identifier*

An abstract class, primarily defined to identify Nodes that are not Literals.

The name “Identified Node” is not explicitly defined in the RDF specification, but can be drawn from this section: <https://www.w3.org/TR/rdf-concepts/#section-URI-Vocabulary>

```
__annotations__ = {}
```

```
__dict__ = mappingproxy({'__module__': 'rdflib.term', '__doc__': '\n An abstract
class, primarily defined to identify Nodes that are not Literals.\n\n The name
"Identified Node" is not explicitly defined in the RDF specification, but can be
drawn from this section:
https://www.w3.org/TR/rdf-concepts/#section-URI-Vocabulary\n ', '__getnewargs__':
<function IdentifiedNode.__getnewargs__>, 'toPython': <function
IdentifiedNode.toPython>, '__dict__': <attribute '__dict__' of 'IdentifiedNode'
objects>, '__weakref__': <attribute '__weakref__' of 'IdentifiedNode' objects>,
'__annotations__': {}})
```

```
__getnewargs__()
```

#### Return type

Tuple[str]

```
__module__ = 'rdflib.term'
```

```
__weakref__
```

list of weak references to the object (if defined)

```
toPython()
```

#### Return type

str

```
class rdflib Literal(lexical_or_value: Any, lang: str | None = None, datatype: str | None = None, normalize:
bool | None = None)
```

Bases: *Identifier*

RDF 1.1’s Literals Section: <http://www.w3.org/TR/rdf-concepts/#section-Graph-Literal>

Literals are used for values such as strings, numbers, and dates.

A literal in an RDF graph consists of two or three elements:

- a lexical form, being a Unicode string, which SHOULD be in Normal Form C
- a datatype IRI, being an IRI identifying a datatype that determines how the lexical form maps to a literal value, and
- if and only if the datatype IRI is `http://www.w3.org/1999/02/22-rdf-syntax-ns#langString`, a non-empty language tag. The language tag MUST be well-formed according to section 2.2.9 of [Tags for identifying languages](#).

A literal is a language-tagged string if the third element is present. Lexical representations of language tags MAY be converted to lower case. The value space of language tags is always in lower case.

—

For valid XSD datatypes, the lexical form is optionally normalized at construction time. Default behaviour is set by `rdflib.NORMALIZE_LITERALS` and can be overridden by the `normalize` parameter to `__new__`

Equality and hashing of Literals are done based on the lexical form, i.e.:

```
>>> from rdflib.namespace import XSD
```

```
>>> Literal('01') != Literal('1') # clear - strings differ
True
```

but with data-type they get normalized:

```
>>> Literal('01', datatype=XSD.integer) != Literal('1', datatype=XSD.integer)
False
```

unless disabled:

```
>>> Literal('01', datatype=XSD.integer, normalize=False) != Literal('1',
↳datatype=XSD.integer)
True
```

Value based comparison is possible:

```
>>> Literal('01', datatype=XSD.integer).eq(Literal('1', datatype=XSD.float))
True
```

The `eq` method also provides limited support for basic python types:

```
>>> Literal(1).eq(1) # fine - int compatible with xsd:integer
True
>>> Literal('a').eq('b') # fine - str compatible with plain-lit
False
>>> Literal('a', datatype=XSD.string).eq('a') # fine - str compatible with
↳xsd:string
True
>>> Literal('a').eq(1) # not fine, int incompatible with plain-lit
NotImplemented
```

Greater-than/less-than ordering comparisons are also done in value space, when compatible datatypes are used. Incompatible datatypes are ordered by DT, or by lang-tag. For other nodes the ordering is `None < BNode < URIRef < Literal`



Any comparison with non-`rdflib` Node are “NotImplemented” In PY3 this is an error.

```
>>> from rdflib import Literal, XSD
>>> lit2006 = Literal('2006-01-01',datatype=XSD.date)
>>> lit2006.toPython()
datetime.date(2006, 1, 1)
>>> lit2006 < Literal('2007-01-01',datatype=XSD.date)
True
>>> Literal(datetime.utcnow()).datatype
rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#dateTime')
>>> Literal(1) > Literal(2) # by value
False
>>> Literal(1) > Literal(2.0) # by value
False
>>> Literal('1') > Literal(1) # by DT
True
>>> Literal('1') < Literal('1') # by lexical form
False
>>> Literal('a', lang='en') > Literal('a', lang='fr') # by lang-tag
False
>>> Literal(1) > URIRef('foo') # by node-type
True
```

The `>` `<` operators will eat this `NotImplemented` and throw a `TypeError` (py3k):

```
>>> Literal(1).__gt__(2.0)
NotImplemented
```

`__abs__()`

**Return type**  
*Literal*

```
>>> abs(Literal(-1))
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
```

```
>>> from rdflib.namespace import XSD
>>> abs(Literal("-1", datatype=XSD.integer))
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
```

```
>>> abs(Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: Not a number; rdflib.term.Literal('1')
```

`__add__(val)`

```
>>> from rdflib.namespace import XSD
>>> Literal(1) + 1
rdflib.term.Literal('2', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
```

(continues on next page)

(continued from previous page)

```
>>> Literal("1") + "1"
rdflib.term.Literal('11')
```

```
# Handling dateTime/date/time based operations in Literals >>> a = Literal('2006-01-01T20:50:00',
datatype=XSD.dateTime) >>> b = Literal('P31D', datatype=XSD.duration) >>> (a + b)
rdflib.term.Literal('2006-02-01T20:50:00', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
XMLSchema#dateTime')) >>> from rdflib.namespace import XSD >>> a = Literal('2006-07-
01T20:52:00', datatype=XSD.dateTime) >>> b = Literal('P122DT15H58M', datatype=XSD.duration)
>>> (a + b) rdflib.term.Literal('2006-11-01T12:50:00', datatype=rdflib.term.URIRef('http:
//www.w3.org/2001/XMLSchema#dateTime'))
```

#### Parameters

**val** (*Any*) –

#### Return type

*Literal*

```
__annotations__ = {'_datatype': typing.Optional[rdflib.term.URIRef], '_ill_typed':
typing.Optional[bool], '_language': typing.Optional[str], '_value': typing.Any}
```

**\_\_bool\_\_**()

Is the Literal “True” This is used for if statements, bool(literal), etc.

#### Return type

*bool*

**\_\_eq\_\_**(*other*)

Literals are only equal to other literals.

“Two literals are equal if and only if all of the following hold: \* The strings of the two lexical forms compare equal, character by character. \* Either both or neither have language tags. \* The language tags, if any, compare equal. \* Either both or neither have datatype URIs. \* The two datatype URIs, if any, compare equal, character by character.” – 6.5.1 Literal Equality (RDF: Concepts and Abstract Syntax)

```
>>> Literal("1", datatype=URIRef("foo")) == Literal("1", datatype=URIRef("foo"))
True
>>> Literal("1", datatype=URIRef("foo")) == Literal("1", datatype=URIRef("foo2
↪"))
False
```

```
>>> Literal("1", datatype=URIRef("foo")) == Literal("2", datatype=URIRef("foo"))
False
>>> Literal("1", datatype=URIRef("foo")) == "asdf"
False
>>> from rdflib import XSD
>>> Literal('2007-01-01', datatype=XSD.date) == Literal('2007-01-01', ↵
↪datatype=XSD.date)
True
>>> Literal('2007-01-01', datatype=XSD.date) == date(2007, 1, 1)
False
>>> Literal("one", lang="en") == Literal("one", lang="en")
True
>>> Literal("hast", lang='en') == Literal("hast", lang='de')
False
>>> Literal("1", datatype=XSD.integer) == Literal(1)
```

(continues on next page)

(continued from previous page)

```
True
>>> Literal("1", datatype=XSD.integer) == Literal("01", datatype=XSD.integer)
True
```

**Parameters****other** (*Any*) –**Return type***bool***\_\_ge\_\_**(*other*)

Return self&gt;=value.

**Parameters****other** (*Any*) –**Return type***bool***\_\_getstate\_\_**()**Return type***Tuple*[*None*, *Dict*[*str*, *Optional*[*str*]]]**\_\_gt\_\_**(*other*)

This implements ordering for Literals, the other comparison methods delegate here

This tries to implement this: <http://www.w3.org/TR/sparql11-query/#modOrderBy>

In short, Literals with compatible data-types are ordered in value space, i.e. &gt;&gt;&gt; from rdflib import XSD

```
>>> Literal(1) > Literal(2) # int/int
False
>>> Literal(2.0) > Literal(1) # double/int
True
>>> from decimal import Decimal
>>> Literal(Decimal("3.3")) > Literal(2.0) # decimal/double
True
>>> Literal(Decimal("3.3")) < Literal(4.0) # decimal/double
True
>>> Literal('b') > Literal('a') # plain lit/plain lit
True
>>> Literal('b') > Literal('a', datatype=XSD.string) # plain lit/xsd:str
True
```

Incompatible datatype mismatches ordered by DT

```
>>> Literal(1) > Literal("2") # int>string
False
```

Langtagged literals by lang tag &gt;&gt;&gt; Literal("a", lang="en") &gt; Literal("a", lang="fr") False

**Parameters****other** (*Any*) –**Return type***bool*

`__hash__()`

```
>>> from rdflib.namespace import XSD
>>> a = {Literal('1', datatype=XSD.integer): 'one'}
:rtype: :py:class:`int`
```

```
>>> Literal('1', datatype=XSD.double) in a
False
```

“Called for the key object for dictionary operations, and by the built-in function hash(). Should return a 32-bit integer usable as a hash value for dictionary operations. The only required property is that objects which compare equal have the same hash value; it is advised to somehow mix together (e.g., using exclusive or) the hash values for the components of the object that also play a part in comparison of objects.” – 3.4.1 Basic customization (Python)

“Two literals are equal if and only if all of the following hold: \* The strings of the two lexical forms compare equal, character by character. \* Either both or neither have language tags. \* The language tags, if any, compare equal. \* Either both or neither have datatype URIs. \* The two datatype URIs, if any, compare equal, character by character.” – 6.5.1 Literal Equality (RDF: Concepts and Abstract Syntax)

`__invert__()`

**Return type**

*Literal*

```
>>> ~(Literal(-1))
rdflib.term.Literal('0', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
```

```
>>> from rdflib.namespace import XSD
>>> ~(Literal("-1", datatype=XSD.integer))
rdflib.term.Literal('0', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))
```

Not working:

```
>>> ~(Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: Not a number; rdflib.term.Literal('1')
```

`__le__(other)`

```
>>> from rdflib.namespace import XSD
>>> Literal('2007-01-01T10:00:00', datatype=XSD.dateTime
...       ) <= Literal('2007-01-01T10:00:00', datatype=XSD.dateTime)
True
```

**Parameters**

**other** (*Any*) –

**Return type**

*bool*

`__lt__(other)`

Return self<value.

**Parameters**

**other** (*Any*) –

**Return type**

*bool*

`__module__ = 'rdflib.term'`

`__neg__()`

```
>>> (- Literal(1))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
>>> (- Literal(10.5))
rdflib.term.Literal('-10.5', datatype=rdflib.term.URIRef('http://www.w3.org/
↳2001/XMLSchema#double'))
>>> from rdflib.namespace import XSD
:rtype: :py:class:`~rdflib.term.Literal`
```

```
>>> (- Literal("1", datatype=XSD.integer))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
```

```
>>> (- Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: Not a number; rdflib.term.Literal('1')
>>>
```

**static** `__new__(cls, lexical_or_value, lang=None, datatype=None, normalize=None)`

**Parameters**

- **lexical\_or\_value** (*Any*) –
- **lang** (*Optional[str]*) –
- **datatype** (*Optional[str]*) –
- **normalize** (*Optional[bool]*) –

**Return type**

*Literal*

`__pos__()`

```
>>> (+ Literal(1))
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
>>> (+ Literal(-1))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
>>> from rdflib.namespace import XSD
:rtype: :py:class:`~rdflib.term.Literal`
```

```
>>> (+ Literal("-1", datatype=XSD.integer))
rdflib.term.Literal('-1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
```

```
>>> (+ Literal("1"))
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: Not a number; rdflib.term.Literal('1')
```

**\_\_reduce\_\_()**

Helper for pickle.

**Return type**

`Tuple[Type[Literal], Tuple[str, Optional[str], Optional[str]]]`

**\_\_repr\_\_()**

Return repr(self).

**Return type**

`str`

**\_\_setstate\_\_(arg)**

**Parameters**

**arg** (`Tuple[Any, Dict[str, Any]]`) –

**Return type**

`None`

**\_\_slots\_\_** = ('\_language', '\_datatype', '\_value', '\_ill\_typed')

**\_\_sub\_\_(val)**

```
>>> from rdflib.namespace import XSD
>>> Literal(2) - 1
rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#integer'))
>>> Literal(1.1) - 1.0
rdflib.term.Literal('0.100000000000000009', datatype=rdflib.term.URIRef('http://
↳www.w3.org/2001/XMLSchema#double'))
>>> Literal(1.1) - 1
rdflib.term.Literal('0.1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/
↳XMLSchema#decimal'))
>>> Literal(1.1, datatype=XSD.float) - Literal(1.0, datatype=XSD.float)
rdflib.term.Literal('0.100000000000000009', datatype=rdflib.term.URIRef('http://
↳www.w3.org/2001/XMLSchema#float'))
>>> Literal("1.1") - 1.0
Traceback (most recent call last):
...
TypeError: Not a number; rdflib.term.Literal('1.1')
>>> Literal(1.1, datatype=XSD.integer) - Literal(1.0, datatype=XSD.integer)
rdflib.term.Literal('0.100000000000000009', datatype=rdflib.term.URIRef('http://
↳www.w3.org/2001/XMLSchema#integer'))
```

```
# Handling dateTime/date/time based operations in Literals >>> a = Literal('2006-01-01T20:50:00',
datatype=XSD.dateTime) >>> b = Literal('2006-02-01T20:50:00', datatype=XSD.dateTime) >>> (b -
```

```
a) rdflib.term.Literal('P31D', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#duration')) >>> from rdflib.namespace import XSD >>> a = Literal('2006-07-01T20:52:00', datatype=XSD.dateTime) >>> b = Literal('2006-11-01T12:50:00', datatype=XSD.dateTime) >>> (a - b) rdflib.term.Literal('-P122DT15H58M', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#duration')) >>> (b - a) rdflib.term.Literal('P122DT15H58M', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#duration'))
```

**Parameters****val** (*Any*) –**Return type***Literal***property datatype:** *URIRef* | *None***eq**(*other*)

Compare the value of this literal with something else

Either, with the value of another literal comparisons are then done in literal “value space”, and according to the rules of XSD subtype-substitution/type-promotion

OR, with a python object:

basestring objects can be compared with plain-literals, or those with datatype xsd:string

bool objects with xsd:boolean

a int, long or float with numeric xsd types

isodate date,time,datetime objects with xsd:date,xsd:time or xsd:datetime

Any other operations returns NotImplemented

**Parameters****other** (*Any*) –**Return type***bool***property ill\_typed:** *bool* | *None*

For *recognized datatype IRIs*, this value will be *True* if the literal is ill formed, otherwise it will be *False*. *Literal.value* (i.e. the *literal value*) should always be defined if this property is *False*, but should not be considered reliable if this property is *True*.

If the literal’s datatype is *None* or not in the set of *recognized datatype IRIs* this value will be *None*.

**property language:** *str* | *None***n3**(*namespace\_manager=None*)

Returns a representation in the N3 format.

Examples:

```
>>> Literal("foo").n3()
'"foo"'
```

Strings with newlines or triple-quotes:

```
>>> Literal("foo\nbar").n3()
'"""foo\nbar"""'
```

(continues on next page)

(continued from previous page)

```
>>> Literal("\\"").n3()
'\\'
>>> Literal('\\\\').n3()
'\\'
```

Language:

```
>>> Literal("hello", lang="en").n3()
'"hello"@en'
```

Datatypes:

```
>>> Literal(1).n3()
'"1"^^<http://www.w3.org/2001/XMLSchema#integer>'

>>> Literal(1.0).n3()
'"1.0"^^<http://www.w3.org/2001/XMLSchema#double>'

>>> Literal(True).n3()
'"true"^^<http://www.w3.org/2001/XMLSchema#boolean>'
```

Datatype and language isn't allowed (datatype takes precedence):

```
>>> Literal(1, lang="en").n3()
'1'^'^<http://www.w3.org/2001/XMLSchema#integer>'
```

Custom datatype:

```
>>> footype = URIRef("http://example.org/ns#foo")
>>> Literal("1", datatype=footype).n3()
'"1"^^<http://example.org/ns#foo>'
```

Passing a namespace-manager will use it to abbreviate datatype URIs:

```
>>> from rdflib import Graph
>>> Literal(1).n3(Graph().namespace_manager)
'"1"^^xsd:integer'
```

## Parameters

**namespace\_manager** (Optional[*NamespaceManager*]) –

### Return type

str

**neq**(*other*)

A “semantic”/interpreted not equal function, by default, same as `__ne__`

## Parameters

**other (Any) –**

### Return type

bool



**normalize()**

Returns a new literal with a normalised lexical representation of this literal >>> from rdflib import XSD >>> Literal("01", datatype=XSD.integer, normalize=False).normalize() rdflib.term.Literal('1', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))

Illegal lexical forms for the datatype given are simply passed on >>> Literal("a", datatype=XSD.integer, normalize=False) rdflib.term.Literal('a', datatype=rdflib.term.URIRef('http://www.w3.org/2001/XMLSchema#integer'))

**Return type**  
*Literal*

**toPython()**

Returns an appropriate python datatype derived from this RDF Literal

**Return type**  
*Any*

**property value:** *Any*

**rdflib.NORMALIZE\_LITERALS = True**

If True - Literals lexical forms are normalized when created. I.e. the lexical forms is parsed according to datatype, then the stored lexical form is the re-serialized value that was parsed.

Illegal values for a datatype are simply kept. The normalized keyword for Literal.\_\_new\_\_ can override this.

For example:

```
>>> from rdflib import Literal, XSD
>>> Literal("01", datatype=XSD.int)
rdflib.term.Literal("1", datatype=rdflib.term.URIRef("http://www.w3.org/2001/
↳XMLSchema#integer"))
```

This flag may be changed at any time, but will only affect literals created after that time, previously created literals will remain (un)normalized.

**class rdflib.Namespace(value: str | bytes)**

Bases: *str*

Utility class for quickly generating URIRefs with a common prefix

```
>>> from rdflib.namespace import Namespace
>>> n = Namespace("http://example.org/")
>>> n.Person # as attribute
rdflib.term.URIRef('http://example.org/Person')
>>> n['first-name'] # as item - for things that are not valid python identifiers
rdflib.term.URIRef('http://example.org/first-name')
>>> n.Person in n
True
>>> n2 = Namespace("http://example2.org/")
>>> n.Person in n2
False
```

**\_\_contains\_\_(ref)**

Allows to check if a URI is within (starts with) this Namespace.

```

>>> from rdflib import URIRef
>>> namespace = Namespace('http://example.org/')
>>> uri = URIRef('http://example.org/foo')
>>> uri in namespace
True
>>> person_class = namespace['Person']
>>> person_class in namespace
True
>>> obj = URIRef('http://not.example.org/bar')
>>> obj in namespace
False

```

**Parameters****ref** (*str*) –**Return type***bool*

```

__dict__ = mappingproxy({'__module__': 'rdflib.namespace', '__doc__': '\n Utility
class for quickly generating URIRefs with a common prefix\n\n >>> from
rdflib.namespace import Namespace\n >>> n = Namespace("http://example.org/")\n >>>
n.Person # as attribute\n rdflib.term.URIRef(\'http://example.org/Person\')\n >>>
n[\'first-name\'] # as item - for things that are not valid python identifiers\n
rdflib.term.URIRef(\'http://example.org/first-name\')\n >>> n.Person in n\n True\n
>>> n2 = Namespace("http://example2.org/")\n >>> n.Person in n2\n False\n ',
'__new__': <staticmethod object>, 'title': <property object>, 'term': <function
Namespace.term>, '__getitem__': <function Namespace.__getitem__>, '__getattr__':
<function Namespace.__getattr__>, '__repr__': <function Namespace.__repr__>,
'__contains__': <function Namespace.__contains__>, '__dict__': <attribute
'__dict__' of 'Namespace' objects>, '__weakref__': <attribute '__weakref__' of
'Namespace' objects>, '__annotations__': {}})

```

**\_\_getattr\_\_** (*name*)**Parameters****name** (*str*) –**Return type***URIRef***\_\_getitem\_\_** (*key*)

Return self[key].

**Parameters****key** (*str*) –**Return type***URIRef***\_\_module\_\_** = 'rdflib.namespace'**static** **\_\_new\_\_** (*cls, value*)**Parameters****value** (*Union[str, bytes]*) –

**Return type***Namespace***\_\_repr\_\_()**

Return repr(self).

**Return type***str***\_\_weakref\_\_**

list of weak references to the object (if defined)

**term(name)****Parameters****name** (*str*) –**Return type***URIRef***property title:** *URIRef*

Return a version of the string where each word is titlecased.

More specifically, words start with uppercased characters and all remaining cased characters have lower case.

**class** rdflib.URIRef(*value: str, base: str | None = None*)Bases: *IdentifiedNode*RDF 1.1's IRI Section <https://www.w3.org/TR/rdf11-concepts/#section-IRIs>


---

**Note:** Documentation on RDF outside of RDFLib uses the term IRI or URI whereas this class is called URIRef. This is because it was made when the first version of the RDF specification was current, and it used the term *URIRef*, see [RDF 1.0 URIRef](#)

---

An IRI (Internationalized Resource Identifier) within an RDF graph is a Unicode string that conforms to the syntax defined in RFC 3987.

IRIs in the RDF abstract syntax **MUST** be absolute, and **MAY** contain a fragment identifier.

IRIs are a generalization of URIs [RFC3986] that permits a wider range of Unicode characters.

**\_\_add\_\_(other)**

Return self+value.

**Return type***URIRef*

```
__annotations__ = {'__invert__': typing.Callable[[ForwardRef('URIRef')],
ForwardRef('InvPath')], '__neg__': typing.Callable[[ForwardRef('URIRef')],
ForwardRef('NegatedPath')], '__or__': typing.Callable[[ForwardRef('URIRef'),
typing.Union[ForwardRef('URIRef'), ForwardRef('Path')]],
ForwardRef('AlternativePath')], '__truediv__':
typing.Callable[[ForwardRef('URIRef'), typing.Union[ForwardRef('URIRef'),
ForwardRef('Path')]], ForwardRef('SequencePath')]]}
```

**\_\_invert\_\_()**

inverse path

**Parameters**

**p** (`Union[URIRef, Path]`) –

**Return type**

`InvPath`

`__mod__` (*other*)

Return self%value.

**Return type**

`URIRef`

`__module__` = 'rdflib.term'

`__mul__` (*mul*)

cardinality path

**Parameters**

- **p** (`Union[URIRef, Path]`) –
- **mul** (`Literal['*', '+', '?']`) –

**Return type**

`MulPath`

`__neg__` ()

negated path

**Parameters**

**p** (`Union[URIRef, AlternativePath, InvPath]`) –

**Return type**

`NegatedPath`

**static** `__new__` (*cls*, *value*, *base=None*)

**Parameters**

- **value** (`str`) –
- **base** (`Optional[str]`) –

**Return type**

`URIRef`

`__or__` (*other*)

alternative path

**Parameters**

- **self** (`Union[URIRef, Path]`) –
- **other** (`Union[URIRef, Path]`) –

`__radd__` (*other*)

**Return type**

`URIRef`

`__reduce__` ()

Helper for pickle.

**Return type**

`Tuple[Type[URIRef], Tuple[str]]`

**\_\_repr\_\_()**

Return repr(self).

**Return type**

*str*

**\_\_slots\_\_ = ()**

**\_\_truediv\_\_**(*other*)

sequence path

**Parameters**

- **self** (*Union*[*URIRef*, *Path*]) –
- **other** (*Union*[*URIRef*, *Path*]) –

**de\_skolemize()**

Create a Blank Node from a skolem URI, in accordance with <http://www.w3.org/TR/rdf11-concepts/#section-skolemization>. This function accepts only rdflib type skolemization, to provide a round-tripping within the system. :rtype: *BNode*

New in version 4.0.

**defrag()**

**Return type**

*URIRef*

**property fragment:** *str*

Return the URL Fragment

```
>>> URIRef("http://example.com/some/path/#some-fragment").fragment
'some-fragment'
>>> URIRef("http://example.com/some/path/").fragment
''
```

**n3**(*namespace\_manager=None*)

This will do a limited check for valid URIs, essentially just making sure that the string includes no illegal characters (<, >, ", {, }, |, \, `, ^)

**Parameters**

**namespace\_manager** (*Optional*[*NamespaceManager*]) – if not None, will be used to make up a prefixed name

**Return type**

*str*

**class rdflib.Variable**(*value: str*)

Bases: *Identifier*

A Variable - this is used for querying, or in Formula aware graphs, where Variables can be stored

**\_\_annotations\_\_** = {}

**\_\_module\_\_** = 'rdflib.term'

**static \_\_new\_\_**(*cls, value*)

**Parameters**

**value** (*str*) –

**Return type**

*Variable*

`__reduce__()`

Helper for pickle.

**Return type**

`Tuple[Type[Variable], Tuple[str]]`

`__repr__()`

Return repr(self).

**Return type**

`str`

`__slots__ = ()`

`n3(namespace_manager=None)`

**Parameters**

`namespace_manager` (`Optional[NamespaceManager]`) –

**Return type**

`str`

`toPython()`

**Return type**

`str`

## 3.2 Plugins

Many parts of RDFLib are extensible with plugins, see [setuptools' 'Creating and discovering plugins'](#). These pages list the plugins included in RDFLib core.

### 3.2.1 Plugin parsers

These serializers are available in default RDFLib, you can use them by passing the name to graph's `parse()` method:

```
graph.parse(my_url, format='n3')
```

The `html` parser will auto-detect RDFa, HTurtle or Microdata.

It is also possible to pass a mime-type for the `format` parameter:

```
graph.parse(my_url, format='application/rdf+xml')
```

If you are not sure what format your file will be, you can use `rdflib.util.guess_format()` which will guess based on the file extension.

Name	Class
json-ld	<i>JsonLDParser</i>
hext	<i>HextuplesParser</i>
n3	<i>N3Parser</i>
nquads	<i>NQuadsParser</i>
nt	<i>NTParser</i>
trix	<i>TriXParser</i>
turtle	<i>TurtleParser</i>
xml	<i>RDFXMLParser</i>

### Multi-graph IDs

Note that for correct parsing of multi-graph data, e.g. Trig, HexT, etc., into a `ConjunctiveGraph` or a `Dataset`, as opposed to a context-unaware `Graph`, you will need to set the `publicID` of the `ConjunctiveGraph` or a `Dataset` to the identifier of the `default_context` (default graph), for example:

```
d = Dataset()
d.parse(
    data="""" ... """,
    format="trig",
    publicID=d.default_context.identifier
)
```

(from the file `tests/test_serializer_hext.py`)

### 3.2.2 Plugin serializers

These serializers are available in default RDFLib, you can use them by passing the name to a graph's `serialize()` method:

```
print graph.serialize(format='n3')
```

It is also possible to pass a mime-type for the `format` parameter:

```
graph.serialize(my_url, format='application/rdf+xml')
```

Name	Class
json-ld	<i>JsonLDSerializer</i>
n3	<i>N3Serializer</i>
nquads	<i>NQuadsSerializer</i>
nt	<i>NTSerializer</i>
hext	<i>HextuplesSerializer</i>
pretty-xml	<i>PrettyXMLSerializer</i>
trig	<i>TrigSerializer</i>
trix	<i>TriXSerializer</i>
turtle	<i>TurtleSerializer</i>
longturtle	<i>LongTurtleSerializer</i>
xml	<i>XMLSerializer</i>

## JSON-LD

JSON-LD - 'json-ld' - has been incorporated into RDFLib since v6.0.0.

## HexTuples

The HexTuples Serializer - 'hext' - uses the HexTuples format defined at <https://github.com/ontola/hextuples>.

For serialization of non-context-aware data sources, e.g. a single `Graph`, the 'graph' field (6th variable in the Hextuple) will be an empty string.

For context-aware (multi-graph) serialization, the 'graph' field of the default graph will be an empty string and the values for other graphs will be Blank Node IDs or IRIs.

## Longturtle

Longturtle is just the turtle format with newlines preferred over compactness - multiple nodes on the same line to enhance the format's text file version control (think Git) friendliness - and more modern forms of prefix markers - PREFIX instead of @prefix - to make it as similar to SPARQL as possible.

Longturtle is Turtle 1.1 compliant and will work wherever ordinary turtle works, however some very old parsers don't understand PREFIX, only @prefix...

## 3.2.3 Plugin stores

### Built In

The following Stores are contained within the rdflib core package:

Name	Class
Auditable	<i>AuditableStore</i>
Concurrent	<i>ConcurrentStore</i>
SimpleMemory	<i>SimpleMemory</i>
Memory	<i>Memory</i>
SPARQLStore	<i>SPARQLStore</i>
SPARQLUpdateStore	<i>SPARQLUpdateStore</i>
BerkeleyDB	<i>BerkeleyDB</i>
default	<i>Memory</i>

### External

The following Stores are defined externally to rdflib's core package, so look to their documentation elsewhere for specific details of use.



Name	Repository	Notes
SQLAlche	<a href="https://github.com/RDFLib/rdflib-sqlalchemy">https://github.com/RDFLib/rdflib-sqlalchemy</a>	An SQLAlchemy-backed, formula-aware RDFLib Store. Tested dialects are: SQLite, MySQL & PostgreSQL
leveldb	<a href="https://github.com/RDFLib/rdflib-leveldb">https://github.com/RDFLib/rdflib-leveldb</a>	An adaptation of RDFLib BerkeleyDB Store's key-value approach, using LevelDB as a back-end
Kyoto Cabinet	<a href="https://github.com/RDFLib/rdflib-kyotocabinet">https://github.com/RDFLib/rdflib-kyotocabinet</a>	An adaptation of RDFLib BerkeleyDB Store's key-value approach, using Kyoto Cabinet as a back-end
HDT	<a href="https://github.com/RDFLib/rdflib-hdt">https://github.com/RDFLib/rdflib-hdt</a>	A Store back-end for rdflib to allow for reading and querying HDT documents
Oxi-graph	<a href="https://github.com/oxigraph/oxrdflib">https://github.com/oxigraph/oxrdflib</a>	Works with the <a href="#">Pyoxigraph</a> Python graph database library

*If you have, or know of a Store implementation and would like it listed here, please submit a Pull Request!*

## Use

You can use these stores like this:

```
from rdflib import Graph

# use the default memory Store
graph = Graph()

# use the BerkeleyDB Store
graph = Graph(store="BerkeleyDB")
```

In some cases, you must explicitly *open* and *close* a store, for example:

```
from rdflib import Graph

# use the BerkeleyDB Store
graph = Graph(store="BerkeleyDB")
graph.open("/some/folder/location")
# do things ...
graph.close()
```

### 3.2.4 Plugin query results

Plugins for reading and writing of (SPARQL) *Result* - pass name to either *parse()* or *serialize()*

## Parsers

Name	Class
csv	<i>CSVResultParser</i>
json	<i>JSONResultParser</i>
tsv	<i>TSVResultParser</i>
xml	<i>XMLResultParser</i>

## Serializers

Name	Class
csv	<i>CSVResultSerializer</i>
json	<i>JSONResultSerializer</i>
txt	<i>TXTResultSerializer</i>
xml	<i>XMLResultSerializer</i>

## VERSIONING

RDFLib follows [Semantic Versioning 2.0.0](#), which can be summarized as follows:

Given a version number `MAJOR.MINOR.PATCH`, increment the:

1. **MAJOR** version when you make incompatible API changes
2. **MINOR** version when you add functionality in a backwards-compatible manner
3. **PATCH** version when you make backwards-compatible bug fixes



## FOR DEVELOPERS

### 5.1 RDFLib developers guide

#### 5.1.1 Introduction

This document describes the process and conventions to follow when developing RDFLib code.

- Please be as Pythonic as possible ([PEP 8](#)).
- Code should be formatted using [black](#) and we use Black v23.1.0, with the black config in `pyproject.toml`.
- Code should also pass [flake8](#) linting and [mypy](#) type checking.
- You must supply tests for new code.
- RDFLib uses [Poetry](#) for dependency management and packaging.

If you add a new cool feature, consider also adding an example in `./examples`.

#### 5.1.2 Pull Requests Guidelines

Contributions to RDFLib are made through pull requests (PRs).

For changes that add features or affect the public API of RDFLib, it is recommended to first open an issue to discuss the change before starting to work on it. That way you can get feedback on the design of the feature before spending time on it.

In general, maintainers will only merge PRs if the following conditions are met:

- The PR has been sufficiently reviewed.

Each PR should be reviewed and approved by at least two people other than the author of the PR before it is merged and PRs will be processed faster if they are easier to review and approve of.

Reviews are open to everyone, but the weight assigned to any particular review is at the discretion of maintainers.
- Changes that have a runtime impact are covered by unit tests.

There should either be existing tests that cover the changed code and behaviour, or the PR should include tests. For more information about what is considered adequate testing see the [Tests section](#).
- Documentation that covers something that changed has been updated.
- Type checks and unit tests that are part of our continuous integration workflow pass.

In addition to these conditions, PRs that are easier to review and approve will be processed quicker. The primary factors that determine this are the scope and size of a PR. If there are few changes and the scope is limited, then there is less

that a reviewer has to understand and less that they can disagree with. It is thus important to try to split up your changes into multiple independent PRs if possible. No PR is too small.

For PRs that introduce breaking changes, it is even more critical that they are limited in size and scope, as they will likely have to be kept up to date with the `main` branch of this project for some time before they are merged.

It is also critical that your PR is understandable both in what it does and why it does it, and how the change will impact the users of this project, for this reason, it is essential that your PR's description explains the nature of the PR, what the PR intends to do, why this is desirable, and how this will affect the users of this project.

Please note that while we would like all PRs to follow the guidelines given here, we will not reject a PR just because it does not.

### 5.1.3 Maintenance Guidelines

This section contains guidelines for maintaining RDFLib. RDFLib maintainers should try to follow these. These guidelines also serve as an indication to RDFLib users what they can expect.

#### Breaking changes

Breaking changes to RDFLib's public API should be made incrementally, with small pull requests to the `main` branch that change as few things as possible.

Breaking changes should be discussed first in an issue before work is started, as it is possible that the change is not necessary or that there is a better way to achieve the same goal, in which case the work on the PR would have been wasted. This will however not be strictly enforced, and no PR will be rejected solely on the basis that it was not discussed upfront.

RDFLib follows [semantic versioning](#) and [trunk-based development](#), so if any breaking changes were introduced into the `main` branch since the last release, then the next release will be a major release with an incremented major version.

Releases of RDFLib will not as a rule be conditioned on specific features, so there may be new major releases that contain very few breaking changes, and there could be no minor or patch releases between two major releases.

#### Rationale

RDFLib has been around for more than a decade, and in this time both Python and RDF have evolved, and RDFLib's API also has to evolve to keep up with these changes and to make it easier for users to use. This will inevitably require breaking changes.

There are more or less two ways to introduce breaking changes to RDFLib's public API:

- **Revolutionary:** Create a new API from scratch and reimplement it, and when ready, release a new version of RDFLib with the new API.
- **Evolutionary:** Incrementally improve the existing API with small changes and release any breaking changes that were made at regular intervals.

While the revolutionary approach seems appealing, it is also risky and time-consuming.

The evolutionary approach puts a lot of strain on the users of RDFLib as they have to adapt to breaking changes more often, but the shortcomings of the RDFLib public API also put a lot of strain on the users of RDFLib. On the other hand, a major advantage of the evolutionary approach is that it is simple and achievable from a maintenance and contributor perspective.

## Deprecating functionality

To whatever extent possible, classes, functions, variables, or parameters that will be removed should be marked for deprecation in documentation, and if possible, should be changed to raise deprecation warnings if used.

There is however no hard requirement that something may only be removed after a deprecation notice has been added, or only after a release was made with a deprecation notice.

Consequently, functionality may be removed without it ever being marked as deprecated.

## Rationale

Current resource limitations and the backlog of issues make it impractical to first release or incorporate deprecation notices before making quality of life changes.

RDFLib uses semantic versioning and provides type hints, and these are the primary mechanisms for signalling breaking changes to our users.

## 5.1.4 Tests

Any new functionality being added to RDFLib *must* have unit tests and should have doc tests supplied.

Typically, you should add your functionality and new tests to a branch of RDFLib and run all tests locally and see them pass. There are currently close to 4,000 tests, with a some expected failures and skipped tests. We won't merge pull requests unless the test suite completes successfully.

Tests that you add should show how your new feature or bug fix is doing what you say it is doing: if you remove your enhancement, your new tests should fail!

Finally, please consider adding simple and more complex tests. It's good to see the basic functionality of your feature tests and then also any tricky bits or edge cases.

## Testing framework

RDFLib uses the `pytest` testing framework.

## Running tests

To run RDFLib's test suite with `pytest`:

```
$ poetry install
$ poetry run pytest
```

Specific tests can be run by file name. For example:

```
$ poetry run pytest test/test_graph/test_graph.py
```

For more extensive tests, including tests for the `berkeleydb` backend, install extra requirements before executing the tests.

```
$ poetry install --all-extras
$ poetry run pytest
```

## Writing tests

New tests should be written for `pytest` instead of for python's built-in `unittest` module as `pytest` provides advanced features such as parameterization and more flexibility in writing expected failure tests than `unittest`.

A primer on how to write tests for `pytest` can be found [here](#).

The existing tests that use `unittest` work well with `pytest`, but they should ideally be updated to the `pytest` test-style when they are touched.

Test should go into the `test/` directory, either into an existing test file with a name that is applicable to the test being written, or into a new test file with a name that is descriptive of the tests placed in it. Test files should be named `test_*.py` so that `pytest` can discover them.

### 5.1.5 Running static checks

Check formatting with `black`, making sure you use our `black.toml` config file:

```
poetry run black .
```

Check style and conventions with `flake8`:

```
poetry run flake8 rdflib
```

We also provide a `flakeheaven` baseline that ignores existing `flake8` errors and only reports on newly introduced `flake8` errors:

```
poetry run flakeheaven
```

Check types with `mypy`:

```
poetry run mypy --show-error-context --show-error-codes
```

### 5.1.6 pre-commit and pre-commit ci

We have `pre-commit` configured with `black` for formatting code.

Some useful commands for using `pre-commit`:

```
# Install pre-commit.
pip install --user --upgrade pre-commit

# Install pre-commit hooks, this will run pre-commit
# every time you make a git commit.
pre-commit install

# Run pre-commit on changed files.
pre-commit run

# Run pre-commit on all files.
pre-commit run --all-files
```

There is also two tox environments for `pre-commit`:



```
# run pre-commit on changed files.
tox -e precommit

# run pre-commit on all files.
tox -e precommitall
```

There is no hard requirement for pull requests to be processed with pre-commit (or the underlying processors), however doing this makes for a less noisy codebase with cleaner history.

We have enabled <https://pre-commit.ci/> and this can be used to automatically fix pull requests by commenting `pre-commit.ci autofix` on a pull request.

### 5.1.7 Using tox

RDFLib has a `tox` config file that makes it easier to run validation on all supported python versions.

```
# Install tox.
pip install tox

# List the tox environments that run by default.
tox -e

# Run the default environments.
tox

# List all tox environments, including ones that don't run by default.
tox -a

# Run a specific environment.
tox -e py37 # default environment with py37
tox -e py39-extra # extra tests with py39

# Override the test command.
# the below command will run `pytest test/test_translate_algebra.py`
# instead of the default pytest command.
tox -e py37,py39 -- pytest test/test_translate_algebra.py
```

### 5.1.8 go-task and Taskfile.yml

A `Taskfile.yml` is provided for `go-task` with various commands that facilitate development.

Instructions for installing `go-task` can be seen in the [go-task installation guide](#).

Some useful commands for working with the task in the taskfile is given below:

```
# List available tasks.
task -l

# Configure the environment for development
task configure

# Run basic validation
```

(continues on next page)

(continued from previous page)

```
task validate

# Build docs
task docs:build

# Run live-preview on the docs
task docs:live-server

# Run the py310 tox environment
task tox -- -e py310
```

The [Taskfile usage documentation](#) provides more information on how to work with taskfiles.

### 5.1.9 Development container

To simplify the process of getting a working development environment to develop rdflib in we provide a [Development Container](#) (*devcontainer*) that is configured in [Docker Compose](#). This container can be used directly to run various commands, or it can be used with [editors that support Development Containers](#).

---

**Important:** The devcontainer is intended to run with a [rootless docker](#) daemon so it can edit files owned by the invoking user without an involved configuration process.

Using a rootless docker daemon also has general security benefits.

---

To use the development container directly:

```
# Build the devcontainer docker image.
docker-compose build

# Configure the system for development.
docker-compose run --rm run task configure

# Run the validate task inside the devtools container.
docker-compose run --rm run task validate

# Run extensive tests inside the devtools container.
docker-compose run --rm run task EXTENSIVE=true test

# To get a shell into the devcontainer docker image.
docker-compose run --rm run bash
```

The devcontainer also works with [Podman Compose](#).

Details on how to use the development container with [VSCode](#) can found in the [Developing inside a Container](#) page. With the VSCode [development container CLI](#) installed the following command can be used to open the repository inside the development container:

```
# Inside the repository base directory
cd ./rdflib/

# Build the development container.
```

(continues on next page)

(continued from previous page)

```
devcontainer build .

# Open the code inside the development container.
devcontainer open .
```

### 5.1.10 Writing documentation

We use sphinx for generating HTML docs, see *Writing RDFLib Documentation*.

### 5.1.11 Continuous Integration

We used GitHub Actions for CI, see:

<https://github.com/RDFLib/rdflib/actions>

If you make a pull-request to RDFLib on GitHub, GitHub Actions will automatically test your code and we will only merge code passing all tests.

Please do *not* commit tests you know will fail, even if you're just pointing out a bug. If you commit such tests, flag them as expecting to fail.

### 5.1.12 Compatibility

RDFLib 7.0.0 release and later only support Python 3.8.1 and newer.

RDFLib 6.0.0 release and later only support Python 3.7 and newer.

RDFLib 5.0.0 maintained compatibility with Python versions 2.7, 3.4, 3.5, 3.6, 3.7.

### 5.1.13 Releasing

Create a release-preparation pull request with the following changes:

- Updated copyright year in the LICENSE file.
- Updated copyright year in the docs/conf.py file.
- Updated main branch version and current version in the README.md file. The main branch version should be the next major version with an `a0` suffix to indicate it is alpha 0. When releasing 6.3.1, the main branch version in the README should be 6.4.0a0.
- Updated version in the pyproject.toml file.
- Updated `__date__` in the rdflib/\_\_init\_\_.py file.
- Accurate CHANGELOG.md entry for the release.

Once the PR is merged, switch to the main branch, build the release and upload it to PyPI:

```
# Clean up any previous builds
\rm -vf dist/*

# Build artifacts
poetry build
```

(continues on next page)

(continued from previous page)

```
# Check that the built wheel works correctly:
pipx run --spec "${readlink -f dist/rdflib*.whl}" rdfpipe --version

# Publish to PyPI
poetry publish
```

Once this is done, create a release tag from [GitHub releases](#). For a release of version 6.3.1 the tag should be 6.3.1 (without a “v” prefix), and the release title should be “RDFLib 6.3.1”. The release notes for the latest version be added to the release description. The artifacts built with `poetry build` should be uploaded to the release as release artifacts.

The resulting release will be available at <https://github.com/RDFLib/rdflib/releases/tag/6.3.1>

Once this is done announce the release at the following locations:

- Twitter: Just make a tweet from your own account linking to the latest release.
- RDFLib mailing list.
- RDFLib Gitter / matrix.org chat room.

Once this is all done, create another post-release pull request with the following changes:

- Set the just released version in `docker/latest/requirements.in` and run `task docker:prepare` to update the `docker/latest/requirements.txt` file.
- Set the version in the `pyproject.toml` file to the next minor release with a `a0` suffix to indicate alpha 0.

## 5.2 Contributor Covenant Code of Conduct

### 5.2.1 Our Pledge

We as members, contributors, and leaders pledge to make participation in our community a harassment-free experience for everyone, regardless of age, body size, visible or invisible disability, ethnicity, sex characteristics, gender identity and expression, level of experience, education, socio-economic status, nationality, personal appearance, race, caste, color, religion, or sexual identity and orientation.

We pledge to act and interact in ways that contribute to an open, welcoming, diverse, inclusive, and healthy community.

### 5.2.2 Our Standards

Examples of behavior that contributes to a positive environment for our community include:

- Demonstrating empathy and kindness toward other people
- Being respectful of differing opinions, viewpoints, and experiences
- Giving and gracefully accepting constructive feedback
- Accepting responsibility and apologizing to those affected by our mistakes, and learning from the experience
- Focusing on what is best not just for us as individuals, but for the overall community

Examples of unacceptable behavior include:

- The use of sexualized language or imagery, and sexual attention or advances of any kind
- Trolling, insulting or derogatory comments, and personal or political attacks

- Public or private harassment
- Publishing others' private information, such as a physical or email address, without their explicit permission
- Other conduct which could reasonably be considered inappropriate in a professional setting

### 5.2.3 Enforcement Responsibilities

Community leaders are responsible for clarifying and enforcing our standards of acceptable behavior and will take appropriate and fair corrective action in response to any behavior that they deem inappropriate, threatening, offensive, or harmful.

Community leaders have the right and responsibility to remove, edit, or reject comments, commits, code, wiki edits, issues, and other contributions that are not aligned to this Code of Conduct, and will communicate reasons for moderation decisions when appropriate.

### 5.2.4 Scope

This Code of Conduct applies within all community spaces, and also applies when an individual is officially representing the community in public spaces. Examples of representing our community include using an official e-mail address, posting via an official social media account, or acting as an appointed representative at an online or offline event.

### 5.2.5 Enforcement

Instances of abusive, harassing, or otherwise unacceptable behavior may be reported to the community leaders responsible for enforcement at <https://github.com/RDFLib/rdfLib/discussions>. All complaints will be reviewed and investigated promptly and fairly.

All community leaders are obligated to respect the privacy and security of the reporter of any incident.

### 5.2.6 Enforcement Guidelines

Community leaders will follow these Community Impact Guidelines in determining the consequences for any action they deem in violation of this Code of Conduct:

#### 1. Correction

**Community Impact:** Use of inappropriate language or other behavior deemed unprofessional or unwelcome in the community.

**Consequence:** A private, written warning from community leaders, providing clarity around the nature of the violation and an explanation of why the behavior was inappropriate. A public apology may be requested.

## 2. Warning

**Community Impact:** A violation through a single incident or series of actions.

**Consequence:** A warning with consequences for continued behavior. No interaction with the people involved, including unsolicited interaction with those enforcing the Code of Conduct, for a specified period of time. This includes avoiding interactions in community spaces as well as external channels like social media. Violating these terms may lead to a temporary or permanent ban.

## 3. Temporary Ban

**Community Impact:** A serious violation of community standards, including sustained inappropriate behavior.

**Consequence:** A temporary ban from any sort of interaction or public communication with the community for a specified period of time. No public or private interaction with the people involved, including unsolicited interaction with those enforcing the Code of Conduct, is allowed during this period. Violating these terms may lead to a permanent ban.

## 4. Permanent Ban

**Community Impact:** Demonstrating a pattern of violation of community standards, including sustained inappropriate behavior, harassment of an individual, or aggression toward or disparagement of classes of individuals.

**Consequence:** A permanent ban from any sort of public interaction within the community.

## 5.2.7 Attribution

This Code of Conduct is adapted from the Contributor Covenant, version 2.1, available at [https://www.contributor-covenant.org/version/2/1/code\\_of\\_conduct.html](https://www.contributor-covenant.org/version/2/1/code_of_conduct.html).

Community Impact Guidelines were inspired by Mozilla's [code of conduct enforcement ladder](#).

For answers to common questions about this code of conduct, see the FAQ at <https://www.contributor-covenant.org/faq>. Translations are available at <https://www.contributor-covenant.org/translations>.

## 5.3 Writing RDFLib Documentation

These docs are generated with Sphinx.

Sphinx makes it very easy to pull in doc-strings from modules, classes, methods, etc. When writing doc-strings, special reST fields can be used to annotate parameters, return-types, etc. This makes for pretty API docs. See [here](#) for the Sphinx documentation about these fields.

### 5.3.1 Building

To build the documentation you can use Sphinx from within the poetry environment. To do this, run the following commands:

```
# Install poetry venv
poetry install

# Build the sphinx docs
poetry run sphinx-build -b html -d docs/_build/doctrees docs docs/_build/html
```

Docs will be generated in docs/\_build/html and API documentation, generated from doc-strings, will be placed in docs/apidocs/.

There is also a `tox` environment for building documentation:

```
tox -e docs
```

### 5.3.2 API Docs

API Docs are automatically generated with `sphinx-apidoc`:

```
poetry run sphinx-apidoc -f -d 10 -o docs/apidocs/ rdflib examples
```

**Note that `rdflib.rst` was manually tweaked so as to not include all imports in `rdflib/__init__.py`.**

### 5.3.3 Tables

The tables in `plugin_*.rst` were generated with `plugintable.py`

## 5.4 Persisting Notation 3 Terms

### 5.4.1 Using N3 Syntax for Persistence

Blank Nodes, Literals, URI References, and Variables can be distinguished in persistence by relying on Notation 3 syntax convention.

All URI References can be expanded and persisted as:

```
<..URI..>
```

All Literals can be expanded and persisted as:

```
"..value.."@lang or "..value.."^^dtype_uri
```

---

**Note:** `@lang` is a language tag and `^^dtype_uri` is the URI of a data type associated with the Literal

---

Blank Nodes can be expanded and persisted as:

```
_:Id
```

**Note:** where `Id` is an identifier as determined by skolemization. Skolemization is a syntactic transformation routinely used in automatic inference systems in which existential variables are replaced by ‘new’ functions - function names not used elsewhere - applied to any enclosing universal variables. In RDF, Skolemization amounts to replacing every blank node in a graph by a ‘new’ name, i.e. a URI reference which is guaranteed to not occur anywhere else. In effect, it gives ‘arbitrary’ names to the anonymous entities whose existence was asserted by the use of blank nodes: the arbitrariness of the names ensures that nothing can be inferred that would not follow from the bare assertion of existence represented by the blank node. (Using a literal would not do. Literals are never ‘new’ in the required sense.)

Variables can be persisted as they appear in their serialization (`?varName`) - since they only need be unique within their scope (the context of their associated statements)

These syntactic conventions can facilitate term round-tripping.

### 5.4.2 Variables by Scope

Would an interface be needed in order to facilitate a quick way to aggregate all the variables in a scope (given by a formula identifier)? An interface such as:

```
def variables(formula_identifier)
```

### 5.4.3 The Need to Skolemize Formula Identifiers

It would seem reasonable to assume that a formula-aware store would assign Blank Node identifiers as names of formulae that appear in a N3 serialization. So for instance, the following bit of N3:

```
{?x a :N3Programmer} => {?x :has :Migrane}
```

Could be interpreted as the assertion of the following statement:

```
_:a log:implies _:b
```

However, how are `_:a` and `_:b` distinguished from other Blank Nodes? A formula-aware store would be expected to persist the first set of statements as quoted statements in a formula named `_:a` and the second set as quoted statements in a formula named `_:b`, but it would not be cost-effective for a serializer to have to query the store for all statements in a context named `_:a` in order to determine if `_:a` was associated with a formula (so that it could be serialized properly).

### 5.4.4 Relying on `log:Formula` Membership

The store could rely on explicit `log:Formula` membership (via `rdf:type` statements) to model the distinction of Blank Nodes associated with formulae. However, would these statements be expected from an N3 parser or known implicitly by the store? i.e., would all such Blank Nodes match the following pattern:

```
?formula rdf:type log:Formula
```



### 5.4.5 Relying on an Explicit Interface

A formula-aware store could also support the persistence of this distinction by implementing a method that returns an iterator over all the formulae in the store:

```
def formulae(triple=None)
```

This function would return all the Blank Node identifiers assigned to formulae or just those that contain statements matching the given triple pattern and would be the way a serializer determines if a term refers to a formula (in order to properly serialize it).

How much would such an interface reduce the need to model formulae terms as first class objects (perhaps to be returned by the `triples()` function)? Would it be more useful for the `Graph` (or the store itself) to return a Context object in place of a formula term (using the formulae interface to make this determination)?

Conversely, would these interfaces (variables and formulae) be considered optimizations only since you have the distinction by the kinds of terms triples returns (which would be expanded to include variables and formulae)?

### 5.4.6 Persisting Formula Identifiers

This is the most straight forward way to maintain this distinction - without relying on extra interfaces. Formula identifiers could be persisted distinctly from other terms by using the following notation:

```
{_:bnode} or {<.. URI ..>}
```

This would facilitate their persistence round-trip - same as the other terms that rely on N3 syntax to distinguish between each other.

## 5.5 Type Hints

This document provides some details about the type hints for RDFLib. More information about type hints can be found [here](#)

### 5.5.1 Rationale for Type Hints

Type hints are code annotations that describe the types of variables, function parameters and function return value types in a way that can be understood by humans, static type checkers like `mypy`, code editors like VSCode, documentation generators like Sphinx, and other tools.

Static type checkers can use type hints to detect certain classes of errors by inspection. Code editors and IDEs can use type hints to provide better auto-completion and documentation generators can use type hints to generate better documentation.

These capabilities make it easier to develop a defect-free RDFLib and they also make it easier for users of RDFLib who can now use static type checkers to detect type errors in code that uses RDFLib.

### 5.5.2 Gradual Typing Process

Type hints are being added to RDFLib through a process called [gradual typing](#). This process involves adding type hints to some parts of RDFLib while leaving the rest without type hints. Gradual typing is being applied to many, long-lived, Python code bases.

This process is beneficial in that we can realize some of the benefits of type hints without requiring that the whole codebase have type hints.

### 5.5.3 Intended Type Hints

The intent is to have type hints in place for all of RDFLib and to have these type hints be as accurate as possible.

The accuracy of type hints is determined by both the standards that RDFLib aims to conform to, like RDF 1.1, and the deliberate choices that are made when implementing RDFLib. For example, given that the RDF 1.1 specification stipulates that the subject of an RDF triple cannot be a literal, all functions that accept an *RDF term* to be used as the subject of a triple should have type hints which excludes values that are literals.

There may be cases where some functionality of RDFLib may work perfectly well with values of types that are excluded by the type hints, but if these additional types violate the relevant standards we will consider the correct type hints to be those that exclude values of these types.

### 5.5.4 Public Type Aliases

In python, type hints are specified in annotations. Type hints are different from type aliases which are normal python variables that are not intended to provide runtime utility and are instead intended for use in static type checking.

For clarity, the following is an example of a function `foo` with type hints:

```
def foo(a: int) -> int:
    return a + 1
```

In the function `foo`, the input variable `a` is indicated to be of type `int` and the function is indicated to return an `int`.

The following is an example of a type alias `Bar`:

```
from typing import Tuple

Bar = Tuple[int, str]
```

RDFLib will provide public type aliases under the `rdflib.typing` package, for example, `rdflib.typing.Triple`, `rdflib.typing.Quad`. Type aliases in the rest of RDFLib should be private (i.e. being with an underscore).

### 5.5.5 Versioning, Compatibility and Stability

RDFLib attempts to adhere to [semver 2.0](#) which is concerned with the public API of software.

Ignoring type hints, the public API of RDFLib exists implicitly as a consequence of the code of RDFLib and the actual behaviour this entails, the relevant standards that RDFLib is trying to implement, and the documentation of RDFLib, with some interplay between all three of these. RDFLib's public API includes public type aliases, as these are normal python variables and not annotations.

Type hints attempt to formally document RDFLib's implicitly-defined public API in a machine-readable fashion as accurately and correctly as possible within the framework outline earlier in this document.

Type hints do not affect the runtime API or behaviour of RDFLib. In this way then, they are somewhat outside of the scope of semver, however, they still have an impact on the users of RDFLib, even if this impact is not at runtime, but during development. This necessitates some clarity as to what users of RDFLib should expect regarding type hints in RDFLib releases.

Changes to type hints can broadly be classified as follow:

### Type Declaration

Adding type hints to existing code that had no explicit type hints, for example, changing

```
def foo(val):
    return val + 1
```

to

```
def foo(val: int) -> int:
    return val + 1
```

### Type Refinement

Refining existing type hints to be narrower, for example, changing a type hint of `typing.Collection` to `typing.Sequence`.

### Type Corrections

Correcting existing type hints which contradict the behaviour of the code or relevant specifications, for example, changing `typing.Sequence` from `typing.Set`

Given semver version components MAJOR.MINOR.PATCH, RDFLib will attempt to constrain type hint changes as follow:

Version Component	Type Declaration	Type Refinement	Type Corrections
MAJOR	YES	YES	YES
MINOR	YES	YES	YES
PATCH	NO	NO	YES

**Caution:** A caveat worth nothing here is that code that passed type validation on one version of RDFLib can fail type validation on a later version of RDFLib that only differs in PATCH version component. This is as a consequence of potential *Type Corrections*.

## 5.6 RDFLib Contributing Guide

Thank you for considering contributing to RDFLib. This project has no formal funding or full-time maintainers, and relies entirely on independent contributors to keep it alive and relevant.

### 5.6.1 Ways to contribute

Some ways in which you can contribute to RDFLib are:

- Address open issues:
- Fix [expected failure](#) tests.
- Add additional [expected failure](#) tests for open issues:
- Add tests for untested code:
- Review pull requests marked with the
- Answer questions on Stack Overflow:
- Convert [unittest](#) based tests to [pytest](#) based tests:
- Add, correct or improve docstrings:
- Update the RDFLib Wikipedia entry:
- Update the RDFLib Wikidata entry:
- Participate on Gitter/Matrix chat:
- Participate in GitHub discussions:
- Fix flake8 failures.

### 5.6.2 Pull Requests

Contributions that involve changes to the RDFLib repository have to be made with pull requests and should follow the *RDFLib developers guide*.

For changes that add features or affect the public API of RDFLib, it is recommended to first open an issue to discuss the change before starting to work on it. That way you can get feedback on the design of the feature before spending time on it.

### 5.6.3 Code of Conduct

All contributions to the project should be consistent with the *code of conduct* adopted by RDFLib.

## 5.7 Decision Records

To ensure that significant changes to RDFLib are made with sufficient consultation, consideration and planning they should be preceded by a decision record that captures the particulars of the decision that lead to the change.

Decision records present the users and maintainers of RDFLib with an opportunity to review decisions before effort is expended to implement the decision in code, and it also makes it possible to review decisions without having to reconstruct them from the code changes that implement them.

Whether a change is significant is hard to measure objectively, but some characteristics that may indicate that a change is significant include:

- It will require changes to code that use RDFLib.
- It cannot be reversed without requiring changes to code that use RDFLib.
- It is onerous to reverse later.
- It increases the maintenance burden of RDFLib.
- It is very large.

Some of these characteristics are not binary but measured in degrees, so some discretion is required when determining if an architectural decision record is appropriate.

Decision records may also be used for changes that do not have any of the listed characteristics if a decision record would be otherwise helpful, for example to capture a decision to change the maintenance process of RDFLib.

Changes not preceded by decision records won't be rejected solely on this basis even if they are deemed significant, and decision records may also be created retrospectively for changes.

Decision records as described here are similar to the concept of [Architectural Decision Records](#), though it is slightly broader as it could include decisions which are not classified as architectural.

### 5.7.1 Creating a decision record

Decision records should be added to the RDFLib repository in the `./docs/decisions/` directory with a name `{YYYYmmdd}-{title}.rst`.

The content of the decision record should succinctly describe the context of the decision, the decision itself, and the status of the decision.

Decision records should preferably follow [Michael Nygard decision record template](#) that he described in a [2011 article](#) on documenting architecture decisions.

For questions about decision records please reach out to the RDFLib maintainers and community using the options given in [Further help & Contact](#).

### 5.7.2 Decision list

#### Default Branch Name

---

#### Status

Accepted

---

## Context

In recent years usage of the word `master` has become somewhat controversial [[SFC-BNAMING](#)] and consequently default branch name of Git repos has become `main`, both in Git itself [[SFC-BNAMING](#)] and in Git hosting solutions such as GitHub [[GH-BRANCHES](#)].

## Decision

RDFLib's default branch will be renamed from `master` to `main`. This is primarily to stay in line with modern conventions and to adhere to the principle of least surprise.

## Consequences

Anticipated negative consequences:

- Some links to old code will be broken.
- Some people's workflow may break unexpectedly and need adjusting.
- Any code and systems reliant on the old default branch name will fail.

Anticipated positive consequences:

- It will become a bit easier to work with RDFLib for developers that are used to `main` as the default branch.

## References

## **SOURCE CODE**

The rdflib source code is hosted on GitHub at <https://github.com/RDFLib/rdflib> where you can lodge Issues and create Pull Requests to help improve this community project!

The RDFlib organisation on GitHub at <https://github.com/RDFLib> maintains this package and a number of other RDF and RDFlib-related packages that you might also find useful.





## FURTHER HELP & CONTACT

If you would like help with using RDFlib, rather than developing it, please post a question on StackOverflow using the tag `[rdflib]`. A list of existing `[rdflib]` tagged questions can be found [here](#).

You might also like to join RDFlib's [dev mailing list](#) or use RDFLib's [GitHub discussions section](#).

The chat is available at [gitter](#) or via matrix `#RDFLib_rdfli:gitter.im`.



## BIBLIOGRAPHY

[GH-BRANCHES] [GitHub: About the default branch](#)

[SFC-BNAMING] [Regarding Git and Branch Naming](#)



## PYTHON MODULE INDEX

### e

- `examples.berkeleydb_example`, 23
- `examples.conjunctive_graphs`, 22
- `examples.custom_datatype`, 22
- `examples.custom_eval`, 22
- `examples.foafpaths`, 22
- `examples.prepared_query`, 23
- `examples.resource_example`, 23
- `examples.secure_with_audit`, 26
- `examples.secure_with_urlopen`, 26
- `examples.slice`, 24
- `examples.smushing`, 24
- `examples.sparql_query_example`, 24
- `examples.sparql_update_example`, 25
- `examples.sparqlstore_example`, 25
- `examples.swap_primer`, 25
- `examples.transitive`, 25

### r

- `rdflib`, 574
- `rdflib.collection`, 461
- `rdflib.compare`, 466
- `rdflib.compat`, 470
- `rdflib.container`, 470
- `rdflib.events`, 473
- `rdflib.exceptions`, 475
- `rdflib.extras`, 72
- `rdflib.extras.cmdlineutils`, 49
- `rdflib.extras.describer`, 49
- `rdflib.extras.external_graph_libs`, 53
- `rdflib.extras.infixowl`, 58
- `rdflib.graph`, 476
- `rdflib.namespace`, 72
- `rdflib.parser`, 516
- `rdflib.paths`, 519
- `rdflib.plugin`, 528
- `rdflib.plugins`, 458
- `rdflib.plugins.parsers`, 353
- `rdflib.plugins.parsers.hext`, 319
- `rdflib.plugins.parsers.jsonld`, 320
- `rdflib.plugins.parsers.notation3`, 321
- `rdflib.plugins.parsers.nquads`, 337

- `rdflib.plugins.parsers.ntriples`, 338
- `rdflib.plugins.parsers.RDFVOC`, 319
- `rdflib.plugins.parsers.rdfxml`, 342
- `rdflib.plugins.parsers.trig`, 348
- `rdflib.plugins.parsers.trix`, 350
- `rdflib.plugins.serializers`, 364
- `rdflib.plugins.serializers.hext`, 353
- `rdflib.plugins.serializers.jsonld`, 354
- `rdflib.plugins.serializers.longturtle`, 355
- `rdflib.plugins.serializers.n3`, 356
- `rdflib.plugins.serializers.nquads`, 357
- `rdflib.plugins.serializers.nt`, 358
- `rdflib.plugins.serializers.rdfxml`, 358
- `rdflib.plugins.serializers.trig`, 360
- `rdflib.plugins.serializers.trix`, 360
- `rdflib.plugins.serializers.turtle`, 361
- `rdflib.plugins.serializers.xmlwriter`, 363
- `rdflib.plugins.shared`, 371
- `rdflib.plugins.shared.jsonld`, 371
- `rdflib.plugins.shared.jsonld.context`, 364
- `rdflib.plugins.shared.jsonld.errors`, 370
- `rdflib.plugins.shared.jsonld.keys`, 370
- `rdflib.plugins.shared.jsonld.util`, 370
- `rdflib.plugins.sparql`, 428
- `rdflib.plugins.sparql.aggregates`, 379
- `rdflib.plugins.sparql.algebra`, 386
- `rdflib.plugins.sparql.datatypes`, 392
- `rdflib.plugins.sparql.evaluate`, 392
- `rdflib.plugins.sparql.evalutils`, 396
- `rdflib.plugins.sparql.operators`, 396
- `rdflib.plugins.sparql.parser`, 408
- `rdflib.plugins.sparql.parserutils`, 409
- `rdflib.plugins.sparql.processor`, 414
- `rdflib.plugins.sparql.results`, 379
- `rdflib.plugins.sparql.results.csvresults`, 371
- `rdflib.plugins.sparql.results.graph`, 373
- `rdflib.plugins.sparql.results.jsonresults`, 373
- `rdflib.plugins.sparql.results.rdfresults`, 375
- `rdflib.plugins.sparql.results.tsvresults`, 375
- `rdflib.plugins.sparql.results.txtresults`, 376
- `rdflib.plugins.sparql.results.xmlresults`, 376

- `rdflib.plugins.sparql.sparql`, 416
- `rdflib.plugins.sparql.update`, 425
- `rdflib.plugins.stores`, 458
  - `rdflib.plugins.stores.auditable`, 429
  - `rdflib.plugins.stores.berkeleydb`, 432
  - `rdflib.plugins.stores.concurrent`, 435
  - `rdflib.plugins.stores.memory`, 436
  - `rdflib.plugins.stores.regexmatching`, 441
  - `rdflib.plugins.stores.sparqlconnector`, 443
  - `rdflib.plugins.stores.sparqlstore`, 445
- `rdflib.query`, 531
- `rdflib.resource`, 538
- `rdflib.serializer`, 545
- `rdflib.store`, 546
- `rdflib.term`, 553
- `rdflib.tools`, 461
  - `rdflib.tools.chunk_serializer`, 458
  - `rdflib.tools.csv2rdf`, 459
  - `rdflib.tools.defined_namespace_creator`, 459
  - `rdflib.tools.graphisomorphism`, 460
  - `rdflib.tools.rdf2dot`, 461
  - `rdflib.tools.rdfpipe`, 461
  - `rdflib.tools.rdfs2dot`, 461
- `rdflib.util`, 570
- `rdflib.void`, 574

## Symbols

- `__abs__()` (*rdflib.Literal* method), 605
- `__abs__()` (*rdflib.term.Literal* method), 559
- `__abstractmethods__` (*rdflib.plugins.sparql.parserutils.Comp* attribute), 409
- `__abstractmethods__` (*rdflib.plugins.sparql.parserutils.Param* attribute), 411
- `__abstractmethods__` (*rdflib.plugins.sparql.parserutils.ParamList* attribute), 412
- `__abstractmethods__` (*rdflib.plugins.sparql.sparql.Bindings* attribute), 416
- `__abstractmethods__` (*rdflib.plugins.sparql.sparql.FrozenBindings* attribute), 418
- `__abstractmethods__` (*rdflib.plugins.sparql.sparql.FrozenDict* attribute), 419
- `__add__()` (*rdflib.Graph* method), 585
- `__add__()` (*rdflib.Literal* method), 605
- `__add__()` (*rdflib.URIRef* method), 615
- `__add__()` (*rdflib.graph.Graph* method), 491
- `__add__()` (*rdflib.term.Literal* method), 559
- `__add__()` (*rdflib.term.URIRef* method), 567
- `__and__()` (*rdflib.Graph* method), 585
- `__and__()` (*rdflib.extras.infixowl.Class* method), 63
- `__and__()` (*rdflib.graph.Graph* method), 491
- `__annotations__` (*rdflib.BNode* attribute), 575
- `__annotations__` (*rdflib.ConjunctiveGraph* attribute), 576
- `__annotations__` (*rdflib.Dataset* attribute), 582
- `__annotations__` (*rdflib.Graph* attribute), 586
- `__annotations__` (*rdflib.IdentifiedNode* attribute), 603
- `__annotations__` (*rdflib.Literal* attribute), 606
- `__annotations__` (*rdflib.URIRef* attribute), 615
- `__annotations__` (*rdflib.Variable* attribute), 617
- `__annotations__` (*rdflib.events.Dispatcher* attribute), 474
- `__annotations__` (*rdflib.namespace.ClosedNamespace* attribute), 141
- `__annotations__` (*rdflib.namespace.Namespace* attribute), 156
- `__annotations__` (*rdflib.parser.URLInputSource* attribute), 518
- `__annotations__` (*rdflib.paths.Path* attribute), 524
- `__annotations__` (*rdflib.plugins.sparql.aggregates.GroupConcat* attribute), 383
- `__annotations__` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* attribute), 432
- `__annotations__` (*rdflib.query.ResultRow* attribute), 535
- `__annotations__` (*rdflib.store.Store* attribute), 547
- `__annotations__` (*rdflib.term.Literal* attribute), 559
- `__annotations__` (*rdflib.term.URIRef* attribute), 567
- `__bool__()` (*rdflib.Literal* method), 606
- `__bool__()` (*rdflib.query.Result* method), 532
- `__bool__()` (*rdflib.term.Literal* method), 559
- `__call__()` (*rdflib.extras.infixowl.Callable* method), 62
- `__call__()` (*rdflib.extras.infixowl.Infix* method), 67
- `__cmp__()` (*rdflib.Graph* method), 586
- `__cmp__()` (*rdflib.graph.Graph* method), 491
- `__cmp__()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 509
- `__contains__()` (*rdflib.ConjunctiveGraph* method), 576
- `__contains__()` (*rdflib.Graph* method), 586
- `__contains__()` (*rdflib.Namespace* method), 613
- `__contains__()` (*rdflib.extras.infixowl.OWLRDFListProxy* method), 68
- `__contains__()` (*rdflib.graph.ConjunctiveGraph* method), 482
- `__contains__()` (*rdflib.graph.Graph* method), 491
- `__contains__()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 509
- `__contains__()` (*rdflib.namespace.ClosedNamespace* method), 141
- `__contains__()` (*rdflib.namespace.Namespace* method), 156
- `__contains__()` (*rdflib.namespace.NamespaceManager* method), 156

- method*), 159
- `__contains__()` (*rdflib.plugins.sparql.sparql.Bindings* *method*), 416
- `__del__()` (*rdflib.plugins.stores.concurrent.ResponsibleGenerator* *method*), 436
- `__delitem__()` (*rdflib.collection.Collection* *method*), 462
- `__delitem__()` (*rdflib.container.Container* *method*), 471
- `__delitem__()` (*rdflib.extras.infixowl.OWL RDFListProxy* *method*), 68
- `__delitem__()` (*rdflib.plugins.sparql.sparql.Bindings* *method*), 416
- `__dict__` (*rdflib.Graph* *attribute*), 586
- `__dict__` (*rdflib.IdentifiedNode* *attribute*), 603
- `__dict__` (*rdflib.Namespace* *attribute*), 614
- `__dict__` (*rdflib.collection.Collection* *attribute*), 463
- `__dict__` (*rdflib.container.Container* *attribute*), 471
- `__dict__` (*rdflib.events.Dispatcher* *attribute*), 474
- `__dict__` (*rdflib.events.Event* *attribute*), 474
- `__dict__` (*rdflib.extras.describer.Describer* *attribute*), 51
- `__dict__` (*rdflib.extras.infixowl.Callable* *attribute*), 62
- `__dict__` (*rdflib.extras.infixowl.Individual* *attribute*), 66
- `__dict__` (*rdflib.extras.infixowl.Infix* *attribute*), 67
- `__dict__` (*rdflib.extras.infixowl.OWL RDFListProxy* *attribute*), 68
- `__dict__` (*rdflib.graph.BatchAddGraph* *attribute*), 480
- `__dict__` (*rdflib.graph.Graph* *attribute*), 491
- `__dict__` (*rdflib.graph.Seq* *attribute*), 514
- `__dict__` (*rdflib.namespace.Namespace* *attribute*), 157
- `__dict__` (*rdflib.namespace.NamespaceManager* *attribute*), 159
- `__dict__` (*rdflib.paths.Path* *attribute*), 525
- `__dict__` (*rdflib.paths.PathList* *attribute*), 526
- `__dict__` (*rdflib.plugin.Plugin* *attribute*), 529
- `__dict__` (*rdflib.plugins.parsers.hextr.HexuplesParser* *attribute*), 319
- `__dict__` (*rdflib.plugins.parsers.jsonld.JsonLDParser* *attribute*), 320
- `__dict__` (*rdflib.plugins.parsers.notation3.Formula* *attribute*), 322
- `__dict__` (*rdflib.plugins.parsers.notation3.RDFSink* *attribute*), 324
- `__dict__` (*rdflib.plugins.parsers.notation3.SinkParser* *attribute*), 327
- `__dict__` (*rdflib.plugins.parsers.notation3.TurtleParser* *attribute*), 335
- `__dict__` (*rdflib.plugins.parsers.nquads.NQuadsParser* *attribute*), 337
- `__dict__` (*rdflib.plugins.parsers.ntriples.DummySink* *attribute*), 338
- `__dict__` (*rdflib.plugins.parsers.rdfxml.RDFXMLParser* *attribute*), 347
- `__dict__` (*rdflib.plugins.parsers.trig.TrigParser* *attribute*), 348
- `__dict__` (*rdflib.plugins.parsers.trix.TriXParser* *attribute*), 352
- `__dict__` (*rdflib.plugins.serializers.xmlwriter.XMLWriter* *attribute*), 363
- `__dict__` (*rdflib.plugins.shared.jsonld.context.Context* *attribute*), 364
- `__dict__` (*rdflib.plugins.shared.jsonld.context.Defined* *attribute*), 369
- `__dict__` (*rdflib.plugins.sparql.aggregates.Accumulator* *attribute*), 379
- `__dict__` (*rdflib.plugins.sparql.aggregates.Aggregator* *attribute*), 380
- `__dict__` (*rdflib.plugins.sparql.parserutils.ParamValue* *attribute*), 412
- `__dict__` (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter* *attribute*), 376
- `__dict__` (*rdflib.plugins.sparql.sparql.Bindings* *attribute*), 416
- `__dict__` (*rdflib.plugins.sparql.sparql.FrozenDict* *attribute*), 419
- `__dict__` (*rdflib.plugins.sparql.sparql.Prologue* *attribute*), 421
- `__dict__` (*rdflib.plugins.sparql.sparql.Query* *attribute*), 422
- `__dict__` (*rdflib.plugins.sparql.sparql.QueryContext* *attribute*), 422
- `__dict__` (*rdflib.plugins.sparql.sparql.Update* *attribute*), 425
- `__dict__` (*rdflib.plugins.stores.concurrent.ConcurrentStore* *attribute*), 435
- `__dict__` (*rdflib.plugins.stores.regexmatching.REGEXTerm* *attribute*), 443
- `__dict__` (*rdflib.plugins.stores.sparqlconnector.SPARQLConnector* *attribute*), 443
- `__dict__` (*rdflib.query.EncodeOnlyUnicode* *attribute*), 531
- `__dict__` (*rdflib.query.Processor* *attribute*), 531
- `__dict__` (*rdflib.query.Result* *attribute*), 532
- `__dict__` (*rdflib.query.ResultParser* *attribute*), 534
- `__dict__` (*rdflib.query.ResultRow* *attribute*), 535
- `__dict__` (*rdflib.query.ResultSerializer* *attribute*), 537
- `__dict__` (*rdflib.query.UpdateProcessor* *attribute*), 537
- `__dict__` (*rdflib.resource.Resource* *attribute*), 543
- `__dict__` (*rdflib.serializer.Serializer* *attribute*), 545
- `__dict__` (*rdflib.store.NodePickler* *attribute*), 546
- `__dict__` (*rdflib.store.Store* *attribute*), 547
- `__dict__` (*rdflib.term.IdentifiedNode* *attribute*), 554
- `__dict__` (*rdflib.tools.csv2rdf.CSV2RDF* *attribute*), 459
- `__dir__()` (*rdflib.namespace.ClosedNamespace* *method*), 141
- `__enter__()` (*rdflib.graph.BatchAddGraph* *method*), 481



- `__eq__()` (*rdflib.Graph* method), 587
- `__eq__()` (*rdflib.Literal* method), 606
- `__eq__()` (*rdflib.compare.IsomorphicGraph* method), 468
- `__eq__()` (*rdflib.extras.infixowl.Class* method), 63
- `__eq__()` (*rdflib.extras.infixowl.OWLRDFListProxy* method), 68
- `__eq__()` (*rdflib.extras.infixowl.Restriction* method), 70
- `__eq__()` (*rdflib.graph.Graph* method), 492
- `__eq__()` (*rdflib.paths.Path* method), 525
- `__eq__()` (*rdflib.query.Result* method), 533
- `__eq__()` (*rdflib.resource.Resource* method), 544
- `__eq__()` (*rdflib.term.Identifier* method), 555
- `__eq__()` (*rdflib.term.Literal* method), 559
- `__eq__()` (*rdflib.tools.graphisomorphism.IsomorphicTestableGraph* method), 460
- `__exit__()` (*rdflib.graph.BatchAddGraph* method), 481
- `__ge__()` (*rdflib.Graph* method), 588
- `__ge__()` (*rdflib.Literal* method), 607
- `__ge__()` (*rdflib.graph.Graph* method), 493
- `__ge__()` (*rdflib.paths.Path* method), 525
- `__ge__()` (*rdflib.resource.Resource* method), 544
- `__ge__()` (*rdflib.term.Identifier* method), 555
- `__ge__()` (*rdflib.term.Literal* method), 560
- `__getattr__()` (*rdflib.Namespace* method), 614
- `__getattr__()` (*rdflib.extras.infixowl.ClassNamespaceFactory* method), 64
- `__getattr__()` (*rdflib.namespace.ClosedNamespace* method), 141
- `__getattr__()` (*rdflib.namespace.Namespace* method), 157
- `__getattr__()` (*rdflib.plugins.sparql.parserutils.CompValue* method), 410
- `__getattr__()` (*rdflib.query.EncodeOnlyUnicode* method), 531
- `__getattr__()` (*rdflib.query.Result* method), 533
- `__getattr__()` (*rdflib.query.ResultRow* method), 536
- `__getitem__()` (*rdflib.Graph* method), 588
- `__getitem__()` (*rdflib.Namespace* method), 614
- `__getitem__()` (*rdflib.collection.Collection* method), 464
- `__getitem__()` (*rdflib.container.Container* method), 472
- `__getitem__()` (*rdflib.extras.infixowl.ClassNamespaceFactory* method), 64
- `__getitem__()` (*rdflib.extras.infixowl.OWLRDFListProxy* method), 68
- `__getitem__()` (*rdflib.graph.Graph* method), 493
- `__getitem__()` (*rdflib.graph.Seq* method), 514
- `__getitem__()` (*rdflib.namespace.ClosedNamespace* method), 141
- `__getitem__()` (*rdflib.namespace.Namespace* method), 157
- `__getitem__()` (*rdflib.plugins.sparql.parserutils.CompValue* method), 410
- `__getitem__()` (*rdflib.plugins.sparql.sparql.Bindings* method), 417
- `__getitem__()` (*rdflib.plugins.sparql.sparql.FrozenBindings* method), 418
- `__getitem__()` (*rdflib.plugins.sparql.sparql.FrozenDict* method), 419
- `__getitem__()` (*rdflib.plugins.sparql.sparql.QueryContext* method), 422
- `__getitem__()` (*rdflib.query.ResultRow* method), 536
- `__getitem__()` (*rdflib.resource.Resource* method), 544
- `__getnewargs__()` (*rdflib.IdentifiedNode* method), 603
- `__getnewargs__()` (*rdflib.plugins.shared.jsonld.context.Term* method), 369
- `__getnewargs__()` (*rdflib.term.IdentifiedNode* method), 555
- `__getstate__()` (*rdflib.Dataset* method), 582
- `__getstate__()` (*rdflib.Literal* method), 607
- `__getstate__()` (*rdflib.graph.Dataset* method), 488
- `__getstate__()` (*rdflib.store.NodePickler* method), 546
- `__getstate__()` (*rdflib.term.Literal* method), 560
- `__gt__()` (*rdflib.Graph* method), 588
- `__gt__()` (*rdflib.Literal* method), 607
- `__gt__()` (*rdflib.graph.Graph* method), 493
- `__gt__()` (*rdflib.paths.Path* method), 525
- `__gt__()` (*rdflib.resource.Resource* method), 544
- `__gt__()` (*rdflib.term.Identifier* method), 556
- `__gt__()` (*rdflib.term.Literal* method), 560
- `__hash__` (*rdflib.extras.infixowl.OWLRDFListProxy* attribute), 68
- `__hash__` (*rdflib.query.Result* attribute), 533
- `__hash__` (*rdflib.tools.graphisomorphism.IsomorphicTestableGraph* attribute), 460
- `__hash__()` (*rdflib.Graph* method), 588
- `__hash__()` (*rdflib.Literal* method), 607
- `__hash__()` (*rdflib.compare.IsomorphicGraph* method), 468
- `__hash__()` (*rdflib.extras.infixowl.Class* method), 63
- `__hash__()` (*rdflib.extras.infixowl.Restriction* method), 70
- `__hash__()` (*rdflib.graph.Graph* method), 493
- `__hash__()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 510
- `__hash__()` (*rdflib.paths.Path* method), 525
- `__hash__()` (*rdflib.plugins.sparql.sparql.FrozenDict* method), 419
- `__hash__()` (*rdflib.resource.Resource* method), 544
- `__hash__()` (*rdflib.term.Identifier* method), 556
- `__hash__()` (*rdflib.term.Literal* method), 561
- `__iadd__()` (*rdflib.Graph* method), 589
- `__iadd__()` (*rdflib.collection.Collection* method), 464
- `__iadd__()` (*rdflib.extras.infixowl.Class* method), 63

- `__iadd__()` (*rdflib.extras.infixowl.OWLRDFListProxy* method), 69
- `__iadd__()` (*rdflib.graph.Graph* method), 494
- `__iadd__()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 510
- `__init__()` (*rdflib.ConjunctiveGraph* method), 576
- `__init__()` (*rdflib.Dataset* method), 582
- `__init__()` (*rdflib.Graph* method), 589
- `__init__()` (*rdflib.collection.Collection* method), 464
- `__init__()` (*rdflib.compare.IsomorphicGraph* method), 468
- `__init__()` (*rdflib.container.Alt* method), 470
- `__init__()` (*rdflib.container.Bag* method), 470
- `__init__()` (*rdflib.container.Container* method), 472
- `__init__()` (*rdflib.container.NoElementException* method), 473
- `__init__()` (*rdflib.container.Seq* method), 473
- `__init__()` (*rdflib.events.Event* method), 475
- `__init__()` (*rdflib.exceptions.Error* method), 475
- `__init__()` (*rdflib.exceptions.ParserError* method), 475
- `__init__()` (*rdflib.exceptions.UniquenessError* method), 476
- `__init__()` (*rdflib.extras.describer.Describer* method), 51
- `__init__()` (*rdflib.extras.infixowl.AnnotatableTerms* method), 61
- `__init__()` (*rdflib.extras.infixowl.BooleanClass* method), 61
- `__init__()` (*rdflib.extras.infixowl.Callable* method), 62
- `__init__()` (*rdflib.extras.infixowl.Class* method), 63
- `__init__()` (*rdflib.extras.infixowl.EnumeratedClass* method), 66
- `__init__()` (*rdflib.extras.infixowl.Individual* method), 66
- `__init__()` (*rdflib.extras.infixowl.Infix* method), 67
- `__init__()` (*rdflib.extras.infixowl.MalformedClassError* method), 68
- `__init__()` (*rdflib.extras.infixowl.OWLRDFListProxy* method), 69
- `__init__()` (*rdflib.extras.infixowl.Ontology* method), 69
- `__init__()` (*rdflib.extras.infixowl.Property* method), 69
- `__init__()` (*rdflib.extras.infixowl.Restriction* method), 70
- `__init__()` (*rdflib.graph.BatchAddGraph* method), 481
- `__init__()` (*rdflib.graph.ConjunctiveGraph* method), 482
- `__init__()` (*rdflib.graph.Dataset* method), 488
- `__init__()` (*rdflib.graph.Graph* method), 494
- `__init__()` (*rdflib.graph.ModificationException* method), 508
- `__init__()` (*rdflib.graph.QuotedGraph* method), 508
- `__init__()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 510
- `__init__()` (*rdflib.graph.Seq* method), 515
- `__init__()` (*rdflib.graph.UnSupportedAggregateOperation* method), 515
- `__init__()` (*rdflib.namespace.NamespaceManager* method), 160
- `__init__()` (*rdflib.parser.FileInputSource* method), 516
- `__init__()` (*rdflib.parser.InputSource* method), 516
- `__init__()` (*rdflib.parser.Parser* method), 516
- `__init__()` (*rdflib.parser.PythonInputSource* method), 517
- `__init__()` (*rdflib.parser.StringInputSource* method), 518
- `__init__()` (*rdflib.parser.URLInputSource* method), 518
- `__init__()` (*rdflib.paths.AlternativePath* method), 522
- `__init__()` (*rdflib.paths.InvPath* method), 523
- `__init__()` (*rdflib.paths.MulPath* method), 523
- `__init__()` (*rdflib.paths.NegatedPath* method), 524
- `__init__()` (*rdflib.paths.SequencePath* method), 527
- `__init__()` (*rdflib.plugin.PKGPlugin* method), 529
- `__init__()` (*rdflib.plugin.Plugin* method), 529
- `__init__()` (*rdflib.plugins.parsers.hextr.HextuplesParser* method), 319
- `__init__()` (*rdflib.plugins.parsers.jsonld.JsonLdParser* method), 320
- `__init__()` (*rdflib.plugins.parsers.notation3.BadSyntax* method), 322
- `__init__()` (*rdflib.plugins.parsers.notation3.Formula* method), 322
- `__init__()` (*rdflib.plugins.parsers.notation3.N3Parser* method), 323
- `__init__()` (*rdflib.plugins.parsers.notation3.RDFSink* method), 324
- `__init__()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 327
- `__init__()` (*rdflib.plugins.parsers.notation3.TurtleParser* method), 335
- `__init__()` (*rdflib.plugins.parsers.ntriples.DummySink* method), 338
- `__init__()` (*rdflib.plugins.parsers.ntriples.NTGraphSink* method), 339
- `__init__()` (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser* method), 340
- `__init__()` (*rdflib.plugins.parsers.rdfxml.BagID* method), 342
- `__init__()` (*rdflib.plugins.parsers.rdfxml.ElementHandler* method), 342
- `__init__()` (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 343
- `__init__()` (*rdflib.plugins.parsers.rdfxml.RDFXMLParser* method), 348
- `__init__()` (*rdflib.plugins.parsers.trig.TrigParser* method), 348
- `__init__()` (*rdflib.plugins.parsers.trix.TriXHandler* method), 350

<code>__init__()</code> ( <code>rdflib.plugins.parsers.trix.TriXParser</code> method), 353	<code>__init__()</code> ( <code>rdflib.plugins.sparql.parserutils.Param</code> method), 411
<code>__init__()</code> ( <code>rdflib.plugins.serializers.hext.HextuplesSerializer</code> method), 353	<code>__init__()</code> ( <code>rdflib.plugins.sparql.parserutils.ParamList</code> method), 412
<code>__init__()</code> ( <code>rdflib.plugins.serializers.jsonld.JsonLDSerializer</code> method), 354	<code>__init__()</code> ( <code>rdflib.plugins.sparql.parserutils.ParamValue</code> method), 412
<code>__init__()</code> ( <code>rdflib.plugins.serializers.longturtle.LongTurtleSerializer</code> method), 355	<code>__init__()</code> ( <code>rdflib.plugins.sparql.processor.SPARQLProcessor</code> method), 414
<code>__init__()</code> ( <code>rdflib.plugins.serializers.n3.N3Serializer</code> method), 356	<code>__init__()</code> ( <code>rdflib.plugins.sparql.processor.SPARQLResult</code> method), 414
<code>__init__()</code> ( <code>rdflib.plugins.serializers.nquads.NQuadsSerializer</code> method), 357	<code>__init__()</code> ( <code>rdflib.plugins.sparql.processor.SPARQLUpdateProcessor</code> method), 415
<code>__init__()</code> ( <code>rdflib.plugins.serializers.nt.NTSerializer</code> method), 358	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.csvresults.CSVResultParser</code> method), 372
<code>__init__()</code> ( <code>rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer</code> method), 358	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.csvresults.CSVResultSerializer</code> method), 372
<code>__init__()</code> ( <code>rdflib.plugins.serializers.rdfxml.XMLSerializer</code> method), 359	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.jsonresults.JSONResult</code> method), 373
<code>__init__()</code> ( <code>rdflib.plugins.serializers.trig.TrigSerializer</code> method), 360	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.jsonresults.JSONResultSerializer</code> method), 374
<code>__init__()</code> ( <code>rdflib.plugins.serializers.trix.TriXSerializer</code> method), 360	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.rdfresults.RDFResult</code> method), 375
<code>__init__()</code> ( <code>rdflib.plugins.serializers.turtle.RecursiveSerializer</code> method), 361	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter</code> method), 377
<code>__init__()</code> ( <code>rdflib.plugins.serializers.turtle.TurtleSerializer</code> method), 362	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.xmlresults.XMLResult</code> method), 378
<code>__init__()</code> ( <code>rdflib.plugins.serializers.xmlwriter.XMLWriter</code> method), 363	<code>__init__()</code> ( <code>rdflib.plugins.sparql.results.xmlresults.XMLResultSerializer</code> method), 378
<code>__init__()</code> ( <code>rdflib.plugins.shared.jsonld.context.Context</code> method), 365	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.AlreadyBound</code> method), 416
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.Accumulator</code> method), 380	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.Bindings</code> method), 417
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.Aggregator</code> method), 381	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.FrozenBindings</code> method), 418
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.Average</code> method), 381	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.FrozenDict</code> method), 419
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.Counter</code> method), 382	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.NotBoundError</code> method), 420
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.Extremum</code> method), 383	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.Prologue</code> method), 421
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.GroupConcat</code> method), 383	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.Query</code> method), 422
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.Sample</code> method), 384	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.QueryContext</code> method), 423
<code>__init__()</code> ( <code>rdflib.plugins.sparql.aggregates.Sum</code> method), 385	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.SPARQLError</code> method), 424
<code>__init__()</code> ( <code>rdflib.plugins.sparql.algebra.StopTraversal</code> method), 387	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.SPARQLTypeError</code> method), 424
<code>__init__()</code> ( <code>rdflib.plugins.sparql.parserutils.Comp</code> method), 409	<code>__init__()</code> ( <code>rdflib.plugins.sparql.sparql.Update</code> method), 425
<code>__init__()</code> ( <code>rdflib.plugins.sparql.parserutils.CompValue</code> method), 410	<code>__init__()</code> ( <code>rdflib.plugins.stores.auditable.AuditableStore</code> method), 429
<code>__init__()</code> ( <code>rdflib.plugins.sparql.parserutils.Expr</code> method), 411	<code>__init__()</code> ( <code>rdflib.plugins.stores.berkeleydb.BerkeleyDB</code> method), 432

`__init__()` (`rdflib.plugins.stores.concurrent.ConcurrentStore` method), 417  
`__init__()` (`rdflib.plugins.stores.concurrent.ResponsibleGenerator` method), 419  
`__init__()` (`rdflib.plugins.stores.memory.Memory` method), 436  
`__init__()` (`rdflib.plugins.stores.memory.SimpleMemory` method), 439  
`__init__()` (`rdflib.plugins.stores.regexmatching.REGEXMatching` method), 441  
`__init__()` (`rdflib.plugins.stores.regexmatching.REGEXTerm` method), 443  
`__init__()` (`rdflib.plugins.stores.sparqlconnector.SPARQLConnector` method), 444  
`__init__()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 446  
`__init__()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 452  
`__init__()` (`rdflib.query.EncodeOnlyUnicode` method), 531  
`__init__()` (`rdflib.query.Processor` method), 532  
`__init__()` (`rdflib.query.Result` method), 533  
`__init__()` (`rdflib.query.ResultParser` method), 534  
`__init__()` (`rdflib.query.ResultSerializer` method), 537  
`__init__()` (`rdflib.query.UpdateProcessor` method), 537  
`__init__()` (`rdflib.resource.Resource` method), 544  
`__init__()` (`rdflib.serializer.Serializer` method), 545  
`__init__()` (`rdflib.store.NodePickler` method), 546  
`__init__()` (`rdflib.store.Store` method), 548  
`__init__()` (`rdflib.tools.csv2rdf.CSV2RDF` method), 459  
`__init__()` (`rdflib.tools.graphisomorphism.IsomorphicTestableGraph` method), 460  
`__invert__()` (`rdflib.Literal` method), 608  
`__invert__()` (`rdflib.URIRef` method), 615  
`__invert__()` (`rdflib.extras.infixowl.Class` method), 63  
`__invert__()` (`rdflib.paths.Path` method), 525  
`__invert__()` (`rdflib.term.Literal` method), 561  
`__invert__()` (`rdflib.term.URIRef` method), 567  
`__isub__()` (`rdflib.Graph` method), 589  
`__isub__()` (`rdflib.extras.infixowl.Class` method), 63  
`__isub__()` (`rdflib.graph.Graph` method), 494  
`__isub__()` (`rdflib.graph.ReadOnlyGraphAggregate` method), 510  
`__iter__()` (`rdflib.Dataset` method), 583  
`__iter__()` (`rdflib.Graph` method), 589  
`__iter__()` (`rdflib.collection.Collection` method), 464  
`__iter__()` (`rdflib.extras.infixowl.OWLRLDFListProxy` method), 69  
`__iter__()` (`rdflib.graph.Dataset` method), 488  
`__iter__()` (`rdflib.graph.Graph` method), 494  
`__iter__()` (`rdflib.graph.Seq` method), 515  
`__iter__()` (`rdflib.plugins.sparql.sparql.Bindings` method), 417  
`__iter__()` (`rdflib.plugins.sparql.sparql.FrozenDict` method), 419  
`__iter__()` (`rdflib.plugins.stores.concurrent.ConcurrentStore` method), 435  
`__iter__()` (`rdflib.plugins.stores.memory.Memory` method), 436  
`__iter__()` (`rdflib.plugins.stores.memory.SimpleMemory` method), 439  
`__iter__()` (`rdflib.plugins.stores.regexmatching.REGEXMatching` method), 442  
`__iter__()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 446  
`__iter__()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 453  
`__iter__()` (`rdflib.query.Result` method), 533  
`__iter__()` (`rdflib.store.Store` method), 548  
`__lt__()` (`rdflib.Graph` method), 589  
`__lt__()` (`rdflib.Literal` method), 608  
`__lt__()` (`rdflib.graph.Graph` method), 494  
`__lt__()` (`rdflib.paths.Path` method), 525  
`__lt__()` (`rdflib.resource.Resource` method), 544  
`__lt__()` (`rdflib.term.Identifier` method), 556  
`__len__()` (`rdflib.ConjunctiveGraph` method), 577  
`__len__()` (`rdflib.Graph` method), 589  
`__len__()` (`rdflib.collection.Collection` method), 465  
`__len__()` (`rdflib.container.Container` method), 472  
`__len__()` (`rdflib.extras.infixowl.OWLRLDFListProxy` method), 69  
`__len__()` (`rdflib.graph.ConjunctiveGraph` method), 482  
`__len__()` (`rdflib.graph.Graph` method), 494  
`__len__()` (`rdflib.graph.ReadOnlyGraphAggregate` method), 510  
`__len__()` (`rdflib.graph.Seq` method), 515  
`__len__()` (`rdflib.plugins.sparql.sparql.Bindings` method), 417  
`__len__()` (`rdflib.plugins.sparql.sparql.FrozenDict` method), 419  
`__len__()` (`rdflib.plugins.stores.auditable.AuditableStore` method), 429  
`__len__()` (`rdflib.plugins.stores.berkeleydb.BerkeleyDB` method), 432  
`__len__()` (`rdflib.plugins.stores.concurrent.ConcurrentStore` method), 435  
`__len__()` (`rdflib.plugins.stores.memory.Memory` method), 436  
`__len__()` (`rdflib.plugins.stores.memory.SimpleMemory` method), 439  
`__len__()` (`rdflib.plugins.stores.regexmatching.REGEXMatching` method), 442  
`__len__()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 446  
`__len__()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 453  
`__len__()` (`rdflib.query.Result` method), 533  
`__len__()` (`rdflib.store.Store` method), 548  
`__lt__()` (`rdflib.Graph` method), 589  
`__lt__()` (`rdflib.Literal` method), 608  
`__lt__()` (`rdflib.graph.Graph` method), 494  
`__lt__()` (`rdflib.paths.Path` method), 525  
`__lt__()` (`rdflib.resource.Resource` method), 544  
`__lt__()` (`rdflib.term.Identifier` method), 556



- `__lt__()` (*rdflib.term.Literal* method), 562
- `__matmul__()` (*rdflib.extras.infixowl.Infix* method), 67
- `__mod__()` (*rdflib.URIRef* method), 616
- `__mod__()` (*rdflib.term.URIRef* method), 567
- `__module__` (*examples.secure\_with\_urlopen.SecuredHTTPHandler* attribute), 26
- `__module__` (*rdflib.BNode* attribute), 575
- `__module__` (*rdflib.ConjunctiveGraph* attribute), 577
- `__module__` (*rdflib.Dataset* attribute), 583
- `__module__` (*rdflib.Graph* attribute), 590
- `__module__` (*rdflib.IdentifiedNode* attribute), 603
- `__module__` (*rdflib.Literal* attribute), 609
- `__module__` (*rdflib.Namespace* attribute), 614
- `__module__` (*rdflib.URIRef* attribute), 616
- `__module__` (*rdflib.Variable* attribute), 617
- `__module__` (*rdflib.collection.Collection* attribute), 465
- `__module__` (*rdflib.compare.IsomorphicGraph* attribute), 468
- `__module__` (*rdflib.container.Alt* attribute), 470
- `__module__` (*rdflib.container.Bag* attribute), 470
- `__module__` (*rdflib.container.Container* attribute), 472
- `__module__` (*rdflib.container.NoElementException* attribute), 473
- `__module__` (*rdflib.container.Seq* attribute), 473
- `__module__` (*rdflib.events.Dispatcher* attribute), 474
- `__module__` (*rdflib.events.Event* attribute), 475
- `__module__` (*rdflib.exceptions.Error* attribute), 475
- `__module__` (*rdflib.exceptions.ParserError* attribute), 475
- `__module__` (*rdflib.exceptions.UniquenessError* attribute), 476
- `__module__` (*rdflib.extras.describer.Describer* attribute), 51
- `__module__` (*rdflib.extras.infixowl.AnnotatableTerms* attribute), 61
- `__module__` (*rdflib.extras.infixowl.BooleanClass* attribute), 61
- `__module__` (*rdflib.extras.infixowl.Callable* attribute), 62
- `__module__` (*rdflib.extras.infixowl.Class* attribute), 63
- `__module__` (*rdflib.extras.infixowl.ClassNamespaceFactory* attribute), 64
- `__module__` (*rdflib.extras.infixowl.EnumeratedClass* attribute), 66
- `__module__` (*rdflib.extras.infixowl.Individual* attribute), 67
- `__module__` (*rdflib.extras.infixowl.Infix* attribute), 68
- `__module__` (*rdflib.extras.infixowl.MalformedClass* attribute), 68
- `__module__` (*rdflib.extras.infixowl.MalformedClassError* attribute), 68
- `__module__` (*rdflib.extras.infixowl.OWLRDFListProxy* attribute), 69
- `__module__` (*rdflib.extras.infixowl.Ontology* attribute), 69
- `__module__` (*rdflib.extras.infixowl.Property* attribute), 69
- `__module__` (*rdflib.extras.infixowl.Restriction* attribute), 71
- `__module__` (*rdflib.graph.BatchAddGraph* attribute), 481
- `__module__` (*rdflib.graph.ConjunctiveGraph* attribute), 482
- `__module__` (*rdflib.graph.Dataset* attribute), 488
- `__module__` (*rdflib.graph.Graph* attribute), 495
- `__module__` (*rdflib.graph.ModificationException* attribute), 508
- `__module__` (*rdflib.graph.QuotedGraph* attribute), 508
- `__module__` (*rdflib.graph.ReadOnlyGraphAggregate* attribute), 510
- `__module__` (*rdflib.graph.Seq* attribute), 515
- `__module__` (*rdflib.graph.UnSupportedAggregateOperation* attribute), 515
- `__module__` (*rdflib.namespace.ClosedNamespace* attribute), 141
- `__module__` (*rdflib.namespace.Namespace* attribute), 157
- `__module__` (*rdflib.namespace.NamespaceManager* attribute), 160
- `__module__` (*rdflib.parser.FileInputSource* attribute), 516
- `__module__` (*rdflib.parser.InputSource* attribute), 516
- `__module__` (*rdflib.parser.Parser* attribute), 516
- `__module__` (*rdflib.parser.PythonInputSource* attribute), 517
- `__module__` (*rdflib.parser.StringInputSource* attribute), 518
- `__module__` (*rdflib.parser.URLInputSource* attribute), 518
- `__module__` (*rdflib.paths.AlternativePath* attribute), 522
- `__module__` (*rdflib.paths.InvPath* attribute), 523
- `__module__` (*rdflib.paths.MulPath* attribute), 523
- `__module__` (*rdflib.paths.NegatedPath* attribute), 524
- `__module__` (*rdflib.paths.Path* attribute), 525
- `__module__` (*rdflib.paths.PathList* attribute), 526
- `__module__` (*rdflib.paths.SequencePath* attribute), 527
- `__module__` (*rdflib.plugin.PKGPlugin* attribute), 529
- `__module__` (*rdflib.plugin.Plugin* attribute), 530
- `__module__` (*rdflib.plugin.PluginException* attribute), 530
- `__module__` (*rdflib.plugin.PluginT* attribute), 530
- `__module__` (*rdflib.plugins.parsers.hexst.HexuplesParser* attribute), 320
- `__module__` (*rdflib.plugins.parsers.jsonld.JsonLDParser* attribute), 321
- `__module__` (*rdflib.plugins.parsers.notation3.BadSyntax* attribute), 322
- `__module__` (*rdflib.plugins.parsers.notation3.Formula* attribute), 322

<code>__module__</code> ( <i>rdflib.plugins.parsers.notation3.N3Parser</i> attribute), 323	<code>__module__</code> ( <i>rdflib.plugins.serializers.turtle.RecursiveSerializer</i> attribute), 361
<code>__module__</code> ( <i>rdflib.plugins.parsers.notation3.RDFSink</i> attribute), 324	<code>__module__</code> ( <i>rdflib.plugins.serializers.turtle.TurtleSerializer</i> attribute), 362
<code>__module__</code> ( <i>rdflib.plugins.parsers.notation3.SinkParser</i> attribute), 328	<code>__module__</code> ( <i>rdflib.plugins.serializers.xmlwriter.XMLWriter</i> attribute), 363
<code>__module__</code> ( <i>rdflib.plugins.parsers.notation3.TurtleParser</i> attribute), 335	<code>__module__</code> ( <i>rdflib.plugins.shared.jsonld.context.Context</i> attribute), 365
<code>__module__</code> ( <i>rdflib.plugins.parsers.nquads.NQuadsParser</i> attribute), 338	<code>__module__</code> ( <i>rdflib.plugins.shared.jsonld.context.Defined</i> attribute), 369
<code>__module__</code> ( <i>rdflib.plugins.parsers.ntriples.DummySink</i> attribute), 339	<code>__module__</code> ( <i>rdflib.plugins.shared.jsonld.context.Term</i> attribute), 369
<code>__module__</code> ( <i>rdflib.plugins.parsers.ntriples.NTGraphSink</i> attribute), 339	<code>__module__</code> ( <i>rdflib.plugins.shared.jsonld.errors.JSONLDError</i> attribute), 370
<code>__module__</code> ( <i>rdflib.plugins.parsers.ntriples.NTParser</i> attribute), 339	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Accumulator</i> attribute), 380
<code>__module__</code> ( <i>rdflib.plugins.parsers.ntriples.W3CNTriplesParser</i> attribute), 340	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Aggregator</i> attribute), 381
<code>__module__</code> ( <i>rdflib.plugins.parsers.rdfxml.BagID</i> attribute), 342	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Average</i> attribute), 381
<code>__module__</code> ( <i>rdflib.plugins.parsers.rdfxml.ElementHandler</i> attribute), 342	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Counter</i> attribute), 382
<code>__module__</code> ( <i>rdflib.plugins.parsers.rdfxml.RDFXMLHandler</i> attribute), 343	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Extremum</i> attribute), 383
<code>__module__</code> ( <i>rdflib.plugins.parsers.rdfxml.RDFXMLParser</i> attribute), 348	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.GroupConcat</i> attribute), 383
<code>__module__</code> ( <i>rdflib.plugins.parsers.trig.TrigParser</i> attribute), 348	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Maximum</i> attribute), 384
<code>__module__</code> ( <i>rdflib.plugins.parsers.trig.TrigSinkParser</i> attribute), 349	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Minimum</i> attribute), 384
<code>__module__</code> ( <i>rdflib.plugins.parsers.trix.TriXHandler</i> attribute), 350	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Sample</i> attribute), 384
<code>__module__</code> ( <i>rdflib.plugins.parsers.trix.TriXParser</i> attribute), 353	<code>__module__</code> ( <i>rdflib.plugins.sparql.aggregates.Sum</i> attribute), 385
<code>__module__</code> ( <i>rdflib.plugins.serializers.hext.HextuplesSerializer</i> attribute), 353	<code>__module__</code> ( <i>rdflib.plugins.sparql.algebra.ExpressionNotCoveredException</i> attribute), 386
<code>__module__</code> ( <i>rdflib.plugins.serializers.jsonld.JsonLDSerializer</i> attribute), 355	<code>__module__</code> ( <i>rdflib.plugins.sparql.algebra.StopTraversal</i> attribute), 387
<code>__module__</code> ( <i>rdflib.plugins.serializers.longturtle.LongTurtleSerializer</i> attribute), 355	<code>__module__</code> ( <i>rdflib.plugins.sparql.parserutils.Comp</i> attribute), 410
<code>__module__</code> ( <i>rdflib.plugins.serializers.n3.N3Serializer</i> attribute), 356	<code>__module__</code> ( <i>rdflib.plugins.sparql.parserutils.CompValue</i> attribute), 410
<code>__module__</code> ( <i>rdflib.plugins.serializers.nquads.NQuadsSerializer</i> attribute), 357	<code>__module__</code> ( <i>rdflib.plugins.sparql.parserutils.Expr</i> attribute), 411
<code>__module__</code> ( <i>rdflib.plugins.serializers.nt.NTSerializer</i> attribute), 358	<code>__module__</code> ( <i>rdflib.plugins.sparql.parserutils.Param</i> attribute), 411
<code>__module__</code> ( <i>rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer</i> attribute), 358	<code>__module__</code> ( <i>rdflib.plugins.sparql.parserutils.ParamList</i> attribute), 412
<code>__module__</code> ( <i>rdflib.plugins.serializers.rdfxml.XMLSerializer</i> attribute), 359	<code>__module__</code> ( <i>rdflib.plugins.sparql.parserutils.ParamValue</i> attribute), 413
<code>__module__</code> ( <i>rdflib.plugins.serializers.trig.TrigSerializer</i> attribute), 360	<code>__module__</code> ( <i>rdflib.plugins.sparql.processor.SPARQLProcessor</i> attribute), 414
<code>__module__</code> ( <i>rdflib.plugins.serializers.trix.TriXSerializer</i> attribute), 361	<code>__module__</code> ( <i>rdflib.plugins.sparql.processor.SPARQLResult</i> attribute), 414

---

<code>__module__</code> (rdflib.plugins.sparql.processor.SPARQLUpdateProcessor attribute), 415	<code>__module__</code> (rdflib.plugins.stores.berkeleydb.BerkeleyDB attribute), 433
<code>__module__</code> (rdflib.plugins.sparql.results.csvresults.CSVResultModule attribute), 372	<code>__module__</code> (rdflib.plugins.stores.concurrent.ConcurrentStore attribute), 435
<code>__module__</code> (rdflib.plugins.sparql.results.csvresults.CSVResultModule attribute), 372	<code>__module__</code> (rdflib.plugins.stores.concurrent.ResponsibleGenerator attribute), 436
<code>__module__</code> (rdflib.plugins.sparql.results.graph.GraphResultModule attribute), 373	<code>__module__</code> (rdflib.plugins.stores.memory.Memory attribute), 436
<code>__module__</code> (rdflib.plugins.sparql.results.jsonresults.JSONResultModule attribute), 373	<code>__module__</code> (rdflib.plugins.stores.memory.SimpleMemory attribute), 439
<code>__module__</code> (rdflib.plugins.sparql.results.jsonresults.JSONResultModule attribute), 373	<code>__module__</code> (rdflib.plugins.stores.regexmatching.REGEXMatching attribute), 442
<code>__module__</code> (rdflib.plugins.sparql.results.jsonresults.JSONResultModule attribute), 374	<code>__module__</code> (rdflib.plugins.stores.regexmatching.REGEXTerm attribute), 443
<code>__module__</code> (rdflib.plugins.sparql.results.rdfresults.RDFResultModule attribute), 375	<code>__module__</code> (rdflib.plugins.stores.sparqlconnector.SPARQLConnector attribute), 444
<code>__module__</code> (rdflib.plugins.sparql.results.rdfresults.RDFResultModule attribute), 375	<code>__module__</code> (rdflib.plugins.stores.sparqlconnector.SPARQLConnectorException attribute), 444
<code>__module__</code> (rdflib.plugins.sparql.results.tsvresults.TSVResultModule attribute), 375	<code>__module__</code> (rdflib.plugins.stores.sparqlstore.SPARQLStore attribute), 446
<code>__module__</code> (rdflib.plugins.sparql.results.txtresults.TXTResultModule attribute), 376	<code>__module__</code> (rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore attribute), 453
<code>__module__</code> (rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter attribute), 377	<code>__module__</code> (rdflib.query.EncodeOnlyUnicode attribute), 531
<code>__module__</code> (rdflib.plugins.sparql.results.xmlresults.XMLResultModule attribute), 378	<code>__module__</code> (rdflib.query.Processor attribute), 532
<code>__module__</code> (rdflib.plugins.sparql.results.xmlresults.XMLResultModule attribute), 378	<code>__module__</code> (rdflib.query.Result attribute), 533
<code>__module__</code> (rdflib.plugins.sparql.results.xmlresults.XMLResultModule attribute), 378	<code>__module__</code> (rdflib.query.ResultException attribute), 534
<code>__module__</code> (rdflib.plugins.sparql.results.xmlresults.XMLResultModule attribute), 378	<code>__module__</code> (rdflib.query.ResultParser attribute), 535
<code>__module__</code> (rdflib.plugins.sparql.sparql.AlreadyBound attribute), 416	<code>__module__</code> (rdflib.query.ResultRow attribute), 536
<code>__module__</code> (rdflib.plugins.sparql.sparql.Bindings attribute), 417	<code>__module__</code> (rdflib.query.ResultSerializer attribute), 537
<code>__module__</code> (rdflib.plugins.sparql.sparql.FrozenBindings attribute), 418	<code>__module__</code> (rdflib.query.UpdateProcessor attribute), 538
<code>__module__</code> (rdflib.plugins.sparql.sparql.FrozenDict attribute), 420	<code>__module__</code> (rdflib.resource.Resource attribute), 544
<code>__module__</code> (rdflib.plugins.sparql.sparql.NotBoundError attribute), 421	<code>__module__</code> (rdflib.serializer.Serializer attribute), 546
<code>__module__</code> (rdflib.plugins.sparql.sparql.Prologue attribute), 421	<code>__module__</code> (rdflib.store.NodePickler attribute), 546
<code>__module__</code> (rdflib.plugins.sparql.sparql.Query attribute), 422	<code>__module__</code> (rdflib.store.Store attribute), 548
<code>__module__</code> (rdflib.plugins.sparql.sparql.QueryContext attribute), 423	<code>__module__</code> (rdflib.store.StoreCreatedEvent attribute), 552
<code>__module__</code> (rdflib.plugins.sparql.sparql.SPARQLError attribute), 424	<code>__module__</code> (rdflib.store.TripleAddedEvent attribute), 553
<code>__module__</code> (rdflib.plugins.sparql.sparql.SPARQLTypeError attribute), 425	<code>__module__</code> (rdflib.store.TripleRemovedEvent attribute), 553
<code>__module__</code> (rdflib.plugins.sparql.sparql.Update attribute), 425	<code>__module__</code> (rdflib.term.BNode attribute), 553
<code>__module__</code> (rdflib.plugins.stores.auditable.AuditableStore attribute), 429	<code>__module__</code> (rdflib.term.IdentifiedNode attribute), 555
	<code>__module__</code> (rdflib.term.Identifier attribute), 556
	<code>__module__</code> (rdflib.term.Literal attribute), 562
	<code>__module__</code> (rdflib.term.Node attribute), 566
	<code>__module__</code> (rdflib.term.URIRef attribute), 567
	<code>__module__</code> (rdflib.term.Variable attribute), 569
	<code>__module__</code> (rdflib.tools.csv2rdf.CSV2RDF attribute), 459
	<code>__module__</code> (rdflib.tools.graphisomorphism.IsomorphicTestableGraph attribute), 460

- `__mul__()` (*rdflib.Graph* method), 590
- `__mul__()` (*rdflib.URIRef* method), 616
- `__mul__()` (*rdflib.graph.Graph* method), 495
- `__mul__()` (*rdflib.paths.Path* method), 525
- `__mul__()` (*rdflib.term.URIRef* method), 567
- `__ne__()` (*rdflib.compare.IsomorphicGraph* method), 468
- `__ne__()` (*rdflib.resource.Resource* method), 544
- `__ne__()` (*rdflib.term.Identifier* method), 556
- `__ne__()` (*rdflib.tools.graphisomorphism.IsomorphicTestableGraph* method), 460
- `__neg__()` (*rdflib.Literal* method), 609
- `__neg__()` (*rdflib.URIRef* method), 616
- `__neg__()` (*rdflib.paths.Path* method), 526
- `__neg__()` (*rdflib.term.Literal* method), 562
- `__neg__()` (*rdflib.term.URIRef* method), 567
- `__new__()` (*rdflib.BNode* static method), 575
- `__new__()` (*rdflib.Literal* static method), 609
- `__new__()` (*rdflib.Namespace* static method), 614
- `__new__()` (*rdflib.URIRef* static method), 616
- `__new__()` (*rdflib.Variable* static method), 617
- `__new__()` (*rdflib.namespace.ClosedNamespace* static method), 141
- `__new__()` (*rdflib.namespace.Namespace* static method), 157
- `__new__()` (*rdflib.plugins.shared.jsonld.context.Term* static method), 369
- `__new__()` (*rdflib.query.ResultRow* static method), 536
- `__new__()` (*rdflib.term.BNode* static method), 553
- `__new__()` (*rdflib.term.Identifier* static method), 556
- `__new__()` (*rdflib.term.Literal* static method), 563
- `__new__()` (*rdflib.term.URIRef* static method), 568
- `__new__()` (*rdflib.term.Variable* static method), 569
- `__next__()` (*rdflib.plugins.stores.concurrent.ResponsibleGenerator* method), 436
- `__or__()` (*rdflib.Graph* method), 590
- `__or__()` (*rdflib.URIRef* method), 616
- `__or__()` (*rdflib.extras.infixowl.BooleanClass* method), 61
- `__or__()` (*rdflib.extras.infixowl.Class* method), 63
- `__or__()` (*rdflib.graph.Graph* method), 495
- `__or__()` (*rdflib.paths.Path* method), 526
- `__or__()` (*rdflib.term.URIRef* method), 568
- `__orig_bases__` (*rdflib.plugin.PKGPlugin* attribute), 529
- `__orig_bases__` (*rdflib.plugin.Plugin* attribute), 530
- `__orig_bases__` (*rdflib.query.ResultRow* attribute), 536
- `__parameters__` (*rdflib.plugin.PKGPlugin* attribute), 529
- `__parameters__` (*rdflib.plugin.Plugin* attribute), 530
- `__parameters__` (*rdflib.query.ResultRow* attribute), 536
- `__pos__()` (*rdflib.Literal* method), 609
- `__pos__()` (*rdflib.term.Literal* method), 563
- `__radd__()` (*rdflib.URIRef* method), 616
- `__radd__()` (*rdflib.term.URIRef* method), 568
- `__reduce__()` (*rdflib.BNode* method), 575
- `__reduce__()` (*rdflib.ConjunctiveGraph* method), 577
- `__reduce__()` (*rdflib.Dataset* method), 583
- `__reduce__()` (*rdflib.Graph* method), 590
- `__reduce__()` (*rdflib.Literal* method), 610
- `__reduce__()` (*rdflib.URIRef* method), 616
- `__reduce__()` (*rdflib.Variable* method), 618
- `__reduce__()` (*rdflib.graph.ConjunctiveGraph* method), 577
- `__reduce__()` (*rdflib.graph.Dataset* method), 488
- `__reduce__()` (*rdflib.graph.Graph* method), 495
- `__reduce__()` (*rdflib.graph.QuotedGraph* method), 508
- `__reduce__()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 510
- `__reduce__()` (*rdflib.plugins.stores.regexmatching.REGEXTerm* method), 443
- `__reduce__()` (*rdflib.term.BNode* method), 554
- `__reduce__()` (*rdflib.term.Literal* method), 563
- `__reduce__()` (*rdflib.term.URIRef* method), 568
- `__reduce__()` (*rdflib.term.Variable* method), 569
- `__repr__()` (*rdflib.BNode* method), 575
- `__repr__()` (*rdflib.Graph* method), 590
- `__repr__()` (*rdflib.Literal* method), 610
- `__repr__()` (*rdflib.Namespace* method), 615
- `__repr__()` (*rdflib.URIRef* method), 617
- `__repr__()` (*rdflib.Variable* method), 618
- `__repr__()` (*rdflib.events.Event* method), 475
- `__repr__()` (*rdflib.extras.infixowl.BooleanClass* method), 61
- `__repr__()` (*rdflib.extras.infixowl.Class* method), 63
- `__repr__()` (*rdflib.extras.infixowl.EnumeratedClass* method), 66
- `__repr__()` (*rdflib.extras.infixowl.MalformedClassError* method), 68
- `__repr__()` (*rdflib.extras.infixowl.Property* method), 69
- `__repr__()` (*rdflib.extras.infixowl.Restriction* method), 71
- `__repr__()` (*rdflib.graph.Graph* method), 495
- `__repr__()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 510
- `__repr__()` (*rdflib.namespace.ClosedNamespace* method), 142
- `__repr__()` (*rdflib.namespace.Namespace* method), 157
- `__repr__()` (*rdflib.parser.FileInputSource* method), 516
- `__repr__()` (*rdflib.parser.URLInputSource* method), 518
- `__repr__()` (*rdflib.paths.AlternativePath* method), 522
- `__repr__()` (*rdflib.paths.InvPath* method), 523
- `__repr__()` (*rdflib.paths.MulPath* method), 524
- `__repr__()` (*rdflib.paths.NegatedPath* method), 524
- `__repr__()` (*rdflib.paths.SequencePath* method), 527
- `__repr__()` (*rdflib.plugins.shared.jsonld.context.Term* method), 369



- `__repr__` () (*rdflib.plugins.sparql.parserutils.CompValue* method), 410
- `__repr__` () (*rdflib.plugins.sparql.sparql.Bindings* method), 417
- `__repr__` () (*rdflib.plugins.sparql.sparql.FrozenDict* method), 420
- `__repr__` () (*rdflib.resource.Resource* method), 544
- `__repr__` () (*rdflib.term.BNode* method), 554
- `__repr__` () (*rdflib.term.Literal* method), 563
- `__repr__` () (*rdflib.term.URIRef* method), 568
- `__repr__` () (*rdflib.term.Variable* method), 569
- `__rlshift__` () (*rdflib.extras.infixowl.Infix* method), 68
- `__rmatmul__` () (*rdflib.extras.infixowl.Infix* method), 68
- `__rshift__` () (*rdflib.extras.infixowl.Infix* method), 68
- `__setitem__` () (*rdflib.collection.Collection* method), 465
- `__setitem__` () (*rdflib.container.Container* method), 472
- `__setitem__` () (*rdflib.extras.infixowl.OWLRDFListProxy* method), 69
- `__setitem__` () (*rdflib.plugins.sparql.sparql.Bindings* method), 417
- `__setitem__` () (*rdflib.plugins.sparql.sparql.QueryContext* method), 423
- `__setitem__` () (*rdflib.resource.Resource* method), 544
- `__setstate__` () (*rdflib.Dataset* method), 583
- `__setstate__` () (*rdflib.Literal* method), 610
- `__setstate__` () (*rdflib.graph.Dataset* method), 488
- `__setstate__` () (*rdflib.store.NodePickler* method), 546
- `__setstate__` () (*rdflib.term.Literal* method), 563
- `__slotnames__` (*rdflib.plugins.sparql.parserutils.Comp* attribute), 410
- `__slotnames__` (*rdflib.plugins.sparql.parserutils.Param* attribute), 412
- `__slots__` (*rdflib.BNode* attribute), 576
- `__slots__` (*rdflib.Literal* attribute), 610
- `__slots__` (*rdflib.URIRef* attribute), 617
- `__slots__` (*rdflib.Variable* attribute), 618
- `__slots__` (*rdflib.parser.Parser* attribute), 516
- `__slots__` (*rdflib.plugins.parsers.ntriples.NTGraphSink* attribute), 339
- `__slots__` (*rdflib.plugins.parsers.ntriples.NTParser* attribute), 339
- `__slots__` (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser* attribute), 340
- `__slots__` (*rdflib.plugins.parsers.rdfxml.BagID* attribute), 342
- `__slots__` (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342
- `__slots__` (*rdflib.plugins.shared.jsonld.context.Term* attribute), 369
- `__slots__` (*rdflib.plugins.stores.concurrent.ResponsibleGenerator* attribute), 436
- `__slots__` (*rdflib.term.BNode* attribute), 554
- `__slots__` (*rdflib.term.Identifier* attribute), 556
- `__slots__` (*rdflib.term.Literal* attribute), 563
- `__slots__` (*rdflib.term.Node* attribute), 566
- `__slots__` (*rdflib.term.URIRef* attribute), 568
- `__slots__` (*rdflib.term.Variable* attribute), 569
- `__str__` () (*rdflib.ConjunctiveGraph* method), 577
- `__str__` () (*rdflib.Dataset* method), 583
- `__str__` () (*rdflib.Graph* method), 590
- `__str__` () (*rdflib.container.NoElementException* method), 473
- `__str__` () (*rdflib.exceptions.ParserError* method), 475
- `__str__` () (*rdflib.graph.ConjunctiveGraph* method), 482
- `__str__` () (*rdflib.graph.Dataset* method), 488
- `__str__` () (*rdflib.graph.Graph* method), 495
- `__str__` () (*rdflib.graph.ModificationException* method), 508
- `__str__` () (*rdflib.graph.QuotedGraph* method), 509
- `__str__` () (*rdflib.graph.UnSupportedAggregateOperation* method), 515
- `__str__` () (*rdflib.plugins.parsers.notation3.BadSyntax* method), 322
- `__str__` () (*rdflib.plugins.parsers.notation3.Formula* method), 323
- `__str__` () (*rdflib.plugins.sparql.parserutils.CompValue* method), 410
- `__str__` () (*rdflib.plugins.sparql.parserutils.ParamValue* method), 413
- `__str__` () (*rdflib.plugins.sparql.sparql.Bindings* method), 417
- `__str__` () (*rdflib.plugins.sparql.sparql.FrozenDict* method), 420
- `__str__` () (*rdflib.resource.Resource* method), 545
- `__sub__` () (*rdflib.Graph* method), 590
- `__sub__` () (*rdflib.Literal* method), 610
- `__sub__` () (*rdflib.graph.Graph* method), 495
- `__sub__` () (*rdflib.term.Literal* method), 564
- `__truediv__` () (*rdflib.URIRef* method), 617
- `__truediv__` () (*rdflib.paths.Path* method), 526
- `__truediv__` () (*rdflib.term.URIRef* method), 568
- `__unicode__` () (*rdflib.resource.Resource* method), 545
- `__weakref__` (*rdflib.Graph* attribute), 590
- `__weakref__` (*rdflib.IdentifiedNode* attribute), 603
- `__weakref__` (*rdflib.Namespace* attribute), 615
- `__weakref__` (*rdflib.collection.Collection* attribute), 465
- `__weakref__` (*rdflib.container.Container* attribute), 472
- `__weakref__` (*rdflib.container.NoElementException* attribute), 473
- `__weakref__` (*rdflib.events.Dispatcher* attribute), 474
- `__weakref__` (*rdflib.events.Event* attribute), 475
- `__weakref__` (*rdflib.exceptions.Error* attribute), 475
- `__weakref__` (*rdflib.extras.describer.Describer* attribute), 51

- `__weakref__` (`rdflib.extras.infixowl.Callable` attribute), 62
- `__weakref__` (`rdflib.extras.infixowl.Individual` attribute), 67
- `__weakref__` (`rdflib.extras.infixowl.Infix` attribute), 68
- `__weakref__` (`rdflib.extras.infixowl.MalformedClass` attribute), 68
- `__weakref__` (`rdflib.extras.infixowl.OWLRDFListProxy` attribute), 69
- `__weakref__` (`rdflib.graph.BatchAddGraph` attribute), 481
- `__weakref__` (`rdflib.graph.Graph` attribute), 495
- `__weakref__` (`rdflib.graph.ModificationException` attribute), 508
- `__weakref__` (`rdflib.graph.Seq` attribute), 515
- `__weakref__` (`rdflib.graph.UnSupportedAggregateOperation` attribute), 515
- `__weakref__` (`rdflib.namespace.Namespace` attribute), 157
- `__weakref__` (`rdflib.namespace.NamespaceManager` attribute), 160
- `__weakref__` (`rdflib.paths.Path` attribute), 526
- `__weakref__` (`rdflib.paths.PathList` attribute), 526
- `__weakref__` (`rdflib.plugin.Plugin` attribute), 530
- `__weakref__` (`rdflib.plugins.parsers.hext.HextuplesParser` attribute), 320
- `__weakref__` (`rdflib.plugins.parsers.jsonld.JsonLDParse` attribute), 321
- `__weakref__` (`rdflib.plugins.parsers.notation3.BadSyntax` attribute), 322
- `__weakref__` (`rdflib.plugins.parsers.notation3.Formula` attribute), 323
- `__weakref__` (`rdflib.plugins.parsers.notation3.RDFSink` attribute), 324
- `__weakref__` (`rdflib.plugins.parsers.notation3.SinkParser` attribute), 328
- `__weakref__` (`rdflib.plugins.parsers.notation3.TurtleParser` attribute), 335
- `__weakref__` (`rdflib.plugins.parsers.nquads.NQuadsParser` attribute), 338
- `__weakref__` (`rdflib.plugins.parsers.ntriples.DummySink` attribute), 339
- `__weakref__` (`rdflib.plugins.parsers.rdfxml.RDFXMLParser` attribute), 348
- `__weakref__` (`rdflib.plugins.parsers.trig.TrigParser` attribute), 348
- `__weakref__` (`rdflib.plugins.parsers.trix.TriXParser` attribute), 353
- `__weakref__` (`rdflib.plugins.serializers.xmlwriter.XMLWriter` attribute), 363
- `__weakref__` (`rdflib.plugins.shared.jsonld.context.Context` attribute), 365
- `__weakref__` (`rdflib.plugins.shared.jsonld.errors.JSONLDError` attribute), 370
- `__weakref__` (`rdflib.plugins.sparql.aggregates.Accumulator` attribute), 380
- `__weakref__` (`rdflib.plugins.sparql.aggregates.Aggregator` attribute), 381
- `__weakref__` (`rdflib.plugins.sparql.algebra.ExpressionNotCoveredException` attribute), 386
- `__weakref__` (`rdflib.plugins.sparql.algebra.StopTraversal` attribute), 388
- `__weakref__` (`rdflib.plugins.sparql.parserutils.ParamValue` attribute), 413
- `__weakref__` (`rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter` attribute), 377
- `__weakref__` (`rdflib.plugins.sparql.sparql.Bindings` attribute), 417
- `__weakref__` (`rdflib.plugins.sparql.sparql.FrozenDict` attribute), 420
- `__weakref__` (`rdflib.plugins.sparql.sparql.Prologue` attribute), 421
- `__weakref__` (`rdflib.plugins.sparql.sparql.Query` attribute), 422
- `__weakref__` (`rdflib.plugins.sparql.sparql.QueryContext` attribute), 423
- `__weakref__` (`rdflib.plugins.sparql.sparql.SPARQLError` attribute), 424
- `__weakref__` (`rdflib.plugins.sparql.sparql.Update` attribute), 425
- `__weakref__` (`rdflib.plugins.stores.concurrent.ConcurrentStore` attribute), 435
- `__weakref__` (`rdflib.plugins.stores.regexmatching.REGEXTerm` attribute), 443
- `__weakref__` (`rdflib.plugins.stores.sparqlconnector.SPARQLConnector` attribute), 444
- `__weakref__` (`rdflib.plugins.stores.sparqlconnector.SPARQLConnectorException` attribute), 444
- `__weakref__` (`rdflib.query.EncodeOnlyUnicode` attribute), 531
- `__weakref__` (`rdflib.query.Processor` attribute), 532
- `__weakref__` (`rdflib.query.Result` attribute), 533
- `__weakref__` (`rdflib.query.ResultException` attribute), 534
- `__weakref__` (`rdflib.query.ResultParser` attribute), 535
- `__weakref__` (`rdflib.query.ResultSerializer` attribute), 537
- `__weakref__` (`rdflib.query.UpdateProcessor` attribute), 538
- `__weakref__` (`rdflib.resource.Resource` attribute), 545
- `__weakref__` (`rdflib.serializer.Serializer` attribute), 546
- `__weakref__` (`rdflib.store.NodePickler` attribute), 547
- `__weakref__` (`rdflib.store.Store` attribute), 548
- `__weakref__` (`rdflib.term.IdentifiedNode` attribute), 555
- `__weakref__` (`rdflib.tools.csv2rdf.CSV2RDF` attribute), 459
- `__xor__` (`rdflib.Graph` method), 590
- `__xor__` (`rdflib.graph.Graph` method), 495

`_castLexicalToPython()` (in module `rdflib.term`), 36  
`_castPythonToLiteral()` (in module `rdflib.term`), 35

## A

Abdomen (`rdflib.namespace.SDO` attribute), 189

Ablutions\_Room (`rdflib.namespace.BRICK` attribute), 73

about (`rdflib.namespace.SDO` attribute), 241

about (`rdflib.plugins.parsers.RDFVOC.RDFVOC` attribute), 319

about() (`rdflib.extras.describer.Describer` method), 51

AboutPage (`rdflib.namespace.SDO` attribute), 189

aboutUrl (`rdflib.namespace.CSVW` attribute), 138

abridged (`rdflib.namespace.SDO` attribute), 241

absolutePosition (`rdflib.namespace.ODRL2` attribute), 164

absoluteSize (`rdflib.namespace.ODRL2` attribute), 164

absoluteSpatialPosition (`rdflib.namespace.ODRL2` attribute), 164

absoluteTemporalPosition (`rdflib.namespace.ODRL2` attribute), 164

absolutize() (`rdflib.Graph` method), 591

absolutize() (`rdflib.graph.Graph` method), 496

absolutize() (`rdflib.graph.ReadOnlyGraphAggregate` method), 511

absolutize() (`rdflib.namespace.NamespaceManager` method), 160

absolutize() (`rdflib.plugins.parsers.rdfxml.RDFXMLHandler` method), 343

absolutize() (`rdflib.plugins.sparql.sparql.Prologue` method), 421

Absorption\_Chiller (`rdflib.namespace.BRICK` attribute), 73

abstract (`rdflib.namespace.DCTERMS` attribute), 147

abstract (`rdflib.namespace.SDO` attribute), 241

AbstractResult (`rdflib.namespace.SH` attribute), 297

Acceleration\_Time\_Setpoint (`rdflib.namespace.BRICK` attribute), 73

accelerationTime (`rdflib.namespace.SDO` attribute), 241

Accept (`rdflib.namespace.PROV` attribute), 178

AcceptAction (`rdflib.namespace.SDO` attribute), 189

acceptedAnswer (`rdflib.namespace.SDO` attribute), 241

acceptedOffer (`rdflib.namespace.SDO` attribute), 241

acceptedPaymentMethod (`rdflib.namespace.SDO` attribute), 241

acceptsReservations (`rdflib.namespace.SDO` attribute), 241

acceptTracking (`rdflib.namespace.ODRL2` attribute), 164

Access\_Control\_Equipment (`rdflib.namespace.BRICK` attribute), 74

Access\_Reader (`rdflib.namespace.BRICK` attribute), 74

accessCode (`rdflib.namespace.SDO` attribute), 242

accessibilityAPI (`rdflib.namespace.SDO` attribute), 242

accessibilityControl (`rdflib.namespace.SDO` attribute), 242

accessibilityFeature (`rdflib.namespace.SDO` attribute), 242

accessibilityHazard (`rdflib.namespace.SDO` attribute), 242

accessibilitySummary (`rdflib.namespace.SDO` attribute), 242

accessMode (`rdflib.namespace.SDO` attribute), 242

accessModeSufficient (`rdflib.namespace.SDO` attribute), 242

accessRights (`rdflib.namespace.DCTERMS` attribute), 147

accessService (`rdflib.namespace.DCAT` attribute), 143

accessURL (`rdflib.namespace.DCAT` attribute), 143

Accommodation (`rdflib.namespace.SDO` attribute), 189

accommodationCategory (`rdflib.namespace.SDO` attribute), 242

accommodationFloorPlan (`rdflib.namespace.SDO` attribute), 242

account (`rdflib.namespace.FOAF` attribute), 151

accountablePerson (`rdflib.namespace.SDO` attribute), 242

accountId (`rdflib.namespace.SDO` attribute), 242

AccountingService (`rdflib.namespace.SDO` attribute), 189

accountMinimumInflow (`rdflib.namespace.SDO` attribute), 242

accountName (`rdflib.namespace.FOAF` attribute), 151

accountOverdraftLimit (`rdflib.namespace.SDO` attribute), 242

accountServiceHomepage (`rdflib.namespace.FOAF` attribute), 151

accrualMethod (`rdflib.namespace.DCTERMS` attribute), 147

accrualPeriodicity (`rdflib.namespace.DCTERMS` attribute), 147

accrualPolicy (`rdflib.namespace.DCTERMS` attribute), 147

Accumulator (class in `rdflib.plugins.sparql.aggregates`), 379

accumulator\_classes (`rdflib.plugins.sparql.aggregates.Aggregator` attribute), 381

AchieveAction (`rdflib.namespace.SDO` attribute), 189

acquiredFrom (`rdflib.namespace.SDO` attribute), 242

acquireLicensePage (`rdflib.namespace.SDO` attribute), 242

acrissCode (`rdflib.namespace.SDO` attribute), 242

actedOnBehalfOf (`rdflib.namespace.PROV` attribute), 180

Action (`rdflib.namespace.ODRL2` attribute), 163

- `action` (*rdflib.namespace.ODRL2* attribute), 164
- `Action` (*rdflib.namespace.SDO* attribute), 189
- `actionableFeedbackPolicy` (*rdflib.namespace.SDO* attribute), 243
- `actionAccessibilityRequirement` (*rdflib.namespace.SDO* attribute), 242
- `ActionAccessSpecification` (*rdflib.namespace.SDO* attribute), 189
- `actionApplication` (*rdflib.namespace.SDO* attribute), 242
- `actionOption` (*rdflib.namespace.SDO* attribute), 242
- `actionPlatform` (*rdflib.namespace.SDO* attribute), 242
- `actionStatus` (*rdflib.namespace.SDO* attribute), 242
- `ActionStatusType` (*rdflib.namespace.SDO* attribute), 189
- `ActivateAction` (*rdflib.namespace.SDO* attribute), 189
- `ActivationFee` (*rdflib.namespace.SDO* attribute), 189
- `Active_Cooled_Beam` (*rdflib.namespace.BRICK* attribute), 74
- `Active_Power_Sensor` (*rdflib.namespace.BRICK* attribute), 74
- `ActiveActionStatus` (*rdflib.namespace.SDO* attribute), 189
- `activeIngredient` (*rdflib.namespace.SDO* attribute), 243
- `ActiveNotRecruiting` (*rdflib.namespace.SDO* attribute), 189
- `Activity` (*rdflib.namespace.PROV* attribute), 178
- `activity` (*rdflib.namespace.PROV* attribute), 180
- `activityDuration` (*rdflib.namespace.SDO* attribute), 243
- `activityFrequency` (*rdflib.namespace.SDO* attribute), 243
- `ActivityInfluence` (*rdflib.namespace.PROV* attribute), 178
- `activityOfInfluence` (*rdflib.namespace.PROV* attribute), 180
- `actor` (*rdflib.namespace.SDO* attribute), 243
- `actors` (*rdflib.namespace.SDO* attribute), 243
- `actsOnProperty` (*rdflib.namespace.SOSA* attribute), 307
- `ActuableProperty` (*rdflib.namespace.SOSA* attribute), 306
- `Actuation` (*rdflib.namespace.SOSA* attribute), 306
- `Actuator` (*rdflib.namespace.SOSA* attribute), 306
- `add()` (*rdflib.ConjunctiveGraph* method), 577
- `add()` (*rdflib.Graph* method), 591
- `add()` (*rdflib.graph.BatchAddGraph* method), 481
- `add()` (*rdflib.graph.ConjunctiveGraph* method), 483
- `add()` (*rdflib.graph.Graph* method), 496
- `add()` (*rdflib.graph.QuotedGraph* method), 509
- `add()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 511
- `add()` (*rdflib.plugins.stores.auditable.AuditableStore* method), 429
- `add()` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 433
- `add()` (*rdflib.plugins.stores.concurrent.ConcurrentStore* method), 435
- `add()` (*rdflib.plugins.stores.memory.Memory* method), 437
- `add()` (*rdflib.plugins.stores.memory.SimpleMemory* method), 439
- `add()` (*rdflib.plugins.stores.regexmatching.REGEXMatching* method), 442
- `add()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 446
- `add()` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* method), 453
- `add()` (*rdflib.resource.Resource* method), 545
- `add()` (*rdflib.store.Store* method), 548
- `add_at_position()` (*rdflib.container.Seq* method), 473
- `add_graph()` (*rdflib.Dataset* method), 583
- `add_graph()` (*rdflib.graph.Dataset* method), 489
- `add_graph()` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 433
- `add_graph()` (*rdflib.plugins.stores.memory.Memory* method), 437
- `add_graph()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 447
- `add_graph()` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* method), 453
- `add_graph()` (*rdflib.store.Store* method), 549
- `add_reified()` (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 343
- `add_term()` (*rdflib.plugins.shared.jsonld.context.Context* method), 365
- `AddAction` (*rdflib.namespace.SDO* attribute), 189
- `additionalName` (*rdflib.namespace.SDO* attribute), 243
- `additionalNumberOfGuests` (*rdflib.namespace.SDO* attribute), 243
- `additionalProperty` (*rdflib.namespace.SDO* attribute), 243
- `additionalType` (*rdflib.namespace.SDO* attribute), 243
- `additionalVariable` (*rdflib.namespace.SDO* attribute), 243
- `AdditiveExpression()` (in module *rdflib.plugins.sparql.operators*), 396
- `addN()` (*rdflib.ConjunctiveGraph* method), 577
- `addN()` (*rdflib.Graph* method), 591
- `addN()` (*rdflib.graph.BatchAddGraph* method), 481
- `addN()` (*rdflib.graph.ConjunctiveGraph* method), 483
- `addN()` (*rdflib.graph.Graph* method), 496
- `addN()` (*rdflib.graph.QuotedGraph* method), 509
- `addN()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 511
- `addN()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 446



- `addN()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 453
- `addN()` (`rdflib.store.Store` method), 548
- `addNamespace()` (`rdflib.plugins.serializers.longturtle.LongTurtleSerializer` method), 355
- `addNamespace()` (`rdflib.plugins.serializers.turtle.RecursiveTurtleSerializer` method), 361
- `addNamespace()` (`rdflib.plugins.serializers.turtle.TurtleSerializer` method), 362
- `addOn` (`rdflib.namespace.SDO` attribute), 243
- `address` (`rdflib.namespace.SDO` attribute), 243
- `addressCountry` (`rdflib.namespace.SDO` attribute), 243
- `addressLocality` (`rdflib.namespace.SDO` attribute), 243
- `addressRegion` (`rdflib.namespace.SDO` attribute), 243
- `adHocShare` (`rdflib.namespace.ODRL2` attribute), 164
- `Adjust_Sensor` (`rdflib.namespace.BRICK` attribute), 74
- `administrationRoute` (`rdflib.namespace.SDO` attribute), 243
- `AdministrativeArea` (`rdflib.namespace.SDO` attribute), 189
- `AdultEntertainment` (`rdflib.namespace.SDO` attribute), 189
- `advanceBookingRequirement` (`rdflib.namespace.SDO` attribute), 243
- `adverseOutcome` (`rdflib.namespace.SDO` attribute), 243
- `AdvertiserContentArticle` (`rdflib.namespace.SDO` attribute), 190
- `AED` (`rdflib.namespace.BRICK` attribute), 73
- `AerobicActivity` (`rdflib.namespace.SDO` attribute), 190
- `affectedBy` (`rdflib.namespace.SDO` attribute), 243
- `affiliation` (`rdflib.namespace.SDO` attribute), 243
- `after` (`rdflib.namespace.TIME` attribute), 310
- `afterMedia` (`rdflib.namespace.SDO` attribute), 243
- `age` (`rdflib.namespace.FOAF` attribute), 151
- `Agent` (`rdflib.namespace.DCTERMS` attribute), 145
- `Agent` (`rdflib.namespace.FOAF` attribute), 151
- `Agent` (`rdflib.namespace.PROV` attribute), 178
- `agent` (`rdflib.namespace.PROV` attribute), 180
- `agent` (`rdflib.namespace.SDO` attribute), 243
- `AgentClass` (`rdflib.namespace.DCTERMS` attribute), 145
- `AgentInfluence` (`rdflib.namespace.PROV` attribute), 178
- `agentOfInfluence` (`rdflib.namespace.PROV` attribute), 180
- `aggregate` (`rdflib.namespace.BRICK` attribute), 135
- `aggregate` (`rdflib.namespace.ODRL2` attribute), 164
- `AggregateOffer` (`rdflib.namespace.SDO` attribute), 190
- `AggregateRating` (`rdflib.namespace.SDO` attribute), 190
- `aggregateRating` (`rdflib.namespace.SDO` attribute), 243
- `Aggregator` (class in `rdflib.plugins.sparql.aggregates`), 380
- `AgreeAction` (`rdflib.namespace.SDO` attribute), 190
- `Agreement` (`rdflib.namespace.ODRL2` attribute), 163
- `AHU` (`rdflib.namespace.BRICK` attribute), 73
- `Amplifier` (`rdflib.namespace.FOAF` attribute), 151
- `Air` (`rdflib.namespace.BRICK` attribute), 74
- `AirAlarm` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Differential_Pressure_Sensor` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Differential_Pressure_Setpoint` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Diffuser` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Enthalpy_Sensor` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Flow_Deadband_Setpoint` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Flow_Demand_Setpoint` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Flow_Loss_Alarm` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Flow_Sensor` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Flow_Setpoint` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Grains_Sensor` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Handler_Unit` (`rdflib.namespace.BRICK` attribute), 74
- `Air_Handling_Unit` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Humidity_Setpoint` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Loop` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Plenum` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Quality_Sensor` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Static_Pressure_Step_Parameter` (`rdflib.namespace.BRICK` attribute), 75
- `Air_System` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Temperature_Alarm` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Temperature_Integral_Time_Parameter` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Temperature_Sensor` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Temperature_Setpoint` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Temperature_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 75
- `Air_Temperature_Step_Parameter` (`rdflib.namespace.BRICK` attribute), 75

- `Air_Wet_Bulb_Temperature_Sensor` (*rdflib.namespace.BRICK* attribute), 75
- `aircraft` (*rdflib.namespace.SDO* attribute), 243
- `Airline` (*rdflib.namespace.SDO* attribute), 190
- `Airport` (*rdflib.namespace.SDO* attribute), 190
- `Alarm` (*rdflib.namespace.BRICK* attribute), 75
- `Alarm_Delay_Parameter` (*rdflib.namespace.BRICK* attribute), 75
- `album` (*rdflib.namespace.SDO* attribute), 244
- `albumProductionType` (*rdflib.namespace.SDO* attribute), 244
- `AlbumRelease` (*rdflib.namespace.SDO* attribute), 190
- `albumRelease` (*rdflib.namespace.SDO* attribute), 244
- `albumReleaseType` (*rdflib.namespace.SDO* attribute), 244
- `albums` (*rdflib.namespace.SDO* attribute), 244
- `alcoholWarning` (*rdflib.namespace.SDO* attribute), 244
- `algorithm` (*rdflib.namespace.SDO* attribute), 244
- `AlignmentObject` (*rdflib.namespace.SDO* attribute), 190
- `alignmentType` (*rdflib.namespace.SDO* attribute), 244
- `All` (*rdflib.namespace.ODRL2* attribute), 163
- `All2ndConnections` (*rdflib.namespace.ODRL2* attribute), 163
- `all_nodes()` (*rdflib.Graph* method), 591
- `all_nodes()` (*rdflib.graph.Graph* method), 496
- `AllClasses()` (in module *rdflib.extras.infixowl*), 59
- `AllConnections` (*rdflib.namespace.ODRL2* attribute), 163
- `AllDifferent` (*rdflib.namespace.OWL* attribute), 172
- `AllDifferent()` (in module *rdflib.extras.infixowl*), 59
- `AllDisjointClasses` (*rdflib.namespace.OWL* attribute), 173
- `AllDisjointProperties` (*rdflib.namespace.OWL* attribute), 173
- `AllergiesHealthAspect` (*rdflib.namespace.SDO* attribute), 190
- `AllGroups` (*rdflib.namespace.ODRL2* attribute), 163
- `AllocateAction` (*rdflib.namespace.SDO* attribute), 190
- `AllProperties()` (in module *rdflib.extras.infixowl*), 59
- `allValuesFrom` (*rdflib.extras.infixowl.Restriction* property), 71
- `allValuesFrom` (*rdflib.namespace.OWL* attribute), 174
- `AllWheelDriveConfiguration` (*rdflib.namespace.SDO* attribute), 190
- `AlreadyBound`, 416
- `Alt` (class in *rdflib.container*), 470
- `Alt` (*rdflib.namespace.RDF* attribute), 187
- `alt` (*rdflib.namespace.WGS* attribute), 315
- `alternateName` (*rdflib.namespace.SDO* attribute), 244
- `alternateOf` (*rdflib.namespace.PROV* attribute), 180
- `alternative` (*rdflib.namespace.DCTERMS* attribute), 147
- `alternativeHeadline` (*rdflib.namespace.SDO* attribute), 244
- `alternativeOf` (*rdflib.namespace.SDO* attribute), 244
- `AlternativePath` (class in *rdflib.paths*), 522
- `alternativePath` (*rdflib.namespace.SH* attribute), 301
- `altLabel` (*rdflib.namespace.SKOS* attribute), 305
- `alumni` (*rdflib.namespace.SDO* attribute), 244
- `alumniOf` (*rdflib.namespace.SDO* attribute), 244
- `amenityFeature` (*rdflib.namespace.SDO* attribute), 244
- `amount` (*rdflib.namespace.SDO* attribute), 244
- `amountOfThisGood` (*rdflib.namespace.SDO* attribute), 244
- `AmpStory` (*rdflib.namespace.SDO* attribute), 190
- `AMRadioChannel` (*rdflib.namespace.SDO* attribute), 189
- `AmusementPark` (*rdflib.namespace.SDO* attribute), 190
- `AnaerobicActivity` (*rdflib.namespace.SDO* attribute), 190
- `analyse()` (in module *rdflib.plugins.sparql.algebra*), 388
- `AnalysisNewsArticle` (*rdflib.namespace.SDO* attribute), 190
- `AnatomicalStructure` (*rdflib.namespace.SDO* attribute), 190
- `AnatomicalSystem` (*rdflib.namespace.SDO* attribute), 190
- `and_()` (in module *rdflib.plugins.sparql.operators*), 405
- `AndConstraintComponent` (*rdflib.namespace.SH* attribute), 297
- `andSequence` (*rdflib.namespace.ODRL2* attribute), 164
- `Anesthesia` (*rdflib.namespace.SDO* attribute), 190
- `Angle_Sensor` (*rdflib.namespace.BRICK* attribute), 75
- `AnimalShelter` (*rdflib.namespace.SDO* attribute), 190
- `AnnotatableTerms` (class in *rdflib.extras.infixowl*), 59
- `annotate` (*rdflib.namespace.ODRL2* attribute), 164
- `annotatedProperty` (*rdflib.namespace.OWL* attribute), 174
- `annotatedSource` (*rdflib.namespace.OWL* attribute), 174
- `annotatedTarget` (*rdflib.namespace.OWL* attribute), 174
- `annotation` (*rdflib.extras.infixowl.Class* property), 63
- `Annotation` (*rdflib.namespace.OWL* attribute), 173
- `AnnotationProperty` (*rdflib.namespace.OWL* attribute), 173
- `annotationProperty` (*rdflib.namespace.SH* attribute), 301
- `annotationValue` (*rdflib.namespace.SH* attribute), 301
- `annotationVarName` (*rdflib.namespace.SH* attribute), 301
- `announcementLocation` (*rdflib.namespace.SDO* attribute), 244
- `annualPercentageRate` (*rdflib.namespace.SDO* attribute), 244
- `anonymize` (*rdflib.namespace.ODRL2* attribute), 164
- `anonymousNode()` (*rd-*

- flib.plugins.parsers.notation3.SinkParser* method), 328
- Answer (*rdflib.namespace.SDO* attribute), 190
- answerCount (*rdflib.namespace.SDO* attribute), 244
- answerExplanation (*rdflib.namespace.SDO* attribute), 244
- antagonist (*rdflib.namespace.SDO* attribute), 244
- anyone() (*rdflib.container.Alt* method), 470
- anyURI (*rdflib.namespace.XSD* attribute), 316
- Apartment (*rdflib.namespace.SDO* attribute), 190
- ApartmentComplex (*rdflib.namespace.SDO* attribute), 190
- APIReference (*rdflib.namespace.SDO* attribute), 189
- Appearance (*rdflib.namespace.SDO* attribute), 190
- appearance (*rdflib.namespace.SDO* attribute), 244
- append (*rdflib.namespace.ODRL2* attribute), 164
- append() (*rdflib.collection.Collection* method), 465
- append() (*rdflib.container.Container* method), 472
- append() (*rdflib.extras.infixowl.OWLRDFListProxy* method), 69
- append\_multiple() (*rdflib.container.Container* method), 472
- AppendAction (*rdflib.namespace.SDO* attribute), 190
- appendTo (*rdflib.namespace.ODRL2* attribute), 164
- applicableLocation (*rdflib.namespace.SDO* attribute), 244
- applicantLocationRequirements (*rdflib.namespace.SDO* attribute), 244
- application (*rdflib.namespace.SDO* attribute), 244
- applicationCategory (*rdflib.namespace.SDO* attribute), 245
- applicationContact (*rdflib.namespace.SDO* attribute), 245
- applicationDeadline (*rdflib.namespace.SDO* attribute), 245
- applicationStartDate (*rdflib.namespace.SDO* attribute), 245
- applicationSubCategory (*rdflib.namespace.SDO* attribute), 245
- applicationSuite (*rdflib.namespace.SDO* attribute), 245
- appliesToDeliveryMethod (*rdflib.namespace.SDO* attribute), 245
- appliesToPaymentMethod (*rdflib.namespace.SDO* attribute), 245
- ApplyAction (*rdflib.namespace.SDO* attribute), 191
- ApprovedIndication (*rdflib.namespace.SDO* attribute), 191
- aq (*rdflib.namespace.PROV* attribute), 180
- Aquarium (*rdflib.namespace.SDO* attribute), 191
- archive (*rdflib.namespace.ODRL2* attribute), 164
- ArchiveComponent (*rdflib.namespace.SDO* attribute), 191
- archivedAt (*rdflib.namespace.SDO* attribute), 245
- archiveHeld (*rdflib.namespace.SDO* attribute), 245
- ArchiveOrganization (*rdflib.namespace.SDO* attribute), 191
- ArchRepository (*rdflib.namespace.DOAP* attribute), 149
- area (*rdflib.namespace.BRICK* attribute), 135
- area (*rdflib.namespace.SDO* attribute), 245
- areaServed (*rdflib.namespace.SDO* attribute), 245
- arrivalAirport (*rdflib.namespace.SDO* attribute), 245
- arrivalBoatTerminal (*rdflib.namespace.SDO* attribute), 245
- arrivalBusStop (*rdflib.namespace.SDO* attribute), 245
- arrivalGate (*rdflib.namespace.SDO* attribute), 245
- arrivalPlatform (*rdflib.namespace.SDO* attribute), 245
- arrivalStation (*rdflib.namespace.SDO* attribute), 245
- arrivalTerminal (*rdflib.namespace.SDO* attribute), 245
- arrivalTime (*rdflib.namespace.SDO* attribute), 245
- ArriveAction (*rdflib.namespace.SDO* attribute), 191
- artEdition (*rdflib.namespace.SDO* attribute), 245
- arterialBranch (*rdflib.namespace.SDO* attribute), 245
- Artery (*rdflib.namespace.SDO* attribute), 191
- artform (*rdflib.namespace.SDO* attribute), 245
- ArtGallery (*rdflib.namespace.SDO* attribute), 191
- Article (*rdflib.namespace.SDO* attribute), 191
- articleBody (*rdflib.namespace.SDO* attribute), 245
- articleSection (*rdflib.namespace.SDO* attribute), 246
- artist (*rdflib.namespace.SDO* attribute), 246
- artMedium (*rdflib.namespace.SDO* attribute), 245
- artworkSurface (*rdflib.namespace.SDO* attribute), 246
- ascii() (in module *rdflib.compat*), 470
- asdict() (*rdflib.query.ResultRow* method), 536
- asGML (*rdflib.namespace.GEO* attribute), 154
- asInBundle (*rdflib.namespace.PROV* attribute), 180
- ask (*rdflib.namespace.SH* attribute), 301
- AskAction (*rdflib.namespace.SDO* attribute), 191
- askAnswer (*rdflib.plugins.sparql.processor.SPARQLResult* attribute), 414
- askAnswer (*rdflib.plugins.sparql.results.jsonresults.JSONResult* attribute), 373
- askAnswer (*rdflib.plugins.sparql.results.rdfresults.RDFResult* attribute), 375
- askAnswer (*rdflib.plugins.sparql.results.xmlresults.XMLResult* attribute), 378
- AskPublicNewsArticle (*rdflib.namespace.SDO* attribute), 191
- aspect (*rdflib.namespace.SDO* attribute), 246
- assembly (*rdflib.namespace.SDO* attribute), 246
- assemblyVersion (*rdflib.namespace.SDO* attribute), 246
- Assertion (*rdflib.namespace.ODRL2* attribute), 163
- assertionProperty (*rdflib.namespace.OWL* attribute), 174



- Assertions (*rdflib.namespace.XSD* attribute), 315
- AssessAction (*rdflib.namespace.SDO* attribute), 191
- assesses (*rdflib.namespace.SDO* attribute), 246
- Asset (*rdflib.namespace.ODRL2* attribute), 163
- AssetCollection (*rdflib.namespace.ODRL2* attribute), 163
- AssetScope (*rdflib.namespace.ODRL2* attribute), 163
- AssignAction (*rdflib.namespace.SDO* attribute), 191
- assignee (*rdflib.namespace.ODRL2* attribute), 165
- assigneeOf (*rdflib.namespace.ODRL2* attribute), 165
- assigner (*rdflib.namespace.ODRL2* attribute), 165
- assignerOf (*rdflib.namespace.ODRL2* attribute), 165
- associatedAnatomy (*rdflib.namespace.SDO* attribute), 246
- associatedArticle (*rdflib.namespace.SDO* attribute), 246
- associatedClaimReview (*rdflib.namespace.SDO* attribute), 246
- associatedDisease (*rdflib.namespace.SDO* attribute), 246
- associatedMedia (*rdflib.namespace.SDO* attribute), 246
- associatedMediaReview (*rdflib.namespace.SDO* attribute), 246
- associatedPathophysiology (*rdflib.namespace.SDO* attribute), 246
- associatedReview (*rdflib.namespace.SDO* attribute), 246
- Association (*rdflib.namespace.PROV* attribute), 178
- asWKT (*rdflib.namespace.GEO* attribute), 154
- AsymmetricProperty (*rdflib.namespace.OWL* attribute), 173
- athlete (*rdflib.namespace.SDO* attribute), 246
- Atlas (*rdflib.namespace.SDO* attribute), 191
- atLocation (*rdflib.namespace.PROV* attribute), 180
- Attachable (*rdflib.namespace.QB* attribute), 185
- attachPolicy (*rdflib.namespace.ODRL2* attribute), 165
- attachSource (*rdflib.namespace.ODRL2* attribute), 165
- attendee (*rdflib.namespace.SDO* attribute), 246
- attendees (*rdflib.namespace.SDO* attribute), 246
- atTime (*rdflib.namespace.PROV* attribute), 180
- Attorney (*rdflib.namespace.SDO* attribute), 191
- attribute (*rdflib.namespace.ODRL2* attribute), 165
- attribute (*rdflib.namespace.QB* attribute), 186
- attribute() (*rdflib.plugins.serializers.xmlwriter.XMLWriter* method), 363
- attributedParty (*rdflib.namespace.ODRL2* attribute), 165
- AttributeProperty (*rdflib.namespace.QB* attribute), 185
- attributingParty (*rdflib.namespace.ODRL2* attribute), 165
- Attribution (*rdflib.namespace.PROV* attribute), 178
- audience (*rdflib.namespace.DCTERMS* attribute), 147
- audience (*rdflib.namespace.DOAP* attribute), 149
- Audience (*rdflib.namespace.SDO* attribute), 191
- audience (*rdflib.namespace.SDO* attribute), 246
- audienceType (*rdflib.namespace.SDO* attribute), 246
- audio (*rdflib.namespace.SDO* attribute), 246
- Audiobook (*rdflib.namespace.SDO* attribute), 191
- AudiobookFormat (*rdflib.namespace.SDO* attribute), 191
- AudioObject (*rdflib.namespace.SDO* attribute), 191
- AudioObjectSnapshot (*rdflib.namespace.SDO* attribute), 191
- audit\_hook() (in module *examples.secure\_with\_audit*), 26
- AuditableStore (class in *rdflib.plugins.stores.auditable*), 429
- Auditorium (*rdflib.namespace.BRICK* attribute), 75
- authenticator (*rdflib.namespace.SDO* attribute), 246
- author (*rdflib.namespace.SDO* attribute), 246
- AuthoritativeLegalValue (*rdflib.namespace.SDO* attribute), 191
- AuthorizeAction (*rdflib.namespace.SDO* attribute), 191
- auto (*rdflib.namespace.CSVW* attribute), 138
- AutoBodyShop (*rdflib.namespace.SDO* attribute), 191
- AutoDealer (*rdflib.namespace.SDO* attribute), 191
- Automated\_External\_Defibrillator (*rdflib.namespace.BRICK* attribute), 75
- AutomatedTeller (*rdflib.namespace.SDO* attribute), 192
- Automatic\_Mode\_Command (*rdflib.namespace.BRICK* attribute), 76
- AutomotiveBusiness (*rdflib.namespace.SDO* attribute), 192
- AutoPartsStore (*rdflib.namespace.SDO* attribute), 191
- AutoRental (*rdflib.namespace.SDO* attribute), 191
- AutoRepair (*rdflib.namespace.SDO* attribute), 191
- AutoWash (*rdflib.namespace.SDO* attribute), 192
- availability (*rdflib.namespace.SDO* attribute), 246
- Availability\_Status (*rdflib.namespace.BRICK* attribute), 76
- availabilityEnds (*rdflib.namespace.SDO* attribute), 246
- availabilityStarts (*rdflib.namespace.SDO* attribute), 246
- available (*rdflib.namespace.DCTERMS* attribute), 147
- availableAtOrFrom (*rdflib.namespace.SDO* attribute), 247
- availableChannel (*rdflib.namespace.SDO* attribute), 247
- availableDeliveryMethod (*rdflib.namespace.SDO* attribute), 247
- availableFrom (*rdflib.namespace.SDO* attribute), 247
- availableIn (*rdflib.namespace.SDO* attribute), 247
- availableLanguage (*rdflib.namespace.SDO* attribute),



- 247  
 availableOnDevice (rdflib.namespace.SDO attribute), 247  
 availableService (rdflib.namespace.SDO attribute), 247  
 availableStrength (rdflib.namespace.SDO attribute), 247  
 availableTest (rdflib.namespace.SDO attribute), 247  
 availableThrough (rdflib.namespace.SDO attribute), 247  
 Average (class in rdflib.plugins.sparql.aggregates), 381  
 Average\_Cooling\_Demand\_Sensor (rdflib.namespace.BRICK attribute), 76  
 Average\_Discharge\_Air\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 76  
 Average\_Exhaust\_Air\_Static\_Pressure\_Sensor (rdflib.namespace.BRICK attribute), 76  
 Average\_Heating\_Demand\_Sensor (rdflib.namespace.BRICK attribute), 76  
 Average\_Supply\_Air\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 76  
 Average\_Zone\_Air\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 76  
 award (rdflib.namespace.SDO attribute), 247  
 awards (rdflib.namespace.SDO attribute), 247  
 awayTeam (rdflib.namespace.SDO attribute), 247  
 Axiom (rdflib.namespace.OWL attribute), 173  
 Ayurvedic (rdflib.namespace.SDO attribute), 192  
 azimuth (rdflib.namespace.BRICK attribute), 135
- ## B
- BackgroundNewsArticle (rdflib.namespace.SDO attribute), 192  
 BackOrder (rdflib.namespace.SDO attribute), 192  
 backstory (rdflib.namespace.SDO attribute), 247  
 backwardCompatibleWith (rdflib.namespace.OWL attribute), 174  
 Bacteria (rdflib.namespace.SDO attribute), 192  
 BadSyntax, 321  
 BadSyntax() (rdflib.plugins.parsers.notation3.SinkParser method), 326  
 Bag (class in rdflib.container), 470  
 Bag (rdflib.namespace.RDF attribute), 187  
 BagID (class in rdflib.plugins.parsers.rdfxml), 342  
 Bakery (rdflib.namespace.SDO attribute), 192  
 Balance (rdflib.namespace.SDO attribute), 192  
 BankAccount (rdflib.namespace.SDO attribute), 192  
 bankAccountType (rdflib.namespace.SDO attribute), 247  
 BankOrCreditUnion (rdflib.namespace.SDO attribute), 192  
 Barcode (rdflib.namespace.SDO attribute), 192  
 bareWord() (rdflib.plugins.parsers.notation3.SinkParser method), 328  
 BarOrPub (rdflib.namespace.SDO attribute), 192  
 base (rdflib.namespace.CSVW attribute), 138  
 base (rdflib.plugins.parsers.rdfxml.ElementHandler attribute), 342  
 base (rdflib.plugins.serializers.hexst.HexuplesSerializer attribute), 354  
 base (rdflib.plugins.serializers.jsonld.JsonLDSerializer attribute), 355  
 base (rdflib.plugins.serializers.longturtle.LongTurtleSerializer attribute), 355  
 base (rdflib.plugins.serializers.n3.N3Serializer attribute), 357  
 base (rdflib.plugins.serializers.nquads.NQuadsSerializer attribute), 357  
 base (rdflib.plugins.serializers.nt.NTSerializer attribute), 358  
 base (rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer attribute), 358  
 base (rdflib.plugins.serializers.rdfxml.XMLSerializer attribute), 359  
 base (rdflib.plugins.serializers.trig.TrigSerializer attribute), 360  
 base (rdflib.plugins.serializers.trix.TriXSerializer attribute), 361  
 base (rdflib.plugins.serializers.turtle.RecursiveSerializer attribute), 361  
 base (rdflib.plugins.serializers.turtle.TurtleSerializer attribute), 362  
 base (rdflib.plugins.shared.jsonld.context.Context property), 366  
 base() (in module rdflib.plugins.parsers.notation3), 335  
 base64Binary (rdflib.namespace.XSD attribute), 316  
 Baseboard\_Radiator (rdflib.namespace.BRICK attribute), 76  
 based\_near (rdflib.namespace.FOAF attribute), 151  
 basedAt (rdflib.namespace.ORG attribute), 171  
 Basement (rdflib.namespace.BRICK attribute), 76  
 baseSalary (rdflib.namespace.SDO attribute), 247  
 BasicIncome (rdflib.namespace.SDO attribute), 192  
 BatchAddGraph (class in rdflib.graph), 480  
 Battery (rdflib.namespace.BRICK attribute), 76  
 Battery\_Energy\_Storage\_System (rdflib.namespace.BRICK attribute), 76  
 Battery\_Room (rdflib.namespace.BRICK attribute), 76  
 Battery\_Voltage\_Sensor (rdflib.namespace.BRICK attribute), 76  
 BazaarBranch (rdflib.namespace.DOAP attribute), 149  
 bbox (rdflib.namespace.DCAT attribute), 143  
 bccRecipient (rdflib.namespace.SDO attribute), 247  
 Beach (rdflib.namespace.SDO attribute), 192  
 BeautySalon (rdflib.namespace.SDO attribute), 192  
 becauseSubGraph() (in module rdflib.plugins.parsers.trig), 350  
 bed (rdflib.namespace.SDO attribute), 247

- BedAndBreakfast (*rdflib.namespace.SDO* attribute), 192
- BedDetails (*rdflib.namespace.SDO* attribute), 192
- BedType (*rdflib.namespace.SDO* attribute), 192
- before (*rdflib.namespace.TIME* attribute), 310
- beforeMedia (*rdflib.namespace.SDO* attribute), 247
- BefriendAction (*rdflib.namespace.SDO* attribute), 192
- Bench\_Space (*rdflib.namespace.BRICK* attribute), 76
- beneficiaryBank (*rdflib.namespace.SDO* attribute), 247
- benefits (*rdflib.namespace.SDO* attribute), 247
- BenefitsHealthAspect (*rdflib.namespace.SDO* attribute), 192
- benefitsSummaryUrl (*rdflib.namespace.SDO* attribute), 247
- BerkeleyDB (class in *rdflib.plugins.stores.berkeleydb*), 432
- bestRating (*rdflib.namespace.SDO* attribute), 247
- BGP() (in module *rdflib.plugins.sparql.algebra*), 386
- bibliographicCitation (*rdflib.namespace.DCTERMS* attribute), 147
- BibliographicResource (*rdflib.namespace.DCTERMS* attribute), 145
- BikeStore (*rdflib.namespace.SDO* attribute), 192
- billingAddress (*rdflib.namespace.SDO* attribute), 247
- billingDuration (*rdflib.namespace.SDO* attribute), 248
- billingIncrement (*rdflib.namespace.SDO* attribute), 248
- billingPeriod (*rdflib.namespace.SDO* attribute), 248
- billingStart (*rdflib.namespace.SDO* attribute), 248
- bind() (in module *rdflib.term*), 569
- bind() (*rdflib.Graph* method), 591
- bind() (*rdflib.graph.Graph* method), 496
- bind() (*rdflib.graph.ReadOnlyGraphAggregate* method), 511
- bind() (*rdflib.namespace.NamespaceManager* method), 161
- bind() (*rdflib.plugins.parsers.notation3.RDFSink* method), 324
- bind() (*rdflib.plugins.parsers.notation3.SinkParser* method), 328
- bind() (*rdflib.plugins.sparql.sparql.Prologue* method), 421
- bind() (*rdflib.plugins.stores.auditable.AuditableStore* method), 430
- bind() (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 433
- bind() (*rdflib.plugins.stores.memory.Memory* method), 437
- bind() (*rdflib.plugins.stores.memory.SimpleMemory* method), 440
- bind() (*rdflib.plugins.stores.regexmatching.REGEXMatching* method), 442
- bind() (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 447
- bind() (*rdflib.store.Store* method), 549
- Bindings (class in *rdflib.plugins.sparql.sparql*), 416
- bindings (*rdflib.query.Result* property), 533
- BioChemEntity (*rdflib.namespace.SDO* attribute), 192
- bioChemInteraction (*rdflib.namespace.SDO* attribute), 248
- bioChemSimilarity (*rdflib.namespace.SDO* attribute), 248
- biologicalRole (*rdflib.namespace.SDO* attribute), 248
- biomechanicalClass (*rdflib.namespace.SDO* attribute), 248
- birthDate (*rdflib.namespace.SDO* attribute), 248
- birthday (*rdflib.namespace.FOAF* attribute), 151
- birthPlace (*rdflib.namespace.SDO* attribute), 248
- bitrate (*rdflib.namespace.SDO* attribute), 248
- BKRepository (*rdflib.namespace.DOAP* attribute), 149
- BlankNode (*rdflib.namespace.SH* attribute), 297
- blankNode() (*rdflib.plugins.parsers.notation3.SinkParser* method), 328
- BlankNodeOrIRI (*rdflib.namespace.SH* attribute), 297
- BlankNodeOrLiteral (*rdflib.namespace.SH* attribute), 297
- BLOCK\_END (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- BLOCK\_FINDING\_PATTERN (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- BLOCK\_START (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- BlockContent (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- BlockFinding (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- blog (*rdflib.namespace.DOAP* attribute), 150
- Blog (*rdflib.namespace.SDO* attribute), 192
- blogPost (*rdflib.namespace.SDO* attribute), 248
- BlogPosting (*rdflib.namespace.SDO* attribute), 192
- blogPosts (*rdflib.namespace.SDO* attribute), 248
- bloodSupply (*rdflib.namespace.SDO* attribute), 248
- BloodTest (*rdflib.namespace.SDO* attribute), 192
- Blowdown\_Water (*rdflib.namespace.BRICK* attribute), 76
- BNode (class in *rdflib*), 575
- BNode (class in *rdflib.term*), 553
- bnodes (*rdflib.plugins.sparql.sparql.FrozenBindings* property), 418
- boardingGroup (*rdflib.namespace.SDO* attribute), 248
- boardingPolicy (*rdflib.namespace.SDO* attribute), 248
- BoardingPolicyType (*rdflib.namespace.SDO* attribute), 192
- BoatReservation (*rdflib.namespace.SDO* attribute), 192

- BoatTerminal (*rdflib.namespace.SDO* attribute), 193
- BoatTrip (*rdflib.namespace.SDO* attribute), 193
- bodyLocation (*rdflib.namespace.SDO* attribute), 248
- BodyMeasurementArm (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementBust (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementChest (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementFoot (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementHand (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementHead (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementHeight (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementHips (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementInsideLeg (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementNeck (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementTypeEnumeration (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementUnderbust (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementWaist (*rdflib.namespace.SDO* attribute), 193
- BodyMeasurementWeight (*rdflib.namespace.SDO* attribute), 193
- BodyOfWater (*rdflib.namespace.SDO* attribute), 193
- bodyType (*rdflib.namespace.SDO* attribute), 248
- Boiler (*rdflib.namespace.BRICK* attribute), 76
- Bone (*rdflib.namespace.SDO* attribute), 193
- Book (*rdflib.namespace.SDO* attribute), 193
- bookEdition (*rdflib.namespace.SDO* attribute), 248
- bookFormat (*rdflib.namespace.SDO* attribute), 248
- BookFormatType (*rdflib.namespace.SDO* attribute), 193
- bookingAgent (*rdflib.namespace.SDO* attribute), 248
- bookingTime (*rdflib.namespace.SDO* attribute), 248
- BookmarkAction (*rdflib.namespace.SDO* attribute), 194
- BookSeries (*rdflib.namespace.SDO* attribute), 193
- BookStore (*rdflib.namespace.SDO* attribute), 193
- Boolean (*rdflib.namespace.SDO* attribute), 194
- boolean (*rdflib.namespace.XSD* attribute), 316
- BooleanClass (class in *rdflib.extras.infixowl*), 61
- Booster\_Fan (*rdflib.namespace.BRICK* attribute), 76
- bopen() (in module *rdflib.compat*), 470
- BorrowAction (*rdflib.namespace.SDO* attribute), 194
- borrower (*rdflib.namespace.SDO* attribute), 248
- bottomDataProperty (*rdflib.namespace.OWL* attribute), 174
- bottomObjectProperty (*rdflib.namespace.OWL* attribute), 174
- bounded (*rdflib.namespace.XSD* attribute), 316
- BowlingAlley (*rdflib.namespace.SDO* attribute), 194
- Box (*rdflib.namespace.DCTERMS* attribute), 145
- box (*rdflib.namespace.SDO* attribute), 248
- Box\_Mode\_Command (*rdflib.namespace.BRICK* attribute), 76
- BrainStructure (*rdflib.namespace.SDO* attribute), 194
- branch (*rdflib.namespace.SDO* attribute), 248
- branchCode (*rdflib.namespace.SDO* attribute), 248
- branchOf (*rdflib.namespace.SDO* attribute), 248
- Brand (*rdflib.namespace.SDO* attribute), 194
- brand (*rdflib.namespace.SDO* attribute), 248
- breadcrumb (*rdflib.namespace.SDO* attribute), 249
- BreadcrumbList (*rdflib.namespace.SDO* attribute), 194
- Break\_Room (*rdflib.namespace.BRICK* attribute), 77
- Breaker\_Panel (*rdflib.namespace.BRICK* attribute), 77
- Breakroom (*rdflib.namespace.BRICK* attribute), 77
- breastfeedingWarning (*rdflib.namespace.SDO* attribute), 249
- Brewery (*rdflib.namespace.SDO* attribute), 194
- BRICK (class in *rdflib.namespace*), 73
- Bridge (*rdflib.namespace.SDO* attribute), 194
- Broadcast\_Room (*rdflib.namespace.BRICK* attribute), 77
- broadcastAffiliateOf (*rdflib.namespace.SDO* attribute), 249
- BroadcastChannel (*rdflib.namespace.SDO* attribute), 194
- broadcastChannelId (*rdflib.namespace.SDO* attribute), 249
- broadcastDisplayName (*rdflib.namespace.SDO* attribute), 249
- broadcaster (*rdflib.namespace.SDO* attribute), 249
- BroadcastEvent (*rdflib.namespace.SDO* attribute), 194
- broadcastFrequency (*rdflib.namespace.SDO* attribute), 249
- BroadcastFrequencySpecification (*rdflib.namespace.SDO* attribute), 194
- broadcastFrequencyValue (*rdflib.namespace.SDO* attribute), 249
- broadcastOfEvent (*rdflib.namespace.SDO* attribute), 249
- BroadcastRelease (*rdflib.namespace.SDO* attribute), 194
- BroadcastService (*rdflib.namespace.SDO* attribute), 194
- broadcastServiceTier (*rdflib.namespace.SDO* attribute), 249
- broadcastSignalModulation (*rdflib.namespace.SDO* attribute), 249
- broadcastSubChannel (*rdflib.namespace.SDO* attribute), 249
- broadcastTimezone (*rdflib.namespace.SDO* attribute), 249

249			
broader (rdflib.namespace.SKOS attribute), 305			
broaderTransitive (rdflib.namespace.SKOS attribute), 305			
broadMatch (rdflib.namespace.SKOS attribute), 305			
broker (rdflib.namespace.SDO attribute), 249			
BrokerageAccount (rdflib.namespace.SDO attribute), 194			
browse (rdflib.namespace.DOAP attribute), 150			
browserRequirements (rdflib.namespace.SDO attribute), 249			
BuddhistTemple (rdflib.namespace.SDO attribute), 194			
buffer (rdflib.plugins.parsers.nquads.NQuadsParser attribute), 338			
buffer (rdflib.plugins.parsers.ntriples.W3CNTriplesParser attribute), 340			
Building (rdflib.namespace.BRICK attribute), 77			
Building_Air (rdflib.namespace.BRICK attribute), 77			
Building_Air_Humidity_Setpoint (rdflib.namespace.BRICK attribute), 77			
Building_Air_Static_Pressure_Sensor (rdflib.namespace.BRICK attribute), 77			
Building_Air_Static_Pressure_Setpoint (rdflib.namespace.BRICK attribute), 77			
Building_Chilled_Water_Meter (rdflib.namespace.BRICK attribute), 77			
Building_Electrical_Meter (rdflib.namespace.BRICK attribute), 77			
Building_Gas_Meter (rdflib.namespace.BRICK attribute), 77			
Building_Hot_Water_Meter (rdflib.namespace.BRICK attribute), 77			
Building_Meter (rdflib.namespace.BRICK attribute), 77			
Building_Water_Meter (rdflib.namespace.BRICK attribute), 77			
buildingPrimaryFunction (rdflib.namespace.BRICK attribute), 135			
buildingThermalTransmittance (rdflib.namespace.BRICK attribute), 135			
buildPredicateHash() (rdflib.plugins.serializers.turtle.RecursiveSerializer method), 361			
Builtin_ABS() (in module rdflib.plugins.sparql.operators), 397			
Builtin_BNODE() (in module rdflib.plugins.sparql.operators), 397			
Builtin_BOUND() (in module rdflib.plugins.sparql.operators), 397			
Builtin_CEIL() (in module rdflib.plugins.sparql.operators), 397			
Builtin_COALESCE() (in module rdflib.plugins.sparql.operators), 397			
Builtin_CONCAT() (in module rdflib.plugins.sparql.operators), 397			
Builtin_CONTAINS() (in module rdflib.plugins.sparql.operators), 397			
Builtin_DATATYPE() (in module rdflib.plugins.sparql.operators), 397			
Builtin_DAY() (in module rdflib.plugins.sparql.operators), 398			
Builtin_ENCODE_FOR_URI() (in module rdflib.plugins.sparql.operators), 398			
Builtin_EXISTS() (in module rdflib.plugins.sparql.operators), 398			
Builtin_FLOOR() (in module rdflib.plugins.sparql.operators), 398			
Builtin_HOURS() (in module rdflib.plugins.sparql.operators), 398			
Builtin_IF() (in module rdflib.plugins.sparql.operators), 398			
Builtin_IRI() (in module rdflib.plugins.sparql.operators), 398			
Builtin_isBLANK() (in module rdflib.plugins.sparql.operators), 403			
Builtin_isIRI() (in module rdflib.plugins.sparql.operators), 403			
Builtin_isLITERAL() (in module rdflib.plugins.sparql.operators), 403			
Builtin_isNUMERIC() (in module rdflib.plugins.sparql.operators), 403			
Builtin_LANG() (in module rdflib.plugins.sparql.operators), 399			
Builtin_LANGMATCHES() (in module rdflib.plugins.sparql.operators), 399			
Builtin_LCASE() (in module rdflib.plugins.sparql.operators), 399			
Builtin_MD5() (in module rdflib.plugins.sparql.operators), 399			
Builtin_MINUTES() (in module rdflib.plugins.sparql.operators), 399			
Builtin_MONTH() (in module rdflib.plugins.sparql.operators), 399			
Builtin_NOW() (in module rdflib.plugins.sparql.operators), 399			
Builtin_RAND() (in module rdflib.plugins.sparql.operators), 400			
Builtin_REGEX() (in module rdflib.plugins.sparql.operators), 400			
Builtin_REPLACE() (in module rdflib.plugins.sparql.operators), 400			
Builtin_ROUND() (in module rdflib.plugins.sparql.operators), 400			
Builtin_sameTerm() (in module rdflib.plugins.sparql.operators), 403			
Builtin_SECONDS() (in module rdflib.plugins.sparql.operators), 400			
Builtin_SHA1() (in module rdflib.plugins.sparql.operators), 397			



- flib.plugins.sparql.operators*), 400
- Builtin\_SHA256() (in module *flib.plugins.sparql.operators*), 400
- Builtin\_SHA384() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_SHA512() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_STR() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_STRAFTER() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_STRBEFORE() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_STRDT() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_STRENGTHS() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_STRLANG() (in module *flib.plugins.sparql.operators*), 401
- Builtin\_STRLLEN() (in module *flib.plugins.sparql.operators*), 402
- Builtin\_STRSTARTS() (in module *flib.plugins.sparql.operators*), 402
- Builtin\_STRUUID() (in module *flib.plugins.sparql.operators*), 402
- Builtin\_SUBSTR() (in module *flib.plugins.sparql.operators*), 402
- Builtin\_TIMEZONE() (in module *flib.plugins.sparql.operators*), 402
- Builtin\_TZ() (in module *flib.plugins.sparql.operators*), 402
- Builtin\_UCASE() (in module *flib.plugins.sparql.operators*), 402
- Builtin\_UUID() (in module *flib.plugins.sparql.operators*), 403
- Builtin\_YEAR() (in module *flib.plugins.sparql.operators*), 403
- Bundle (*rdflib.namespace.PROV* attribute), 178
- Bus\_Riser (*rdflib.namespace.BRICK* attribute), 77
- BusinessAudience (*rdflib.namespace.SDO* attribute), 194
- businessDays (*rdflib.namespace.SDO* attribute), 249
- BusinessEntityType (*rdflib.namespace.SDO* attribute), 194
- BusinessEvent (*rdflib.namespace.SDO* attribute), 194
- BusinessFunction (*rdflib.namespace.SDO* attribute), 194
- businessFunction (*rdflib.namespace.SDO* attribute), 249
- BusinessSupport (*rdflib.namespace.SDO* attribute), 194
- busName (*rdflib.namespace.SDO* attribute), 249
- busNumber (*rdflib.namespace.SDO* attribute), 249
- BusOrCoach (*rdflib.namespace.SDO* attribute), 194
- BusReservation (*rdflib.namespace.SDO* attribute), 194
- rd-BusStation (*rdflib.namespace.SDO* attribute), 194
- BusStop (*rdflib.namespace.SDO* attribute), 194
- rd-BusTrip (*rdflib.namespace.SDO* attribute), 194
- BuyAction (*rdflib.namespace.SDO* attribute), 195
- rd-buyer (*rdflib.namespace.SDO* attribute), 249
- byArtist (*rdflib.namespace.SDO* attribute), 249
- rd-byDay (*rdflib.namespace.SDO* attribute), 249
- byMonth (*rdflib.namespace.SDO* attribute), 249
- rd-byMonthDay (*rdflib.namespace.SDO* attribute), 250
- byMonthWeek (*rdflib.namespace.SDO* attribute), 250
- rd-Bypass\_Air (*rdflib.namespace.BRICK* attribute), 77
- Bypass\_Air\_Flow\_Sensor (*rdflib.namespace.BRICK* attribute), 77
- rd-Bypass\_Air\_Humidity\_Setpoint (*rdflib.namespace.BRICK* attribute), 77
- rd-Bypass\_Command (*rdflib.namespace.BRICK* attribute), 78
- Bypass\_Valve (*rdflib.namespace.BRICK* attribute), 78
- rd-Bypass\_Water (*rdflib.namespace.BRICK* attribute), 78
- Bypass\_Water\_Flow\_Sensor (*rdflib.namespace.BRICK* attribute), 78
- rd-Bypass\_Water\_Flow\_Setpoint (*rdflib.namespace.BRICK* attribute), 78
- byte (*rdflib.namespace.XSD* attribute), 316
- rd-byteSize (*rdflib.namespace.DCAT* attribute), 143
- rd-C
- CableOrSatelliteService (*rdflib.namespace.SDO* attribute), 195
- rd-CafeOrCoffeeShop (*rdflib.namespace.SDO* attribute), 195
- Cafeteria (*rdflib.namespace.BRICK* attribute), 78
- rd-calculateDuration() (in module *flib.plugins.sparql.operators*), 405
- rd-calculateFinalDateTime() (in module *flib.plugins.sparql.operators*), 405
- Callable (class in *rdflib.extras.infixowl*), 62
- callSign (*rdflib.namespace.SDO* attribute), 250
- calories (*rdflib.namespace.SDO* attribute), 250
- Camera (*rdflib.namespace.BRICK* attribute), 78
- Campground (*rdflib.namespace.SDO* attribute), 195
- CampingPitch (*rdflib.namespace.SDO* attribute), 195
- Canal (*rdflib.namespace.SDO* attribute), 195
- CancelAction (*rdflib.namespace.SDO* attribute), 195
- candidate (*rdflib.namespace.SDO* attribute), 250
- Capacity\_Sensor (*rdflib.namespace.BRICK* attribute), 78
- caption (*rdflib.namespace.SDO* attribute), 250
- Car (*rdflib.namespace.SDO* attribute), 195
- carbohydrateContent (*rdflib.namespace.SDO* attribute), 250
- cardinality (*rdflib.extras.infixowl.Restriction* property), 71

- ul style="list-style-type: none; padding-left: 0;">
- cardinality (*rdflib.namespace.OWL* attribute), 174
- cardinality (*rdflib.namespace.XSD* attribute), 316
- Cardiovascular (*rdflib.namespace.SDO* attribute), 195
- CardiovascularExam (*rdflib.namespace.SDO* attribute), 195
- cargoVolume (*rdflib.namespace.SDO* attribute), 250
- carrier (*rdflib.namespace.SDO* attribute), 250
- carrierRequirements (*rdflib.namespace.SDO* attribute), 250
- CarUsageType (*rdflib.namespace.SDO* attribute), 195
- CaseSeries (*rdflib.namespace.SDO* attribute), 195
- cashBack (*rdflib.namespace.SDO* attribute), 250
- Casino (*rdflib.namespace.SDO* attribute), 195
- CassetteFormat (*rdflib.namespace.SDO* attribute), 195
- cast\_bytes() (in module *rdflib.compat*), 470
- cast\_identifier() (in module *rdflib.extras.describer*), 53
- cast\_value() (in module *rdflib.extras.describer*), 53
- CastClass() (in module *rdflib.extras.infixowl*), 62
- Catalog (*rdflib.namespace.DCAT* attribute), 143
- catalog (*rdflib.namespace.DCAT* attribute), 144
- catalog (*rdflib.namespace.SDO* attribute), 250
- catalogNumber (*rdflib.namespace.SDO* attribute), 250
- CatalogRecord (*rdflib.namespace.DCAT* attribute), 143
- category (*rdflib.namespace.DOAP* attribute), 150
- category (*rdflib.namespace.PROV* attribute), 180
- category (*rdflib.namespace.SDO* attribute), 250
- CategoryCode (*rdflib.namespace.SDO* attribute), 195
- CategoryCodeSet (*rdflib.namespace.SDO* attribute), 195
- CatholicChurch (*rdflib.namespace.SDO* attribute), 195
- causeOf (*rdflib.namespace.SDO* attribute), 250
- CausesHealthAspect (*rdflib.namespace.SDO* attribute), 195
- CAV (*rdflib.namespace.BRICK* attribute), 78
- cbd() (*rdflib.Graph* method), 591
- cbd() (*rdflib.graph.Graph* method), 496
- ccRecipient (*rdflib.namespace.SDO* attribute), 250
- CDCPMDRecord (*rdflib.namespace.SDO* attribute), 195
- CDFormat (*rdflib.namespace.SDO* attribute), 195
- Ceiling\_Fan (*rdflib.namespace.BRICK* attribute), 78
- Cell (*rdflib.namespace.CSVW* attribute), 137
- Cemetery (*rdflib.namespace.SDO* attribute), 195
- Centrifugal\_Chiller (*rdflib.namespace.BRICK* attribute), 79
- centroid (*rdflib.namespace.DCAT* attribute), 144
- Change\_Filter\_Alarm (*rdflib.namespace.BRICK* attribute), 79
- changedBy (*rdflib.namespace.ORG* attribute), 171
- ChangeEvent (*rdflib.namespace.ORG* attribute), 170
- changeNote (*rdflib.namespace.SKOS* attribute), 305
- changeOperator() (*rdflib.extras.infixowl.BooleanClass* method), 61
- changes (*rdflib.namespace.VANN* attribute), 313
- Chapter (*rdflib.namespace.SDO* attribute), 195
- char (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342
- character (*rdflib.namespace.SDO* attribute), 250
- characterAttribute (*rdflib.namespace.SDO* attribute), 250
- characterName (*rdflib.namespace.SDO* attribute), 250
- characters() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 343
- characters() (*rdflib.plugins.parsers.trix.TriXHandler* method), 350
- CharitableIncorporatedOrganization (*rdflib.namespace.SDO* attribute), 195
- cheatCode (*rdflib.namespace.SDO* attribute), 250
- CheckAction (*rdflib.namespace.SDO* attribute), 195
- checkDot() (*rdflib.plugins.parsers.notation3.SinkParser* method), 328
- CheckInAction (*rdflib.namespace.SDO* attribute), 195
- checkinTime (*rdflib.namespace.SDO* attribute), 250
- CheckoutAction (*rdflib.namespace.SDO* attribute), 195
- CheckoutPage (*rdflib.namespace.SDO* attribute), 195
- checkoutTime (*rdflib.namespace.SDO* attribute), 250
- checkSubject() (*rdflib.plugins.serializers.turtle.RecursiveSerializer* method), 361
- chemicalComposition (*rdflib.namespace.SDO* attribute), 250
- chemicalRole (*rdflib.namespace.SDO* attribute), 250
- ChemicalSubstance (*rdflib.namespace.SDO* attribute), 196
- ChildCare (*rdflib.namespace.SDO* attribute), 196
- childMaxAge (*rdflib.namespace.SDO* attribute), 250
- childMinAge (*rdflib.namespace.SDO* attribute), 250
- children (*rdflib.namespace.SDO* attribute), 250
- ChildrensEvent (*rdflib.namespace.SDO* attribute), 196
- childTaxon (*rdflib.namespace.SDO* attribute), 250
- Chilled\_Beam (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Coil (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Deadband\_Setpoint (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Integral\_Time\_Parameters (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Load\_Shed\_Reset\_Status (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Load\_Shed\_Setpoint (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Load\_Shed\_Status (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Proportional\_Band\_Parameters (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Sensor (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Setpoint

- (*rdflib.namespace.BRICK* attribute), 79
- Chilled\_Water\_Differential\_Pressure\_Step\_Parameter (rdflib.namespace.BRICK attribute), 79
- Chilled\_Water\_Differential\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 79
- Chilled\_Water\_Discharge\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 79
- Chilled\_Water\_Discharge\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Loop (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Meter (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Pump (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Pump\_Differential\_Pressure\_Deadband\_Setpoint (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Return\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Return\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Static\_Pressure\_Setpoint (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Supply\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Supply\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Supply\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_System (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_System\_Enable\_Command (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 80
- Chilled\_Water\_Valve (rdflib.namespace.BRICK attribute), 80
- Chiller (rdflib.namespace.BRICK attribute), 81
- Chiropractic (rdflib.namespace.SDO attribute), 196
- cholesterolContent (rdflib.namespace.SDO attribute), 251
- ChooseAction (rdflib.namespace.SDO attribute), 196
- Church (rdflib.namespace.SDO attribute), 196
- circle (rdflib.namespace.SDO attribute), 251
- citation (rdflib.namespace.SDO attribute), 251
- City (rdflib.namespace.SDO attribute), 196
- CityHall (rdflib.namespace.SDO attribute), 196
- CivicStructure (rdflib.namespace.SDO attribute), 196
- Claim (rdflib.namespace.SDO attribute), 196
- ClaimInterpreter (rdflib.namespace.SDO attribute), 251
- ClaimReview (rdflib.namespace.SDO attribute), 196
- claimReviewed (rdflib.namespace.SDO attribute), 251
- Class (class in *rdflib.extras.infixowl*), 62
- Class (rdflib.namespace.BRICK attribute), 81
- Class (rdflib.namespace.OWL attribute), 173
- Class (rdflib.namespace.RDFS attribute), 188
- Class (rdflib.namespace.SDO attribute), 196
- ClassConstraintComponent (rdflib.namespace.SH attribute), 297
- classes (rdflib.namespace.VOID attribute), 314
- classification (rdflib.namespace.ORG attribute), 171
- ClassNamespaceFactory (class in *rdflib.extras.infixowl*), 64
- classOrIdentifier() (in module *rdflib.extras.infixowl*), 71
- classOrTerm() (in module *rdflib.extras.infixowl*), 72
- classSetpoint (rdflib.namespace.VOID attribute), 314
- clean() (*rdflib.plugins.sparql.sparql.QueryContext* method), 423
- CleaningFee (rdflib.namespace.SDO attribute), 196
- cleanup (rdflib.plugins.stores.concurrent.ResponsibleGenerator attribute), 436
- clear() (*rdflib.collection.Collection* method), 465
- clear() (*rdflib.container.Container* method), 472
- clear() (*rdflib.extras.infixowl.OWLRLDFListProxy* method), 69
- clearInDegree() (*rdflib.extras.infixowl.Individual* method), 67
- clearOutDegree() (*rdflib.extras.infixowl.Individual* method), 67
- clinicalPharmacology (rdflib.namespace.SDO attribute), 251
- clinicalPharmacology (rdflib.namespace.SDO attribute), 251
- Clinician (rdflib.namespace.SDO attribute), 196
- Clip (rdflib.namespace.SDO attribute), 196
- clipNumber (rdflib.namespace.SDO attribute), 251
- clone() (*rdflib.plugins.sparql.parserutils.CompValue* method), 410
- clone() (*rdflib.plugins.sparql.sparql.QueryContext* method), 423
- close() (*rdflib.Graph* method), 592
- close() (*rdflib.graph.Graph* method), 497
- close() (*rdflib.graph.ReadOnlyGraphAggregate* method), 511
- close() (*rdflib.parser.InputSource* method), 516
- close() (*rdflib.parser.PythonInputSource* method), 517
- close() (*rdflib.plugins.parsers.notation3.Formula* method), 323
- close() (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter*



- method*), 377
- `close()` (*rdflib.plugins.stores.auditable.AuditableStore* *method*), 430
- `close()` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* *method*), 433
- `close()` (*rdflib.plugins.stores.regexmatching.REGEXMatching* *method*), 442
- `close()` (*rdflib.store.Store* *method*), 549
- `Close_Limit` (*rdflib.namespace.BRICK* attribute), 81
- `closed` (*rdflib.namespace.SH* attribute), 301
- `ClosedConstraintComponent` (*rdflib.namespace.SH* attribute), 297
- `ClosedNamespace` (*class in rdflib.namespace*), 141
- `closeMatch` (*rdflib.namespace.SKOS* attribute), 305
- `closes` (*rdflib.namespace.SDO* attribute), 251
- `ClothingStore` (*rdflib.namespace.SDO* attribute), 196
- `C0` (*rdflib.namespace.BRICK* attribute), 78
- `C02` (*rdflib.namespace.BRICK* attribute), 78
- `C02_Alarm` (*rdflib.namespace.BRICK* attribute), 78
- `C02_Differential_Sensor` (*rdflib.namespace.BRICK* attribute), 78
- `C02_Level_Sensor` (*rdflib.namespace.BRICK* attribute), 78
- `C02_Sensor` (*rdflib.namespace.BRICK* attribute), 78
- `C02_Setpoint` (*rdflib.namespace.BRICK* attribute), 78
- `C0_Differential_Sensor` (*rdflib.namespace.BRICK* attribute), 78
- `C0_Level_Sensor` (*rdflib.namespace.BRICK* attribute), 78
- `C0_Sensor` (*rdflib.namespace.BRICK* attribute), 78
- `coach` (*rdflib.namespace.SDO* attribute), 251
- `Code` (*rdflib.namespace.SDO* attribute), 196
- `code` (*rdflib.namespace.SDO* attribute), 251
- `CodedProperty` (*rdflib.namespace.QB* attribute), 185
- `codeList` (*rdflib.namespace.QB* attribute), 186
- `codeRepository` (*rdflib.namespace.SDO* attribute), 251
- `codeSampleType` (*rdflib.namespace.SDO* attribute), 251
- `codeValue` (*rdflib.namespace.SDO* attribute), 251
- `codingSystem` (*rdflib.namespace.SDO* attribute), 251
- `CohortStudy` (*rdflib.namespace.SDO* attribute), 196
- `Coil` (*rdflib.namespace.BRICK* attribute), 81
- `Cold_Box` (*rdflib.namespace.BRICK* attribute), 81
- `Coldest_Zone_Air_Temperature_Sensor` (*rdflib.namespace.BRICK* attribute), 81
- `colleague` (*rdflib.namespace.SDO* attribute), 251
- `colleagues` (*rdflib.namespace.SDO* attribute), 251
- `collectAndRemoveFilters()` (*in module rdflib.plugins.sparql.algebra*), 388
- `Collection` (*class in rdflib.collection*), 461
- `Collection` (*rdflib.namespace.BRICK* attribute), 81
- `Collection` (*rdflib.namespace.DCMITYPE* attribute), 145
- `Collection` (*rdflib.namespace.PROV* attribute), 178
- `Collection` (*rdflib.namespace.SDO* attribute), 196
- `collection` (*rdflib.namespace.SDO* attribute), 251
- `Collection` (*rdflib.namespace.SKOS* attribute), 305
- `collection()` (*rdflib.Graph* *method*), 592
- `collection()` (*rdflib.graph.Graph* *method*), 497
- `Collection_Basin_Water` (*rdflib.namespace.BRICK* attribute), 81
- `Collection_Basin_Water_Heater` (*rdflib.namespace.BRICK* attribute), 81
- `Collection_Basin_Water_Level_Alarm` (*rdflib.namespace.BRICK* attribute), 81
- `Collection_Basin_Water_Level_Sensor` (*rdflib.namespace.BRICK* attribute), 81
- `Collection_Basin_Water_Temperature_Sensor` (*rdflib.namespace.BRICK* attribute), 81
- `CollectionPage` (*rdflib.namespace.SDO* attribute), 196
- `collectionSize` (*rdflib.namespace.SDO* attribute), 251
- `CollegeOrUniversity` (*rdflib.namespace.SDO* attribute), 196
- `color` (*rdflib.namespace.SDO* attribute), 251
- `colorist` (*rdflib.namespace.SDO* attribute), 251
- `Column` (*rdflib.namespace.CSVW* attribute), 138
- `column` (*rdflib.namespace.CSVW* attribute), 138
- `columnReference` (*rdflib.namespace.CSVW* attribute), 138
- `ComedyClub` (*rdflib.namespace.SDO* attribute), 196
- `ComedyEvent` (*rdflib.namespace.SDO* attribute), 196
- `ComicCoverArt` (*rdflib.namespace.SDO* attribute), 196
- `ComicIssue` (*rdflib.namespace.SDO* attribute), 196
- `ComicSeries` (*rdflib.namespace.SDO* attribute), 196
- `ComicStory` (*rdflib.namespace.SDO* attribute), 196
- `Command` (*rdflib.namespace.BRICK* attribute), 81
- `commaSeparatedList()` (*rdflib.plugins.parsers.notation3.SinkParser* *method*), 329
- `comment` (*rdflib.extras.infixowl.AnnotatableTerms* *property*), 61
- `comment` (*rdflib.namespace.RDFS* attribute), 188
- `Comment` (*rdflib.namespace.SDO* attribute), 196
- `comment` (*rdflib.namespace.SDO* attribute), 251
- `COMMENT` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- `CommentAction` (*rdflib.namespace.SDO* attribute), 197
- `commentCount` (*rdflib.namespace.SDO* attribute), 251
- `CommentPermission` (*rdflib.namespace.SDO* attribute), 197
- `commentPrefix` (*rdflib.namespace.CSVW* attribute), 138
- `commentText` (*rdflib.namespace.SDO* attribute), 251
- `commentTime` (*rdflib.namespace.SDO* attribute), 251
- `commercialize` (*rdflib.namespace.ODRL2* attribute), 165
- `commit()` (*rdflib.Graph* *method*), 593
- `commit()` (*rdflib.graph.Graph* *method*), 498
- `commit()` (*rdflib.graph.ReadOnlyGraphAggregate* *method*), 512



- `commit()` (`rdflib.plugins.stores.auditable.AuditableStore` method), 430
- `commit()` (`rdflib.plugins.stores.regexmatching.REGEXMatchingStore` method), 442
- `commit()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 447
- `commit()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 454
- `commit()` (`rdflib.store.Store` method), 549
- `Common_Space` (`rdflib.namespace.BRICK` attribute), 81
- `CommonNSBindings()` (in module `rdflib.extras.infixowl`), 64
- `CommunicateAction` (`rdflib.namespace.SDO` attribute), 197
- `Communication` (`rdflib.namespace.PROV` attribute), 178
- `Communication_Loss_Alarm` (`rdflib.namespace.BRICK` attribute), 81
- `CommunityHealth` (`rdflib.namespace.SDO` attribute), 197
- `Comp` (class in `rdflib.plugins.sparql.parserutils`), 409
- `compare()` (`rdflib.plugins.sparql.aggregates.Maximum` method), 384
- `compare()` (`rdflib.plugins.sparql.aggregates.Minimum` method), 384
- `compatible()` (`rdflib.plugins.sparql.sparql.FrozenDict` method), 420
- `compensate` (`rdflib.namespace.ODRL2` attribute), 165
- `compensatedParty` (`rdflib.namespace.ODRL2` attribute), 165
- `compensatingParty` (`rdflib.namespace.ODRL2` attribute), 165
- `competencyRequired` (`rdflib.namespace.SDO` attribute), 251
- `competitor` (`rdflib.namespace.SDO` attribute), 251
- `CompilationAlbum` (`rdflib.namespace.SDO` attribute), 197
- `complementOf` (`rdflib.extras.infixowl.Class` property), 63
- `complementOf` (`rdflib.namespace.OWL` attribute), 174
- `Completed` (`rdflib.namespace.SDO` attribute), 197
- `CompletedActionStatus` (`rdflib.namespace.SDO` attribute), 197
- `CompleteDataFeed` (`rdflib.namespace.SDO` attribute), 197
- `component` (`rdflib.namespace.PROV` attribute), 180
- `component` (`rdflib.namespace.QB` attribute), 186
- `componentAttachment` (`rdflib.namespace.QB` attribute), 186
- `ComponentProperty` (`rdflib.namespace.QB` attribute), 185
- `componentProperty` (`rdflib.namespace.QB` attribute), 186
- `componentRequired` (`rdflib.namespace.QB` attribute), 186
- `ComponentSet` (`rdflib.namespace.QB` attribute), 185
- `ComponentSpecification` (`rdflib.namespace.QB` attribute), 185
- `ComponentTerms()` (in module `rdflib.extras.infixowl`), 64
- `composer` (`rdflib.namespace.SDO` attribute), 251
- `CompoundLiteral` (`rdflib.namespace.RDF` attribute), 187
- `CompoundPriceSpecification` (`rdflib.namespace.SDO` attribute), 197
- `compressFormat` (`rdflib.namespace.DCAT` attribute), 144
- `Compressor` (`rdflib.namespace.BRICK` attribute), 81
- `comprisedOf` (`rdflib.namespace.SDO` attribute), 252
- `compute_qname()` (`rdflib.Graph` method), 593
- `compute_qname()` (`rdflib.graph.Graph` method), 498
- `compute_qname()` (`rdflib.graph.ReadOnlyGraphAggregate` method), 512
- `compute_qname()` (`rdflib.namespace.NamespaceManager` method), 161
- `compute_qname_strict()` (`rdflib.namespace.NamespaceManager` method), 161
- `Computer_Room_Air_Conditioning` (`rdflib.namespace.BRICK` attribute), 81
- `ComputerLanguage` (`rdflib.namespace.SDO` attribute), 197
- `ComputerStore` (`rdflib.namespace.SDO` attribute), 197
- `CompValue` (class in `rdflib.plugins.sparql.parserutils`), 410
- `concept` (`rdflib.namespace.QB` attribute), 186
- `Concept` (`rdflib.namespace.SKOS` attribute), 305
- `ConceptScheme` (`rdflib.namespace.SKOS` attribute), 305
- `Concession` (`rdflib.namespace.BRICK` attribute), 81
- `ConcurrentStore` (class in `rdflib.plugins.stores.concurrent`), 435
- `concurrentUse` (`rdflib.namespace.ODRL2` attribute), 165
- `Condensate_Leak_Alarm` (`rdflib.namespace.BRICK` attribute), 81
- `Condenser` (`rdflib.namespace.BRICK` attribute), 81
- `Condenser_Heat_Exchanger` (`rdflib.namespace.BRICK` attribute), 82
- `Condenser_Water` (`rdflib.namespace.BRICK` attribute), 82
- `Condenser_Water_Bypass_Valve` (`rdflib.namespace.BRICK` attribute), 82
- `Condenser_Water_Isolation_Valve` (`rdflib.namespace.BRICK` attribute), 82
- `Condenser_Water_Pump` (`rdflib.namespace.BRICK` attribute), 82
- `Condenser_Water_System` (`rdflib.namespace.BRICK` attribute), 82
- `Condenser_Water_Temperature_Sensor` (`rd-`

- flib.namespace.BRICK* attribute), 82
- Condenser\_Water\_Valve (*rdflib.namespace.BRICK* attribute), 82
- Condensing\_Natural\_Gas\_Boiler (*rdflib.namespace.BRICK* attribute), 82
- condition (*rdflib.namespace.SH* attribute), 301
- ConditionalAndExpression() (in module *rdflib.plugins.sparql.operators*), 403
- ConditionalOrExpression() (in module *rdflib.plugins.sparql.operators*), 404
- conditionsOfAccess (*rdflib.namespace.SDO* attribute), 252
- Conductivity\_Sensor (*rdflib.namespace.BRICK* attribute), 82
- Conference\_Room (*rdflib.namespace.BRICK* attribute), 82
- ConfirmAction (*rdflib.namespace.SDO* attribute), 197
- confirmationNumber (*rdflib.namespace.SDO* attribute), 252
- conflict (*rdflib.namespace.ODRL2* attribute), 165
- ConflictTerm (*rdflib.namespace.ODRL2* attribute), 163
- conforms (*rdflib.namespace.SH* attribute), 301
- conformsTo (*rdflib.namespace.DCTERMS* attribute), 147
- ConjunctiveGraph (class in *rdflib*), 576
- ConjunctiveGraph (class in *rdflib.graph*), 482
- connected() (*rdflib.Graph* method), 593
- connected() (*rdflib.graph.Graph* method), 498
- connectedTo (*rdflib.namespace.SDO* attribute), 252
- consentedParty (*rdflib.namespace.ODRL2* attribute), 165
- consentingParty (*rdflib.namespace.ODRL2* attribute), 165
- consequence (*rdflib.namespace.ODRL2* attribute), 165
- Consortium (*rdflib.namespace.SDO* attribute), 197
- Constant\_Air\_Volume\_Box (*rdflib.namespace.BRICK* attribute), 82
- constrainingProperty (*rdflib.namespace.SDO* attribute), 252
- Constraint (*rdflib.namespace.ODRL2* attribute), 163
- constraint (*rdflib.namespace.ODRL2* attribute), 165
- ConstraintComponent (*rdflib.namespace.SH* attribute), 297
- constraints (*rdflib.namespace.PROV* attribute), 180
- construct (*rdflib.namespace.SH* attribute), 301
- ConsumeAction (*rdflib.namespace.SDO* attribute), 197
- Contact\_Sensor (*rdflib.namespace.BRICK* attribute), 82
- contactlessPayment (*rdflib.namespace.SDO* attribute), 252
- contactOption (*rdflib.namespace.SDO* attribute), 252
- ContactPage (*rdflib.namespace.SDO* attribute), 197
- contactPoint (*rdflib.namespace.DCAT* attribute), 144
- ContactPoint (*rdflib.namespace.SDO* attribute), 197
- contactPoint (*rdflib.namespace.SDO* attribute), 252
- ContactPointOption (*rdflib.namespace.SDO* attribute), 197
- contactPoints (*rdflib.namespace.SDO* attribute), 252
- contactType (*rdflib.namespace.SDO* attribute), 252
- ContagiousnessHealthAspect (*rdflib.namespace.SDO* attribute), 197
- containedIn (*rdflib.namespace.SDO* attribute), 252
- containedInPlace (*rdflib.namespace.SDO* attribute), 252
- Container (class in *rdflib.container*), 471
- Container (*rdflib.namespace.RDFS* attribute), 188
- container (*rdflib.plugins.shared.jsonld.context.Term* attribute), 369
- ContainerMembershipProperty (*rdflib.namespace.RDFS* attribute), 188
- containsPlace (*rdflib.namespace.SDO* attribute), 252
- containsSeason (*rdflib.namespace.SDO* attribute), 252
- content\_type (*rdflib.parser.PythonInputSource* attribute), 517
- content\_type (*rdflib.parser.StringInputSource* attribute), 518
- contentLocation (*rdflib.namespace.SDO* attribute), 252
- contentRating (*rdflib.namespace.SDO* attribute), 252
- contentReferenceTime (*rdflib.namespace.SDO* attribute), 252
- contentSize (*rdflib.namespace.SDO* attribute), 252
- contentType (*rdflib.namespace.SDO* attribute), 252
- contentUrl (*rdflib.namespace.SDO* attribute), 252
- Context (class in *rdflib.plugins.shared.jsonld.context*), 364
- context (*rdflib.plugins.shared.jsonld.context.Term* attribute), 369
- context\_aware (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* attribute), 433
- context\_aware (*rdflib.plugins.stores.memory.Memory* attribute), 437
- context\_aware (*rdflib.store.Store* attribute), 549
- context\_from\_urlinputsource() (in module *rdflib.plugins.shared.jsonld.util*), 370
- context\_id() (*rdflib.ConjunctiveGraph* method), 577
- context\_id() (*rdflib.graph.ConjunctiveGraph* method), 483
- contexts() (*rdflib.ConjunctiveGraph* method), 578
- contexts() (*rdflib.Dataset* method), 583
- contexts() (*rdflib.graph.ConjunctiveGraph* method), 483
- contexts() (*rdflib.graph.Dataset* method), 489
- contexts() (*rdflib.plugins.stores.auditable.AuditableStore* method), 430
- contexts() (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 433
- contexts() (*rdflib.plugins.stores.memory.Memory* method), 430

- method*), 437
- `contexts()` (*rdflib.plugins.stores.regexmatching.REGEXMatching* *flib.namespace.BRICK* attribute), 83
- method*), 442
- `contexts()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* *flib.namespace.BRICK* attribute), 83
- method*), 447
- `contexts()` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* (*rdflib.namespace.BRICK* attribute), 83
- method*), 454
- `contexts()` (*rdflib.store.Store* *method*), 549
- `Continent` (*rdflib.namespace.SDO* attribute), 197
- `contractedParty` (*rdflib.namespace.ODRL2* attribute), 165
- `contractingParty` (*rdflib.namespace.ODRL2* attribute), 165
- `contraindication` (*rdflib.namespace.SDO* attribute), 252
- `Contribute` (*rdflib.namespace.PROV* attribute), 178
- `contributed` (*rdflib.namespace.PROV* attribute), 180
- `contributor` (*rdflib.namespace.DC* attribute), 142
- `contributor` (*rdflib.namespace.DCTERMS* attribute), 147
- `Contributor` (*rdflib.namespace.PROV* attribute), 178
- `contributor` (*rdflib.namespace.SDO* attribute), 252
- `Control_Room` (*rdflib.namespace.BRICK* attribute), 82
- `ControlAction` (*rdflib.namespace.SDO* attribute), 197
- `ConvenienceStore` (*rdflib.namespace.SDO* attribute), 197
- `Conversation` (*rdflib.namespace.SDO* attribute), 197
- `conversionEfficiency` (*rdflib.namespace.BRICK* attribute), 135
- `convert()` (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* *method*), 343
- `convert()` (*rdflib.tools.csv2rdf.CSV2RDF* *method*), 459
- `convertTerm()` (*rdflib.plugins.sparql.results.csvresults.CSVResult* *method*), 372
- `convertTerm()` (*rdflib.plugins.sparql.results.tsvresults.TSVResult* *method*), 375
- `CookAction` (*rdflib.namespace.SDO* attribute), 197
- `cookingMethod` (*rdflib.namespace.SDO* attribute), 252
- `cookTime` (*rdflib.namespace.SDO* attribute), 252
- `Cooling_Coil` (*rdflib.namespace.BRICK* attribute), 82
- `Cooling_Command` (*rdflib.namespace.BRICK* attribute), 82
- `Cooling_Demand_Sensor` (*rdflib.namespace.BRICK* attribute), 82
- `Cooling_Demand_Setpoint` (*rdflib.namespace.BRICK* attribute), 82
- `Cooling_Discharge_Air_Flow_Setpoint` (*rdflib.namespace.BRICK* attribute), 82
- `Cooling_Discharge_Air_Temperature_Deadband_Setpoint` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Discharge_Air_Temperature_Integral_Time_Parameter` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Discharge_Air_Temperature_Proportional_Band_Parameter` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Start_Stop_Status` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Supply_Air_Flow_Setpoint` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Supply_Air_Temperature_Deadband_Setpoint` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Supply_Air_Temperature_Integral_Time_Parameter` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Supply_Air_Temperature_Proportional_Band_Parameter` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Tower` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Tower_Fan` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Valve` (*rdflib.namespace.BRICK* attribute), 83
- `coolingCapacity` (*rdflib.namespace.BRICK* attribute), 135
- `CoOp` (*rdflib.namespace.SDO* attribute), 196
- `coordinateDimension` (*rdflib.namespace.GEO* attribute), 154
- `coordinates` (*rdflib.namespace.BRICK* attribute), 135
- `copy` (*rdflib.namespace.ODRL2* attribute), 165
- `copy()` (*rdflib.extras.infixowl.BooleanClass* *method*), 62
- `Copy_Room` (*rdflib.namespace.BRICK* attribute), 83
- `Copyright` (*rdflib.namespace.PROV* attribute), 178
- `copyrightHolder` (*rdflib.namespace.SDO* attribute), 252
- `copyrightNotice` (*rdflib.namespace.SDO* attribute), 252
- `copyrightYear` (*rdflib.namespace.SDO* attribute), 253
- `core` (*rdflib.namespace.ODRL2* attribute), 165
- `Cooling_Temperature_Sensor` (*rdflib.namespace.BRICK* attribute), 83
- `Cooling_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 83
- `Corporation` (*rdflib.namespace.SDO* attribute), 197
- `correction` (*rdflib.namespace.SDO* attribute), 253
- `CorrectionComment` (*rdflib.namespace.SDO* attribute), 197
- `correctionsPolicy` (*rdflib.namespace.SDO* attribute), 253
- `costCategory` (*rdflib.namespace.SDO* attribute), 253
- `costCurrency` (*rdflib.namespace.SDO* attribute), 253
- `costOrigin` (*rdflib.namespace.SDO* attribute), 253
- `costPerUnit` (*rdflib.namespace.SDO* attribute), 253
- `count` (*rdflib.namespace.ODRL2* attribute), 166
- `Counter` (*class in rdflib.plugins.sparql.aggregates*), 382
- `countriesNotSupported` (*rdflib.namespace.SDO* attribute), 253
- `countriesSupported` (*rdflib.namespace.SDO* attribute), 253
- `Country` (*rdflib.namespace.SDO* attribute), 198
- `countryOfAssembly` (*rdflib.namespace.SDO* attribute), 198



- 253
- countryOfLastProcessing (rdflib.namespace.SDO attribute), 253
- countryOfOrigin (rdflib.namespace.SDO attribute), 253
- Course (rdflib.namespace.SDO attribute), 198
- course (rdflib.namespace.SDO attribute), 253
- courseCode (rdflib.namespace.SDO attribute), 253
- CourseInstance (rdflib.namespace.SDO attribute), 198
- courseMode (rdflib.namespace.SDO attribute), 253
- coursePrerequisites (rdflib.namespace.SDO attribute), 253
- courseWorkload (rdflib.namespace.SDO attribute), 253
- Courthouse (rdflib.namespace.SDO attribute), 198
- coverage (rdflib.namespace.DC attribute), 142
- coverage (rdflib.namespace.DCTERMS attribute), 147
- coverageEndTime (rdflib.namespace.SDO attribute), 253
- coverageStartTime (rdflib.namespace.SDO attribute), 253
- CoverArt (rdflib.namespace.SDO attribute), 198
- CovidTestingFacility (rdflib.namespace.SDO attribute), 198
- CRAC (rdflib.namespace.BRICK attribute), 78
- Create (rdflib.namespace.PROV attribute), 178
- create() (rdflib.plugins.stores.sparqlstore.SPARQLStore method), 447
- create() (rdflib.store.Store method), 549
- create\_parser() (in module rdflib.plugins.parsers.rdfxml), 348
- create\_parser() (in module rdflib.plugins.parsers.trix), 353
- CreateAction (rdflib.namespace.SDO attribute), 198
- created (rdflib.namespace.DCTERMS attribute), 147
- created (rdflib.namespace.DOAP attribute), 150
- CreativeWork (rdflib.namespace.SDO attribute), 198
- CreativeWorkSeason (rdflib.namespace.SDO attribute), 198
- CreativeWorkSeries (rdflib.namespace.SDO attribute), 198
- creativeWorkStatus (rdflib.namespace.SDO attribute), 253
- creator (rdflib.namespace.DC attribute), 142
- creator (rdflib.namespace.DCTERMS attribute), 147
- Creator (rdflib.namespace.PROV attribute), 178
- creator (rdflib.namespace.SDO attribute), 253
- credentialCategory (rdflib.namespace.SDO attribute), 253
- CreditCard (rdflib.namespace.SDO attribute), 198
- creditedTo (rdflib.namespace.SDO attribute), 253
- creditText (rdflib.namespace.SDO attribute), 253
- Crematorium (rdflib.namespace.SDO attribute), 198
- CriticReview (rdflib.namespace.SDO attribute), 198
- CrossSectional (rdflib.namespace.SDO attribute), 198
- cssSelector (rdflib.namespace.SDO attribute), 253
- CssSelectorType (rdflib.namespace.SDO attribute), 198
- CSV2RDF (class in rdflib.tools.csv2rdf), 459
- csvEncodedTabularData (rdflib.namespace.CSVW attribute), 138
- CSVResultParser (class in rdflib.plugins.sparql.results.csvresults), 371
- CSVResultSerializer (class in rdflib.plugins.sparql.results.csvresults), 372
- CSVW (class in rdflib.namespace), 137
- CT (rdflib.namespace.SDO attribute), 195
- Cubicle (rdflib.namespace.BRICK attribute), 83
- curie() (rdflib.namespace.NamespaceManager method), 161
- currenciesAccepted (rdflib.namespace.SDO attribute), 254
- currency (rdflib.namespace.SDO attribute), 254
- CurrencyConversionService (rdflib.namespace.SDO attribute), 198
- current (rdflib.plugins.parsers.rdfxml.RDFXMLHandler property), 344
- Current\_Imbalance\_Sensor (rdflib.namespace.BRICK attribute), 83
- Current\_Limit (rdflib.namespace.BRICK attribute), 84
- Current\_Output\_Sensor (rdflib.namespace.BRICK attribute), 84
- Current\_Sensor (rdflib.namespace.BRICK attribute), 84
- currentExchangeRate (rdflib.namespace.SDO attribute), 254
- currentFlowType (rdflib.namespace.BRICK attribute), 135
- currentProject (rdflib.namespace.FOAF attribute), 152
- Curtailment\_Override\_Command (rdflib.namespace.BRICK attribute), 84
- CUSTOM\_EVALS (in module rdflib.plugins.sparql), 428
- custom\_function() (in module rdflib.plugins.sparql.operators), 406
- customer (rdflib.namespace.SDO attribute), 254
- customerRemorseReturnFees (rdflib.namespace.SDO attribute), 254
- customerRemorseReturnLabelSource (rdflib.namespace.SDO attribute), 254
- customerRemorseReturnShippingFeesAmount (rdflib.namespace.SDO attribute), 254
- customEval() (in module examples.custom\_eval), 22
- customName (rdflib.plugins.sparql.parserutils.ParamList attribute), 412
- cutoffTime (rdflib.namespace.SDO attribute), 254
- cvdCollectionDate (rdflib.namespace.SDO attribute), 254
- cvdFacilityCounty (rdflib.namespace.SDO attribute),

- 254  
 cvdFacilityId (*rdflib.namespace.SDO* attribute), 254  
 cvdNumBeds (*rdflib.namespace.SDO* attribute), 254  
 cvdNumBedsOcc (*rdflib.namespace.SDO* attribute), 254  
 cvdNumC19Died (*rdflib.namespace.SDO* attribute), 254  
 cvdNumC19HOPats (*rdflib.namespace.SDO* attribute), 254  
 cvdNumC19HospPats (*rdflib.namespace.SDO* attribute), 254  
 cvdNumC19MechVentPats (*rdflib.namespace.SDO* attribute), 254  
 cvdNumC190FMechVentPats (*rdflib.namespace.SDO* attribute), 254  
 cvdNumC190verflowPats (*rdflib.namespace.SDO* attribute), 254  
 cvdNumICUBeds (*rdflib.namespace.SDO* attribute), 254  
 cvdNumICUBedsOcc (*rdflib.namespace.SDO* attribute), 254  
 cvdNumTotBeds (*rdflib.namespace.SDO* attribute), 254  
 cvdNumVent (*rdflib.namespace.SDO* attribute), 254  
 cvdNumVentUse (*rdflib.namespace.SDO* attribute), 255  
 CVSRepository (*rdflib.namespace.DOAP* attribute), 149  
 Cycle\_Alarm (*rdflib.namespace.BRICK* attribute), 84
- ## D
- DamagedCondition (*rdflib.namespace.SDO* attribute), 198  
 Damper (*rdflib.namespace.BRICK* attribute), 84  
 Damper\_Command (*rdflib.namespace.BRICK* attribute), 84  
 Damper\_Position\_Command (*rdflib.namespace.BRICK* attribute), 84  
 Damper\_Position\_Sensor (*rdflib.namespace.BRICK* attribute), 84  
 Damper\_Position\_Setpoint (*rdflib.namespace.BRICK* attribute), 84  
 DanceEvent (*rdflib.namespace.SDO* attribute), 198  
 DanceGroup (*rdflib.namespace.SDO* attribute), 198  
 DarcsRepository (*rdflib.namespace.DOAP* attribute), 149  
 data (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342  
 DataCatalog (*rdflib.namespace.SDO* attribute), 198  
 DataDownload (*rdflib.namespace.SDO* attribute), 198  
 dataDump (*rdflib.namespace.VOID* attribute), 314  
 DataFeed (*rdflib.namespace.SDO* attribute), 198  
 dataFeedElement (*rdflib.namespace.SDO* attribute), 255  
 DataFeedItem (*rdflib.namespace.SDO* attribute), 198  
 DataRange (*rdflib.namespace.OWL* attribute), 173  
 DataService (*rdflib.namespace.DCAT* attribute), 143  
 Dataset (*class in rdflib*), 580  
 Dataset (*class in rdflib.graph*), 485  
 Dataset (*rdflib.namespace.DCAT* attribute), 143  
 dataset (*rdflib.namespace.DCAT* attribute), 144  
 Dataset (*rdflib.namespace.DCMITYPE* attribute), 145  
 DataSet (*rdflib.namespace.QB* attribute), 185  
 dataSet (*rdflib.namespace.QB* attribute), 186  
 Dataset (*rdflib.namespace.SDO* attribute), 199  
 dataset (*rdflib.namespace.SDO* attribute), 255  
 Dataset (*rdflib.namespace.VOID* attribute), 313  
 dataset (*rdflib.plugins.sparql.sparql.QueryContext* property), 423  
 DatasetDescription (*rdflib.namespace.VOID* attribute), 313  
 datasetTimeInterval (*rdflib.namespace.SDO* attribute), 255  
 DataStructureDefinition (*rdflib.namespace.QB* attribute), 185  
 datatype (*rdflib.Literal* property), 611  
 Datatype (*rdflib.namespace.CSVW* attribute), 138  
 datatype (*rdflib.namespace.CSVW* attribute), 138  
 dataType (*rdflib.namespace.ODRL2* attribute), 166  
 Datatype (*rdflib.namespace.RDFS* attribute), 188  
 DataType (*rdflib.namespace.SDO* attribute), 198  
 datatype (*rdflib.namespace.SH* attribute), 301  
 datatype (*rdflib.plugins.parsers.RDFVOC.RDFVOC* attribute), 319  
 datatype (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342  
 datatype (*rdflib.term.Literal* property), 564  
 datatypeComplementOf (*rdflib.namespace.OWL* attribute), 174  
 DatatypeConstraintComponent (*rdflib.namespace.SH* attribute), 297  
 DatatypeProperty (*rdflib.namespace.OWL* attribute), 173  
 date (*rdflib.namespace.DC* attribute), 142  
 date (*rdflib.namespace.DCTERMS* attribute), 147  
 Date (*rdflib.namespace.SDO* attribute), 199  
 date (*rdflib.namespace.XSD* attribute), 316  
 date() (*in module rdflib.plugins.sparql.operators*), 406  
 date\_time() (*in module rdflib.util*), 570  
 dateAccepted (*rdflib.namespace.DCTERMS* attribute), 147  
 dateCopyrighted (*rdflib.namespace.DCTERMS* attribute), 147  
 dateCreated (*rdflib.namespace.SDO* attribute), 255  
 dateDeleted (*rdflib.namespace.SDO* attribute), 255  
 DatedMoneySpecification (*rdflib.namespace.SDO* attribute), 199  
 dateIssued (*rdflib.namespace.SDO* attribute), 255  
 dateline (*rdflib.namespace.SDO* attribute), 255  
 dateModified (*rdflib.namespace.SDO* attribute), 255  
 datePosted (*rdflib.namespace.SDO* attribute), 255  
 datePublished (*rdflib.namespace.SDO* attribute), 255  
 dateRead (*rdflib.namespace.SDO* attribute), 255  
 dateReceived (*rdflib.namespace.SDO* attribute), 255

- `dateSent` (*rdflib.namespace.SDO* attribute), 255
- `dateSubmitted` (*rdflib.namespace.DCTERMS* attribute), 147
- `dateTime` (*rdflib.namespace.ODRL2* attribute), 166
- `DateTime` (*rdflib.namespace.SDO* attribute), 199
- `dateTime` (*rdflib.namespace.XSD* attribute), 316
- `datetime()` (in module *rdflib.plugins.sparql.operators*), 406
- `DateTimeDescription` (*rdflib.namespace.TIME* attribute), 309
- `DateTimeInterval` (*rdflib.namespace.TIME* attribute), 309
- `dateTimeObjects()` (in module *rdflib.plugins.sparql.operators*), 406
- `dateTimeStamp` (*rdflib.namespace.XSD* attribute), 316
- `dateVehicleFirstRegistered` (*rdflib.namespace.SDO* attribute), 255
- `day` (*rdflib.namespace.TIME* attribute), 310
- `day` (*rdflib.namespace.XSD* attribute), 316
- `DayOfWeek` (*rdflib.namespace.SDO* attribute), 199
- `dayOfWeek` (*rdflib.namespace.SDO* attribute), 255
- `DayOfWeek` (*rdflib.namespace.TIME* attribute), 309
- `dayOfWeek` (*rdflib.namespace.TIME* attribute), 310
- `dayOfYear` (*rdflib.namespace.TIME* attribute), 310
- `days` (*rdflib.namespace.TIME* attribute), 310
- `DaySpa` (*rdflib.namespace.SDO* attribute), 199
- `dayTimeDuration` (*rdflib.namespace.XSD* attribute), 316
- `db_env` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* attribute), 434
- `DC` (class in *rdflib.namespace*), 142
- `DC_Bus_Voltage_Sensor` (*rdflib.namespace.BRICK* attribute), 84
- `DCAM` (class in *rdflib.namespace*), 143
- `DCAT` (class in *rdflib.namespace*), 143
- `DCMITYPE` (class in *rdflib.namespace*), 144
- `DCMIType` (*rdflib.namespace.DCTERMS* attribute), 145
- `DCTERMS` (class in *rdflib.namespace*), 145
- `DDC` (*rdflib.namespace.DCTERMS* attribute), 145
- `DDxElement` (*rdflib.namespace.SDO* attribute), 198
- `de_skolemize()` (*rdflib.Graph* method), 593
- `de_skolemize()` (*rdflib.graph.Graph* method), 498
- `de_skolemize()` (*rdflib.term.URIRef* method), 568
- `de_skolemize()` (*rdflib.URIRef* method), 617
- `DeactivateAction` (*rdflib.namespace.SDO* attribute), 199
- `deactivated` (*rdflib.namespace.SH* attribute), 301
- `Deadband_Setpoint` (*rdflib.namespace.BRICK* attribute), 84
- `deathDate` (*rdflib.namespace.SDO* attribute), 255
- `deathPlace` (*rdflib.namespace.SDO* attribute), 255
- `Deceleration_Time_Setpoint` (*rdflib.namespace.BRICK* attribute), 84
- `decimal` (*rdflib.namespace.XSD* attribute), 316
- `decimalChar` (*rdflib.namespace.CSVW* attribute), 138
- `declare` (*rdflib.namespace.SH* attribute), 301
- `declared` (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342
- `declareExistential()` (*rdflib.plugins.parsers.notation3.Formula* method), 323
- `decodeStringEscape()` (in module *rdflib.compat*), 470
- `decodeUnicodeEscape()` (in module *rdflib.compat*), 470
- `DecontextualizedContent` (*rdflib.namespace.SDO* attribute), 199
- `Dedicated_Outdoor_Air_System_Unit` (*rdflib.namespace.BRICK* attribute), 84
- `DeepClassClear()` (in module *rdflib.extras.infixowl*), 64
- `default` (*rdflib.namespace.CSVW* attribute), 138
- `default_cast()` (in module *rdflib.plugins.sparql.operators*), 406
- `default_context` (*rdflib.ConjunctiveGraph* attribute), 578
- `default_context` (*rdflib.Dataset* attribute), 583
- `default_context` (*rdflib.graph.Dataset* attribute), 489
- `default_context` (*rdflib.graph.ReadOnlyGraphAggregate* attribute), 512
- `defaultGeometry` (*rdflib.namespace.GEO* attribute), 154
- `defaultValue` (*rdflib.namespace.SDO* attribute), 255
- `defaultValue` (*rdflib.namespace.SH* attribute), 301
- `DefenceEstablishment` (*rdflib.namespace.SDO* attribute), 199
- `Defined` (class in *rdflib.plugins.shared.jsonld.context*), 369
- `DefinedNamespace` (class in *rdflib.namespace*), 150
- `DefinedRegion` (*rdflib.namespace.SDO* attribute), 199
- `DefinedTerm` (*rdflib.namespace.SDO* attribute), 199
- `DefinedTermSet` (*rdflib.namespace.SDO* attribute), 199
- `definition` (*rdflib.namespace.PROV* attribute), 180
- `definition` (*rdflib.namespace.SKOS* attribute), 305
- `DefinitiveLegalValue` (*rdflib.namespace.SDO* attribute), 199
- `defrag()` (*rdflib.term.URIRef* method), 568
- `defrag()` (*rdflib.URIRef* method), 617
- `Dehumidification_Start_Stop_Status` (*rdflib.namespace.BRICK* attribute), 84
- `Deionised_Water_Conductivity_Sensor` (*rdflib.namespace.BRICK* attribute), 84
- `Deionised_Water_Level_Sensor` (*rdflib.namespace.BRICK* attribute), 84
- `Deionized_Water` (*rdflib.namespace.BRICK* attribute), 84
- `Deionized_Water_Alarm` (*rdflib.namespace.BRICK* attribute), 84
- `Delay_Parameter` (*rdflib.namespace.BRICK* attribute),



- 85
- delayPeriod (*rdflib.namespace.ODRL2* attribute), 166
- Delegation (*rdflib.namespace.PROV* attribute), 178
- delete (*rdflib.namespace.ODRL2* attribute), 166
- delete() (*rdflib.extras.infixowl.Individual* method), 67
- DeleteAction (*rdflib.namespace.SDO* attribute), 199
- delimiter (*rdflib.namespace.CSVW* attribute), 138
- deliveryAddress (*rdflib.namespace.SDO* attribute), 255
- deliveryChannel (*rdflib.namespace.ODRL2* attribute), 166
- DeliveryChargeSpecification (*rdflib.namespace.SDO* attribute), 199
- DeliveryEvent (*rdflib.namespace.SDO* attribute), 199
- deliveryLeadTime (*rdflib.namespace.SDO* attribute), 255
- DeliveryMethod (*rdflib.namespace.SDO* attribute), 199
- deliveryMethod (*rdflib.namespace.SDO* attribute), 255
- deliveryStatus (*rdflib.namespace.SDO* attribute), 255
- deliveryTime (*rdflib.namespace.SDO* attribute), 255
- DeliveryTimeSettings (*rdflib.namespace.SDO* attribute), 199
- Demand (*rdflib.namespace.SDO* attribute), 199
- Demand\_Sensor (*rdflib.namespace.BRICK* attribute), 85
- Demand\_Setpoint (*rdflib.namespace.BRICK* attribute), 85
- DemoAlbum (*rdflib.namespace.SDO* attribute), 199
- Dentist (*rdflib.namespace.SDO* attribute), 199
- Dentistry (*rdflib.namespace.SDO* attribute), 199
- DepartAction (*rdflib.namespace.SDO* attribute), 199
- department (*rdflib.namespace.SDO* attribute), 255
- DepartmentStore (*rdflib.namespace.SDO* attribute), 199
- departureAirport (*rdflib.namespace.SDO* attribute), 255
- departureBoatTerminal (*rdflib.namespace.SDO* attribute), 255
- departureBusStop (*rdflib.namespace.SDO* attribute), 255
- departureGate (*rdflib.namespace.SDO* attribute), 256
- departurePlatform (*rdflib.namespace.SDO* attribute), 256
- departureStation (*rdflib.namespace.SDO* attribute), 256
- departureTerminal (*rdflib.namespace.SDO* attribute), 256
- departureTime (*rdflib.namespace.SDO* attribute), 256
- dependencies (*rdflib.namespace.SDO* attribute), 256
- depiction (*rdflib.namespace.FOAF* attribute), 152
- depicts (*rdflib.namespace.FOAF* attribute), 152
- deployedOnPlatform (*rdflib.namespace.SSN* attribute), 308
- deployedSystem (*rdflib.namespace.SSN* attribute), 308
- Deployment (*rdflib.namespace.SSN* attribute), 308
- DepositAccount (*rdflib.namespace.SDO* attribute), 199
- deprecated (*rdflib.namespace.OWL* attribute), 174
- DeprecatedClass (*rdflib.namespace.OWL* attribute), 173
- DeprecatedProperty (*rdflib.namespace.OWL* attribute), 173
- depth (*rdflib.namespace.SDO* attribute), 256
- Derivation (*rdflib.namespace.PROV* attribute), 178
- Derivative\_Gain\_Parameter (*rdflib.namespace.BRICK* attribute), 85
- Derivative\_Time\_Parameter (*rdflib.namespace.BRICK* attribute), 85
- derive (*rdflib.namespace.ODRL2* attribute), 166
- derivedByInsertionFrom (*rdflib.namespace.PROV* attribute), 180
- derivedByRemovalFrom (*rdflib.namespace.PROV* attribute), 180
- Dermatologic (*rdflib.namespace.SDO* attribute), 199
- Dermatology (*rdflib.namespace.SDO* attribute), 200
- Describer (class in *rdflib.extras.describer*), 51
- describes (*rdflib.namespace.CSVW* attribute), 138
- describesService (*rdflib.namespace.PROV* attribute), 180
- description (*rdflib.namespace.DC* attribute), 142
- description (*rdflib.namespace.DCTERMS* attribute), 147
- description (*rdflib.namespace.DOAP* attribute), 150
- description (*rdflib.namespace.SDO* attribute), 256
- description (*rdflib.namespace.SH* attribute), 301
- Description (*rdflib.plugins.parsers.RDFVOC.RDFVOC* attribute), 319
- destroy() (*rdflib.Graph* method), 593
- destroy() (*rdflib.graph.Graph* method), 498
- destroy() (*rdflib.graph.ReadOnlyGraphAggregate* method), 512
- destroy() (*rdflib.plugins.stores.auditable.AuditableStore* method), 430
- destroy() (*rdflib.plugins.stores.regexmatching.REGEXMatching* method), 442
- destroy() (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 447
- destroy() (*rdflib.store.Store* method), 550
- detail (*rdflib.namespace.SH* attribute), 301
- detects (*rdflib.namespace.SSN* attribute), 308
- Detention\_Room (*rdflib.namespace.BRICK* attribute), 85
- developer (*rdflib.namespace.DOAP* attribute), 150
- device (*rdflib.namespace.ODRL2* attribute), 166
- device (*rdflib.namespace.SDO* attribute), 256
- Dew\_Point\_Setpoint (*rdflib.namespace.BRICK* attribute), 85
- Dewpoint\_Sensor (*rdflib.namespace.BRICK* attribute), 85
- DiabeticDiet (*rdflib.namespace.SDO* attribute), 200

- diagnosis (*rdflib.namespace.SDO* attribute), 256  
 Diagnostic (*rdflib.namespace.SDO* attribute), 200  
 DiagnosticLab (*rdflib.namespace.SDO* attribute), 200  
 DiagnosticProcedure (*rdflib.namespace.SDO* attribute), 200  
 diagram (*rdflib.namespace.SDO* attribute), 256  
 Dialect (*rdflib.namespace.CSVW* attribute), 138  
 dialect (*rdflib.namespace.CSVW* attribute), 138  
 Dictionary (*rdflib.namespace.PROV* attribute), 178  
 dictionary (*rdflib.namespace.PROV* attribute), 180  
 Diet (*rdflib.namespace.SDO* attribute), 200  
 diet (*rdflib.namespace.SDO* attribute), 256  
 DietarySupplement (*rdflib.namespace.SDO* attribute), 200  
 dietFeatures (*rdflib.namespace.SDO* attribute), 256  
 DietNutrition (*rdflib.namespace.SDO* attribute), 200  
 differentFrom (*rdflib.namespace.OWL* attribute), 174  
 Differential\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Bypass\_Valve (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Deadband\_Setpoint (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Integral\_Time\_Parameter (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Load\_Shed\_Status (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Proportional\_Band (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Sensor (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Setpoint (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Setpoint\_Limit (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Pressure\_Step\_Parameter (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Speed\_Sensor (*rdflib.namespace.BRICK* attribute), 85  
 Differential\_Speed\_Setpoint (*rdflib.namespace.BRICK* attribute), 86  
 Differential\_Supply\_Return\_Water\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 86  
 differentialDiagnosis (*rdflib.namespace.SDO* attribute), 256  
 DigitalAudioTapeFormat (*rdflib.namespace.SDO* attribute), 200  
 DigitalDocument (*rdflib.namespace.SDO* attribute), 200  
 DigitalDocumentPermission (*rdflib.namespace.SDO* attribute), 200  
 DigitalDocumentPermissionType (*rdflib.namespace.SDO* attribute), 200  
 DigitalFormat (*rdflib.namespace.SDO* attribute), 200  
 digitize (*rdflib.namespace.ODRL2* attribute), 166  
 dimension (*rdflib.namespace.GEO* attribute), 154  
 dimension (*rdflib.namespace.QB* attribute), 186  
 DimensionProperty (*rdflib.namespace.QB* attribute), 185  
 Dimmer (*rdflib.namespace.BRICK* attribute), 86  
 Direct\_Expansion\_Cooling\_Coil (*rdflib.namespace.BRICK* attribute), 86  
 Direct\_Expansion\_Heating\_Coil (*rdflib.namespace.BRICK* attribute), 86  
 directApply (*rdflib.namespace.SDO* attribute), 256  
 Direction (*rdflib.namespace.CSVW* attribute), 138  
 direction (*rdflib.namespace.RDF* attribute), 187  
 Direction\_Command (*rdflib.namespace.BRICK* attribute), 86  
 Direction\_Sensor (*rdflib.namespace.BRICK* attribute), 86  
 Direction\_Status (*rdflib.namespace.BRICK* attribute), 86  
 directive() (*rdflib.plugins.parsers.notation3.SinkParser* method), 329  
 directiveOrStatement() (*rdflib.plugins.parsers.notation3.SinkParser* method), 329  
 directiveOrStatement() (*rdflib.plugins.parsers.trig.TrigSinkParser* method), 349  
 director (*rdflib.namespace.SDO* attribute), 256  
 directors (*rdflib.namespace.SDO* attribute), 256  
 DirectQueryService (*rdflib.namespace.PROV* attribute), 178  
 DisabilitySupport (*rdflib.namespace.SDO* attribute), 200  
 Disable\_Command (*rdflib.namespace.BRICK* attribute), 86  
 Disable\_Differential\_Enthalpy\_Command (*rdflib.namespace.BRICK* attribute), 86  
 Disable\_Differential\_Temperature\_Command (*rdflib.namespace.BRICK* attribute), 86  
 Disable\_Fixed\_Enthalpy\_Command (*rdflib.namespace.BRICK* attribute), 86  
 Disable\_Fixed\_Temperature\_Command (*rdflib.namespace.BRICK* attribute), 86  
 Disable\_Hot\_Water\_System\_Outside\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 86  
 Disable\_Status (*rdflib.namespace.BRICK* attribute), 86  
 DisagreeAction (*rdflib.namespace.SDO* attribute), 200  
 disambiguatingDescription (*rdflib.namespace.SDO* attribute), 256  
 Discharge\_Air (*rdflib.namespace.BRICK* attribute), 86  
 Discharge\_Air\_Dewpoint\_Sensor (*rdflib.namespace.BRICK* attribute), 86  
 Discharge\_Air\_Duct\_Pressure\_Status (*rdflib.namespace.BRICK* attribute), 86



- flib.namespace.BRICK attribute*), 86
- Discharge\_Air\_Flow\_Demand\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 86
- Discharge\_Air\_Flow\_High\_Reset\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Flow\_Low\_Reset\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Flow\_Reset\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Flow\_Sensor (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Flow\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Humidity\_Sensor (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Humidity\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Smoke\_Detection\_Alarm (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Static\_Pressure\_Deadband\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Static\_Pressure\_Integral\_Time\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Static\_Pressure\_Proportional\_Band\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Static\_Pressure\_Sensor (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Static\_Pressure\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Static\_Pressure\_Step\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Temperature\_Alarm (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Temperature\_Cooling\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Temperature\_Deadband\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Temperature\_Heating\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 87
- Discharge\_Air\_Temperature\_High\_Reset\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Temperature\_Low\_Reset\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Temperature\_Proportional\_Band\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Temperature\_Reset\_Differential\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Temperature\_Sensor (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Temperature\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Temperature\_Setpoint\_Limit (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Temperature\_Step\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Air\_Velocity\_Pressure\_Sensor (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Chilled\_Water (*rdflib.namespace.BRICK  
attribute*), 88
- Discharge\_Fan (*rdflib.namespace.BRICK attribute*), 88
- Discharge\_Hot\_Water (*rdflib.namespace.BRICK  
attribute*), 88
- Discharge\_Water (*rdflib.namespace.BRICK attribute*), 88
- Discharge\_Water\_Differential\_Pressure\_Deadband\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Water\_Differential\_Pressure\_Integral\_Time\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Water\_Differential\_Pressure\_Proportional\_Band\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Water\_Flow\_Sensor (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Water\_Flow\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 88
- Discharge\_Water\_Temperature\_Alarm (*rd-  
flib.namespace.BRICK attribute*), 89
- Discharge\_Water\_Temperature\_Proportional\_Band\_Parameter (*rd-  
flib.namespace.BRICK attribute*), 89
- Discharge\_Water\_Temperature\_Sensor (*rd-  
flib.namespace.BRICK attribute*), 89
- Discharge\_Water\_Temperature\_Setpoint (*rd-  
flib.namespace.BRICK attribute*), 89
- Disconnect\_Switch (*rdflib.namespace.BRICK  
attribute*), 89
- Discontinued (*rdflib.namespace.SDO attribute*), 200
- discount (*rdflib.namespace.SDO attribute*), 256
- discountCode (*rdflib.namespace.SDO attribute*), 256
- discountCurrency (*rdflib.namespace.SDO attribute*), 256
- DiscoverAction (*rdflib.namespace.SDO attribute*), 200
- discusses (*rdflib.namespace.SDO attribute*), 256
- DiscussionForumPosting (*rdflib.namespace.SDO  
attribute*), 200
- discussionUrl (*rdflib.namespace.SDO attribute*), 256
- diseasePreventionInfo (*rdflib.namespace.SDO  
attribute*), 256
- diseaseSpreadStatistics (*rdflib.namespace.SDO  
attribute*), 256
- disjoint (*rdflib.namespace.SH attribute*), 301
- DisjointConstraintComponent (*rdflib.namespace.SH  
attribute*), 297
- disjointDomain() (*rd-  
flib.plugins.sparql.sparql.FrozenDict method*), 420
- disjointUnionOf (*rdflib.namespace.OWL attribute*), 174
- disjointWith (*rdflib.extras.infixowl.Class property*), 63
- disjointWith (*rdflib.namespace.OWL attribute*), 174

- DislikeAction (rdflib.namespace.SDO attribute), 200
- dispatch() (rdflib.events.Dispatcher method), 474
- Dispatcher (class in rdflib.events), 474
- Displacement\_Flow\_Air\_Diffuser (rdflib.namespace.BRICK attribute), 89
- display (rdflib.namespace.ODRL2 attribute), 166
- dissolutionDate (rdflib.namespace.SDO attribute), 257
- Distance (rdflib.namespace.SDO attribute), 200
- distance (rdflib.namespace.SDO attribute), 257
- DistanceFee (rdflib.namespace.SDO attribute), 200
- Distillery (rdflib.namespace.SDO attribute), 200
- distinctMembers (rdflib.namespace.OWL attribute), 174
- distinctObjects (rdflib.namespace.VOID attribute), 314
- distinctSubjects (rdflib.namespace.VOID attribute), 314
- distinguishingSign (rdflib.namespace.SDO attribute), 257
- distribute (rdflib.namespace.ODRL2 attribute), 166
- Distribution (rdflib.namespace.DCAT attribute), 143
- distribution (rdflib.namespace.DCAT attribute), 144
- distribution (rdflib.namespace.SDO attribute), 257
- Distribution\_Frame (rdflib.namespace.BRICK attribute), 89
- diversityPolicy (rdflib.namespace.SDO attribute), 257
- diversityStaffingReport (rdflib.namespace.SDO attribute), 257
- DJMixAlbum (rdflib.namespace.SDO attribute), 198
- dm (rdflib.namespace.PROV attribute), 180
- dnaChecksum (rdflib.namespace.FOAF attribute), 152
- DOAP (class in rdflib.namespace), 149
- DOAS (rdflib.namespace.BRICK attribute), 84
- Document (rdflib.namespace.FOAF attribute), 151
- document\_element\_start() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 344
- documentation (rdflib.namespace.SDO attribute), 257
- documenter (rdflib.namespace.DOAP attribute), 150
- documents (rdflib.namespace.VOID attribute), 314
- doesNotShip (rdflib.namespace.SDO attribute), 257
- doList() (rdflib.plugins.serializers.longturtle.LongTurtleSerializer method), 355
- doList() (rdflib.plugins.serializers.turtle.TurtleSerializer method), 362
- domain (rdflib.extras.infixowl.Property property), 70
- domain (rdflib.namespace.RDFS attribute), 188
- domainIncludes (rdflib.namespace.DCAM attribute), 143
- domainIncludes (rdflib.namespace.SDO attribute), 257
- Domestic\_Hot\_Water\_Supply\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 89
- Domestic\_Hot\_Water\_Supply\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 89
- Domestic\_Hot\_Water\_System (rdflib.namespace.BRICK attribute), 89
- Domestic\_Hot\_Water\_System\_Enable\_Command (rdflib.namespace.BRICK attribute), 89
- Domestic\_Hot\_Water\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 89
- Domestic\_Hot\_Water\_Valve (rdflib.namespace.BRICK attribute), 89
- Domestic\_Water (rdflib.namespace.BRICK attribute), 89
- Domestic\_Water\_Loop (rdflib.namespace.BRICK attribute), 89
- domiciledMortgage (rdflib.namespace.SDO attribute), 257
- DonateAction (rdflib.namespace.SDO attribute), 200
- dont\_care() (rdflib.plugins.sparql.aggregates.Accumulator method), 380
- doorTime (rdflib.namespace.SDO attribute), 257
- dosageForm (rdflib.namespace.SDO attribute), 257
- DoseSchedule (rdflib.namespace.SDO attribute), 200
- doseSchedule (rdflib.namespace.SDO attribute), 257
- doseUnit (rdflib.namespace.SDO attribute), 257
- doseValue (rdflib.namespace.SDO attribute), 257
- double (rdflib.namespace.XSD attribute), 316
- DoubleBlindedTrial (rdflib.namespace.SDO attribute), 200
- doubleQuote (rdflib.namespace.CSVW attribute), 138
- DownloadAction (rdflib.namespace.SDO attribute), 200
- downloadURL (rdflib.namespace.DCAT attribute), 144
- downloadUrl (rdflib.namespace.SDO attribute), 257
- Downpayment (rdflib.namespace.SDO attribute), 201
- downPayment (rdflib.namespace.SDO attribute), 257
- downvoteCount (rdflib.namespace.SDO attribute), 257
- drainsTo (rdflib.namespace.SDO attribute), 257
- DrawAction (rdflib.namespace.SDO attribute), 201
- Drawing (rdflib.namespace.SDO attribute), 201
- Drench\_Hose (rdflib.namespace.BRICK attribute), 89
- DrinkAction (rdflib.namespace.SDO attribute), 201
- Drive\_Ready\_Status (rdflib.namespace.BRICK attribute), 89
- driveWheelConfiguration (rdflib.namespace.SDO attribute), 257
- DriveWheelConfigurationValue (rdflib.namespace.SDO attribute), 201
- DrivingSchoolVehicleUsage (rdflib.namespace.SDO attribute), 201
- dropoffLocation (rdflib.namespace.SDO attribute), 257
- dropoffTime (rdflib.namespace.SDO attribute), 257
- Drug (rdflib.namespace.SDO attribute), 201
- drug (rdflib.namespace.SDO attribute), 257
- DrugClass (rdflib.namespace.SDO attribute), 201

- drugClass (rdflib.namespace.SDO attribute), 257
- DrugCost (rdflib.namespace.SDO attribute), 201
- DrugCostCategory (rdflib.namespace.SDO attribute), 201
- DrugLegalStatus (rdflib.namespace.SDO attribute), 201
- DrugPregnancyCategory (rdflib.namespace.SDO attribute), 201
- DrugPrescriptionStatus (rdflib.namespace.SDO attribute), 201
- DrugStrength (rdflib.namespace.SDO attribute), 201
- drugUnit (rdflib.namespace.SDO attribute), 257
- DryCleaningOrLaundry (rdflib.namespace.SDO attribute), 201
- DummySink (class in rdflib.plugins.parsers.ntriples), 338
- dumps() (rdflib.store.NodePickler method), 547
- duns (rdflib.namespace.SDO attribute), 257
- duplicateTherapy (rdflib.namespace.SDO attribute), 257
- Duration (rdflib.namespace.SDO attribute), 201
- duration (rdflib.namespace.SDO attribute), 258
- Duration (rdflib.namespace.TIME attribute), 309
- duration (rdflib.namespace.XSD attribute), 316
- Duration\_Sensor (rdflib.namespace.BRICK attribute), 90
- DurationDescription (rdflib.namespace.TIME attribute), 309
- durationOfWarranty (rdflib.namespace.SDO attribute), 258
- duringMedia (rdflib.namespace.SDO attribute), 258
- Duty (rdflib.namespace.ODRL2 attribute), 163
- duty (rdflib.namespace.ODRL2 attribute), 166
- DVDFormat (rdflib.namespace.SDO attribute), 198
- E**
- Ear (rdflib.namespace.SDO attribute), 202
- earlyPrepaymentPenalty (rdflib.namespace.SDO attribute), 258
- eat() (rdflib.plugins.parsers.ntriples.W3CNTriplesParser method), 340
- EatAction (rdflib.namespace.SDO attribute), 202
- EBook (rdflib.namespace.SDO attribute), 201
- EBV() (in module rdflib.plugins.sparql.operators), 404
- EconCycle\_Start\_Stop\_Status (rdflib.namespace.BRICK attribute), 90
- Economizer (rdflib.namespace.BRICK attribute), 90
- Economizer\_Damper (rdflib.namespace.BRICK attribute), 90
- EditedOrCroppedContent (rdflib.namespace.SDO attribute), 202
- editEIDR (rdflib.namespace.SDO attribute), 258
- editor (rdflib.namespace.SDO attribute), 258
- editorialNote (rdflib.namespace.PROV attribute), 180
- editorialNote (rdflib.namespace.SKOS attribute), 305
- editorsDefinition (rdflib.namespace.PROV attribute), 180
- educationalAlignment (rdflib.namespace.SDO attribute), 258
- EducationalAudience (rdflib.namespace.SDO attribute), 202
- educationalCredentialAwarded (rdflib.namespace.SDO attribute), 258
- educationalFramework (rdflib.namespace.SDO attribute), 258
- educationalLevel (rdflib.namespace.SDO attribute), 258
- EducationalOccupationalCredential (rdflib.namespace.SDO attribute), 202
- EducationalOccupationalProgram (rdflib.namespace.SDO attribute), 202
- EducationalOrganization (rdflib.namespace.SDO attribute), 202
- educationalProgramMode (rdflib.namespace.SDO attribute), 258
- educationalRole (rdflib.namespace.SDO attribute), 258
- educationalUse (rdflib.namespace.SDO attribute), 258
- EducationEvent (rdflib.namespace.SDO attribute), 202
- educationLevel (rdflib.namespace.DCTERMS attribute), 147
- educationRequirements (rdflib.namespace.SDO attribute), 258
- eduQuestionType (rdflib.namespace.SDO attribute), 258
- Effective\_Air\_Temperature\_Cooling\_Setpoint (rdflib.namespace.BRICK attribute), 90
- Effective\_Air\_Temperature\_Heating\_Setpoint (rdflib.namespace.BRICK attribute), 90
- Effective\_Air\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 90
- Effective\_Discharge\_Air\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 90
- Effective\_Return\_Air\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 90
- Effective\_Room\_Air\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 90
- Effective\_Supply\_Air\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 90
- Effective\_Zone\_Air\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 90
- EffectivenessHealthAspect (rdflib.namespace.SDO attribute), 202
- ehContains (rdflib.namespace.GEO attribute), 154
- ehCoveredBy (rdflib.namespace.GEO attribute), 154
- ehCovers (rdflib.namespace.GEO attribute), 154
- ehDisjoint (rdflib.namespace.GEO attribute), 154
- ehEquals (rdflib.namespace.GEO attribute), 154
- ehInside (rdflib.namespace.GEO attribute), 155



- ehMeet (*rdflib.namespace.GEO* attribute), 155
- ehOverlap (*rdflib.namespace.GEO* attribute), 155
- elapsedTime (*rdflib.namespace.ODRL2* attribute), 166
- Electric\_Baseboard\_Radiator (*rdflib.namespace.BRICK* attribute), 90
- Electric\_Boiler (*rdflib.namespace.BRICK* attribute), 90
- Electric\_Radiator (*rdflib.namespace.BRICK* attribute), 90
- Electrical\_Equipment (*rdflib.namespace.BRICK* attribute), 90
- Electrical\_Meter (*rdflib.namespace.BRICK* attribute), 90
- Electrical\_Power\_Sensor (*rdflib.namespace.BRICK* attribute), 90
- Electrical\_Room (*rdflib.namespace.BRICK* attribute), 91
- Electrical\_System (*rdflib.namespace.BRICK* attribute), 91
- electricalPhaseCount (*rdflib.namespace.BRICK* attribute), 135
- electricalPhases (*rdflib.namespace.BRICK* attribute), 135
- Electrician (*rdflib.namespace.SDO* attribute), 202
- ElectronicsStore (*rdflib.namespace.SDO* attribute), 202
- element() (*rdflib.plugins.serializers.xmlwriter.XMLWriter* method), 363
- ElementarySchool (*rdflib.namespace.SDO* attribute), 202
- ElementHandler (*class in rdflib.plugins.parsers.rdfxml*), 342
- elevation (*rdflib.namespace.SDO* attribute), 258
- Elevator (*rdflib.namespace.BRICK* attribute), 91
- Elevator\_Shaft (*rdflib.namespace.BRICK* attribute), 91
- Elevator\_Space (*rdflib.namespace.BRICK* attribute), 91
- eligibilityToWorkRequirement (*rdflib.namespace.SDO* attribute), 258
- eligibleCustomerType (*rdflib.namespace.SDO* attribute), 258
- eligibleDuration (*rdflib.namespace.SDO* attribute), 258
- eligibleQuantity (*rdflib.namespace.SDO* attribute), 258
- eligibleRegion (*rdflib.namespace.SDO* attribute), 258
- eligibleTransactionVolume (*rdflib.namespace.SDO* attribute), 258
- email (*rdflib.namespace.SDO* attribute), 259
- EmailMessage (*rdflib.namespace.SDO* attribute), 202
- Embassy (*rdflib.namespace.SDO* attribute), 202
- Embedded\_Surface\_System\_Panel (*rdflib.namespace.BRICK* attribute), 91
- Embedded\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 91
- Embedded\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 91
- embeddedTextCaption (*rdflib.namespace.SDO* attribute), 259
- embedUrl (*rdflib.namespace.SDO* attribute), 259
- Emergency (*rdflib.namespace.SDO* attribute), 202
- Emergency\_Air\_Flow\_System (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Air\_Flow\_System\_Status (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Alarm (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Generator\_Alarm (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Generator\_Status (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Phone (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Power\_Off\_System (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Power\_Off\_System\_Activated\_By\_High\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Power\_Off\_System\_Activated\_By\_Leak\_Detection\_System (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Power\_Off\_System\_Status (*rdflib.namespace.BRICK* attribute), 91
- Emergency\_Push\_Button\_Status (*rdflib.namespace.BRICK* attribute), 92
- Emergency\_Wash\_Station (*rdflib.namespace.BRICK* attribute), 92
- EmergencyService (*rdflib.namespace.SDO* attribute), 202
- emissionsCO2 (*rdflib.namespace.SDO* attribute), 259
- employee (*rdflib.namespace.SDO* attribute), 259
- Employee\_Entrance\_Lobby (*rdflib.namespace.BRICK* attribute), 92
- EmployeeRole (*rdflib.namespace.SDO* attribute), 202
- employees (*rdflib.namespace.SDO* attribute), 259
- EmployerAggregateRating (*rdflib.namespace.SDO* attribute), 203
- employerOverview (*rdflib.namespace.SDO* attribute), 259
- EmployerReview (*rdflib.namespace.SDO* attribute), 203
- EmploymentAgency (*rdflib.namespace.SDO* attribute), 203
- employmentType (*rdflib.namespace.SDO* attribute), 259
- employmentUnit (*rdflib.namespace.SDO* attribute), 259
- EmptyCollection (*rdflib.namespace.PROV* attribute), 178
- EmptyDictionary (*rdflib.namespace.PROV* attribute), 178
- Enable\_Command (*rdflib.namespace.BRICK* attribute),

- 92
- Enable\_Differential\_Enthalpy\_Command (rdflib.namespace.BRICK attribute), 92
- Enable\_Differential\_Temperature\_Command (rdflib.namespace.BRICK attribute), 92
- Enable\_Fixed\_Enthalpy\_Command (rdflib.namespace.BRICK attribute), 92
- Enable\_Fixed\_Temperature\_Command (rdflib.namespace.BRICK attribute), 92
- Enable\_Hot\_Water\_System\_Outside\_Air\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 92
- Enable\_Status (rdflib.namespace.BRICK attribute), 92
- Enclosed\_Office (rdflib.namespace.BRICK attribute), 92
- EncodeOnlyUnicode (class in rdflib.query), 531
- encodesBioChemEntity (rdflib.namespace.SDO attribute), 259
- encodesCreativeWork (rdflib.namespace.SDO attribute), 259
- encoding (rdflib.namespace.CSVW attribute), 139
- encoding (rdflib.namespace.SDO attribute), 259
- encoding (rdflib.plugins.serializers.hext.HextuplesSerializer attribute), 354
- encoding (rdflib.plugins.serializers.jsonld.JsonLDSerializer attribute), 355
- encoding (rdflib.plugins.serializers.longturtle.LongTurtleSerializer attribute), 356
- encoding (rdflib.plugins.serializers.n3.N3Serializer attribute), 357
- encoding (rdflib.plugins.serializers.nquads.NQuadsSerializer attribute), 357
- encoding (rdflib.plugins.serializers.nt.NTSerializer attribute), 358
- encoding (rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer attribute), 358
- encoding (rdflib.plugins.serializers.rdfxml.XMLSerializer attribute), 359
- encoding (rdflib.plugins.serializers.trig.TrigSerializer attribute), 360
- encoding (rdflib.plugins.serializers.trix.TriXSerializer attribute), 361
- encoding (rdflib.plugins.serializers.turtle.RecursiveSerializer attribute), 361
- encoding (rdflib.plugins.serializers.turtle.TurtleSerializer attribute), 362
- encodingFormat (rdflib.namespace.SDO attribute), 259
- encodings (rdflib.namespace.SDO attribute), 259
- encodingType (rdflib.namespace.SDO attribute), 259
- End (rdflib.namespace.PROV attribute), 178
- end (rdflib.plugins.parsers.rdfxml.ElementHandler attribute), 342
- end() (rdflib.container.Container method), 473
- endDate (rdflib.namespace.DCAT attribute), 144
- endDate (rdflib.namespace.SDO attribute), 259
- endDoc() (rdflib.plugins.parsers.notation3.RDFSink method), 324
- endDoc() (rdflib.plugins.parsers.notation3.SinkParser method), 329
- endDocument() (rdflib.plugins.serializers.longturtle.LongTurtleSerializer method), 356
- endDocument() (rdflib.plugins.serializers.n3.N3Serializer method), 357
- endDocument() (rdflib.plugins.serializers.turtle.TurtleSerializer method), 362
- ended (rdflib.namespace.PROV attribute), 180
- endedAtTime (rdflib.namespace.PROV attribute), 180
- endElementNS() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 344
- endElementNS() (rdflib.plugins.parsers.trix.TriXHandler method), 350
- Endocrine (rdflib.namespace.SDO attribute), 203
- endOffset (rdflib.namespace.SDO attribute), 259
- EndorseAction (rdflib.namespace.SDO attribute), 203
- endorsee (rdflib.namespace.SDO attribute), 259
- EndorsementRating (rdflib.namespace.SDO attribute), 203
- endorsers (rdflib.namespace.SDO attribute), 259
- endpointDescription (rdflib.namespace.DCAT attribute), 144
- endpointURL (rdflib.namespace.DCAT attribute), 144
- endPrefixMapping() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 344
- endPrefixMapping() (rdflib.plugins.parsers.trix.TriXHandler method), 350
- endTime (rdflib.namespace.SDO attribute), 259
- Energy (rdflib.namespace.SDO attribute), 203
- Energy\_Generation\_System (rdflib.namespace.BRICK attribute), 92
- Energy\_Sensor (rdflib.namespace.BRICK attribute), 92
- Energy\_Storage (rdflib.namespace.BRICK attribute), 92
- Energy\_Storage\_System (rdflib.namespace.BRICK attribute), 92
- Energy\_System (rdflib.namespace.BRICK attribute), 92
- Energy\_Usage\_Sensor (rdflib.namespace.BRICK attribute), 92
- Energy\_Zone (rdflib.namespace.BRICK attribute), 92
- EnergyConsumptionDetails (rdflib.namespace.SDO attribute), 203
- EnergyEfficiencyEnumeration (rdflib.namespace.SDO attribute), 203
- energyEfficiencyScaleMax (rdflib.namespace.SDO attribute), 259
- energyEfficiencyScaleMin (rdflib.namespace.SDO attribute), 259
- EnergyStarCertified (rdflib.namespace.SDO attribute), 259

- tribute*), 203
- EnergyStarEnergyEfficiencyEnumeration (*rdflib.namespace.SDO* attribute), 203
- engineDisplacement (*rdflib.namespace.SDO* attribute), 259
- enginePower (*rdflib.namespace.SDO* attribute), 259
- EngineSpecification (*rdflib.namespace.SDO* attribute), 203
- engineType (*rdflib.namespace.SDO* attribute), 259
- EnrollingByInvitation (*rdflib.namespace.SDO* attribute), 203
- ensureExclusivity (*rdflib.namespace.ODRL2* attribute), 166
- entailment (*rdflib.namespace.SH* attribute), 301
- Entering\_Water (*rdflib.namespace.BRICK* attribute), 93
- Entering\_Water\_Flow\_Sensor (*rdflib.namespace.BRICK* attribute), 93
- Entering\_Water\_Flow\_Setpoint (*rdflib.namespace.BRICK* attribute), 93
- Entering\_Water\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 93
- Entering\_Water\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 93
- EntertainmentBusiness (*rdflib.namespace.SDO* attribute), 203
- entertainmentBusiness (*rdflib.namespace.SDO* attribute), 259
- Enthalpy\_Sensor (*rdflib.namespace.BRICK* attribute), 93
- Enthalpy\_Setpoint (*rdflib.namespace.BRICK* attribute), 93
- entities (*rdflib.namespace.VOID* attribute), 314
- ENTITIES (*rdflib.namespace.XSD* attribute), 315
- Entity (*rdflib.namespace.PROV* attribute), 179
- entity (*rdflib.namespace.PROV* attribute), 181
- ENTITY (*rdflib.namespace.XSD* attribute), 315
- EntityInfluence (*rdflib.namespace.PROV* attribute), 179
- entityOfInfluence (*rdflib.namespace.PROV* attribute), 181
- Entrance (*rdflib.namespace.BRICK* attribute), 93
- EntryPoint (*rdflib.namespace.SDO* attribute), 203
- EnumeratedClass (class in *rdflib.extras.infixowl*), 65
- Enumeration (*rdflib.namespace.SDO* attribute), 203
- enumeration (*rdflib.namespace.XSD* attribute), 316
- Environment\_Box (*rdflib.namespace.BRICK* attribute), 93
- epidemiology (*rdflib.namespace.SDO* attribute), 260
- Episode (*rdflib.namespace.SDO* attribute), 203
- episode (*rdflib.namespace.SDO* attribute), 260
- episodeNumber (*rdflib.namespace.SDO* attribute), 260
- episodes (*rdflib.namespace.SDO* attribute), 260
- EPRelease (*rdflib.namespace.SDO* attribute), 201
- eq (*rdflib.namespace.ODRL2* attribute), 166
- eq() (*rdflib.Literal* method), 611
- eq() (*rdflib.term.Identifier* method), 556
- eq() (*rdflib.term.Literal* method), 564
- equal (*rdflib.namespace.SDO* attribute), 260
- equals (*rdflib.namespace.SH* attribute), 301
- EqualsConstraintComponent (*rdflib.namespace.SH* attribute), 297
- Equipment (*rdflib.namespace.BRICK* attribute), 93
- Equipment\_Room (*rdflib.namespace.BRICK* attribute), 93
- equivalentClass (*rdflib.extras.infixowl.Class* property), 63
- equivalentClass (*rdflib.namespace.OWL* attribute), 175
- equivalentProperty (*rdflib.namespace.OWL* attribute), 175
- Error, 475
- error (*rdflib.namespace.SDO* attribute), 260
- error() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 344
- error() (*rdflib.plugins.parsers.trix.TriXHandler* method), 351
- ESCAPED (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- ESS\_Panel (*rdflib.namespace.BRICK* attribute), 90
- estimatedCost (*rdflib.namespace.SDO* attribute), 260
- estimatedFlightDuration (*rdflib.namespace.SDO* attribute), 260
- estimatedSalary (*rdflib.namespace.SDO* attribute), 260
- estimatesRiskOf (*rdflib.namespace.SDO* attribute), 260
- ethicsPolicy (*rdflib.namespace.SDO* attribute), 260
- EUEnergyEfficiencyCategoryA (*rdflib.namespace.SDO* attribute), 201
- EUEnergyEfficiencyCategoryA1Plus (*rdflib.namespace.SDO* attribute), 201
- EUEnergyEfficiencyCategoryA2Plus (*rdflib.namespace.SDO* attribute), 201
- EUEnergyEfficiencyCategoryA3Plus (*rdflib.namespace.SDO* attribute), 201
- EUEnergyEfficiencyCategoryB (*rdflib.namespace.SDO* attribute), 201
- EUEnergyEfficiencyCategoryC (*rdflib.namespace.SDO* attribute), 201
- EUEnergyEfficiencyCategoryD (*rdflib.namespace.SDO* attribute), 202
- EUEnergyEfficiencyCategoryE (*rdflib.namespace.SDO* attribute), 202
- EUEnergyEfficiencyCategoryF (*rdflib.namespace.SDO* attribute), 202
- EUEnergyEfficiencyCategoryG (*rdflib.namespace.SDO* attribute), 202

- EUEnergyEfficiencyEnumeration (rdflib.namespace.SDO attribute), 202  
 eval() (rdflib.paths.AlternativePath method), 522  
 eval() (rdflib.paths.InvPath method), 523  
 eval() (rdflib.paths.MulPath method), 524  
 eval() (rdflib.paths.NegatedPath method), 524  
 eval() (rdflib.paths.Path method), 526  
 eval() (rdflib.paths.SequencePath method), 527  
 eval() (rdflib.plugins.sparql.parserutils.Expr method), 411  
 eval\_full\_row() (rdflib.plugins.sparql.aggregates.Counter method), 382  
 eval\_path() (in module rdflib.paths), 527  
 eval\_row() (rdflib.plugins.sparql.aggregates.Counter method), 382  
 evalAdd() (in module rdflib.plugins.sparql.update), 425  
 evalAggregateJoin() (in module rdflib.plugins.sparql.evaluate), 392  
 evalAskQuery() (in module rdflib.plugins.sparql.evaluate), 392  
 evalBGP() (in module rdflib.plugins.sparql.evaluate), 392  
 evalClear() (in module rdflib.plugins.sparql.update), 425  
 evalConstructQuery() (in module rdflib.plugins.sparql.evaluate), 392  
 evalCopy() (in module rdflib.plugins.sparql.update), 426  
 evalCreate() (in module rdflib.plugins.sparql.update), 426  
 evalDeleteData() (in module rdflib.plugins.sparql.update), 426  
 evalDeleteWhere() (in module rdflib.plugins.sparql.update), 426  
 evalDescribeQuery() (in module rdflib.plugins.sparql.evaluate), 393  
 evalDistinct() (in module rdflib.plugins.sparql.evaluate), 393  
 evalDrop() (in module rdflib.plugins.sparql.update), 426  
 evalExtend() (in module rdflib.plugins.sparql.evaluate), 393  
 evalFilter() (in module rdflib.plugins.sparql.evaluate), 393  
 evalGraph() (in module rdflib.plugins.sparql.evaluate), 393  
 evalGroup() (in module rdflib.plugins.sparql.evaluate), 393  
 evalInsertData() (in module rdflib.plugins.sparql.update), 426  
 evalJoin() (in module rdflib.plugins.sparql.evaluate), 394  
 evalLazyJoin() (in module rdflib.plugins.sparql.evaluate), 394  
 evalLeftJoin() (in module rdflib.plugins.sparql.evaluate), 394  
 evalLoad() (in module rdflib.plugins.sparql.update), 427  
 evalMinus() (in module rdflib.plugins.sparql.evaluate), 394  
 evalModify() (in module rdflib.plugins.sparql.update), 427  
 evalMove() (in module rdflib.plugins.sparql.update), 427  
 evalMultiset() (in module rdflib.plugins.sparql.evaluate), 394  
 evalOrderBy() (in module rdflib.plugins.sparql.evaluate), 394  
 evalPart() (in module rdflib.plugins.sparql.evaluate), 395  
 evalPath() (in module rdflib.paths), 527  
 evalProject() (in module rdflib.plugins.sparql.evaluate), 395  
 evalQuery() (in module rdflib.plugins.sparql.evaluate), 395  
 evalReduced() (in module rdflib.plugins.sparql.evaluate), 395  
 evalSelectQuery() (in module rdflib.plugins.sparql.evaluate), 396  
 evalServiceQuery() (in module rdflib.plugins.sparql.evaluate), 396  
 evalSlice() (in module rdflib.plugins.sparql.evaluate), 396  
 evalUnion() (in module rdflib.plugins.sparql.evaluate), 396  
 evalUpdate() (in module rdflib.plugins.sparql.update), 427  
 evalValues() (in module rdflib.plugins.sparql.evaluate), 396  
 Evaporative\_Heat\_Exchanger (rdflib.namespace.BRICK attribute), 93  
 Even\_Month\_Status (rdflib.namespace.BRICK attribute), 93  
 Event (class in rdflib.events), 474  
 Event (rdflib.namespace.DCMITYPE attribute), 145  
 event (rdflib.namespace.ODRL2 attribute), 166  
 Event (rdflib.namespace.SDO attribute), 203  
 event (rdflib.namespace.SDO attribute), 260  
 eventAttendanceMode (rdflib.namespace.SDO attribute), 260  
 EventAttendanceModeEnumeration (rdflib.namespace.SDO attribute), 203  
 EventCancelled (rdflib.namespace.SDO attribute), 203  
 EventMovedOnline (rdflib.namespace.SDO attribute), 203  
 EventPostponed (rdflib.namespace.SDO attribute), 203  
 EventRescheduled (rdflib.namespace.SDO attribute), 203



- 203
- EventReservation (*rdflib.namespace.SDO* attribute), 204
- events (*rdflib.namespace.SDO* attribute), 260
- eventSchedule (*rdflib.namespace.SDO* attribute), 260
- EventScheduled (*rdflib.namespace.SDO* attribute), 204
- EventSeries (*rdflib.namespace.SDO* attribute), 204
- eventStatus (*rdflib.namespace.SDO* attribute), 260
- EventStatusType (*rdflib.namespace.SDO* attribute), 204
- EventVenue (*rdflib.namespace.SDO* attribute), 204
- evidenceLevel (*rdflib.namespace.SDO* attribute), 260
- EvidenceLevelA (*rdflib.namespace.SDO* attribute), 204
- EvidenceLevelB (*rdflib.namespace.SDO* attribute), 204
- EvidenceLevelC (*rdflib.namespace.SDO* attribute), 204
- evidenceOrigin (*rdflib.namespace.SDO* attribute), 260
- exactMatch (*rdflib.namespace.SKOS* attribute), 305
- example (*rdflib.namespace.SKOS* attribute), 305
- example (*rdflib.namespace.VANN* attribute), 313
- example\_1() (in module *examples.berkeleydb\_example*), 23
- example\_2() (in module *examples.berkeleydb\_example*), 24
- exampleOfWork (*rdflib.namespace.SDO* attribute), 260
- exampleResource (*rdflib.namespace.VOID* attribute), 314
- examples.berkeleydb\_example* module, 23
- examples.conjunctive\_graphs* module, 22
- examples.custom\_datatype* module, 22
- examples.custom\_eval* module, 22
- examples.foafpaths* module, 22
- examples.prepared\_query* module, 23
- examples.resource\_example* module, 23
- examples.secure\_with\_audit* module, 26
- examples.secure\_with\_urlopen* module, 26
- examples.slice* module, 24
- examples.smushing* module, 24
- examples.sparql\_query\_example* module, 24
- examples.sparql\_update\_example* module, 25
- examples.sparqlstore\_example* module, 25
- examples.swap\_primer* module, 25
- examples.transitive* module, 25
- exceptDate (*rdflib.namespace.SDO* attribute), 260
- ExchangeRateSpecification (*rdflib.namespace.SDO* attribute), 204
- exchangeRateSpread (*rdflib.namespace.SDO* attribute), 260
- ExchangeRefund (*rdflib.namespace.SDO* attribute), 204
- executableLibraryName (*rdflib.namespace.SDO* attribute), 260
- execute (*rdflib.namespace.ODRL2* attribute), 166
- Exercise\_Room (*rdflib.namespace.BRICK* attribute), 93
- ExerciseAction (*rdflib.namespace.SDO* attribute), 204
- exerciseCourse (*rdflib.namespace.SDO* attribute), 260
- ExerciseGym (*rdflib.namespace.SDO* attribute), 204
- ExercisePlan (*rdflib.namespace.SDO* attribute), 204
- exercisePlan (*rdflib.namespace.SDO* attribute), 260
- exerciseRelatedDiet (*rdflib.namespace.SDO* attribute), 260
- exerciseType (*rdflib.namespace.SDO* attribute), 260
- Exhaust\_Air (*rdflib.namespace.BRICK* attribute), 93
- Exhaust\_Air\_Dewpoint\_Sensor (*rdflib.namespace.BRICK* attribute), 93
- Exhaust\_Air\_Differential\_Pressure\_Sensor (*rdflib.namespace.BRICK* attribute), 93
- Exhaust\_Air\_Differential\_Pressure\_Setpoint (*rdflib.namespace.BRICK* attribute), 93
- Exhaust\_Air\_Flow\_Integral\_Time\_Parameter (*rdflib.namespace.BRICK* attribute), 93
- Exhaust\_Air\_Flow\_Proportional\_Band\_Parameter (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Flow\_Sensor (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Flow\_Setpoint (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Humidity\_Sensor (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Humidity\_Setpoint (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Stack\_Flow\_Deadband\_Setpoint (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Stack\_Flow\_Integral\_Time\_Parameter (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Stack\_Flow\_Proportional\_Band\_Parameter (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Stack\_Flow\_Sensor (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Stack\_Flow\_Setpoint (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Static\_Pressure\_Proportional\_Band\_Parameter (*rdflib.namespace.BRICK* attribute), 94
- Exhaust\_Air\_Static\_Pressure\_Sensor (*rd-*



- flib.namespace.BRICK* attribute), 94  
 Exhaust\_Air\_Static\_Pressure\_Setpoint (*rdflib.namespace.BRICK* attribute), 94  
 Exhaust\_Air\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 94  
 Exhaust\_Air\_Velocity\_Pressure\_Sensor (*rdflib.namespace.BRICK* attribute), 94  
 Exhaust\_Damper (*rdflib.namespace.BRICK* attribute), 94  
 Exhaust\_Fan (*rdflib.namespace.BRICK* attribute), 94  
 Exhaust\_Fan\_Disable\_Command (*rdflib.namespace.BRICK* attribute), 94  
 Exhaust\_Fan\_Enable\_Command (*rdflib.namespace.BRICK* attribute), 95  
 ExhibitionEvent (*rdflib.namespace.SDO* attribute), 204  
 exifData (*rdflib.namespace.SDO* attribute), 260  
 expand() (*rdflib.plugins.shared.jsonld.context.Context* method), 366  
 expand\_curie() (*rdflib.namespace.NamespaceManager* method), 162  
 expandBNodeTriples() (in module *rdflib.plugins.sparql.parser*), 408  
 expandCollection() (in module *rdflib.plugins.sparql.parser*), 408  
 expandTriples() (in module *rdflib.plugins.sparql.parser*), 408  
 expandUnicodeEscapes() (in module *rdflib.plugins.sparql.parser*), 408  
 expectedArrivalFrom (*rdflib.namespace.SDO* attribute), 261  
 expectedArrivalUntil (*rdflib.namespace.SDO* attribute), 261  
 expectedPrognosis (*rdflib.namespace.SDO* attribute), 261  
 expectsAcceptanceOf (*rdflib.namespace.SDO* attribute), 261  
 experienceInPlaceOfEducation (*rdflib.namespace.SDO* attribute), 261  
 experienceRequirements (*rdflib.namespace.SDO* attribute), 261  
 expertConsiderations (*rdflib.namespace.SDO* attribute), 261  
 expires (*rdflib.namespace.SDO* attribute), 261  
 explicitTimezone (*rdflib.namespace.XSD* attribute), 316  
 export (*rdflib.namespace.ODRL2* attribute), 166  
 Expr (class in *rdflib.plugins.sparql.parserutils*), 411  
 expressedIn (*rdflib.namespace.SDO* attribute), 261  
 expression (*rdflib.namespace.SH* attribute), 301  
 ExpressionConstraintComponent (*rdflib.namespace.SH* attribute), 297  
 ExpressionNotCoveredException, 386  
 Extend() (in module *rdflib.plugins.sparql.algebra*), 386  
 extent (*rdflib.extras.infixowl.Class* property), 64  
 extent (*rdflib.extras.infixowl.Property* property), 70  
 extent (*rdflib.namespace.DCTERMS* attribute), 148  
 extentQuery (*rdflib.extras.infixowl.Class* property), 64  
 extract (*rdflib.namespace.ODRL2* attribute), 166  
 extractChar (*rdflib.namespace.ODRL2* attribute), 166  
 extractPage (*rdflib.namespace.ODRL2* attribute), 166  
 extractWord (*rdflib.namespace.ODRL2* attribute), 166  
 Extremum (class in *rdflib.plugins.sparql.aggregates*), 382  
 Eye (*rdflib.namespace.SDO* attribute), 204  
 Eye\_Wash\_Station (*rdflib.namespace.BRICK* attribute), 95
- ## F
- factoryGraph (*rdflib.extras.infixowl.Individual* attribute), 67  
 failAction (*rdflib.plugins.sparql.parserutils.ParamList* attribute), 412  
 FailedActionStatus (*rdflib.namespace.SDO* attribute), 204  
 failure (*rdflib.namespace.ODRL2* attribute), 166  
 Failure\_Alarm (*rdflib.namespace.BRICK* attribute), 95  
 family\_name (*rdflib.namespace.FOAF* attribute), 152  
 familyName (*rdflib.namespace.FOAF* attribute), 152  
 familyName (*rdflib.namespace.SDO* attribute), 261  
 Fan (*rdflib.namespace.BRICK* attribute), 95  
 Fan\_Coil\_Unit (*rdflib.namespace.BRICK* attribute), 95  
 Fan\_On\_Off\_Status (*rdflib.namespace.BRICK* attribute), 95  
 Fan\_Status (*rdflib.namespace.BRICK* attribute), 95  
 Fan\_VFD (*rdflib.namespace.BRICK* attribute), 95  
 FAQPage (*rdflib.namespace.SDO* attribute), 204  
 FastFoodRestaurant (*rdflib.namespace.SDO* attribute), 204  
 fatContent (*rdflib.namespace.SDO* attribute), 261  
 Fault\_Reset\_Command (*rdflib.namespace.BRICK* attribute), 95  
 Fault\_Status (*rdflib.namespace.BRICK* attribute), 95  
 faxNumber (*rdflib.namespace.SDO* attribute), 261  
 FCU (*rdflib.namespace.BRICK* attribute), 95  
 FDACategoryA (*rdflib.namespace.SDO* attribute), 204  
 FDACategoryB (*rdflib.namespace.SDO* attribute), 204  
 FDACategoryC (*rdflib.namespace.SDO* attribute), 204  
 FDACategoryD (*rdflib.namespace.SDO* attribute), 204  
 FDACategoryX (*rdflib.namespace.SDO* attribute), 204  
 FDAnotEvaluated (*rdflib.namespace.SDO* attribute), 204  
 Feature (*rdflib.namespace.GEO* attribute), 154  
 feature (*rdflib.namespace.VOID* attribute), 314  
 featureList (*rdflib.namespace.SDO* attribute), 261  
 FeatureOfInterest (*rdflib.namespace.SOSA* attribute), 306  
 feed() (*rdflib.plugins.parsers.notation3.SinkParser* method), 329

- `feeds` (`rdflib.namespace.BRICK` attribute), 135
- `feedsAir` (`rdflib.namespace.BRICK` attribute), 135
- `feesAndCommissionsSpecification` (`rdflib.namespace.SDO` attribute), 261
- `Female` (`rdflib.namespace.SDO` attribute), 204
- `Festival` (`rdflib.namespace.SDO` attribute), 204
- `fiberContent` (`rdflib.namespace.SDO` attribute), 261
- `Field_Of_Play` (`rdflib.namespace.BRICK` attribute), 95
- `file` (`rdflib.plugins.parsers.nquads.NQuadsParser` attribute), 338
- `file` (`rdflib.plugins.parsers.ntriples.W3CNTriplesParser` attribute), 340
- `FileFormat` (`rdflib.namespace.DCTERMS` attribute), 145
- `fileFormat` (`rdflib.namespace.ODRL2` attribute), 166
- `fileFormat` (`rdflib.namespace.SDO` attribute), 261
- `FileInputSource` (class in `rdflib.parser`), 516
- `fileSize` (`rdflib.namespace.SDO` attribute), 261
- `FilmAction` (`rdflib.namespace.SDO` attribute), 204
- `Filter` (`rdflib.namespace.BRICK` attribute), 95
- `Filter()` (in module `rdflib.plugins.sparql.algebra`), 386
- `Filter_Differential_Pressure_Sensor` (`rdflib.namespace.BRICK` attribute), 95
- `Filter_Reset_Command` (`rdflib.namespace.BRICK` attribute), 95
- `Filter_Status` (`rdflib.namespace.BRICK` attribute), 95
- `filterShape` (`rdflib.namespace.SH` attribute), 301
- `Final_Filter` (`rdflib.namespace.BRICK` attribute), 95
- `financialAidEligible` (`rdflib.namespace.SDO` attribute), 261
- `FinancialProduct` (`rdflib.namespace.SDO` attribute), 205
- `FinancialService` (`rdflib.namespace.SDO` attribute), 205
- `find_roots()` (in module `rdflib.util`), 570
- `find_term()` (`rdflib.plugins.shared.jsonld.context.Context` method), 366
- `FindAction` (`rdflib.namespace.SDO` attribute), 205
- `Fire_Control_Panel` (`rdflib.namespace.BRICK` attribute), 95
- `Fire_Safety_Equipment` (`rdflib.namespace.BRICK` attribute), 95
- `Fire_Safety_System` (`rdflib.namespace.BRICK` attribute), 95
- `Fire_Sensor` (`rdflib.namespace.BRICK` attribute), 96
- `Fire_Zone` (`rdflib.namespace.BRICK` attribute), 96
- `FireStation` (`rdflib.namespace.SDO` attribute), 205
- `first` (`rdflib.namespace.RDF` attribute), 187
- `first()` (in module `rdflib.util`), 570
- `First_Aid_Kit` (`rdflib.namespace.BRICK` attribute), 96
- `First_Aid_Room` (`rdflib.namespace.BRICK` attribute), 96
- `firstAppearance` (`rdflib.namespace.SDO` attribute), 261
- `firstName` (`rdflib.namespace.FOAF` attribute), 152
- `firstPerformance` (`rdflib.namespace.SDO` attribute), 261
- `fix()` (in module `rdflib.plugins.serializers.rdfxml`), 359
- `flags` (`rdflib.namespace.SH` attribute), 301
- `Flexibility` (`rdflib.namespace.SDO` attribute), 205
- `Flight` (`rdflib.namespace.SDO` attribute), 205
- `flightDistance` (`rdflib.namespace.SDO` attribute), 261
- `flightNumber` (`rdflib.namespace.SDO` attribute), 261
- `FlightReservation` (`rdflib.namespace.SDO` attribute), 205
- `Float` (`rdflib.namespace.SDO` attribute), 205
- `float` (`rdflib.namespace.XSD` attribute), 316
- `Floor` (`rdflib.namespace.BRICK` attribute), 96
- `floorLevel` (`rdflib.namespace.SDO` attribute), 261
- `floorLimit` (`rdflib.namespace.SDO` attribute), 261
- `FloorPlan` (`rdflib.namespace.SDO` attribute), 205
- `floorSize` (`rdflib.namespace.SDO` attribute), 261
- `Florist` (`rdflib.namespace.SDO` attribute), 205
- `Flow_Sensor` (`rdflib.namespace.BRICK` attribute), 96
- `Flow_Setpoint` (`rdflib.namespace.BRICK` attribute), 96
- `Fluid` (`rdflib.namespace.BRICK` attribute), 96
- `FMRadioChannel` (`rdflib.namespace.SDO` attribute), 204
- `FOAF` (class in `rdflib.namespace`), 151
- `focus` (`rdflib.namespace.FOAF` attribute), 152
- `focusNode` (`rdflib.namespace.SH` attribute), 301
- `FollowAction` (`rdflib.namespace.SDO` attribute), 205
- `follower` (`rdflib.namespace.SDO` attribute), 262
- `follows` (`rdflib.namespace.SDO` attribute), 262
- `followup` (`rdflib.namespace.SDO` attribute), 262
- `Food_Service_Room` (`rdflib.namespace.BRICK` attribute), 96
- `FoodEstablishment` (`rdflib.namespace.SDO` attribute), 205
- `foodEstablishment` (`rdflib.namespace.SDO` attribute), 262
- `FoodEstablishmentReservation` (`rdflib.namespace.SDO` attribute), 205
- `FoodEvent` (`rdflib.namespace.SDO` attribute), 205
- `foodEvent` (`rdflib.namespace.SDO` attribute), 262
- `FoodService` (`rdflib.namespace.SDO` attribute), 205
- `foodWarning` (`rdflib.namespace.SDO` attribute), 262
- `ForeignKey` (`rdflib.namespace.CSVW` attribute), 138
- `foreignKey` (`rdflib.namespace.CSVW` attribute), 139
- `forget()` (`rdflib.plugins.sparql.sparql.FrozenBindings` method), 418
- `Formaldehyde_Level_Sensor` (`rdflib.namespace.BRICK` attribute), 96
- `FormalOrganization` (`rdflib.namespace.ORG` attribute), 171
- `format` (`rdflib.namespace.CSVW` attribute), 139
- `format` (`rdflib.namespace.DC` attribute), 142
- `format` (`rdflib.namespace.DCTERMS` attribute), 148
- `Formula` (class in `rdflib.plugins.parsers.notation3`), 322

- formula() (*rdflib.plugins.parsers.notation3.SinkParser* method), 329
- formula\_aware (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* attribute), 434
- formula\_aware (*rdflib.plugins.stores.memory.Memory* attribute), 437
- formula\_aware (*rdflib.plugins.stores.sparqlstore.SPARQLStore* attribute), 447
- formula\_aware (*rdflib.store.Store* attribute), 550
- forProperty (*rdflib.namespace.SSN* attribute), 308
- founder (*rdflib.namespace.SDO* attribute), 262
- founders (*rdflib.namespace.SDO* attribute), 262
- foundingDate (*rdflib.namespace.SDO* attribute), 262
- foundingLocation (*rdflib.namespace.SDO* attribute), 262
- FourWheelDriveConfiguration (*rdflib.namespace.SDO* attribute), 205
- fractionDigits (*rdflib.namespace.XSD* attribute), 316
- fragment (*rdflib.term.URIRef* property), 568
- fragment (*rdflib.URIRef* property), 617
- free (*rdflib.namespace.SDO* attribute), 262
- FreeReturn (*rdflib.namespace.SDO* attribute), 205
- freeShippingThreshold (*rdflib.namespace.SDO* attribute), 262
- Freeze\_Status (*rdflib.namespace.BRICK* attribute), 96
- Freezer (*rdflib.namespace.BRICK* attribute), 96
- Frequency (*rdflib.namespace.DCTERMS* attribute), 145
- frequency (*rdflib.namespace.SDO* attribute), 262
- Frequency\_Command (*rdflib.namespace.BRICK* attribute), 96
- Frequency\_Sensor (*rdflib.namespace.BRICK* attribute), 96
- Fresh\_Air\_Fan (*rdflib.namespace.BRICK* attribute), 96
- Fresh\_Air\_Setpoint\_Limit (*rdflib.namespace.BRICK* attribute), 96
- Friday (*rdflib.namespace.SDO* attribute), 205
- Friday (*rdflib.namespace.TIME* attribute), 309
- from\_n3() (in module *rdflib.util*), 571
- from\_rdf() (in module *rdflib.plugins.serializers.jsonld*), 355
- fromLocation (*rdflib.namespace.SDO* attribute), 262
- FrontWheelDriveConfiguration (*rdflib.namespace.SDO* attribute), 205
- Frost (*rdflib.namespace.BRICK* attribute), 96
- Frost\_Sensor (*rdflib.namespace.BRICK* attribute), 96
- FrozenBindings (class in *rdflib.plugins.sparql.sparql*), 418
- FrozenDict (class in *rdflib.plugins.sparql.sparql*), 419
- Fuel\_Oil (*rdflib.namespace.BRICK* attribute), 96
- fuelCapacity (*rdflib.namespace.SDO* attribute), 262
- fuelConsumption (*rdflib.namespace.SDO* attribute), 262
- fuelEfficiency (*rdflib.namespace.SDO* attribute), 262
- fuelType (*rdflib.namespace.SDO* attribute), 262
- FullRefund (*rdflib.namespace.SDO* attribute), 205
- Fume\_Hood (*rdflib.namespace.BRICK* attribute), 96
- Fume\_Hood\_Air\_Flow\_Sensor (*rdflib.namespace.BRICK* attribute), 97
- function (*rdflib.namespace.ODRL2* attribute), 166
- Function (*rdflib.namespace.SH* attribute), 297
- Function() (in module *rdflib.plugins.sparql.operators*), 404
- functionalClass (*rdflib.namespace.SDO* attribute), 262
- FunctionalProperty (*rdflib.namespace.OWL* attribute), 173
- fundedBy (*rdflib.namespace.FOAF* attribute), 152
- fundedItem (*rdflib.namespace.SDO* attribute), 262
- funder (*rdflib.namespace.SDO* attribute), 262
- FundingAgency (*rdflib.namespace.SDO* attribute), 205
- FundingScheme (*rdflib.namespace.SDO* attribute), 205
- Fungus (*rdflib.namespace.SDO* attribute), 205
- Furniture (*rdflib.namespace.BRICK* attribute), 97
- FurnitureStore (*rdflib.namespace.SDO* attribute), 205
- ## G
- g (*rdflib.plugins.parsers.ntriples.NTGraphSink* attribute), 339
- Gain\_Parameter (*rdflib.namespace.BRICK* attribute), 97
- Game (*rdflib.namespace.SDO* attribute), 205
- game (*rdflib.namespace.SDO* attribute), 262
- gameItem (*rdflib.namespace.SDO* attribute), 262
- gameLocation (*rdflib.namespace.SDO* attribute), 262
- gamePlatform (*rdflib.namespace.SDO* attribute), 262
- GamePlayMode (*rdflib.namespace.SDO* attribute), 205
- GameServer (*rdflib.namespace.SDO* attribute), 206
- gameServer (*rdflib.namespace.SDO* attribute), 262
- GameServerStatus (*rdflib.namespace.SDO* attribute), 206
- gameTip (*rdflib.namespace.SDO* attribute), 262
- GardenStore (*rdflib.namespace.SDO* attribute), 206
- Gas (*rdflib.namespace.BRICK* attribute), 97
- Gas\_Distribution (*rdflib.namespace.BRICK* attribute), 97
- Gas\_Meter (*rdflib.namespace.BRICK* attribute), 97
- Gas\_Sensor (*rdflib.namespace.BRICK* attribute), 97
- Gas\_System (*rdflib.namespace.BRICK* attribute), 97
- Gas\_Valve (*rdflib.namespace.BRICK* attribute), 97
- Gasoline (*rdflib.namespace.BRICK* attribute), 97
- GasStation (*rdflib.namespace.SDO* attribute), 206
- Gastroenterologic (*rdflib.namespace.SDO* attribute), 206
- GatedResidenceCommunity (*rdflib.namespace.SDO* attribute), 206
- Gatehouse (*rdflib.namespace.BRICK* attribute), 97
- gc() (*rdflib.store.Store* method), 550
- gDay (*rdflib.namespace.XSD* attribute), 316



- ul style="list-style-type: none; padding-left: 0;">
- geekcode (*rdflib.namespace.FOAF* attribute), 152
- gen (*rdflib.plugins.stores.concurrent.ResponsibleGenerator* attribute), 436
- gender (*rdflib.namespace.FOAF* attribute), 152
- gender (*rdflib.namespace.SDO* attribute), 262
- GenderType (*rdflib.namespace.SDO* attribute), 206
- Gene (*rdflib.namespace.SDO* attribute), 206
- GeneralContractor (*rdflib.namespace.SDO* attribute), 206
- GeneralDateTimeDescription (*rdflib.namespace.TIME* attribute), 309
- generalDay (*rdflib.namespace.TIME* attribute), 310
- GeneralDurationDescription (*rdflib.namespace.TIME* attribute), 309
- generalizationOf (*rdflib.namespace.PROV* attribute), 181
- generalMonth (*rdflib.namespace.TIME* attribute), 310
- generalYear (*rdflib.namespace.TIME* attribute), 310
- generated (*rdflib.namespace.PROV* attribute), 181
- generatedAsDerivation (*rdflib.namespace.PROV* attribute), 181
- generatedAtTime (*rdflib.namespace.PROV* attribute), 181
- generateQName() (in module *rdflib.extras.infixowl*), 72
- generateVoID() (in module *rdflib.void*), 574
- Generation (*rdflib.namespace.PROV* attribute), 179
- Generator\_Room (*rdflib.namespace.BRICK* attribute), 97
- Genetic (*rdflib.namespace.SDO* attribute), 206
- Genitourinary (*rdflib.namespace.SDO* attribute), 206
- genre (*rdflib.namespace.SDO* attribute), 262
- GEO (class in *rdflib.namespace*), 153
- geo (*rdflib.namespace.SDO* attribute), 263
- GeoCircle (*rdflib.namespace.SDO* attribute), 206
- geoContains (*rdflib.namespace.SDO* attribute), 263
- GeoCoordinates (*rdflib.namespace.SDO* attribute), 206
- geoCoveredBy (*rdflib.namespace.SDO* attribute), 263
- geoCovers (*rdflib.namespace.SDO* attribute), 263
- geoCrosses (*rdflib.namespace.SDO* attribute), 263
- geoDisjoint (*rdflib.namespace.SDO* attribute), 263
- geoEquals (*rdflib.namespace.SDO* attribute), 263
- geographicArea (*rdflib.namespace.SDO* attribute), 263
- geoIntersects (*rdflib.namespace.SDO* attribute), 263
- Geometry (*rdflib.namespace.GEO* attribute), 154
- geoMidpoint (*rdflib.namespace.SDO* attribute), 263
- geoOverlaps (*rdflib.namespace.SDO* attribute), 263
- geoRadius (*rdflib.namespace.SDO* attribute), 263
- GeoShape (*rdflib.namespace.SDO* attribute), 206
- GeospatialGeometry (*rdflib.namespace.SDO* attribute), 206
- geoTouches (*rdflib.namespace.SDO* attribute), 263
- geoWithin (*rdflib.namespace.SDO* attribute), 263
- Geriatric (*rdflib.namespace.SDO* attribute), 206
- get() (in module *rdflib.plugin*), 530
- get() (*rdflib.plugins.sparql.parserutils.CompValue* method), 411
- get() (*rdflib.plugins.sparql.sparql.QueryContext* method), 423
- get() (*rdflib.query.ResultRow* method), 536
- get\_alternates() (*rdflib.parser.URLInputSource* method), 519
- get\_bindings() (*rdflib.plugins.sparql.aggregates.Aggregator* method), 381
- get\_bnode() (*rdflib.plugins.parsers.trix.TriXHandler* method), 351
- get\_context() (*rdflib.ConjunctiveGraph* method), 578
- get\_context() (*rdflib.graph.ConjunctiveGraph* method), 483
- get\_context\_for\_term() (*rdflib.plugins.shared.jsonld.context.Context* method), 366
- get\_context\_for\_type() (*rdflib.plugins.shared.jsonld.context.Context* method), 366
- get\_current() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 344
- get\_graph() (*rdflib.ConjunctiveGraph* method), 578
- get\_graph() (*rdflib.graph.ConjunctiveGraph* method), 484
- get\_graph() (*rdflib.plugins.shared.jsonld.context.Context* method), 366
- get\_id() (*rdflib.plugins.shared.jsonld.context.Context* method), 366
- get\_key() (*rdflib.plugins.shared.jsonld.context.Context* method), 367
- get\_keys() (*rdflib.plugins.shared.jsonld.context.Context* method), 367
- get\_language() (*rdflib.plugins.shared.jsonld.context.Context* method), 367
- get\_links() (*rdflib.parser.URLInputSource* class method), 519
- get\_list() (*rdflib.plugins.shared.jsonld.context.Context* method), 367
- get\_map() (*rdflib.events.Dispatcher* method), 474
- get\_next() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 344
- get\_parent() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 344
- get\_rev() (*rdflib.plugins.shared.jsonld.context.Context* method), 367
- get\_set() (*rdflib.plugins.shared.jsonld.context.Context* method), 367
- get\_target\_namespace\_elements() (in module *rdflib.tools.defined\_namespace\_creator*), 459
- get\_tree() (in module *rdflib.util*), 571
- get\_type() (*rdflib.plugins.shared.jsonld.context.Context* method), 367
- get\_value (*rdflib.plugins.sparql.aggregates.Extremum*

- attribute*), 383
- `get_value` (*rdflib.plugins.sparql.aggregates.Maximum attribute*), 384
- `get_value` (*rdflib.plugins.sparql.aggregates.Minimum attribute*), 384
- `get_value()` (*rdflib.plugins.shared.jsonld.context.Context method*), 367
- `get_value()` (*rdflib.plugins.sparql.aggregates.Average method*), 381
- `get_value()` (*rdflib.plugins.sparql.aggregates.Counter method*), 382
- `get_value()` (*rdflib.plugins.sparql.aggregates.GroupConcat method*), 383
- `get_value()` (*rdflib.plugins.sparql.aggregates.Sample method*), 385
- `get_value()` (*rdflib.plugins.sparql.aggregates.Sum method*), 385
- `getallmatchingheaders()` (*rdflib.parser.URLInputSource class method*), 519
- `getClass()` (*rdflib.plugin.PKGPlugin method*), 529
- `getClass()` (*rdflib.plugin.Plugin method*), 530
- `GetIdentifiedClasses()` (*in module rdflib.extras.infixowl*), 66
- `getIntersections` (*rdflib.extras.infixowl.BooleanClass attribute*), 62
- `getPublicId()` (*rdflib.parser.PythonInputSource method*), 517
- `getQName()` (*rdflib.plugins.serializers.longturtle.LongTurtleSerialize method*), 356
- `getQName()` (*rdflib.plugins.serializers.n3.N3Serializer method*), 357
- `getQName()` (*rdflib.plugins.serializers.turtle.TurtleSerialize method*), 362
- `getSystemId()` (*rdflib.parser.PythonInputSource method*), 517
- `GettingAccessHealthAspect` (*rdflib.namespace.SDO attribute*), 206
- `gettingTestedInfo` (*rdflib.namespace.SDO attribute*), 263
- `getUnions` (*rdflib.extras.infixowl.BooleanClass attribute*), 62
- `GitBranch` (*rdflib.namespace.DOAP attribute*), 149
- `GitRepository` (*rdflib.namespace.DOAP attribute*), 149
- `give` (*rdflib.namespace.ODRL2 attribute*), 166
- `GiveAction` (*rdflib.namespace.SDO attribute*), 206
- `givenName` (*rdflib.namespace.FOAF attribute*), 152
- `givenname` (*rdflib.namespace.FOAF attribute*), 152
- `givenName` (*rdflib.namespace.SDO attribute*), 263
- `globalLocationNumber` (*rdflib.namespace.SDO attribute*), 263
- `GlutenFreeDiet` (*rdflib.namespace.SDO attribute*), 206
- `Glycol` (*rdflib.namespace.BRICK attribute*), 97
- `gmLiteral` (*rdflib.namespace.GEO attribute*), 155
- `gMonth` (*rdflib.namespace.XSD attribute*), 316
- `gMonthDay` (*rdflib.namespace.XSD attribute*), 316
- `GolfCourse` (*rdflib.namespace.SDO attribute*), 206
- `governmentBenefitsInfo` (*rdflib.namespace.SDO attribute*), 263
- `GovernmentBenefitsType` (*rdflib.namespace.SDO attribute*), 206
- `GovernmentBuilding` (*rdflib.namespace.SDO attribute*), 206
- `GovernmentOffice` (*rdflib.namespace.SDO attribute*), 206
- `GovernmentOrganization` (*rdflib.namespace.SDO attribute*), 206
- `GovernmentPermit` (*rdflib.namespace.SDO attribute*), 206
- `GovernmentService` (*rdflib.namespace.SDO attribute*), 207
- `gracePeriod` (*rdflib.namespace.SDO attribute*), 263
- `Grant` (*rdflib.namespace.SDO attribute*), 207
- `grantee` (*rdflib.namespace.SDO attribute*), 263
- `grantUse` (*rdflib.namespace.ODRL2 attribute*), 166
- `Graph` (*class in rdflib*), 585
- `Graph` (*class in rdflib.graph*), 490
- `graph` (*rdflib.plugins.sparql.processor.SPARQLResult attribute*), 414
- `graph` (*rdflib.plugins.sparql.results.jsonresults.JSONResult attribute*), 373
- `graph` (*rdflib.plugins.sparql.results.rdfresults.RDFResult attribute*), 375
- `graph` (*rdflib.plugins.sparql.results.xmlresults.XMLResult attribute*), 378
- `graph` (*rdflib.resource.Resource property*), 545
- `graph()` (*in module rdflib.plugins.sparql.algebra*), 386
- `graph()` (*rdflib.Dataset method*), 583
- `graph()` (*rdflib.graph.Dataset method*), 489
- `graph()` (*rdflib.plugins.parsers.trig.TrigSinkParser method*), 349
- `graph_aware` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB attribute*), 434
- `graph_aware` (*rdflib.plugins.stores.memory.Memory attribute*), 437
- `graph_aware` (*rdflib.plugins.stores.sparqlstore.SPARQLStore attribute*), 448
- `graph_aware` (*rdflib.store.Store attribute*), 550
- `graph_diff()` (*in module rdflib.compare*), 468
- `graph_digest()` (*rdflib.compare.IsomorphicGraph method*), 468
- `graph_key` (*rdflib.plugins.shared.jsonld.context.Context property*), 368
- `GraphicNovel` (*rdflib.namespace.SDO attribute*), 207
- `GraphResultParser` (*class in rdflib.plugins.sparql.results.graph*), 373
- `graphs()` (*rdflib.Dataset method*), 584
- `graphs()` (*rdflib.graph.Dataset method*), 489

greater (*rdflib.namespace.SDO* attribute), 263  
 greaterOrEqual (*rdflib.namespace.SDO* attribute), 263  
 GroceryStore (*rdflib.namespace.SDO* attribute), 207  
 grossArea (*rdflib.namespace.BRICK* attribute), 135  
 Group (*rdflib.namespace.FOAF* attribute), 151  
 Group (*rdflib.namespace.ODRL2* attribute), 163  
 group (*rdflib.namespace.SH* attribute), 302  
 Group() (in module *rdflib.plugins.sparql.algebra*), 386  
 GroupBoardingPolicy (*rdflib.namespace.SDO* attribute), 207  
 groupChar (*rdflib.namespace.CSVW* attribute), 139  
 GroupConcat (class in *rdflib.plugins.sparql.aggregates*), 383  
 gt (*rdflib.namespace.ODRL2* attribute), 166  
 gteq (*rdflib.namespace.ODRL2* attribute), 166  
 gtin (*rdflib.namespace.SDO* attribute), 263  
 gtin12 (*rdflib.namespace.SDO* attribute), 263  
 gtin13 (*rdflib.namespace.SDO* attribute), 263  
 gtin14 (*rdflib.namespace.SDO* attribute), 263  
 gtin8 (*rdflib.namespace.SDO* attribute), 263  
 guess\_format() (in module *rdflib.util*), 572  
 Guide (*rdflib.namespace.SDO* attribute), 207  
 guideline (*rdflib.namespace.SDO* attribute), 263  
 guidelineDate (*rdflib.namespace.SDO* attribute), 263  
 guidelineSubject (*rdflib.namespace.SDO* attribute), 264  
 gYear (*rdflib.namespace.XSD* attribute), 316  
 gYearMonth (*rdflib.namespace.XSD* attribute), 316  
 Gynecologic (*rdflib.namespace.SDO* attribute), 207

## H

Hackathon (*rdflib.namespace.SDO* attribute), 207  
 hadActivity (*rdflib.namespace.PROV* attribute), 181  
 hadDelegate (*rdflib.namespace.PROV* attribute), 181  
 hadDerivation (*rdflib.namespace.PROV* attribute), 181  
 hadDictionaryMember (*rdflib.namespace.PROV* attribute), 181  
 hadGeneration (*rdflib.namespace.PROV* attribute), 181  
 hadInfluence (*rdflib.namespace.PROV* attribute), 181  
 hadMember (*rdflib.namespace.PROV* attribute), 181  
 hadPlan (*rdflib.namespace.PROV* attribute), 181  
 hadPrimarySource (*rdflib.namespace.PROV* attribute), 181  
 hadRevision (*rdflib.namespace.PROV* attribute), 181  
 hadRole (*rdflib.namespace.DCAT* attribute), 144  
 hadRole (*rdflib.namespace.PROV* attribute), 181  
 hadUsage (*rdflib.namespace.PROV* attribute), 181  
 Hail (*rdflib.namespace.BRICK* attribute), 97  
 Hail\_Sensor (*rdflib.namespace.BRICK* attribute), 97  
 HairSalon (*rdflib.namespace.SDO* attribute), 207  
 HalalDiet (*rdflib.namespace.SDO* attribute), 207  
 Hallway (*rdflib.namespace.BRICK* attribute), 97  
 handleAnnotation() (*rdflib.extras.infixowl.AnnotatableTerms* method),

61  
 handlingTime (*rdflib.namespace.SDO* attribute), 264  
 Hardcover (*rdflib.namespace.SDO* attribute), 207  
 HardwareStore (*rdflib.namespace.SDO* attribute), 207  
 has\_anchor (*rdflib.namespace.PROV* attribute), 181  
 has\_provenance (*rdflib.namespace.PROV* attribute), 181  
 has\_query\_service (*rdflib.namespace.PROV* attribute), 181  
 hasAddress (*rdflib.namespace.BRICK* attribute), 135  
 hasArtifact (*rdflib.namespace.PROV* attribute), 177  
 hasAssociatedTag (*rdflib.namespace.BRICK* attribute), 135  
 hasBeginning (*rdflib.namespace.TIME* attribute), 310  
 hasBioChemEntityPart (*rdflib.namespace.SDO* attribute), 264  
 hasBioPolymerSequence (*rdflib.namespace.SDO* attribute), 264  
 hasBroadcastChannel (*rdflib.namespace.SDO* attribute), 264  
 hasCategoryCode (*rdflib.namespace.SDO* attribute), 264  
 hasCourse (*rdflib.namespace.SDO* attribute), 264  
 hasCourseInstance (*rdflib.namespace.SDO* attribute), 264  
 hasCredential (*rdflib.namespace.SDO* attribute), 264  
 hasDateTimeDescription (*rdflib.namespace.TIME* attribute), 310  
 hasDefinedTerm (*rdflib.namespace.SDO* attribute), 264  
 hasDeliveryMethod (*rdflib.namespace.SDO* attribute), 264  
 hasDeployment (*rdflib.namespace.SSN* attribute), 308  
 hasDigitalDocumentPermission (*rdflib.namespace.SDO* attribute), 264  
 hasDriveThroughService (*rdflib.namespace.SDO* attribute), 264  
 hasDuration (*rdflib.namespace.TIME* attribute), 310  
 hasDurationDescription (*rdflib.namespace.TIME* attribute), 310  
 hasEnd (*rdflib.namespace.TIME* attribute), 310  
 hasEnergyConsumptionDetails (*rdflib.namespace.SDO* attribute), 264  
 hasEnergyEfficiencyCategory (*rdflib.namespace.SDO* attribute), 264  
 hasFeatureOfInterest (*rdflib.namespace.SOSA* attribute), 307  
 hasFormat (*rdflib.namespace.DCTERMS* attribute), 148  
 hasGeometry (*rdflib.namespace.GEO* attribute), 155  
 hasHealthAspect (*rdflib.namespace.SDO* attribute), 264  
 hashtriples() (*rdflib.tools.graphisomorphism.IsomorphicTestableGraph* method), 460  
 hasInput (*rdflib.namespace.SSN* attribute), 308  
 hasInputSubstance (*rdflib.namespace.BRICK* at-



- tribute*), 135
- hasKey (*rdflib.namespace.OWL* attribute), 175
- hasLocation (*rdflib.namespace.BRICK* attribute), 135
- hasMap (*rdflib.namespace.SDO* attribute), 264
- hasMeasurement (*rdflib.namespace.SDO* attribute), 264
- hasMember (*rdflib.namespace.ORG* attribute), 171
- hasMembership (*rdflib.namespace.ORG* attribute), 171
- hasMenu (*rdflib.namespace.SDO* attribute), 264
- hasMenuItem (*rdflib.namespace.SDO* attribute), 264
- hasMenuSection (*rdflib.namespace.SDO* attribute), 264
- hasMerchantReturnPolicy (*rdflib.namespace.SDO* attribute), 264
- hasMolecularFunction (*rdflib.namespace.SDO* attribute), 264
- hasOccupation (*rdflib.namespace.SDO* attribute), 265
- hasOfferCatalog (*rdflib.namespace.SDO* attribute), 265
- hasOutput (*rdflib.namespace.SSN* attribute), 308
- hasOutputSubstance (*rdflib.namespace.BRICK* attribute), 135
- hasPart (*rdflib.namespace.BRICK* attribute), 135
- hasPart (*rdflib.namespace.DCTERMS* attribute), 148
- hasPart (*rdflib.namespace.ODRL2* attribute), 167
- hasPart (*rdflib.namespace.SDO* attribute), 265
- hasPoint (*rdflib.namespace.BRICK* attribute), 136
- hasPolicy (*rdflib.namespace.ODRL2* attribute), 167
- hasPOS (*rdflib.namespace.SDO* attribute), 265
- hasPost (*rdflib.namespace.ORG* attribute), 171
- hasPrimarySite (*rdflib.namespace.ORG* attribute), 171
- hasProperty (*rdflib.namespace.SSN* attribute), 308
- hasQUDTReference (*rdflib.namespace.BRICK* attribute), 136
- hasRegisteredSite (*rdflib.namespace.ORG* attribute), 171
- hasRepresentation (*rdflib.namespace.SDO* attribute), 265
- hasResource (*rdflib.namespace.PROF* attribute), 177
- hasResult (*rdflib.namespace.SOSA* attribute), 307
- hasRole (*rdflib.namespace.PROF* attribute), 177
- hasSample (*rdflib.namespace.SOSA* attribute), 307
- hasSelf (*rdflib.namespace.OWL* attribute), 175
- hasSerialization (*rdflib.namespace.GEO* attribute), 155
- hasSimpleResult (*rdflib.namespace.SOSA* attribute), 307
- hasSite (*rdflib.namespace.ORG* attribute), 171
- hasSubOrganization (*rdflib.namespace.ORG* attribute), 171
- hasSubSystem (*rdflib.namespace.SSN* attribute), 308
- hasTag (*rdflib.namespace.BRICK* attribute), 136
- hasTemporalDuration (*rdflib.namespace.TIME* attribute), 311
- hasTime (*rdflib.namespace.TIME* attribute), 311
- hasTimeseriesId (*rdflib.namespace.BRICK* attribute), 136
- hasToken (*rdflib.namespace.PROF* attribute), 177
- hasTopConcept (*rdflib.namespace.SKOS* attribute), 305
- hasTRS (*rdflib.namespace.TIME* attribute), 311
- hasUnit (*rdflib.namespace.BRICK* attribute), 136
- hasUnit (*rdflib.namespace.ORG* attribute), 171
- hasValue (*rdflib.extras.infixowl.Restriction* property), 71
- hasValue (*rdflib.namespace.OWL* attribute), 175
- hasValue (*rdflib.namespace.SH* attribute), 302
- HasValueConstraintComponent (*rdflib.namespace.SH* attribute), 298
- hasVariant (*rdflib.namespace.SDO* attribute), 265
- hasVersion (*rdflib.namespace.DCTERMS* attribute), 148
- hasXSDDuration (*rdflib.namespace.TIME* attribute), 311
- Hazardous\_Materials\_Storage (*rdflib.namespace.BRICK* attribute), 98
- Head (*rdflib.namespace.ORG* attribute), 171
- Head (*rdflib.namespace.SDO* attribute), 207
- header (*rdflib.namespace.CSVW* attribute), 139
- headerRowCount (*rdflib.namespace.CSVW* attribute), 139
- headline (*rdflib.namespace.SDO* attribute), 265
- headOf (*rdflib.namespace.ORG* attribute), 171
- HealthAndBeautyBusiness (*rdflib.namespace.SDO* attribute), 207
- HealthAspectEnumeration (*rdflib.namespace.SDO* attribute), 207
- HealthCare (*rdflib.namespace.SDO* attribute), 207
- healthcareReportingData (*rdflib.namespace.SDO* attribute), 265
- HealthClub (*rdflib.namespace.SDO* attribute), 207
- healthCondition (*rdflib.namespace.SDO* attribute), 265
- HealthInsurancePlan (*rdflib.namespace.SDO* attribute), 207
- healthPlanCoinsuranceOption (*rdflib.namespace.SDO* attribute), 265
- healthPlanCoinsuranceRate (*rdflib.namespace.SDO* attribute), 265
- healthPlanCopay (*rdflib.namespace.SDO* attribute), 265
- healthPlanCopayOption (*rdflib.namespace.SDO* attribute), 265
- healthPlanCostSharing (*rdflib.namespace.SDO* attribute), 265
- HealthPlanCostSharingSpecification (*rdflib.namespace.SDO* attribute), 207
- healthPlanDrugOption (*rdflib.namespace.SDO* attribute), 265
- healthPlanDrugTier (*rdflib.namespace.SDO* attribute), 265

HealthPlanFormulary (rdflib.namespace.SDO attribute), 207

healthPlanId (rdflib.namespace.SDO attribute), 265

healthPlanMarketingUrl (rdflib.namespace.SDO attribute), 265

HealthPlanNetwork (rdflib.namespace.SDO attribute), 207

healthPlanNetworkId (rdflib.namespace.SDO attribute), 265

healthPlanNetworkTier (rdflib.namespace.SDO attribute), 265

healthPlanPharmacyCategory (rdflib.namespace.SDO attribute), 265

HealthTopicContent (rdflib.namespace.SDO attribute), 207

HearingImpairedSupported (rdflib.namespace.SDO attribute), 207

Heat\_Exchange (rdflib.namespace.BRICK attribute), 98

Heat\_Exchange\_Supply\_Water\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 98

Heat\_Exchange\_System\_Enable\_Status (rdflib.namespace.BRICK attribute), 98

Heat\_Recovery\_Hot\_Water\_System (rdflib.namespace.BRICK attribute), 98

Heat\_Sensor (rdflib.namespace.BRICK attribute), 98

Heat\_Wheel (rdflib.namespace.BRICK attribute), 98

Heat\_Wheel\_VFD (rdflib.namespace.BRICK attribute), 98

Heating\_Coil (rdflib.namespace.BRICK attribute), 98

Heating\_Command (rdflib.namespace.BRICK attribute), 98

Heating\_Demand\_Sensor (rdflib.namespace.BRICK attribute), 98

Heating\_Demand\_Setpoint (rdflib.namespace.BRICK attribute), 98

Heating\_Discharge\_Air\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 98

Heating\_Discharge\_Air\_Temperature\_Deadband\_Setpoint (rdflib.namespace.BRICK attribute), 98

Heating\_Discharge\_Air\_Temperature\_Integral\_Time\_Parameter (rdflib.namespace.BRICK attribute), 98

Heating\_Discharge\_Air\_Temperature\_Proportional\_Band\_Parameter (rdflib.namespace.BRICK attribute), 98

Heating\_Start\_Stop\_Status (rdflib.namespace.BRICK attribute), 98

Heating\_Supply\_Air\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 99

Heating\_Supply\_Air\_Temperature\_Deadband\_Setpoint (rdflib.namespace.BRICK attribute), 99

Heating\_Supply\_Air\_Temperature\_Integral\_Time\_Parameter (rdflib.namespace.BRICK attribute), 99

Heating\_Supply\_Air\_Temperature\_Proportional\_Band\_Parameter (rdflib.namespace.BRICK attribute), 99

Heating\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 99

Heating\_Thermal\_Power\_Sensor (rdflib.namespace.BRICK attribute), 99

Heating\_Valve (rdflib.namespace.BRICK attribute), 99

Heating\_Ventilation\_Air\_Conditioning\_System (rdflib.namespace.BRICK attribute), 99

height (rdflib.namespace.SDO attribute), 265

heldBy (rdflib.namespace.ORG attribute), 171

helper (rdflib.namespace.DOAP attribute), 150

Hematologic (rdflib.namespace.SDO attribute), 208

here() (rdflib.plugins.parsers.notation3.SinkParser method), 330

hexBinary (rdflib.namespace.XSD attribute), 316

hexify() (in module rdflib.plugins.parsers.notation3), 335

HextuplesParser (class in rdflib.plugins.parsers.hex), 319

HextuplesSerializer (class in rdflib.plugins.serializers.hex), 353

HgRepository (rdflib.namespace.DOAP attribute), 149

hiddenLabel (rdflib.namespace.SKOS attribute), 305

HierarchicalCodeList (rdflib.namespace.QB attribute), 185

hierarchyRoot (rdflib.namespace.QB attribute), 186

High\_CO2\_Alarm (rdflib.namespace.BRICK attribute), 99

High\_Discharge\_Air\_Temperature\_Alarm (rdflib.namespace.BRICK attribute), 99

High\_Head\_Pressure\_Alarm (rdflib.namespace.BRICK attribute), 99

High\_Humidity\_Alarm (rdflib.namespace.BRICK attribute), 99

High\_Humidity\_Alarm\_Parameter (rdflib.namespace.BRICK attribute), 99

High\_Outside\_Air\_Lockout\_Temperature\_Differential\_Parameter (rdflib.namespace.BRICK attribute), 99

High\_Return\_Air\_Temperature\_Alarm (rdflib.namespace.BRICK attribute), 99

High\_Static\_Pressure\_Cutout\_Setpoint\_Limit (rdflib.namespace.BRICK attribute), 99

High\_Temperature\_Alarm (rdflib.namespace.BRICK attribute), 99

High\_Temperature\_Alarm\_Parameter (rdflib.namespace.BRICK attribute), 100

High\_Temperature\_Hot\_Water\_Return\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 100

High\_Temperature\_Hot\_Water\_Supply\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 100

highPrice (rdflib.namespace.SDO attribute), 265

highSchool (rdflib.namespace.SDO attribute), 208

HinduDiet (rdflib.namespace.SDO attribute), 208

hiringOrganization (rdflib.namespace.SDO attribute), 208



- tribute), 266
- historyNote (rdflib.namespace.SKOS attribute), 305
- HobbyShop (rdflib.namespace.SDO attribute), 208
- Hold\_Status (rdflib.namespace.BRICK attribute), 100
- holdingArchive (rdflib.namespace.SDO attribute), 266
- holds (rdflib.namespace.ORG attribute), 171
- holdsAccount (rdflib.namespace.FOAF attribute), 152
- HomeAndConstructionBusiness (rdflib.namespace.SDO attribute), 208
- HomeGoodsStore (rdflib.namespace.SDO attribute), 208
- homeLocation (rdflib.namespace.SDO attribute), 266
- Homeopathic (rdflib.namespace.SDO attribute), 208
- homepage (rdflib.namespace.DOAP attribute), 150
- homepage (rdflib.namespace.FOAF attribute), 152
- homeTeam (rdflib.namespace.SDO attribute), 266
- honorificPrefix (rdflib.namespace.SDO attribute), 266
- honorificSuffix (rdflib.namespace.SDO attribute), 266
- Hospital (rdflib.namespace.SDO attribute), 208
- hospitalAffiliation (rdflib.namespace.SDO attribute), 266
- Hospitality\_Box (rdflib.namespace.BRICK attribute), 100
- Hostel (rdflib.namespace.SDO attribute), 208
- hostingOrganization (rdflib.namespace.SDO attribute), 266
- hosts (rdflib.namespace.SOSA attribute), 307
- Hot\_Box (rdflib.namespace.BRICK attribute), 100
- Hot\_Water (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Baseboard\_Radiator (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Coil (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Pressure\_Deadband\_Setpoint (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Pressure\_Integral\_Time\_Parameter (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Pressure\_Load\_Shed\_Reset\_Status (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Pressure\_Load\_Shed\_Status (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Pressure\_Proportional\_Band\_Parameter (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Pressure\_Sensor (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Pressure\_Setpoint (rdflib.namespace.BRICK attribute), 100
- Hot\_Water\_Differential\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Discharge\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Discharge\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Discharge\_Temperature\_Load\_Shed\_Status (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Loop (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Meter (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Pump (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Radiator (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Return\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Return\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Static\_Pressure\_Setpoint (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Supply\_Flow\_Sensor (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Supply\_Flow\_Setpoint (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Supply\_Temperature\_High\_Reset\_Setpoint (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Supply\_Temperature\_Load\_Shed\_Status (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Supply\_Temperature\_Low\_Reset\_Setpoint (rdflib.namespace.BRICK attribute), 101
- Hot\_Water\_Supply\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 102
- Hot\_Water\_System (rdflib.namespace.BRICK attribute), 102
- Hot\_Water\_System\_Enable\_Command (rdflib.namespace.BRICK attribute), 102
- Hot\_Water\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 102
- Hot\_Water\_Usage\_Sensor (rdflib.namespace.BRICK attribute), 102
- Hot\_Water\_Valve (rdflib.namespace.BRICK attribute), 102
- HomePainter (rdflib.namespace.SDO attribute), 208
- HotelRoom (rdflib.namespace.SDO attribute), 208
- hour (rdflib.namespace.TIME attribute), 311
- hour (rdflib.namespace.XSD attribute), 317
- hours (rdflib.namespace.TIME attribute), 311
- hoursAvailable (rdflib.namespace.SDO attribute), 266
- House (rdflib.namespace.SDO attribute), 208
- HousePainter (rdflib.namespace.SDO attribute), 208
- HowItWorksHealthAspect (rdflib.namespace.SDO attribute), 208
- HowOrWhereHealthAspect (rdflib.namespace.SDO attribute), 208

- `howPerformed` (*rdflib.namespace.SDO* attribute), 266
- `HowTo` (*rdflib.namespace.SDO* attribute), 208
- `HowToDirection` (*rdflib.namespace.SDO* attribute), 208
- `HowToItem` (*rdflib.namespace.SDO* attribute), 208
- `HowToSection` (*rdflib.namespace.SDO* attribute), 208
- `HowToStep` (*rdflib.namespace.SDO* attribute), 208
- `HowToSupply` (*rdflib.namespace.SDO* attribute), 208
- `HowToTip` (*rdflib.namespace.SDO* attribute), 208
- `HowToTool` (*rdflib.namespace.SDO* attribute), 208
- `HTML` (*rdflib.namespace.RDF* attribute), 187
- `http_open()` (*examples.secure\_with\_urlopen.SecuredHTTPHandler* method), 26
- `httpMethod` (*rdflib.namespace.SDO* attribute), 266
- `Humidification_Start_Stop_Status` (*rdflib.namespace.BRICK* attribute), 102
- `Humidifier` (*rdflib.namespace.BRICK* attribute), 102
- `Humidifier_Fault_Status` (*rdflib.namespace.BRICK* attribute), 102
- `Humidify_Command` (*rdflib.namespace.BRICK* attribute), 102
- `Humidity_Alarm` (*rdflib.namespace.BRICK* attribute), 102
- `Humidity_Parameter` (*rdflib.namespace.BRICK* attribute), 102
- `Humidity_Sensor` (*rdflib.namespace.BRICK* attribute), 102
- `Humidity_Setpoint` (*rdflib.namespace.BRICK* attribute), 102
- `Humidity_Tolerance_Parameter` (*rdflib.namespace.BRICK* attribute), 102
- `HVAC_Equipment` (*rdflib.namespace.BRICK* attribute), 97
- `HVAC_System` (*rdflib.namespace.BRICK* attribute), 97
- `HVAC_Zone` (*rdflib.namespace.BRICK* attribute), 97
- `HVACBusiness` (*rdflib.namespace.SDO* attribute), 207
- `HX` (*rdflib.namespace.BRICK* attribute), 97
- `HyperToc` (*rdflib.namespace.SDO* attribute), 208
- `HyperTocEntry` (*rdflib.namespace.SDO* attribute), 208
- I**
- `iataCode` (*rdflib.namespace.SDO* attribute), 266
- `icaoCode` (*rdflib.namespace.SDO* attribute), 266
- `Ice` (*rdflib.namespace.BRICK* attribute), 102
- `Ice_Tank_Leaving_Water_Temperature_Sensor` (*rdflib.namespace.BRICK* attribute), 102
- `IceCreamShop` (*rdflib.namespace.SDO* attribute), 208
- `icqChatID` (*rdflib.namespace.FOAF* attribute), 152
- `ID` (*rdflib.namespace.XSD* attribute), 315
- `ID` (*rdflib.plugins.parsers.RDFVOC.RDFVOC* attribute), 319
- `id` (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342
- `id` (*rdflib.plugins.shared.jsonld.context.Term* attribute), 369
- `id()` (*rdflib.plugins.parsers.notation3.Formula* method), 323
- `id_key` (*rdflib.plugins.shared.jsonld.context.Context* property), 368
- `IdentifiedNode` (class in *rdflib*), 603
- `IdentifiedNode` (class in *rdflib.term*), 554
- `Identifier` (class in *rdflib.term*), 555
- `identifier` (*rdflib.extras.infixowl.Individual* property), 67
- `identifier` (*rdflib.Graph* property), 594
- `identifier` (*rdflib.graph.Graph* property), 499
- `identifier` (*rdflib.namespace.DC* attribute), 142
- `identifier` (*rdflib.namespace.DCTERMS* attribute), 148
- `identifier` (*rdflib.namespace.ORG* attribute), 171
- `identifier` (*rdflib.namespace.SDO* attribute), 266
- `identifier` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* property), 434
- `identifier` (*rdflib.resource.Resource* property), 545
- `identifyingExam` (*rdflib.namespace.SDO* attribute), 266
- `identifyingTest` (*rdflib.namespace.SDO* attribute), 266
- `IDF` (*rdflib.namespace.BRICK* attribute), 102
- `IDREF` (*rdflib.namespace.XSD* attribute), 315
- `IDREFS` (*rdflib.namespace.XSD* attribute), 315
- `ignorableWhitespace()` (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 344
- `ignorableWhitespace()` (*rdflib.plugins.parsers.trix.TriXHandler* method), 351
- `ignore` (*rdflib.namespace.ODRL2* attribute), 167
- `IgnoreAction` (*rdflib.namespace.SDO* attribute), 208
- `ignoredProperties` (*rdflib.namespace.SH* attribute), 302
- `ignoreExprs` (*rdflib.plugins.sparql.parserutils.ParamList* attribute), 412
- `ill_typed` (*rdflib.Literal* property), 611
- `ill_typed` (*rdflib.term.Literal* property), 565
- `Illuminance_Sensor` (*rdflib.namespace.BRICK* attribute), 102
- `illustrator` (*rdflib.namespace.SDO* attribute), 266
- `Image` (*rdflib.namespace.DCMITYPE* attribute), 145
- `Image` (*rdflib.namespace.FOAF* attribute), 151
- `image` (*rdflib.namespace.SDO* attribute), 266
- `ImageGallery` (*rdflib.namespace.SDO* attribute), 209
- `ImageObject` (*rdflib.namespace.SDO* attribute), 209
- `ImageObjectSnapshot` (*rdflib.namespace.SDO* attribute), 209
- `imagingTechnique` (*rdflib.namespace.SDO* attribute), 266
- `ImagingTest` (*rdflib.namespace.SDO* attribute), 209

- Imbalance\_Sensor (rdflib.namespace.BRICK attribute), 103
- img (rdflib.namespace.FOAF attribute), 152
- implementedBy (rdflib.namespace.SSN attribute), 309
- implements (rdflib.namespace.DOAP attribute), 150
- implements (rdflib.namespace.SSN attribute), 309
- implies (rdflib.namespace.ODRL2 attribute), 167
- imports (rdflib.extras.infixowl.Ontology property), 69
- imports (rdflib.namespace.OWL attribute), 175
- IMT (rdflib.namespace.DCTERMS attribute), 145
- inAlbum (rdflib.namespace.SDO attribute), 266
- inBroadcastLineup (rdflib.namespace.SDO attribute), 266
- incentiveCompensation (rdflib.namespace.SDO attribute), 267
- incentives (rdflib.namespace.SDO attribute), 267
- inChI (rdflib.namespace.SDO attribute), 266
- inChIKey (rdflib.namespace.SDO attribute), 266
- include (rdflib.namespace.ODRL2 attribute), 167
- includedComposition (rdflib.namespace.SDO attribute), 267
- includedDataCatalog (rdflib.namespace.SDO attribute), 267
- includedIn (rdflib.namespace.ODRL2 attribute), 167
- includedInDataCatalog (rdflib.namespace.SDO attribute), 267
- includedInHealthInsurancePlan (rdflib.namespace.SDO attribute), 267
- includedRiskFactor (rdflib.namespace.SDO attribute), 267
- includesAttraction (rdflib.namespace.SDO attribute), 267
- includesHealthPlanFormulary (rdflib.namespace.SDO attribute), 267
- includesHealthPlanNetwork (rdflib.namespace.SDO attribute), 267
- includesObject (rdflib.namespace.SDO attribute), 267
- inCodeSet (rdflib.namespace.SDO attribute), 266
- incompatibleWith (rdflib.namespace.OWL attribute), 175
- InConstraintComponent (rdflib.namespace.SH attribute), 298
- increasesRiskOf (rdflib.namespace.SDO attribute), 267
- inDataset (rdflib.namespace.VOID attribute), 314
- inDateTime (rdflib.namespace.TIME attribute), 311
- inDefinedTermSet (rdflib.namespace.SDO attribute), 266
- indent (rdflib.plugins.serializers.xmlwriter.XMLWriter property), 363
- indent() (rdflib.plugins.serializers.n3.N3Serializer method), 357
- indent() (rdflib.plugins.serializers.turtle.RecursiveSerializer method), 361
- indentString (rdflib.plugins.serializers.longturtle.LongTurtleSerializer attribute), 356
- indentString (rdflib.plugins.serializers.trig.TrigSerializer attribute), 360
- indentString (rdflib.plugins.serializers.turtle.RecursiveSerializer attribute), 361
- indentString (rdflib.plugins.serializers.turtle.TurtleSerializer attribute), 362
- inDeployment (rdflib.namespace.SSN attribute), 309
- index (rdflib.namespace.ODRL2 attribute), 167
- index (rdflib.plugins.shared.jsonld.context.Term attribute), 370
- index() (rdflib.collection.Collection method), 465
- index() (rdflib.container.Container method), 473
- index() (rdflib.extras.infixowl.OWLRLDListProxy method), 69
- Individual (class in rdflib.extras.infixowl), 66
- Individual (rdflib.namespace.ODRL2 attribute), 163
- IndividualProduct (rdflib.namespace.SDO attribute), 209
- Induction\_Unit (rdflib.namespace.BRICK attribute), 103
- industry (rdflib.namespace.ODRL2 attribute), 167
- industry (rdflib.namespace.SDO attribute), 267
- ineligibleRegion (rdflib.namespace.SDO attribute), 267
- Infectious (rdflib.namespace.SDO attribute), 209
- infectiousAgent (rdflib.namespace.SDO attribute), 267
- InfectiousAgentClass (rdflib.namespace.SDO attribute), 209
- infectiousAgentClass (rdflib.namespace.SDO attribute), 267
- InfectiousDisease (rdflib.namespace.SDO attribute), 209
- Infix (class in rdflib.extras.infixowl), 67
- Influence (rdflib.namespace.PROV attribute), 179
- influenced (rdflib.namespace.PROV attribute), 181
- influencer (rdflib.namespace.PROV attribute), 181
- Info (rdflib.namespace.SH attribute), 298
- InForce (rdflib.namespace.SDO attribute), 209
- inform (rdflib.namespace.ODRL2 attribute), 167
- InformAction (rdflib.namespace.SDO attribute), 209
- Information\_Area (rdflib.namespace.BRICK attribute), 103
- informed (rdflib.namespace.PROV attribute), 181
- informedParty (rdflib.namespace.ODRL2 attribute), 167
- informingParty (rdflib.namespace.ODRL2 attribute), 167
- ingredients (rdflib.namespace.SDO attribute), 267
- IngredientsHealthAspect (rdflib.namespace.SDO attribute), 209
- inherit (rdflib.namespace.CSVW attribute), 139

- `inheritAllowed` (`rdflib.namespace.ODRL2` attribute), 167
- `inheritFrom` (`rdflib.namespace.ODRL2` attribute), 167
- `inheritRelation` (`rdflib.namespace.ODRL2` attribute), 167
- `inker` (`rdflib.namespace.SDO` attribute), 267
- `inLanguage` (`rdflib.namespace.SDO` attribute), 266
- `inPlaylist` (`rdflib.namespace.SDO` attribute), 266
- `inProductGroupWithID` (`rdflib.namespace.SDO` attribute), 267
- `Input` (`rdflib.namespace.SSN` attribute), 308
- `InputSource` (class in `rdflib.parser`), 516
- `inScheme` (`rdflib.namespace.SKOS` attribute), 305
- `InsertAction` (`rdflib.namespace.SDO` attribute), 209
- `insertedKeyEntityPair` (`rdflib.namespace.PROV` attribute), 181
- `Insertion` (`rdflib.namespace.PROV` attribute), 179
- `insertion` (`rdflib.namespace.SDO` attribute), 267
- `inside` (`rdflib.namespace.TIME` attribute), 311
- `Inside_Face_Surface_Temperature_Sensor` (`rdflib.namespace.BRICK` attribute), 103
- `Inside_Face_Surface_Temperature_Setpoint` (`rdflib.namespace.BRICK` attribute), 103
- `install` (`rdflib.namespace.ODRL2` attribute), 167
- `InstallAction` (`rdflib.namespace.SDO` attribute), 209
- `Installment` (`rdflib.namespace.SDO` attribute), 209
- `installUrl` (`rdflib.namespace.SDO` attribute), 267
- `Instant` (`rdflib.namespace.TIME` attribute), 309
- `InstantaneousEvent` (`rdflib.namespace.PROV` attribute), 179
- `InStock` (`rdflib.namespace.SDO` attribute), 209
- `InStoreOnly` (`rdflib.namespace.SDO` attribute), 209
- `inStoreReturnsOffered` (`rdflib.namespace.SDO` attribute), 267
- `instructionalMethod` (`rdflib.namespace.DCTERMS` attribute), 148
- `instructor` (`rdflib.namespace.SDO` attribute), 268
- `instrument` (`rdflib.namespace.SDO` attribute), 268
- `inSupportOf` (`rdflib.namespace.SDO` attribute), 267
- `InsuranceAgency` (`rdflib.namespace.SDO` attribute), 209
- `int` (`rdflib.namespace.XSD` attribute), 317
- `Intake_Air_Filter` (`rdflib.namespace.BRICK` attribute), 103
- `Intake_Air_Temperature_Sensor` (`rdflib.namespace.BRICK` attribute), 103
- `Intangible` (`rdflib.namespace.SDO` attribute), 209
- `Integer` (`rdflib.namespace.SDO` attribute), 209
- `integer` (`rdflib.namespace.XSD` attribute), 317
- `Integral_Gain_Parameter` (`rdflib.namespace.BRICK` attribute), 103
- `Integral_Time_Parameter` (`rdflib.namespace.BRICK` attribute), 103
- `inTemporalPosition` (`rdflib.namespace.TIME` attribute), 311
- `intensity` (`rdflib.namespace.SDO` attribute), 268
- `InteractAction` (`rdflib.namespace.SDO` attribute), 209
- `interactingDrug` (`rdflib.namespace.SDO` attribute), 268
- `interactionCount` (`rdflib.namespace.SDO` attribute), 268
- `InteractionCounter` (`rdflib.namespace.SDO` attribute), 209
- `interactionService` (`rdflib.namespace.SDO` attribute), 268
- `interactionStatistic` (`rdflib.namespace.SDO` attribute), 268
- `interactionType` (`rdflib.namespace.SDO` attribute), 268
- `InteractiveResource` (`rdflib.namespace.DCMITYPE` attribute), 145
- `interactivityType` (`rdflib.namespace.SDO` attribute), 268
- `Intercom_Equipment` (`rdflib.namespace.BRICK` attribute), 103
- `interest` (`rdflib.namespace.FOAF` attribute), 152
- `interestRate` (`rdflib.namespace.SDO` attribute), 268
- `Interface` (`rdflib.namespace.BRICK` attribute), 103
- `intern()` (`rdflib.plugins.parsers.notation3.RDFSink` method), 324
- `internal_hash()` (`rdflib.compare.IsomorphicGraph` method), 468
- `internal_hash()` (`rdflib.tools.graphisomorphism.IsomorphicTestableGraph` method), 460
- `InternationalTrial` (`rdflib.namespace.SDO` attribute), 209
- `InternetCafe` (`rdflib.namespace.SDO` attribute), 209
- `interpretedAsClaim` (`rdflib.namespace.SDO` attribute), 268
- `intersection` (`rdflib.namespace.SH` attribute), 302
- `intersectionOf` (`rdflib.namespace.OWL` attribute), 175
- `Interval` (`rdflib.namespace.TIME` attribute), 309
- `intervalAfter` (`rdflib.namespace.TIME` attribute), 311
- `intervalBefore` (`rdflib.namespace.TIME` attribute), 311
- `intervalContains` (`rdflib.namespace.TIME` attribute), 311
- `intervalDisjoint` (`rdflib.namespace.TIME` attribute), 311
- `intervalDuring` (`rdflib.namespace.TIME` attribute), 311
- `intervalEquals` (`rdflib.namespace.TIME` attribute), 311
- `intervalFinishedBy` (`rdflib.namespace.TIME` attribute), 311
- `intervalFinishes` (`rdflib.namespace.TIME` attribute), 311



- 312
- `intervalIn` (*rdflib.namespace.TIME* attribute), 312
- `intervalMeets` (*rdflib.namespace.TIME* attribute), 312
- `intervalMetBy` (*rdflib.namespace.TIME* attribute), 312
- `intervalOverlappedBy` (*rdflib.namespace.TIME* attribute), 312
- `intervalOverlaps` (*rdflib.namespace.TIME* attribute), 312
- `intervalStartedBy` (*rdflib.namespace.TIME* attribute), 312
- `intervalStarts` (*rdflib.namespace.TIME* attribute), 312
- `inTimePosition` (*rdflib.namespace.TIME* attribute), 311
- `Intrusion_Detection_Equipment` (*rdflib.namespace.BRICK* attribute), 103
- `inv_path()` (in module *rdflib.paths*), 527
- `invalid` (*rdflib.namespace.ODRL2* attribute), 167
- `invalidated` (*rdflib.namespace.PROV* attribute), 182
- `invalidatedAtTime` (*rdflib.namespace.PROV* attribute), 182
- `Invalidation` (*rdflib.namespace.PROV* attribute), 179
- `inventoryLevel` (*rdflib.namespace.SDO* attribute), 268
- `inverse` (*rdflib.namespace.PROV* attribute), 182
- `InverseFunctionalProperty` (*rdflib.namespace.OWL* attribute), 173
- `inverseOf` (*rdflib.extras.infixowl.Property* property), 70
- `inverseOf` (*rdflib.namespace.OWL* attribute), 175
- `inverseOf` (*rdflib.namespace.SDO* attribute), 268
- `inversePath` (*rdflib.namespace.SH* attribute), 302
- `Inverter` (*rdflib.namespace.BRICK* attribute), 103
- `InvestmentFund` (*rdflib.namespace.SDO* attribute), 209
- `InvestmentOrDeposit` (*rdflib.namespace.SDO* attribute), 209
- `InviteAction` (*rdflib.namespace.SDO* attribute), 209
- `Invoice` (*rdflib.namespace.SDO* attribute), 210
- `InvoicePrice` (*rdflib.namespace.SDO* attribute), 210
- `InvPath` (class in *rdflib.paths*), 523
- `inXSDDate` (*rdflib.namespace.TIME* attribute), 311
- `inXSDDateTime` (*rdflib.namespace.TIME* attribute), 311
- `inXSDDateTimeStamp` (*rdflib.namespace.TIME* attribute), 311
- `inXSdgYear` (*rdflib.namespace.TIME* attribute), 311
- `inXSdgYearMonth` (*rdflib.namespace.TIME* attribute), 311
- `IRI` (*rdflib.namespace.SH* attribute), 298
- `IRIOrLiteral` (*rdflib.namespace.SH* attribute), 298
- `IRIREF` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 452
- `IrreflexiveProperty` (*rdflib.namespace.OWL* attribute), 173
- `is_ncname()` (in module *rdflib.namespace*), 318
- `is_open()` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 434
- `isA` (*rdflib.namespace.ODRL2* attribute), 167
- `isAcceptingNewPatients` (*rdflib.namespace.SDO* attribute), 268
- `isAccessibleForFree` (*rdflib.namespace.SDO* attribute), 268
- `isAccessoryOrSparePartFor` (*rdflib.namespace.SDO* attribute), 268
- `isActedOnBy` (*rdflib.namespace.SOSA* attribute), 307
- `isAllOf` (*rdflib.namespace.ODRL2* attribute), 167
- `isAnyOf` (*rdflib.namespace.ODRL2* attribute), 167
- `isAssociatedWith` (*rdflib.namespace.BRICK* attribute), 136
- `isAvailableGenerically` (*rdflib.namespace.SDO* attribute), 268
- `isBasedOn` (*rdflib.namespace.SDO* attribute), 268
- `isBasedOnUrl` (*rdflib.namespace.SDO* attribute), 268
- `isblank()` (*rdflib.plugins.shared.jsonld.context.Context* method), 368
- `isbn` (*rdflib.namespace.SDO* attribute), 269
- `isCompatibleDateTimeDatatype()` (in module *rdflib.plugins.sparql.operators*), 406
- `isConsumableFor` (*rdflib.namespace.SDO* attribute), 268
- `isDefinedBy` (*rdflib.namespace.RDFS* attribute), 188
- `isDone()` (*rdflib.plugins.serializers.turtle.RecursiveSerializer* method), 361
- `isEmpty` (*rdflib.namespace.GEO* attribute), 155
- `isEncodedByBioChemEntity` (*rdflib.namespace.SDO* attribute), 268
- `isFamilyFriendly` (*rdflib.namespace.SDO* attribute), 268
- `isFeatureOfInterestOf` (*rdflib.namespace.SOSA* attribute), 307
- `isFedBy` (*rdflib.namespace.BRICK* attribute), 136
- `isFormatOf` (*rdflib.namespace.DCTERMS* attribute), 148
- `isGift` (*rdflib.namespace.SDO* attribute), 268
- `isHostedBy` (*rdflib.namespace.SOSA* attribute), 307
- `isicV4` (*rdflib.namespace.SDO* attribute), 269
- `isInheritedFrom` (*rdflib.namespace.PROF* attribute), 177
- `isInvolvedInBiologicalProcess` (*rdflib.namespace.SDO* attribute), 268
- `isLiveBroadcast` (*rdflib.namespace.SDO* attribute), 269
- `isLocatedInSubcellularLocation` (*rdflib.namespace.SDO* attribute), 269
- `isLocationOf` (*rdflib.namespace.BRICK* attribute), 136
- `isMeasuredBy` (*rdflib.namespace.BRICK* attribute), 136
- `isNoneOf` (*rdflib.namespace.ODRL2* attribute), 167
- `ISO3166` (*rdflib.namespace.DCTERMS* attribute), 145
- `isObservedBy` (*rdflib.namespace.SOSA* attribute), 307
- `Isolation_Valve` (*rdflib.namespace.BRICK* attribute), 103

isomorphic() (in module *rdflib.compare*), 468  
 isomorphic() (*rdflib.Graph* method), 594  
 isomorphic() (*rdflib.graph.Graph* method), 499  
 IsomorphicGraph (class in *rdflib.compare*), 467  
 IsomorphicTestableGraph (class in *rdflib.tools.graphisomorphism*), 460  
 isPartOf (*rdflib.namespace.BRICK* attribute), 136  
 isPartOf (*rdflib.namespace.DCTERMS* attribute), 148  
 isPartOf (*rdflib.namespace.ODRL2* attribute), 167  
 isPartOf (*rdflib.namespace.SDO* attribute), 269  
 isPartOfBioChemEntity (*rdflib.namespace.SDO* attribute), 269  
 isPlanForApartment (*rdflib.namespace.SDO* attribute), 269  
 isPointOf (*rdflib.namespace.BRICK* attribute), 136  
 isPrimaryTopicOf (*rdflib.namespace.FOAF* attribute), 152  
 isPrimitive() (*rdflib.extras.infixowl.BooleanClass* method), 62  
 isPrimitive() (*rdflib.extras.infixowl.Class* method), 64  
 isPrimitive() (*rdflib.extras.infixowl.EnumeratedClass* method), 66  
 isPrimitive() (*rdflib.extras.infixowl.Restriction* method), 71  
 isProfileOf (*rdflib.namespace.PROF* attribute), 177  
 isPropertyOf (*rdflib.namespace.SSN* attribute), 309  
 isProprietary (*rdflib.namespace.SDO* attribute), 269  
 isProxyFor (*rdflib.namespace.SSN* attribute), 309  
 isrcCode (*rdflib.namespace.SDO* attribute), 269  
 isReferencedBy (*rdflib.namespace.DCTERMS* attribute), 148  
 isRegulatedBy (*rdflib.namespace.BRICK* attribute), 136  
 isRelatedTo (*rdflib.namespace.SDO* attribute), 269  
 isReplacedBy (*rdflib.namespace.DCTERMS* attribute), 148  
 isRequiredBy (*rdflib.namespace.DCTERMS* attribute), 148  
 isResizable (*rdflib.namespace.SDO* attribute), 269  
 isResultOf (*rdflib.namespace.SOSA* attribute), 307  
 isSampleOf (*rdflib.namespace.SOSA* attribute), 307  
 isSimilarTo (*rdflib.namespace.SDO* attribute), 269  
 isSimple (*rdflib.namespace.GEO* attribute), 155  
 issn (*rdflib.namespace.SDO* attribute), 269  
 issued (*rdflib.namespace.DCTERMS* attribute), 148  
 issuedBy (*rdflib.namespace.SDO* attribute), 269  
 issuedThrough (*rdflib.namespace.SDO* attribute), 269  
 issueNumber (*rdflib.namespace.SDO* attribute), 269  
 isTagOf (*rdflib.namespace.BRICK* attribute), 136  
 isTransitiveProfileOf (*rdflib.namespace.PROF* attribute), 177  
 isUnlabelledFallback (*rdflib.namespace.SDO* attribute), 269

isValidList() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356  
 isValidList() (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 362  
 isVariantOf (*rdflib.namespace.SDO* attribute), 269  
 isVersionOf (*rdflib.namespace.DCTERMS* attribute), 148  
 iswcCode (*rdflib.namespace.SDO* attribute), 269  
 item (*rdflib.namespace.SDO* attribute), 269  
 item() (*rdflib.plugins.parsers.notation3.SinkParser* method), 330  
 ItemAvailability (*rdflib.namespace.SDO* attribute), 210  
 itemCondition (*rdflib.namespace.SDO* attribute), 269  
 itemDefectReturnFees (*rdflib.namespace.SDO* attribute), 269  
 itemDefectReturnLabelSource (*rdflib.namespace.SDO* attribute), 269  
 itemDefectReturnShippingFeesAmount (*rdflib.namespace.SDO* attribute), 269  
 ItemList (*rdflib.namespace.SDO* attribute), 210  
 itemListElement (*rdflib.namespace.SDO* attribute), 269  
 itemListOrder (*rdflib.namespace.SDO* attribute), 269  
 ItemListOrderAscending (*rdflib.namespace.SDO* attribute), 210  
 ItemListOrderDescending (*rdflib.namespace.SDO* attribute), 210  
 ItemListOrderType (*rdflib.namespace.SDO* attribute), 210  
 ItemListUnordered (*rdflib.namespace.SDO* attribute), 210  
 itemLocation (*rdflib.namespace.SDO* attribute), 270  
 itemOffered (*rdflib.namespace.SDO* attribute), 270  
 ItemPage (*rdflib.namespace.SDO* attribute), 210  
 itemReviewed (*rdflib.namespace.SDO* attribute), 270  
 items() (*rdflib.container.Container* method), 473  
 items() (*rdflib.Graph* method), 594  
 items() (*rdflib.graph.Graph* method), 499  
 items() (*rdflib.resource.Resource* method), 545  
 itemShipped (*rdflib.namespace.SDO* attribute), 270  
 itinerary (*rdflib.namespace.SDO* attribute), 270  
 iupacName (*rdflib.namespace.SDO* attribute), 270

## J

jabberID (*rdflib.namespace.FOAF* attribute), 152  
 Janitor\_Room (*rdflib.namespace.BRICK* attribute), 103  
 January (*rdflib.namespace.TIME* attribute), 309  
 Jet\_Nozzle\_Air\_Diffuser (*rdflib.namespace.BRICK* attribute), 103  
 JewelryStore (*rdflib.namespace.SDO* attribute), 210  
 jobBenefits (*rdflib.namespace.SDO* attribute), 270  
 jobImmediateStart (*rdflib.namespace.SDO* attribute), 270

jobLocation (*rdflib.namespace.SDO* attribute), 270  
 jobLocationType (*rdflib.namespace.SDO* attribute), 270  
 JobPosting (*rdflib.namespace.SDO* attribute), 210  
 jobStartDate (*rdflib.namespace.SDO* attribute), 270  
 jobTitle (*rdflib.namespace.SDO* attribute), 270  
 join() (in module *rdflib.plugins.parsers.notation3*), 335  
 Join() (in module *rdflib.plugins.sparql.algebra*), 386  
 JoinAction (*rdflib.namespace.SDO* attribute), 210  
 Joint (*rdflib.namespace.SDO* attribute), 210  
 js (*rdflib.namespace.SH* attribute), 302  
 JSConstraint (*rdflib.namespace.SH* attribute), 298  
 JSConstraintComponent (*rdflib.namespace.SH* attribute), 298  
 JSExecutable (*rdflib.namespace.SH* attribute), 298  
 JSFunction (*rdflib.namespace.SH* attribute), 298  
 jsFunctionName (*rdflib.namespace.SH* attribute), 302  
 JSLibrary (*rdflib.namespace.SH* attribute), 298  
 jsLibrary (*rdflib.namespace.SH* attribute), 302  
 jsLibraryURL (*rdflib.namespace.SH* attribute), 302  
 JSON (*rdflib.namespace.CSVW* attribute), 138  
 JSON (*rdflib.namespace.RDF* attribute), 187  
 JSONLDException, 370  
 JsonLDParse (class in *rdflib.plugins.parsers.jsonld*), 320  
 JsonLDSerializer (class in *rdflib.plugins.serializers.jsonld*), 354  
 JSONResult (class in *rdflib.plugins.sparql.results.jsonresults*), 373  
 JSONResultParser (class in *rdflib.plugins.sparql.results.jsonresults*), 373  
 JSONResultSerializer (class in *rdflib.plugins.sparql.results.jsonresults*), 374  
 JSRule (*rdflib.namespace.SH* attribute), 298  
 JSTarget (*rdflib.namespace.SH* attribute), 298  
 JSTargetType (*rdflib.namespace.SH* attribute), 298  
 JSValidator (*rdflib.namespace.SH* attribute), 298  
 Jurisdiction (*rdflib.namespace.DCTERMS* attribute), 146  
 jurisdiction (*rdflib.namespace.SDO* attribute), 270

## K

KeyEntityPair (*rdflib.namespace.PROV* attribute), 179  
 keyword (*rdflib.namespace.DCAT* attribute), 144  
 keywords (*rdflib.namespace.SDO* attribute), 270  
 knownVehicleDamages (*rdflib.namespace.SDO* attribute), 270  
 knows (*rdflib.namespace.FOAF* attribute), 152  
 knows (*rdflib.namespace.SDO* attribute), 270  
 knowsAbout (*rdflib.namespace.SDO* attribute), 270  
 knowsLanguage (*rdflib.namespace.SDO* attribute), 270  
 KosherDiet (*rdflib.namespace.SDO* attribute), 210

## L

label (*rdflib.extras.infixowl.AnnotatableTerms* property), 61  
 label (*rdflib.namespace.RDFS* attribute), 188  
 label() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356  
 label() (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 362  
 labelDetails (*rdflib.namespace.SDO* attribute), 270  
 labelOrSubject() (*rdflib.plugins.parsers.trig.TrigSinkParser* method), 349  
 LabelProperty (*rdflib.namespace.FOAF* attribute), 151  
 labels (*rdflib.query.ResultRow* attribute), 536  
 labelTemplate (*rdflib.namespace.SH* attribute), 302  
 Laboratory (*rdflib.namespace.BRICK* attribute), 103  
 LaboratoryScience (*rdflib.namespace.SDO* attribute), 210  
 LakeBodyOfWater (*rdflib.namespace.SDO* attribute), 210  
 Laminar\_Flow\_Air\_Diffuser (*rdflib.namespace.BRICK* attribute), 103  
 Landform (*rdflib.namespace.SDO* attribute), 210  
 landingPage (*rdflib.namespace.DCAT* attribute), 144  
 landlord (*rdflib.namespace.SDO* attribute), 270  
 LandmarksOrHistoricalBuildings (*rdflib.namespace.SDO* attribute), 210  
 lang (*rdflib.namespace.CSVW* attribute), 139  
 lang\_key (*rdflib.plugins.shared.jsonld.context.Context* property), 368  
 langString (*rdflib.namespace.RDF* attribute), 187  
 language (*rdflib.Literal* property), 611  
 language (*rdflib.namespace.DC* attribute), 142  
 language (*rdflib.namespace.DCTERMS* attribute), 148  
 language (*rdflib.namespace.DOAP* attribute), 150  
 language (*rdflib.namespace.ODRL2* attribute), 167  
 language (*rdflib.namespace.RDF* attribute), 187  
 Language (*rdflib.namespace.SDO* attribute), 210  
 language (*rdflib.namespace.SDO* attribute), 270  
 language (*rdflib.namespace.XSD* attribute), 317  
 language (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342  
 language (*rdflib.plugins.shared.jsonld.context.Term* attribute), 370  
 language (*rdflib.term.Literal* property), 565  
 languageIn (*rdflib.namespace.SH* attribute), 302  
 LanguageInConstraintComponent (*rdflib.namespace.SH* attribute), 298  
 LaserDiscFormat (*rdflib.namespace.SDO* attribute), 210  
 Last\_Fault\_Code\_Status (*rdflib.namespace.BRICK* attribute), 103  
 lastName (*rdflib.namespace.FOAF* attribute), 152  
 lastReviewed (*rdflib.namespace.SDO* attribute), 270



- lat (*rdflib.namespace.WGS* attribute), 315
- lat\_long (*rdflib.namespace.WGS* attribute), 315
- latitude (*rdflib.namespace.BRICK* attribute), 136
- latitude (*rdflib.namespace.SDO* attribute), 270
- layoutImage (*rdflib.namespace.SDO* attribute), 270
- LCC (*rdflib.namespace.DCTERMS* attribute), 146
- LCSH (*rdflib.namespace.DCTERMS* attribute), 146
- Lead\_Lag\_Command (*rdflib.namespace.BRICK* attribute), 104
- Lead\_Lag\_Status (*rdflib.namespace.BRICK* attribute), 104
- Lead\_On\_Off\_Command (*rdflib.namespace.BRICK* attribute), 104
- Leak\_Alarm (*rdflib.namespace.BRICK* attribute), 104
- LearningResource (*rdflib.namespace.SDO* attribute), 210
- learningResourceType (*rdflib.namespace.SDO* attribute), 270
- lease (*rdflib.namespace.ODRL2* attribute), 167
- leaseLength (*rdflib.namespace.SDO* attribute), 270
- LeaveAction (*rdflib.namespace.SDO* attribute), 210
- Leaving\_Water (*rdflib.namespace.BRICK* attribute), 104
- Leaving\_Water\_Flow\_Sensor (*rdflib.namespace.BRICK* attribute), 104
- Leaving\_Water\_Flow\_Setpoint (*rdflib.namespace.BRICK* attribute), 104
- Leaving\_Water\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 104
- Leaving\_Water\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 104
- LeftHandDriving (*rdflib.namespace.SDO* attribute), 210
- LeftJoin() (in module *rdflib.plugins.sparql.algebra*), 387
- LeftOperand (*rdflib.namespace.ODRL2* attribute), 163
- leftOperand (*rdflib.namespace.ODRL2* attribute), 167
- LegalForceStatus (*rdflib.namespace.SDO* attribute), 210
- legalName (*rdflib.namespace.SDO* attribute), 270
- LegalService (*rdflib.namespace.SDO* attribute), 210
- legalStatus (*rdflib.namespace.SDO* attribute), 270
- LegalValueLevel (*rdflib.namespace.SDO* attribute), 211
- Legislation (*rdflib.namespace.SDO* attribute), 211
- legislationApplies (*rdflib.namespace.SDO* attribute), 270
- legislationChanges (*rdflib.namespace.SDO* attribute), 271
- legislationConsolidates (*rdflib.namespace.SDO* attribute), 271
- legislationDate (*rdflib.namespace.SDO* attribute), 271
- legislationDateVersion (*rdflib.namespace.SDO* attribute), 271
- legislationIdentifier (*rdflib.namespace.SDO* attribute), 271
- legislationJurisdiction (*rdflib.namespace.SDO* attribute), 271
- legislationLegalForce (*rdflib.namespace.SDO* attribute), 271
- legislationLegalValue (*rdflib.namespace.SDO* attribute), 271
- LegislationObject (*rdflib.namespace.SDO* attribute), 211
- legislationPassedBy (*rdflib.namespace.SDO* attribute), 271
- legislationResponsible (*rdflib.namespace.SDO* attribute), 271
- legislationTransposes (*rdflib.namespace.SDO* attribute), 271
- legislationType (*rdflib.namespace.SDO* attribute), 271
- LegislativeBuilding (*rdflib.namespace.SDO* attribute), 211
- leiCode (*rdflib.namespace.SDO* attribute), 271
- LeisureTimeActivity (*rdflib.namespace.SDO* attribute), 211
- lend (*rdflib.namespace.ODRL2* attribute), 167
- LendAction (*rdflib.namespace.SDO* attribute), 211
- lender (*rdflib.namespace.SDO* attribute), 271
- length (*rdflib.namespace.CSVW* attribute), 139
- length (*rdflib.namespace.XSD* attribute), 317
- lesser (*rdflib.namespace.SDO* attribute), 271
- lesserOrEqual (*rdflib.namespace.SDO* attribute), 271
- lessThan (*rdflib.namespace.SH* attribute), 302
- LessThanConstraintComponent (*rdflib.namespace.SH* attribute), 298
- lessThanOrEquals (*rdflib.namespace.SH* attribute), 302
- LessThanOrEqualsConstraintComponent (*rdflib.namespace.SH* attribute), 298
- letterer (*rdflib.namespace.SDO* attribute), 271
- li (*rdflib.plugins.parsers.RDFVOC.RDFVOC* attribute), 319
- li (*rdflib.plugins.parsers.rdfxml.BagID* attribute), 342
- li (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 342
- Library (*rdflib.namespace.BRICK* attribute), 104
- Library (*rdflib.namespace.SDO* attribute), 211
- LibrarySystem (*rdflib.namespace.SDO* attribute), 211
- license (*rdflib.namespace.DCTERMS* attribute), 148
- license (*rdflib.namespace.DOAP* attribute), 150
- license (*rdflib.namespace.ODRL2* attribute), 167
- license (*rdflib.namespace.SDO* attribute), 271
- LicenseDocument (*rdflib.namespace.DCTERMS* attribute), 146



- LifestyleModification (*rdflib.namespace.SDO* attribute), 211
- Ligament (*rdflib.namespace.SDO* attribute), 211
- Lighting (*rdflib.namespace.BRICK* attribute), 104
- Lighting\_Equipment (*rdflib.namespace.BRICK* attribute), 104
- Lighting\_System (*rdflib.namespace.BRICK* attribute), 104
- Lighting\_Zone (*rdflib.namespace.BRICK* attribute), 104
- LikeAction (*rdflib.namespace.SDO* attribute), 211
- Limit (*rdflib.namespace.BRICK* attribute), 104
- LimitedAvailability (*rdflib.namespace.SDO* attribute), 211
- LimitedByGuaranteeCharity (*rdflib.namespace.SDO* attribute), 211
- line (*rdflib.namespace.SDO* attribute), 271
- line (*rdflib.plugins.parsers.nquads.NQuadsParser* attribute), 338
- line (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser* attribute), 340
- lineTerminators (*rdflib.namespace.CSVW* attribute), 139
- LinguisticSystem (*rdflib.namespace.DCTERMS* attribute), 146
- linkedTo (*rdflib.namespace.ORG* attribute), 171
- linkPredicate (*rdflib.namespace.VOID* attribute), 314
- linkRelationship (*rdflib.namespace.SDO* attribute), 271
- LinkRole (*rdflib.namespace.SDO* attribute), 211
- links (*rdflib.parser.URLInputSource* attribute), 519
- Linkset (*rdflib.namespace.VOID* attribute), 313
- Liquid (*rdflib.namespace.BRICK* attribute), 104
- Liquid\_CO2 (*rdflib.namespace.BRICK* attribute), 104
- Liquid\_Detection\_Alarm (*rdflib.namespace.BRICK* attribute), 104
- LiquorStore (*rdflib.namespace.SDO* attribute), 211
- List (*rdflib.namespace.RDF* attribute), 187
- list (*rdflib.plugins.parsers.rdfxml.ElementHandler* attribute), 343
- list2set() (in module *rdflib.util*), 572
- list\_key (*rdflib.plugins.shared.jsonld.context.Context* property), 368
- list\_node\_element\_end() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 345
- ListenAction (*rdflib.namespace.SDO* attribute), 211
- ListItem (*rdflib.namespace.SDO* attribute), 211
- ListPrice (*rdflib.namespace.SDO* attribute), 211
- Literal (class in *rdflib*), 603
- Literal (class in *rdflib.term*), 557
- Literal (*rdflib.namespace.RDFS* attribute), 188
- Literal (*rdflib.namespace.SH* attribute), 298
- literal() (in module *rdflib.plugins.sparql.operators*), 407
- literal() (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser* method), 340
- literal\_element\_char() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 345
- literal\_element\_end() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 345
- literal\_element\_start() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 345
- LiteraryEvent (*rdflib.namespace.SDO* attribute), 211
- LiveAlbum (*rdflib.namespace.SDO* attribute), 211
- LiveBlogPosting (*rdflib.namespace.SDO* attribute), 211
- liveBlogUpdate (*rdflib.namespace.SDO* attribute), 271
- LivingWithHealthAspect (*rdflib.namespace.SDO* attribute), 211
- load() (*rdflib.plugins.shared.jsonld.context.Context* method), 368
- load() (*rdflib.plugins.sparql.sparql.QueryContext* method), 423
- Load\_Current\_Sensor (*rdflib.namespace.BRICK* attribute), 104
- Load\_Parameter (*rdflib.namespace.BRICK* attribute), 104
- Load\_Setpoint (*rdflib.namespace.BRICK* attribute), 105
- Load\_Shed\_Command (*rdflib.namespace.BRICK* attribute), 105
- Load\_Shed\_Differential\_Pressure\_Setpoint (*rdflib.namespace.BRICK* attribute), 105
- Load\_Shed\_Setpoint (*rdflib.namespace.BRICK* attribute), 105
- Load\_Shed\_Status (*rdflib.namespace.BRICK* attribute), 105
- loadBuf() (*rdflib.plugins.parsers.notation3.SinkParser* method), 330
- Loading\_Dock (*rdflib.namespace.BRICK* attribute), 105
- loads() (*rdflib.store.NodePickler* method), 547
- loadStream() (*rdflib.plugins.parsers.notation3.SinkParser* method), 330
- loanMortgageMandateAmount (*rdflib.namespace.SDO* attribute), 271
- LoanOrCredit (*rdflib.namespace.SDO* attribute), 211
- loanPaymentAmount (*rdflib.namespace.SDO* attribute), 271
- loanPaymentFrequency (*rdflib.namespace.SDO* attribute), 272
- loanRepaymentForm (*rdflib.namespace.SDO* attribute), 272
- loanTerm (*rdflib.namespace.SDO* attribute), 272
- loanType (*rdflib.namespace.SDO* attribute), 272

Lobby (*rdflib.namespace.BRICK* attribute), 105  
 LocalBusiness (*rdflib.namespace.SDO* attribute), 211  
 Locally\_On\_Off\_Status (*rdflib.namespace.BRICK* attribute), 105  
 Location (*rdflib.namespace.BRICK* attribute), 105  
 Location (*rdflib.namespace.DCTERMS* attribute), 146  
 location (*rdflib.namespace.DOAP* attribute), 150  
 location (*rdflib.namespace.ORG* attribute), 171  
 Location (*rdflib.namespace.PROV* attribute), 179  
 location (*rdflib.namespace.SDO* attribute), 272  
 location (*rdflib.namespace.WGS* attribute), 315  
 locationCreated (*rdflib.namespace.SDO* attribute), 272  
 LocationFeatureSpecification (*rdflib.namespace.SDO* attribute), 211  
 locationOf (*rdflib.namespace.PROV* attribute), 182  
 LocationPeriodOrJurisdiction (*rdflib.namespace.DCTERMS* attribute), 146  
 LockerDelivery (*rdflib.namespace.SDO* attribute), 211  
 Lockout\_Status (*rdflib.namespace.BRICK* attribute), 105  
 Lockout\_Temperature\_Differential\_Parameter (*rdflib.namespace.BRICK* attribute), 105  
 Locksmith (*rdflib.namespace.SDO* attribute), 212  
 LodgingBusiness (*rdflib.namespace.SDO* attribute), 212  
 LodgingReservation (*rdflib.namespace.SDO* attribute), 212  
 lodgingUnitDescription (*rdflib.namespace.SDO* attribute), 272  
 lodgingUnitType (*rdflib.namespace.SDO* attribute), 272  
 log (in module *rdflib.plugins.sparql.results.xmlresults*), 379  
 LogicalConstraint (*rdflib.namespace.ODRL2* attribute), 163  
 logo (*rdflib.namespace.FOAF* attribute), 152  
 logo (*rdflib.namespace.SDO* attribute), 272  
 long (*rdflib.namespace.WGS* attribute), 315  
 long (*rdflib.namespace.XSD* attribute), 317  
 longitude (*rdflib.namespace.BRICK* attribute), 136  
 longitude (*rdflib.namespace.SDO* attribute), 272  
 Longitudinal (*rdflib.namespace.SDO* attribute), 212  
 LongTurtleSerializer (class in *rdflib.plugins.serializers.longturtle*), 355  
 Loop (*rdflib.namespace.BRICK* attribute), 105  
 LoseAction (*rdflib.namespace.SDO* attribute), 212  
 loser (*rdflib.namespace.SDO* attribute), 272  
 Lounge (*rdflib.namespace.BRICK* attribute), 105  
 Louver (*rdflib.namespace.BRICK* attribute), 105  
 Low\_Freeze\_Protect\_Temperature\_Parameter (*rdflib.namespace.BRICK* attribute), 105  
 Low\_Humidity\_Alarm (*rdflib.namespace.BRICK* attribute), 105

Low\_Humidity\_Alarm\_Parameter (*rdflib.namespace.BRICK* attribute), 105  
 Low\_Outside\_Air\_Lockout\_Temperature\_Differential\_Parameter (*rdflib.namespace.BRICK* attribute), 105  
 Low\_Outside\_Air\_Temperature\_Enable\_Differential\_Sensor (*rdflib.namespace.BRICK* attribute), 105  
 Low\_Outside\_Air\_Temperature\_Enable\_Setpoint (*rdflib.namespace.BRICK* attribute), 105  
 Low\_Return\_Air\_Temperature\_Alarm (*rdflib.namespace.BRICK* attribute), 106  
 Low\_Suction\_Pressure\_Alarm (*rdflib.namespace.BRICK* attribute), 106  
 Low\_Temperature\_Alarm (*rdflib.namespace.BRICK* attribute), 106  
 Low\_Temperature\_Alarm\_Parameter (*rdflib.namespace.BRICK* attribute), 106  
 LowCalorieDiet (*rdflib.namespace.SDO* attribute), 212  
 Lowest\_Exhaust\_Air\_Static\_Pressure\_Sensor (*rdflib.namespace.BRICK* attribute), 106  
 LowFatDiet (*rdflib.namespace.SDO* attribute), 212  
 LowLactoseDiet (*rdflib.namespace.SDO* attribute), 212  
 lowPrice (*rdflib.namespace.SDO* attribute), 272  
 LowSaltDiet (*rdflib.namespace.SDO* attribute), 212  
 lt (*rdflib.namespace.ODRL2* attribute), 167  
 lteq (*rdflib.namespace.ODRL2* attribute), 167  
 ltr (*rdflib.namespace.CSVW* attribute), 139  
 Luminaire (*rdflib.namespace.BRICK* attribute), 106  
 Luminaire\_Driver (*rdflib.namespace.BRICK* attribute), 106  
 Luminance\_Alarm (*rdflib.namespace.BRICK* attribute), 106  
 Luminance\_Command (*rdflib.namespace.BRICK* attribute), 106  
 Luminance\_Sensor (*rdflib.namespace.BRICK* attribute), 106  
 Luminance\_Setpoint (*rdflib.namespace.BRICK* attribute), 106  
 Lung (*rdflib.namespace.SDO* attribute), 212  
 LymphaticVessel (*rdflib.namespace.SDO* attribute), 212  
 lyricist (*rdflib.namespace.SDO* attribute), 272  
 lyrics (*rdflib.namespace.SDO* attribute), 272

## M

made (*rdflib.namespace.FOAF* attribute), 152  
 madeActuation (*rdflib.namespace.SOSA* attribute), 307  
 madeByActuator (*rdflib.namespace.SOSA* attribute), 307  
 madeBySampler (*rdflib.namespace.SOSA* attribute), 307  
 madeBySensor (*rdflib.namespace.SOSA* attribute), 307  
 madeObservation (*rdflib.namespace.SOSA* attribute), 308  
 madeSampling (*rdflib.namespace.SOSA* attribute), 308  
 Mail\_Room (*rdflib.namespace.BRICK* attribute), 106

- `main()` (in module `examples.secure_with_audit`), 26
- `main()` (in module `examples.secure_with_urlopen`), 27
- `main()` (in module `rdflib.extras.cmdlineutils`), 49
- `main()` (in module `rdflib.tools.graphisomorphism`), 460
- `main()` (in module `rdflib.tools.rdf2dot`), 461
- `main()` (in module `rdflib.tools.rdfpipe`), 461
- `main()` (in module `rdflib.tools.rdfs2dot`), 461
- `mainContentOfPage` (`rdflib.namespace.SDO` attribute), 272
- `mainEntity` (`rdflib.namespace.SDO` attribute), 272
- `mainEntityOfPage` (`rdflib.namespace.SDO` attribute), 272
- `maintainer` (`rdflib.namespace.DOAP` attribute), 150
- `maintainer` (`rdflib.namespace.SDO` attribute), 272
- `Maintenance_Mode_Command` (`rdflib.namespace.BRICK` attribute), 106
- `Maintenance_Required_Alarm` (`rdflib.namespace.BRICK` attribute), 106
- `Majlis` (`rdflib.namespace.BRICK` attribute), 106
- `make_dn_file()` (in module `rdflib.tools.defined_namespace_creator`), 459
- `make_option_parser()` (in module `rdflib.tools.rdfpipe`), 461
- `maker` (`rdflib.namespace.FOAF` attribute), 152
- `makesOffer` (`rdflib.namespace.SDO` attribute), 272
- `makeStatement()` (`rdflib.plugins.parsers.notation3.RDFSink` method), 325
- `makeStatement()` (`rdflib.plugins.parsers.notation3.SinkParser` method), 330
- `Makeup_Air_Unit` (`rdflib.namespace.BRICK` attribute), 106
- `Makeup_Water` (`rdflib.namespace.BRICK` attribute), 106
- `Makeup_Water_Valve` (`rdflib.namespace.BRICK` attribute), 106
- `Male` (`rdflib.namespace.SDO` attribute), 212
- `MalformedClass`, 68
- `MalformedClassError`, 68
- `manchesterSyntax()` (in module `rdflib.extras.infixowl`), 72
- `Manual_Auto_Status` (`rdflib.namespace.BRICK` attribute), 107
- `manufacturer` (`rdflib.namespace.SDO` attribute), 272
- `Manuscript` (`rdflib.namespace.SDO` attribute), 212
- `Map` (`rdflib.namespace.SDO` attribute), 212
- `map` (`rdflib.namespace.SDO` attribute), 272
- `MapCategoryType` (`rdflib.namespace.SDO` attribute), 212
- `mappingRelation` (`rdflib.namespace.SKOS` attribute), 306
- `maps` (`rdflib.namespace.SDO` attribute), 272
- `mapType` (`rdflib.namespace.SDO` attribute), 272
- `marginOfError` (`rdflib.namespace.SDO` attribute), 272
- `MarryAction` (`rdflib.namespace.SDO` attribute), 212
- `Mass` (`rdflib.namespace.SDO` attribute), 212
- `Massage_Room` (`rdflib.namespace.BRICK` attribute), 107
- `masthead` (`rdflib.namespace.SDO` attribute), 272
- `material` (`rdflib.namespace.SDO` attribute), 272
- `materialExtent` (`rdflib.namespace.SDO` attribute), 272
- `mathExpression` (`rdflib.namespace.SDO` attribute), 273
- `MathSolver` (`rdflib.namespace.SDO` attribute), 212
- `MAU` (`rdflib.namespace.BRICK` attribute), 106
- `Max_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Air_Temperature_Setpoint` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Chilled_Water_Differential_Pressure_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Cooling_Discharge_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Cooling_Supply_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Discharge_Air_Static_Pressure_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Discharge_Air_Temperature_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Frequency_Command` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Heating_Discharge_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Heating_Supply_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Hot_Water_Differential_Pressure_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Load_Setpoint` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Occupied_Cooling_Discharge_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Occupied_Cooling_Supply_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 107
- `Max_Occupied_Heating_Discharge_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108
- `Max_Occupied_Heating_Supply_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108
- `Max_Position_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108
- `Max_Speed_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108
- `Max_Static_Pressure_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108
- `Max_Supply_Air_Static_Pressure_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108
- `Max_Temperature_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108
- `Max_Unoccupied_Cooling_Discharge_Air_Flow_Setpoint_Limit` (`rdflib.namespace.BRICK` attribute), 108



Max\_Unoccupied\_Cooling\_Supply\_Air\_Flow\_SetpointLimit (rdflib.namespace.BRICK attribute), 108  
 Max\_Unoccupied\_Heating\_Discharge\_Air\_Flow\_SetpointLimit (rdflib.namespace.BRICK attribute), 108  
 Max\_Unoccupied\_Heating\_Supply\_Air\_Flow\_SetpointLimit (rdflib.namespace.BRICK attribute), 108  
 Max\_Water\_Level\_Alarm (rdflib.namespace.BRICK attribute), 108  
 Max\_Water\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 108  
 maxCardinality (rdflib.extras.infixowl.Restriction property), 71  
 maxCardinality (rdflib.namespace.OWL attribute), 175  
 maxCount (rdflib.namespace.SH attribute), 302  
 MaxCountConstraintComponent (rdflib.namespace.SH attribute), 298  
 maxDepth (rdflib.plugins.serializers.turtle.RecursiveSerializer attribute), 361  
 maxExclusive (rdflib.namespace.CSVW attribute), 139  
 maxExclusive (rdflib.namespace.SH attribute), 302  
 maxExclusive (rdflib.namespace.XSD attribute), 317  
 MaxExclusiveConstraintComponent (rdflib.namespace.SH attribute), 298  
 Maximum (class in rdflib.plugins.sparql.aggregates), 384  
 maximumAttendeeCapacity (rdflib.namespace.SDO attribute), 273  
 MaximumDoseSchedule (rdflib.namespace.SDO attribute), 212  
 maximumEnrollment (rdflib.namespace.SDO attribute), 273  
 maximumIntake (rdflib.namespace.SDO attribute), 273  
 maximumPhysicalAttendeeCapacity (rdflib.namespace.SDO attribute), 273  
 maximumVirtualAttendeeCapacity (rdflib.namespace.SDO attribute), 273  
 maxInclusive (rdflib.namespace.CSVW attribute), 139  
 maxInclusive (rdflib.namespace.SH attribute), 302  
 maxInclusive (rdflib.namespace.XSD attribute), 317  
 MaxInclusiveConstraintComponent (rdflib.namespace.SH attribute), 298  
 maxLength (rdflib.namespace.CSVW attribute), 139  
 maxLength (rdflib.namespace.SH attribute), 302  
 maxLength (rdflib.namespace.XSD attribute), 317  
 MaxLengthConstraintComponent (rdflib.namespace.SH attribute), 298  
 maxPrice (rdflib.namespace.SDO attribute), 273  
 maxQualifiedCardinality (rdflib.namespace.OWL attribute), 175  
 maxValue (rdflib.namespace.SDO attribute), 273  
 MayTreatHealthAspect (rdflib.namespace.SDO attribute), 212  
 mbox (rdflib.namespace.FOAF attribute), 152  
 mbox\_sha1sum (rdflib.namespace.FOAF attribute), 152  
 MDF (rdflib.namespace.BRICK attribute), 106  
 mediaService (rdflib.namespace.SDO attribute), 273  
 Measurable (rdflib.namespace.BRICK attribute), 108  
 measurementUnit (rdflib.namespace.QB attribute), 186  
 measuredDimension (rdflib.namespace.QB attribute), 186  
 measuredModuleConversionEfficiency (rdflib.namespace.BRICK attribute), 136  
 measuredPowerOutput (rdflib.namespace.BRICK attribute), 136  
 measuredProperty (rdflib.namespace.SDO attribute), 273  
 measuredValue (rdflib.namespace.SDO attribute), 273  
 measurementTechnique (rdflib.namespace.SDO attribute), 273  
 MeasurementTypeEnumeration (rdflib.namespace.SDO attribute), 212  
 MeasureProperty (rdflib.namespace.QB attribute), 185  
 measures (rdflib.namespace.BRICK attribute), 136  
 measureType (rdflib.namespace.QB attribute), 186  
 Mechanical\_Room (rdflib.namespace.BRICK attribute), 108  
 mechanismOfAction (rdflib.namespace.SDO attribute), 273  
 media (rdflib.namespace.ODRL2 attribute), 168  
 Media\_Hot\_Desk (rdflib.namespace.BRICK attribute), 108  
 Media\_Production\_Room (rdflib.namespace.BRICK attribute), 109  
 Media\_Room (rdflib.namespace.BRICK attribute), 109  
 mediaAuthenticityCategory (rdflib.namespace.SDO attribute), 273  
 MediaGallery (rdflib.namespace.SDO attribute), 212  
 mediaItemAppearance (rdflib.namespace.SDO attribute), 273  
 MediaManipulationRatingEnumeration (rdflib.namespace.SDO attribute), 212  
 median (rdflib.namespace.SDO attribute), 273  
 MediaObject (rdflib.namespace.SDO attribute), 212  
 MediaReview (rdflib.namespace.SDO attribute), 212  
 MediaReviewItem (rdflib.namespace.SDO attribute), 212  
 MediaSubscription (rdflib.namespace.SDO attribute), 213  
 mediator (rdflib.namespace.DCTERMS attribute), 148  
 mediaType (rdflib.namespace.DCAT attribute), 144  
 MediaType (rdflib.namespace.DCTERMS attribute), 146  
 MediaTypeOrExtent (rdflib.namespace.DCTERMS attribute), 146  
 Medical\_Room (rdflib.namespace.BRICK attribute), 109  
 MedicalAudience (rdflib.namespace.SDO attribute), 213  
 medicalAudience (rdflib.namespace.SDO attribute), 273  
 MedicalAudienceType (rdflib.namespace.SDO attribute), 273

- tribute), 213
- MedicalBusiness (rdflib.namespace.SDO attribute), 213
- MedicalCause (rdflib.namespace.SDO attribute), 213
- MedicalClinic (rdflib.namespace.SDO attribute), 213
- MedicalCode (rdflib.namespace.SDO attribute), 213
- MedicalCondition (rdflib.namespace.SDO attribute), 213
- MedicalConditionStage (rdflib.namespace.SDO attribute), 213
- MedicalContraindication (rdflib.namespace.SDO attribute), 213
- MedicalDevice (rdflib.namespace.SDO attribute), 213
- MedicalDevicePurpose (rdflib.namespace.SDO attribute), 213
- MedicalEntity (rdflib.namespace.SDO attribute), 213
- MedicalEnumeration (rdflib.namespace.SDO attribute), 213
- MedicalEvidenceLevel (rdflib.namespace.SDO attribute), 213
- MedicalGuideline (rdflib.namespace.SDO attribute), 213
- MedicalGuidelineContraindication (rdflib.namespace.SDO attribute), 213
- MedicalGuidelineRecommendation (rdflib.namespace.SDO attribute), 213
- MedicalImagingTechnique (rdflib.namespace.SDO attribute), 213
- MedicalIndication (rdflib.namespace.SDO attribute), 213
- MedicalIntangible (rdflib.namespace.SDO attribute), 213
- MedicalObservationalStudy (rdflib.namespace.SDO attribute), 213
- MedicalObservationalStudyDesign (rdflib.namespace.SDO attribute), 214
- MedicalOrganization (rdflib.namespace.SDO attribute), 214
- MedicalProcedure (rdflib.namespace.SDO attribute), 214
- MedicalProcedureType (rdflib.namespace.SDO attribute), 214
- MedicalResearcher (rdflib.namespace.SDO attribute), 214
- MedicalRiskCalculator (rdflib.namespace.SDO attribute), 214
- MedicalRiskEstimator (rdflib.namespace.SDO attribute), 214
- MedicalRiskFactor (rdflib.namespace.SDO attribute), 214
- MedicalRiskScore (rdflib.namespace.SDO attribute), 214
- MedicalScholarlyArticle (rdflib.namespace.SDO attribute), 214
- MedicalSign (rdflib.namespace.SDO attribute), 214
- MedicalSignOrSymptom (rdflib.namespace.SDO attribute), 214
- MedicalSpecialty (rdflib.namespace.SDO attribute), 214
- medicalSpecialty (rdflib.namespace.SDO attribute), 273
- MedicalStudy (rdflib.namespace.SDO attribute), 214
- MedicalStudyStatus (rdflib.namespace.SDO attribute), 214
- MedicalSymptom (rdflib.namespace.SDO attribute), 214
- MedicalTest (rdflib.namespace.SDO attribute), 214
- MedicalTestPanel (rdflib.namespace.SDO attribute), 214
- MedicalTherapy (rdflib.namespace.SDO attribute), 214
- MedicalTrial (rdflib.namespace.SDO attribute), 214
- MedicalTrialDesign (rdflib.namespace.SDO attribute), 214
- MedicalWebPage (rdflib.namespace.SDO attribute), 215
- MedicineSystem (rdflib.namespace.SDO attribute), 215
- medicineSystem (rdflib.namespace.SDO attribute), 273
- medium (rdflib.namespace.DCTERMS attribute), 148
- Medium\_Temperature\_Hot\_Water\_Differential\_Pressure\_Load\_Shedding (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Differential\_Pressure\_Load\_Shedding (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Differential\_Pressure\_Load\_Shedding (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Differential\_Pressure\_Sensor (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Differential\_Pressure\_Setpoint (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Discharge\_Temperature\_High\_Reset (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Discharge\_Temperature\_Low\_Reset (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Return\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Supply\_Temperature\_High\_Reset (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Supply\_Temperature\_Load\_Shedding (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Supply\_Temperature\_Load\_Shedding (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Supply\_Temperature\_Low\_Reset (rdflib.namespace.BRICK attribute), 109
- Medium\_Temperature\_Hot\_Water\_Supply\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 110
- MeetingRoom (rdflib.namespace.SDO attribute), 215
- meetsEmissionStandard (rdflib.namespace.SDO attribute), 273
- member (rdflib.namespace.FOAF attribute), 152
- member (rdflib.namespace.ORG attribute), 172
- member (rdflib.namespace.RDFS attribute), 188

- `member` (*rdflib.namespace.SDO* attribute), 273
- `member` (*rdflib.namespace.SKOS* attribute), 306
- `memberDuring` (*rdflib.namespace.ORG* attribute), 172
- `memberList` (*rdflib.namespace.SKOS* attribute), 306
- `memberOf` (*rdflib.namespace.DCAM* attribute), 143
- `memberOf` (*rdflib.namespace.ORG* attribute), 172
- `memberOf` (*rdflib.namespace.SDO* attribute), 273
- `members` (*rdflib.namespace.OWL* attribute), 175
- `members` (*rdflib.namespace.SDO* attribute), 273
- `Membership` (*rdflib.namespace.ORG* attribute), 171
- `membershipClass` (*rdflib.namespace.FOAF* attribute), 152
- `membershipNumber` (*rdflib.namespace.SDO* attribute), 273
- `membershipPointsEarned` (*rdflib.namespace.SDO* attribute), 274
- `Memory` (class in *rdflib.plugins.stores.memory*), 436
- `memoryRequirements` (*rdflib.namespace.SDO* attribute), 274
- `MensClothingStore` (*rdflib.namespace.SDO* attribute), 215
- `mentionOf` (*rdflib.namespace.PROV* attribute), 182
- `mentions` (*rdflib.namespace.SDO* attribute), 274
- `Menu` (*rdflib.namespace.SDO* attribute), 215
- `menu` (*rdflib.namespace.SDO* attribute), 274
- `menuAddOn` (*rdflib.namespace.SDO* attribute), 274
- `MenuItem` (*rdflib.namespace.SDO* attribute), 215
- `MenuSection` (*rdflib.namespace.SDO* attribute), 215
- `merchant` (*rdflib.namespace.SDO* attribute), 274
- `merchantReturnDays` (*rdflib.namespace.SDO* attribute), 274
- `MerchantReturnEnumeration` (*rdflib.namespace.SDO* attribute), 215
- `MerchantReturnFiniteReturnWindow` (*rdflib.namespace.SDO* attribute), 215
- `merchantReturnLink` (*rdflib.namespace.SDO* attribute), 274
- `MerchantReturnNotPermitted` (*rdflib.namespace.SDO* attribute), 215
- `MerchantReturnPolicy` (*rdflib.namespace.SDO* attribute), 215
- `MerchantReturnPolicySeasonalOverride` (*rdflib.namespace.SDO* attribute), 215
- `MerchantReturnUnlimitedWindow` (*rdflib.namespace.SDO* attribute), 215
- `MerchantReturnUnspecified` (*rdflib.namespace.SDO* attribute), 215
- `merge()` (*rdflib.plugins.sparql.sparql.FrozenBindings* method), 418
- `merge()` (*rdflib.plugins.sparql.sparql.FrozenDict* method), 420
- `MESH` (*rdflib.namespace.DCTERMS* attribute), 146
- `Message` (*rdflib.namespace.SDO* attribute), 215
- `message` (*rdflib.namespace.SH* attribute), 302
- `message` (*rdflib.plugins.parsers.notation3.BadSyntax* property), 322
- `messageAttachment` (*rdflib.namespace.SDO* attribute), 274
- `Meter` (*rdflib.namespace.BRICK* attribute), 110
- `meteredTime` (*rdflib.namespace.ODRL2* attribute), 168
- `Methane_Level_Sensor` (*rdflib.namespace.BRICK* attribute), 110
- `method` (*rdflib.plugins.stores.sparqlconnector.SPARQLConnector* property), 444
- `MethodOfAccrual` (*rdflib.namespace.DCTERMS* attribute), 146
- `MethodOfInstruction` (*rdflib.namespace.DCTERMS* attribute), 146
- `MiddleSchool` (*rdflib.namespace.SDO* attribute), 215
- `Midwifery` (*rdflib.namespace.SDO* attribute), 215
- `mileageFromOdometer` (*rdflib.namespace.SDO* attribute), 274
- `Min_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Chilled_Water_Differential_Pressure_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Cooling_Discharge_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Cooling_Supply_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Discharge_Air_Static_Pressure_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Discharge_Air_Temperature_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Fresh_Air_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Heating_Discharge_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Heating_Supply_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Hot_Water_Differential_Pressure_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Occupied_Cooling_Discharge_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Occupied_Cooling_Supply_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 110
- `Min_Occupied_Heating_Discharge_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 111
- `Min_Occupied_Heating_Supply_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 111
- `Min_Outside_Air_Flow_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 111
- `Min_Position_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 111
- `Min_Speed_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 111

- flib.namespace.BRICK attribute*), 111
- Min\_Static\_Pressure\_Setpoint\_Limit (rd-  
*flib.namespace.BRICK attribute*), 111
- Min\_Supply\_Air\_Static\_Pressure\_Setpoint\_Limit  
(rdflib.namespace.BRICK attribute), 111
- Min\_Temperature\_Setpoint\_Limit (rd-  
*flib.namespace.BRICK attribute*), 111
- Min\_Unoccupied\_Cooling\_Discharge\_Air\_Flow\_Setpoint\_Limit  
(rdflib.namespace.BRICK attribute), 111
- Min\_Unoccupied\_Cooling\_Supply\_Air\_Flow\_Setpoint\_Limit  
(rdflib.namespace.BRICK attribute), 111
- Min\_Unoccupied\_Heating\_Discharge\_Air\_Flow\_Setpoint\_Limit  
(rdflib.namespace.BRICK attribute), 111
- Min\_Unoccupied\_Heating\_Supply\_Air\_Flow\_Setpoint\_Limit  
(rdflib.namespace.BRICK attribute), 111
- Min\_Water\_Level\_Alarm (rdflib.namespace.BRICK at-  
tribute), 111
- Min\_Water\_Temperature\_Setpoint (rd-  
*flib.namespace.BRICK attribute*), 111
- minCardinality (rdflib.extras.infixowl.Restriction  
property), 71
- minCardinality (rdflib.namespace.OWL attribute), 175
- minCount (rdflib.namespace.SH attribute), 302
- MinCountConstraintComponent (rdflib.namespace.SH  
attribute), 299
- minExclusive (rdflib.namespace.CSVW attribute), 139
- minExclusive (rdflib.namespace.SH attribute), 302
- minExclusive (rdflib.namespace.XSD attribute), 317
- MinExclusiveConstraintComponent (rd-  
*flib.namespace.SH attribute*), 299
- Minimum (class in rdflib.plugins.sparql.aggregates), 384
- MinimumAdvertisedPrice (rdflib.namespace.SDO at-  
tribute), 215
- minimumPaymentDue (rdflib.namespace.SDO attribute),  
274
- minInclusive (rdflib.namespace.CSVW attribute), 139
- minInclusive (rdflib.namespace.SH attribute), 302
- minInclusive (rdflib.namespace.XSD attribute), 317
- MinInclusiveConstraintComponent (rd-  
*flib.namespace.SH attribute*), 299
- minLength (rdflib.namespace.CSVW attribute), 139
- minLength (rdflib.namespace.SH attribute), 302
- minLength (rdflib.namespace.XSD attribute), 317
- MinLengthConstraintComponent (rd-  
*flib.namespace.SH attribute*), 299
- minPrice (rdflib.namespace.SDO attribute), 274
- minQualifiedCardinality (rdflib.namespace.OWL  
attribute), 175
- Minus() (in module rdflib.plugins.sparql.algebra), 387
- minute (rdflib.namespace.TIME attribute), 312
- minute (rdflib.namespace.XSD attribute), 317
- minutes (rdflib.namespace.TIME attribute), 312
- minValue (rdflib.namespace.SDO attribute), 274
- MisconceptionsHealthAspect (rd-  
*flib.namespace.SDO attribute*), 215
- missionCoveragePrioritiesPolicy (rd-  
*flib.namespace.SDO attribute*), 274
- Mixed\_Air (rdflib.namespace.BRICK attribute), 111
- Mixed\_Air\_Filter (rdflib.namespace.BRICK at-  
tribute), 111
- Mixed\_Air\_Flow\_Sensor (rdflib.namespace.BRICK at-  
tribute), 112
- Mixed\_Air\_Humidity\_Sensor (rd-  
*flib.namespace.BRICK attribute*), 112
- Mixed\_Air\_Humidity\_Setpoint (rd-  
*flib.namespace.BRICK attribute*), 112
- Mixed\_Air\_Temperature\_Sensor (rd-  
*flib.namespace.BRICK attribute*), 112
- Mixed\_Air\_Temperature\_Setpoint (rd-  
*flib.namespace.BRICK attribute*), 112
- Mixed\_Damper (rdflib.namespace.BRICK attribute), 112
- MixedEventAttendanceMode (rdflib.namespace.SDO  
attribute), 215
- MixtapeAlbum (rdflib.namespace.SDO attribute), 215
- MobileApplication (rdflib.namespace.SDO attribute),  
215
- MobilePhoneStore (rdflib.namespace.SDO attribute),  
215
- Mode\_Command (rdflib.namespace.BRICK attribute), 112
- Mode\_Status (rdflib.namespace.BRICK attribute), 112
- model (rdflib.namespace.SDO attribute), 274
- modelDate (rdflib.namespace.SDO attribute), 274
- ModificationException, 508
- modified (rdflib.namespace.DCTERMS attribute), 148
- modifiedTime (rdflib.namespace.SDO attribute), 274
- modify (rdflib.namespace.ODRL2 attribute), 168
- Modify (rdflib.namespace.PROV attribute), 179
- module
  - examples.berkeleydb\_example, 23
  - examples.conjunctive\_graphs, 22
  - examples.custom\_datatype, 22
  - examples.custom\_eval, 22
  - examples.foafpaths, 22
  - examples.prepared\_query, 23
  - examples.resource\_example, 23
  - examples.secure\_with\_audit, 26
  - examples.secure\_with\_urlopen, 26
  - examples.slice, 24
  - examples.smushing, 24
  - examples.sparql\_query\_example, 24
  - examples.sparql\_update\_example, 25
  - examples.sparqlstore\_example, 25
  - examples.swap\_primer, 25
  - examples.transitive, 25
  - rdflib, 574
  - rdflib.collection, 461
  - rdflib.compare, 466



- rdflib.compat, 470
- rdflib.container, 470
- rdflib.events, 473
- rdflib.exceptions, 475
- rdflib.extras, 72
- rdflib.extras.cmdlineutils, 49
- rdflib.extras.describer, 49
- rdflib.extras.external\_graph\_libs, 53
- rdflib.extras.infixowl, 58
- rdflib.graph, 476
- rdflib.namespace, 72
- rdflib.parser, 516
- rdflib.paths, 519
- rdflib.plugin, 528
- rdflib.plugins, 458
- rdflib.plugins.parsers, 353
- rdflib.plugins.parsers.hext, 319
- rdflib.plugins.parsers.jsonld, 320
- rdflib.plugins.parsers.notation3, 321
- rdflib.plugins.parsers.nquads, 337
- rdflib.plugins.parsers.ntriples, 338
- rdflib.plugins.parsers.RDFVOC, 319
- rdflib.plugins.parsers.rdfxml, 342
- rdflib.plugins.parsers.trig, 348
- rdflib.plugins.parsers.trix, 350
- rdflib.plugins.serializers, 364
- rdflib.plugins.serializers.hext, 353
- rdflib.plugins.serializers.jsonld, 354
- rdflib.plugins.serializers.longturtle, 355
- rdflib.plugins.serializers.n3, 356
- rdflib.plugins.serializers.nquads, 357
- rdflib.plugins.serializers.nt, 358
- rdflib.plugins.serializers.rdfxml, 358
- rdflib.plugins.serializers.trig, 360
- rdflib.plugins.serializers.trix, 360
- rdflib.plugins.serializers.turtle, 361
- rdflib.plugins.serializers.xmlwriter, 363
- rdflib.plugins.shared, 371
- rdflib.plugins.shared.jsonld, 371
- rdflib.plugins.shared.jsonld.context, 364
- rdflib.plugins.shared.jsonld.errors, 370
- rdflib.plugins.shared.jsonld.keys, 370
- rdflib.plugins.shared.jsonld.util, 370
- rdflib.plugins.sparql, 428
- rdflib.plugins.sparql.aggregates, 379
- rdflib.plugins.sparql.algebra, 386
- rdflib.plugins.sparql.datatypes, 392
- rdflib.plugins.sparql.evaluate, 392
- rdflib.plugins.sparql.evalutils, 396
- rdflib.plugins.sparql.operators, 396
- rdflib.plugins.sparql.parser, 408
- rdflib.plugins.sparql.parserutils, 409
- rdflib.plugins.sparql.processor, 414
- rdflib.plugins.sparql.results, 379
- rdflib.plugins.sparql.results.csvresults, 371
- rdflib.plugins.sparql.results.graph, 373
- rdflib.plugins.sparql.results.jsonresults, 373
- rdflib.plugins.sparql.results.rdfresults, 375
- rdflib.plugins.sparql.results.tsvresults, 375
- rdflib.plugins.sparql.results.txtresults, 376
- rdflib.plugins.sparql.results.xmlresults, 376
- rdflib.plugins.sparql.sparql, 416
- rdflib.plugins.sparql.update, 425
- rdflib.plugins.stores, 458
- rdflib.plugins.stores.auditabile, 429
- rdflib.plugins.stores.berkeleydb, 432
- rdflib.plugins.stores.concurrent, 435
- rdflib.plugins.stores.memory, 436
- rdflib.plugins.stores.regexmatching, 441
- rdflib.plugins.stores.sparqlconnector, 443
- rdflib.plugins.stores.sparqlstore, 445
- rdflib.query, 531
- rdflib.resource, 538
- rdflib.serializer, 545
- rdflib.store, 546
- rdflib.term, 553
- rdflib.tools, 461
- rdflib.tools.chunk\_serializer, 458
- rdflib.tools.csv2rdf, 459
- rdflib.tools.defined\_namespace\_creator, 459
- rdflib.tools.graphisomorphism, 460
- rdflib.tools.rdf2dot, 461
- rdflib.tools.rdfpipe, 461
- rdflib.tools.rdfs2dot, 461
- rdflib.util, 570
- rdflib.void, 574
- module (*rdflib.namespace.DOAP attribute*), 150
- MolecularEntity (*rdflib.namespace.SDO attribute*), 216
- molecularFormula (*rdflib.namespace.SDO attribute*), 274
- molecularWeight (*rdflib.namespace.SDO attribute*), 274
- Monday (*rdflib.namespace.SDO attribute*), 216
- Monday (*rdflib.namespace.TIME attribute*), 309
- MonetaryAmount (*rdflib.namespace.SDO attribute*), 216
- MonetaryAmountDistribution (*rdflib.namespace.SDO attribute*), 216
- MonetaryGrant (*rdflib.namespace.SDO attribute*), 216



- MoneyTransfer (rdflib.namespace.SDO attribute), 216  
 monoisotopicMolecularWeight (rdflib.namespace.SDO attribute), 274  
 month (rdflib.namespace.TIME attribute), 312  
 month (rdflib.namespace.XSD attribute), 317  
 monthlyMinimumRepaymentAmount (rdflib.namespace.SDO attribute), 274  
 MonthOfYear (rdflib.namespace.TIME attribute), 309  
 monthOfYear (rdflib.namespace.TIME attribute), 312  
 months (rdflib.namespace.TIME attribute), 312  
 monthsOfExperience (rdflib.namespace.SDO attribute), 274  
 more\_than() (in module rdflib.util), 573  
 MortgageLoan (rdflib.namespace.SDO attribute), 216  
 Mosque (rdflib.namespace.SDO attribute), 216  
 Motel (rdflib.namespace.SDO attribute), 216  
 Motion\_Sensor (rdflib.namespace.BRICK attribute), 112  
 Motor (rdflib.namespace.BRICK attribute), 112  
 Motor\_Control\_Center (rdflib.namespace.BRICK attribute), 112  
 Motor\_Current\_Sensor (rdflib.namespace.BRICK attribute), 112  
 Motor\_Direction\_Status (rdflib.namespace.BRICK attribute), 112  
 Motor\_On\_Off\_Status (rdflib.namespace.BRICK attribute), 112  
 Motor\_Speed\_Sensor (rdflib.namespace.BRICK attribute), 112  
 Motor\_Torque\_Sensor (rdflib.namespace.BRICK attribute), 112  
 Motorcycle (rdflib.namespace.SDO attribute), 216  
 MotorcycleDealer (rdflib.namespace.SDO attribute), 216  
 MotorcycleRepair (rdflib.namespace.SDO attribute), 216  
 MotorizedBicycle (rdflib.namespace.SDO attribute), 216  
 Mountain (rdflib.namespace.SDO attribute), 216  
 move (rdflib.namespace.ODRL2 attribute), 168  
 MoveAction (rdflib.namespace.SDO attribute), 216  
 Movie (rdflib.namespace.SDO attribute), 216  
 MovieClip (rdflib.namespace.SDO attribute), 216  
 MovieRentalStore (rdflib.namespace.SDO attribute), 216  
 MovieSeries (rdflib.namespace.SDO attribute), 216  
 MovieTheater (rdflib.namespace.SDO attribute), 216  
 MovingCompany (rdflib.namespace.SDO attribute), 216  
 MovingImage (rdflib.namespace.DCMITYPE attribute), 145  
 mpn (rdflib.namespace.SDO attribute), 274  
 MRI (rdflib.namespace.SDO attribute), 212  
 msnChatID (rdflib.namespace.FOAF attribute), 153  
 MSRP (rdflib.namespace.SDO attribute), 212  
 mul\_path() (in module rdflib.paths), 528  
 MulPath (class in rdflib.paths), 523  
 MulticellularParasite (rdflib.namespace.SDO attribute), 216  
 MultiCenterTrial (rdflib.namespace.SDO attribute), 216  
 MultiPlayer (rdflib.namespace.SDO attribute), 216  
 multipleValues (rdflib.namespace.SDO attribute), 275  
 MultiplicativeExpression() (in module rdflib.plugins.sparql.operators), 404  
 Muscle (rdflib.namespace.SDO attribute), 216  
 muscleAction (rdflib.namespace.SDO attribute), 275  
 Musculoskeletal (rdflib.namespace.SDO attribute), 216  
 MusculoskeletalExam (rdflib.namespace.SDO attribute), 217  
 Museum (rdflib.namespace.SDO attribute), 217  
 MusicAlbum (rdflib.namespace.SDO attribute), 217  
 MusicAlbumProductionType (rdflib.namespace.SDO attribute), 217  
 MusicAlbumReleaseType (rdflib.namespace.SDO attribute), 217  
 musicalKey (rdflib.namespace.SDO attribute), 275  
 musicArrangement (rdflib.namespace.SDO attribute), 275  
 musicBy (rdflib.namespace.SDO attribute), 275  
 MusicComposition (rdflib.namespace.SDO attribute), 217  
 musicCompositionForm (rdflib.namespace.SDO attribute), 275  
 MusicEvent (rdflib.namespace.SDO attribute), 217  
 MusicGroup (rdflib.namespace.SDO attribute), 217  
 musicGroupMember (rdflib.namespace.SDO attribute), 275  
 MusicPlaylist (rdflib.namespace.SDO attribute), 217  
 MusicRecording (rdflib.namespace.SDO attribute), 217  
 MusicRelease (rdflib.namespace.SDO attribute), 217  
 musicReleaseFormat (rdflib.namespace.SDO attribute), 275  
 MusicReleaseFormatType (rdflib.namespace.SDO attribute), 217  
 MusicStore (rdflib.namespace.SDO attribute), 217  
 MusicVenue (rdflib.namespace.SDO attribute), 217  
 MusicVideoObject (rdflib.namespace.SDO attribute), 217  
 myersBriggs (rdflib.namespace.FOAF attribute), 153
- ## N
- n (rdflib.namespace.PROV attribute), 182  
 n3() (rdflib.BNode method), 576  
 n3() (rdflib.collection.Collection method), 465  
 n3() (rdflib.container.Container method), 473  
 n3() (rdflib.Graph method), 594  
 n3() (rdflib.graph.Graph method), 499

- `n3()` (*rdflib.graph.QuotedGraph* method), 509
- `n3()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 512
- `n3()` (*rdflib.Literal* method), 611
- `n3()` (*rdflib.paths.AlternativePath* method), 522
- `n3()` (*rdflib.paths.InvPath* method), 523
- `n3()` (*rdflib.paths.MulPath* method), 524
- `n3()` (*rdflib.paths.NegatedPath* method), 524
- `n3()` (*rdflib.paths.SequencePath* method), 527
- `n3()` (*rdflib.term.BNode* method), 554
- `n3()` (*rdflib.term.Literal* method), 565
- `n3()` (*rdflib.term.URIRef* method), 569
- `n3()` (*rdflib.term.Variable* method), 569
- `n3()` (*rdflib.URIRef* method), 617
- `n3()` (*rdflib.Variable* method), 618
- `N3Parser` (class in *rdflib.plugins.parsers.notation3*), 323
- `N3Serializer` (class in *rdflib.plugins.serializers.n3*), 356
- `naics` (*rdflib.namespace.SDO* attribute), 275
- `NailSalon` (*rdflib.namespace.SDO* attribute), 217
- `name` (*rdflib.namespace.CSVW* attribute), 139
- `name` (*rdflib.namespace.DOAP* attribute), 150
- `name` (*rdflib.namespace.FOAF* attribute), 153
- `name` (*rdflib.namespace.SDO* attribute), 275
- `name` (*rdflib.namespace.SH* attribute), 302
- `Name` (*rdflib.namespace.XSD* attribute), 315
- `name` (*rdflib.plugins.shared.jsonld.context.Term* attribute), 370
- `NamedIndividual` (*rdflib.namespace.OWL* attribute), 173
- `namedPosition` (*rdflib.namespace.SDO* attribute), 275
- `Namespace` (class in *rdflib*), 613
- `Namespace` (class in *rdflib.namespace*), 156
- `namespace` (*rdflib.namespace.SH* attribute), 302
- `namespace()` (*rdflib.plugins.stores.auditable.AuditableStore* method), 430
- `namespace()` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 434
- `namespace()` (*rdflib.plugins.stores.memory.Memory* method), 437
- `namespace()` (*rdflib.plugins.stores.memory.SimpleMemory* method), 440
- `namespace()` (*rdflib.plugins.stores.regexmatching.REGEXMatching* method), 442
- `namespace()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 448
- `namespace()` (*rdflib.store.Store* method), 550
- `namespace_manager` (*rdflib.Graph* property), 594
- `namespace_manager` (*rdflib.graph.Graph* property), 499
- `NamespaceManager` (class in *rdflib.namespace*), 158
- `namespaces()` (*rdflib.Graph* method), 594
- `namespaces()` (*rdflib.graph.Graph* method), 499
- `namespaces()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 512
- `namespaces()` (*rdflib.namespace.NamespaceManager* method), 162
- `namespaces()` (*rdflib.plugins.serializers.xmlwriter.XMLWriter* method), 363
- `namespaces()` (*rdflib.plugins.stores.auditable.AuditableStore* method), 431
- `namespaces()` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 434
- `namespaces()` (*rdflib.plugins.stores.memory.Memory* method), 437
- `namespaces()` (*rdflib.plugins.stores.memory.SimpleMemory* method), 440
- `namespaces()` (*rdflib.plugins.stores.regexmatching.REGEXMatching* method), 442
- `namespaces()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 448
- `namespaces()` (*rdflib.store.Store* method), 550
- `narrower` (*rdflib.namespace.SKOS* attribute), 306
- `narrowerTransitive` (*rdflib.namespace.SKOS* attribute), 306
- `narrowMatch` (*rdflib.namespace.SKOS* attribute), 306
- `nationality` (*rdflib.namespace.SDO* attribute), 275
- `Natural_Gas` (*rdflib.namespace.BRICK* attribute), 112
- `Natural_Gas_Boiler` (*rdflib.namespace.BRICK* attribute), 112
- `naturalProgression` (*rdflib.namespace.SDO* attribute), 275
- `NCName` (*rdflib.namespace.XSD* attribute), 315
- `Neck` (*rdflib.namespace.SDO* attribute), 217
- `neg()` (in module *rdflib.plugins.sparql.parser*), 408
- `neg_path()` (in module *rdflib.paths*), 528
- `NegatedPath` (class in *rdflib.paths*), 524
- `negativeInteger` (*rdflib.namespace.XSD* attribute), 317
- `negativeNotes` (*rdflib.namespace.SDO* attribute), 275
- `NegativePropertyAssertion` (*rdflib.namespace.OWL* attribute), 173
- `neq` (*rdflib.namespace.ODRL2* attribute), 168
- `neq()` (*rdflib.Literal* method), 612
- `neq()` (*rdflib.term.Identifier* method), 557
- `neq()` (*rdflib.term.Literal* method), 566
- `Nerve` (*rdflib.namespace.SDO* attribute), 217
- `nerve` (*rdflib.namespace.SDO* attribute), 275
- `nerveMotor` (*rdflib.namespace.SDO* attribute), 275
- `netArea` (*rdflib.namespace.BRICK* attribute), 136
- `Network_Video_Recorder` (*rdflib.namespace.BRICK* attribute), 113
- `netWorth` (*rdflib.namespace.SDO* attribute), 275
- `Neuro` (*rdflib.namespace.SDO* attribute), 217
- `Neurologic` (*rdflib.namespace.SDO* attribute), 217
- `newBlankNode()` (*rdflib.plugins.parsers.notation3.Formula* method), 323
- `newBlankNode()` (*rdflib.plugins.parsers.notation3.RDFSink* method), 325

- NewCondition (rdflib.namespace.SDO attribute), 217  
 newFormula() (rdflib.plugins.parsers.notation3.RDFSink method), 325  
 newGraph() (rdflib.plugins.parsers.notation3.RDFSink method), 325  
 newList() (rdflib.plugins.parsers.notation3.RDFSink method), 325  
 newLiteral() (rdflib.plugins.parsers.notation3.RDFSink method), 325  
 NewsArticle (rdflib.namespace.SDO attribute), 217  
 newSet() (rdflib.plugins.parsers.notation3.RDFSink method), 325  
 NewsMediaOrganization (rdflib.namespace.SDO attribute), 217  
 Newspaper (rdflib.namespace.SDO attribute), 217  
 newsUpdatesAndGuidelines (rdflib.namespace.SDO attribute), 275  
 newSymbol() (rdflib.plugins.parsers.notation3.RDFSink method), 326  
 newUniversal() (rdflib.plugins.parsers.notation3.Formula method), 323  
 next (rdflib.plugins.parsers.rdfxml.RDFXMLHandler property), 345  
 next\_li() (rdflib.plugins.parsers.rdfxml.BagID method), 342  
 next\_li() (rdflib.plugins.parsers.rdfxml.ElementHandler method), 343  
 nextItem (rdflib.namespace.SDO attribute), 275  
 nextPolicy (rdflib.namespace.ODRL2 attribute), 168  
 NGO (rdflib.namespace.SDO attribute), 217  
 nick (rdflib.namespace.FOAF attribute), 153  
 NightClub (rdflib.namespace.SDO attribute), 218  
 nil (rdflib.namespace.RDF attribute), 188  
 NLM (rdflib.namespace.DCTERMS attribute), 146  
 NLNonprofitType (rdflib.namespace.SDO attribute), 217  
 NMTOKEN (rdflib.namespace.XSD attribute), 315  
 NMTOKENS (rdflib.namespace.XSD attribute), 315  
 NO2\_Level\_Sensor (rdflib.namespace.BRICK attribute), 112  
 No\_Water\_Alarm (rdflib.namespace.BRICK attribute), 113  
 noBylinesPolicy (rdflib.namespace.SDO attribute), 275  
 Node (class in rdflib.term), 566  
 node (rdflib.namespace.SH attribute), 302  
 node() (rdflib.plugins.parsers.notation3.SinkParser method), 330  
 node\_element\_end() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 345  
 node\_element\_start() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 345  
 node\_pickler (rdflib.store.Store property), 550  
 NodeConstraintComponent (rdflib.namespace.SH attribute), 299  
 nodeID (rdflib.plugins.parsers.RDFVOC.RDFVOC attribute), 319  
 nodeid() (rdflib.plugins.parsers.ntriples.W3CNTriplesParser method), 340  
 NodeKind (rdflib.namespace.SH attribute), 299  
 nodeKind (rdflib.namespace.SH attribute), 303  
 NodeKindConstraintComponent (rdflib.namespace.SH attribute), 299  
 nodeOrLiteral() (rdflib.plugins.parsers.notation3.SinkParser method), 331  
 NodePickler (class in rdflib.store), 546  
 nodes (rdflib.namespace.SH attribute), 303  
 NodeShape (rdflib.namespace.SH attribute), 299  
 nodeValidator (rdflib.namespace.SH attribute), 303  
 NoElementException, 473  
 nominalPosition (rdflib.namespace.TIME attribute), 312  
 Noncondensing\_Natural\_Gas\_Boiler (rdflib.namespace.BRICK attribute), 113  
 nonEqual (rdflib.namespace.SDO attribute), 275  
 NoninvasiveProcedure (rdflib.namespace.SDO attribute), 218  
 nonNegativeInteger (rdflib.namespace.XSD attribute), 317  
 nonPositiveInteger (rdflib.namespace.XSD attribute), 317  
 Nonprofit501a (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c1 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c10 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c11 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c12 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c13 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c14 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c15 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c16 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c17 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c18 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c19 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c2 (rdflib.namespace.SDO attribute), 218  
 Nonprofit501c20 (rdflib.namespace.SDO attribute), 218

- 218
- Nonprofit501c21 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c22 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c23 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c24 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c25 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c26 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c27 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c28 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c3 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c4 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c5 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c6 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c7 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c8 (*rdflib.namespace.SDO* attribute), 218
- Nonprofit501c9 (*rdflib.namespace.SDO* attribute), 219
- Nonprofit501d (*rdflib.namespace.SDO* attribute), 219
- Nonprofit501e (*rdflib.namespace.SDO* attribute), 219
- Nonprofit501f (*rdflib.namespace.SDO* attribute), 219
- Nonprofit501k (*rdflib.namespace.SDO* attribute), 219
- Nonprofit501n (*rdflib.namespace.SDO* attribute), 219
- Nonprofit501q (*rdflib.namespace.SDO* attribute), 219
- Nonprofit527 (*rdflib.namespace.SDO* attribute), 219
- NonprofitANBI (*rdflib.namespace.SDO* attribute), 219
- NonprofitSBBi (*rdflib.namespace.SDO* attribute), 219
- nonprofitStatus (*rdflib.namespace.SDO* attribute), 275
- NonprofitType (*rdflib.namespace.SDO* attribute), 219
- nonProprietaryName (*rdflib.namespace.SDO* attribute), 275
- norm\_url() (in module *rdflib.plugins.shared.jsonld.util*), 370
- normalise() (*rdflib.plugins.parsers.notation3.RDFSink* method), 326
- normalize() (*rdflib.Literal* method), 612
- normalize() (*rdflib.term.Literal* method), 566
- NORMALIZE\_LITERALS (in module *rdflib*), 613
- normalizedString (*rdflib.namespace.XSD* attribute), 317
- normalizeUri() (*rdflib.namespace.NamespaceManager* method), 162
- normalRange (*rdflib.namespace.SDO* attribute), 275
- Nose (*rdflib.namespace.SDO* attribute), 219
- not\_() (in module *rdflib.plugins.sparql.operators*), 407
- Notary (*rdflib.namespace.SDO* attribute), 219
- notation (*rdflib.namespace.SKOS* attribute), 306
- NOTATION (*rdflib.namespace.XSD* attribute), 315
- NotBoundError, 420
- NotConstraintComponent (*rdflib.namespace.SH* attribute), 299
- note (*rdflib.namespace.CSVW* attribute), 139
- note (*rdflib.namespace.SKOS* attribute), 306
- NoteDigitalDocument (*rdflib.namespace.SDO* attribute), 219
- Nothing (*rdflib.namespace.OWL* attribute), 173
- NotInForce (*rdflib.namespace.SDO* attribute), 219
- NotYetRecruiting (*rdflib.namespace.SDO* attribute), 219
- now (*rdflib.plugins.sparql.sparql.FrozenBindings* property), 418
- now (*rdflib.plugins.sparql.sparql.QueryContext* property), 424
- NQuadsParser (class in *rdflib.plugins.parsers.nquads*), 337
- NQuadsSerializer (class in *rdflib.plugins.serializers.nquads*), 357
- nsBindings (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* attribute), 454
- nsn (*rdflib.namespace.SDO* attribute), 275
- NTGraphSink (class in *rdflib.plugins.parsers.ntriples*), 339
- NTParser (class in *rdflib.plugins.parsers.ntriples*), 339
- NTSerializer (class in *rdflib.plugins.serializers.nt*), 358
- null (*rdflib.namespace.CSVW* attribute), 139
- numAdults (*rdflib.namespace.SDO* attribute), 275
- Number (*rdflib.namespace.SDO* attribute), 219
- number (*rdflib.plugins.parsers.notation3.Formula* attribute), 323
- numberedPosition (*rdflib.namespace.SDO* attribute), 277
- numberOfAccommodationUnits (*rdflib.namespace.SDO* attribute), 276
- numberOfAirbags (*rdflib.namespace.SDO* attribute), 276
- numberOfAvailableAccommodationUnits (*rdflib.namespace.SDO* attribute), 276
- numberOfAxles (*rdflib.namespace.SDO* attribute), 276
- numberOfBathroomsTotal (*rdflib.namespace.SDO* attribute), 276
- numberOfBedrooms (*rdflib.namespace.SDO* attribute), 276
- numberOfBeds (*rdflib.namespace.SDO* attribute), 276
- numberOfCredits (*rdflib.namespace.SDO* attribute), 276
- numberOfDoors (*rdflib.namespace.SDO* attribute), 276
- numberOfEmployees (*rdflib.namespace.SDO* attribute), 276
- numberOfEpisodes (*rdflib.namespace.SDO* attribute), 276
- numberOfForwardGears (*rdflib.namespace.SDO*



- attribute*), 276
- `numberOfFullBathrooms` (*rdflib.namespace.SDO attribute*), 276
- `numberOfItems` (*rdflib.namespace.SDO attribute*), 276
- `numberOfLoanPayments` (*rdflib.namespace.SDO attribute*), 276
- `numberOfPages` (*rdflib.namespace.SDO attribute*), 276
- `numberOfPartialBathrooms` (*rdflib.namespace.SDO attribute*), 276
- `numberOfPlayers` (*rdflib.namespace.SDO attribute*), 276
- `numberOfPreviousOwners` (*rdflib.namespace.SDO attribute*), 276
- `numberOfRooms` (*rdflib.namespace.SDO attribute*), 276
- `numberOfSeasons` (*rdflib.namespace.SDO attribute*), 276
- `numChildren` (*rdflib.namespace.SDO attribute*), 276
- `numConstraints` (*rdflib.namespace.SDO attribute*), 276
- `numeric` (*rdflib.namespace.XSD attribute*), 317
- `numeric()` (in module *rdflib.plugins.sparql.operators*), 407
- `numericDuration` (*rdflib.namespace.TIME attribute*), 312
- `NumericFormat` (*rdflib.namespace.CSVW attribute*), 138
- `numericPosition` (*rdflib.namespace.TIME attribute*), 312
- `numTracks` (*rdflib.namespace.SDO attribute*), 276
- `Nursing` (*rdflib.namespace.SDO attribute*), 219
- `nutrition` (*rdflib.namespace.SDO attribute*), 277
- `NutritionInformation` (*rdflib.namespace.SDO attribute*), 219
- `NVR` (*rdflib.namespace.BRICK attribute*), 112
- O**
- `object` (*rdflib.namespace.RDF attribute*), 188
- `object` (*rdflib.namespace.SDO attribute*), 277
- `object` (*rdflib.namespace.SH attribute*), 303
- `object` (*rdflib.plugins.parsers.rdfxml.ElementHandler attribute*), 343
- `object()` (*rdflib.plugins.parsers.notation3.SinkParser method*), 331
- `object()` (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser method*), 340
- `objectList()` (*rdflib.plugins.parsers.notation3.SinkParser method*), 331
- `objectList()` (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer method*), 356
- `objectList()` (*rdflib.plugins.serializers.turtle.TurtleSerializer method*), 362
- `ObjectProperty` (*rdflib.namespace.OWL attribute*), 173
- `objects()` (*rdflib.Graph method*), 594
- `objects()` (*rdflib.graph.Graph method*), 499
- `objects()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore method*), 448
- `objects()` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore method*), 454
- `objects()` (*rdflib.resource.Resource method*), 545
- `objectsTarget` (*rdflib.namespace.VOID attribute*), 314
- `obligation` (*rdflib.namespace.ODRL2 attribute*), 168
- `ObservableProperty` (*rdflib.namespace.SOSA attribute*), 307
- `Observation` (*rdflib.namespace.QB attribute*), 186
- `observation` (*rdflib.namespace.QB attribute*), 186
- `Observation` (*rdflib.namespace.SDO attribute*), 219
- `Observation` (*rdflib.namespace.SOSA attribute*), 307
- `Observational` (*rdflib.namespace.SDO attribute*), 219
- `observationDate` (*rdflib.namespace.SDO attribute*), 277
- `ObservationGroup` (*rdflib.namespace.QB attribute*), 186
- `observationGroup` (*rdflib.namespace.QB attribute*), 186
- `observedNode` (*rdflib.namespace.SDO attribute*), 277
- `observedProperty` (*rdflib.namespace.SOSA attribute*), 308
- `observes` (*rdflib.namespace.SOSA attribute*), 308
- `Obstetric` (*rdflib.namespace.SDO attribute*), 219
- `obtainConsent` (*rdflib.namespace.ODRL2 attribute*), 168
- `occupancy` (*rdflib.namespace.SDO attribute*), 277
- `Occupancy_Command` (*rdflib.namespace.BRICK attribute*), 113
- `Occupancy_Sensor` (*rdflib.namespace.BRICK attribute*), 113
- `Occupancy_Status` (*rdflib.namespace.BRICK attribute*), 113
- `Occupation` (*rdflib.namespace.SDO attribute*), 219
- `OccupationalActivity` (*rdflib.namespace.SDO attribute*), 219
- `occupationalCategory` (*rdflib.namespace.SDO attribute*), 277
- `occupationalCredentialAwarded` (*rdflib.namespace.SDO attribute*), 277
- `OccupationalExperienceRequirements` (*rdflib.namespace.SDO attribute*), 219
- `OccupationalTherapy` (*rdflib.namespace.SDO attribute*), 219
- `occupationLocation` (*rdflib.namespace.SDO attribute*), 277
- `Occupied_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK attribute*), 113
- `Occupied_Cooling_Discharge_Air_Flow_Setpoint` (*rdflib.namespace.BRICK attribute*), 113
- `Occupied_Cooling_Supply_Air_Flow_Setpoint` (*rdflib.namespace.BRICK attribute*), 113
- `Occupied_Cooling_Temperature_Deadband_Setpoint` (*rdflib.namespace.BRICK attribute*), 113
- `Occupied_Discharge_Air_Flow_Setpoint` (*rd-*

- flib.namespace.BRICK attribute*), 113
- Occupied\_Discharge\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 113
- Occupied\_Heating\_Discharge\_Air\_Flow\_Setpoint (*rdflib.namespace.BRICK attribute*), 113
- Occupied\_Heating\_Supply\_Air\_Flow\_Setpoint (*rdflib.namespace.BRICK attribute*), 113
- Occupied\_Heating\_Temperature\_Deadband\_Setpoint (*rdflib.namespace.BRICK attribute*), 113
- Occupied\_Mode\_Status (*rdflib.namespace.BRICK attribute*), 113
- Occupied\_Return\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 113
- Occupied\_Room\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 113
- Occupied\_Supply\_Air\_Flow\_Setpoint (*rdflib.namespace.BRICK attribute*), 114
- Occupied\_Supply\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 114
- Occupied\_Zone\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 114
- OceanBodyOfWater (*rdflib.namespace.SDO attribute*), 220
- ODRL2 (class in *rdflib.namespace*), 163
- Off\_Command (*rdflib.namespace.BRICK attribute*), 114
- Off\_Status (*rdflib.namespace.BRICK attribute*), 114
- Offer (*rdflib.namespace.ODRL2 attribute*), 163
- Offer (*rdflib.namespace.SDO attribute*), 220
- OfferCatalog (*rdflib.namespace.SDO attribute*), 220
- offerCount (*rdflib.namespace.SDO attribute*), 277
- offeredBy (*rdflib.namespace.SDO attribute*), 277
- OfferForLease (*rdflib.namespace.SDO attribute*), 220
- OfferForPurchase (*rdflib.namespace.SDO attribute*), 220
- OfferItemCondition (*rdflib.namespace.SDO attribute*), 220
- offers (*rdflib.namespace.SDO attribute*), 277
- OfferShippingDetails (*rdflib.namespace.SDO attribute*), 220
- offersPrescriptionByMail (*rdflib.namespace.SDO attribute*), 277
- Office (*rdflib.namespace.BRICK attribute*), 114
- Office\_Kitchen (*rdflib.namespace.BRICK attribute*), 114
- OfficeEquipmentStore (*rdflib.namespace.SDO attribute*), 220
- OfficialLegalValue (*rdflib.namespace.SDO attribute*), 220
- OfflineEventAttendanceMode (*rdflib.namespace.SDO attribute*), 220
- OfflinePermanently (*rdflib.namespace.SDO attribute*), 220
- OfflineTemporarily (*rdflib.namespace.SDO attribute*), 220
- Oil (*rdflib.namespace.BRICK attribute*), 114
- On\_Command (*rdflib.namespace.BRICK attribute*), 114
- On\_Off\_Command (*rdflib.namespace.BRICK attribute*), 114
- On\_Off\_Status (*rdflib.namespace.BRICK attribute*), 114
- On\_Status (*rdflib.namespace.BRICK attribute*), 114
- On\_Timer\_Sensor (*rdflib.namespace.BRICK attribute*), 114
- onClass (*rdflib.namespace.OWL attribute*), 175
- Oncologic (*rdflib.namespace.SDO attribute*), 220
- onDataRange (*rdflib.namespace.OWL attribute*), 175
- onDatatype (*rdflib.namespace.OWL attribute*), 175
- OnDemandEvent (*rdflib.namespace.SDO attribute*), 220
- oneOf (*rdflib.namespace.OWL attribute*), 175
- oneOrMorePath (*rdflib.namespace.SH attribute*), 303
- OneTimePayments (*rdflib.namespace.SDO attribute*), 220
- Online (*rdflib.namespace.SDO attribute*), 220
- OnlineAccount (*rdflib.namespace.FOAF attribute*), 151
- OnlineChatAccount (*rdflib.namespace.FOAF attribute*), 151
- OnlineEcommerceAccount (*rdflib.namespace.FOAF attribute*), 151
- OnlineEventAttendanceMode (*rdflib.namespace.SDO attribute*), 220
- OnlineFull (*rdflib.namespace.SDO attribute*), 220
- OnlineGamingAccount (*rdflib.namespace.FOAF attribute*), 151
- OnlineOnly (*rdflib.namespace.SDO attribute*), 220
- onProperties (*rdflib.namespace.OWL attribute*), 175
- onProperty (*rdflib.extras.infixowl.Restriction property*), 71
- onProperty (*rdflib.namespace.OWL attribute*), 175
- OnSitePickup (*rdflib.namespace.SDO attribute*), 220
- Ontology (class in *rdflib.extras.infixowl*), 69
- Ontology (*rdflib.namespace.OWL attribute*), 173
- OntologyProperty (*rdflib.namespace.OWL attribute*), 173
- open() (*rdflib.Graph method*), 594
- open() (*rdflib.graph.Graph method*), 499
- open() (*rdflib.graph.ReadOnlyGraphAggregate method*), 512
- open() (*rdflib.plugins.stores.auditable.AuditableStore method*), 431
- open() (*rdflib.plugins.stores.berkeleydb.BerkeleyDB method*), 434
- open() (*rdflib.plugins.stores.regexmatching.REGEXMatching method*), 442
- open() (*rdflib.plugins.stores.sparqlstore.SPARQLStore method*), 448
- open() (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore method*), 454
- open() (*rdflib.store.Store method*), 550

Open\_Close\_Status (*rdflib.namespace.BRICK* attribute), 114  
 Open\_Heating\_Valve\_Outside\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 114  
 Open\_Office (*rdflib.namespace.BRICK* attribute), 114  
 openId (*rdflib.namespace.FOAF* attribute), 153  
 openingHours (*rdflib.namespace.SDO* attribute), 277  
 OpeningHoursSpecification (*rdflib.namespace.SDO* attribute), 220  
 openingHoursSpecification (*rdflib.namespace.SDO* attribute), 277  
 opens (*rdflib.namespace.SDO* attribute), 277  
 openSearchDescription (*rdflib.namespace.VOID* attribute), 314  
 OpenTrial (*rdflib.namespace.SDO* attribute), 220  
 operand (*rdflib.namespace.ODRL2* attribute), 168  
 Operating\_Mode\_Status (*rdflib.namespace.BRICK* attribute), 114  
 operatingSystem (*rdflib.namespace.SDO* attribute), 277  
 operationalStage (*rdflib.namespace.BRICK* attribute), 137  
 operationalStageCount (*rdflib.namespace.BRICK* attribute), 137  
 Operator (*rdflib.namespace.ODRL2* attribute), 163  
 operator (*rdflib.namespace.ODRL2* attribute), 168  
 OpinionNewsArticle (*rdflib.namespace.SDO* attribute), 220  
 opponent (*rdflib.namespace.SDO* attribute), 277  
 Optician (*rdflib.namespace.SDO* attribute), 221  
 option (*rdflib.namespace.SDO* attribute), 277  
 optional (*rdflib.namespace.SH* attribute), 303  
 Optometric (*rdflib.namespace.SDO* attribute), 221  
 OrConstraintComponent (*rdflib.namespace.SH* attribute), 299  
 order (*rdflib.namespace.PROV* attribute), 182  
 order (*rdflib.namespace.QB* attribute), 186  
 Order (*rdflib.namespace.SDO* attribute), 221  
 order (*rdflib.namespace.SH* attribute), 303  
 OrderAction (*rdflib.namespace.SDO* attribute), 221  
 OrderBy() (in module *rdflib.plugins.sparql.algebra*), 387  
 OrderCancelled (*rdflib.namespace.SDO* attribute), 221  
 orderDate (*rdflib.namespace.SDO* attribute), 277  
 OrderDelivered (*rdflib.namespace.SDO* attribute), 221  
 orderDelivery (*rdflib.namespace.SDO* attribute), 277  
 ordered (*rdflib.namespace.CSVW* attribute), 139  
 ordered (*rdflib.namespace.XSD* attribute), 317  
 OrderedCollection (*rdflib.namespace.SKOS* attribute), 305  
 orderedItem (*rdflib.namespace.SDO* attribute), 277  
 OrderInTransit (*rdflib.namespace.SDO* attribute), 221  
 OrderItem (*rdflib.namespace.SDO* attribute), 221  
 orderItemNumber (*rdflib.namespace.SDO* attribute), 277  
 orderItemStatus (*rdflib.namespace.SDO* attribute), 277  
 orderNumber (*rdflib.namespace.SDO* attribute), 277  
 OrderPaymentDue (*rdflib.namespace.SDO* attribute), 221  
 OrderPickupAvailable (*rdflib.namespace.SDO* attribute), 221  
 OrderProblem (*rdflib.namespace.SDO* attribute), 221  
 OrderProcessing (*rdflib.namespace.SDO* attribute), 221  
 orderQuantity (*rdflib.namespace.SDO* attribute), 277  
 OrderReturned (*rdflib.namespace.SDO* attribute), 221  
 OrderStatus (*rdflib.namespace.SDO* attribute), 221  
 orderStatus (*rdflib.namespace.SDO* attribute), 277  
 orderSubjects() (*rdflib.plugins.serializers.turtle.RecursiveSerializer* method), 361  
 ORG (class in *rdflib.namespace*), 170  
 Organization (*rdflib.namespace.FOAF* attribute), 151  
 Organization (*rdflib.namespace.ORG* attribute), 171  
 organization (*rdflib.namespace.ORG* attribute), 172  
 Organization (*rdflib.namespace.PROV* attribute), 179  
 Organization (*rdflib.namespace.SDO* attribute), 221  
 OrganizationalCollaboration (*rdflib.namespace.ORG* attribute), 171  
 OrganizationalUnit (*rdflib.namespace.ORG* attribute), 171  
 OrganizationRole (*rdflib.namespace.SDO* attribute), 221  
 OrganizeAction (*rdflib.namespace.SDO* attribute), 221  
 organizer (*rdflib.namespace.SDO* attribute), 278  
 originAddress (*rdflib.namespace.SDO* attribute), 278  
 OriginalMediaContent (*rdflib.namespace.SDO* attribute), 221  
 originalMediaContextDescription (*rdflib.namespace.SDO* attribute), 278  
 originalMediaLink (*rdflib.namespace.SDO* attribute), 278  
 originalOrganization (*rdflib.namespace.ORG* attribute), 172  
 OriginalShippingFees (*rdflib.namespace.SDO* attribute), 221  
 originatesFrom (*rdflib.namespace.SDO* attribute), 278  
 os (*rdflib.namespace.DOAP* attribute), 150  
 Osteopathic (*rdflib.namespace.SDO* attribute), 221  
 OTC (*rdflib.namespace.SDO* attribute), 219  
 Otologyngologic (*rdflib.namespace.SDO* attribute), 221  
 Outdoor\_Area (*rdflib.namespace.BRICK* attribute), 114  
 OutletStore (*rdflib.namespace.SDO* attribute), 221  
 OutOfStock (*rdflib.namespace.SDO* attribute), 221  
 output (*rdflib.namespace.ODRL2* attribute), 168  
 Output (*rdflib.namespace.SSN* attribute), 308  
 Output\_Frequency\_Sensor (*rdflib.namespace.BRICK*



- attribute*), 114
  - Output\_Voltage\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_CO2\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_CO\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Dewpoint\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Enthalpy\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Flow\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Flow\_Setpoint (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Grains\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Humidity\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Humidity\_Setpoint (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Lockout\_Temperature\_Differential\_Parameter (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Lockout\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Temperature\_Enable\_Differential\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Temperature\_High\_Reset\_Setpoint (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Temperature\_Low\_Reset\_Setpoint (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Temperature\_Sensor (*rdflib.namespace.BRICK attribute*), 115
  - Outside\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 116
  - Outside\_Air\_Wet\_Bulb\_Temperature\_Sensor (*rdflib.namespace.BRICK attribute*), 116
  - Outside\_Damper (*rdflib.namespace.BRICK attribute*), 116
  - Outside\_Face\_Surface\_Temperature\_Sensor (*rdflib.namespace.BRICK attribute*), 116
  - Outside\_Face\_Surface\_Temperature\_Setpoint (*rdflib.namespace.BRICK attribute*), 116
  - Outside\_Illuminance\_Sensor (*rdflib.namespace.BRICK attribute*), 116
  - overdosage (*rdflib.namespace.SDO attribute*), 278
  - Overload\_Alarm (*rdflib.namespace.BRICK attribute*), 116
  - Overridden\_Off\_Status (*rdflib.namespace.BRICK attribute*), 116
  - Overridden\_On\_Status (*rdflib.namespace.BRICK attribute*), 116
  - Overridden\_Status (*rdflib.namespace.BRICK attribute*), 116
  - Override\_Command (*rdflib.namespace.BRICK attribute*), 116
  - OverviewHealthAspect (*rdflib.namespace.SDO attribute*), 221
  - OWL (*class in rdflib.namespace*), 172
  - OWL RDFListProxy (*class in rdflib.extras.infixowl*), 68
  - ownedFrom (*rdflib.namespace.SDO attribute*), 278
  - ownedThrough (*rdflib.namespace.SDO attribute*), 278
  - ownershipFundingInfo (*rdflib.namespace.SDO attribute*), 278
  - OwnershipInfo (*rdflib.namespace.SDO attribute*), 221
  - owns (*rdflib.namespace.SDO attribute*), 278
  - Ozone\_Level\_Sensor (*rdflib.namespace.BRICK attribute*), 116
- ## P
- p\_clause() (*rdflib.plugins.serializers.n3.N3Serializer method*), 357
  - p\_default() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer method*), 356
  - p\_default() (*rdflib.plugins.serializers.turtle.TurtleSerializer method*), 362
  - p\_squared() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer method*), 356
  - p\_squared() (*rdflib.plugins.serializers.turtle.TurtleSerializer method*), 362
  - packageFormat (*rdflib.namespace.DCAT attribute*), 144
  - page (*rdflib.namespace.FOAF attribute*), 153
  - pageEnd (*rdflib.namespace.SDO attribute*), 278
  - pageStart (*rdflib.namespace.SDO attribute*), 278
  - pagination (*rdflib.namespace.SDO attribute*), 278
  - PaidLeave (*rdflib.namespace.SDO attribute*), 221
  - PaintAction (*rdflib.namespace.SDO attribute*), 222
  - Painting (*rdflib.namespace.SDO attribute*), 222
  - pairEntity (*rdflib.namespace.PROV attribute*), 182
  - pairKey (*rdflib.namespace.PROV attribute*), 182
  - PalliativeProcedure (*rdflib.namespace.SDO attribute*), 222
  - panelArea (*rdflib.namespace.BRICK attribute*), 137
  - Paperback (*rdflib.namespace.SDO attribute*), 222
  - Param (*class in rdflib.plugins.sparql.parserutils*), 411
  - Parameter (*rdflib.namespace.BRICK attribute*), 117
  - Parameter (*rdflib.namespace.SH attribute*), 299
  - parameter (*rdflib.namespace.SH attribute*), 303
  - Parameterizable (*rdflib.namespace.SH attribute*), 299
  - ParamList (*class in rdflib.plugins.sparql.parserutils*), 412
  - ParamValue (*class in rdflib.plugins.sparql.parserutils*), 412
  - ParcelDelivery (*rdflib.namespace.SDO attribute*), 222
  - ParcelService (*rdflib.namespace.SDO attribute*), 222
  - parent (*rdflib.namespace.SDO attribute*), 278



- `parent` (`rdflib.plugins.parsers.rdfxml.RDFXMLHandler` property), 346
- `ParentalSupport` (`rdflib.namespace.SDO` attribute), 222
- `ParentAudience` (`rdflib.namespace.SDO` attribute), 222
- `parentChildProperty` (`rdflib.namespace.QB` attribute), 186
- `parentItem` (`rdflib.namespace.SDO` attribute), 278
- `parentOrganization` (`rdflib.namespace.SDO` attribute), 278
- `parents` (`rdflib.extras.infixowl.Class` property), 64
- `parents` (`rdflib.namespace.SDO` attribute), 278
- `parentService` (`rdflib.namespace.SDO` attribute), 278
- `parentTaxon` (`rdflib.namespace.SDO` attribute), 278
- `Park` (`rdflib.namespace.SDO` attribute), 222
- `Parking_Level` (`rdflib.namespace.BRICK` attribute), 117
- `Parking_Space` (`rdflib.namespace.BRICK` attribute), 117
- `Parking_Structure` (`rdflib.namespace.BRICK` attribute), 117
- `ParkingFacility` (`rdflib.namespace.SDO` attribute), 222
- `ParkingMap` (`rdflib.namespace.SDO` attribute), 222
- `parse()` (`rdflib.ConjunctiveGraph` method), 578
- `parse()` (`rdflib.Dataset` method), 584
- `parse()` (`rdflib.Graph` method), 595
- `parse()` (`rdflib.graph.ConjunctiveGraph` method), 484
- `parse()` (`rdflib.graph.Dataset` method), 489
- `parse()` (`rdflib.graph.Graph` method), 500
- `parse()` (`rdflib.graph.ReadOnlyGraphAggregate` method), 512
- `parse()` (`rdflib.parser.Parser` method), 516
- `parse()` (`rdflib.plugins.parsers.hexl.HexTuplesParser` method), 320
- `parse()` (`rdflib.plugins.parsers.jsonld.JsonLDParser` method), 321
- `parse()` (`rdflib.plugins.parsers.notation3.N3Parser` method), 323
- `parse()` (`rdflib.plugins.parsers.notation3.TurtleParser` method), 335
- `parse()` (`rdflib.plugins.parsers.nquads.NQuadsParser` method), 338
- `parse()` (`rdflib.plugins.parsers.ntriples.NTParser` class method), 339
- `parse()` (`rdflib.plugins.parsers.ntriples.W3CNTriplesParser` method), 341
- `parse()` (`rdflib.plugins.parsers.rdfxml.RDFXMLParser` method), 348
- `parse()` (`rdflib.plugins.parsers.trig.TrigParser` method), 348
- `parse()` (`rdflib.plugins.parsers.trix.TriXParser` method), 353
- `parse()` (`rdflib.plugins.sparql.results.csvresults.CSVResultParser` method), 372
- `parse()` (`rdflib.plugins.sparql.results.graph.GraphResultParser` method), 373
- `parse()` (`rdflib.plugins.sparql.results.jsonresults.JSONResultParser` method), 373
- `parse()` (`rdflib.plugins.sparql.results.rdfresults.RDFResultParser` method), 375
- `parse()` (`rdflib.plugins.sparql.results.tsvresults.TSVResultParser` method), 376
- `parse()` (`rdflib.plugins.sparql.results.xmlresults.XMLResultParser` method), 378
- `parse()` (`rdflib.query.Result` static method), 533
- `parse()` (`rdflib.query.ResultParser` method), 535
- `parse_and_serialize()` (in module `rdflib.tools.rdfpipe`), 461
- `parse_date_time()` (in module `rdflib.util`), 573
- `parseAction` (`rdflib.plugins.sparql.parserutils.ParamList` attribute), 412
- `parseJsonTerm()` (in module `rdflib.plugins.sparql.results.jsonresults`), 374
- `parseline()` (`rdflib.plugins.parsers.nquads.NQuadsParser` method), 338
- `parseline()` (`rdflib.plugins.parsers.ntriples.W3CNTriplesParser` method), 341
- `parseQuery()` (in module `rdflib.plugins.sparql.parser`), 409
- `Parser` (class in `rdflib.parser`), 516
- `ParserError`, 475
- `parseRow()` (`rdflib.plugins.sparql.results.csvresults.CSVResultParser` method), 372
- `parsestring()` (`rdflib.plugins.parsers.ntriples.W3CNTriplesParser` method), 341
- `parseTerm()` (in module `rdflib.plugins.sparql.results.xmlresults`), 379
- `parseType` (`rdflib.plugins.parsers.RDFVOC.RDFVOC` attribute), 319
- `parseUpdate()` (in module `rdflib.plugins.sparql.parser`), 409
- `PartiallyInForce` (`rdflib.namespace.SDO` attribute), 222
- `participant` (`rdflib.namespace.SDO` attribute), 278
- `Particulate_Matter_Sensor` (`rdflib.namespace.BRICK` attribute), 117
- `partOf` (`rdflib.namespace.ODRL2` attribute), 168
- `partOfEpisode` (`rdflib.namespace.SDO` attribute), 278
- `partOfInvoice` (`rdflib.namespace.SDO` attribute), 278
- `partOfOrder` (`rdflib.namespace.SDO` attribute), 278
- `partOfSeason` (`rdflib.namespace.SDO` attribute), 278
- `partOfSeries` (`rdflib.namespace.SDO` attribute), 278
- `partOfSystem` (`rdflib.namespace.SDO` attribute), 278
- `partOfTrip` (`rdflib.namespace.SDO` attribute), 278
- `partOfTVSeries` (`rdflib.namespace.SDO` attribute), 278
- `Party` (`rdflib.namespace.ODRL2` attribute), 163
- `PartyCollection` (`rdflib.namespace.ODRL2` attribute), 163

- 164
- PartyScope (*rdflib.namespace.ODRL2* attribute), 164
- partySize (*rdflib.namespace.SDO* attribute), 279
- passengerPriorityStatus (*rdflib.namespace.SDO* attribute), 279
- passengerSequenceNumber (*rdflib.namespace.SDO* attribute), 279
- Passive\_Chilled\_Beam (*rdflib.namespace.BRICK* attribute), 117
- pastProject (*rdflib.namespace.FOAF* attribute), 153
- Path (class in *rdflib.paths*), 524
- path (*rdflib.namespace.SH* attribute), 303
- path() (*rdflib.plugins.parsers.notation3.SinkParser* method), 331
- path() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356
- path() (*rdflib.plugins.serializers.n3.N3Serializer* method), 357
- path() (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 362
- path\_alternative() (in module *rdflib.paths*), 528
- path\_sequence() (in module *rdflib.paths*), 528
- PathList (class in *rdflib.paths*), 526
- Pathology (*rdflib.namespace.SDO* attribute), 222
- PathologyTest (*rdflib.namespace.SDO* attribute), 222
- pathophysiology (*rdflib.namespace.SDO* attribute), 279
- Patient (*rdflib.namespace.SDO* attribute), 222
- PatientExperienceHealthAspect (*rdflib.namespace.SDO* attribute), 222
- pattern (*rdflib.namespace.CSVW* attribute), 139
- pattern (*rdflib.namespace.SDO* attribute), 279
- pattern (*rdflib.namespace.SH* attribute), 303
- pattern (*rdflib.namespace.XSD* attribute), 317
- PatternConstraintComponent (*rdflib.namespace.SH* attribute), 299
- PAU (*rdflib.namespace.BRICK* attribute), 116
- PawnShop (*rdflib.namespace.SDO* attribute), 222
- pay (*rdflib.namespace.ODRL2* attribute), 168
- PayAction (*rdflib.namespace.SDO* attribute), 222
- payAmount (*rdflib.namespace.ODRL2* attribute), 168
- payeeParty (*rdflib.namespace.ODRL2* attribute), 168
- payload (*rdflib.namespace.SDO* attribute), 279
- paymentAccepted (*rdflib.namespace.SDO* attribute), 279
- PaymentAutomaticallyApplied (*rdflib.namespace.SDO* attribute), 222
- PaymentCard (*rdflib.namespace.SDO* attribute), 222
- PaymentChargeSpecification (*rdflib.namespace.SDO* attribute), 222
- PaymentComplete (*rdflib.namespace.SDO* attribute), 222
- PaymentDeclined (*rdflib.namespace.SDO* attribute), 222
- PaymentDue (*rdflib.namespace.SDO* attribute), 222
- paymentDue (*rdflib.namespace.SDO* attribute), 279
- paymentDueDate (*rdflib.namespace.SDO* attribute), 279
- PaymentMethod (*rdflib.namespace.SDO* attribute), 222
- paymentMethod (*rdflib.namespace.SDO* attribute), 279
- paymentMethodId (*rdflib.namespace.SDO* attribute), 279
- PaymentPastDue (*rdflib.namespace.SDO* attribute), 222
- PaymentService (*rdflib.namespace.SDO* attribute), 222
- paymentStatus (*rdflib.namespace.SDO* attribute), 279
- PaymentStatusType (*rdflib.namespace.SDO* attribute), 222
- paymentUrl (*rdflib.namespace.SDO* attribute), 279
- Peak\_Power\_Demand\_Sensor (*rdflib.namespace.BRICK* attribute), 117
- Pediatric (*rdflib.namespace.SDO* attribute), 223
- peek() (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser* method), 341
- penciler (*rdflib.namespace.SDO* attribute), 279
- PeopleAudience (*rdflib.namespace.SDO* attribute), 223
- percentage (*rdflib.namespace.ODRL2* attribute), 168
- percentile10 (*rdflib.namespace.SDO* attribute), 279
- percentile25 (*rdflib.namespace.SDO* attribute), 279
- percentile75 (*rdflib.namespace.SDO* attribute), 279
- percentile90 (*rdflib.namespace.SDO* attribute), 279
- PercutaneousProcedure (*rdflib.namespace.SDO* attribute), 223
- PerformAction (*rdflib.namespace.SDO* attribute), 223
- PerformanceRole (*rdflib.namespace.SDO* attribute), 223
- performer (*rdflib.namespace.SDO* attribute), 279
- performerIn (*rdflib.namespace.SDO* attribute), 279
- performers (*rdflib.namespace.SDO* attribute), 279
- PerformingArtsTheater (*rdflib.namespace.SDO* attribute), 223
- PerformingGroup (*rdflib.namespace.SDO* attribute), 223
- performTime (*rdflib.namespace.SDO* attribute), 279
- Period (*rdflib.namespace.DCTERMS* attribute), 146
- Periodical (*rdflib.namespace.SDO* attribute), 223
- PeriodOfTime (*rdflib.namespace.DCTERMS* attribute), 146
- perm (*rdflib.namespace.ODRL2* attribute), 168
- Permission (*rdflib.namespace.ODRL2* attribute), 164
- permission (*rdflib.namespace.ODRL2* attribute), 168
- permissions (*rdflib.namespace.SDO* attribute), 279
- permissionType (*rdflib.namespace.SDO* attribute), 279
- Permit (*rdflib.namespace.SDO* attribute), 223
- permitAudience (*rdflib.namespace.SDO* attribute), 279
- permittedUsage (*rdflib.namespace.SDO* attribute), 279
- Person (*rdflib.namespace.FOAF* attribute), 151
- Person (*rdflib.namespace.PROV* attribute), 179
- Person (*rdflib.namespace.SDO* attribute), 223

- PersonalProfileDocument (rdflib.namespace.FOAF attribute), 151
- PET (rdflib.namespace.SDO attribute), 221
- petsAllowed (rdflib.namespace.SDO attribute), 279
- PetStore (rdflib.namespace.SDO attribute), 223
- Pharmacy (rdflib.namespace.SDO attribute), 223
- PharmacySpecialty (rdflib.namespace.SDO attribute), 223
- phenomenonTime (rdflib.namespace.SOSA attribute), 308
- phone (rdflib.namespace.FOAF attribute), 153
- phoneticText (rdflib.namespace.SDO attribute), 279
- photo (rdflib.namespace.SDO attribute), 279
- Photograph (rdflib.namespace.SDO attribute), 223
- PhotographAction (rdflib.namespace.SDO attribute), 223
- photos (rdflib.namespace.SDO attribute), 280
- Photovoltaic\_Array (rdflib.namespace.BRICK attribute), 117
- Photovoltaic\_Current\_Output\_Sensor (rdflib.namespace.BRICK attribute), 117
- PhysicalActivity (rdflib.namespace.SDO attribute), 223
- PhysicalActivityCategory (rdflib.namespace.SDO attribute), 223
- PhysicalExam (rdflib.namespace.SDO attribute), 223
- PhysicalMedium (rdflib.namespace.DCTERMS attribute), 146
- PhysicalObject (rdflib.namespace.DCMITYPE attribute), 145
- physicalRequirement (rdflib.namespace.SDO attribute), 280
- PhysicalResource (rdflib.namespace.DCTERMS attribute), 146
- PhysicalTherapy (rdflib.namespace.SDO attribute), 223
- Physician (rdflib.namespace.SDO attribute), 223
- physiologicalBenefits (rdflib.namespace.SDO attribute), 280
- Physiotherapy (rdflib.namespace.SDO attribute), 223
- pickupLocation (rdflib.namespace.SDO attribute), 280
- pickupTime (rdflib.namespace.SDO attribute), 280
- PID\_Parameter (rdflib.namespace.BRICK attribute), 116
- Piezoelectric\_Sensor (rdflib.namespace.BRICK attribute), 117
- pingback (rdflib.namespace.PROV attribute), 182
- PIR\_Sensor (rdflib.namespace.BRICK attribute), 116
- PKGPlugin (class in rdflib.plugin), 529
- Place (rdflib.namespace.SDO attribute), 223
- PlaceboControlledTrial (rdflib.namespace.SDO attribute), 223
- PlaceOfWorship (rdflib.namespace.SDO attribute), 223
- PlainLiteral (rdflib.namespace.RDF attribute), 187
- plan (rdflib.namespace.FOAF attribute), 153
- Plan (rdflib.namespace.PROV attribute), 179
- PlanAction (rdflib.namespace.SDO attribute), 223
- PlasticSurgery (rdflib.namespace.SDO attribute), 223
- platform (rdflib.namespace.DOAP attribute), 150
- Platform (rdflib.namespace.SOSA attribute), 307
- play (rdflib.namespace.ODRL2 attribute), 168
- Play (rdflib.namespace.SDO attribute), 224
- PlayAction (rdflib.namespace.SDO attribute), 224
- playersOnline (rdflib.namespace.SDO attribute), 280
- playerType (rdflib.namespace.SDO attribute), 280
- Playground (rdflib.namespace.SDO attribute), 224
- playMode (rdflib.namespace.SDO attribute), 280
- Plugin (class in rdflib.plugin), 529
- PluginException, 530
- plugins() (in module rdflib.plugin), 530
- PluginT (class in rdflib.plugin), 530
- PlugStrip (rdflib.namespace.BRICK attribute), 117
- Plumber (rdflib.namespace.SDO attribute), 224
- Plumbing\_Room (rdflib.namespace.BRICK attribute), 117
- PM10\_Level\_Sensor (rdflib.namespace.BRICK attribute), 116
- PM10\_Sensor (rdflib.namespace.BRICK attribute), 116
- PM1\_Level\_Sensor (rdflib.namespace.BRICK attribute), 116
- PM1\_Sensor (rdflib.namespace.BRICK attribute), 116
- PodcastEpisode (rdflib.namespace.SDO attribute), 224
- PodcastSeason (rdflib.namespace.SDO attribute), 224
- PodcastSeries (rdflib.namespace.SDO attribute), 224
- Podiatric (rdflib.namespace.SDO attribute), 224
- Point (rdflib.namespace.BRICK attribute), 117
- Point (rdflib.namespace.DCTERMS attribute), 146
- Point (rdflib.namespace.WGS attribute), 315
- PoliceStation (rdflib.namespace.SDO attribute), 224
- Policy (rdflib.namespace.DCTERMS attribute), 146
- Policy (rdflib.namespace.ODRL2 attribute), 164
- policyUsage (rdflib.namespace.ODRL2 attribute), 168
- polygon (rdflib.namespace.SDO attribute), 280
- Pond (rdflib.namespace.SDO attribute), 224
- pop() (rdflib.plugins.serializers.xmlwriter.XMLWriter method), 363
- populationType (rdflib.namespace.SDO attribute), 280
- Portfolio (rdflib.namespace.BRICK attribute), 117
- position (rdflib.namespace.SDO attribute), 280
- Position\_Command (rdflib.namespace.BRICK attribute), 118
- Position\_Limit (rdflib.namespace.BRICK attribute), 118
- Position\_Sensor (rdflib.namespace.BRICK attribute), 118
- positiveInteger (rdflib.namespace.XSD attribute), 317
- positiveNotes (rdflib.namespace.SDO attribute), 280



- ul style="list-style-type: none; padding-left: 0;">
- `possibleComplication` (`rdflib.namespace.SDO` attribute), 280
- `possibleTreatment` (`rdflib.namespace.SDO` attribute), 280
- `Post` (`rdflib.namespace.ORG` attribute), 171
- `PostalAddress` (`rdflib.namespace.SDO` attribute), 224
- `postalCode` (`rdflib.namespace.SDO` attribute), 280
- `postalCodeBegin` (`rdflib.namespace.SDO` attribute), 280
- `postalCodeEnd` (`rdflib.namespace.SDO` attribute), 280
- `postalCodePrefix` (`rdflib.namespace.SDO` attribute), 280
- `postalCodeRange` (`rdflib.namespace.SDO` attribute), 280
- `PostalCodeRangeSpecification` (`rdflib.namespace.SDO` attribute), 224
- `Poster` (`rdflib.namespace.SDO` attribute), 224
- `postIn` (`rdflib.namespace.ORG` attribute), 172
- `PostOffice` (`rdflib.namespace.SDO` attribute), 224
- `postOfficeBoxNumber` (`rdflib.namespace.SDO` attribute), 280
- `postOp` (`rdflib.namespace.SDO` attribute), 280
- `postParse()` (`rdflib.plugins.sparql.parserutils.Comp` method), 410
- `postParse2()` (`rdflib.plugins.sparql.parserutils.Param` method), 412
- `Potable_Water` (`rdflib.namespace.BRICK` attribute), 118
- `potentialAction` (`rdflib.namespace.SDO` attribute), 280
- `PotentialActionStatus` (`rdflib.namespace.SDO` attribute), 224
- `potentialUse` (`rdflib.namespace.SDO` attribute), 280
- `Power_Alarm` (`rdflib.namespace.BRICK` attribute), 118
- `Power_Loss_Alarm` (`rdflib.namespace.BRICK` attribute), 118
- `Power_Sensor` (`rdflib.namespace.BRICK` attribute), 118
- `powerComplexity` (`rdflib.namespace.BRICK` attribute), 137
- `powerFlow` (`rdflib.namespace.BRICK` attribute), 137
- `pprintAlgebra()` (in module `rdflib.plugins.sparql.algebra`), 388
- `Prayer_Room` (`rdflib.namespace.BRICK` attribute), 118
- `Pre_Filter` (`rdflib.namespace.BRICK` attribute), 118
- `Pre_Filter_Status` (`rdflib.namespace.BRICK` attribute), 118
- `predecessorOf` (`rdflib.namespace.SDO` attribute), 280
- `predicate` (`rdflib.namespace.RDF` attribute), 188
- `predicate` (`rdflib.namespace.SH` attribute), 303
- `predicate` (`rdflib.plugins.parsers.rdfxml.ElementHandler` attribute), 343
- `predicate()` (`rdflib.plugins.parsers.ntriples.W3CNTriplesParser` method), 341
- `predicate()` (`rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer` method), 358
- `predicate()` (`rdflib.plugins.serializers.rdfxml.XMLSerializer` method), 359
- `predicate_objects()` (`rdflib.Graph` method), 596
- `predicate_objects()` (`rdflib.graph.Graph` method), 501
- `predicate_objects()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 448
- `predicate_objects()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 454
- `predicate_objects()` (`rdflib.resource.Resource` method), 545
- `predicateList()` (`rdflib.plugins.serializers.longturtle.LongTurtleSerializer` method), 356
- `predicateList()` (`rdflib.plugins.serializers.turtle.TurtleSerializer` method), 362
- `predicateOrder` (`rdflib.plugins.serializers.turtle.RecursiveSerializer` attribute), 361
- `predicates()` (`rdflib.Graph` method), 596
- `predicates()` (`rdflib.graph.Graph` method), 501
- `predicates()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 448
- `predicates()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 455
- `predicates()` (`rdflib.resource.Resource` method), 545
- `preferredNamespacePrefix` (`rdflib.namespace.VANN` attribute), 313
- `preferredNamespaceUri` (`rdflib.namespace.VANN` attribute), 313
- `prefix` (`rdflib.namespace.SH` attribute), 303
- `prefix` (`rdflib.plugins.shared.jsonld.context.Term` attribute), 370
- `prefix()` (`rdflib.plugins.stores.auditable.AuditableStore` method), 431
- `prefix()` (`rdflib.plugins.stores.berkeleydb.BerkeleyDB` method), 434
- `prefix()` (`rdflib.plugins.stores.memory.Memory` method), 438
- `prefix()` (`rdflib.plugins.stores.memory.SimpleMemory` method), 440
- `prefix()` (`rdflib.plugins.stores.regexmatching.REGEXMatching` method), 442
- `prefix()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 448
- `prefix()` (`rdflib.store.Store` method), 550
- `PrefixDeclaration` (`rdflib.namespace.SH` attribute), 299
- `prefixes` (`rdflib.namespace.SH` attribute), 303
- `prefLabel` (`rdflib.namespace.SKOS` attribute), 306
- `pregnancyCategory` (`rdflib.namespace.SDO` attribute), 280

- 280
- PregnancyHealthAspect (*rdflib.namespace.SDO* attribute), 224
- pregnancyWarning (*rdflib.namespace.SDO* attribute), 281
- Preheat\_Demand\_Setpoint (*rdflib.namespace.BRICK* attribute), 118
- Preheat\_Discharge\_Air\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 118
- Preheat\_Hot\_Water\_System (*rdflib.namespace.BRICK* attribute), 118
- Preheat\_Hot\_Water\_Valve (*rdflib.namespace.BRICK* attribute), 118
- Preheat\_Supply\_Air\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 118
- preOp (*rdflib.namespace.SDO* attribute), 280
- PreOrder (*rdflib.namespace.SDO* attribute), 224
- PreOrderAction (*rdflib.namespace.SDO* attribute), 224
- preparation (*rdflib.namespace.SDO* attribute), 281
- prepareQuery() (in module *rdflib.plugins.sparql*), 428
- prepareQuery() (in module *rdflib.plugins.sparql.processor*), 415
- prepareUpdate() (in module *rdflib.plugins.sparql*), 428
- prepareUpdate() (in module *rdflib.plugins.sparql.processor*), 415
- PrependAction (*rdflib.namespace.SDO* attribute), 224
- preprocess() (*rdflib.plugins.serializers.trig.TrigSerializer* method), 360
- preprocess() (*rdflib.plugins.serializers.turtle.RecursiveSerializer* method), 362
- preprocessTriple() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356
- preprocessTriple() (*rdflib.plugins.serializers.n3.N3Serializer* method), 357
- preprocessTriple() (*rdflib.plugins.serializers.turtle.RecursiveSerializer* method), 362
- preprocessTriple() (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 362
- prepTime (*rdflib.namespace.SDO* attribute), 281
- PreSale (*rdflib.namespace.SDO* attribute), 224
- Preschool (*rdflib.namespace.SDO* attribute), 224
- prescribingInfo (*rdflib.namespace.SDO* attribute), 281
- PrescriptionOnly (*rdflib.namespace.SDO* attribute), 224
- prescriptionStatus (*rdflib.namespace.SDO* attribute), 281
- present (*rdflib.namespace.ODRL2* attribute), 168
- PresentationDigitalDocument (*rdflib.namespace.SDO* attribute), 224
- Pressure\_Alarm (*rdflib.namespace.BRICK* attribute), 118
- Pressure\_Sensor (*rdflib.namespace.BRICK* attribute), 118
- Pressure\_Setpoint (*rdflib.namespace.BRICK* attribute), 118
- Pressure\_Status (*rdflib.namespace.BRICK* attribute), 118
- prettify\_parsetree() (in module *rdflib.plugins.sparql.parserutils*), 413
- PrettyXMLSerializer (class in *rdflib.plugins.serializers.rdfxml*), 358
- PreventionHealthAspect (*rdflib.namespace.SDO* attribute), 224
- PreventionIndication (*rdflib.namespace.SDO* attribute), 224
- preview (*rdflib.namespace.ODRL2* attribute), 168
- previousItem (*rdflib.namespace.SDO* attribute), 281
- previousStartDate (*rdflib.namespace.SDO* attribute), 281
- price (*rdflib.namespace.SDO* attribute), 281
- priceComponent (*rdflib.namespace.SDO* attribute), 281
- priceComponentType (*rdflib.namespace.SDO* attribute), 281
- PriceComponentTypeEnumeration (*rdflib.namespace.SDO* attribute), 224
- priceCurrency (*rdflib.namespace.SDO* attribute), 281
- priceRange (*rdflib.namespace.SDO* attribute), 281
- PriceSpecification (*rdflib.namespace.SDO* attribute), 225
- priceSpecification (*rdflib.namespace.SDO* attribute), 281
- priceType (*rdflib.namespace.SDO* attribute), 281
- PriceTypeEnumeration (*rdflib.namespace.SDO* attribute), 225
- priceValidUntil (*rdflib.namespace.SDO* attribute), 281
- PrimaryCare (*rdflib.namespace.SDO* attribute), 225
- primaryImageOfPage (*rdflib.namespace.SDO* attribute), 281
- primaryKey (*rdflib.namespace.CSVW* attribute), 139
- primaryPrevention (*rdflib.namespace.SDO* attribute), 281
- PrimarySource (*rdflib.namespace.PROV* attribute), 179
- primaryTopic (*rdflib.namespace.FOAF* attribute), 153
- print (*rdflib.namespace.ODRL2* attribute), 168
- print() (*rdflib.Graph* method), 597
- print() (*rdflib.graph.Graph* method), 502
- printColumn (*rdflib.namespace.SDO* attribute), 281
- printEdition (*rdflib.namespace.SDO* attribute), 281
- printPage (*rdflib.namespace.SDO* attribute), 281
- printSection (*rdflib.namespace.SDO* attribute), 281
- Prion (*rdflib.namespace.SDO* attribute), 225
- priorVersion (*rdflib.namespace.OWL* attribute), 175

- Privacy (*rdflib.namespace.ODRL2* attribute), 164
- Private\_Office (*rdflib.namespace.BRICK* attribute), 119
- procedure (*rdflib.namespace.SDO* attribute), 281
- Procedure (*rdflib.namespace.SOSA* attribute), 307
- procedureType (*rdflib.namespace.SDO* attribute), 281
- processingInstruction() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 346
- processingInstruction() (*rdflib.plugins.parsers.trix.TriXHandler* method), 351
- processingTime (*rdflib.namespace.SDO* attribute), 281
- Processor (class in *rdflib.query*), 531
- processorRequirements (*rdflib.namespace.SDO* attribute), 281
- processUpdate() (in module *rdflib.plugins.sparql*), 428
- processUpdate() (in module *rdflib.plugins.sparql.processor*), 415
- producer (*rdflib.namespace.SDO* attribute), 282
- produces (*rdflib.namespace.SDO* attribute), 282
- product (*rdflib.namespace.ODRL2* attribute), 168
- Product (*rdflib.namespace.SDO* attribute), 225
- ProductCollection (*rdflib.namespace.SDO* attribute), 225
- ProductGroup (*rdflib.namespace.SDO* attribute), 225
- productGroupID (*rdflib.namespace.SDO* attribute), 282
- productID (*rdflib.namespace.SDO* attribute), 282
- productionCompany (*rdflib.namespace.SDO* attribute), 282
- productionDate (*rdflib.namespace.SDO* attribute), 282
- ProductModel (*rdflib.namespace.SDO* attribute), 225
- productSupported (*rdflib.namespace.SDO* attribute), 282
- PROF (class in *rdflib.namespace*), 176
- ProfessionalService (*rdflib.namespace.SDO* attribute), 225
- proficiencyLevel (*rdflib.namespace.SDO* attribute), 282
- profile (*rdflib.namespace.ODRL2* attribute), 168
- Profile (*rdflib.namespace.PROF* attribute), 176
- ProfilePage (*rdflib.namespace.SDO* attribute), 225
- PrognosisHealthAspect (*rdflib.namespace.SDO* attribute), 225
- ProgramMembership (*rdflib.namespace.SDO* attribute), 225
- programMembershipUsed (*rdflib.namespace.SDO* attribute), 282
- programmingLanguage (*rdflib.namespace.SDO* attribute), 282
- programmingModel (*rdflib.namespace.SDO* attribute), 282
- programName (*rdflib.namespace.SDO* attribute), 282
- programPrerequisites (*rdflib.namespace.SDO* attribute), 282
- programType (*rdflib.namespace.SDO* attribute), 282
- prohibit (*rdflib.namespace.ODRL2* attribute), 168
- Prohibition (*rdflib.namespace.ODRL2* attribute), 164
- prohibition (*rdflib.namespace.ODRL2* attribute), 168
- Project (*rdflib.namespace.DOAP* attribute), 149
- Project (*rdflib.namespace.FOAF* attribute), 151
- Project (*rdflib.namespace.SDO* attribute), 225
- Project() (in module *rdflib.plugins.sparql.algebra*), 387
- project() (*rdflib.plugins.sparql.sparql.FrozenBindings* method), 418
- project() (*rdflib.plugins.sparql.sparql.FrozenDict* method), 420
- Prologue (class in *rdflib.plugins.sparql.sparql*), 421
- prologue (*rdflib.plugins.sparql.sparql.FrozenBindings* property), 418
- PronounceableText (*rdflib.namespace.SDO* attribute), 225
- prop() (*rdflib.plugins.parsers.notation3.SinkParser* method), 331
- ProperInterval (*rdflib.namespace.TIME* attribute), 309
- properties (*rdflib.namespace.VOID* attribute), 314
- Property (class in *rdflib.extras.infixowl*), 69
- Property (*rdflib.namespace.RDF* attribute), 187
- Property (*rdflib.namespace.SDO* attribute), 225
- property (*rdflib.namespace.SH* attribute), 303
- Property (*rdflib.namespace.SSN* attribute), 308
- property (*rdflib.namespace.VOID* attribute), 314
- property\_element\_char() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 346
- property\_element\_end() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 346
- property\_element\_start() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 346
- property\_list() (*rdflib.plugins.parsers.notation3.SinkParser* method), 332
- propertyChainAxiom (*rdflib.namespace.OWL* attribute), 175
- PropertyConstraintComponent (*rdflib.namespace.SH* attribute), 299
- propertyDisjointWith (*rdflib.namespace.OWL* attribute), 175
- PropertyGroup (*rdflib.namespace.SH* attribute), 299
- propertyID (*rdflib.namespace.SDO* attribute), 282
- propertyOrIdentifier() (in module *rdflib.extras.infixowl*), 72
- propertyPartition (*rdflib.namespace.VOID* attribute), 314
- PropertyShape (*rdflib.namespace.SH* attribute), 299

- `propertyUrl` (*rdflib.namespace.CSVW* attribute), 139
  - `propertyValidator` (*rdflib.namespace.SH* attribute), 303
  - `PropertyValue` (*rdflib.namespace.SDO* attribute), 225
  - `PropertyValueSpecification` (*rdflib.namespace.SDO* attribute), 225
  - `Proportional_Band_Parameter` (*rdflib.namespace.BRICK* attribute), 119
  - `Proportional_Gain_Parameter` (*rdflib.namespace.BRICK* attribute), 119
  - `proprietaryName` (*rdflib.namespace.SDO* attribute), 282
  - `protected` (*rdflib.plugins.shared.jsonld.context.Term* attribute), 370
  - `Protein` (*rdflib.namespace.SDO* attribute), 225
  - `proteinContent` (*rdflib.namespace.SDO* attribute), 282
  - `Protozoa` (*rdflib.namespace.SDO* attribute), 225
  - `PROV` (class in *rdflib.namespace*), 177
  - `provenance` (*rdflib.namespace.DCTERMS* attribute), 148
  - `ProvenanceStatement` (*rdflib.namespace.DCTERMS* attribute), 146
  - `provenanceUriTemplate` (*rdflib.namespace.PROV* attribute), 182
  - `provider` (*rdflib.namespace.SDO* attribute), 282
  - `providerMobility` (*rdflib.namespace.SDO* attribute), 282
  - `providesBroadcastService` (*rdflib.namespace.SDO* attribute), 282
  - `providesService` (*rdflib.namespace.SDO* attribute), 282
  - `proximity` (*rdflib.namespace.ODRL2* attribute), 168
  - `Psychiatric` (*rdflib.namespace.SDO* attribute), 225
  - `PsychologicalTreatment` (*rdflib.namespace.SDO* attribute), 225
  - `publicAccess` (*rdflib.namespace.SDO* attribute), 282
  - `publication` (*rdflib.namespace.SDO* attribute), 282
  - `PublicationEvent` (*rdflib.namespace.SDO* attribute), 226
  - `PublicationIssue` (*rdflib.namespace.SDO* attribute), 226
  - `publications` (*rdflib.namespace.FOAF* attribute), 153
  - `publicationType` (*rdflib.namespace.SDO* attribute), 283
  - `PublicationVolume` (*rdflib.namespace.SDO* attribute), 226
  - `PublicHealth` (*rdflib.namespace.SDO* attribute), 225
  - `PublicHolidays` (*rdflib.namespace.SDO* attribute), 225
  - `PublicSwimmingPool` (*rdflib.namespace.SDO* attribute), 225
  - `PublicToilet` (*rdflib.namespace.SDO* attribute), 226
  - `publicTransportClosuresInfo` (*rdflib.namespace.SDO* attribute), 282
  - `Publish` (*rdflib.namespace.PROV* attribute), 179
  - `publishedBy` (*rdflib.namespace.SDO* attribute), 283
  - `publishedOn` (*rdflib.namespace.SDO* attribute), 283
  - `publisher` (*rdflib.namespace.DC* attribute), 142
  - `publisher` (*rdflib.namespace.DCTERMS* attribute), 148
  - `Publisher` (*rdflib.namespace.PROV* attribute), 179
  - `publisher` (*rdflib.namespace.SDO* attribute), 283
  - `publisherImprint` (*rdflib.namespace.SDO* attribute), 283
  - `publishingPrinciples` (*rdflib.namespace.SDO* attribute), 283
  - `Pulmonary` (*rdflib.namespace.SDO* attribute), 226
  - `Pump` (*rdflib.namespace.BRICK* attribute), 119
  - `Pump_Command` (*rdflib.namespace.BRICK* attribute), 119
  - `Pump_On_Off_Status` (*rdflib.namespace.BRICK* attribute), 119
  - `Pump_Room` (*rdflib.namespace.BRICK* attribute), 119
  - `Pump_VFD` (*rdflib.namespace.BRICK* attribute), 119
  - `purchaseDate` (*rdflib.namespace.SDO* attribute), 283
  - `purpose` (*rdflib.namespace.ODRL2* attribute), 168
  - `purpose` (*rdflib.namespace.ORG* attribute), 172
  - `push()` (*rdflib.plugins.serializers.xmlwriter.XMLWriter* method), 363
  - `push()` (*rdflib.plugins.sparql.sparql.QueryContext* method), 424
  - `pushGraph()` (*rdflib.plugins.sparql.sparql.QueryContext* method), 424
  - `PV_Array` (*rdflib.namespace.BRICK* attribute), 117
  - `PV_Current_Output_Sensor` (*rdflib.namespace.BRICK* attribute), 117
  - `PV_Generation_System` (*rdflib.namespace.BRICK* attribute), 117
  - `PV_Panel` (*rdflib.namespace.BRICK* attribute), 117
  - `PVT_Panel` (*rdflib.namespace.BRICK* attribute), 117
  - Python Enhancement Proposals  
PEP 8, 625
  - `PythonInputSource` (class in *rdflib.parser*), 517
- ## Q
- `QAPage` (*rdflib.namespace.SDO* attribute), 226
  - `QB` (class in *rdflib.namespace*), 185
  - `QName` (*rdflib.namespace.XSD* attribute), 316
  - `qname()` (*rdflib.Graph* method), 597
  - `qname()` (*rdflib.graph.Graph* method), 502
  - `qname()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 513
  - `qname()` (*rdflib.namespace.NamespaceManager* method), 162
  - `qname()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 332
  - `qname()` (*rdflib.plugins.serializers.xmlwriter.XMLWriter* method), 363
  - `qname()` (*rdflib.resource.Resource* method), 545
  - `qname_strict()` (*rdflib.namespace.NamespaceManager* method), 162



- `quads()` (*rdflib.ConjunctiveGraph* method), 579
- `quads()` (*rdflib.Dataset* method), 584
- `quads()` (*rdflib.graph.ConjunctiveGraph* method), 484
- `quads()` (*rdflib.graph.Dataset* method), 490
- `quads()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 513
- `qualifications` (*rdflib.namespace.SDO* attribute), 283
- `qualifiedAssociation` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedAssociationOf` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedAttribution` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedAttributionOf` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedCardinality` (*rdflib.namespace.OWL* attribute), 176
- `qualifiedCommunication` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedCommunicationOf` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedDelegation` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedDelegationOf` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedDerivation` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedDerivationOf` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedEnd` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedEndOf` (*rdflib.namespace.PROV* attribute), 182
- `qualifiedForm` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedGeneration` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedGenerationOf` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedInfluence` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedInfluenceOf` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedInsertion` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedInvalidation` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedInvalidationOf` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedMaxCount` (*rdflib.namespace.SH* attribute), 303
- `QualifiedMaxCountConstraintComponent` (*rdflib.namespace.SH* attribute), 299
- `qualifiedMinCount` (*rdflib.namespace.SH* attribute), 303
- `QualifiedMinCountConstraintComponent` (*rdflib.namespace.SH* attribute), 299
- `qualifiedPrimarySource` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedQuotation` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedQuotationOf` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedRelation` (*rdflib.namespace.DCAT* attribute), 144
- `qualifiedRemoval` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedRevision` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedSourceOf` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedStart` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedStartOf` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedUsage` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedUsingActivity` (*rdflib.namespace.PROV* attribute), 183
- `qualifiedValueShape` (*rdflib.namespace.SH* attribute), 303
- `qualifiedValueShapesDisjoint` (*rdflib.namespace.SH* attribute), 303
- `QualitativeValue` (*rdflib.namespace.SDO* attribute), 226
- `QuantitativeValue` (*rdflib.namespace.SDO* attribute), 226
- `QuantitativeValueDistribution` (*rdflib.namespace.SDO* attribute), 226
- `Quantity` (*rdflib.namespace.BRICK* attribute), 119
- `Quantity` (*rdflib.namespace.SDO* attribute), 226
- `quarantineGuidelines` (*rdflib.namespace.SDO* attribute), 283
- `Query` (class in *rdflib.plugins.sparql.sparql*), 421
- `query` (*rdflib.namespace.SDO* attribute), 283
- `query()` (*rdflib.Graph* method), 597
- `query()` (*rdflib.graph.Graph* method), 502
- `query()` (*rdflib.plugins.sparql.processor.SPARQLProcessor* method), 414
- `query()` (*rdflib.plugins.stores.auditable.AuditableStore* method), 431
- `query()` (*rdflib.plugins.stores.memory.Memory* method), 438
- `query()` (*rdflib.plugins.stores.memory.SimpleMemory* method), 440
- `query()` (*rdflib.plugins.stores.sparqlconnector.SPARQLConnector* method), 444
- `query()` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 449
- `query()` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* method), 449



method), 455  
 query() (rdflib.query.Processor method), 532  
 query() (rdflib.store.Store method), 551  
 QueryContext (class in rdflib.plugins.sparql.sparql), 422  
 quest (rdflib.namespace.SDO attribute), 283  
 Question (rdflib.namespace.SDO attribute), 226  
 question (rdflib.namespace.SDO attribute), 283  
 Quiz (rdflib.namespace.SDO attribute), 226  
 Quotation (rdflib.namespace.PROV attribute), 179  
 Quotation (rdflib.namespace.SDO attribute), 226  
 QuoteAction (rdflib.namespace.SDO attribute), 226  
 quoteChar (rdflib.namespace.CSVW attribute), 139  
 quotedAs (rdflib.namespace.PROV attribute), 183  
 QuotedGraph (class in rdflib.graph), 508

## R

Radiant\_Ceiling\_Panel (rdflib.namespace.BRICK attribute), 119  
 Radiant\_Panel (rdflib.namespace.BRICK attribute), 119  
 Radiant\_Panel\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 119  
 Radiant\_Panel\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 119  
 Radiation\_Hot\_Water\_System (rdflib.namespace.BRICK attribute), 119  
 RadiationTherapy (rdflib.namespace.SDO attribute), 226  
 Radiator (rdflib.namespace.BRICK attribute), 119  
 Radioactivity\_Concentration\_Sensor (rdflib.namespace.BRICK attribute), 119  
 RadioBroadcastService (rdflib.namespace.SDO attribute), 226  
 RadioChannel (rdflib.namespace.SDO attribute), 226  
 RadioClip (rdflib.namespace.SDO attribute), 226  
 RadioEpisode (rdflib.namespace.SDO attribute), 226  
 Radiography (rdflib.namespace.SDO attribute), 226  
 RadioSeason (rdflib.namespace.SDO attribute), 226  
 RadioSeries (rdflib.namespace.SDO attribute), 226  
 RadioStation (rdflib.namespace.SDO attribute), 226  
 Radon\_Concentration\_Sensor (rdflib.namespace.BRICK attribute), 119  
 Rain\_Duration\_Sensor (rdflib.namespace.BRICK attribute), 120  
 Rain\_Sensor (rdflib.namespace.BRICK attribute), 120  
 RandomizedTrial (rdflib.namespace.SDO attribute), 226  
 range (rdflib.extras.infixowl.Property property), 70  
 range (rdflib.namespace.RDFS attribute), 188  
 rangeIncludes (rdflib.namespace.DCAM attribute), 143  
 rangeIncludes (rdflib.namespace.SDO attribute), 283  
 Rated\_Speed\_Setpoint (rdflib.namespace.BRICK attribute), 120  
 ratedModuleConversionEfficiency (rdflib.namespace.BRICK attribute), 137  
 ratedPowerOutput (rdflib.namespace.BRICK attribute), 137  
 Rating (rdflib.namespace.SDO attribute), 227  
 ratingCount (rdflib.namespace.SDO attribute), 283  
 ratingExplanation (rdflib.namespace.SDO attribute), 283  
 ratingValue (rdflib.namespace.SDO attribute), 283  
 rational (rdflib.namespace.OWL attribute), 176  
 RC\_Panel (rdflib.namespace.BRICK attribute), 119  
 rcc8dc (rdflib.namespace.GEO attribute), 155  
 rcc8ec (rdflib.namespace.GEO attribute), 155  
 rcc8eq (rdflib.namespace.GEO attribute), 155  
 rcc8ntpp (rdflib.namespace.GEO attribute), 155  
 rcc8ntppi (rdflib.namespace.GEO attribute), 155  
 rcc8po (rdflib.namespace.GEO attribute), 155  
 rcc8tpp (rdflib.namespace.GEO attribute), 155  
 rcc8tpi (rdflib.namespace.GEO attribute), 155  
 RDF (class in rdflib.namespace), 187  
 RDF (rdflib.plugins.parsers.RDFVOC.RDFVOC attribute), 319  
 rdf2dot() (in module rdflib.tools.rdf2dot), 461  
 rdflib  
   module, 574  
 rdflib.collection  
   module, 461  
 rdflib.compare  
   module, 466  
 rdflib.compat  
   module, 470  
 rdflib.container  
   module, 470  
 rdflib.events  
   module, 473  
 rdflib.exceptions  
   module, 475  
 rdflib.extras  
   module, 72  
 rdflib.extras.cmdlineutils  
   module, 49  
 rdflib.extras.describer  
   module, 49  
 rdflib.extras.external\_graph\_libs  
   module, 53  
 rdflib.extras.infixowl  
   module, 58  
 rdflib.graph  
   module, 476  
 rdflib.namespace  
   module, 72  
 rdflib.parser

- module, 516
- rdflib.paths
  - module, 519
- rdflib.plugin
  - module, 528
- rdflib.plugins
  - module, 458
- rdflib.plugins.parsers
  - module, 353
- rdflib.plugins.parsers.hext
  - module, 319
- rdflib.plugins.parsers.jsonld
  - module, 320
- rdflib.plugins.parsers.notation3
  - module, 321
- rdflib.plugins.parsers.nquads
  - module, 337
- rdflib.plugins.parsers.ntriples
  - module, 338
- rdflib.plugins.parsers.RDFVOC
  - module, 319
- rdflib.plugins.parsers.rdfxml
  - module, 342
- rdflib.plugins.parsers.trig
  - module, 348
- rdflib.plugins.parsers.trix
  - module, 350
- rdflib.plugins.serializers
  - module, 364
- rdflib.plugins.serializers.hext
  - module, 353
- rdflib.plugins.serializers.jsonld
  - module, 354
- rdflib.plugins.serializers.longturtle
  - module, 355
- rdflib.plugins.serializers.n3
  - module, 356
- rdflib.plugins.serializers.nquads
  - module, 357
- rdflib.plugins.serializers.nt
  - module, 358
- rdflib.plugins.serializers.rdfxml
  - module, 358
- rdflib.plugins.serializers.trig
  - module, 360
- rdflib.plugins.serializers.trix
  - module, 360
- rdflib.plugins.serializers.turtle
  - module, 361
- rdflib.plugins.serializers.xmlwriter
  - module, 363
- rdflib.plugins.shared
  - module, 371
- rdflib.plugins.shared.jsonld
  - module, 371
- rdflib.plugins.shared.jsonld.context
  - module, 364
- rdflib.plugins.shared.jsonld.errors
  - module, 370
- rdflib.plugins.shared.jsonld.keys
  - module, 370
- rdflib.plugins.shared.jsonld.util
  - module, 370
- rdflib.plugins.sparql
  - module, 428
- rdflib.plugins.sparql.aggregates
  - module, 379
- rdflib.plugins.sparql.algebra
  - module, 386
- rdflib.plugins.sparql.datatypes
  - module, 392
- rdflib.plugins.sparql.evaluate
  - module, 392
- rdflib.plugins.sparql.evalutils
  - module, 396
- rdflib.plugins.sparql.operators
  - module, 396
- rdflib.plugins.sparql.parser
  - module, 408
- rdflib.plugins.sparql.parserutils
  - module, 409
- rdflib.plugins.sparql.processor
  - module, 414
- rdflib.plugins.sparql.results
  - module, 379
- rdflib.plugins.sparql.results.csvresults
  - module, 371
- rdflib.plugins.sparql.results.graph
  - module, 373
- rdflib.plugins.sparql.results.jsonresults
  - module, 373
- rdflib.plugins.sparql.results.rdfresults
  - module, 375
- rdflib.plugins.sparql.results.tsvresults
  - module, 375
- rdflib.plugins.sparql.results.txtresults
  - module, 376
- rdflib.plugins.sparql.results.xmlresults
  - module, 376
- rdflib.plugins.sparql.sparql
  - module, 416
- rdflib.plugins.sparql.update
  - module, 425
- rdflib.plugins.stores
  - module, 458
- rdflib.plugins.stores.auditable
  - module, 429
- rdflib.plugins.stores.berkeleydb

- module, 432
- rdflib.plugins.stores.concurrent
  - module, 435
- rdflib.plugins.stores.memory
  - module, 436
- rdflib.plugins.stores.regexmatching
  - module, 441
- rdflib.plugins.stores.sparqlconnector
  - module, 443
- rdflib.plugins.stores.sparqlstore
  - module, 445
- rdflib.query
  - module, 531
- rdflib.resource
  - module, 538
- rdflib.serializer
  - module, 545
- rdflib.store
  - module, 546
- rdflib.term
  - module, 553
- rdflib.tools
  - module, 461
- rdflib.tools.chunk\_serializer
  - module, 458
- rdflib.tools.csv2rdf
  - module, 459
- rdflib.tools.defined\_namespace\_creator
  - module, 459
- rdflib.tools.graphisomorphism
  - module, 460
- rdflib.tools.rdf2dot
  - module, 461
- rdflib.tools.rdfpipe
  - module, 461
- rdflib.tools.rdfs2dot
  - module, 461
- rdflib.util
  - module, 570
- rdflib.void
  - module, 574
- rdflib\_to\_graphtool() (in module *rdflib.extras.external\_graph\_libs*), 53
- rdflib\_to\_networkx\_digraph() (in module *rdflib.extras.external\_graph\_libs*), 54
- rdflib\_to\_networkx\_graph() (in module *rdflib.extras.external\_graph\_libs*), 55
- rdflib\_to\_networkx\_multidigraph() (in module *rdflib.extras.external\_graph\_libs*), 56
- RDFResult (class in *rdflib.plugins.sparql.results.rdfresults*), 375
- RDFResultParser (class in *rdflib.plugins.sparql.results.rdfresults*), 375
- RDFS (class in *rdflib.namespace*), 188
- rdfs2dot() (in module *rdflib.tools.rdfs2dot*), 461
- RDFSink (class in *rdflib.plugins.parsers.notation3*), 324
- rdftype() (*rdflib.extras.describer.Describer* method), 52
- RDFVOC (class in *rdflib.plugins.parsers.RDFVOC*), 319
- RDFXMLHandler (class in *rdflib.plugins.parsers.rdfxml*), 343
- RDFXMLParser (class in *rdflib.plugins.parsers.rdfxml*), 347
- ReactAction (*rdflib.namespace.SDO* attribute), 227
- Reactive\_Power\_Sensor (*rdflib.namespace.BRICK* attribute), 120
- read (*rdflib.namespace.ODRL2* attribute), 168
- ReadAction (*rdflib.namespace.SDO* attribute), 227
- readBy (*rdflib.namespace.SDO* attribute), 283
- readline() (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser* method), 341
- ReadOnlyGraphAggregate (class in *rdflib.graph*), 509
- readonlyValue (*rdflib.namespace.SDO* attribute), 283
- ReadPermission (*rdflib.namespace.SDO* attribute), 227
- real (*rdflib.namespace.OWL* attribute), 176
- RealEstateAgent (*rdflib.namespace.SDO* attribute), 227
- realEstateAgent (*rdflib.namespace.SDO* attribute), 283
- RealEstateListing (*rdflib.namespace.SDO* attribute), 227
- RearWheelDriveConfiguration (*rdflib.namespace.SDO* attribute), 227
- ReceiveAction (*rdflib.namespace.SDO* attribute), 227
- Reception (*rdflib.namespace.BRICK* attribute), 120
- Recipe (*rdflib.namespace.SDO* attribute), 227
- recipe (*rdflib.namespace.SDO* attribute), 283
- recipeCategory (*rdflib.namespace.SDO* attribute), 283
- recipeCuisine (*rdflib.namespace.SDO* attribute), 283
- recipeIngredient (*rdflib.namespace.SDO* attribute), 283
- recipeInstructions (*rdflib.namespace.SDO* attribute), 283
- recipeYield (*rdflib.namespace.SDO* attribute), 283
- recipient (*rdflib.namespace.ODRL2* attribute), 169
- recipient (*rdflib.namespace.SDO* attribute), 283
- recognizedBy (*rdflib.namespace.SDO* attribute), 283
- recognizingAuthority (*rdflib.namespace.SDO* attribute), 284
- Recommendation (*rdflib.namespace.SDO* attribute), 227
- recommendationStrength (*rdflib.namespace.SDO* attribute), 284
- RecommendedDoseSchedule (*rdflib.namespace.SDO* attribute), 227
- recommendedIntake (*rdflib.namespace.SDO* attribute), 284
- record (*rdflib.namespace.DCAT* attribute), 144
- recordedAs (*rdflib.namespace.SDO* attribute), 284

- `recordedAt` (*rdflib.namespace.SDO* attribute), 284
- `recordedIn` (*rdflib.namespace.SDO* attribute), 284
- `recordingOf` (*rdflib.namespace.SDO* attribute), 284
- `recordLabel` (*rdflib.namespace.SDO* attribute), 284
- `recourseLoan` (*rdflib.namespace.SDO* attribute), 284
- `Recruiting` (*rdflib.namespace.SDO* attribute), 227
- `RecursiveSerializer` (class in *rdflib.plugins.serializers.turtle*), 361
- `RecyclingCenter` (*rdflib.namespace.SDO* attribute), 227
- `reference` (*rdflib.namespace.CSVW* attribute), 139
- `referencedRow` (*rdflib.namespace.CSVW* attribute), 139
- `referenceQuantity` (*rdflib.namespace.SDO* attribute), 284
- `references` (*rdflib.namespace.DCTERMS* attribute), 148
- `referencesOrder` (*rdflib.namespace.SDO* attribute), 284
- `refinement` (*rdflib.namespace.ODRL2* attribute), 169
- `ReflexiveProperty` (*rdflib.namespace.OWL* attribute), 173
- `refundType` (*rdflib.namespace.SDO* attribute), 284
- `RefundTypeEnumeration` (*rdflib.namespace.SDO* attribute), 227
- `RefurbishedCondition` (*rdflib.namespace.SDO* attribute), 227
- `regex_matching` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* attribute), 449
- `regexCompareQuad()` (in module *rdflib.plugins.stores.regexmatching*), 443
- `REGEXMatching` (class in *rdflib.plugins.stores.regexmatching*), 441
- `REGEXTerm` (class in *rdflib.plugins.stores.regexmatching*), 443
- `Region` (*rdflib.namespace.BRICK* attribute), 120
- `regionDrained` (*rdflib.namespace.SDO* attribute), 284
- `regionsAllowed` (*rdflib.namespace.SDO* attribute), 284
- `register()` (in module *rdflib.plugin*), 531
- `register()` (*rdflib.store.NodePickler* method), 547
- `register_custom_function()` (in module *rdflib.plugins.sparql.operators*), 407
- `RegisterAction` (*rdflib.namespace.SDO* attribute), 227
- `Registry` (*rdflib.namespace.SDO* attribute), 227
- `regulates` (*rdflib.namespace.BRICK* attribute), 137
- `Reheat_Hot_Water_System` (*rdflib.namespace.BRICK* attribute), 120
- `Reheat_Valve` (*rdflib.namespace.BRICK* attribute), 120
- `ReimbursementCap` (*rdflib.namespace.SDO* attribute), 227
- `RejectAction` (*rdflib.namespace.SDO* attribute), 227
- `rel()` (*rdflib.extras.describer.Describer* method), 52
- `related` (*rdflib.namespace.SKOS* attribute), 306
- `relatedAnatomy` (*rdflib.namespace.SDO* attribute), 284
- `relatedCondition` (*rdflib.namespace.SDO* attribute), 284
- `relatedDrug` (*rdflib.namespace.SDO* attribute), 284
- `relatedLink` (*rdflib.namespace.SDO* attribute), 284
- `relatedMatch` (*rdflib.namespace.SKOS* attribute), 306
- `relatedStructure` (*rdflib.namespace.SDO* attribute), 284
- `relatedTherapy` (*rdflib.namespace.SDO* attribute), 284
- `relatedTo` (*rdflib.namespace.SDO* attribute), 284
- `RelatedTopicsHealthAspect` (*rdflib.namespace.SDO* attribute), 227
- `relation` (*rdflib.namespace.DC* attribute), 142
- `relation` (*rdflib.namespace.DCTERMS* attribute), 148
- `relation` (*rdflib.namespace.ODRL2* attribute), 169
- `RelationalExpression()` (in module *rdflib.plugins.sparql.operators*), 404
- `Relationship` (*rdflib.namespace.DCAT* attribute), 143
- `Relative_Humidity_Sensor` (*rdflib.namespace.BRICK* attribute), 120
- `relativePosition` (*rdflib.namespace.ODRL2* attribute), 169
- `relativeSize` (*rdflib.namespace.ODRL2* attribute), 169
- `relativeSpatialPosition` (*rdflib.namespace.ODRL2* attribute), 169
- `relativeTemporalPosition` (*rdflib.namespace.ODRL2* attribute), 169
- `relativize()` (*rdflib.serializer.Serializer* method), 546
- `release` (*rdflib.namespace.DOAP* attribute), 150
- `releaseDate` (*rdflib.namespace.SDO* attribute), 284
- `releasedEvent` (*rdflib.namespace.SDO* attribute), 284
- `releaseNotes` (*rdflib.namespace.SDO* attribute), 284
- `releaseOf` (*rdflib.namespace.SDO* attribute), 284
- `relevantOccupation` (*rdflib.namespace.SDO* attribute), 284
- `relevantSpecialty` (*rdflib.namespace.SDO* attribute), 285
- `Relief_Damper` (*rdflib.namespace.BRICK* attribute), 120
- `Relief_Fan` (*rdflib.namespace.BRICK* attribute), 120
- `remainingAttendeeCapacity` (*rdflib.namespace.SDO* attribute), 285
- `remedy` (*rdflib.namespace.ODRL2* attribute), 169
- `remember()` (*rdflib.plugins.sparql.sparql.FrozenBindings* method), 418
- `RemixAlbum` (*rdflib.namespace.SDO* attribute), 227
- `Remotely_On_Off_Status` (*rdflib.namespace.BRICK* attribute), 120
- `Removal` (*rdflib.namespace.PROV* attribute), 179
- `remove()` (*rdflib.ConjunctiveGraph* method), 579
- `remove()` (*rdflib.Graph* method), 598
- `remove()` (*rdflib.graph.ConjunctiveGraph* method), 485
- `remove()` (*rdflib.graph.Graph* method), 503
- `remove()` (*rdflib.graph.ReadOnlyGraphAggregate* method), 513



remove() (rdflib.plugins.stores.auditable.AuditableStore method), 431  
 remove() (rdflib.plugins.stores.berkeleydb.BerkeleyDB method), 434  
 remove() (rdflib.plugins.stores.concurrent.ConcurrentStore method), 435  
 remove() (rdflib.plugins.stores.memory.Memory method), 438  
 remove() (rdflib.plugins.stores.memory.SimpleMemory method), 441  
 remove() (rdflib.plugins.stores.regexmatching.REGEXMatching method), 442  
 remove() (rdflib.plugins.stores.sparqlstore.SPARQLStore method), 449  
 remove() (rdflib.plugins.stores.sparqlstore.SPARQLUpdate method), 455  
 remove() (rdflib.resource.Resource method), 545  
 remove() (rdflib.store.Store method), 551  
 remove\_context() (rdflib.ConjunctiveGraph method), 579  
 remove\_context() (rdflib.graph.ConjunctiveGraph method), 485  
 remove\_context() (rdflib.plugins.stores.regexmatching.REGEXMatching method), 442  
 remove\_graph() (rdflib.Dataset method), 585  
 remove\_graph() (rdflib.graph.Dataset method), 490  
 remove\_graph() (rdflib.plugins.stores.berkeleydb.BerkeleyDB method), 435  
 remove\_graph() (rdflib.plugins.stores.memory.Memory method), 438  
 remove\_graph() (rdflib.plugins.stores.sparqlstore.SPARQLStore method), 449  
 remove\_graph() (rdflib.plugins.stores.sparqlstore.SPARQLUpdate method), 455  
 remove\_graph() (rdflib.store.Store method), 551  
 removedKey (rdflib.namespace.PROV attribute), 184  
 remuneration (rdflib.namespace.ORG attribute), 172  
 Renal (rdflib.namespace.SDO attribute), 227  
 renegotiableLoan (rdflib.namespace.SDO attribute), 285  
 RentAction (rdflib.namespace.SDO attribute), 227  
 RentalCarReservation (rdflib.namespace.SDO attribute), 227  
 RentalVehicleUsage (rdflib.namespace.SDO attribute), 227  
 reorderTriples() (in module rdflib.plugins.sparql.algebra), 388  
 RepaymentSpecification (rdflib.namespace.SDO attribute), 228  
 repeatCount (rdflib.namespace.SDO attribute), 285  
 repeatFrequency (rdflib.namespace.SDO attribute), 285  
 repetitions (rdflib.namespace.SDO attribute), 285  
 Replace (rdflib.namespace.PROV attribute), 179  
 replace() (rdflib.extras.infixowl.Individual method), 67  
 replace() (rdflib.extras.infixowl.Property method), 70  
 ReplaceAction (rdflib.namespace.SDO attribute), 228  
 replaceee (rdflib.namespace.SDO attribute), 285  
 replacer (rdflib.namespace.SDO attribute), 285  
 replaces (rdflib.namespace.DCTERMS attribute), 148  
 ReplyAction (rdflib.namespace.SDO attribute), 228  
 replyToUrl (rdflib.namespace.SDO attribute), 285  
 Report (rdflib.namespace.SDO attribute), 228  
 ReportageNewsArticle (rdflib.namespace.SDO attribute), 228  
 ReportedDoseSchedule (rdflib.namespace.SDO attribute), 228  
 ReportNumber (rdflib.namespace.SDO attribute), 285  
 reportsTo (rdflib.namespace.ORG attribute), 172  
 Repository (rdflib.namespace.DOAP attribute), 149  
 repository (rdflib.namespace.DOAP attribute), 150  
 repositoryOf (rdflib.namespace.DOAP attribute), 150  
 representativeOfPage (rdflib.namespace.SDO attribute), 285  
 reproduce (rdflib.namespace.ODRL2 attribute), 169  
 Request (rdflib.namespace.ODRL2 attribute), 164  
 required (rdflib.namespace.CSVW attribute), 139  
 requiredCollateral (rdflib.namespace.SDO attribute), 285  
 requiredGender (rdflib.namespace.SDO attribute), 285  
 requiredMaxAge (rdflib.namespace.SDO attribute), 285  
 requiredMinAge (rdflib.namespace.SDO attribute), 285  
 requiredQuantity (rdflib.namespace.SDO attribute), 285  
 requirements (rdflib.namespace.SDO attribute), 285  
 requires (rdflib.namespace.DCTERMS attribute), 148  
 requiresSubscription (rdflib.namespace.SDO attribute), 285  
 Researcher (rdflib.namespace.SDO attribute), 228  
 ResearchOrganization (rdflib.namespace.SDO attribute), 228  
 ResearchProject (rdflib.namespace.SDO attribute), 228  
 Reservation (rdflib.namespace.SDO attribute), 228  
 ReservationCancelled (rdflib.namespace.SDO attribute), 228  
 ReservationConfirmed (rdflib.namespace.SDO attribute), 228  
 reservationFor (rdflib.namespace.SDO attribute), 285  
 ReservationHold (rdflib.namespace.SDO attribute), 228  
 reservationId (rdflib.namespace.SDO attribute), 285  
 ReservationPackage (rdflib.namespace.SDO attribute), 228  
 ReservationPending (rdflib.namespace.SDO attribute), 228

- `reservationStatus` (*rdflib.namespace.SDO* attribute), 285
- `ReservationStatusType` (*rdflib.namespace.SDO* attribute), 228
- `ReserveAction` (*rdflib.namespace.SDO* attribute), 228
- `reservedTicket` (*rdflib.namespace.SDO* attribute), 285
- `Reservoir` (*rdflib.namespace.SDO* attribute), 228
- `reset()` (*rdflib.graph.BatchAddGraph* method), 481
- `reset()` (*rdflib.namespace.NamespaceManager* method), 162
- `reset()` (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 346
- `reset()` (*rdflib.plugins.parsers.trix.TriXHandler* method), 351
- `reset()` (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356
- `reset()` (*rdflib.plugins.serializers.n3.N3Serializer* method), 357
- `reset()` (*rdflib.plugins.serializers.trig.TrigSerializer* method), 360
- `reset()` (*rdflib.plugins.serializers.turtle.RecursiveSerializer* method), 362
- `reset()` (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 363
- `Reset_Command` (*rdflib.namespace.BRICK* attribute), 120
- `Reset_Setpoint` (*rdflib.namespace.BRICK* attribute), 120
- `Residence` (*rdflib.namespace.SDO* attribute), 228
- `resolution` (*rdflib.namespace.ODRL2* attribute), 169
- `resolve()` (*rdflib.plugins.shared.jsonld.context.Context* method), 368
- `resolve_iri()` (*rdflib.plugins.shared.jsonld.context.Context* method), 368
- `resolvePName()` (*rdflib.plugins.sparql.sparql.Prologue* method), 421
- `Resort` (*rdflib.namespace.SDO* attribute), 228
- `Resource` (class in *rdflib.resource*), 543
- `resource` (*rdflib.namespace.CSVW* attribute), 139
- `Resource` (*rdflib.namespace.DCAT* attribute), 143
- `Resource` (*rdflib.namespace.RDFS* attribute), 188
- `resource` (*rdflib.plugins.parsers.RDFVOC.RDFVOC* attribute), 319
- `resource()` (*rdflib.Graph* method), 598
- `resource()` (*rdflib.graph.Graph* method), 503
- `ResourceDescriptor` (*rdflib.namespace.PROF* attribute), 176
- `ResourceRole` (*rdflib.namespace.PROF* attribute), 177
- `RespiratoryTherapy` (*rdflib.namespace.SDO* attribute), 228
- `responsibilities` (*rdflib.namespace.SDO* attribute), 285
- `ResponsibleGenerator` (class in *rdflib.plugins.stores.concurrent*), 436
- `rest` (*rdflib.namespace.RDF* attribute), 188
- `Rest_Room` (*rdflib.namespace.BRICK* attribute), 120
- `Restaurant` (*rdflib.namespace.SDO* attribute), 228
- `restockingFee` (*rdflib.namespace.SDO* attribute), 285
- `RestockingFees` (*rdflib.namespace.SDO* attribute), 228
- `restPeriods` (*rdflib.namespace.SDO* attribute), 285
- `RestrictedDiet` (*rdflib.namespace.SDO* attribute), 228
- `Restriction` (class in *rdflib.extras.infixowl*), 70
- `Restriction` (*rdflib.namespace.OWL* attribute), 174
- `restrictionKind()` (*rdflib.extras.infixowl.Restriction* method), 71
- `restrictionKinds` (*rdflib.extras.infixowl.Restriction* attribute), 71
- `Restroom` (*rdflib.namespace.BRICK* attribute), 120
- `Result` (class in *rdflib.query*), 532
- `result` (*rdflib.namespace.SDO* attribute), 286
- `result` (*rdflib.namespace.SH* attribute), 303
- `Result` (*rdflib.namespace.SOSA* attribute), 307
- `ResultAnnotation` (*rdflib.namespace.SH* attribute), 299
- `resultAnnotation` (*rdflib.namespace.SH* attribute), 303
- `resultComment` (*rdflib.namespace.SDO* attribute), 286
- `resultedFrom` (*rdflib.namespace.ORG* attribute), 172
- `ResultException`, 534
- `resultingOrganization` (*rdflib.namespace.ORG* attribute), 172
- `resultMessage` (*rdflib.namespace.SH* attribute), 303
- `ResultParser` (class in *rdflib.query*), 534
- `resultPath` (*rdflib.namespace.SH* attribute), 303
- `resultReview` (*rdflib.namespace.SDO* attribute), 286
- `ResultRow` (class in *rdflib.query*), 535
- `ResultsAvailable` (*rdflib.namespace.SDO* attribute), 229
- `ResultSerializer` (class in *rdflib.query*), 537
- `resultSeverity` (*rdflib.namespace.SH* attribute), 303
- `resultsName` (*rdflib.plugins.sparql.parserutils.ParamList* attribute), 412
- `ResultsNotAvailable` (*rdflib.namespace.SDO* attribute), 229
- `resultTime` (*rdflib.namespace.SOSA* attribute), 308
- `ResumeAction` (*rdflib.namespace.SDO* attribute), 229
- `Retail` (*rdflib.namespace.SDO* attribute), 229
- `Retail_Room` (*rdflib.namespace.BRICK* attribute), 120
- `Return_Air` (*rdflib.namespace.BRICK* attribute), 120
- `Return_Air_CO2_Sensor` (*rdflib.namespace.BRICK* attribute), 120
- `Return_Air_CO2_Setpoint` (*rdflib.namespace.BRICK* attribute), 121
- `Return_Air_CO_Sensor` (*rdflib.namespace.BRICK* attribute), 121
- `Return_Air_Dewpoint_Sensor` (*rdflib.namespace.BRICK* attribute), 121

Return_Air_Differential_Pressure_Sensor (rdflib.namespace.BRICK attribute), 121	ReturnAction (rdflib.namespace.SDO attribute), 229
Return_Air_Differential_Pressure_Setpoint (rdflib.namespace.BRICK attribute), 121	ReturnAtKiosk (rdflib.namespace.SDO attribute), 229
Return_Air_Enthalpy_Sensor (rdflib.namespace.BRICK attribute), 121	ReturnByMail (rdflib.namespace.SDO attribute), 229
Return_Air_Filter (rdflib.namespace.BRICK attribute), 121	returnFees (rdflib.namespace.SDO attribute), 286
Return_Air_Flow_Sensor (rdflib.namespace.BRICK attribute), 121	ReturnFeesCustomerResponsibility (rdflib.namespace.SDO attribute), 229
Return_Air_Grains_Sensor (rdflib.namespace.BRICK attribute), 121	ReturnFeesEnumeration (rdflib.namespace.SDO attribute), 229
Return_Air_Humidity_Sensor (rdflib.namespace.BRICK attribute), 121	ReturnInStore (rdflib.namespace.SDO attribute), 229
Return_Air_Humidity_Setpoint (rdflib.namespace.BRICK attribute), 121	ReturnLabelCustomerResponsibility (rdflib.namespace.SDO attribute), 229
Return_Air_Plenum (rdflib.namespace.BRICK attribute), 121	ReturnLabelDownloadAndPrint (rdflib.namespace.SDO attribute), 229
Return_Air_Temperature_Alarm (rdflib.namespace.BRICK attribute), 121	ReturnLabelInBox (rdflib.namespace.SDO attribute), 229
Return_Air_Temperature_High_Reset_Setpoint (rdflib.namespace.BRICK attribute), 121	returnLabelSource (rdflib.namespace.SDO attribute), 286
Return_Air_Temperature_Low_Reset_Setpoint (rdflib.namespace.BRICK attribute), 121	ReturnLabelSourceEnumeration (rdflib.namespace.SDO attribute), 229
Return_Air_Temperature_Sensor (rdflib.namespace.BRICK attribute), 121	returnMethod (rdflib.namespace.SDO attribute), 286
Return_Air_Temperature_Setpoint (rdflib.namespace.BRICK attribute), 121	ReturnMethodEnumeration (rdflib.namespace.SDO attribute), 229
Return_Chilled_Water_Temperature_Setpoint (rdflib.namespace.BRICK attribute), 121	returnPolicyCategory (rdflib.namespace.SDO attribute), 286
Return_Condenser_Water (rdflib.namespace.BRICK attribute), 121	returnPolicyCountry (rdflib.namespace.SDO attribute), 286
Return_Condenser_Water_Flow_Sensor (rdflib.namespace.BRICK attribute), 122	returnPolicySeasonalOverride (rdflib.namespace.SDO attribute), 286
Return_Condenser_Water_Temperature_Sensor (rdflib.namespace.BRICK attribute), 122	ReturnShippingFees (rdflib.namespace.SDO attribute), 229
Return_Condenser_Water_Temperature_Setpoint (rdflib.namespace.BRICK attribute), 122	returnShippingFeesAmount (rdflib.namespace.SDO attribute), 286
Return_Damper (rdflib.namespace.BRICK attribute), 122	returnType (rdflib.namespace.SH attribute), 303
Return_Fan (rdflib.namespace.BRICK attribute), 122	rev() (rdflib.extras.describer.Describer method), 52
Return_Heating_Valve (rdflib.namespace.BRICK attribute), 122	rev_key (rdflib.plugins.shared.jsonld.context.Context property), 368
Return_Hot_Water (rdflib.namespace.BRICK attribute), 122	reverse (rdflib.plugins.shared.jsonld.context.Term attribute), 370
Return_Hot_Water_Temperature_Setpoint (rdflib.namespace.BRICK attribute), 122	Review (rdflib.namespace.SDO attribute), 229
Return_Water (rdflib.namespace.BRICK attribute), 122	review (rdflib.namespace.SDO attribute), 286
Return_Water_Flow_Sensor (rdflib.namespace.BRICK attribute), 122	ReviewAction (rdflib.namespace.SDO attribute), 229
Return_Water_Temperature_Sensor (rdflib.namespace.BRICK attribute), 122	reviewAspect (rdflib.namespace.SDO attribute), 286
Return_Water_Temperature_Setpoint (rdflib.namespace.BRICK attribute), 122	reviewBody (rdflib.namespace.SDO attribute), 286
	reviewCount (rdflib.namespace.SDO attribute), 286
	reviewedBy (rdflib.namespace.SDO attribute), 286
	ReviewNewsArticle (rdflib.namespace.SDO attribute), 229
	reviewPolicy (rdflib.namespace.ODRL2 attribute), 169
	reviewRating (rdflib.namespace.SDO attribute), 286
	reviews (rdflib.namespace.SDO attribute), 286
	revisedEntity (rdflib.namespace.PROV attribute), 184
	revision (rdflib.namespace.DOAP attribute), 150
	Revision (rdflib.namespace.PROV attribute), 179
	RFC



- RFC 3066, 29, 33
  - RFC1766 (*rdflib.namespace.DCTERMS* attribute), 146
  - RFC3066 (*rdflib.namespace.DCTERMS* attribute), 146
  - RFC4646 (*rdflib.namespace.DCTERMS* attribute), 146
  - RFC5646 (*rdflib.namespace.DCTERMS* attribute), 146
  - Rheumatologic (*rdflib.namespace.SDO* attribute), 229
  - RightHandDriving (*rdflib.namespace.SDO* attribute), 229
  - RightOperand (*rdflib.namespace.ODRL2* attribute), 164
  - rightOperand (*rdflib.namespace.ODRL2* attribute), 169
  - rightOperandReference (*rdflib.namespace.ODRL2* attribute), 169
  - rights (*rdflib.namespace.DC* attribute), 142
  - rights (*rdflib.namespace.DCTERMS* attribute), 148
  - RightsAssignment (*rdflib.namespace.PROV* attribute), 179
  - rightsHolder (*rdflib.namespace.DCTERMS* attribute), 148
  - RightsHolder (*rdflib.namespace.PROV* attribute), 179
  - RightsStatement (*rdflib.namespace.DCTERMS* attribute), 146
  - Riser (*rdflib.namespace.BRICK* attribute), 122
  - riskFactor (*rdflib.namespace.SDO* attribute), 286
  - risks (*rdflib.namespace.SDO* attribute), 286
  - RisksOrComplicationsHealthAspect (*rdflib.namespace.SDO* attribute), 229
  - RiverBodyOfWater (*rdflib.namespace.SDO* attribute), 229
  - Role (*rdflib.namespace.DCAT* attribute), 143
  - Role (*rdflib.namespace.ORG* attribute), 171
  - role (*rdflib.namespace.ORG* attribute), 172
  - Role (*rdflib.namespace.PROV* attribute), 179
  - Role (*rdflib.namespace.SDO* attribute), 230
  - roleName (*rdflib.namespace.SDO* attribute), 286
  - roleProperty (*rdflib.namespace.ORG* attribute), 172
  - rollback() (*rdflib.Graph* method), 598
  - rollback() (*rdflib.graph.Graph* method), 503
  - rollback() (*rdflib.graph.ReadOnlyGraphAggregate* method), 514
  - rollback() (*rdflib.plugins.stores.auditable.AuditableStore* method), 431
  - rollback() (*rdflib.plugins.stores.regexmatching.REGEXMatching* method), 442
  - rollback() (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 449
  - rollback() (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* method), 455
  - rollback() (*rdflib.store.Store* method), 551
  - RoofingContractor (*rdflib.namespace.SDO* attribute), 230
  - roofLoad (*rdflib.namespace.SDO* attribute), 286
  - Rooftop (*rdflib.namespace.BRICK* attribute), 122
  - Rooftop\_Unit (*rdflib.namespace.BRICK* attribute), 122
  - Room (*rdflib.namespace.BRICK* attribute), 122
  - Room (*rdflib.namespace.SDO* attribute), 230
  - Room\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 122
  - rootResource (*rdflib.namespace.VOID* attribute), 314
  - roundtrip\_prefixes (*rdflib.plugins.serializers.turtle.RecursiveSerializer* attribute), 362
  - Row (*rdflib.namespace.CSVW* attribute), 138
  - row (*rdflib.namespace.CSVW* attribute), 140
  - rownum (*rdflib.namespace.CSVW* attribute), 140
  - rowTitle (*rdflib.namespace.CSVW* attribute), 140
  - RsvpAction (*rdflib.namespace.SDO* attribute), 230
  - rsvpResponse (*rdflib.namespace.SDO* attribute), 286
  - RsvpResponseMaybe (*rdflib.namespace.SDO* attribute), 230
  - RsvpResponseNo (*rdflib.namespace.SDO* attribute), 230
  - RsvpResponseType (*rdflib.namespace.SDO* attribute), 230
  - RsvpResponseYes (*rdflib.namespace.SDO* attribute), 230
  - rtl (*rdflib.namespace.CSVW* attribute), 140
  - RTU (*rdflib.namespace.BRICK* attribute), 119
  - Rule (*rdflib.namespace.ODRL2* attribute), 164
  - Rule (*rdflib.namespace.SH* attribute), 300
  - rule (*rdflib.namespace.SH* attribute), 304
  - Run\_Enable\_Command (*rdflib.namespace.BRICK* attribute), 122
  - Run\_Request\_Status (*rdflib.namespace.BRICK* attribute), 122
  - Run\_Status (*rdflib.namespace.BRICK* attribute), 122
  - Run\_Time\_Sensor (*rdflib.namespace.BRICK* attribute), 123
  - runNamespace() (in module *rdflib.plugins.parsers.notation3*), 336
  - runsTo (*rdflib.namespace.SDO* attribute), 286
  - runtime (*rdflib.namespace.SDO* attribute), 286
  - runtimePlatform (*rdflib.namespace.SDO* attribute), 286
  - RVAV (*rdflib.namespace.BRICK* attribute), 119
  - RVPark (*rdflib.namespace.SDO* attribute), 226
  - rxcul (*rdflib.namespace.SDO* attribute), 286
- ## S
- s\_clause() (*rdflib.plugins.serializers.n3.N3Serializer* method), 357
  - s\_default() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356
  - s\_default() (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 363
  - s\_squared() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356
  - s\_squared() (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 363



- Safety\_Equipment (*rdflib.namespace.BRICK* attribute), 123
- Safety\_Shower (*rdflib.namespace.BRICK* attribute), 123
- Safety\_System (*rdflib.namespace.BRICK* attribute), 123
- safetyConsideration (*rdflib.namespace.SDO* attribute), 286
- SafetyHealthAspect (*rdflib.namespace.SDO* attribute), 230
- salaryCurrency (*rdflib.namespace.SDO* attribute), 287
- salaryUponCompletion (*rdflib.namespace.SDO* attribute), 287
- SaleEvent (*rdflib.namespace.SDO* attribute), 230
- SalePrice (*rdflib.namespace.SDO* attribute), 230
- sameAs (*rdflib.extras.infixowl.Individual* property), 67
- sameAs (*rdflib.namespace.OWL* attribute), 176
- sameAs (*rdflib.namespace.SDO* attribute), 287
- Sample (class in *rdflib.plugins.sparql.aggregates*), 384
- Sample (*rdflib.namespace.SOSA* attribute), 307
- Sampler (*rdflib.namespace.SOSA* attribute), 307
- sampleType (*rdflib.namespace.SDO* attribute), 287
- Sampling (*rdflib.namespace.SOSA* attribute), 307
- Sash\_Position\_Sensor (*rdflib.namespace.BRICK* attribute), 123
- SatireOrParodyContent (*rdflib.namespace.SDO* attribute), 230
- SatiricalArticle (*rdflib.namespace.SDO* attribute), 230
- saturatedFatContent (*rdflib.namespace.SDO* attribute), 287
- Saturday (*rdflib.namespace.SDO* attribute), 230
- Saturday (*rdflib.namespace.TIME* attribute), 309
- Schedule (*rdflib.namespace.SDO* attribute), 230
- Schedule\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 123
- ScheduleAction (*rdflib.namespace.SDO* attribute), 230
- scheduledPaymentDate (*rdflib.namespace.SDO* attribute), 287
- scheduledTime (*rdflib.namespace.SDO* attribute), 287
- scheduleTimezone (*rdflib.namespace.SDO* attribute), 287
- Schema (*rdflib.namespace.CSVW* attribute), 138
- schemaReference (*rdflib.namespace.CSVW* attribute), 140
- schemaVersion (*rdflib.namespace.SDO* attribute), 287
- ScholarlyArticle (*rdflib.namespace.SDO* attribute), 230
- School (*rdflib.namespace.SDO* attribute), 230
- schoolClosuresInfo (*rdflib.namespace.SDO* attribute), 287
- SchoolDistrict (*rdflib.namespace.SDO* attribute), 230
- schoolHomepage (*rdflib.namespace.FOAF* attribute), 153
- scope (*rdflib.namespace.ODRL2* attribute), 169
- scopeNote (*rdflib.namespace.SKOS* attribute), 306
- screenCount (*rdflib.namespace.SDO* attribute), 287
- ScreeningEvent (*rdflib.namespace.SDO* attribute), 230
- ScreeningHealthAspect (*rdflib.namespace.SDO* attribute), 230
- screenshot (*rdflib.namespace.SDO* attribute), 287
- screenshots (*rdflib.namespace.DOAP* attribute), 150
- scriptFormat (*rdflib.namespace.CSVW* attribute), 140
- Sculpture (*rdflib.namespace.SDO* attribute), 230
- sdDatePublished (*rdflib.namespace.SDO* attribute), 287
- sdLicense (*rdflib.namespace.SDO* attribute), 287
- SDO (class in *rdflib.namespace*), 189
- sdPublisher (*rdflib.namespace.SDO* attribute), 287
- SeaBodyOfWater (*rdflib.namespace.SDO* attribute), 230
- SearchAction (*rdflib.namespace.SDO* attribute), 230
- SearchResultsPage (*rdflib.namespace.SDO* attribute), 231
- Season (*rdflib.namespace.SDO* attribute), 231
- season (*rdflib.namespace.SDO* attribute), 287
- seasonNumber (*rdflib.namespace.SDO* attribute), 287
- seasons (*rdflib.namespace.SDO* attribute), 287
- Seat (*rdflib.namespace.SDO* attribute), 231
- seatingCapacity (*rdflib.namespace.SDO* attribute), 287
- SeatingMap (*rdflib.namespace.SDO* attribute), 231
- seatingType (*rdflib.namespace.SDO* attribute), 287
- seatNumber (*rdflib.namespace.SDO* attribute), 287
- seatRow (*rdflib.namespace.SDO* attribute), 287
- seatSection (*rdflib.namespace.SDO* attribute), 287
- second (*rdflib.namespace.TIME* attribute), 312
- second (*rdflib.namespace.XSD* attribute), 317
- secondaryPrevention (*rdflib.namespace.SDO* attribute), 287
- secondaryUse (*rdflib.namespace.ODRL2* attribute), 169
- seconds (*rdflib.namespace.TIME* attribute), 312
- SecuredHTTPHandler (class in *examples.secure\_with\_urlopen*), 26
- Security\_Equipment (*rdflib.namespace.BRICK* attribute), 123
- Security\_Service\_Room (*rdflib.namespace.BRICK* attribute), 123
- securityClearanceRequirement (*rdflib.namespace.SDO* attribute), 287
- securityScreening (*rdflib.namespace.SDO* attribute), 287
- seeAlso (*rdflib.extras.infixowl.AnnotatableTerms* property), 61
- seeAlso (*rdflib.namespace.RDFS* attribute), 189
- SeeDoctorHealthAspect (*rdflib.namespace.SDO* attribute), 231
- seeks (*rdflib.namespace.SDO* attribute), 288
- SeekToAction (*rdflib.namespace.SDO* attribute), 231

- seen (*rdflib.plugins.sparql.aggregates.Average* attribute), 381
- seen (*rdflib.plugins.sparql.aggregates.Counter* attribute), 382
- seen (*rdflib.plugins.sparql.aggregates.Extremum* attribute), 383
- seen (*rdflib.plugins.sparql.aggregates.Maximum* attribute), 384
- seen (*rdflib.plugins.sparql.aggregates.Minimum* attribute), 384
- seen (*rdflib.plugins.sparql.aggregates.Sample* attribute), 385
- seen (*rdflib.plugins.sparql.aggregates.Sum* attribute), 385
- select (*rdflib.namespace.SH* attribute), 304
- SelfCareHealthAspect (*rdflib.namespace.SDO* attribute), 231
- SelfStorage (*rdflib.namespace.SDO* attribute), 231
- sell (*rdflib.namespace.ODRL2* attribute), 169
- SellAction (*rdflib.namespace.SDO* attribute), 231
- seller (*rdflib.namespace.SDO* attribute), 288
- semanticRelation (*rdflib.namespace.SKOS* attribute), 306
- SendAction (*rdflib.namespace.SDO* attribute), 231
- sender (*rdflib.namespace.SDO* attribute), 288
- Sensor (*rdflib.namespace.BRICK* attribute), 123
- Sensor (*rdflib.namespace.SOSA* attribute), 307
- sensoryRequirement (*rdflib.namespace.SDO* attribute), 288
- sensoryUnit (*rdflib.namespace.SDO* attribute), 288
- separator (*rdflib.namespace.CSVW* attribute), 140
- Seq (class in *rdflib.container*), 473
- Seq (class in *rdflib.graph*), 514
- Seq (*rdflib.namespace.RDF* attribute), 187
- SequencePath (class in *rdflib.paths*), 526
- serialize() (*rdflib.extras.infixowl.BooleanClass* method), 62
- serialize() (*rdflib.extras.infixowl.Class* method), 64
- serialize() (*rdflib.extras.infixowl.EnumeratedClass* method), 66
- serialize() (*rdflib.extras.infixowl.Individual* method), 67
- serialize() (*rdflib.extras.infixowl.Property* method), 70
- serialize() (*rdflib.extras.infixowl.Restriction* method), 71
- serialize() (*rdflib.Graph* method), 598
- serialize() (*rdflib.graph.Graph* method), 503
- serialize() (*rdflib.plugins.serializers.hext.HextuplesSerializer* method), 354
- serialize() (*rdflib.plugins.serializers.jsonld.JsonLDSerializer* method), 355
- serialize() (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356
- serialize() (*rdflib.plugins.serializers.nquads.NQuadsSerializer* method), 357
- serialize() (*rdflib.plugins.serializers.nt.NTSerializer* method), 358
- serialize() (*rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer* method), 358
- serialize() (*rdflib.plugins.serializers.rdfxml.XMLSerializer* method), 359
- serialize() (*rdflib.plugins.serializers.trig.TrigSerializer* method), 360
- serialize() (*rdflib.plugins.serializers.trix.TriXSerializer* method), 361
- serialize() (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 363
- serialize() (*rdflib.plugins.sparql.results.csvresults.CSVResultSerializer* method), 372
- serialize() (*rdflib.plugins.sparql.results.jsonresults.JSONResultSerializer* method), 374
- serialize() (*rdflib.plugins.sparql.results.txtresults.TXTResultSerializer* method), 376
- serialize() (*rdflib.plugins.sparql.results.xmlresults.XMLResultSerializer* method), 379
- serialize() (*rdflib.query.Result* method), 534
- serialize() (*rdflib.query.ResultSerializer* method), 537
- serialize() (*rdflib.serializer.Serializer* method), 546
- serialize\_in\_chunks() (in module *rdflib.tools.chunk\_serializer*), 458
- Serializer (class in *rdflib.serializer*), 545
- serializeTerm() (*rdflib.plugins.sparql.results.csvresults.CSVResultSerializer* method), 372
- serialNumber (*rdflib.namespace.SDO* attribute), 288
- Series (*rdflib.namespace.SDO* attribute), 231
- seriousAdverseOutcome (*rdflib.namespace.SDO* attribute), 288
- Server\_Room (*rdflib.namespace.BRICK* attribute), 123
- serverStatus (*rdflib.namespace.SDO* attribute), 288
- servesCuisine (*rdflib.namespace.SDO* attribute), 288
- servesDataset (*rdflib.namespace.DCAT* attribute), 144
- service (*rdflib.namespace.DCAT* attribute), 144
- Service (*rdflib.namespace.DCMITYPE* attribute), 145
- Service (*rdflib.namespace.SDO* attribute), 231
- Service\_Room (*rdflib.namespace.BRICK* attribute), 123
- serviceArea (*rdflib.namespace.SDO* attribute), 288
- serviceAudience (*rdflib.namespace.SDO* attribute), 288
- ServiceChannel (*rdflib.namespace.SDO* attribute), 231
- ServiceDescription (*rdflib.namespace.PROV* attribute), 179
- serviceLocation (*rdflib.namespace.SDO* attribute), 288
- serviceOperator (*rdflib.namespace.SDO* attribute), 288
- serviceOutput (*rdflib.namespace.SDO* attribute), 288

- servicePhone (*rdflib.namespace.SDO* attribute), 288  
 servicePostalAddress (*rdflib.namespace.SDO* attribute), 288  
 serviceSmsNumber (*rdflib.namespace.SDO* attribute), 288  
 serviceType (*rdflib.namespace.SDO* attribute), 288  
 serviceUrl (*rdflib.namespace.SDO* attribute), 288  
 servingSize (*rdflib.namespace.SDO* attribute), 288  
 Set (*rdflib.namespace.ODRL2* attribute), 164  
 set() (*rdflib.Graph* method), 599  
 set() (*rdflib.graph.Graph* method), 504  
 set() (*rdflib.resource.Resource* method), 545  
 set\_map() (*rdflib.events.Dispatcher* method), 474  
 set\_value() (*rdflib.plugins.sparql.aggregates.Accumulator* method), 380  
 set\_value() (*rdflib.plugins.sparql.aggregates.Extremum* method), 383  
 setDataType() (in module *rdflib.plugins.sparql.parser*), 409  
 setDefaultNamespace() (*rdflib.plugins.parsers.notation3.RDFSink* method), 326  
 setDocumentLocator() (*rdflib.plugins.parsers.rdfxml.RDFXMLHandler* method), 346  
 setDocumentLocator() (*rdflib.plugins.parsers.trix.TriXHandler* method), 351  
 setEvalFn() (*rdflib.plugins.sparql.parserutils.Comp* method), 410  
 setKeywords() (*rdflib.plugins.parsers.notation3.SinkParser* method), 332  
 setLanguage() (in module *rdflib.plugins.sparql.parser*), 409  
 Setpoint (*rdflib.namespace.BRICK* attribute), 123  
 setPublicId() (*rdflib.parser.PythonInputSource* method), 517  
 setSystemId() (*rdflib.parser.PythonInputSource* method), 518  
 setTimeout() (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 456  
 setupACEAnnotations() (*rdflib.extras.infixowl.AnnotatableTerms* method), 61  
 setupNounAnnotations() (*rdflib.extras.infixowl.Class* method), 64  
 setupVerbAnnotations() (*rdflib.extras.infixowl.Property* method), 70  
 setVersion() (*rdflib.extras.infixowl.Ontology* method), 69  
 Severity (*rdflib.namespace.SH* attribute), 300  
 severity (*rdflib.namespace.SH* attribute), 304  
 sfContains (*rdflib.namespace.GEO* attribute), 155  
 sfCrosses (*rdflib.namespace.GEO* attribute), 155  
 sfDisjoint (*rdflib.namespace.GEO* attribute), 155  
 sfEquals (*rdflib.namespace.GEO* attribute), 155  
 sfIntersects (*rdflib.namespace.GEO* attribute), 155  
 sfOverlaps (*rdflib.namespace.GEO* attribute), 156  
 sfTouches (*rdflib.namespace.GEO* attribute), 156  
 sfWithin (*rdflib.namespace.GEO* attribute), 156  
 SH (class in *rdflib.namespace*), 297  
 sha1 (*rdflib.namespace.FOAF* attribute), 153  
 sha256 (*rdflib.namespace.SDO* attribute), 288  
 Shading\_System (*rdflib.namespace.BRICK* attribute), 123  
 Shape (*rdflib.namespace.SH* attribute), 300  
 shapesGraph (*rdflib.namespace.SH* attribute), 304  
 shapesGraphWellFormed (*rdflib.namespace.SH* attribute), 304  
 share (*rdflib.namespace.ODRL2* attribute), 169  
 ShareAction (*rdflib.namespace.SDO* attribute), 231  
 shareAlike (*rdflib.namespace.ODRL2* attribute), 169  
 Shared\_Office (*rdflib.namespace.BRICK* attribute), 123  
 sharedContent (*rdflib.namespace.SDO* attribute), 288  
 sharesDefinitionWith (*rdflib.namespace.PROV* attribute), 184  
 SheetMusic (*rdflib.namespace.SDO* attribute), 231  
 ShippingDeliveryTime (*rdflib.namespace.SDO* attribute), 231  
 shippingDestination (*rdflib.namespace.SDO* attribute), 288  
 shippingDetails (*rdflib.namespace.SDO* attribute), 288  
 shippingLabel (*rdflib.namespace.SDO* attribute), 288  
 shippingRate (*rdflib.namespace.SDO* attribute), 288  
 ShippingRateSettings (*rdflib.namespace.SDO* attribute), 231  
 shippingSettingsLink (*rdflib.namespace.SDO* attribute), 288  
 ShoeStore (*rdflib.namespace.SDO* attribute), 231  
 ShoppingCenter (*rdflib.namespace.SDO* attribute), 231  
 short (*rdflib.namespace.XSD* attribute), 318  
 ShortCycle\_Alarm (*rdflib.namespace.BRICK* attribute), 123  
 short\_name (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* attribute), 356  
 short\_name (*rdflib.plugins.serializers.n3.N3Serializer* attribute), 357  
 short\_name (*rdflib.plugins.serializers.trig.TrigSerializer* attribute), 360  
 short\_name (*rdflib.plugins.serializers.turtle.TurtleSerializer* attribute), 363  
 shortdesc (*rdflib.namespace.DOAP* attribute), 150  
 ShortStory (*rdflib.namespace.SDO* attribute), 231  
 Shower (*rdflib.namespace.BRICK* attribute), 123  
 shrink\_iri() (*rdflib.plugins.shared.jsonld.context.Context* method), 368



- ul style="list-style-type: none; padding-left: 0;">
- sibling (*rdflib.namespace.SDO* attribute), 289
- siblings (*rdflib.namespace.SDO* attribute), 289
- SideEffectsHealthAspect (*rdflib.namespace.SDO* attribute), 231
- sign() (in module *rdflib.compat*), 470
- signDetected (*rdflib.namespace.SDO* attribute), 289
- significance (*rdflib.namespace.SDO* attribute), 289
- significantLink (*rdflib.namespace.SDO* attribute), 289
- significantLinks (*rdflib.namespace.SDO* attribute), 289
- signOrSymptom (*rdflib.namespace.SDO* attribute), 289
- similar() (in module *rdflib.compare*), 469
- SimpleMemory (class in *rdflib.plugins.stores.memory*), 439
- simplify() (in module *rdflib.plugins.sparql.algebra*), 389
- simplify() (in module *rdflib.plugins.sparql.operators*), 407
- SingleBlindedTrial (*rdflib.namespace.SDO* attribute), 231
- SingleCenterTrial (*rdflib.namespace.SDO* attribute), 231
- SingleFamilyResidence (*rdflib.namespace.SDO* attribute), 231
- SinglePlayer (*rdflib.namespace.SDO* attribute), 231
- SingleRelease (*rdflib.namespace.SDO* attribute), 232
- sink (*rdflib.plugins.parsers.nquads.NQuadsParser* attribute), 338
- sink (*rdflib.plugins.parsers.ntriples.W3CNTriplesParser* attribute), 341
- SinkParser (class in *rdflib.plugins.parsers.notation3*), 326
- Site (*rdflib.namespace.BRICK* attribute), 123
- Site (*rdflib.namespace.ORG* attribute), 171
- siteAddress (*rdflib.namespace.ORG* attribute), 172
- SiteNavigationElement (*rdflib.namespace.SDO* attribute), 232
- siteOf (*rdflib.namespace.ORG* attribute), 172
- size (*rdflib.namespace.SDO* attribute), 289
- sizeGroup (*rdflib.namespace.SDO* attribute), 289
- SizeGroupEnumeration (*rdflib.namespace.SDO* attribute), 232
- SizeOrDuration (*rdflib.namespace.DCTERMS* attribute), 147
- SizeSpecification (*rdflib.namespace.SDO* attribute), 232
- sizeSystem (*rdflib.namespace.SDO* attribute), 289
- SizeSystemEnumeration (*rdflib.namespace.SDO* attribute), 232
- SizeSystemImperial (*rdflib.namespace.SDO* attribute), 232
- SizeSystemMetric (*rdflib.namespace.SDO* attribute), 232
- skills (*rdflib.namespace.SDO* attribute), 289
- Skin (*rdflib.namespace.SDO* attribute), 232
- skipBlankRows (*rdflib.namespace.CSVW* attribute), 140
- skipColumns (*rdflib.namespace.CSVW* attribute), 140
- skipInitialSpace (*rdflib.namespace.CSVW* attribute), 140
- skipRows (*rdflib.namespace.CSVW* attribute), 140
- skipSpace() (*rdflib.plugins.parsers.notation3.SinkParser* method), 332
- SkiResort (*rdflib.namespace.SDO* attribute), 232
- skolemize() (*rdflib.BNode* method), 576
- skolemize() (*rdflib.Graph* method), 599
- skolemize() (*rdflib.graph.Graph* method), 504
- skolemize() (*rdflib.term.BNode* method), 554
- SKOS (class in *rdflib.namespace*), 304
- sku (*rdflib.namespace.SDO* attribute), 289
- skypeID (*rdflib.namespace.FOAF* attribute), 153
- Slice (*rdflib.namespace.QB* attribute), 186
- slice (*rdflib.namespace.QB* attribute), 186
- SliceKey (*rdflib.namespace.QB* attribute), 186
- sliceKey (*rdflib.namespace.QB* attribute), 187
- sliceStructure (*rdflib.namespace.QB* attribute), 187
- slogan (*rdflib.namespace.SDO* attribute), 289
- smiles (*rdflib.namespace.SDO* attribute), 289
- Smoke\_Alarm (*rdflib.namespace.BRICK* attribute), 123
- Smoke\_Detection\_Alarm (*rdflib.namespace.BRICK* attribute), 123
- smokingAllowed (*rdflib.namespace.SDO* attribute), 289
- SocialEvent (*rdflib.namespace.SDO* attribute), 232
- SocialMediaPosting (*rdflib.namespace.SDO* attribute), 232
- sodiumContent (*rdflib.namespace.SDO* attribute), 289
- Software (*rdflib.namespace.DCMITYPE* attribute), 145
- softwareAddOn (*rdflib.namespace.SDO* attribute), 289
- SoftwareAgent (*rdflib.namespace.PROV* attribute), 179
- SoftwareApplication (*rdflib.namespace.SDO* attribute), 232
- softwareHelp (*rdflib.namespace.SDO* attribute), 289
- softwareRequirements (*rdflib.namespace.SDO* attribute), 289
- SoftwareSourceCode (*rdflib.namespace.SDO* attribute), 232
- softwareVersion (*rdflib.namespace.SDO* attribute), 289
- Solar\_Azimuth\_Angle\_Sensor (*rdflib.namespace.BRICK* attribute), 123
- Solar\_Radiance\_Sensor (*rdflib.namespace.BRICK* attribute), 124
- Solar\_Thermal\_Collector (*rdflib.namespace.BRICK* attribute), 124
- Solar\_Zenith\_Angle\_Sensor (*rdflib.namespace.BRICK* attribute), 124
- SoldOut (*rdflib.namespace.SDO* attribute), 232
- Solid (*rdflib.namespace.BRICK* attribute), 124

- `solution()` (*rdflib.plugins.sparql.sparql.QueryContext* method), 424
- `SolveMathAction` (*rdflib.namespace.SDO* attribute), 232
- `SomeProducts` (*rdflib.namespace.SDO* attribute), 232
- `someValuesFrom` (*rdflib.extras.infixowl.Restriction* property), 71
- `someValuesFrom` (*rdflib.namespace.OWL* attribute), 176
- `sortProperties()` (*rdflib.plugins.serializers.turtle.RecursiveSerializer* method), 362
- `SOSA` (class in *rdflib.namespace*), 306
- `Sound` (*rdflib.namespace.DCMITYPE* attribute), 145
- `SoundtrackAlbum` (*rdflib.namespace.SDO* attribute), 232
- `source` (*rdflib.namespace.CSVW* attribute), 140
- `source` (*rdflib.namespace.DC* attribute), 142
- `source` (*rdflib.namespace.DCTERMS* attribute), 148
- `source` (*rdflib.namespace.ODRL2* attribute), 169
- `source_to_json()` (in module *rdflib.plugins.shared.jsonld.util*), 371
- `sourceConstraint` (*rdflib.namespace.SH* attribute), 304
- `sourceConstraintComponent` (*rdflib.namespace.SH* attribute), 304
- `sourcedFrom` (*rdflib.namespace.SDO* attribute), 289
- `sourceIndividual` (*rdflib.namespace.OWL* attribute), 176
- `sourceOrganization` (*rdflib.namespace.SDO* attribute), 289
- `sourceShape` (*rdflib.namespace.SH* attribute), 304
- `Space` (*rdflib.namespace.BRICK* attribute), 124
- `Space_Heater` (*rdflib.namespace.BRICK* attribute), 124
- `sparql` (*rdflib.namespace.SH* attribute), 304
- `SPARQLAskExecutable` (*rdflib.namespace.SH* attribute), 300
- `SPARQLAskValidator` (*rdflib.namespace.SH* attribute), 300
- `SPARQLConnector` (class in *rdflib.plugins.stores.sparqlconnector*), 443
- `SPARQLConnectorException`, 444
- `SPARQLConstraint` (*rdflib.namespace.SH* attribute), 300
- `SPARQLConstraintComponent` (*rdflib.namespace.SH* attribute), 300
- `SPARQLConstructExecutable` (*rdflib.namespace.SH* attribute), 300
- `sparqlDirective()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 332
- `sparqlEndpoint` (*rdflib.namespace.VOID* attribute), 314
- `SPARQLError`, 424
- `SPARQLExecutable` (*rdflib.namespace.SH* attribute), 300
- `SPARQLFunction` (*rdflib.namespace.SH* attribute), 300
- `SPARQLProcessor` (class in *rdflib.plugins.sparql.processor*), 414
- `SPARQLResult` (class in *rdflib.plugins.sparql.processor*), 414
- `SPARQLRule` (*rdflib.namespace.SH* attribute), 300
- `SPARQLSelectExecutable` (*rdflib.namespace.SH* attribute), 300
- `SPARQLSelectValidator` (*rdflib.namespace.SH* attribute), 300
- `SPARQLStore` (class in *rdflib.plugins.stores.sparqlstore*), 445
- `SPARQLTarget` (*rdflib.namespace.SH* attribute), 300
- `SPARQLTargetType` (*rdflib.namespace.SH* attribute), 300
- `sparqlTok()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 332
- `SPARQLTypeError`, 424
- `SPARQLUpdateExecutable` (*rdflib.namespace.SH* attribute), 300
- `SPARQLUpdateProcessor` (class in *rdflib.plugins.sparql.processor*), 414
- `SPARQLUpdateStore` (class in *rdflib.plugins.stores.sparqlstore*), 451
- `SPARQLXMLWriter` (class in *rdflib.plugins.sparql.results.xmlresults*), 376
- `spatial` (*rdflib.namespace.DCTERMS* attribute), 148
- `spatial` (*rdflib.namespace.ODRL2* attribute), 169
- `spatial` (*rdflib.namespace.SDO* attribute), 289
- `spatialCoordinates` (*rdflib.namespace.ODRL2* attribute), 169
- `spatialCoverage` (*rdflib.namespace.SDO* attribute), 289
- `spatialDimension` (*rdflib.namespace.GEO* attribute), 156
- `SpatialObject` (*rdflib.namespace.GEO* attribute), 154
- `spatialResolutionInMeters` (*rdflib.namespace.DCAT* attribute), 144
- `SpatialThing` (*rdflib.namespace.WGS* attribute), 315
- `speakable` (*rdflib.namespace.SDO* attribute), 289
- `SpeakableSpecification` (*rdflib.namespace.SDO* attribute), 232
- `SpecialAnnouncement` (*rdflib.namespace.SDO* attribute), 232
- `specialCommitments` (*rdflib.namespace.SDO* attribute), 289
- `specializationOf` (*rdflib.namespace.PROV* attribute), 184
- `specialOpeningHoursSpecification` (*rdflib.namespace.SDO* attribute), 289
- `Specialty` (*rdflib.namespace.SDO* attribute), 232
- `specialty` (*rdflib.namespace.SDO* attribute), 290
- `Specification` (*rdflib.namespace.DOAP* attribute), 149

- SpeechPathology (rdflib.namespace.SDO attribute), 232
- speechToTextMarkup (rdflib.namespace.SDO attribute), 290
- speed (rdflib.namespace.SDO attribute), 290
- Speed\_Reset\_Command (rdflib.namespace.BRICK attribute), 124
- Speed\_Sensor (rdflib.namespace.BRICK attribute), 124
- Speed\_Setpoint (rdflib.namespace.BRICK attribute), 124
- Speed\_Setpoint\_Limit (rdflib.namespace.BRICK attribute), 124
- Speed\_Status (rdflib.namespace.BRICK attribute), 124
- split\_iri() (in module rdflib.plugins.shared.jsonld.util), 371
- split\_uri() (in module rdflib.namespace), 318
- splitFragPC() (in module rdflib.plugins.parsers.notation3), 336
- spokenByCharacter (rdflib.namespace.SDO attribute), 290
- SpokenWordAlbum (rdflib.namespace.SDO attribute), 232
- sponsor (rdflib.namespace.SDO attribute), 290
- sport (rdflib.namespace.SDO attribute), 290
- SportingGoodsStore (rdflib.namespace.SDO attribute), 232
- Sports\_Service\_Room (rdflib.namespace.BRICK attribute), 124
- SportsActivityLocation (rdflib.namespace.SDO attribute), 233
- sportsActivityLocation (rdflib.namespace.SDO attribute), 290
- SportsClub (rdflib.namespace.SDO attribute), 233
- SportsEvent (rdflib.namespace.SDO attribute), 233
- sportsEvent (rdflib.namespace.SDO attribute), 290
- SportsOrganization (rdflib.namespace.SDO attribute), 233
- SportsTeam (rdflib.namespace.SDO attribute), 233
- sportsTeam (rdflib.namespace.SDO attribute), 290
- spouse (rdflib.namespace.SDO attribute), 290
- SpreadsheetDigitalDocument (rdflib.namespace.SDO attribute), 233
- SRP (rdflib.namespace.SDO attribute), 230
- SSN (class in rdflib.namespace), 308
- StadiumOrArena (rdflib.namespace.SDO attribute), 233
- stage (rdflib.namespace.SDO attribute), 290
- Stage\_Enable\_Command (rdflib.namespace.BRICK attribute), 124
- Stage\_Riser (rdflib.namespace.BRICK attribute), 124
- stageAsNumber (rdflib.namespace.SDO attribute), 290
- StagedContent (rdflib.namespace.SDO attribute), 233
- Stages\_Status (rdflib.namespace.BRICK attribute), 124
- StagesHealthAspect (rdflib.namespace.SDO attribute), 233
- Staircase (rdflib.namespace.BRICK attribute), 124
- Standard (rdflib.namespace.DCTERMS attribute), 147
- Standby\_CRAC (rdflib.namespace.BRICK attribute), 124
- Standby\_Fan (rdflib.namespace.BRICK attribute), 124
- Standby\_Glycool\_Unit\_On\_Off\_Status (rdflib.namespace.BRICK attribute), 124
- Standby\_Load\_Shed\_Command (rdflib.namespace.BRICK attribute), 124
- Standby\_Unit\_On\_Off\_Status (rdflib.namespace.BRICK attribute), 125
- starRating (rdflib.namespace.SDO attribute), 290
- Start (rdflib.namespace.PROV attribute), 179
- start (rdflib.plugins.parsers.rdfxml.ElementHandler attribute), 343
- Start\_Stop\_Command (rdflib.namespace.BRICK attribute), 125
- Start\_Stop\_Status (rdflib.namespace.BRICK attribute), 125
- startDate (rdflib.namespace.DCAT attribute), 144
- startDate (rdflib.namespace.SDO attribute), 290
- startDoc() (rdflib.plugins.parsers.notation3.RDFSink method), 326
- startDoc() (rdflib.plugins.parsers.notation3.SinkParser method), 333
- startDocument() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 347
- startDocument() (rdflib.plugins.parsers.trix.TriXHandler method), 352
- startDocument() (rdflib.plugins.serializers.longturtle.LongTurtleSerializer method), 356
- startDocument() (rdflib.plugins.serializers.turtle.TurtleSerializer method), 363
- started (rdflib.namespace.PROV attribute), 184
- startedAtTime (rdflib.namespace.PROV attribute), 184
- startElementNS() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 347
- startElementNS() (rdflib.plugins.parsers.trix.TriXHandler method), 352
- startOffset (rdflib.namespace.SDO attribute), 290
- startPrefixMapping() (rdflib.plugins.parsers.rdfxml.RDFXMLHandler method), 347
- startPrefixMapping() (rdflib.plugins.parsers.trix.TriXHandler method), 352
- startswith() (rdflib.term.Identifier method), 557

- `startTime` (*rdflib.namespace.SDO* attribute), 290
- `State` (*rdflib.namespace.SDO* attribute), 233
- `Statement` (*rdflib.namespace.RDF* attribute), 187
- `Statement` (*rdflib.namespace.SDO* attribute), 233
- `statement()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 333
- `statement()` (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* method), 356
- `statement()` (*rdflib.plugins.serializers.n3.N3Serializer* method), 357
- `statement()` (*rdflib.plugins.serializers.turtle.TurtleSerializer* method), 363
- `Static_Pressure_Deadband_Setpoint` (*rdflib.namespace.BRICK* attribute), 125
- `Static_Pressure_Integral_Time_Parameter` (*rdflib.namespace.BRICK* attribute), 125
- `Static_Pressure_Proportional_Band_Parameter` (*rdflib.namespace.BRICK* attribute), 125
- `Static_Pressure_Sensor` (*rdflib.namespace.BRICK* attribute), 125
- `Static_Pressure_Setpoint` (*rdflib.namespace.BRICK* attribute), 125
- `Static_Pressure_Setpoint_Limit` (*rdflib.namespace.BRICK* attribute), 125
- `Static_Pressure_Step_Parameter` (*rdflib.namespace.BRICK* attribute), 125
- `StatisticalPopulation` (*rdflib.namespace.SDO* attribute), 233
- `Status` (*rdflib.namespace.BRICK* attribute), 125
- `status` (*rdflib.namespace.FOAF* attribute), 153
- `status` (*rdflib.namespace.ODRL2* attribute), 169
- `status` (*rdflib.namespace.SDO* attribute), 290
- `StatusEnumeration` (*rdflib.namespace.SDO* attribute), 233
- `Steam` (*rdflib.namespace.BRICK* attribute), 125
- `Steam_Baseboard_Radiator` (*rdflib.namespace.BRICK* attribute), 125
- `Steam_Distribution` (*rdflib.namespace.BRICK* attribute), 125
- `Steam_On_Off_Command` (*rdflib.namespace.BRICK* attribute), 125
- `Steam_Radiator` (*rdflib.namespace.BRICK* attribute), 125
- `Steam_System` (*rdflib.namespace.BRICK* attribute), 125
- `Steam_Usage_Sensor` (*rdflib.namespace.BRICK* attribute), 125
- `Steam_Valve` (*rdflib.namespace.BRICK* attribute), 125
- `steeringPosition` (*rdflib.namespace.SDO* attribute), 290
- `SteeringPositionValue` (*rdflib.namespace.SDO* attribute), 233
- `step` (*rdflib.namespace.SDO* attribute), 290
- `Step_Parameter` (*rdflib.namespace.BRICK* attribute), 125
- `steps` (*rdflib.namespace.SDO* attribute), 290
- `stepValue` (*rdflib.namespace.SDO* attribute), 290
- `StillImage` (*rdflib.namespace.DCMITYPE* attribute), 145
- `Stimulus` (*rdflib.namespace.SSN* attribute), 308
- `StopTraversal`, 387
- `StorageRoom` (*rdflib.namespace.BRICK* attribute), 126
- `storageRequirements` (*rdflib.namespace.SDO* attribute), 290
- `Store` (class in *rdflib.store*), 547
- `store` (*rdflib.Graph* property), 599
- `store` (*rdflib.graph.Graph* property), 504
- `store` (*rdflib.namespace.NamespaceManager* property), 163
- `Store` (*rdflib.namespace.SDO* attribute), 233
- `store` (*rdflib.plugins.serializers.hext.HexuplesSerializer* attribute), 354
- `store` (*rdflib.plugins.serializers.jsonld.JsonLDSerializer* attribute), 355
- `store` (*rdflib.plugins.serializers.longturtle.LongTurtleSerializer* attribute), 356
- `store` (*rdflib.plugins.serializers.n3.N3Serializer* attribute), 357
- `store` (*rdflib.plugins.serializers.nquads.NQuadsSerializer* attribute), 357
- `store` (*rdflib.plugins.serializers.nt.NTSerializer* attribute), 358
- `store` (*rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer* attribute), 359
- `store` (*rdflib.plugins.serializers.rdfxml.XMLSerializer* attribute), 359
- `store` (*rdflib.plugins.serializers.trig.TrigSerializer* attribute), 360
- `store` (*rdflib.plugins.serializers.trix.TriXSerializer* attribute), 361
- `store` (*rdflib.plugins.serializers.turtle.RecursiveSerializer* attribute), 362
- `store` (*rdflib.plugins.serializers.turtle.TurtleSerializer* attribute), 363
- `StoreCreatedEvent` (class in *rdflib.store*), 552
- `StoreCreditRefund` (*rdflib.namespace.SDO* attribute), 233
- `storedAt` (*rdflib.namespace.BRICK* attribute), 137
- `Storey` (*rdflib.namespace.BRICK* attribute), 126
- `strconst()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 333
- `stream` (*rdflib.namespace.ODRL2* attribute), 169
- `streetAddress` (*rdflib.namespace.SDO* attribute), 290
- `StrengthTraining` (*rdflib.namespace.SDO* attribute), 233
- `strengthUnit` (*rdflib.namespace.SDO* attribute), 290
- `strengthValue` (*rdflib.namespace.SDO* attribute), 290
- `string` (*rdflib.namespace.XSD* attribute), 318
- `String` (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore*



- attribute*), 452
- `string()` (in module `rdflib.plugins.sparql.operators`), 407
- `STRING_LITERAL1` (rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore *attribute*), 452
- `STRING_LITERAL2` (rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore *attribute*), 452
- `STRING_LITERAL_LONG1` (rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore *attribute*), 452
- `STRING_LITERAL_LONG2` (rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore *attribute*), 452
- `StringInputSource` (class in `rdflib.parser`), 518
- `structuralClass` (`rdflib.namespace.SDO` *attribute*), 290
- `structure` (`rdflib.namespace.QB` *attribute*), 187
- `StructuredValue` (`rdflib.namespace.SDO` *attribute*), 233
- `Studio` (`rdflib.namespace.BRICK` *attribute*), 126
- `StudioAlbum` (`rdflib.namespace.SDO` *attribute*), 233
- `study` (`rdflib.namespace.SDO` *attribute*), 290
- `studyDesign` (`rdflib.namespace.SDO` *attribute*), 291
- `studyLocation` (`rdflib.namespace.SDO` *attribute*), 291
- `studySubject` (`rdflib.namespace.SDO` *attribute*), 291
- `subClassOf` (`rdflib.extras.infixowl.Class` *property*), 64
- `subClassOf` (`rdflib.namespace.RDFS` *attribute*), 189
- `subcontext()` (`rdflib.plugins.shared.jsonld.context.Context` *method*), 368
- `subEvent` (`rdflib.namespace.SDO` *attribute*), 291
- `subEvents` (`rdflib.namespace.SDO` *attribute*), 291
- `subject` (`rdflib.namespace.DC` *attribute*), 142
- `subject` (`rdflib.namespace.DCTERMS` *attribute*), 149
- `subject` (`rdflib.namespace.RDF` *attribute*), 188
- `subject` (`rdflib.namespace.SH` *attribute*), 304
- `subject` (`rdflib.plugins.parsers.rdfxml.ElementHandler` *attribute*), 343
- `subject()` (`rdflib.plugins.parsers.notation3.SinkParser` *method*), 333
- `subject()` (`rdflib.plugins.parsers.ntriples.W3CNTriplesParser` *method*), 341
- `subject()` (`rdflib.plugins.serializers.rdfxml.PrettyXMLSerializer` *method*), 359
- `subject()` (`rdflib.plugins.serializers.rdfxml.XMLSerializer` *method*), 359
- `subject_objects()` (`rdflib.Graph` *method*), 599
- `subject_objects()` (`rdflib.graph.Graph` *method*), 504
- `subject_objects()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` *method*), 449
- `subject_objects()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` *method*), 456
- `subject_objects()` (`rdflib.resource.Resource` *method*), 545
- `subject_predicates()` (`rdflib.Graph` *method*), 600
- `subject_predicates()` (`rdflib.graph.Graph` *method*), 505
- `subject_predicates()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` *method*), 450
- `subject_predicates()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` *method*), 456
- `subject_predicates()` (`rdflib.resource.Resource` *method*), 545
- `subjectDone()` (`rdflib.plugins.serializers.turtle.RecursiveSerializer` *method*), 362
- `subjectOf` (`rdflib.namespace.SDO` *attribute*), 291
- `subjects()` (`rdflib.Graph` *method*), 600
- `subjects()` (`rdflib.graph.Graph` *method*), 505
- `subjects()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` *method*), 450
- `subjects()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` *method*), 456
- `subjects()` (`rdflib.resource.Resource` *method*), 545
- `subjectsTarget` (`rdflib.namespace.VOID` *attribute*), 314
- `Submit` (`rdflib.namespace.PROV` *attribute*), 180
- `subOrganization` (`rdflib.namespace.SDO` *attribute*), 291
- `subOrganizationOf` (`rdflib.namespace.ORG` *attribute*), 172
- `subPropertyOf` (`rdflib.extras.infixowl.Property` *property*), 70
- `subPropertyOf` (`rdflib.namespace.RDFS` *attribute*), 189
- `subReservation` (`rdflib.namespace.SDO` *attribute*), 291
- `subscribe()` (`rdflib.events.Dispatcher` *method*), 474
- `SubscribeAction` (`rdflib.namespace.SDO` *attribute*), 233
- `Subscription` (`rdflib.namespace.SDO` *attribute*), 233
- `subset` (`rdflib.namespace.VOID` *attribute*), 314
- `subStageSuffix` (`rdflib.namespace.SDO` *attribute*), 291
- `Substance` (`rdflib.namespace.BRICK` *attribute*), 126
- `Substance` (`rdflib.namespace.SDO` *attribute*), 233
- `subStructure` (`rdflib.namespace.SDO` *attribute*), 291
- `subSumpteeIds()` (`rdflib.extras.infixowl.Class` *method*), 64
- `subTest` (`rdflib.namespace.SDO` *attribute*), 291
- `subtitleLanguage` (`rdflib.namespace.SDO` *attribute*), 291
- `subTrip` (`rdflib.namespace.SDO` *attribute*), 291
- `SubwayStation` (`rdflib.namespace.SDO` *attribute*), 233
- `successorOf` (`rdflib.namespace.SDO` *attribute*), 291
- `sugarContent` (`rdflib.namespace.SDO` *attribute*), 291
- `suggestedAge` (`rdflib.namespace.SDO` *attribute*), 291



<code>suggestedAnswer</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Air_Static_Pressure_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>suggestedGender</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Air_Temperature_Alarm</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>suggestedMaxAge</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Air_Temperature_Deadband_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>suggestedMeasurement</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Air_Temperature_High_Reset_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>suggestedMinAge</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Air_Temperature_Low_Reset_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>suggestedShapesGraph</code> ( <code>rdflib.namespace.SH</code> attribute), 304	<code>Supply_Air_Temperature_Proportional_Band_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>suitableForDiet</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Air_Temperature_Reset_Differential_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Suite</code> ( <code>rdflib.namespace.SDO</code> attribute), 233	<code>Supply_Air_Temperature_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Sum</code> (class in <code>rdflib.plugins.sparql.aggregates</code> ), 385	<code>Supply_Air_Temperature_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Sunday</code> ( <code>rdflib.namespace.SDO</code> attribute), 233	<code>Supply_Air_Temperature_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Sunday</code> ( <code>rdflib.namespace.TIME</code> attribute), 309	<code>Supply_Air_Temperature_Step_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>superEvent</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Air_Velocity_Pressure_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>SuperficialAnatomy</code> ( <code>rdflib.namespace.SDO</code> attribute), 234	<code>Supply_Chilled_Water</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>supersededBy</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Chilled_Water_Temperature_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>supply</code> ( <code>rdflib.namespace.SDO</code> attribute), 291	<code>Supply_Condenser_Water</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Supply_Air</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Condenser_Water_Flow_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Supply_Air_Differential_Pressure_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Condenser_Water_Temperature_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Supply_Air_Differential_Pressure_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Condenser_Water_Temperature_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127
<code>Supply_Air_Duct_Pressure_Status</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Fan</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Flow_Demand_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Hot_Water</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Flow_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Hot_Water_Temperature_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Flow_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Humidity_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water_Differential_Pressure_Deadband_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Humidity_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water_Differential_Pressure_Integral_Time_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Integral_Gain_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water_Differential_Pressure_Proportional_Band_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Plenum</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water_Flow_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Proportional_Gain_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water_Flow_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Static_Pressure_Deadband_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water_Temperature_Alarm</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Static_Pressure_Integral_Time_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	<code>Supply_Water_Temperature_Deadband_Setpoint</code> ( <code>rdflib.namespace.BRICK</code> attribute), 128
<code>Supply_Air_Static_Pressure_Proportional_Band_Parameter</code> ( <code>rdflib.namespace.BRICK</code> attribute), 126	
<code>Supply_Air_Static_Pressure_Sensor</code> ( <code>rdflib.namespace.BRICK</code> attribute), 127	

- Supply\_Water\_Temperature\_Integral\_Time\_Parameter (rdflib.namespace.BRICK attribute), 128
  - Supply\_Water\_Temperature\_Proportional\_Band\_Parameter (rdflib.namespace.BRICK attribute), 128
  - Supply\_Water\_Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 128
  - supplyTo (rdflib.namespace.SDO attribute), 291
  - support (rdflib.namespace.ODRL2 attribute), 169
  - supportingData (rdflib.namespace.SDO attribute), 291
  - suppress\_warnings\_ (rdflib.plugins.sparql.parserutils.ParamList attribute), 412
  - suppressOutput (rdflib.namespace.CSVW attribute), 140
  - surface (rdflib.namespace.SDO attribute), 291
  - Surgical (rdflib.namespace.SDO attribute), 234
  - SurgicalProcedure (rdflib.namespace.SDO attribute), 234
  - surname (rdflib.namespace.FOAF attribute), 153
  - Surveillance\_Camera (rdflib.namespace.BRICK attribute), 128
  - SuspendAction (rdflib.namespace.SDO attribute), 234
  - Suspended (rdflib.namespace.SDO attribute), 234
  - SVNRepository (rdflib.namespace.DOAP attribute), 149
  - Switch (rdflib.namespace.BRICK attribute), 128
  - Switch\_Room (rdflib.namespace.BRICK attribute), 128
  - Switchgear (rdflib.namespace.BRICK attribute), 129
  - SymmetricProperty (rdflib.namespace.OWL attribute), 174
  - SymptomsHealthAspect (rdflib.namespace.SDO attribute), 234
  - Synagogue (rdflib.namespace.SDO attribute), 234
  - sync() (rdflib.plugins.stores.berkeleydb.BerkeleyDB method), 435
  - synchronize (rdflib.namespace.ODRL2 attribute), 169
  - System (rdflib.namespace.BRICK attribute), 129
  - system (rdflib.namespace.ODRL2 attribute), 170
  - System (rdflib.namespace.SSN attribute), 308
  - System\_Enable\_Command (rdflib.namespace.BRICK attribute), 129
  - System\_Shutdown\_Status (rdflib.namespace.BRICK attribute), 129
  - System\_Status (rdflib.namespace.BRICK attribute), 129
  - systemDevice (rdflib.namespace.ODRL2 attribute), 170
- ## T
- Table (rdflib.namespace.CSVW attribute), 138
  - table (rdflib.namespace.CSVW attribute), 140
  - Table (rdflib.namespace.SDO attribute), 234
  - tableDirection (rdflib.namespace.CSVW attribute), 140
  - TableGroup (rdflib.namespace.CSVW attribute), 138
  - TableOfContents (rdflib.namespace.DCTERMS attribute), 149
  - TableReference (rdflib.namespace.CSVW attribute), 138
  - tableSchema (rdflib.namespace.CSVW attribute), 140
  - TABS\_Panel (rdflib.namespace.BRICK attribute), 129
  - tabularMetadata (rdflib.namespace.CSVW attribute), 140
  - TakeAction (rdflib.namespace.SDO attribute), 234
  - target (rdflib.namespace.ODRL2 attribute), 170
  - target (rdflib.namespace.SDO attribute), 291
  - Target (rdflib.namespace.SH attribute), 300
  - target (rdflib.namespace.SH attribute), 304
  - target (rdflib.namespace.VOID attribute), 314
  - targetClass (rdflib.namespace.SH attribute), 304
  - targetCollection (rdflib.namespace.SDO attribute), 292
  - targetDescription (rdflib.namespace.SDO attribute), 292
  - targetFormat (rdflib.namespace.CSVW attribute), 140
  - targetIndividual (rdflib.namespace.OWL attribute), 176
  - targetName (rdflib.namespace.SDO attribute), 292
  - targetNode (rdflib.namespace.SH attribute), 304
  - targetObjectsOf (rdflib.namespace.SH attribute), 304
  - targetPlatform (rdflib.namespace.SDO attribute), 292
  - targetPopulation (rdflib.namespace.SDO attribute), 292
  - targetProduct (rdflib.namespace.SDO attribute), 292
  - targetSubjectsOf (rdflib.namespace.SH attribute), 304
  - TargetType (rdflib.namespace.SH attribute), 300
  - targetUrl (rdflib.namespace.SDO attribute), 292
  - targetValue (rdflib.namespace.OWL attribute), 176
  - TattooParlor (rdflib.namespace.SDO attribute), 234
  - Taxi (rdflib.namespace.SDO attribute), 234
  - taxID (rdflib.namespace.SDO attribute), 292
  - TaxiReservation (rdflib.namespace.SDO attribute), 234
  - TaxiService (rdflib.namespace.SDO attribute), 234
  - TaxiStand (rdflib.namespace.SDO attribute), 234
  - TaxiVehicleUsage (rdflib.namespace.SDO attribute), 234
  - Taxon (rdflib.namespace.SDO attribute), 234
  - taxonomicRange (rdflib.namespace.SDO attribute), 292
  - taxonRank (rdflib.namespace.SDO attribute), 292
  - teaches (rdflib.namespace.SDO attribute), 292
  - Team\_Room (rdflib.namespace.BRICK attribute), 129
  - TechArticle (rdflib.namespace.SDO attribute), 234
  - TechnicalFeature (rdflib.namespace.VOID attribute), 313
  - Telecom\_Room (rdflib.namespace.BRICK attribute), 129
  - telephone (rdflib.namespace.SDO attribute), 292

- TelevisionChannel (rdflib.namespace.SDO attribute), 234
- TelevisionStation (rdflib.namespace.SDO attribute), 234
- Temperature\_Alarm (rdflib.namespace.BRICK attribute), 129
- Temperature\_Deadband\_Setpoint (rdflib.namespace.BRICK attribute), 129
- Temperature\_Differential\_Reset\_Setpoint (rdflib.namespace.BRICK attribute), 129
- Temperature\_High\_Reset\_Setpoint (rdflib.namespace.BRICK attribute), 129
- Temperature\_Low\_Reset\_Setpoint (rdflib.namespace.BRICK attribute), 129
- Temperature\_Parameter (rdflib.namespace.BRICK attribute), 129
- Temperature\_Sensor (rdflib.namespace.BRICK attribute), 129
- Temperature\_Setpoint (rdflib.namespace.BRICK attribute), 129
- Temperature\_Step\_Parameter (rdflib.namespace.BRICK attribute), 130
- Temperature\_Tolerance\_Parameter (rdflib.namespace.BRICK attribute), 130
- temperatureCoefficientofPmax (rdflib.namespace.BRICK attribute), 137
- temporal (rdflib.namespace.DCTERMS attribute), 149
- temporal (rdflib.namespace.SDO attribute), 292
- temporalCoverage (rdflib.namespace.SDO attribute), 292
- TemporalDuration (rdflib.namespace.TIME attribute), 310
- TemporalEntity (rdflib.namespace.TIME attribute), 310
- TemporalPosition (rdflib.namespace.TIME attribute), 310
- temporalResolution (rdflib.namespace.DCAT attribute), 144
- TemporalUnit (rdflib.namespace.TIME attribute), 310
- Temporary\_Occupancy\_Status (rdflib.namespace.BRICK attribute), 130
- TennisComplex (rdflib.namespace.SDO attribute), 234
- Term (class in rdflib.plugins.shared.jsonld.context), 369
- term() (rdflib.extras.infixowl.ClassNamespaceFactory method), 64
- term() (rdflib.Namespace method), 615
- term() (rdflib.namespace.ClosedNamespace method), 142
- term() (rdflib.namespace.Namespace method), 157
- termCode (rdflib.namespace.SDO attribute), 292
- termDuration (rdflib.namespace.SDO attribute), 292
- termGroup (rdflib.namespace.VANN attribute), 313
- Terminal\_Unit (rdflib.namespace.BRICK attribute), 130
- Terminated (rdflib.namespace.SDO attribute), 234
- termsOfService (rdflib.namespace.SDO attribute), 292
- termsPerYear (rdflib.namespace.SDO attribute), 292
- termToJson() (in module rdflib.plugins.sparql.results.jsonresults), 374
- tester (rdflib.namespace.DOAP attribute), 150
- TETRA\_Room (rdflib.namespace.BRICK attribute), 129
- Text (rdflib.namespace.DCMITYPE attribute), 145
- Text (rdflib.namespace.SDO attribute), 234
- text (rdflib.namespace.SDO attribute), 292
- text() (rdflib.plugins.serializers.xmlwriter.XMLWriter method), 364
- TextDigitalDocument (rdflib.namespace.SDO attribute), 234
- textDirection (rdflib.namespace.CSVW attribute), 140
- textToSpeech (rdflib.namespace.ODRL2 attribute), 170
- textValue (rdflib.namespace.SDO attribute), 292
- TGN (rdflib.namespace.DCTERMS attribute), 147
- thaw() (rdflib.plugins.sparql.sparql.QueryContext method), 424
- TheaterEvent (rdflib.namespace.SDO attribute), 235
- TheaterGroup (rdflib.namespace.SDO attribute), 235
- theme (rdflib.namespace.DCAT attribute), 144
- theme (rdflib.namespace.FOAF attribute), 153
- themeTaxonomy (rdflib.namespace.DCAT attribute), 144
- Therapeutic (rdflib.namespace.SDO attribute), 235
- TherapeuticProcedure (rdflib.namespace.SDO attribute), 235
- Thermal\_Power\_Meter (rdflib.namespace.BRICK attribute), 130
- Thermal\_Power\_Sensor (rdflib.namespace.BRICK attribute), 130
- Thermally\_Activated\_Building\_System\_Panel (rdflib.namespace.BRICK attribute), 130
- thermalTransmittance (rdflib.namespace.BRICK attribute), 137
- Thermostat (rdflib.namespace.BRICK attribute), 130
- Thesis (rdflib.namespace.SDO attribute), 235
- Thing (rdflib.namespace.OWL attribute), 174
- Thing (rdflib.namespace.SDO attribute), 235
- this (rdflib.namespace.SH attribute), 304
- Throat (rdflib.namespace.SDO attribute), 235
- thumbnail (rdflib.namespace.FOAF attribute), 153
- thumbnail (rdflib.namespace.SDO attribute), 292
- thumbnailUrl (rdflib.namespace.SDO attribute), 292
- Thursday (rdflib.namespace.SDO attribute), 235
- Thursday (rdflib.namespace.TIME attribute), 310
- tickerSymbol (rdflib.namespace.SDO attribute), 292
- Ticket (rdflib.namespace.ODRL2 attribute), 164
- Ticket (rdflib.namespace.SDO attribute), 235
- ticketedSeat (rdflib.namespace.SDO attribute), 292
- Ticketing\_Booth (rdflib.namespace.BRICK attribute), 130
- ticketNumber (rdflib.namespace.SDO attribute), 292



- `ticketToken` (*rdflib.namespace.SDO* attribute), 292
- `TieAction` (*rdflib.namespace.SDO* attribute), 235
- `tilt` (*rdflib.namespace.BRICK* attribute), 137
- `TIME` (class in *rdflib.namespace*), 309
- `Time` (*rdflib.namespace.SDO* attribute), 235
- `time` (*rdflib.namespace.XSD* attribute), 318
- `Time_Parameter` (*rdflib.namespace.BRICK* attribute), 130
- `Time_Setpoint` (*rdflib.namespace.BRICK* attribute), 130
- `timedCount` (*rdflib.namespace.ODRL2* attribute), 170
- `timeInterval` (*rdflib.namespace.ODRL2* attribute), 170
- `timeOfDay` (*rdflib.namespace.SDO* attribute), 292
- `TimePosition` (*rdflib.namespace.TIME* attribute), 310
- `timeRequired` (*rdflib.namespace.SDO* attribute), 292
- `timeseries` (*rdflib.namespace.BRICK* attribute), 137
- `timeToComplete` (*rdflib.namespace.SDO* attribute), 293
- `TimeZone` (*rdflib.namespace.TIME* attribute), 310
- `timeZone` (*rdflib.namespace.TIME* attribute), 312
- `timezoneOffset` (*rdflib.namespace.XSD* attribute), 318
- `TipAction` (*rdflib.namespace.SDO* attribute), 235
- `tipjar` (*rdflib.namespace.FOAF* attribute), 153
- `TireShop` (*rdflib.namespace.SDO* attribute), 235
- `tissueSample` (*rdflib.namespace.SDO* attribute), 293
- `title` (*rdflib.Namespace* property), 615
- `title` (*rdflib.namespace.CSVW* attribute), 140
- `title` (*rdflib.namespace.DC* attribute), 142
- `title` (*rdflib.namespace.DCTERMS* attribute), 149
- `title` (*rdflib.namespace.FOAF* attribute), 153
- `title` (*rdflib.namespace.Namespace* property), 157
- `title` (*rdflib.namespace.SDO* attribute), 293
- `titleEIDR` (*rdflib.namespace.SDO* attribute), 293
- `to_canonical_graph()` (in module *rdflib.compare*), 469
- `to_dict()` (*rdflib.plugins.shared.jsonld.context.Context* method), 369
- `to_isomorphic()` (in module *rdflib.compare*), 469
- `to_rdf()` (in module *rdflib.plugins.parsers.jsonld*), 321
- `to_symbol()` (*rdflib.plugins.shared.jsonld.context.Context* method), 369
- `to_term()` (in module *rdflib.util*), 573
- `tocContinuation` (*rdflib.namespace.SDO* attribute), 293
- `tocEntry` (*rdflib.namespace.SDO* attribute), 293
- `todo` (*rdflib.namespace.PROV* attribute), 184
- `tok()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 333
- `token` (*rdflib.namespace.XSD* attribute), 318
- `Tolerance_Parameter` (*rdflib.namespace.BRICK* attribute), 130
- `TollFree` (*rdflib.namespace.SDO* attribute), 235
- `toLocation` (*rdflib.namespace.SDO* attribute), 293
- `ToMultiSet()` (in module *rdflib.plugins.sparql.algebra*), 388
- `tongueWeight` (*rdflib.namespace.SDO* attribute), 293
- `tool` (*rdflib.namespace.SDO* attribute), 293
- `topClasses` (*rdflib.plugins.serializers.turtle.RecursiveSerializer* attribute), 362
- `topConceptOf` (*rdflib.namespace.SKOS* attribute), 306
- `topDataProperty` (*rdflib.namespace.OWL* attribute), 176
- `topic` (*rdflib.namespace.FOAF* attribute), 153
- `topic_interest` (*rdflib.namespace.FOAF* attribute), 153
- `topObjectProperty` (*rdflib.namespace.OWL* attribute), 176
- `toPython()` (*rdflib.Graph* method), 600
- `toPython()` (*rdflib.graph.Graph* method), 505
- `toPython()` (*rdflib.graph.Seq* method), 515
- `toPython()` (*rdflib.IdentifiedNode* method), 603
- `toPython()` (*rdflib.Literal* method), 613
- `toPython()` (*rdflib.term.IdentifiedNode* method), 555
- `toPython()` (*rdflib.term.Literal* method), 566
- `toPython()` (*rdflib.term.Variable* method), 569
- `toPython()` (*rdflib.Variable* method), 618
- `toRecipient` (*rdflib.namespace.SDO* attribute), 293
- `torque` (*rdflib.namespace.SDO* attribute), 293
- `Torque_Sensor` (*rdflib.namespace.BRICK* attribute), 130
- `totalDigits` (*rdflib.namespace.XSD* attribute), 318
- `totalJobOpenings` (*rdflib.namespace.SDO* attribute), 293
- `totalPaymentDue` (*rdflib.namespace.SDO* attribute), 293
- `totalPrice` (*rdflib.namespace.SDO* attribute), 293
- `totalTime` (*rdflib.namespace.SDO* attribute), 293
- `Touchpanel` (*rdflib.namespace.BRICK* attribute), 130
- `tourBookingPage` (*rdflib.namespace.SDO* attribute), 293
- `TouristAttraction` (*rdflib.namespace.SDO* attribute), 235
- `TouristDestination` (*rdflib.namespace.SDO* attribute), 235
- `TouristInformationCenter` (*rdflib.namespace.SDO* attribute), 235
- `TouristTrip` (*rdflib.namespace.SDO* attribute), 235
- `touristType` (*rdflib.namespace.SDO* attribute), 293
- `Toxicologic` (*rdflib.namespace.SDO* attribute), 235
- `ToyStore` (*rdflib.namespace.SDO* attribute), 235
- `Trace_Heat_Sensor` (*rdflib.namespace.BRICK* attribute), 130
- `track` (*rdflib.namespace.SDO* attribute), 293
- `TrackAction` (*rdflib.namespace.SDO* attribute), 235
- `trackedParty` (*rdflib.namespace.ODRL2* attribute), 170
- `trackingNumber` (*rdflib.namespace.SDO* attribute), 293
- `trackingParty` (*rdflib.namespace.ODRL2* attribute), 170
- `trackingUrl` (*rdflib.namespace.SDO* attribute), 293

- `tracks` (*rdflib.namespace.SDO* attribute), 293
- `TradeAction` (*rdflib.namespace.SDO* attribute), 235
- `TraditionalChinese` (*rdflib.namespace.SDO* attribute), 235
- `trailer` (*rdflib.namespace.SDO* attribute), 293
- `trailerWeight` (*rdflib.namespace.SDO* attribute), 293
- `trainingSalary` (*rdflib.namespace.SDO* attribute), 293
- `trainName` (*rdflib.namespace.SDO* attribute), 293
- `trainNumber` (*rdflib.namespace.SDO* attribute), 293
- `TrainReservation` (*rdflib.namespace.SDO* attribute), 235
- `TrainStation` (*rdflib.namespace.SDO* attribute), 235
- `TrainTrip` (*rdflib.namespace.SDO* attribute), 235
- `transaction_aware` (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* attribute), 435
- `transaction_aware` (*rdflib.plugins.stores.sparqlstore.SPARQLStore* attribute), 450
- `transaction_aware` (*rdflib.store.Store* attribute), 551
- `transcript` (*rdflib.namespace.SDO* attribute), 293
- `transFatContent` (*rdflib.namespace.SDO* attribute), 293
- `transfer` (*rdflib.namespace.ODRL2* attribute), 170
- `TransferAction` (*rdflib.namespace.SDO* attribute), 236
- `transform` (*rdflib.namespace.ODRL2* attribute), 170
- `Transformation` (*rdflib.namespace.CSVW* attribute), 138
- `transformations` (*rdflib.namespace.CSVW* attribute), 140
- `TransformedContent` (*rdflib.namespace.SDO* attribute), 236
- `Transformer` (*rdflib.namespace.BRICK* attribute), 130
- `Transformer_Room` (*rdflib.namespace.BRICK* attribute), 130
- `transitive_objects()` (*rdflib.Graph* method), 601
- `transitive_objects()` (*rdflib.graph.Graph* method), 506
- `transitive_objects()` (*rdflib.resource.Resource* method), 545
- `transitive_subjects()` (*rdflib.Graph* method), 601
- `transitive_subjects()` (*rdflib.graph.Graph* method), 506
- `transitive_subjects()` (*rdflib.resource.Resource* method), 545
- `transitiveClosure()` (*rdflib.Graph* method), 600
- `transitiveClosure()` (*rdflib.graph.Graph* method), 505
- `TransitiveProperty` (*rdflib.namespace.OWL* attribute), 174
- `transitiveSubOrganizationOf` (*rdflib.namespace.ORG* attribute), 172
- `TransitMap` (*rdflib.namespace.SDO* attribute), 236
- `transitTime` (*rdflib.namespace.SDO* attribute), 293
- `transitTimeLabel` (*rdflib.namespace.SDO* attribute), 293
- `translate` (*rdflib.namespace.ODRL2* attribute), 170
- `translate()` (in module *rdflib.plugins.sparql.algebra*), 389
- `translateAggregates()` (in module *rdflib.plugins.sparql.algebra*), 389
- `translateAlgebra()` (in module *rdflib.plugins.sparql.algebra*), 389
- `translateExists()` (in module *rdflib.plugins.sparql.algebra*), 389
- `translateGraphGraphPattern()` (in module *rdflib.plugins.sparql.algebra*), 389
- `translateGroupGraphPattern()` (in module *rdflib.plugins.sparql.algebra*), 390
- `translateGroupOrUnionGraphPattern()` (in module *rdflib.plugins.sparql.algebra*), 390
- `translateInlineData()` (in module *rdflib.plugins.sparql.algebra*), 390
- `translatePath()` (in module *rdflib.plugins.sparql.algebra*), 390
- `translatePName()` (in module *rdflib.plugins.sparql.algebra*), 390
- `translatePrologue()` (in module *rdflib.plugins.sparql.algebra*), 390
- `translateQuads()` (in module *rdflib.plugins.sparql.algebra*), 390
- `translateQuery()` (in module *rdflib.plugins.sparql.algebra*), 391
- `translateUpdate()` (in module *rdflib.plugins.sparql.algebra*), 391
- `translateUpdate1()` (in module *rdflib.plugins.sparql.algebra*), 391
- `translateValues()` (in module *rdflib.plugins.sparql.algebra*), 391
- `translationOfWork` (*rdflib.namespace.SDO* attribute), 294
- `translator` (*rdflib.namespace.DOAP* attribute), 150
- `translator` (*rdflib.namespace.SDO* attribute), 294
- `transmissionMethod` (*rdflib.namespace.SDO* attribute), 294
- `TravelAction` (*rdflib.namespace.SDO* attribute), 236
- `TravelAgency` (*rdflib.namespace.SDO* attribute), 236
- `travelBans` (*rdflib.namespace.SDO* attribute), 294
- `traverse()` (in module *rdflib.plugins.sparql.algebra*), 391
- `TreatmentIndication` (*rdflib.namespace.SDO* attribute), 236
- `TreatmentsHealthAspect` (*rdflib.namespace.SDO* attribute), 236
- `trialDesign` (*rdflib.namespace.SDO* attribute), 294
- `tributary` (*rdflib.namespace.SDO* attribute), 294
- `TrigParser` (class in *rdflib.plugins.parsers.trig*), 348
- `TrigSerializer` (class in *rdflib.plugins.serializers.trig*), 348

- 360
- TrigSinkParser (class in *rdflib.plugins.parsers.trig*), 349
- trim (*rdflib.namespace.CSVW* attribute), 140
- Trip (*rdflib.namespace.SDO* attribute), 236
- triple() (*rdflib.plugins.parsers.ntriples.DummySink* method), 339
- triple() (*rdflib.plugins.parsers.ntriples.NTGraphSink* method), 339
- triple() (*rdflib.tools.csv2rdf.CSV2RDF* method), 459
- TripleAddedEvent (class in *rdflib.store*), 552
- TripleBlindedTrial (*rdflib.namespace.SDO* attribute), 236
- TripleRemovedEvent (class in *rdflib.store*), 553
- TripleRule (*rdflib.namespace.SH* attribute), 300
- triples (*rdflib.namespace.VOID* attribute), 314
- triples() (in module *rdflib.plugins.sparql.algebra*), 392
- triples() (*rdflib.ConjunctiveGraph* method), 579
- triples() (*rdflib.Graph* method), 602
- triples() (*rdflib.graph.ConjunctiveGraph* method), 485
- triples() (*rdflib.graph.Graph* method), 507
- triples() (*rdflib.graph.ReadOnlyGraphAggregate* method), 514
- triples() (*rdflib.plugins.stores.auditable.AuditableStore* method), 431
- triples() (*rdflib.plugins.stores.berkeleydb.BerkeleyDB* method), 435
- triples() (*rdflib.plugins.stores.concurrent.ConcurrentStore* method), 436
- triples() (*rdflib.plugins.stores.memory.Memory* method), 438
- triples() (*rdflib.plugins.stores.memory.SimpleMemory* method), 441
- triples() (*rdflib.plugins.stores.regexmatching.REGEXMatching* method), 442
- triples() (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 450
- triples() (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore* method), 456
- triples() (*rdflib.store.Store* method), 551
- triples\_choices() (*rdflib.ConjunctiveGraph* method), 580
- triples\_choices() (*rdflib.Graph* method), 602
- triples\_choices() (*rdflib.graph.ConjunctiveGraph* method), 485
- triples\_choices() (*rdflib.graph.Graph* method), 507
- triples\_choices() (*rdflib.graph.ReadOnlyGraphAggregate* method), 514
- triples\_choices() (*rdflib.plugins.stores.sparqlstore.SPARQLStore* method), 451
- triples\_choices() (*rdflib.store.Store* method), 552
- TriXHandler (class in *rdflib.plugins.parsers.trix*), 350
- TriXParser (class in *rdflib.plugins.parsers.trix*), 352
- TriXSerializer (class in *rdflib.plugins.serializers.trix*), 360
- TRS (*rdflib.namespace.TIME* attribute), 310
- TSVResultParser (class in *rdflib.plugins.sparql.results.tsvresults*), 375
- Tuesday (*rdflib.namespace.SDO* attribute), 236
- Tuesday (*rdflib.namespace.TIME* attribute), 310
- Tunnel (*rdflib.namespace.BRICK* attribute), 130
- TurtleParser (class in *rdflib.plugins.parsers.notation3*), 335
- TurtleSerializer (class in *rdflib.plugins.serializers.turtle*), 362
- TVClip (*rdflib.namespace.SDO* attribute), 234
- TVEpisode (*rdflib.namespace.SDO* attribute), 234
- TVOC\_Level\_Sensor (*rdflib.namespace.BRICK* attribute), 129
- TVOC\_Sensor (*rdflib.namespace.BRICK* attribute), 129
- TVSeason (*rdflib.namespace.SDO* attribute), 234
- TVSeries (*rdflib.namespace.SDO* attribute), 234
- TXTResultSerializer (class in *rdflib.plugins.sparql.results.txtresults*), 376
- type (*rdflib.extras.infixowl.Individual* property), 67
- type (*rdflib.namespace.DC* attribute), 143
- type (*rdflib.namespace.DCTERMS* attribute), 149
- type (*rdflib.namespace.RDF* attribute), 188
- type (*rdflib.plugins.shared.jsonld.context.Term* attribute), 370
- type\_key (*rdflib.plugins.shared.jsonld.context.Context* property), 369
- type\_of\_container() (*rdflib.container.Container* method), 473
- type\_promotion() (in module *rdflib.plugins.sparql.datatypes*), 392
- type\_safe\_numbers() (in module *rdflib.plugins.sparql.aggregates*), 385
- TypeAndQuantityNode (*rdflib.namespace.SDO* attribute), 236
- typeOfBed (*rdflib.namespace.SDO* attribute), 294
- typeOfGood (*rdflib.namespace.SDO* attribute), 294
- TypesHealthAspect (*rdflib.namespace.SDO* attribute), 236
- typicalAgeRange (*rdflib.namespace.SDO* attribute), 294
- typicalCreditsPerTerm (*rdflib.namespace.SDO* attribute), 294
- typicalTest (*rdflib.namespace.SDO* attribute), 294
- ## U
- UDC (*rdflib.namespace.DCTERMS* attribute), 147
- UEscape() (*rdflib.plugins.parsers.notation3.SinkParser* method), 327



- `uEscape()` (*rdflib.plugins.parsers.notation3.SinkParser* method), 334
- `uid` (*rdflib.namespace.ODRL2* attribute), 170
- `UKNonprofitType` (*rdflib.namespace.SDO* attribute), 236
- `UKTrust` (*rdflib.namespace.SDO* attribute), 236
- `Ultrasound` (*rdflib.namespace.SDO* attribute), 236
- `UnaryMinus()` (in module *rdflib.plugins.sparql.operators*), 405
- `UnaryNot()` (in module *rdflib.plugins.sparql.operators*), 405
- `UnaryPlus()` (in module *rdflib.plugins.sparql.operators*), 405
- `undefined` (*rdflib.namespace.ODRL2* attribute), 170
- `UndefinedTerm` (*rdflib.namespace.ODRL2* attribute), 164
- `Underfloor_Air_Plenum` (*rdflib.namespace.BRICK* attribute), 130
- `Underfloor_Air_Plenum_Static_Pressure_Sensor` (*rdflib.namespace.BRICK* attribute), 131
- `Underfloor_Air_Plenum_Static_Pressure_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Underfloor_Air_Temperature_Sensor` (*rdflib.namespace.BRICK* attribute), 131
- `underName` (*rdflib.namespace.SDO* attribute), 294
- `UnemploymentSupport` (*rdflib.namespace.SDO* attribute), 236
- `UnincorporatedAssociationCharity` (*rdflib.namespace.SDO* attribute), 236
- `uninstall` (*rdflib.namespace.ODRL2* attribute), 170
- `union` (*rdflib.namespace.SH* attribute), 304
- `Union()` (in module *rdflib.plugins.sparql.algebra*), 388
- `unionOf` (*rdflib.namespace.OWL* attribute), 176
- `uniq()` (in module *rdflib.util*), 573
- `uniqueLang` (*rdflib.namespace.SH* attribute), 304
- `UniqueLangConstraintComponent` (*rdflib.namespace.SH* attribute), 300
- `UniquenessError`, 476
- `uniqueURI()` (in module *rdflib.plugins.parsers.notation3*), 337
- `unit` (*rdflib.namespace.ODRL2* attribute), 170
- `Unit_Failure_Alarm` (*rdflib.namespace.BRICK* attribute), 131
- `unitCode` (*rdflib.namespace.SDO* attribute), 294
- `unitDay` (*rdflib.namespace.TIME* attribute), 312
- `unitHour` (*rdflib.namespace.TIME* attribute), 312
- `unitMinute` (*rdflib.namespace.TIME* attribute), 312
- `unitMonth` (*rdflib.namespace.TIME* attribute), 312
- `unitOf` (*rdflib.namespace.ORG* attribute), 172
- `unitOfCount` (*rdflib.namespace.ODRL2* attribute), 170
- `UnitPriceSpecification` (*rdflib.namespace.SDO* attribute), 236
- `unitSecond` (*rdflib.namespace.TIME* attribute), 312
- `unitText` (*rdflib.namespace.SDO* attribute), 294
- `unitType` (*rdflib.namespace.TIME* attribute), 313
- `unitWeek` (*rdflib.namespace.TIME* attribute), 313
- `unitYear` (*rdflib.namespace.TIME* attribute), 313
- `unnamedSourcesPolicy` (*rdflib.namespace.SDO* attribute), 294
- `Unoccupied_Air_Temperature_Cooling_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Air_Temperature_Heating_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Cooling_Discharge_Air_Flow_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Discharge_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Load_Shed_Command` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Return_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Room_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Supply_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `Unoccupied_Zone_Air_Temperature_Setpoint` (*rdflib.namespace.BRICK* attribute), 131
- `UnofficialLegalValue` (*rdflib.namespace.SDO* attribute), 236
- `unqualifiedForm` (*rdflib.namespace.PROV* attribute), 184
- `unquote()` (in module *rdflib.plugins.parsers.ntriples*), 341
- `unregister_custom_function()` (in module *rdflib.plugins.sparql.operators*), 408
- `UnRegisterAction` (*rdflib.namespace.SDO* attribute), 236
- `unsaturatedFatContent` (*rdflib.namespace.SDO* attribute), 294
- `unsignedByte` (*rdflib.namespace.XSD* attribute), 318
- `unsignedInt` (*rdflib.namespace.XSD* attribute), 318
- `unsignedLong` (*rdflib.namespace.XSD* attribute), 318
- `unsignedShort` (*rdflib.namespace.XSD* attribute), 318
- `UnsupportedAggregateOperation`, 515
- `Update` (class in *rdflib.plugins.sparql.sparql*), 425
- `update` (*rdflib.namespace.SH* attribute), 304
- `update()` (*rdflib.Graph* method), 602
- `update()` (*rdflib.graph.Graph* method), 507
- `update()` (*rdflib.plugins.sparql.aggregates.Aggregator* method), 381
- `update()` (*rdflib.plugins.sparql.aggregates.Average* method), 381
- `update()` (*rdflib.plugins.sparql.aggregates.Counter* method), 382
- `update()` (*rdflib.plugins.sparql.aggregates.Extremum* method), 383

- `update()` (`rdflib.plugins.sparql.aggregates.GroupConcat` method), 383
  - `update()` (`rdflib.plugins.sparql.aggregates.Sample` method), 385
  - `update()` (`rdflib.plugins.sparql.aggregates.Sum` method), 385
  - `update()` (`rdflib.plugins.sparql.processor.SPARQLUpdateProcessor` method), 415
  - `update()` (`rdflib.plugins.stores.memory.Memory` method), 439
  - `update()` (`rdflib.plugins.stores.memory.SimpleMemory` method), 441
  - `update()` (`rdflib.plugins.stores.sparqlconnector.SPARQLConnector` method), 444
  - `update()` (`rdflib.plugins.stores.sparqlstore.SPARQLStore` method), 451
  - `update()` (`rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore` method), 457
  - `update()` (`rdflib.query.UpdateProcessor` method), 538
  - `update()` (`rdflib.store.Store` method), 552
  - `UpdateAction` (`rdflib.namespace.SDO` attribute), 236
  - `UpdateProcessor` (class in `rdflib.query`), 537
  - `uploadDate` (`rdflib.namespace.SDO` attribute), 294
  - `upvoteCount` (`rdflib.namespace.SDO` attribute), 294
  - `uri` (`rdflib.namespace.ClosedNamespace` property), 142
  - `URI` (`rdflib.namespace.DCTERMS` attribute), 147
  - `uri_ref2()` (`rdflib.plugins.parsers.notation3.SinkParser` method), 334
  - `uriLookupEndpoint` (`rdflib.namespace.VOID` attribute), 314
  - `uriOf()` (`rdflib.plugins.parsers.notation3.SinkParser` method), 334
  - `uriquote()` (in module `rdflib.plugins.parsers.ntriples`), 342
  - `URIRef` (class in `rdflib`), 615
  - `URIRef` (class in `rdflib.term`), 566
  - `uriref()` (`rdflib.plugins.parsers.ntriples.W3CNTriplesParser` method), 341
  - `uriRegexPattern` (`rdflib.namespace.VOID` attribute), 314
  - `uriSpace` (`rdflib.namespace.VOID` attribute), 315
  - `uriTemplate` (`rdflib.namespace.CSVW` attribute), 140
  - `url` (`rdflib.namespace.CSVW` attribute), 140
  - `URL` (`rdflib.namespace.SDO` attribute), 236
  - `url` (`rdflib.namespace.SDO` attribute), 294
  - `URLInputSource` (class in `rdflib.parser`), 518
  - `urlTemplate` (`rdflib.namespace.SDO` attribute), 294
  - `Urologic` (`rdflib.namespace.SDO` attribute), 236
  - `Usage` (`rdflib.namespace.PROV` attribute), 180
  - `Usage_Sensor` (`rdflib.namespace.BRICK` attribute), 131
  - `usageInfo` (`rdflib.namespace.SDO` attribute), 294
  - `usageNote` (`rdflib.namespace.VANN` attribute), 313
  - `UsageOrScheduleHealthAspect` (`rdflib.namespace.SDO` attribute), 237
  - `use` (`rdflib.namespace.ODRL2` attribute), 170
  - `use_row()` (`rdflib.plugins.sparql.aggregates.Accumulator` method), 380
  - `use_row()` (`rdflib.plugins.sparql.aggregates.Counter` method), 382
  - `UseAction` (`rdflib.namespace.SDO` attribute), 237
  - `Used` (`rdflib.namespace.PROV` attribute), 184
  - `UsedCondition` (`rdflib.namespace.SDO` attribute), 237
  - `usedProcedure` (`rdflib.namespace.SOSA` attribute), 308
  - `usedToDiagnose` (`rdflib.namespace.SDO` attribute), 294
  - `UserBlocks` (`rdflib.namespace.SDO` attribute), 237
  - `UserCheckins` (`rdflib.namespace.SDO` attribute), 237
  - `UserComments` (`rdflib.namespace.SDO` attribute), 237
  - `UserDownloads` (`rdflib.namespace.SDO` attribute), 237
  - `UserInteraction` (`rdflib.namespace.SDO` attribute), 237
  - `UserInteractionCount` (`rdflib.namespace.SDO` attribute), 294
  - `UserLikes` (`rdflib.namespace.SDO` attribute), 237
  - `UserPageVisits` (`rdflib.namespace.SDO` attribute), 237
  - `UserPlays` (`rdflib.namespace.SDO` attribute), 237
  - `UserPlusOnes` (`rdflib.namespace.SDO` attribute), 237
  - `UserReview` (`rdflib.namespace.SDO` attribute), 237
  - `UserTweets` (`rdflib.namespace.SDO` attribute), 237
  - `usesDevice` (`rdflib.namespace.SDO` attribute), 294
  - `usesHealthPlanIdStandard` (`rdflib.namespace.SDO` attribute), 294
  - `USNonprofitType` (`rdflib.namespace.SDO` attribute), 236
  - `utterances` (`rdflib.namespace.SDO` attribute), 294
- ## V
- `valid` (`rdflib.namespace.DCTERMS` attribute), 149
  - `validate_namespace()` (in module `rdflib.tools.defined_namespace_creator`), 459
  - `validate_object_id()` (in module `rdflib.tools.defined_namespace_creator`), 460
  - `ValidationReport` (`rdflib.namespace.SH` attribute), 300
  - `ValidationResult` (`rdflib.namespace.SH` attribute), 300
  - `Validator` (`rdflib.namespace.SH` attribute), 301
  - `validator` (`rdflib.namespace.SH` attribute), 304
  - `validFor` (`rdflib.namespace.SDO` attribute), 295
  - `validFrom` (`rdflib.namespace.SDO` attribute), 295
  - `validIn` (`rdflib.namespace.SDO` attribute), 295
  - `validThrough` (`rdflib.namespace.SDO` attribute), 295
  - `validUntil` (`rdflib.namespace.SDO` attribute), 295
  - `value` (`rdflib.Literal` property), 613
  - `value` (`rdflib.namespace.BRICK` attribute), 137
  - `value` (`rdflib.namespace.PROV` attribute), 184
  - `value` (`rdflib.namespace.RDF` attribute), 188
  - `value` (`rdflib.namespace.SDO` attribute), 295
  - `value` (`rdflib.namespace.SH` attribute), 304



- `value` (`rdflib.plugins.sparql.aggregates.GroupConcat` attribute), 384
- `value` (`rdflib.plugins.sparql.aggregates.Maximum` attribute), 384
- `value` (`rdflib.plugins.sparql.aggregates.Minimum` attribute), 384
- `value` (`rdflib.term.Literal` property), 566
- `value()` (in module `rdflib.plugins.sparql.parserutils`), 413
- `value()` (`rdflib.extras.describer.Describer` method), 53
- `value()` (`rdflib.Graph` method), 602
- `value()` (`rdflib.graph.Graph` method), 507
- `value()` (`rdflib.resource.Resource` method), 545
- `value_key` (`rdflib.plugins.shared.jsonld.context.Context` property), 369
- `valueAddedTaxIncluded` (`rdflib.namespace.SDO` attribute), 295
- `valueMaxLength` (`rdflib.namespace.SDO` attribute), 295
- `valueMinLength` (`rdflib.namespace.SDO` attribute), 295
- `valueName` (`rdflib.namespace.SDO` attribute), 295
- `valuePattern` (`rdflib.namespace.SDO` attribute), 295
- `valueReference` (`rdflib.namespace.SDO` attribute), 295
- `valueRequired` (`rdflib.namespace.SDO` attribute), 295
- `Values()` (in module `rdflib.plugins.sparql.algebra`), 388
- `valueUrl` (`rdflib.namespace.CSVW` attribute), 140
- `Valve` (`rdflib.namespace.BRICK` attribute), 131
- `Valve_Command` (`rdflib.namespace.BRICK` attribute), 132
- `Valve_Position_Sensor` (`rdflib.namespace.BRICK` attribute), 132
- `VANN` (class in `rdflib.namespace`), 313
- `Variable` (class in `rdflib`), 617
- `Variable` (class in `rdflib.term`), 569
- `variable()` (`rdflib.plugins.parsers.notation3.SinkParser` method), 334
- `Variable_Air_Volume_Box` (`rdflib.namespace.BRICK` attribute), 132
- `Variable_Air_Volume_Box_With_Reheat` (`rdflib.namespace.BRICK` attribute), 132
- `Variable_Frequency_Drive` (`rdflib.namespace.BRICK` attribute), 132
- `variableMeasured` (`rdflib.namespace.SDO` attribute), 295
- `variantCover` (`rdflib.namespace.SDO` attribute), 295
- `variesBy` (`rdflib.namespace.SDO` attribute), 295
- `vars` (`rdflib.plugins.sparql.processor.SPARQLResult` attribute), 414
- `vars` (`rdflib.plugins.sparql.results.jsonresults.JSONResult` attribute), 373
- `vars` (`rdflib.plugins.sparql.results.rdfresults.RDFResult` attribute), 375
- `vars` (`rdflib.plugins.sparql.results.xmlresults.XMLResult` attribute), 378
- `vars` (`rdflib.query.Result` attribute), 534
- `vatID` (`rdflib.namespace.SDO` attribute), 295
- `VAV` (`rdflib.namespace.BRICK` attribute), 131
- `VeganDiet` (`rdflib.namespace.SDO` attribute), 237
- `VegetarianDiet` (`rdflib.namespace.SDO` attribute), 237
- `Vehicle` (`rdflib.namespace.SDO` attribute), 237
- `vehicleConfiguration` (`rdflib.namespace.SDO` attribute), 295
- `vehicleEngine` (`rdflib.namespace.SDO` attribute), 295
- `vehicleIdentificationNumber` (`rdflib.namespace.SDO` attribute), 295
- `vehicleInteriorColor` (`rdflib.namespace.SDO` attribute), 295
- `vehicleInteriorType` (`rdflib.namespace.SDO` attribute), 295
- `vehicleModelDate` (`rdflib.namespace.SDO` attribute), 295
- `vehicleSeatingCapacity` (`rdflib.namespace.SDO` attribute), 295
- `vehicleSpecialUsage` (`rdflib.namespace.SDO` attribute), 295
- `vehicleTransmission` (`rdflib.namespace.SDO` attribute), 296
- `Vein` (`rdflib.namespace.SDO` attribute), 237
- `Velocity_Pressure_Sensor` (`rdflib.namespace.BRICK` attribute), 132
- `Velocity_Pressure_Setpoint` (`rdflib.namespace.BRICK` attribute), 132
- `vendor` (`rdflib.namespace.DOAP` attribute), 150
- `vendor` (`rdflib.namespace.SDO` attribute), 296
- `Vent_Operating_Mode_Status` (`rdflib.namespace.BRICK` attribute), 132
- `Ventilation_Air_Flow_Ratio_Limit` (`rdflib.namespace.BRICK` attribute), 132
- `Ventilation_Air_System` (`rdflib.namespace.BRICK` attribute), 132
- `VenueMap` (`rdflib.namespace.SDO` attribute), 237
- `verb()` (`rdflib.plugins.parsers.notation3.SinkParser` method), 334
- `verb()` (`rdflib.plugins.serializers.longturtle.LongTurtleSerializer` method), 356
- `verb()` (`rdflib.plugins.serializers.turtle.TurtleSerializer` method), 363
- `verificationFactCheckingPolicy` (`rdflib.namespace.SDO` attribute), 296
- `Version` (`rdflib.namespace.DOAP` attribute), 149
- `version` (`rdflib.namespace.ODRL2` attribute), 170
- `version` (`rdflib.namespace.SDO` attribute), 296
- `versionInfo` (`rdflib.namespace.OWL` attribute), 176
- `versionIRI` (`rdflib.namespace.OWL` attribute), 176
- `Vertical_Space` (`rdflib.namespace.BRICK` attribute), 132
- `Vessel` (`rdflib.namespace.SDO` attribute), 237
- `VeterinaryCare` (`rdflib.namespace.SDO` attribute), 237
- `VFD` (`rdflib.namespace.BRICK` attribute), 131

- VFD\_Enable\_Command (rdflib.namespace.BRICK attribute), 131
- vhash() (rdflib.tools.graphisomorphism.IsomorphicTestable method), 460
- vhashtriple() (rdflib.tools.graphisomorphism.IsomorphicTestable method), 460
- vhashtriples() (rdflib.tools.graphisomorphism.IsomorphicTestable method), 460
- video (rdflib.namespace.SDO attribute), 296
- Video\_Intercom (rdflib.namespace.BRICK attribute), 132
- Video\_Surveillance\_Equipment (rdflib.namespace.BRICK attribute), 132
- videoFormat (rdflib.namespace.SDO attribute), 296
- videoFrameSize (rdflib.namespace.SDO attribute), 296
- VideoGallery (rdflib.namespace.SDO attribute), 237
- VideoGame (rdflib.namespace.SDO attribute), 237
- VideoGameClip (rdflib.namespace.SDO attribute), 237
- VideoGameSeries (rdflib.namespace.SDO attribute), 237
- VideoObject (rdflib.namespace.SDO attribute), 237
- VideoObjectSnapshot (rdflib.namespace.SDO attribute), 237
- videoQuality (rdflib.namespace.SDO attribute), 296
- ViewAction (rdflib.namespace.SDO attribute), 237
- VinylFormat (rdflib.namespace.SDO attribute), 237
- Violation (rdflib.namespace.SH attribute), 301
- virtual (rdflib.namespace.CSVW attribute), 140
- virtualLocation (rdflib.namespace.ODRL2 attribute), 170
- VirtualLocation (rdflib.namespace.SDO attribute), 238
- Virus (rdflib.namespace.SDO attribute), 238
- Visitor\_Lobby (rdflib.namespace.BRICK attribute), 132
- VisualArtsEvent (rdflib.namespace.SDO attribute), 238
- VisualArtwork (rdflib.namespace.SDO attribute), 238
- VitalSign (rdflib.namespace.SDO attribute), 238
- vocabulary (rdflib.namespace.VOID attribute), 315
- VocabularyEncodingScheme (rdflib.namespace.DCAM attribute), 143
- VOID (class in rdflib.namespace), 313
- Volcano (rdflib.namespace.SDO attribute), 238
- Voltage\_Imbalance\_Sensor (rdflib.namespace.BRICK attribute), 132
- Voltage\_Sensor (rdflib.namespace.BRICK attribute), 132
- volume (rdflib.namespace.BRICK attribute), 137
- volumeNumber (rdflib.namespace.SDO attribute), 296
- VoteAction (rdflib.namespace.SDO attribute), 238
- W3CDTF (rdflib.namespace.DCTERMS attribute), 147
- W3CNTriplesParser (class in rdflib.plugins.parsers.ntriples), 339
- Warning (rdflib.namespace.SDO attribute), 238
- Wardrobe (rdflib.namespace.BRICK attribute), 132
- WarmUpCoolDownAdjust\_Sensor (rdflib.namespace.BRICK attribute), 132
- Water (rdflib.namespace.BRICK attribute), 133
- Water\_Air\_Temperature\_Sensor (rdflib.namespace.BRICK attribute), 132
- warning (rdflib.namespace.SDO attribute), 296
- Warning (rdflib.namespace.SH attribute), 301
- warranty (rdflib.namespace.SDO attribute), 296
- WarrantyPromise (rdflib.namespace.SDO attribute), 238
- warrantyPromise (rdflib.namespace.SDO attribute), 296
- WarrantyScope (rdflib.namespace.SDO attribute), 238
- warrantyScope (rdflib.namespace.SDO attribute), 296
- wasActivityOfInfluence (rdflib.namespace.PROV attribute), 184
- wasAssociatedWith (rdflib.namespace.PROV attribute), 184
- wasAssociateFor (rdflib.namespace.PROV attribute), 184
- wasAttributedTo (rdflib.namespace.PROV attribute), 184
- wasDerivedFrom (rdflib.namespace.PROV attribute), 184
- wasEndedBy (rdflib.namespace.PROV attribute), 184
- wasGeneratedBy (rdflib.namespace.PROV attribute), 184
- wasInfluencedBy (rdflib.namespace.PROV attribute), 184
- wasInformedBy (rdflib.namespace.PROV attribute), 184
- wasInvalidatedBy (rdflib.namespace.PROV attribute), 184
- wasMemberOf (rdflib.namespace.PROV attribute), 184
- wasOriginatedBy (rdflib.namespace.SSN attribute), 309
- wasPlanOf (rdflib.namespace.PROV attribute), 184
- wasPrimarySourceOf (rdflib.namespace.PROV attribute), 185
- wasQuotedFrom (rdflib.namespace.PROV attribute), 185
- wasRevisionOf (rdflib.namespace.PROV attribute), 185
- wasRoleIn (rdflib.namespace.PROV attribute), 185
- wasStartedBy (rdflib.namespace.PROV attribute), 185
- Waste\_Storage (rdflib.namespace.BRICK attribute), 133
- wasUsedBy (rdflib.namespace.PROV attribute), 185
- wasUsedInDerivation (rdflib.namespace.PROV attribute), 185
- WatchAction (rdflib.namespace.SDO attribute), 238
- Water (rdflib.namespace.BRICK attribute), 133
- Water\_Alarm (rdflib.namespace.BRICK attribute), 133
- Water\_Differential\_Pressure\_Setpoint (rdflib.namespace.BRICK attribute), 133

## W

Water_Differential_Temperature_Sensor	(rdflib.namespace.BRICK attribute), 133	flib.namespace.SDO attribute), 239
Water_Differential_Temperature_Setpoint	(rdflib.namespace.BRICK attribute), 133	WearableMeasurementWaist (rdflib.namespace.SDO attribute), 239
Water_Distribution	(rdflib.namespace.BRICK attribute), 133	WearableMeasurementWidth (rdflib.namespace.SDO attribute), 239
Water_Flow_Sensor	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupBig (rdflib.namespace.SDO attribute), 239
Water_Flow_Setpoint	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupBoys (rdflib.namespace.SDO attribute), 239
Water_Heater	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupEnumeration (rdflib.namespace.SDO attribute), 239
Water_Level_Alarm	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupExtraShort (rdflib.namespace.SDO attribute), 239
Water_Level_Sensor	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupExtraTall (rdflib.namespace.SDO attribute), 239
Water_Loop	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupGirls (rdflib.namespace.SDO attribute), 239
Water_Loss_Alarm	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupHusky (rdflib.namespace.SDO attribute), 239
Water_Meter	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupInfants (rdflib.namespace.SDO attribute), 239
Water_Pump	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupJuniors (rdflib.namespace.SDO attribute), 239
Water_System	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupMaternity (rdflib.namespace.SDO attribute), 239
Water_Tank	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupMens (rdflib.namespace.SDO attribute), 239
Water_Temperature_Alarm	(rdflib.namespace.BRICK attribute), 133	WearableSizeGroupMisses (rdflib.namespace.SDO attribute), 239
Water_Temperature_Sensor	(rdflib.namespace.BRICK attribute), 134	WearableSizeGroupPetite (rdflib.namespace.SDO attribute), 239
Water_Temperature_Setpoint	(rdflib.namespace.BRICK attribute), 134	WearableSizeGroupPlus (rdflib.namespace.SDO attribute), 239
Water_Usage_Sensor	(rdflib.namespace.BRICK attribute), 134	WearableSizeGroupRegular (rdflib.namespace.SDO attribute), 239
Water_Valve	(rdflib.namespace.BRICK attribute), 134	WearableSizeGroupShort (rdflib.namespace.SDO attribute), 240
Waterfall	(rdflib.namespace.SDO attribute), 238	WearableSizeGroupTall (rdflib.namespace.SDO attribute), 240
watermark	(rdflib.namespace.ODRL2 attribute), 170	WearableSizeGroupWomens (rdflib.namespace.SDO attribute), 240
WearableMeasurementBack	(rdflib.namespace.SDO attribute), 238	WearableSizeSystemAU (rdflib.namespace.SDO attribute), 240
WearableMeasurementChestOrBust	(rdflib.namespace.SDO attribute), 238	WearableSizeSystemBR (rdflib.namespace.SDO attribute), 240
WearableMeasurementCollar	(rdflib.namespace.SDO attribute), 238	WearableSizeSystemCN (rdflib.namespace.SDO attribute), 240
WearableMeasurementCup	(rdflib.namespace.SDO attribute), 238	WearableSizeSystemContinental (rdflib.namespace.SDO attribute), 240
WearableMeasurementHeight	(rdflib.namespace.SDO attribute), 238	WearableSizeSystemDE (rdflib.namespace.SDO attribute), 240
WearableMeasurementHips	(rdflib.namespace.SDO attribute), 238	WearableSizeSystemEN13402 (rdflib.namespace.SDO attribute), 240
WearableMeasurementInseam	(rdflib.namespace.SDO attribute), 238	WearableSizeSystemEnumeration (rdflib.namespace.SDO attribute), 240
WearableMeasurementLength	(rdflib.namespace.SDO attribute), 238	
WearableMeasurementOutsideLeg	(rdflib.namespace.SDO attribute), 238	
WearableMeasurementSleeve	(rdflib.namespace.SDO attribute), 239	
WearableMeasurementTypeEnumeration	(rdflib.namespace.SDO attribute), 239	

- flib.namespace.SDO attribute*), 240
- WearableSizeSystemEurope (*rdflib.namespace.SDO attribute*), 240
- WearableSizeSystemFR (*rdflib.namespace.SDO attribute*), 240
- WearableSizeSystemGS1 (*rdflib.namespace.SDO attribute*), 240
- WearableSizeSystemIT (*rdflib.namespace.SDO attribute*), 240
- WearableSizeSystemJP (*rdflib.namespace.SDO attribute*), 240
- WearableSizeSystemMX (*rdflib.namespace.SDO attribute*), 240
- WearableSizeSystemUK (*rdflib.namespace.SDO attribute*), 240
- WearableSizeSystemUS (*rdflib.namespace.SDO attribute*), 240
- WearAction (*rdflib.namespace.SDO attribute*), 238
- Weather\_Station (*rdflib.namespace.BRICK attribute*), 134
- WebAPI (*rdflib.namespace.SDO attribute*), 240
- WebApplication (*rdflib.namespace.SDO attribute*), 241
- webCheckinTime (*rdflib.namespace.SDO attribute*), 296
- WebContent (*rdflib.namespace.SDO attribute*), 241
- webFeed (*rdflib.namespace.SDO attribute*), 296
- weblog (*rdflib.namespace.FOAF attribute*), 153
- WebPage (*rdflib.namespace.SDO attribute*), 241
- WebPageElement (*rdflib.namespace.SDO attribute*), 241
- WebSite (*rdflib.namespace.SDO attribute*), 241
- Wednesday (*rdflib.namespace.SDO attribute*), 241
- Wednesday (*rdflib.namespace.TIME attribute*), 310
- week (*rdflib.namespace.TIME attribute*), 313
- weeks (*rdflib.namespace.TIME attribute*), 313
- weight (*rdflib.namespace.SDO attribute*), 296
- weightTotal (*rdflib.namespace.SDO attribute*), 296
- WesternConventional (*rdflib.namespace.SDO attribute*), 241
- WGS (*class in rdflib.namespace*), 315
- wheelbase (*rdflib.namespace.SDO attribute*), 296
- where\_pattern (*rdflib.plugins.stores.sparqlstore.SPARQLUpdateStore method*), 377
- attribute*), 458
- whiteSpace (*rdflib.namespace.XSD attribute*), 318
- Wholesale (*rdflib.namespace.SDO attribute*), 241
- WholesaleStore (*rdflib.namespace.SDO attribute*), 241
- width (*rdflib.namespace.SDO attribute*), 296
- wiki (*rdflib.namespace.DOAP attribute*), 150
- WinAction (*rdflib.namespace.SDO attribute*), 241
- Wind\_Direction\_Sensor (*rdflib.namespace.BRICK attribute*), 134
- Wind\_Speed\_Sensor (*rdflib.namespace.BRICK attribute*), 134
- Winery (*rdflib.namespace.SDO attribute*), 241
- Wing (*rdflib.namespace.BRICK attribute*), 134
- winner (*rdflib.namespace.SDO attribute*), 296
- Withdrawn (*rdflib.namespace.SDO attribute*), 241
- withRestrictions (*rdflib.namespace.OWL attribute*), 176
- wktLiteral (*rdflib.namespace.GEO attribute*), 156
- wordCount (*rdflib.namespace.SDO attribute*), 296
- WorkBasedProgram (*rdflib.namespace.SDO attribute*), 241
- WorkersUnion (*rdflib.namespace.SDO attribute*), 241
- workExample (*rdflib.namespace.SDO attribute*), 296
- workFeatured (*rdflib.namespace.SDO attribute*), 296
- workHours (*rdflib.namespace.SDO attribute*), 296
- workInfoHomepage (*rdflib.namespace.FOAF attribute*), 153
- workload (*rdflib.namespace.SDO attribute*), 296
- workLocation (*rdflib.namespace.SDO attribute*), 296
- workPerformed (*rdflib.namespace.SDO attribute*), 296
- workplaceHomepage (*rdflib.namespace.FOAF attribute*), 153
- workPresented (*rdflib.namespace.SDO attribute*), 296
- worksFor (*rdflib.namespace.SDO attribute*), 297
- Workshop (*rdflib.namespace.BRICK attribute*), 134
- workTranslation (*rdflib.namespace.SDO attribute*), 296
- worstRating (*rdflib.namespace.SDO attribute*), 297
- WPAdBlock (*rdflib.namespace.SDO attribute*), 238
- WPFooter (*rdflib.namespace.SDO attribute*), 238
- WPHeader (*rdflib.namespace.SDO attribute*), 238
- WPSideBar (*rdflib.namespace.SDO attribute*), 238
- write (*rdflib.namespace.ODRL2 attribute*), 170
- write() (*rdflib.plugins.serializers.turtle.RecursiveSerializer method*), 362
- write() (*rdflib.query.EncodeOnlyUnicode method*), 531
- write\_ask() (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter method*), 377
- write\_binding() (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter method*), 377
- write\_end\_result() (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter method*), 377
- write\_header() (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter method*), 377
- write\_results\_header() (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter method*), 377
- write\_start\_result() (*rdflib.plugins.sparql.results.xmlresults.SPARQLXMLWriter method*), 378
- WriteAction (*rdflib.namespace.SDO attribute*), 241
- WritePermission (*rdflib.namespace.SDO attribute*), 241
- writeTo (*rdflib.namespace.ODRL2 attribute*), 170



## X

XMLLiteral (*rdflib.namespace.RDF* attribute), 187  
XMLResult (class in *rdflib.plugins.sparql.results.xmlresults*), 378  
XMLResultParser (class in *rdflib.plugins.sparql.results.xmlresults*), 378  
XMLResultSerializer (class in *rdflib.plugins.sparql.results.xmlresults*), 378  
XMLSerializer (class in *rdflib.plugins.serializers.rdfxml*), 359  
XMLWriter (class in *rdflib.plugins.serializers.xmlwriter*), 363  
xone (*rdflib.namespace.ODRL2* attribute), 170  
xone (*rdflib.namespace.SH* attribute), 304  
XoneConstraintComponent (*rdflib.namespace.SH* attribute), 301  
xpath (*rdflib.namespace.SDO* attribute), 297  
XPathType (*rdflib.namespace.SDO* attribute), 241  
XRay (*rdflib.namespace.SDO* attribute), 241  
XSD (class in *rdflib.namespace*), 315  
xsdDateTime (*rdflib.namespace.TIME* attribute), 313

## Y

yahooChatID (*rdflib.namespace.FOAF* attribute), 153  
Year (*rdflib.namespace.TIME* attribute), 310  
year (*rdflib.namespace.TIME* attribute), 313  
year (*rdflib.namespace.XSD* attribute), 318  
yearBuilt (*rdflib.namespace.BRICK* attribute), 137  
yearBuilt (*rdflib.namespace.SDO* attribute), 297  
yearlyRevenue (*rdflib.namespace.SDO* attribute), 297  
yearMonthDuration (*rdflib.namespace.XSD* attribute), 318  
years (*rdflib.namespace.TIME* attribute), 313  
yearsInOperation (*rdflib.namespace.SDO* attribute), 297

## Z

zeroOrMorePath (*rdflib.namespace.SH* attribute), 304  
zeroOrOnePath (*rdflib.namespace.SH* attribute), 304  
Zone (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Air (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Air\_Cooling\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Air\_Dewpoint\_Sensor (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Air\_Heating\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Air\_Humidity\_Sensor (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Air\_Humidity\_Setpoint (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Air\_Temperature\_Sensor (*rdflib.namespace.BRICK* attribute), 134

Zone\_Air\_Temperature\_Setpoint (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Standby\_Load\_Shed\_Command (*rdflib.namespace.BRICK* attribute), 134  
Zone\_Unoccupied\_Load\_Shed\_Command (*rdflib.namespace.BRICK* attribute), 134  
ZoneBoardingPolicy (*rdflib.namespace.SDO* attribute), 241  
Zoo (*rdflib.namespace.SDO* attribute), 241